

1

# FIELD NOTES

of

REMONUMENTATION

of

FORT APACHE INDIAN RESERVATION BOUNDARY

in

TOWNSHIP 11 NORTH, RANGE 18 EAST

TOWNSHIP 11 NORTH, RANGE 17 EAST

TOWNSHIP 10 NORTH, RANGE 17 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

## EXECUTED BY

Howard H. Thomas, Cadastral Surveyor

Under special instructions dated April 5, 19 68, which provided for the surveys included under Group Number 499, approved April 5, 1968, and assignment instructions dated April 5, 19 68.

Survey commenced April 23, 19 68

Survey completed June 28, 19 68

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 11 N. R. 18 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
31	32	33	34	35	36

FORT APACHE INDIAN  
RESERVATION

NOTE

ONLY THE BEGINNING  
AND ENDING CORNERS  
REMONUMENTED IN EACH  
SECTION ARE DIAGRAMMED.  
SEE PAGE INDEX FOR  
COMPLETE LIST OF  
CORNERS REMONUMENTED  
IN EACH TOWNSHIP.

Tp. 11 N. R. 17 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
31	32	33	34	35	36

FORT APACHE  
INDIAN RESERVATION

Tp. 10 N. R. 17 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

FORT APACHE INDIAN  
RESERVATION

PAGE INDEX TO CORNER MONUMENTS

TOWNSHIP 11 NORTH, RANGE 18 EAST, G&SR M.

<u>Corner</u>	<u>Page</u>	<u>Corner</u>	<u>Page</u>
Angle Point 722 -----	1	Angle Point 745 -----	9
" " 723 -----	1	" " 746 -----	9
" " 724 -----	2	" " 747 -----	10
" " 725 -----	2	" " 748 -----	10
Mile Corner 90 -----	2	Mile Corner 92 (AP749)-----	11
Angle Point 727 -----	3	Angle Point 752 -----	11
" " 728 -----	3	Mile Corner 92½ (AP753)-----	12
" " 729 -----	3	Angle Point 756 -----	12
" " 730 -----	4	" " 757 -----	13
Mile Corner 90½ (AP731)-----	4	" " 758 -----	13
Angle Point 733 -----	5	" " 759 -----	13
" " 734 -----	5	Mile Corner 93 -----	14
" " 735 -----	5	Angle Point 760 -----	14
" " 736 -----	6	" " 761 -----	15
Mile Corner 91 (AP737)-----	6	" " 762 -----	15
Angle Point 738 -----	7	" " 763 -----	15
" " 739 -----	7	" " 764 -----	16
" " 740 -----	7	Mile Corner 93½ -----	16
" " 741 -----	8	Angle Point 765 -----	17
" " 742 -----	8	" " 766 -----	17
" " 743 -----	8	" " 767 -----	17
Mile Corner 91½ (AP744)-----	9		

TOWNSHIP 11 NORTH, RANGE 17 EAST, G&SR M.

<u>Corner</u>	<u>Page</u>	<u>Corner</u>	<u>Page</u>
Mile Corner 94 (AP768)-----	18	Angle Point 779 -----	22
Angle Point 769 -----	18	" " 780 -----	22
" " 770 -----	19	" " 781 -----	22
" " 772 -----	19	Mile Corner 95½ -----	22
Mile Corner 94½ (AP773)-----	19	Angle Point 782 -----	23
Angle Point 774 -----	20	" " 783 -----	23
" " 775 -----	21	" " 785 -----	23
" " 777 -----	21	Mile Corner 96 -----	24
Mile Corner 95 (AP778)-----	21	Angle Point 787 -----	24

TOWNSHIP 10 NORTH, RANGE 17 EAST, G&SR M.

<u>Corner</u>	<u>Page</u>	<u>Corner</u>	<u>Page</u>
Angle Point 789 -----	25	Angle Point 793 -----	26
Mile Corner 96½ -----	25	" " 794 -----	26
Angle Point 791 -----	26	" " 795 -----	27

Township 11 North, Range 18 East  
 Township 11 North, Range 17 East  
 Township 10 North, Range 17 East  
 Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b), dated October 16, 1958.

The approval of the Special Instructions on April 5, 1968, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination used was 14° East.

Township 11 North, Range 18 East, G&SR M., Arizona

The Fort Apache Indian Reservation boundary was resurveyed in 1906 by J. B. Wright and retraced in 1915 by S. E. Blout.

Re monumentation, T. 11 N., R. 18 E., G&SR M., Arizona

Angle point 722, monumented by a dead pine stump, 18 ins. diam., with log alongside, log mkd. BMFR on one face and NB on the other face, from which new bearing accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears S. 33° W., 4.5 lks. dist., with brass cap mkd. T11N R18E AP722 RM 3 FT FAIR 1968 and an arrow pointing to the true cor.

An alligator juniper, 14 ins. diam., bears S. 81° W., 47 lks. dist., mkd. AP722 FAIR BT.

Angle point is 95 lks. W. of rim road and 60 lks. W. of a fence bearing irregularly SE. and NW.

Angle point 723, monumented by a pine tree, 20 ins. diam., mkd. APNBWMIR 723 on W. face and BMFR on E. face, from which new bearing trees

A pine, 12 ins. diam., bears S. 1° W., 35 lks. dist., mkd. AP723 FAIR BT.

A pine, 20 ins. diam., bears N. 80° W., 67 lks. dist., mkd. AP723 FAIR BT.

Angle point is 90 lks. W. of rim road and 15 lks. W. of a fence bearing irregularly N. and SE.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 724, monumented by a dead pine tree, 12 ins. diam., mkd. APNBWMIR 724 on W. face and an overgrown blaze on E. face, from which new bearing accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears N. 23½° E., 9.1 lks. dist., with brass cap mkd. T11N R18E S34 AP724 RM 6 FT 1968 and an arrow pointing to the true cor.

A pine, 10 ins. diam., bears N. 43° W., 15 lks. dist., mkd. AP724 FAIR BT.

Angle point is 40 lks. S. of rim road and 5 lks. S. of a fence bearing irregularly S. and NW.

Angle point 725, monumented by a pine tree, 12 ins. diam., mkd. with overgrown blazes on N. and S. faces, from which new bearing trees

A pine, 17 ins. diam., bears N. 52° E., 20 lks. dist., mkd. AP725 BT.

An alligator juniper, 19 ins. diam., bears S. 65° W., 61 lks. dist., mkd. AP725 FAIR BT.

Angle point is 90 lks. W. of rim road and 35 lks. W. of a fence bearing irregularly SE. and NW.

The 90 mile cor., reestablished by record course and distance from the remains of the remaining orig. bearing trees


A dead pine, 30 ins. diam., bears S. 30° E., 40 lks. dist., mkd. NBWMIR 90M BT.

A dead pine, 15 ins. diam., bears N. 69° W., 11 lks. dist., mkd. NBWMIR 90M BT.

A stump hole, with a dead and fallen pine tree, 10 ins. diam., alongside, bears N. 79° W., 17 lks. dist., mkd. NBWMIR 90M BT. (Note: record bearing S. 80° W.).

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 6 ins. diam., bears S. 8° E., 41.5 lks. dist., mkd. 90M FAIR BT.

An alligator juniper, 17 ins. diam., bears N. 56° W., 110.5 lks. dist., mkd. 90M FAIR BT.

No evidence of orig. cor. stone found.

Cor. is 50 lks. W. of rim road and 15 lks. W. of a fence bearing irregularly SE. and NW.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 727, monumented by a pine tree, 20 ins. diam., mkd. BMFR on NE. face and a blaze, partly overgrown, with faint scribe mks. visible on SE. face, from which new bearing trees

A pine, 10 ins. diam., bears S. 3° W., 79 lks. dist., mkd. AP727 FAIR BT.

A pine, 10 ins. diam., bears S. 83° W., 38 lks. dist., mkd. AP727 FAIR BT.


Angle point is on a fence bearing irregularly SE. and NW., 30 lks. S. of rim road.

Angle point 728 reestablished by record course and distance from the remaining orig. bearing tree

An alligator juniper, 12 ins. diam., bears South, 65 lks. dist., mkd. P728.

At the cor. point

Set the iron post, 12 ins. under the surface of the rim road, brass cap mkd.



from which

A pine, 12 ins. diam., bears S. 19° E., 90 lks. dist., mkd. AP728 FAIR BT.

A pine, 12 ins. diam., bears S. 57° W., 100 lks. dist., mkd. AP728 FAIR BT.

No evidence of orig. cor. stone found.

Angle point falls on the N. edge of rim road, which bears irregularly E. and W.

Angle point 729, monumented by an alligator juniper tree, 12 ins. diam., mkd. APNBWMIR 729 on SE. face and BMFR on NW. face, from which new bearing trees

A pine, 11 ins. diam., bears S. 51° E., 31 lks. dist., mkd. AP729 FAIR BT.

An alligator juniper, 10 ins. diam., bears S. 2° E., 63 lks. dist., mkd. AP729 FAIR BT.

Angle point is 10 lks. S. of a fence bearing irregularly E. and W., and 1 ch. S. of rim road.


Remonumentation T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 730, monumented by a stump hole, with a dead and fallen pine, 10 ins. diam., alongside, mkd. BMFR on one face.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

An alligator juniper, 14 ins. diam., bears S. 22° E., 6 lks. dist., mkd. AP730 FAIR BT.

An alligator juniper, 10 ins. diam., bears N. 7° W., 57 lks. dist., mkd. AP730 BT.

Angle point is 30 lks. S. of a fence bearing irregularly E. and W., and about 1½ chs. S. of rim road.

The 90½ mile cor. and angle point 731, monumented by a quartz stone, 15 x 8 x 8 ins., set 8 ins. in the ground, mkd. NBWMIR 90½M on the S. face, from which the remains of the orig. bearing trees

A pine, 20 ins. diam., bears N. 79° E., 20 lks. dist., mkd. NBWMIR 90½M BT.


A pine, 24 ins. diam., bears S. 24° W., 37 lks. dist., mkd. NBWMIR 90½M BT.

A dead pine stump, with a fallen tree, 24 ins. diam., alongside, bears S. 89½° W., 44 lks. dist., tree mkd. NBWMIR 90½M BT.

A dead pine stump, 18 ins. diam., bears N. 51° W., 49 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, collar of stone to top, brass cap mkd.



Bury the orig. cor. stone alongside the iron post.

Cor. is 70 lks. S. of rim road and 12 lks. S. of a fence bearing irregularly E. and NW.

## Remonumentation, T. 11 N., R. 18 E., Arizona

## CHAINS

Angle point 733, monumented by an alligator juniper tree, 30 ins. diam., mkd. BMFR on N. face and APNBWMIR 733 on S. face, from which new bearing trees

A pine, 13 ins. diam., bears East, 17 lks. dist., mkd. AP733 FAIR BT.

An alligator juniper, 19 ins. diam., bears West, 85 lks. dist., mkd. AP733 BT.

Angle point is 30 lks. N. of rim road.

Angle point 734, monumented by a pine tree, 24 ins. diam., mkd. BMFR on N. face and APWMIR 734 on S. face, from which new bearing trees

A pine, 5 ins. diam., bears N. 75° E., 119 lks. dist., mkd. X BT.

An alligator juniper, 11 ins. diam., bears S. 77° E., 131 lks. dist., mkd. AP734 FAIR BT.

Angle point is 1 ch. S. of rim road and 60 lks. S. of a fence bearing irregularly NE. and W.

Angle point 735, monumented by a quartz stone, 12 x 8 x 6 ins., no mks., lying loose in a scattered mound of stone, verified by record course and dist. from the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 14 ins. diam., alongside, bears N. 49° E., 23 lks. dist., mkd. AP735.

A stump hole, with a dead and fallen pine tree, 15 ins. diam., alongside, bears S. 47° E., 53 lks. dist., mkd. AP735 BT.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T11N R18E  
S33



AP735  
FAIR  
1968

from which

A pine, 4 ins. diam., bears N. 11° E., 19 lks. dist., mkd. X BT.

An alligator juniper, 11 ins. diam., bears S. 11° W., 39 lks. dist., mkd. AP735 FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 60 lks. S. of rim road and 5 lks. N. of a fence bearing irregularly E. and SW.



Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 736, monumented by a pine tree, 30 ins. diam., mkd. with overgrown blazes on E. and W. faces, from which new bearing accessories

An iron post, set 22 ins. in the ground, in a collar of stone, for a reference monument, bears S. 59° E., 13.6 lks. dist., with brass cap mkd. T11N R18E AP736 RM 9 FT FAIR 1968 and an arrow pointing to the true cor.

An alligator juniper, 9 ins. diam., bears N. 38° W., 126 lks. dist., mkd. AP736 BT.

Angle point is 50 lks. S. of rim road and 10 lks. N. of a fence bearing irregularly NE. and SE.

The 91 mile cor. and angle point 737, monumented by a sandstone, 18 x 10 x 10 ins.; set 8 ins. in the ground, mkd. NBWMIR 91M AP737 on E. face and BMFR on W. face, from which the remains of the orig. bearing trees

An oak, 14 ins. diam., bears N. 19° E., 27 lks. dist., mkd. with faint scribe marks


A stump hole, with a dead and fallen pine tree, 18 ins. diam., alongside, bears N. 85° E., 43 lks. dist., mkd. 91M BT. (Note: record dist. 45 lks.).

A dead pine, 22 ins. diam., bears S. 47° E., 54 lks. dist., no mks. (Note: record bearing and dist. S. 53° E., 51 lks.).

A dead pine stump, 21 ins. diam., bears S. 60½° W., 56 lks. dist., mkd. T.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 8 ins. diam., bears S. 54° W., 19 lks. dist., mkd. 91M BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 2 chs. S. of rim road and about 170 lks. S. of a fence bearing irregularly SW. and NW.

## Remonumentation, T. 11 N., R. 18 E., Arizona

## CHAINS

Angle point 738, monumented by a pine tree, 30 ins. diam., mkd. with overgrown blaze on S. face, and blaze, partly overgrown, with scribe mark B visible on N. face, from which new bearing trees

A pine, 10 ins. diam., bears N. 61° E., 101 lks. dist., mkd. AP738 FAIR BT.

A pine, 8 ins. diam., bears S. 15½° E., 121 lks. dist., mkd. AP738 FAIR BT.

Angle point is about 1½ chs. S. of rim road and 35 lks. S. of a fence bearing irregularly NE. and SW.

Angle point 739, monumented by a pine stump, with a dead and fallen tree, 30 ins. diam., alongside, stump mkd. with burned out blaze on S. face, from which the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 6 ins. diam., alongside, bears N. 79° E., 33 lks. dist., no mks.

A pine stump, 12 ins. diam., bears N. 50° W., 69 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R18E  
S33  
↙  
AP739  
FAIR  
1968

from which

A pine, 12 ins. diam., bears S. 34° E., 49 lks. dist., mkd. AP739 FAIR BT.

A pine, 8 ins. diam., bears N. 63° W., 20 lks. dist., mkd. AP739 BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is 1 ch. S. of rim road and 20 lks. S. of a fence bearing irregularly NE. and SW.

Angle point 740, monumented by a pine tree, 20 ins. diam., mkd. with overgrown blazes on N. and S. faces, from which new bearing trees

A pine, 8 ins. diam., bears N. 85° E., 46 lks. dist., mkd. AP740 FAIR BT.

A pine, 12 ins. diam., bears N. 76° W., 41 lks. dist., mkd. AP740 BT.

Angle point is about 1½ chs. S. of rim road and 20 lks. S. of a fence bearing irregularly NE. and W.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS


Angle point 741, monumented by a quartz stone, 18 x 6 x 6 ins., buried under the surface of the ground, in a pile of stone, mkd. AP741 on the S. face, from which the remains of the orig. bearing trees

A dead pine stump, 15 ins. diam., bears S. 28° E., 36 lks. dist., with log alongside, log mkd. AP741 BT.

A pine, 21 ins. diam., bears S. 4° E., 42 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears N. 62° E., 43 lks. dist., mkd. AP741 BT.

Bury the orig. cor. stone alongside the iron post.

Angle point is 50 lks. S. of rim road and 15 lks. N. of a fence bearing irregularly E. and SW.

Angle point 742, monumented by a pine tree, 30 ins. diam., mkd. with blaze, partly overgrown, and faint scribe marks on S. face, from which new bearing trees

A pine, 8 ins. diam., bears N. 42° E., 55 lks. dist., mkd. AP742 BT.

A pine, 19 ins. diam., bears S. 72° E., 83 lks. dist., mkd. AP742 FAIR BT.

Angle point is on a fence bearing irregularly E. and NW., 70 lks. S. of rim road and 15 lks. E. of a logging road.

Angle point 743, monumented by a pine tree, 24 ins. diam., mkd. BMFR on N. face and APNBWMIR 743 on S. face, from which new bearing trees

An alligator juniper, 21 ins. diam., bears N. 40° E., 33 lks. dist., mkd. AP743 BT.

A pine, 13 ins. diam., bears S. 83° W., 61 lks. dist., mkd. AP743 FAIR BT.

Angle point is 1 ch. S. of rim road and 40 lks. S. of a fence bearing irregularly SE. and NW.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

The 91½ mile cor. and angle point 744, monumented by a quartz stone, 12 x 6 x 4 ins., set 6 ins. in the ground, mkd. 91½M BMFR on E. face, with mound of stone to the W. From the cor., the remains of the orig. bearing trees

A pine stump, 30 ins. diam., bears N. 32° E., 62 lks. dist., no mks.


A juniper, 24 ins. diam., bears S. 76½° E., 115 lks. dist., mkd. NBWMIR 91½M BT.

A stump hole, with a dead and fallen pine, 24 ins. diam., alongside, bears South, 79 lks. dist., mkd. with faint scribe marks

An oak, 11 ins. diam., bears N. 31° W., 41 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 9 ins. diam., bears S. 30° W., 50 lks. dist., mkd. 91½M FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 1 ch. S. of rim road and 10 lks. N. of a fence bearing irregularly SE. and NW.

Angle point 745, monumented by a pine tree, 18 ins. diam., mkd. APNBWMIR 745 on S. face and with an overgrown blaze on N. face, from which new bearing accessories

A pine tree, 20 ins. diam., bears N. 61° E., 82 lks. dist., mkd. AP745 BT.

An iron post, set 24 ins. in the ground, for a reference monument, bears S. 80° W., 4.5 lks. dist., mkd. T11N R18E RM 3 FT AP745 1968 and an arrow pointing to the true corner.

Angle point is 40 lks. N. of rim road.

Angle point 746, monumented by a stump hole, with a dead and fallen pine tree, 16 ins. diam., alongside, mkd. APNBWMIR on S. face, from which the remains of the orig. bearing trees

A dead pine, 18 ins. diam., bears N. 48° E., 37 lks. dist., no mks.

A stump hole, with a decomposed pine tree alongside, bears N. 5° W., 24 lks. dist., no mks.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R18E  
S32  
←→  
AP746  
FAIR  
1968

from which

An alligator juniper, 11½ ins. diam., bears S. 6° W., 66 lks. dist., mkd. AP746 FAIR BT.

A pine, 11½ ins. diam., bears N. 23° W., 88 lks. dist., mkd. AP746 BT.

Angle point is 100 lks. S. of rim road and 70 lks. S. of a fence bearing irregularly E. and W.

Angle point 747, monumented by a stump hole, with a dead and fallen pine, 12 ins. diam., alongside, mkd. with faint scribe marks on S. face.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R18E  
S32  
←→  
AP747  
FAIR  
1968

from which

A pine, 7½ ins. diam., bears S. 59° E., 27 lks. dist., mkd. AP747 FAIR BT.

A pine, 7½ ins. diam., bears S. 68° W., 53 lks. dist., mkd. AP747 FAIR BT.

Angle point is on a fence bearing irregularly SE. and NW., 35 lks. S. of rim road.

Angle point 748, monumented by a quartz stone, 16 x 6 x 6 ins., set 8 ins. in the ground, in a collar of stone, mkd. BMFR on N. face and BWM on S. face, from which the remains of the orig. bearing trees

A stump hole, bears S. 73½° E., 54 lks. dist.


A pine, 27 ins. diam., bears S. 27½° W., 36 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS



from which

A pine, 10 ins. diam., bears N. 51° W., 28.5 lks. dist., mkd. AP748 FAIR BT.

Bury the orig. cor. stone alongside the iron post.

Angle point is about 50 lks. S. of rim road and about 15 lks. S. of a fence bearing irregularly SE. and NW.

The 92 mile cor. and angle point 749 is reestablished by record course and distance from the remaining orig. bearing trees


A pine, 16 ins. diam., bears S. 13½° E., 30 lks. dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears S. 44° W., 40 lks. dist., mkd. with an overgrown blaze.

A pine, 18 ins. diam., bears N. 81° W., 17 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.




No evidence of orig. cor. stone found.

Cor. is 35 lks. S. of rim road and 7 lks. N. of a fence bearing irregularly SE. and NW.

Angle point 752, monumented by a rotted pine stump, 24 ins. diam., mkd. BMFR on N. face, no mks. on S. face.

At the cor. point

Set the iron post, 26 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 5 ins. diam., bears N. 33° E., 27 lks. dist., mkd. AP752 BT.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

A pine, 12 ins. diam., bears N. 36° W., 57 lks. dist., mkd. AP752 BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is about 2 chs. N. of rim road and 50 lks. W. of a fire trail.

The 92½ mile cor. and angle point 753, monumented by a quartz stone, 15 x 6 x 5 ins., set 6 ins. in the ground, mkd. NBWMIR 92½ on S. face, from which the remaining orig. bearing trees

A pine, 18 ins. diam., bears N. 57° E., 8 lks. dist., mkd. with an overgrown blaze. (Note: record dist. 6 lks.).

An alligator juniper, 24 ins. diam., bears S. 15½° E., 24 lks. dist., mkd. NBMIR 92½ BT.

A pine, 18 ins. diam., bears S. 54° W., 11 lks. dist., mkd. with a blaze, partly overgrown, and scribe marks ½M BT visible. (Note: record dist. 13 lks.).

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R18E  
S32  
AP753  
← 92½M  
FAIR  
1968

Bury the orig. cor. stone alongside the iron post.

Cor. is 1 ch. S. of rim road and 70 lks. S. of a fence bearing irregularly NE. and W.

Angle point 756, monumented by a stump hole, with a dead and fallen pine tree, 10 ins. diam., alongside, mkd. APNBWMIR 7 6 on one face and BMFR on another face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R18E  
S32  
← AP756  
FAIR  
1968

Angle point is about 1½ chs. S. of rim road and 50 lks. S. of a fence bearing irregularly NE. and W.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 757, monumented by a pine tree, 20 ins. diam., mkd. BMFR on N. face and APNBWMIR 757 on S. face, from which new bearing trees

A pine, 24 ins. diam., bears S. 22° E., 72 lks. dist., mkd. AP757 FAIR BT.

An alligator juniper, 12 ins. diam., bears S. 45° W., 82 lks. dist., mkd. AP757 FAIR BT.

Angle point is on a fence bearing irregularly E. and W., 50 lks. S. of rim road.

Angle point 758, monumented by a stump hole, with a dead and fallen pine tree, 8 ins. diam., alongside, mkd. APNBWMIR 758 on one face and BMFR on the other face.

At the cor. point.

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 79° W., 42.5 lks. dist., mkd. AP758 FAIR BT.

A pine, 15 ins. diam., bears N. 23° W., 103 lks. dist., mkd. AP758 BT.


Angle point is 20 lks. S. of rim road and 50 lks. N. of a fence bearing irregularly E. and NW.

Angle point 759, monumented by an oak stump, 4 ins. diam., no mks., from which the remains of an orig. bearing tree

A dead oak stump, 8 ins. diam., bears S. 76° W., 20 lks. dist., mkd. with part of rotted out blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 8 ins. diam., bears S. 20° E., 28 lks. dist., mkd. AP759 FAIR BT.

A pine, 16 ins. diam., bears S. 72° W., 40 lks. dist., mkd. AP759 FAIR BT.



Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Deposit orig. cor. stump alongside the iron post.

Angle point is 25 lks. S. of rim road and 50 lks. N. of a fence bearing irregularly SE. and W.


The 93 mile cor., monumented by a sandstone, 18 x 12 x 6 ins., set 8 ins. in the ground, mkd. NBWMIR 93M on SE. face, from which the remains of the remaining orig. bearing trees

A rotted pine stump, 18 ins. diam., bears S. 24½° E., 77 lks. dist., mkd. M BT.

A rotted pine stump, 20 ins. diam., bears N. 61½° W., 67 lks. dist., no mks.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 12 ins. diam., bears N. 46° E., 7 lks. dist., mkd. 93M BT.

A pine, 9 ins. diam., bears S. 62½° W., 32 lks. dist., mkd. 93M FAIR BT.


Bury the orig. cor. stone alongside the iron post.

Cor. is on a fence bearing irregularly E. and W., 50 lks. S. of rim road.

Angle point 760, monumented by a stump hole, with a dead and fallen pine tree, 24 ins. diam., alongside, mkd. A on one face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 11 ins. diam., bears N. 74° E., 25 lks. dist., mkd. AP760 BT.

A pine, 13 ins. diam., bears S. 15° W., 53.5 lks. dist., mkd. AP760 FAIR BT.

Angle point is about 1½ chs. S. of rim road and about 1 ch. S. of a fence bearing irregularly E. and NW.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 761, monumented by a pine tree, 15 ins. diam., mkd. with overgrown blazes on N. and S. faces, from which new bearing trees

An alligator juniper, 14 ins. diam., bears S. 12° E., 44 lks. dist., mkd. AP761 FAIR BT.


A pine, 9 ins. diam., bears S. 40° W., 54 lks. dist., mkd. AP761 FAIR BT.

Angle point is 30 lks. S. of rim road and 5 lks. S. of a fence bearing irregularly SE. and W.

Angle point 762, monumented by a dead pine stump, 18 ins. diam., 4 ft. high, mkd. BMFR on N. face and NBWMIR 762 on S. face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 9 ins. diam., bears S. 57° E., 48 lks. dist., mkd. AP762 FAIR BT.

A pine, 11 ins. diam., bears S. 22° W., 16 lks. dist., mkd. AP762 FAIR BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is 50 lks. S. of rim road and 3 lks. S. of a fence bearing irregularly E. and W.


Angle point 763, monumented by a burned out stump hole, verified by record course and dist. from the remains of the orig. bearing trees

A juniper, 36 ins. diam., bears S. 15° W., 46 lks. dist., mkd. AP763 BT.

A pine stump, partly burned, 20 ins. diam., bears N. 45° W., 32 lks. dist., mkd. AP763 BT.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 9 ins. diam., bears N. 32° E., 21 lks. dist., mkd. AP763 BT.

Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point is 50 lks. S. of rim road and 32 lks. S. of a fence bearing irregularly E. and SW.

Angle point 764, monumented by a pine stump, 20 ins. diam., mkd. BMFR on N. face and APNBWMIR 764 on S. face, from which new bearing trees

A pine, 16 ins. diam., bears N.  $11\frac{1}{2}^{\circ}$  E., 26 lks. dist., mkd. AP764 BT.

A pine, 18 ins. diam., bears S.  $40^{\circ}$  E., 37 lks. dist., mkd. AP764 FAIR BT.

Angle point is on a fence bearing irregularly NE. and SW., 40 lks. N. of rim road.

The  $93\frac{1}{2}$  mile cor., monumented by a quartz stone, 12 x 10 x 6 ins., set 3 ins. in the ground, mkd. NBWMIR  $93\frac{1}{2}M$  on the SE. face, from which the remains of the orig. bearing trees

A stump hole, with a dead and fallen pine tree, 24 ins. diam., alongside, bears S.  $11\frac{1}{2}^{\circ}$  E., 54 lks. dist., no mks. (Note: record dist. 56 lks.)


A stump hole, with a dead and fallen pine tree, 10 ins. diam., alongside, bears S.  $32\frac{1}{2}^{\circ}$  W., 53 lks. dist., no mks.

A pine stump, with a dead and fallen tree, 16 ins. diam., alongside, bears S.  $42\frac{1}{2}^{\circ}$  W., 50 lks. dist., mkd. NBWMIR  $93\frac{1}{2}M$  BT.

A pine, 17 ins. diam., bears N.  $22^{\circ}$  W., 49 lks. dist., mkd. NBWMIR  $93\frac{1}{2}M$  BT.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 6 ins. diam., bears S.  $35^{\circ}$  E., 22 lks. dist., mkd.  $93\frac{1}{2}M$  FAIR BT.

A pine, 6 ins. diam., bears S.  $41^{\circ}$  W., 5 lks. dist., mkd.  $93\frac{1}{2}M$  BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about  $1\frac{1}{2}$  chs. S. of rim road and 10 lks. N. of a fence bearing irregularly NE. and SW.


Remonumentation, T. 11 N., R. 18 E., Arizona

CHAINS

Angle point 765, monumented by a pine stump, 12 ins. diam., with a dead and fallen pine tree alongside, tree mkd. APNBWMIR 765 B on top face.

At the cor. point

Set the iron post, 26 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 7 ins. diam., bears S. 85½° E., 45 lks. dist., mkd. AP765 FAIR BT.

A pine, 8 ins. diam., bears N. 81° W., 47 lks. dist., mkd. AP765 BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is 1 ch. S. of rim road and 10 lks. S. of a fence bearing irregularly NE. and W.

Angle point 766, monumented by a pine tree, 14 ins. diam., mkd. with an overgrown blaze on S. face and a blaze, partly overgrown, with scribe mark B visible on N. face, from which new bearing trees

A pine, 13 ins. diam., bears N. 83° E., 83 lks. dist., mkd. AP766 FAIR BT.


A pine, 9 ins. diam., bears S. 83° W., 39 lks. dist., mkd. AP766 FAIR BT.

Angle point is 50 lks. S. of rim road and 12 lks. S. of a fence bearing irregularly E. and W.

Angle point 767; monumented by a stump hole, with a dead and fallen pine tree, 8 ins. diam., alongside, mk. APNBWMIR 767 on one side.

At the cor. point



Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 7 ins. diam., bears S. 55° E., 42 lks. dist., mkd. AP767 FAIR BT.

Remonumentation, T. 11 N., R. 17 E., Arizona

<p>CHAINS</p>	<p>A pine, 8 ins. diam., bears S. 50° W., 40 lks. dist., mkd. AP767 FAIR BT.</p> <p>Angle point is 50 lks. S. of rim road and 10 lks. N. of a fence bearing irregularly SE. and W.</p>
	<p>Township 11 North, Range 17 East, G&amp;SR M., Arizona</p> <p>The Fort Apache Indian Reservation Boundary was resurveyed in 1906 by J. B. Wright and portions of the Boundary were retraced in 1915 by S. E. Blout and in 1935 by A. N. Kimmel.</p>
	<p>Remonumentation, T. 11 N., R. 17 E., G&amp;SR M., Arizona</p>
	<p>The 94 mile cor. and angle point 768, reestablished by record course and distance from the remains of the orig. bearing trees</p> <p>A dead pine snag, 20 ins. diam., bears S. 76½° E., 84 lks. dist., mkd. NBWMIR 94M BT.</p> <p>A pine stump, 24 ins. diam., bears S. 3¼° W., 40 lks. dist., no mks.</p> <p>A pine stump, 18 ins. diam., bears S. 77½° W., 37 lks. dist., no mks.</p> <p>A pine, 30 ins. diam., bears N. 30° W., 12 lks. dist., mkd. NBWMIR.</p> <p>At the cor. point</p> <p>Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11N R17E S36 AP768</p>  <p>94M FAIR 1968</p> </div> <p>from which</p> <p>A pine, 9 ins. diam., bears S. 10° W., 45 lks. dist., mkd. 94M FAIR BT.</p> <p>Angle point is about 2 chs. S. of rim road and 15 lks. N. of a fence bearing irregularly E. and NW.</p>
	<p>Angle point 769, monumented by a stump hole, with a dead and fallen pine tree, 10 ins. diam., alongside, mkd. APNBWMIR 769 on one face.</p> <p>At the cor. point</p> <p>Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11N R17E S36</p>  <p>AP769 FAIR 1968</p> </div>

## Remonumentation, T. 11 N., R. 17 E., Arizona

## CHAINS

from which

A pine, 16 ins. diam., bears S. 77° E., 28 lks. dist., mkd. AP769 BT.

A pine, 9 ins. diam., bears S. 53° W., 26 lks. dist., mkd. AP769 FAIR BT.

Angle point is 30 lks. S. of rim road and 30 lks. N. of a fence bearing irregularly SE. and W.

Angle point 770, monumented by a stump hole, with a dead and fallen pine, 22 ins. diam., alongside, faintly mkd. NBWM on one face.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R17E  
S36



AP770  
FAIR  
1968

Angle point is 1 ch. S. of rim road and 25 lks. S. of a fence bearing irregularly E. and W.

Angle point 772, monumented by a juniper tree, 30 ins. diam., mkd. APNBWMIR 772 on S. face, no mks. on N. face, from which new bearing trees

A pine, 18 ins. diam., bears S. 1° E., 41 lks. dist., mkd. AP772 FAIR BT.

A pine, 15 ins. diam., bears S. 59° W., 38 lks. dist., mkd. AP772 FAIR BT.

Angle point is on a fence bearing irregularly E. and W., 40 lks. S. of rim road.

The 94½ mile cor. and angle point 773, monumented by a sandstone, 18 x 11 x 9 ins., set 2 ins. in the ground, mkd. NBWMIR 94½M on SE. face and BMFR on N. face, from which the remains of the orig. bearing trees

A pine stump, 28 ins. diam., bears N. 64° E., 74 lks. dist., mkd. NBWMIR 94½M BT.

A stump hole, with a dead and fallen pine tree, 24 ins. diam., alongside, bears S. 50¾° E., 51 lks. dist., mkd. NBWMIR 94½M BT.

A dead pine snag, 23 ins. diam., bears S. 13° W., 53 lks. dist., mkd. NBWMIR 94½M BT. (Note: record dist. 63 lks.).


A pine stump, 12 ins. diam., bears N. 81° W., 83 lks. dist., mkd. NBWMIR 94½M BT. (Note: record bearing S. 81° W.).

At the cor. point

Remonumentation, T. 11 N., R. 17 E., Arizona

CHAINS

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 12 ins. diam., bears N. 80° E., 14 lks. dist., mkd. 94 1/2 M BT.

A pine, 9 ins. diam., bears N. 46° W., 34 lks. dist., mkd. 94 1/2 M BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is 1 ch. S. of rim road and 7 lks. S. of a fence bearing irregularly E. and SW.

Angle point 774, monumented by a dead pine snag, 24 ins. diam., mkd. with a rotted blaze on S. face and scribe marks BMFR on N. face, from which the remains of the orig. bearing trees

A pine stump, 24 ins. diam., with a log alongside, bears S. 73 1/2° E., 34 lks. dist., stump mkd. BT.

A stump hole, with a dead and fallen pine, 24 ins. diam., alongside, bears N. 68 1/2° W., 25 lks. dist., mkd. with faint scribe marks.

At the cor. point

Set the iron post, 26 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 8 ins. diam., bears N. 72° E., 23 lks. dist., mkd. AP774 BT.

A pine, 10 ins. diam., bears S. 76° W., 93 lks. dist., mkd. AP774 FAIR BT.

Deposit the orig. cor. snag alongside the iron post. Angle point is about 2 chs. S. of rim road and 50 lks. S. of a fence bearing irregularly NE. and W.

Remonumentation, T. 11 N., R. 17 E., Arizona

CHAINS

Angle point 775, monumented by a juniper tree, 30 ins. diam., mkd. BMFR on N. face, from which new bearing trees

A pine, 11 ins. diam., bears N. 11° E., 23 lks. dist., mkd. AP775 BT.

A pine, 10 ins. diam., bears S. 35° W., 29 lks. dist., mkd. AP775 FAIR BT.

Angle point is 1 ch. S. of rim road and 50 lks. S. of a fence bearing irregularly E. and NW.

Angle point 777, monumented by a pine stump, with a dead and fallen tree, 24 ins. diam., alongside, tree mkd. APNBWMIR on S. face and BMFR on N. face, from which new bearing trees

A pine, 10 ins. diam., bears S. 54½° W., 9 lks. dist., mkd. AP777 FAIR BT.

A pine, 14 ins. diam., bears N. 70° W., 28 lks. dist., mkd. AP777 BT.

Angle point is 1 ch. S. of rim road and 35 lks. N. of a fence bearing irregularly E. and W.

The 95 mile cor. and angle point 778, reestablished by record course and dist. from the orig. bearing trees

A pine, 14 ins. diam., bears N. 66° E., 35 lks. dist., mkd. NBWMIR 95M BT.

A pine, 18 ins. diam., bears N. 72½° E., 41 lks. dist., mkd. with blaze, partly overgrown, and faint scribe marks.

A pine, 20 ins. diam., bears N. 73½° W., 28 lks. dist., mkd. NBWMIR 95M BT.

A pine, 22 ins. diam., bears N. 20° W., 21 lks. dist., mkd. NBWMIR 95M BT.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T11N R17E  
 S35  
 AP778  
 ←————→  
 95M  
 FAIR  
 1968

No evidence of orig. cor. stone found.

Angle point is 60 lks. S. of rim road and 5 lks. S. of a fence bearing irregularly E. and W.



Remonumentation, T. 11 N., R. 17 E., Arizona

CHAINS

Angle point 779, monumented by a dead pine tree, 20 ins. diam., mkd. BMFR on N. face, no mks. on S. face, from which new bearing trees

A pine, 9 ins. diam., bears N. 31° E., 27 lks. dist., mkd. AP779 BT.

A pine, 11 ins. diam., bears S. 82° W., 36 lks. dist., mkd. AP779 FAIR BT.

Angle point is on a fence bearing irregularly E. and W., 50 lks. S. of rim road.

Angle point 780, monumented by a pine tree, 24 ins. diam., mkd. APNBWMIR 780 on S. face and BMFR on N. face, from which new bearing trees

A pine, 12 ins. diam., bears S. 82° W., 47 lks. dist., mkd. AP780 FAIR BT.

A pine, 16 ins. diam., bears N. 33° W., 49 lks. dist., mkd. AP780 BT.

Angle point is 1 ch. S. of rim road and 30 lks. S. of a fence bearing irregularly E. and W.

Angle point 781, monumented by a pine stump, 24 ins. diam., with cut tree alongside, tree mkd. BMFR on N. face, no mks. on S. face, from which new bearing trees

A pine, 8 ins. diam., bears S. 18° E., 48 lks. dist., mkd. AP781 BT.

A pine, 15 ins. diam., bears N. 45° W., 78 lks. dist., mkd. AP781 BT.

Angle point is about 2 chs. S. of rim road and 50 lks. S. of a fence bearing irregularly E. and SW.

The 95½ mile cor., monumented by a quartz stone, 15 x 8 x 8 ins., set 8 ins. in the ground, mkd. NBWMIR 95½ on S. face, from which the remains of the orig. bearing trees

A pine, 22 ins. diam., bears N. 62° E., 88 lks. dist., mkd. with an overgrown blaze.

A pine, 14 ins. diam., bears N. 66° E., 88 lks. dist., mkd. NBWMIR 95½

A stump hole, with a dead and fallen pine tree, 15 ins. diam., alongside, mkd. NBWMIR 95½M BT, bears N. 73° E., 88 lks. dist.


A dead pine stump, 30 ins. diam., bears S. 60° W., 4 lks. dist., mkd. with blaze and faint scribe marks.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

Remonumentation, T. 11 N., R. 17 E., Arizona

CHAINS



from which

A pine, 10 ins. diam., bears S. 73 1/2° W., 28 lks. dist., mkd. 95 1/2 M FAIR BT.

A pine, 14 ins. diam., bears N. 42 1/2° W., 45 lks. dist., mkd. 95 1/2 M BT.

Bury the orig. cor. stone alongside the iron post.

Cor. is about 1 1/2 chs. S. of rim road and 50 lks. S. of a fence bearing irregularly SE. and NW.

Angle point 782, monumented by a pine, 18 ins. diam., mkd. with blaze, partly overgrown, and scribe marks NBWIR on S. face, and with an overgrown blaze on N. face, from which new bearing trees

A pine, 9 ins. diam., bears N. 57° W., 33 lks. dist., mkd. AP782 BT.

A pine, 13 ins. diam., bears N. 14° W., 64 lks. dist., mkd. AP782 BT.

Angle point is about 1 1/2 chs. S. of rim road.

Angle point 783, monumented by a pine tree, 30 ins. diam. mkd. APNBWMIR 783 on S. face and BMFR on N. face, from which new bearing trees

A pine, 14 ins. diam., bears N. 5° E., 131 lks. dist., mkd. AP783 BT.


A pine, 18 ins. diam., bears S. 37° E., 81 lks. dist., mkd. AP783 FAIR BT.

Angle point is 1 ch. S. of rim road.

Angle point 785, monumented by a stump hole, with a dead and fallen pine tree, 18 ins. diam., alongside, mkd. BMFR on one face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 20 ins. diam., bears N. 11° E., 27 lks. dist., mkd. AP785 BT.

Remonumentation, T. 11 N., R. 17 E., Arizona

CHAINS

A pine, 20 ins. diam., bears S. 24° W., 33 lks. dist., mkd. AP785 FAIR BT.

Angle point is about 2 chs. S. of rim road and about 15 lks. S. of a fence bearing irregularly SE. and SW.

The 96 mile cor., monumented by a quartz stone, 12 x 12 x 9 ins., set 6 ins. in the ground, in a mound of stone, mkd. NBWMIR 96M on E. face, from which the remains of the orig. bearing trees

A pine stump, 16 ins. diam., bears S. 54½° E., 14 lks. dist., no mks.


A pine, 14 ins. diam., bears S. 17½° E., 58 lks. dist., mkd. NBWMIR 96M BT.

A pine stump, 6 ins. diam., bears N. 44° W., 8 lks. dist., no mks.

A pine, 21 ins. diam., bears N. 3¼° W., 47 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 14 ins. diam., bears S. 53½° E., 79 lks. dist., mkd. 96M FAIR BT.

Bury orig. cor. stone alongside the iron post.

Cor. is on a fence bearing irregularly NE. and SW., 1 ch. S. of rim road.


Angle point 787, monumented by a dead pine stump, 14 ins. diam., no mks., verified by record course and dist. from the orig. bearing trees

A pine, 25 ins. diam., bears S. 36½° W., 35 lks. dist., mkd. with an overgrown blaze.

A juniper, 18 ins. diam., bears N. 68° W., 58 lks. dist., mkd. AP787 BT.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.



Remonumentation, T. 10 N., R. 17 E., Arizona

CHAINS

Deposit the orig. cor. stump alongside the iron post.

Angle point is 1 ch. S. of rim road and 2 lks. S. of a fence bearing E. and W.

Township 10 North, Range 17 East, G&SR M., Arizona

The Fort Apache Indian Reservation boundary was resurveyed in 1906 by J. B. Wright.

Remonumentation, T. 10 N., R. 17 E., G&SR M., Arizona

Angle point 789, monumented by a pine tree, 28 ins. diam., mkd. APNBWMIR 789 on S. face and BMFR on N. face, from which new bearing trees

A pine, 8 ins. diam., bears N. 10° E., 85 lks. dist., mkd. AP789 BT.

A pine, 9 ins. diam., bears N. 89½° W., 58 lks. dist., mkd. AP789 BT.

Angle point is 1 ch. S. of rim road.

The 96½ mile cor. was reestablished by record course and distance from the remains of the orig. bearing trees

A pine stump, with a dead and fallen tree, 9 ins. diam., alongside, bears S. 26° E., 36 lks. dist., tree mkd. NBWMIR 96½M BT.


A pine, 19 ins. diam., bears S. 13° E., 32 lks. dist., mkd. NBWMIR 96½M BT.

A pine, 18 ins. diam., bears S. 5¾° W., 28 lks. dist., mkd. NBWMIR 96M BT.

A pine, 18 ins. diam., bears S. 33° W., 37 lks. dist., mkd. NBWMIR 96M BT.

At the cor. point

Set the iron post, 23 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 14 ins. diam., bears N. 21° W., 15 lks. dist., mkd. 96½M BT.

The orig. corner stone, a sandstone, 15 x 8 x 6 ins., mkd. 96½ on one face, had been moved and was found lying loose upon the ground. I bury the orig. cor. stone alongside the iron post.

Cor. is 1 ch. SE. of rim road.


Remonumentation, T. 10 N., R. 17 E., Arizona

CHAINS

Angle point 791, monumented by a dead pine stump, 24 ins. diam., with a cut log alongside, log mkd. APNBWMIR 791 on one face and BMFR on the other face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 18 ins. diam., bears N. 50° E., 57 lks. dist., mkd. AP FAIR 791 BT.

A pine, 14 ins. diam., bears N. 65° W., 110 lks. dist., mkd. AP791 FAIR BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is about 25 lks. S. of rim road.

Angle point 793, monumented by a pine tree, 24 ins. diam., mkd. APNBWMIR 793 on E. face and with an overgrown blaze on W. face, from which new bearing trees

A pine, 20 ins. diam., bears N. 62° E., 20 lks. dist., mkd. AP793 BT.


A pine, 17 ins. diam., bears S. 56° E., 50 lks. dist., mkd. AP793 BT.

Angle point is on a fence bearing irregularly N. and S., 60 lks. E. of rim road.

Angle point 794, monumented by a dead pine snag, 18 ins. diam., mkd. APNBWMIR 794 on E. face and BMFR on W. face.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 42° E., 55 lks. dist., mkd. AP794 BT.

A pine, 15 ins. diam., bears N. 45° W., 30 lks. dist., mkd. AP794 BT.

Deposit the orig. cor. stump alongside the iron post.

Angle point is about 4 chs. E. of rim road bearing N. and S.

## Remonumentation, T. 10 N., R. 17 E., Arizona

## CHAINS

Angle point 795, monumented by a dead pine tree, 28 ins. diam., mkd. APNBWMIR 795 on E. face and BMFR on W. face, from which new bearing trees

A pine, 18 ins. diam., bears N. 80° E., 103 lks. dist., mkd. AP FAIR 795 BT.

A pine, 15 ins. diam., bears S. 25° E., 95 lks. dist., mkd. AP FAIR 795 BT.

Angle point is about 3 chs. S. of rim road and 50 lks. S. of a fence bearing E. and W.

General Statement

The official record was found to be in error for some of the bearing and distances given for the bearing trees. A few of the trees were misnamed as to specie. A ring growth count was made on several trees which proved they were marked at the time of the original survey.

Where the original corner monument appeared to be undisturbed, it was accepted as the true point for the corner.

BOOK 4893

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36





CERTIFICATE OF SURVEY

I, Howard H. Thomas, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 5th day of April, 1968, I have remonumented a portion of the cadastral survey corners of the Fort Apache Indian Reservation Boundary in Township 10 North, Range 17 East, and Township 11 North, Ranges 17 and 18 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 14, 1969 (Date)

Howard H. Thomas (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JUN 17 1969

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners of the Fort Apache Indian Reservation Boundary in Township 10 North, Range 17 East, and Township 11 North, Ranges 17 and 18 East, all of the Gila and Salt River Meridian, Arizona,

executed by Howard H. Thomas, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 21 1971 (Date)

Clark F. Lumm (Chief, Division of Engineering Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)