

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of a

RETRACEMENT

between

SECTIONS 11 AND 14

and a

COMPLETION SURVEY

of the

SUBDIVISIONAL LINES

TOWNSHIP 28 NORTH, RANGE 20 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Gary T. Oviatt, Cadastral Surveyor

Under special instructions dated July 11, 19 68, which provided for the surveys
included under Group Number 488, approved July 11, 1968,
and assignment instructions dated September 12, 19 68.

Survey commenced November 6, 19 68

Survey completed November 20, 19 68

1A

BOOK 4899 INDEX DIAGRAM

Township 28 North, Range 20 West

23	23	15	10	10	4
6	22 5	14 4	8	9 2	3 1
22	21	14	9	8	3
7	21 8	13 9	10	7 11	2 12
20	20		7	1	
18	19 17	16	15	14	13
19	18		6		
19	17 20	12 21	22	23	24
17	17	12	5		
30	16 29	11 28	27	26	25
15		11	4		
31	32	33	34	35	36

Township 28 North, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

The north boundary (Seventh Standard Parallel North) was surveyed in 1930 by D. R. Averill. The south four miles of the east boundary and the east two miles of the south boundary were surveyed in 1915-16 by Bardsley, Durnford and Lange. A portion of the subdivisional lines was surveyed in 1916 by Lange. The north two miles of the east boundary, the west four miles of the south boundary, the west boundary and a portion of the subdivisional lines were surveyed in 1955 by D. E. Harding.

The following notes are those of a retracement between sections 11 and 14 and the completion survey of the subdivisional lines in Township 28 North, Range 20 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 11, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position at the corner of sections 26, 27, 34 and 35, as determined by traverse from USC&GS Triangulation Station BUG, located in the southeast portion of section 26 of this township is: Latitude 35°46'42.5" North and Longitude 114°23'50.7" West.

The mean magnetic declination was found to be: 15½° East.

Retracement Between Sections 11 and 14
Township 28 North, Range 20 West

Retracement of the Survey executed
by E. J. Lange in 1916

From the cor. of secs. 11, 12, 13 and 14, monumented by an iron post 2 ins. diam., projecting 10 ins. above the ground, brass cap mkd.

T28N
R20W
S11 | S12
S14 | S13
1916

S. 89°33' W., bet. secs. 11 and 14.

Over rolling land, through moderate undergrowth.

39.98

The ¼ sec. cor. of secs. 11 and 14, monumented by an iron post 1 in. diam., projecting 22 ins. above the ground, mound of stone N., brass cap mkd.

¼
S11
S14
1916

Retracement Between Sections 11 and 14,
T. 28 N., R. 20 W.

CHAINS	
	<p>N. 89°52' W., beginning new measurement.</p> <p>Descend N. slope.</p>
40.05	<p>The cor. of secs. 10, 11, 14 and 15, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R20W <u>S10 S11</u> <u>S15 S14</u> 1916</p> </div> <p>The cor. is located 140 lks. N. of a wash draining W.</p> <p>Land, rolling. Soil, rocky and gravelly clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
<p>Completion Survey, Subdivisional Lines Township 28 North, Range 20 West</p>	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 0°01' W., bet. secs. 11 and 12.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
2.10	Wash, 30 lks. wide, 1 ft. deep, drains W.
3.60	Track road, bears S. 60° E. and N. 60° W.
8.60	Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W.
39.70	Wash, 20 lks. wide, 1 ft. deep, drains W.
40.00	<p>Point for the ¼ sec. cor. of secs. 11 and 12.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R20W ¼ <u>S11 S12</u> 1968</p> </div> <p>Raise a mound of stone W. of the corner.</p>
64.60	Wash, 30 lks. wide, 1 ft. deep, drains W.
71.80	Graded road, bears SE. and NW.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T28N R20W <u>S 2 S 1</u> <u>S11 S12</u> 1968</p> </div>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 15 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W R19W S 1 S 6 S12 S 7 1955</p> <p>Rebuild a mound of stone around iron post.</p> <p>West, bet. secs. 1 and 12.</p> <p>Over rolling land, through moderate undergrowth.</p>
40.01	<p>Point for the ¼ sec. cor. of secs. 1 and 12.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W ¼ $\frac{S 1}{S12}$ 1968</p>
60.90	<p>Raise a mound of stone N. of the corner.</p> <p>Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.</p>
71.15	<p>Telephone line, bears S. 4° E. and N. 4° W.</p>
80.02	<p>The cor. of secs. 1, 2, 11 and 12.</p>
	<p>Land, rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°01' W., bet. secs. 1 and 2.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
16.50	<p>Wash, 30 lks. wide, 1 ft. deep, drains S. 80° W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 1 and 2.</p>
	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W ¼ S 2 S 1 1968</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS													
41.60	Wash, 20 lks. wide, 1 ft. deep, drains W.												
78.40	Wash, 30 lks. wide, 1 ft. deep, drains N. 80° W.												
79.96	Intersect the S. bdy. of T. 29 N., R. 20 W. (Seventh Standard Parallel North).												
	Point for the closing cor. of secs. 1 and 2.												
	Set the iron post 24 ins. in the ground, brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T29N</td></tr> <tr><td colspan="2">S36</td></tr> <tr><td style="border-right: 1px solid black;">S 2</td><td>S 1</td></tr> <tr><td style="border-right: 1px solid black;">T28N</td><td>R20W</td></tr> <tr><td colspan="2">C C</td></tr> <tr><td colspan="2">1968</td></tr> </table>	T29N		S36		S 2	S 1	T28N	R20W	C C		1968	
T29N													
S36													
S 2	S 1												
T28N	R20W												
C C													
1968													
	from which												
	The Standard ¼ sec. cor. of sec. 36, T. 29 N., R. 20 W., bears East, 1.27 chs. dist., monumented by an iron post 1 in. diam., firmly set in a mound of stone, brass cap mkd., SC ¼ S36 1930.												
	Raise a mound of stone S. of the corner.												
	Land, rolling.												
	Soil, gravelly and sandy clay loam.												
	Timber, scattered Joshua trees.												
	Undergrowth, creosote bush, cacti and grass.												
	Point for the ¼ sec. cor. of sec. 1 is on the N. bdy. at mid-point bet. the closing cors.												
	Set the iron post 20 ins. in the ground, brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">¼ S 1</td></tr> <tr><td colspan="2">T28N R20W</td></tr> <tr><td colspan="2">1968</td></tr> </table>	¼ S 1		T28N R20W		1968							
¼ S 1													
T28N R20W													
1968													
	from which												
	The Standard cor. of Tp. 29 N., Rs. 19 and 20 W., bears East, 1.21 chs. dist., monumented by an iron post 3 ins. diam., projecting 8 ins. above the ground, mound of stone N., brass cap mkd. SC T29N R19W R20W S31 S36 1930.												
	Raise a mound of stone S. of the corner.												
	From the cor. of secs. 26, 27, 34 and 35, monumented by an iron post 2 ins. diam., projecting 15 ins. above the ground, mound of stone W., brass cap mkd.												
	<table style="margin-left: auto; margin-right: auto;"> <tr><td colspan="2">T28N</td></tr> <tr><td colspan="2">R20W</td></tr> <tr><td style="border-right: 1px solid black;">S27</td><td>S26</td></tr> <tr><td style="border-right: 1px solid black;">S34</td><td>S35</td></tr> <tr><td colspan="2">1916</td></tr> </table>	T28N		R20W		S27	S26	S34	S35	1916			
T28N													
R20W													
S27	S26												
S34	S35												
1916													

Completion Survey, Subdivisional Lines, T. 28 N , R. 20 W.

CHAINS		
	<p>from which</p> <p>USC&GS Triangulation Station BUG, bears N. 71°04' E., 54.38 chs. dist., monumented by a standard disk, cemented in a drill hole in a malpais boulder, mkd. BUG 1947. This station was tied to by traverse and cannot be seen from the sec. cor.</p> <p>S. 89°56' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Descend a gradual W slope.</p> <p>39.95 Point for the ¼ sec. cor. of secs. 27 and 34.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T28N R20W} \\ \frac{1}{4} \frac{\text{S27}}{\text{S34}} \\ 1968 \end{array}$ <p>Raise a mound of stone N. of the corner.</p> <p>79.90 The cor. of secs. 27, 28, 33 and 34, monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, mound of stone W , brass cap mkd.</p> $\begin{array}{r} \text{T28N R20W} \\ \frac{\text{S28} \text{S27}}{\text{S33} \text{S34}} \\ 1955 \end{array}$ <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>	
	<p>From the cor. of secs. 22, 23, 26 and 27, monumented by an iron post 2 ins. diam., projecting 20 ins. above the ground, mound of stone W , brass cap mkd.</p> $\begin{array}{r} \text{T28N} \\ \text{R20W} \\ \frac{\text{S22} \text{S23}}{\text{S27} \text{S26}} \\ 1916 \end{array}$ <p>S. 89°53' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Descend W. slope.</p> <p>5.00 Wash, 20 lks. wide, 2 ft. deep, drains S. 75° W.</p> <p>12.90 Low ridge, bears N. and S.</p> <p>40.00 Point for the ¼ sec. cor. of secs. 22 and 27.</p>	

Completion Survey, Subdivisional Lines, T 28 N., R. 20 W.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4} \frac{S22}{S27}$ 1968</p> <p>Raise a mound of stone N. of the corner.</p>
77.60	Enter wash, 80 lks. wide, 1 ft. deep, drains W., from N. 75° E.
80.00	<p>The cor. of secs. 21, 22, 27 and 28, monumented by an iron post 2½ ins. diam., projecting 11 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{S21}{S28} \frac{S22}{S27}$ 1955</p> <p>This cor. is located in a wash area draining W.</p> <p>Land, rolling. Soil, gravelly and sandy loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23, monumented by an iron post 2 ins. diam., set in a collar of stone, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{S15}{S22} \frac{S14}{S23}$ 1916</p> <p>S. 89°56' W., bet. secs. 15 and 22.</p> <p>Over mountainous land, through moderate undergrowth.</p>
3.20	Wash, 100 lks. wide, 1 ft. deep, drains NW.; asc. E. slope.
21.40	High rocky ridge, bears S. 20° E. and N. 20° W.; desc. W. slope.
39.20	Track road, bears N. 15° E. and S. 15° W.; enter gently rolling land.
40.00	<p>Point for the ¼ sec. cor. of secs. 15 and 22.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4} \frac{S15}{S22}$ 1968</p> <p>Raise a mound of stone N. of the corner.</p>
71.80	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
80.00	<p>The cor. of secs. 15, 16, 21 and 22, monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W $\frac{S16}{S21} \frac{S15}{S22}$ 1955</p>
	<p>Land, mountainous to gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>S. 89°52' W., bet. secs. 10 and 15.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
5.30	<p>Enter wash, 70 lks. wide, 1 ft. deep, drains W</p>
29.00	<p>Leave same wash, drains S. 70° W.</p>
39.99	<p>Point for the ¼ sec. cor. of secs. 10 and 15.</p>
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W $\frac{1}{4} \frac{S10}{S15}$ 1968</p>
79.98	<p>The cor. of secs. 9, 10, 15 and 16, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W $\frac{S9}{S16} \frac{S10}{S15}$ 1955</p>
	<p>Land, rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
	<p>Ascend steep S. slope.</p>
1.00	<p>Top of low ridge, bears E. and W.; desc. N. slope.</p>
12.00	<p>Wash, 80 lks. wide, 1 ft. deep, drains W.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 10 and 11.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R 20 W.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{2}$ S10 S11 1968</p>
	<p>Set a wooden post, 4 x 4 ins. square, 3 ft. long, alongside the iron post.</p>
45.90	Wash, 10 lks. wide, 1 ft. deep, drains N. 60° W.
72.50	Wash, 20 lks. wide, 1 ft. deep, drains NW.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W <u>S 3 S 2</u> S10 S11 1968</p>
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°48' W , bet. secs. 2 and 11.</p> <p>Over rolling land, through moderate undergrowth.</p>
6.30	Graded road, bears S. 30° E. and N. 30° W.
38.20	Wash, 30 lks. wide, 1 ft. deep, drains NW.
40.00	Point for the $\frac{1}{2}$ sec. cor. of secs. 2 and 11.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{2}$ — <u>S 2</u> S11 1968</p>
	<p>Raise a mound of stone N. of the corner.</p>
44.50	Track road, bears SE. and NW.
80.00	The cor. of secs. 2, 3, 10 and 11.
	<p>Land, rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS									
	<p>S. 89°50' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through moderate undergrowth.</p>								
33.50	Wash, 30 lks. wide, 1 ft. deep, drains SW.								
40.00	Point for the ½ sec. cor. of secs. 3 and 10.								
	Set the iron post 22 ins. in the ground, brass cap mkd.								
	<p>T28N R20W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">½</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">1968</td> </tr> </table>	½	S 3	-----		S10		1968	
½	S 3								

S10									
1968									
	Raise a mound of stone N. of the corner.								
80.00	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, mound of stone W., brass cap mkd.								
	<p>T28N R20W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">S 4</td> <td style="text-align: center;">S 3</td> </tr> <tr> <td style="text-align: center;">S 9</td> <td style="text-align: center;">S10</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">1955</td> </tr> </table>	S 4	S 3	S 9	S10	-----		1955	
S 4	S 3								
S 9	S10								

1955									
	<p>Land, rolling.</p> <p>Soil, gravelly and sandy clay loam.</p> <p>Timber, scattered Joshua trees.</p> <p>Undergrowth, creosote bush, cacti and grass.</p>								
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 0°01' W., bet. secs. 2 and 3.</p> <p>Over rolling land, through moderate undergrowth.</p>								
9.00	Wash, 40 lks. wide, 1 ft. deep, drains W.								
26.40	Wash, 30 lks. wide, 1 ft. deep, drains S. 60° W.								
40.00	Point for the ½ sec. cor. of secs. 2 and 3.								
	Set the iron post 22 ins. in the ground, brass cap mkd.								
	<p>T28N R20W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="text-align: center;">½</td> <td></td> </tr> <tr> <td style="text-align: center;">S 3</td> <td style="text-align: center;">S 2</td> </tr> <tr> <td colspan="2" style="text-align: center;">-----</td> </tr> <tr> <td colspan="2" style="text-align: center;">1968</td> </tr> </table>	½		S 3	S 2	-----		1968	
½									
S 3	S 2								

1968									
	Raise a mound of stone W. of the corner.								
55.20	Wash, 30 lks. wide, 1 ft. deep, drains NW.								
71.20	Track road, bears S. 30° E. and N. 30° W.								
78.80	Track road, bears SE. and NW.								
80.30	Intersect the S. bdy. of T. 29 N., R. 20 W., (Seventh Standard Parallel North).								
	Point for the closing cor. of secs. 2 and 3.								

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS

Set the iron post 24 ins. in the ground, brass cap mkd.

T29N
 S35
 S 3 | S 2
 T28N | R20W
 C C
 1968

from which

The Standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 29 N., R. 20 W., bears East, 1.30 chs. dist., monumented by an iron post 1 in. diam., projecting 10 ins. above the ground, mound of stone N., brass cap mkd. SC $\frac{1}{4}$ S35 1930.

Raise a mound of stone S. of the corner.

Land, rolling.
 Soil, gravelly and sandy clay loam.
 Timber, scattered Joshua trees.
 Undergrowth, creosote bush, cacti and grass.

Point for the $\frac{1}{4}$ sec. cor. of sec. 2 is on the N. bdy. at mid-point bet. the closing cors.

Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.

$\frac{1}{4}$ S 2
 T28N R20W
 1968

from which

The Standard cor. of secs. 35 and 36, T. 29 N., R. 20 W., bears East, 1.28 chs. dist., monumented by an iron post 2 ins. diam., firmly set in a collar of stone, mound of stone N., brass cap mkd. SC T29N R20W S35 S36 1930.

Raise a mound of stone S. of the corner.

Point for the $\frac{1}{4}$ sec. cor. of sec. 3 is on the N. bdy. at mid-point bet. the closing cors.

Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.

$\frac{1}{4}$ S 3
 T28N R20W
 1968

from which

The Standard cor. of secs. 34 and 35, T. 29 N., R. 20 W., bears East, 1.38 chs. dist., monumented by an iron post 2 ins. diam., projecting 10 ins. above the ground, mound of stone N., brass cap mkd. SC T29N R20W S34 S35 1930.

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	Raise a mound of stone S. of the corner.
	From the cor. of secs. 27, 28, 33 and 34. N. 89°58' W., bet. secs. 28 and 33. Over gently rolling land, through moderate undergrowth. Descend gradual W. slope.
39.99	Point for the ¼ sec. cor. of secs. 28 and 33. Set the iron post 24 ins. in the ground, brass cap mkd. T28N R20W S28 ¼ ——— S33 1968
	Raise a mound of stone N. of the corner.
60.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 75° W
79.98	The cor. of secs. 28, 29, 32 and 33, monumented by an iron post 2½ ins. diam., projecting 10 ins. above the ground, mound of stone W, brass cap mkd. T28N R20W S29 S28 S32 S33 1955
	Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	N. 0°03' W., bet. secs. 28 and 29. Over gently rolling land, through moderate undergrowth.
23.60	Wash, 20 lks. wide, 1 ft. deep, drains S 70° W.
32.80	Wash, 20 lks. wide, 1 ft. deep, drains W.
40.00	Point for the ¼ sec. cor. of secs. 28 and 29. Set the iron post 22 ins. in the ground, brass cap mkd. T28N R20W S29 S28 ¼ ——— S33 1968
	Raise a mound of stone W. of the corner.
48.00	Wash, 30 lks. wide, 1 ft. deep, drains N. 80° W.
59.00	Wash, 20 lks. wide, 1 ft. deep, drains W.
68.20	Track road, bears N. 75° E. and S. 75° W.

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
80.00	<p>Point for the cor. of secs. 20, 21, 28 and 29.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{S20}{S29} \frac{S21}{S28}$ 1968</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N 89°56' W., bet. secs. 21 and 28.</p> <p>Over a wash area.</p>
15.90	<p>Leave wash, 80 lks. wide, 1 ft. deep, drains S. 75° W.</p>
33.60	<p>Wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.</p>
39.94	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4} \frac{S21}{S28}$ 1968</p> <p>Raise a mound of stone N of the corner.</p>
46.00	<p>Track road, bears NE. and SW.</p>
79.88	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>N. 0°04' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
39.92	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 20 and 21.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4} \frac{S20}{S21}$ 1968</p> <p>Raise a mound of stone W. of the corner.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
63.70	Wash, 40 lks. wide, 1 ft. deep, drains S. 75° W.
69.70	Wash, 70 lks. wide, 1 ft. deep, drains S. 75° W.
79.84	The cor. of secs. 16, 17, 20 and 21, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone E., brass cap mkd.
	<p style="text-align: center;">T28N R20W $\frac{S17}{S20} \frac{S16}{S21}$ 1955</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 8, 9, 16 and 17, monumented by an iron post 2½ ins. diam., projecting 11 ins. above the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W $\frac{S8}{S17} \frac{S9}{S16}$ 1955</p>
	<p>N. 0°03' W., bet. secs. 8 and 9.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>
1.50	High tension power line, bears S. 71° E. and N. 71° W.
2.50	Track road, bears S. 71° E. and N. 71° W.
7.20	Wash, 30 lks. wide, 2 ft. deep, drains N. 85° W.
14.60	Wash, 40 lks. wide, 3 ft. deep, drains N. 85° W.
40.00	Point for the ¼ sec. cor. of secs. 8 and 9.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W $\frac{1}{4}$ $S8 S9$ 1968</p>
	<p>Raise a mound of stone W. of the corner.</p>
43.30	Wash, 30 lks. wide, 1 ft. deep, drains N. 80° W.
46.40	Wash, 30 lks. wide, 1 ft. deep, drains W.
80.00	Point for the cor. of secs. 4, 5, 8 and 9.
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T28N R20W $\frac{S5}{S8} \frac{S4}{S9}$ 1968</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 89°51' W., bet. secs. 4 and 9.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
29.60	Wash, 50 lks. wide, 2 ft. deep, drains S. 50° W.
40.01	Point for the ¼ sec. cor. of secs. 4 and 9.
	<p>Set the iron post over an X chiseled in solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T28N R20W ¼ — S 4 S 9 1968</p>
80.02	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>N. 0°03' W., bet. secs. 4 and 5.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
0.20	Wash, 15 lks. wide, 1 ft. deep, drains W.
12.20	Wash, 50 lks. wide, 3 ft. deep, drains W.
26.00	Wash, 20 lks. wide, 1 ft. deep, drains W.
35.50	Wash, 20 lks. wide, 2 ft. deep, drains W.
40.00	<p>Point for the ¼ sec. cor. of secs. 4 and 5.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T28N R20W ¼ S 5 S 4 1968</p>
73.80	Wash, 20 lks. wide, 2 ft. deep, drains N. 75° W.
80.44	<p>Intersect the S. bdy. of T. 29 N., R. 20 W., (Seventh Standard Parallel North).</p> <p>Point for the closing cor. of secs. 4 and 5.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

<p>CHAINS</p>	<p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> $\begin{array}{r} T29N \\ S33 \\ \hline S 5 S 4 \\ T28N R20W \\ C C \\ 1968 \end{array}$ <p>from which</p> <p>The Standard $\frac{1}{4}$ sec. cor. of sec. 33, T. 29 N., R. 20 W., bears East, 1.28 chs. dist., monumented by an iron post 1 in. diam., firmly set in a mound of stone and with a mound of stone N., brass cap mkd. SC $\frac{1}{4}$ S33 1930.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p> <hr/> <p>Point for the $\frac{1}{4}$ sec. cor. of sec. 4 is on the N. bdy. at mid-point bet. the closing cors.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \frac{1}{4} S 4 \\ T28N R20W \\ 1968 \end{array}$ <p>from which</p> <p>The Standard cor. of secs. 33 and 34, T. 29 N., R. 20 W., bears East, 1.37 chs. dist., monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. SC T29N R20W S33 S34 1930.</p> <p>Raise a mound of stone S. of the corner.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32, monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, mound of stone W., brass cap mkd.</p> $\begin{array}{r} T28N R20W \\ S30 S29 \\ S31 S32 \\ 1955 \end{array}$ <p>N. $89^{\circ}55'$ W., bet. secs. 30 and 31.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 30 and 31.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} T28N R20W \\ \frac{1}{4} \frac{S30}{S31} \\ 1968 \end{array}$	
---------------	---	--

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	Raise a mound of stone N. of the corner.
53.10	Track road, bears N. 30° E. and S. 30° W.
79.21	The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.
	T28N R21W R20W <u>S25 S30</u> <u>S36 S31</u> 1955
	Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
	From the cor. of secs. 29, 30, 31 and 32. N. 0°03' W., bet. secs. 29 and 30. Over nearly level land, through moderate undergrowth.
17.00	Wash, 20 lks. wide, 1 ft. deep, drains W.
34.00	Track road, bears N. 60° E. and S. 60° W.
40.00	Point for the ¼ sec. cor. of secs. 29 and 30.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T28N R20W ¼ <u>S30 S29</u> 1968
	Raise a mound of stone W. of the corner.
43.20	Wash, 40 lks. wide, 1 ft. deep, drains W.
51.70	Wash, 20 lks. wide, 1 ft. deep, drains W.
80.00	Point for the cor. of secs. 19, 20, 29 and 30.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T28N R20W <u>S19 S20</u> <u>S30 S29</u> 1968
	Raise a mound of stone W. of the corner.
	Land, nearly level. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
39.98	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°54' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 29.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
<p>T28N R20W ¼ $\frac{S20}{S29}$ 1968</p>	
79.96	<p>Raise a mound of stone N. of the corner.</p> <p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
0.20 40.00	<p>N. 89°58' W., bet. secs. 19 and 30.</p> <p>Over nearly level land, through moderate undergrowth. Small wash, drains S. 60° W.</p> <p>Point for the ¼ sec. cor. of secs. 19 and 30.</p>
<p>T28N R20W ¼ $\frac{S19}{S30}$ 1968</p>	
79.13	<p>Raise a mound of stone N. of the corner.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, mound of stone W., brass cap mkd.</p>
<p>T28N R21W R20W S24 S19 S25 S30 1955</p>	
<p>Land, nearly level. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>	
<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°03' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land, through moderate undergrowth.</p>	

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
0.10	Wash, 10 lks. wide, 1 ft. deep, drains S. 60° W.
33.50	Wash, 30 lks. wide, 1 ft. deep, drains S. 80° W.
40.00	Point for the ¼ sec. cor. of secs. 19 and 20. Set the iron post 24 ins. in the ground, brass cap mkd. T28N R20W ¼ S19 S20 1968 Raise a mound of stone W. of the corner.
40.60	Wash, 20 lks. wide, 1 ft. deep, drains S. 80° W.
47.50	Wash, 30 lks. wide, 1 ft. deep, drains S. 80° W.
63.00	Wash, 20 lks. wide, 1 ft. deep, drains S. 75° W.
78.30	Wash, 30 lks. wide, 1 ft. deep, drains S. 80° W.
80.00	Point for the cor. of secs. 17, 18, 19 and 20. Set the iron post 24 ins. in the ground, brass cap mkd. T28N R20W S18 S17 S19 S20 1968 Raise a mound of stone W. of the corner. Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.
<hr/>	
	From the cor. of secs. 16, 17, 20 and 21. N. 89°47' W., bet. secs. 17 and 20. Over gently rolling land, through moderate undergrowth.
2.70	Wash, 20 lks. wide, 1 ft. deep, drains S. 60° W.
39.95	Point for the ¼ sec. cor. of secs. 17 and 20. Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd. T28N R20W ¼ S17 S20 1968 Raise a mound of stone N. of the corner.
79.90	The cor. of secs. 17, 18, 19 and 20.

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
40.00	<p>West, bet. secs. 18 and 19. Over gently rolling land, through moderate undergrowth. Point for the $\frac{1}{4}$ sec. cor. of secs. 18 and 19. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4}$ S18 S19 1968</p>
79.07	<p>Raise a mound of stone N. of the corner.</p> <p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, mound of stone E., brass cap mkd.</p> <p style="text-align: center;">T28N R21W R20W S13 S18 S24 S19 1955</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
12.50	<p>From the cor. of secs. 17, 18, 19 and 20. N. $0^{\circ}03'$ W., bet. secs. 17 and 18. Over gently rolling land, through moderate undergrowth. Wash, 20 lks. wide, 1 ft. deep, drains S. 80° W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4}$ S18 S17 1968</p>
80.00	<p>Raise a mound of stone W. of the corner.</p> <p>Point for the cor. of secs. 7, 8, 17 and 18. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W S 7 S 8 S18 S17 1968</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	<p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
39.94	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°44' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 8 and 17.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W ¼ S 8 ----- S17 1968</p>
79.88	<p>Raise a mound of stone N. of the corner.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
40.00	<p>S. 89°56' W., bet. secs. 7 and 18.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W ¼ S 7 ----- S18 1968</p>
78.97	<p>Raise a mound of stone N. of the corner.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 9 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R21W R20W S12 S 7 ----- S13 S18 1955</p> <p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS							
	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°03' W., bet. secs. 7 and 8.</p> <p>Over nearly level land, through moderate undergrowth.</p>						
13.10	Wash, 20 lks. wide, 1 ft. deep, drains S 80° W.						
28.00	Track road, bears S. 71° E. and N. 71° W.						
28.90	High tension power line, bears S. 71° E. and N. 71° W.						
40.00	Point for the ¼ sec. cor. of secs. 7 and 8.						
	Set the iron post 24 ins. in the ground, brass cap mkd.						
	<p>T28N R20W</p> <p>¼</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1969</td> </tr> </table>	S 7	S 8	1969			
S 7	S 8						
1969							
	Raise a mound of stone W. of the corner.						
57.70	Wash, 20 lks. wide, 1 ft. deep, drains N. 70° W.						
80.00	Point for the cor. of secs. 5, 6, 7 and 8.						
	Set the iron post 22 ins. in the ground, brass cap mkd.						
	<p>T28N R20W</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1968</td> </tr> </table>	S 6	S 5	S 7	S 8	1968	
S 6	S 5						
S 7	S 8						
1968							
	Raise a mound of stone W. of the corner.						
	<p>Land, nearly level.</p> <p>Soil, gravelly and sandy clay loam.</p> <p>Timber, scattered Joshua trees.</p> <p>Undergrowth, creosote bush, cacti and grass.</p>						
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°42' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land, through moderate undergrowth.</p>						
39.93	Point for the ¼ sec. cor. of secs. 5 and 8.						
	Set the iron post 24 ins. in the ground, brass cap mkd.						
	<p>T28N R20W</p> <p>¼</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 5</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td colspan="2" style="text-align: center;">1968</td> </tr> </table>	S 5	S 8	1968			
S 5	S 8						
1968							
	Raise a mound of stone N. of the corner.						
52.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 65° W.						
79.86	The cor. of secs. 5, 6, 7 and 8.						

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS	
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>S. 89°54' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ 1968</p>
	<p>Raise a mound of stone N. of the corner.</p>
54.70	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.</p>
70.00	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 65° W.</p>
78.90	<p>The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., projecting 9 ins. above the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T28N R21W R20W $\frac{S\ 1}{S\ 12}$ $\frac{S\ 6}{S\ 7}$ 1955</p>
	<p>Land, gently rolling. Soil, gravelly and sandy clay loam. Timber, scattered Joshua trees. Undergrowth, creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>N. 0°03' W., bet. secs. 5 and 6.</p> <p>Over gentle rolling land, through moderate undergrowth.</p>
2.90	<p>Wash, 20 lks. wide, 1 ft. deep, drains W.</p>
11.80	<p>Wash, 20 lks. wide, 1 ft. deep, drains N 70° W.</p>
35.10	<p>Wash, 20 lks. wide, 1 ft. deep, drains W.</p>
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T28N R20W $\frac{1}{4}$ S 6 S 5 1968</p>
	<p>Raise a mound of stone W. of the corner.</p>

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS

43.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 60° W.

80.02 Intersect the S. bdy. of T. 29 N., R. 20 W., (Seventh Standard Parallel North).

Point for the closing cor. of secs. 5 and 6.

Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.

T29N
S32

S6 | S5
T28N R20W
C C
1968

from which

The Standard ¼ sec. cor. of sec. 32, T. 29 N., R. 20 W., bears East, 1.15 chs. dist., monumented by an iron post 1 in. diam., projecting 10 ins. above the ground, mound of stone N., brass cap mkd. SC ¼ S32 1930.

Raise a mound of stone S. of the corner.

Land, gently rolling.
Soil, gravelly and sandy clay loam.
Timber, scattered Joshua trees.
Undergrowth, creosote bush, cacti and grass.

The point for the ¼ sec. cor. of sec. 5 is on the N. bdy at mid-point bet. the closing cors.

Set the iron post 20 ins. in the ground, brass cap mkd.

¼ S 5
T28N R20W
1968

from which

The Standard cor. of secs. 32 and 33, T. 29 N., R. 20 W., bears East, 1.21 chs. dist., monumented by an iron post 2 ins. diam., projecting 10 ins. above the ground, mound of stone N., brass cap mkd. SC T29N R20W S32 S33 1930.

Raise a mound of stone S. of the corner.

The point for the ¼ sec. cor. of sec. 6 is on the N. bdy. 40.00 chs. in westing from the closing cor. of sec. 5 and 6.

Set the iron post 24 ins. in the ground, brass cap mkd.

¼ S 6
T28N R20W
1968

Completion Survey, Subdivisional Lines, T. 28 N., R. 20 W.

CHAINS

from which

The Standard cor. of secs. 31 and 32, T. 29 N., R. 20 W., bears East, 1.15 chs. dist., monumented by an iron post 2 ins. diam., projecting 10 ins. above the ground, mound of stone N., brass cap mkd. SC T29N R20W S31 S32 1930.

Raise a mound of stone S. of the corner.

General Description

The elevation in Township 28 North, Range 20 West ranges from 2,350 ft. to 4,150 ft. above sea level, being at its highest point in section 26. The land is mostly rolling and level except in the southeast portion which is mountainous. The soil is rocky in the mountainous regions and gravelly and sandy clay loam throughout the rest of the township. The vegetation consists of Joshua trees, creosote bush, cacti and a good growth of grass.

There are numerous graded and track roads throughout the township. There is a telephone line that traverses northerly in the east portion. A high tension power line enters the township at the east boundary of section 24, bears N. 71° W., and leaves the township at the west boundary of section 7.

There are no settlers in this township and no water was noted throughout the surveyed areas.

The primary use for the land is for grazing.

BOOK 4899

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Howard H. Thomas	Supervisory Surveying Technician
Ira M. Thiessen	Supervisory Surveying Technician
Ronald G. Williams	Surveying Aid
Martin W. Fuller	Surveying Aid
David G. Jaramillo	Surveying Aid

BOOK 4899

CERTIFICATE OF SURVEY

I, Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11 day of July, 1968, I have made a retracement between sections 11 and 14 and a completion survey of the subdivisional lines in Township 28 North, Range 20 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 6, 1969
(Date)

Gary T. Oviatt
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JUL 10 1970

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the retracement between sections 11 and 14 and the completion survey of the subdivisional lines in Township 28 North, Range 20 West, Gila and Salt River Meridian, Arizona,

executed by Gary T. Oviatt

having been critically examined and found correct, are hereby approved.

JUN 21 1971
(Date)

Clark F. Lumm
(Chief, Division of Engineering)
Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)
Cadastral Survey