

BOOK 4732

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

OF A

PORTION

OF THE

EAST BOUNDARY

AND

SUBDIVISIONAL LINES

SURVEY

OF

SUBDIVISIONS IN SECTIONS 3 and 4

AND

MEANDERS AND TRAVERSE OF THE GILA RIVER

IN SECTIONS 2, 3 and 4

AND

SURVEY OF ACCRETION LANDS

TOWNSHIP 6 SOUTH, RANGE 30 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Louis D. Gilbert

Cadastral Surveyor

Under special instructions dated March 4, 19 68, which provided for the surveys included under Group Number 453, approved March 5, 1968, and assignment instructions dated March 5, 19 68.

Survey commenced March 27, 19 68

Survey completed April 1, 19 69

Township 6 South, Range 30 East
Gila and Salt River Meridian, Arizona

CHAINS

The east five miles and the west one mile of the north boundary (the First Standard Parallel South) was surveyed in 1882 by T. F. White and in 1891 by D. Drummond, respectively. The east one mile and the west one mile of the north boundary was retraced in 1902 by J. Nash and in 1913 by W. B. Kimmel, respectively. The east five miles of the north boundary was resurveyed, concurrently under this same group. The east boundary was surveyed in 1891 by D. Drummond; the south three miles of the east boundary was resurveyed in 1957 and 1960 under Group No. 299 by Phil D. Smith, Vern E. Lane, Eldon W. Sibley and Boyd S. Owens. The south boundary was surveyed in 1931 by C. E. Hunter. The north one mile of the west boundary was surveyed in 1891 by D. Drummond; the south five miles of the west boundary was surveyed in 1955 by H. G. Parker; the west boundary was resurveyed in 1957 and 1960 by Phil D. Smith, Vern E. Lane and Boyd S. Owens. The boundaries of Section 1 thru 6 and 11 thru 14 were surveyed in 1891 by D. Drummond, who surveyed the meanders of the Gila River in Sections 1, 2, 3 and 4 the same year. The boundaries of Sections 28 and 33 were surveyed in 1951 by White and Bilbray; the survey of the subdivisional lines was completed and a portion of the subdivisional lines were resurveyed in 1957 and 1960 by Smith, Lane and Owens.

The following field notes are those of a dependent resurvey of a portion of the east boundary and subdivisional lines, designed to restore the corners in their true original location according to the best available evidence and, survey of subdivisions, meanders and traverse of the Gila River in Sections 2, 3 and 4, and survey of accreted lands, Township 6 South, Range 30 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and Special Instructions dated March 4, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base with a brass cap riveted to the top.

The geographic position of the southeast corner of Section 13, as determined by traverse from U.S.C. & G.S. Triangulation Station SIDE, located in the south portion of Section 35, T. 5 S., R. 30 E., is: Latitude; 32° 54'15" North, Longitude; 109°13'06" West.

The mean magnetic declination was found to be 13° East.

Dependent Resurvey, Portion
East Boundary, T. 6 S., R. 30 E.

Reestablishment of the Survey executed by
D. Drummond in 1891

Beginning at the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., set 24 ins. above ground, as described in the official record of the resurvey in 1957.

Dep. Res., Portion East Bdy., T. 6 S., R. 30 E.

CHAINS	
	N. 0°01' E., bet. secs. 13 and 18. Over rolling land.
0.60	Wash, 15 lks. wide, 2 ft. deep, drains NE.
5.00	Spur, slopes NE.
10.50	Wash, 20 lks. wide, 3 ft. deep, drains NE.
19.00	Spur, slopes E.
26.00	Wash, 20 lks. wide, 2 ft. deep, drains E.
29.90	Wash, 5 lks. wide, 2 ft. deep, drains S. 60° E.
35.60	Wash, 5 lks. wide, 2 ft. deep, drains SE.
40.02	The ¼ sec. cor. of secs. 13 and 18, monumented by a malpais stone, 18x12x5 ins., firmly set 6 ins. in the ground, mkd. ¼ on W. face, with mound of stone W. At the corner point Set the iron post 22 ins. in the ground, brass cap mkd. <div style="text-align: center;"> <p>T6S R30E R31E ¼ S13 S18 1968</p> </div> Bury the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the cor. <hr style="width: 20%; margin: 10px auto;"/> N. 0°03' W., beginning new measurement. Over rolling land.
24.30	Wash, 10 lks. wide, 3 ft. deep, drains NE.
27.90	Wash, 10 lks. wide, 3 ft. deep, drains E.
32.00	Wash, 10 lks. wide, 2 ft. deep, drains SE.
40.24	The cor. of secs. 7, 12, 13 and 18, monumented by a malpais stone, 18x6x6 ins., firmly set 10 ins. in the ground, in a mound of stone, and mkd. with 2 notches on E. and 4 notches on S. faces. Cor. is located in fence line bearing E. and W. At the corner point Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd. <div style="text-align: center;"> <p>T6S R30E R31E S12 S 7 S13 S18 1968</p> </div> Bury the orig. cor. stone alongside the iron post.

Dep. Res., Portion East Bdy., T. 6 S., R. 30 E.

CHAINS	
	<p>Land, rolling. Soil, sandy, clay loam. Timber, none. Undergrowth, creosote bush and bunchgrass.</p> <hr/> <p>N. 2°33' E., bet. secs. 7 and 12. Over gently rolling land.</p> <p>40.17 The ¼ sec. cor. of secs. 7 and 12, monumented by a lava stone, 12x10x6 ins., lying in a mound of stone, mkd. ¼ on a face. I reset the orig. cor. stone 6 ins. in the ground and raise a mound of stone W.</p> <hr/> <p>N. 5°10' W., beginning new measurement. Over gently rolling land.</p> <p>36.50 Wash, 15 lks. wide, 2 ft. deep, drains NE.</p> <p>41.05 The cor. of secs. 1, 6, 7 and 12, monumented by a lava stone, 18x5x5 ins., firmly set 10 ins. in the ground, mkd. with + on top, no other mks. legible. I accept this as the orig. cor.</p> <p>At the corner point Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E R31E S 1 S 6 S 12 S 7 1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and bunchgrass.</p>
	<p>N. 2°39' E., bet. secs. 1 and 6. Over rolling land.</p> <p>2.30 Railroad R-0-W fence, bears S. 85° E. and N. 85° W.</p> <p>3.60 Power line, bears E. and W.</p> <p>3.90 Southern Pacific Railroad tracks, bear S. 82°52' E. and N. 82°52' W.</p> <p>4.10 Telegraph line, bears S. 30° E. and N. 30° W.</p> <p>5.20 Railroad R-0-W fence, bears S. 85° E. and N. 85° W.</p> <p>5.30 Point for the 1891 meander cor. of secs. 1 and 6, on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>

Dep. Res., Portion East Bdy., T. 6 S., R. 30 E.

CHAINS	
6.30	Power line, bears NE. and SW.
6.70	Power line, bears S. 30° E. and N. 30° W.
16.30	Present left bank of the Gila River, a cut bank, 3 ft. high, bears E. and W.
17.30	Gila River, 2.00 chs. wide, 1 ft. deep, flows W.
18.30	Present right bank of the Gila River, a cut bank, 3 ft. high, bears E. and W.
19.69	Point for the 1891 meander cor. of secs. 1 and 6, on the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
20.80	Power line, bears SE. and NW.
25.20	Highway R-0-W fence, bears S. 85° E. and N. 85° W.
26.80	Old State Highway No. 75 (abandoned), bears S. 85° E. and N. 85° W.
29.30	Highway R-0-W fence, bears S. 50° E. and N. 50° W.
31.00	State Highway No. 75, bears S. 50° E. and N. 50° W.
32.70	Highway R-0-W fence, bears S. 50° E. and N. 50° W.
35.50	Wash, 30 lks. wide, 2 ft. deep, drains W.
38.20	Willow Creek, 70 lks. wide, 2 ft. deep, drains irregularly W.
39.98	The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, monumented by a granite stone, 17x10x6 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, with mound of stone S.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T6S R30E R31E $\frac{1}{4}$ S 1 S 6 1968
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	Set a steel fence post, 4 ft. long, alongside the cor.
	<hr style="width: 20%; margin: auto;"/> N. 1°15' W., beginning new measurement.
	Over rolling land.
21.20	Jeep Trail, bears N. 20° E. and S. 20° W.
26.20	Head of draw, drains SW.

Dep. Res., Portion East Bdy., T. 6 S., R. 30 E.

CHAINS	
39.04	<p>Intersect the First Standard Parallel South.</p> <p>Point for the closing cor. of secs. 1 and 6, Tps. 6 S., Rs. 30 and 31 E., at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R30E S 36 ----- S 1 S 6 C C R30E R31E T6S 1968</p> </div> <p>from which</p> <p>The Stan. cor. of secs. 35 and 36, T. 5 S., R. 30 E., bears N. 89°55' W., 5.90 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered cottonwood along the river. Undergrowth, creosote bush and bunchgrass, with willows along the Gila River.</p>
<p>Dependent Resurvey, Portion of the Subdivisional Lines, T. 6 S., R. 30 E.</p>	
<p>Reestablishment of the Survey executed by D. Drummond in 1891</p>	
13.80	Spur, slopes E.
14.10	Jeep Trail, bears E. and W.
18.50	Fence, bears E. and W.
34.30	Wash in Toll House Canyon, 3.00 chs. wide, 2 ft. deep, drains E.
37.84	<p>The ¼ sec. cor. of secs. 13 and 14, monumented by a malpais stone, 12x6x4 ins., firmly set in a mound of stone, mkd. ¼ on W. face.</p> <p>At the corner point</p>

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T6S R30E</p>
	<p style="text-align: center;">$\frac{1}{2}$</p>
	<p style="text-align: center;">S14 S13</p>
	<p style="text-align: center;">1968</p>
	Bury the orig. cor. stone alongside the iron post.
	<p style="text-align: center;">_____</p>
	N. 0°25' E., beginning new measurement.
	Over rolling land.
5.70	Spur, slopes E.
10.60	Wash, 5 lks. wide, 2 ft. deep, drains N. 80° E.
16.40	Old Toll Road, bears N. 80° E. and S. 80° W.
40.45	The cor. of secs. 11, 12, 13 and 14, monumented by a sandstone, 16x8x5 ins., lying loose on ground, mkd. with 1 notch on a face and 4 notches on an adjacent face, with mound of stone W.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T6S R30E</p>
	<p style="text-align: center;">S11 S12</p>
	<p style="text-align: center;">S14 S13</p>
	<p style="text-align: center;">1968</p>
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	Land, rolling.
	Soil, rocky, sandy loam.
	Timber, none.
	Undergrowth, creosote bush and bunchgrass.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.
	S. 89°50' W., bet. secs. 12 and 13.
	Over rolling land, along fence line.
20.00	Fence, bears S. 25° W. and N. 89°50' E.
26.90	Jeep Trail, bears NE. and SW.
35.40	Wash in Toll House Canyon, 3.00 chs. wide, 3 ft. deep, drains NE.
40.12	The $\frac{1}{2}$ sec. cor. of secs. 12 and 13, monumented by a malpais stone, 16x9x6 ins., set 12 ins. in the ground, mkd. $\frac{1}{2}$ on N. face, with mound of stone N.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	<p style="text-align: center;">T6S R30E $\frac{1}{4}$ $\frac{S\ 12}{S\ 13}$ 1968</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone N. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89°32' W., beginning new measurement. Over rolling land.</p> <p>13.40 Wash, near head, 10 lks. wide, 1 ft. deep, drains N. 23.00 Spur, slopes N. 29.60 Old Toll Road, bears N. and S. 32.60 Wash, 5 lks. wide, 2 ft. deep, drains N. 38.20 Spur, slopes N. 41.23 The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and bunchgrass.</p>
	<p>N. 0°05' E., bet. secs. 11 and 12. Over rolling land.</p> <p>3.20 Wash, 10 lks. wide, 3 ft. deep, drains N. 20° E. 21.30 Wash, 20 lks. wide, 2 ft. deep, drains E. from irreg. SW. 40.26 The $\frac{1}{4}$ sec. cor. of secs. 11 and 12, monumented by a lava stone, 15x9x6 ins., lying loose on the ground, mkd. $\frac{1}{4}$ on a face, with mound of stone E.</p> <p>At the corner point Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T6S R30E $\frac{1}{4}$ S11 S12 1968</p> <p>Bury the orig. cor. stone alongside the iron post. Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°07' E., beginning new measurement. Over rolling land.</p> <p>8.50 Wash, 30 lks. wide, 3 ft. deep, drains NE.</p>

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS					
11.10	Bladed road, bears N. 80° W. and northerly. Wash, 40 lks. wide, 3 ft. deep, drains northerly along line from S. 10° E.				
23.10	Bladed road, bears southerly and N. 80° E., continue down wash.				
29.70	Leave wash, 30 lks. wide, 3 ft. deep, drains N. 80° E. from S.				
40.40	<p>The cor. of secs. 1, 2, 11 and 12, monumented by a lava stone, 18x12x7 ins., set 4 ins. in the ground, mkd. with 1 notch on E. and 5 notches on S. faces, with mound of stone N.</p> <p>At the corner point</p> <p>Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E</p> <table border="1" style="margin: auto;"> <tr> <td>S 2</td> <td>S 1</td> </tr> <tr> <td>S11</td> <td>S12</td> </tr> </table> <p>1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and bunchgrass.</p>	S 2	S 1	S11	S12
S 2	S 1				
S11	S12				
	From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.				
	N. 89°49' W., bet. secs. 1 and 12.				
	Over rolling land.				
12.50	Bladed road, bears N. 60° E. and S.				
18.10	Draw, drains N.				
23.50	Fence, bears NE. and SW.				
32.70	Bladed road, bears SE. and NW.				
35.51	<p>The ¼ sec. cor. of secs. 1 and 12, monumented by a lava stone, set 6 ins. in the ground, mkd. ¼ on N. face, with mound of stone N.; not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/>				
	S. 89°40' W., beginning new measurement.				
	Over rolling land.				
17.00	Fence, bears N. and S.				
23.00	Wash in Toll House Canyon, 50 lks. wide, 1 ft. deep, drains N.; Old Toll Road in wash, bears N. and S.				
27.20	Bladed road, bears S. and NW.				

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
37.80	Wash, 20 lks. wide, 2 ft. deep, drains N.
43.83	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and bunchgrass.</p>
	N. 0°06' E., bet. secs. 1 and 2.
	Over rolling land.
5.90	Telegraph line, on curve, bears N. 51°51' E. and N. 47°07' W.
6.20	Point for the 1891 meander cor. of secs. 1 and 2, on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
6.30	Southern Pacific Railroad tracks on curve, bears N. 51°51' E. and N. 47°07' W.
10.70	Present left bank of the Gila River, a cut bank, 3 ft. high, bears E. and W.
11.20	Gila River, 1.00 ch. wide, 2 ft. deep, flows W.
11.70	Present right bank of the Gila River, a cut bank, 3 ft. high, bears E. and W.
16.70	U. S. Highway No. 666, bears N. 39°43' E. and S. 39°43' W.
16.90	Point for the 1891 meander cor. of secs. 1 and 2, on the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
29.70	Fence, bears N. 15° E. and S. 15° W.
32.30	Wash, 25 lks. wide, 3 ft. deep, drains W.
40.01	<p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T6S R30E ¼ S 2 S 1 1968</p>
49.10	Power line, bears E. and W.
49.60	Track road, bears N. 65° E. and S. 65° W.
55.00	Draw, drains W.
56.50	Spur, slopes S. 70° W.
58.50	Draw, drains SW.

Dep. Res., Portion Subdivisional Lines, T 6 S., R. 30 E.

CHAINS


77.00 Draw, drains W.

78.10 Spur, slopes W.

79.29 Intersect the First Standard Parallel South.

Point for the closing cor. of secs. 1 and 2.

Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.



from which

A sandstone, 14x8x6 ins., bears N. 0°06' E., 17 lks. dist., lying loose on the ground, mkd. CC on a face, and 5 notches on an adjacent face, no other mks. legible. I mark AM on this orig. closing cor. and bury it in place.

The Stan. cor. of secs. 34 and 35, T. 5 S., R. 30 E., bears N. 89°50' W., 5.77 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.

Land, rolling.

Soil, rocky, sandy loam.


Timber, scattered cottonwood along the river.

Undergrowth, creosote bush and bunchgrass, with willows along the Gila River.

The point for the ¼ sec. cor. of sec. 1 is at midpoint bet. the closing cors. and on the N. bdy. of the Tp.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.



from which

The Stan. ¼ sec. cor. of sec. 35, T. 5 S., R. 30 E., bears N. 89°55' W., 5.83 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.

Set a wooden post, 8 ft. long, 2 ins. square, alongside the iron post.

From the cor. of secs. 11, 12, 13 and 14.

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	<p>S. 89°59' W., bet. secs. 11 and 14.</p> <p>Over rolling land.</p>
1.00	Wash, 10 lks. wide, 3 ft. deep, drains N. 20° E.
6.80	Spur, slopes N. 20° E.
12.00	Wash, 30 lks. wide, 1 ft. deep, drains NE.
40.38	The ¼ sec. cor. of secs. 11 and 14, monumented by an iron post, 2½ ins. diam., set 18 ins. above ground, as described in the official record of the resurveys in 1957-60.
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°52' W., bet. secs. 2 and 11.</p> <p>Over rolling land.</p>
3.90	Draw, drains N. 15° E.
10.10	Highway R-0-W fence, bears N. 15° E. and S. 15° W.
11.90	U. S. Highway No. 666, bears N. 15° E. and S. 15° W.
13.30	Highway R-0-W fence, bears N. 15° E. and S. 15° W.
18.80	Wash, 10 lks. wide, 1 ft. deep, drains N.
25.30	Spur, slopes N. 25° E.
33.30	Wash, 20 lks. wide, 1 ft. deep, drains NE.
39.52	The ¼ sec. cor. of secs. 2 and 11, monumented by a limestone, 16x12x6 ins., set 6 ins. in the ground, mkd. ¼ on N. face, with mound of stone N.
	<p>At the corner point</p> <p>Set the iron post 9 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E</p> <p>¼ $\frac{S\ 2}{S11}$</p> <p>1968</p> </div> <p>Deposit the orig. cor. stone in the mound of stone.</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>S. 89°57' W., beginning new measurement.</p> <p>Over rolling land.</p>
41.02	The cor. of secs. 2, 3, 10 and 11, monumented by an iron post, 2½ ins. diam., as described in the official record of the resurvey in 1957.
	<p>Land, rolling.</p> <p>Soil, rocky, sandy loam.</p> <p>Timber, none.</p> <p>Undergrowth, creosote bush and bunchgrass.</p>



Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	N. 0°28' E., bet. secs. 2 and 3. Over rolling land.
27.10	Wash, 40 lks. wide, 2 ft. deep, drains NE.
32.30	Fence, bears E. and W.
35.80	Spur, slopes E.
40.09	Point for the $\frac{1}{2}$ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd. T6S R30E $\frac{1}{2}$ S 3 S 2 1968
47.70	Railroad R-O-W fence, bears S. 40°13' E. and N. 40°13' W.
48.20	Telegraph line, bears S. 40°13' E. and N. 40°13' W.
48.60	Southern Pacific Railroad tracks, bears S. 40°13' E. and N. 40°13' W.
49.11	Point for the 1891 meander cor. of secs. 2 and 3, on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
53.00	Present left bank of the Gila River, a cut bank, 4 ft. high, bears SE. and NW.
53.90	Gila River, 1.90 chs. wide, 3 ft. deep, flows NW.
54.92	Point for the meander cor. of secs. 2 and 3, on the present right bank of the Gila River, identical with the proportionate point for the 1891 right bank meander cor., falls on a cut bank 5 ft. high, bearing SE. and NW., where a monument cannot be established. There is no remaining evidence of the orig. cor.
55.32	Point selected for the witness meander cor. of secs. 2 and 3, on the right bank of the Gila River. Set the iron post over + chiseled on rock outcrop, mound of stone to top, brass cap mkd. W C T6S R30E S 3 S 2 ↓ M C 1968
60.14	Point for the N $\frac{1}{16}$ sec. cor. of secs. 2 and 3 at proportionate dist.; falls on the NW. end of an old grave. Several graves are located in close proximity easterly of the cor. point.

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
60.24	<p>Point selected for the witness N 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E N 1/16 W C S 3 ↓ S 2 1968</p> </div>
64.40	<p>Desc. over NW. slope of mesa.</p>
69.56	<p>Point for the 1891 meander cor. of secs. 2 and 3 on the right bank of the Gila River at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E M C S 3 S 2 1968</p> </div> <p>from which</p> <p>(for informational purposes only) the proportionate point for the closing cor. of secs. 2 and 3 on the N. bdy. of the Tp., bears N. 0°28' E., 10.02 chs. dist.; there is no remaining evidence of the original witness closing cor. set 3.40 chs. East. Not monumented. From the proportionate point for the closing cor. the point for the standard cor. of secs. 33 and 34, T. 5 S., R. 30 E., bears N. 89°50' W., 5.80 chs. dist., as described in the field notes of the First Standard Parallel South, concurrently resurveyed under this same Group No.</p> <p>The NE. cor. of a frame house, bears S. 66° 58' W., 1.63 chs. dist.</p> <p>The NE. side of porch on a frame house, bears N. 0°28' E., 2.80 chs. dist.</p> <p>The cor. is located near the base of a NW. slope.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>Thence,</p> <p>N. 89°22' W., bet. secs. 2 and 3, over accreted lands.</p>
0.63	<p>Southern Pacific Railroad track, bears N. 18°41' E. and S. 18°41' W.; continue over nearly level land through scattered cottonwood trees.</p>
1.38	<p>Power line leading to house, bears N. 20° E. and S. 20° W.; thence by traverse, topography estimated.</p>

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
1.80	Enter NW. corner of fenced yard.
2.50	Shed on line; leave fenced yard.
3.10	Enter heavy salt cedar.
4.48	<p>The present right bank of the Gila River, bears N. 9°45' E. and S. 9°45' W., and point for the meander cor. of sec. 3.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E</p>  <p>1968</p> </div> <p>Set a wooden post, 4 ft. long, 6 ins. diam., alongside the iron post.</p> <p>The division of the accreted lands has been accomplished on a ratable basis between the adjusted record meander line of each affected section to respective proportionate segments of the present right bank of the Gila River.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered cottonwood along the Gila River. Undergrowth, creosote bush and bunchgrass with heavy salt cedar and willows along the Gila River.</p>
	<p>From the cor. of secs. 3 and 4 only, monumented by an iron post, 2½ ins. diam., as described in the official record of the resurvey in 1957.</p> <p>N. 0°21' E., bet. secs. 3 and 4.</p> <p>Over rolling land.</p>
1.90	Draw, drains E.
5.80	Wash, 20 lks. wide, 2 ft. deep, drains S. 80° E.
32.70	Ridge, bears E. and W.
40.10	<p>Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E</p>  <p>1968</p> </div>
60.14	<p>Point for the N 1/16 sec. cor. of secs. 3 and 4, at proportionate dist.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p>

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	<p style="text-align: center;">T6S R30E N 1/16 S 4 S 3 1968</p>
64.15	<p>Point selected for the witness meander cor. of secs. 3 and 4, on the left bank of the Gila River, identical with the proportionate point for the 1891 left bank meander cor., falls on the top of a 200 ft. high bluff bearing N. 78° E. and N. 89° W. The bluff overlooks the Gila River. There is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">M C ----- S 4 ↑ S 3 T6S R30E W C 1968</p>
	<p>Descend nearly vertical 200 ft. N. slope.</p>
65.95	<p>The present mean high water line and the true point for the meander cor. of secs. 3 and 4, on the left bank of the Gila River, falls on a vertical rock wall 75 ft. high, bearing N. 67°56' E. and N. 77°10' W., where a monument cannot be established.</p>
66.95	<p>Gila River, 2.00 chs. wide, 1 ft. deep, flows north-westerly from northeasterly.</p>
67.16	<p>Point for the 1891 meander cor. of secs. 3 and 4, on the right bank of the Gila River, at proportionate dist., falls in the Gila River; there is no remaining evidence of the orig. cor.; not monumented.</p>
67.95	<p>The present mean high water line and point for the meander cor. of sec. 3 on the right bank of the Gila River, falls on a cut bank, 3 ft. high, bears N. 76°35' E. and N. 79°45' W., where a monument cannot be established.</p>
	<p>Ascend steep S. slope.</p>
69.25	<p>Point selected for the witness meander cor. of sec. 3 on the right bank of the Gila River.</p>
	<p>Set the iron post over a + chiseled on solid rock, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">W C T6S R30E ↓ S 3 ----- M C 1968</p>
75.30	<p>Power line and old railroad bed, bears S. 77°35' E. and N. 77°35' W.</p>
79.59	<p>Intersect the First Standard Parallel South.</p>


Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS

The closing cor. of secs. 3 and 4, monumented by a lava stone, 18x6x4 ins., set 12 ins. in the ground, mkd. with 3 notches on E. and W. faces, and CC on S. face, in a mound of stone.

At the corner point

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.



from which

The Stan. cor. of secs. 32 and 33, T. 5 S., R. 30 E., bears N. 89°50' W., 6.01 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.

Bury the orig. cor. stone alongside the iron post.

Land, rolling.

Soil, rocky, sandy loam.


Timber, scattered cottonwood along the river.

Undergrowth, creosote bush and bunchgrass, with willows along the Gila River.

The point for the ¼ sec. cor. of sec. 3, is at midpoint between the closing cors. and on the N. bdy. of the Tp.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.



from which

The point for the Stan. ¼ sec. cor. of sec. 33, T. 5 S., R. 30 E., bears N. 89°50' W., 5.91 chs. dist., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.

The point for the E 1/16 sec. cor. of sec. 3, is at mid-point bet. the point for the closing cor. of secs. 2 and 3 and the ¼ sec. cor. of sec. 3, and on the N. bdy. of the Tp.; not monumented.

from which

The point for the Stan. sec. cor. of secs. 33 and 34, T. 5 S., R. 30 E., bears S. 89°50' E.,

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	<p>14.15 chs. dist., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.</p> <hr/> <p>From the cor. of secs. 4 and 5 only, T. 6 S., R. 30 E., monumented by an iron post, 2½ ins. diam., as described in the official record of the resurvey in 1957.</p> <p>N. 0°14' E., bet. secs. 4 and 5.</p> <p>Over rolling land.</p> <p>23.40 Wash, 10 lks. wide, 2 ft. deep, drains irregularly N. from SW.</p> <p>30.10 Leave wash, 10 lks. wide, drains N. 10° W.</p> <p>40.20 The ¼ sec. cor. of secs. 4 and 5, monumented by a malpais stone, 14x6x6 ins., set 8 ins. in the ground, mkd. ¼ on W. face.</p> <p>At the corner point</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R30E ¼ S 5 S 4 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°02' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>19.80 Wash, 10 lks. wide, 2 ft. deep, drains irregularly N., from S. 20° E.</p> <p>20.06 Point for the N 1/16 sec. cor. of secs. 4 and 5, at proportionate dist.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R30E N 1/16 S 5 S 4 1968</p> <p>Cor. falls 10 lks. E. of wash, 10 lks. wide, 2 ft. deep, draining irregularly N.</p> <p>32.90 Leave wash, 10 lks. wide, 2 ft. deep, drains N. 15° E. from irregularly S.</p> <p>39.50 Intersect the First Standard Parallel South.</p> <p>The closing cor. of secs. 4 and 5, monumented by a lava stone, 18x10x9 ins., loosely set 3 ins. in the ground, mkd. with 4 notches on E., 2 notches on W. faces and CC on S. face, with mound of stone W.</p>

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS

At the corner point

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

$$\begin{array}{c} \text{T5S} \\ \text{S 32} \\ \hline \text{S 5} \mid \text{S 4} \\ \text{C C} \\ \text{T6S R30E} \\ 1968 \end{array}$$

from which

The Stan. cor. of secs. 31 and 32, T. 5 S., R. 30 E., bears N. 89°52' W., 5.99 chs. dist., monumented by an iron post, 2½ ins. diam., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.

Bury the orig. cor. stone alongside the iron post.

Land, rolling.

Soil, rocky, sandy loam.

Timber, none.

Undergrowth, creosote bush and bunchgrass.

The point for the ¼ sec. cor. of sec. 4 is at midpoint bet. the closing cors. and on the N. bdy. of the Tp.

At the corner point

Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.

$$\begin{array}{c} \hline \frac{1}{4} \text{ S 4} \\ \text{T6S R30E} \\ 1968 \end{array}$$

from which

The true point for the Stan. ¼ sec. cor. of sec. 32, T. 5 S., R. 30 E., bears N. 89°52' W., 6.00 chs. dist., as described in the field notes of the First Stan. Par. South, concurrently being resurveyed under this same Group No.

The point for the E 1/16 sec. cor. of sec. 4, is at midpoint bet. the closing cor. of secs. 3 and 4, and the ¼ sec. cor. of sec. 4, and on the N. bdy. of the Tp.

At the corner point

Set the iron post 18 ins. in the ground, collar of stone to top, brass cap mkd.

$$\begin{array}{c} \hline \text{E } 1/16 \text{ S 4} \\ \text{T6S R30E} \\ 1968 \end{array}$$

Dep. Res., Portion Subdivisional Lines, T. 6 S., R. 30 E.

CHAINS	
	<p>from which</p> <p>The Stan. cor. of secs. 32 and 33, T. 5 S., R. 30 E., bears S. 89°52' E., 14.015 chs. dist., hereinbefore described.</p>
	<p>Subdivision of Section 3, T. 6 S., R. 30 E.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of sec. 3 only, on the S. bdy. of sec. 3, monumented by an iron post, 2$\frac{1}{2}$ ins. diam., as described in the official record of the resurvey in 1957.</p> <p>N. 0°28' E., on the N. and S. centerline of sec. 3.</p> <p>Over rolling land.</p>
0.30	Draw, drains NE. from the W.
17.50	Spur, slopes E.
23.50	Wash, 5 lks. wide, 2 ft. deep, drains E.
28.30	Spur, slopes E.
40.77	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 3, at the intersection with the E. and W. centerline of sec. 3.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R30E C $\frac{1}{4}$ + S 3 1968</p>
60.80	<p>Point for the C-N 1/16 sec. cor. of sec. 3, at proportionate dist.</p> <p>Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R30E C N 1/16 S 3 C 1968</p>
61.00	Fence, bears E. and W., 10 lks. dist., to cor. of fences bearing N. and E.
67.40	Power line, bears N. 75°38' E. and S. 75°38' W., 70 lks. dist., thence N. 77°35' W.
70.20	Wash, 15 lks. wide, 2 ft. deep, drains NW.
72.10	Old Railroad bed, bears E. and W.; enter scattered cottonwood timber and dense undergrowth, bears E. and W.
79.20	Leave scattered cottonwood timber and dense undergrowth, bears E. and W.

Subdivision of Section 3, T. 6 S., R. 30 E.

CHAINS		
80.23	<p>The $\frac{1}{4}$ sec. cor. of sec. 3 on the N. bdy. of the Tp.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered cottonwood along the river. Undergrowth, creosote bush and bunchgrass, with willows and salt cedar along the Gila River.</p>	
19.97	<p>From the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.</p> <p>N. $89^{\circ}52'$ W., on the E. and W. centerline of sec. 3.</p> <p>Over rolling land.</p> <p>Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 3.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R30E C $\frac{E 1/16}{S 3}$ C 1968</p>	
33.70	<p>Wash, 5 lks. wide, 1 ft. deep, drains N. 10° W.</p>	
39.94	<p>The center $\frac{1}{4}$ sec. cor. of sec. 3.</p> <p>Thence along steep N. slope.</p>	
79.79	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 4.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and bunchgrass.</p>	
Subdivision of NE $\frac{1}{4}$ Section 3		
15.90	<p>From the C-E $\frac{1}{16}$ sec. cor. of sec. 3.</p> <p>N. $0^{\circ}28'$ E., on the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 3.</p> <p>Over rolling land.</p> <p>Thence over nearly level land.</p>	
20.04	<p>Point for the NE $\frac{1}{16}$ sec. cor. of sec. 3, at the intersection with the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 3.</p> <p>Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.</p> <p style="text-align: center;">T6S R30E NE $\frac{1}{16}$ S 3 1968</p> <p>from which</p> <p>The true point for the N $\frac{1}{16}$ sec. cor. of secs. 2 and 3, bears S. $89^{\circ}50'$ E., 19.95 chs. dist.</p>	


Subdivision of Section 3, T. 6 S., R. 30 E.

CHAINS	
20.60	Fence, bears E. and W.
28.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 35° W.
31.80	Power line, bears N. 75°38' E. and S. 75°38' W.
36.50	Old Railroad bed, bears N. 75° E. and S. 75° W.
37.00	Enter scattered cottonwood timber and dense undergrowth, bears N. 75° E. and S. 75° W.
39.47	The point for the E 1/16 sec. cor. of sec. 3, on the N. bdy. of the Tp.
	From the NE 1/16 sec. cor. of sec. 3.
	N. 89°50' W., on a portion of the E. and W. centerline of the NE 1/4 of sec. 3.
	Over flat mesa.
4.20	Ascend over rolling land.
10.20	Wash, 5 lks. wide, 1 ft. deep, drains N. 25° E.
19.95	The C-N 1/16 sec. cor. of sec. 3.
	Subdivision of Section 4
	From the 1/4 sec. cor. of sec. 4 only, on the S. bdy. of sec. 4, monumented by an iron post, 2 1/2 ins. diam., as described in the official record of the resurvey in 1957.
	N. 0°23' E., on the N. and S. centerline of sec. 4.
	Over rolling land.
9.70	Top of round knoll, descend.
40.14	Point for the center 1/4 sec. cor. of sec. 4, at the intersection with the E. and W. centerline of sec. 4.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T6S R30E C 1/4 + S 4 1969
60.21	Point for the C-N 1/16 sec. cor. of sec. 4, at proportionate dist.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T6S R30E C N 1/16 S 4 C 1969
63.00	Point selected for the witness special meander cor. of sec. 4, on the left bank of the Gila River.

Subdivision of Section 4, T. 6 S., R. 30 E.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, collar of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E SMC C S 4 C W C 1969</p> </div>	
63.20	<p>The present mean high water line and true point for the special meander cor. of sec. 4, on the left bank of the Gila River, a cut bank, 3 ft. high, bears S. 86°45' E. and N. 86°45' W., where a monument cannot be established.</p>	
63.95	<p>Gila River, 1.50 chs. wide, 1 ft. deep, flows northwesterly.</p>	
64.70	<p>The present mean high water line and true point for the special meander cor. of sec. 4, on the right bank of the Gila River, a cut bank, 4 ft. high, bears S. 76°45' E. and N. 73°30' W., where a monument cannot be established.</p>	
65.10	<p>Point selected for the witness special meander cor. of sec. 4, on the right bank of the Gila River.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>W C T6S R30E C S 4 C SMC 1969</p> </div>	
73.60	<p>Track road, bears SE. and NW.</p>	
79.66	<p>The 1/4 sec. cor. of sec. 4, on the N. bdy. of the Tp.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered cottonwood along the river. Undergrowth, creosote and bunchgrass, with willows and salt cedar along the Gila River.</p>	
20.04	<p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89°53' W., on the E. and W. centerline of sec. 4.</p> <p>Over rolling land.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 4.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R30E C E 1/16 C S 4 1968</p> </div>	

Subdivision of Section 4, T. 6 S., R. 30 E.

CHAINS	
31.80	Draw, drains N.
40.08	The center $\frac{1}{4}$ sec. cor. of sec. 4.
60.80	Draw, drains N. 30° E.
79.85	The $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	Land, rolling. Soil, rocky, sandy loam. Timber, none. Undergrowth, creosote bush and bunchgrass.
	Subdivision of NE $\frac{1}{4}$ Section 4
	From the C-E 1/16 sec. cor. of sec. 4.
	N. 0°23' E., on the N. and S. centerline of the NE $\frac{1}{4}$ of sec. 4.
	Over rolling land.
18.80	Fence, bears SE. and NW.
20.07	Point for the NE 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. centerline of the NE $\frac{1}{4}$ of sec. 4.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T6S R30E NE 1/16 S 4 1969
27.34	The present mean high water line and point for the special meander cor. of sec. 4, on the left bank of the Gila River, a cut bank 5 ft. high, bears N. 77°30' E. and S. 77°30' W.
	Set the iron post 20 ins. in the ground, collar of stone to top, brass cap mkd.
	T6S R30E SMC E  E 1969
27.66	Calculated mean high water line of the right bank of the Gila River as it existed in 1891; not monumented.
28.14	Gila River, 1.60 chs. wide, 1 ft. deep, flows southwest-erly.
28.94	The present mean high water line and true point for the special meander cor. of sec. 4, on the right bank of the Gila River, a vertical rock wall, 12 ft. high, bears N. 67°01' E. and S. 63° W., where a monument cannot be established.

Subdivision of Section 4, T. 6 S., R. 30 E.

CHAINS	
29.24	<p>Point selected for the witness special meander cor. of sec. 4, on the right bank of the Gila River.</p> <p>Set the iron post over a + chiseled on solid rock, mound of stone to top, brass cap mkd.</p>
<p>W C T6S R30E E S 4 E SMC 1969</p>	
32.60	<p>Old railroad bed and track road, bears N. 80° E. and S. 80° W.</p>
38.70	<p>Power line, bears S. 70° E. and N. 70° W.</p>
39.50	<p>The E 1/16 sec. cor. of sec. 4, on the N. bdy. of the Tp.</p>
<hr/> <p>From the N 1/16 sec. cor. of secs. 3 and 4.</p>	
<p>N. 89°52' W., on the E. and W. centerline of the NE ¼ of sec. 4.</p>	
<p>Over rolling land.</p>	
20.05	<p>The NE 1/16 sec. cor. of sec. 4.</p>
21.35	<p>Fence, bears SE. and NW.</p>
28.40	<p>Draw, drains N. 20° E.</p>
40.10	<p>The C-N 1/16 sec. cor. of sec. 4.</p>
<p>Meanders of the Gila River T. 6 S., R. 30 E.</p>	
<hr/> <p>At the point for the meander cor. of secs. 3 and 33, Tps. 5 and 6 S., R. 30 E., on the present left bank of the Gila River, a cut bank, 3 ft. high, bears N. 15°16' E. and S. 15°16' W.</p>	
<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
<p>MC / T5S S 33 R30E S 3 T6S 1968</p>	
<p>from which</p>	
<p>The ¼ sec. cor. of sec. 3 on the N. bdy. of the Tp., bears S. 89°50' E., 4.01 chs. dist.</p>	
<p>Deposit glass in hole alongside the iron post.</p>	
<p>Thence, with the meanders of the left bank of the Gila River, downstream in Section 3.</p>	

Meanders of the Gila River, T. 6 S., R. 30 E.

CHAINS	
	Along a cut bank about 3 ft. high.
S. 16°15' W., 5.20 chs.	
S. 34°45' W., 1.60 chs.	On this course the bank increases from 3 ft. to 15 ft. high.
N. 49°00' W., 2.00 chs.	
N. 72°45' W., 6.10 chs.	On this course the bank decreases from 15 ft. to 3 ft. high.
N. 76°30' W., 7.60 chs.	
S. 59°15' W., 9.80 chs.	On this course the bank becomes a nearly vertical cliff, 75 ft. to 100 ft. above mean high water.
S. 23°30' W., 3.80 chs.	
S. 67°56' W., 9.65 chs.	At the end of this course, intersect the true point for the meander cor. of secs. 3 and 4, on the left bank of the Gila River.
	Land, rolling. Soil, rocky, sandy loam. Timber, widely scattered cottonwood. Undergrowth, mesquite, oak brush and bunchgrass.
	Thence, with the meanders of the left bank of the Gila River, downstream in Section 4.
	Along a nearly vertical cliff, 75 ft. high, decreasing to a cut bank, 6 ft. high.
N. 77°10' W., 13.63 chs.	
S. 77°30' W., 7.00 chs.	At 6.91 chs. on this course, intersect the special meander cor. on the N. and S. centerline of the NE¼ of sec. 4.
S. 62°23' W., 10.43 chs.	
N. 86°45' W., 11.30 chs.	At 10.75 chs. on this course, intersect the true point for the special meander cor. on the N. and S. centerline of sec. 4.
N. 39°45' W., 15.40 chs.	Along a cut bank, 3 ft. to 6 ft. high.
N. 68°45' W., 3.60 chs.	
S. 82°15' W., 4.00 chs.	
S. 53°15' W., 3.20 chs.	
N. 61°30' W., 4.20 chs.	

Meanders of the Gila River, T. 6 S., R. 30 E.


CHAINS

N. 23°15' W., 4.11 chs. On this course the bank becomes a nearly vertical cliff 20 ft. to 75 ft. high.

At the end of this course intersect the N. bdy. of the Tp.

Point for the meander cor. of secs. 4 and 32, Tps. 5 and 6 S., R. 30 E., on the present left bank of the Gila River, at the base of a nearly vertical cliff, 75 ft. high, bears S. 23°15' E. and N. 23°15' W.

Set the iron post 20 ins. in the ground, brass cap mkd.



from which

The closing cor. of secs. 4 and 5 on the N. bdy. of the Tp., bears N. 89°52' W., 14.35 chs. dist.

Land, rolling.


Soil, rocky, sandy loam.

Timber, widely scattered cottonwood.

Undergrowth, mesquite, oak brush and bunchgrass.

At the point for the meander cor. of secs. 4 and 32, Tps. 5 and 6 S., R. 30 E., on the present right bank of the Gila River, a cut bank, 5 ft. high, bears S. 29°48' E. and N. 29°48' W.

Set the iron post 24 ins. in the ground, brass cap mkd.



from which

The ½ sec. cor. of sec. 4 on the N. bdy. of the Tp., bears S. 89°52' E., 23.80 chs. dist.

Thence, with the meanders of the right bank of the Gila River, upstream in Section 4.

Along a cut bank about 5 ft. high.

S. 29°48' E., 4.56 chs.

N. 69°45' E., 3.90 chs.

N. 87°45' E., 3.70 chs.

N. 68°30' E., 1.60 chs.

On this course the bank becomes a nearly vertical cliff, 20 ft. high.

Meanders of the Gila River, T. 6 S., R. 30 E.

CHAINS		
S. 48°00' E., 3.50 chs.	On this course the bank becomes a cut bank, about 6 ft. high.	
S. 40°00' E., 13.60 chs.		
S. 73°30' E., 1.30 chs.	At the end of this course, intersect the true point for the special meander cor. on the N. and S. centerline of sec. 4.	
S. 76°45' E., 1.70 chs.		
S. 89°30' E., 10.00 chs.		
N. 55°30' E., 3.80 chs.		
N. 63°00' E., 5.90 chs.	On this course the bank becomes a nearly vertical cliff, about 15 ft. high.	
	At the end of this course, intersect the true point for the special meander cor. on the N. and S. centerline of the NE $\frac{1}{4}$ of sec. 4.	
Thence, with traverse of the right bank of the Gila River, upstream in sec. 4.		
N. 67°01' E., 1.85 chs.		
N. 86°30' E., 4.50 chs.		
S. 82°30' E., 6.00 chs.	On this course the bank becomes a cut bank, 3 ft. to 6 ft. high.	
S. 79°45' E., 8.00 chs.	At the end of this course, intersect the true point for the meander cor. of sec. 3 on the right bank of the Gila River.	
Land, rolling. Soil, rocky, sandy loam. Timber, widely scattered cottonwood. Undergrowth, mesquite, oak brush and bunchgrass.		
Thence, with the meanders of the right bank of the Gila River, upstream in Section 3.		
Along a cut bank, 3 ft. to 8 ft. high.		
N. 76°35' E., 6.91 chs.		
N. 29°30' E., 4.30 chs.	On this course the bank becomes a nearly vertical cliff, 75 ft. to 100 ft. high.	
N. 24°00' E., 3.50 chs.		
N. 73°00' E., 9.00 chs.	On this course the bank becomes a cut bank, 3 ft. to 8 ft. high.	
S. 84°00' E., 7.50 chs.		

Meanders of the Gila River, T. 6 S., R. 30 E.


CHAINS

S. 63°00' E., 6.80 chs.

N. 15°30' E., 4.40 chs. At the end of this course, intersect the N. bdy. of the Tp.

Point for the meander cor. of secs. 3 and 33, Tps. 5 and 6 S., R. 30 E., on the present right bank of the Gila River, a cut bank, about 8 ft. high, bears N. 15°30' E. and S. 15°30' W.

Set the iron post over a + chiseled on rock outcrop, mound of stone to top, brass cap mkd.



from which

The ¼ sec. cor. of sec. 3 on the N. bdy. of the Tp., bears S. 89°50' E., 6.41 chs. dist.

Land, rolling.
 Soil, rocky, sandy loam.
 Timber, widely scattered cottonwood.
 Undergrowth, mesquite, oak brush and bunchgrass.

Traverse and Meander of the Present Right Bank of the Gila River Secs. 2 and 3

Beginning at the point for the meander cor. of secs. 2 and 34 on the N. bdy. of the Tp. and on the present right bank of the Gila River. Not monumented.

from which

The proportionate point for the record closing cor. of secs. 2 and 3, bears S. 89°50' E., 1.60 chs. dist. Not monumented.

Thence, with traverse of the present right bank of the Gila River upstream in Sec. 2, along cut bank from 3 to 6 ft. high through heavy willows. For informational purposes only.

S. 22°23' W., 4.38 chs.

S. 14°00' W., 3.60 chs.

S. 9°45' W., 2.48 chs. Intersect the meander cor. of sec. 3 on the present right bank of the Gila River.

Thence, with the meander of the present right bank of the Gila River upstream in section 3 through heavy undergrowth, along cut bank 6 ft. high.

S. 9°45' W., 2.62 chs.

S. 17°30' E., 7.20 chs. At 5.40 chs. on this course, the railroad (at N. end of trestle) bears N. 22° E.

Traverse and Meander of the Present Right Bank of the Gila River Secs. 2 and 3.

<p>CHAINS</p>	<p>and S. 22° W. Continue along base of W. slope.</p> <p>S. 11°11' E , 2.21 chs. At end of this course, continue along base of SW. slope</p> <p>S. 34°30' E., 3.40 chs. At end of this course, slope changes to S.</p> <p>S. 45°00' E., 0.40 chs. Intersect the true point for the meander cor. of secs. 2 and 3 on the present right bank of the Gila River.</p>
	<p>Calculated Adjusted 1891 Right Bank Meanders in Sections 2 and 3.</p>
	<p>Beginning at the proportionate point for the meander cor. of secs. 2 and 34 on the N. bdy. of the Tp. Not monumented.</p> <p>from which</p> <p style="padding-left: 40px;">The proportionate point for the record closing cor. of secs. 2 and 3, bears N. 89°50' W., 3.10 chs. dist.</p> <p>Thence, upstream along the 1891 adjusted record meander line of the right bank of the Gila River in Section 2.</p> <p>S. 17°36' W., 10.50 chs. Intersect the reestablished meander cor. of secs. 2 and 3.</p> <p>Thence, along the adjusted record meander line in sec. 3.</p> <p>S. 17°36' W., 10.07 chs.</p> <p>S. 30°10' E., 5.83 chs. Intersect the true point for the reestablished record meander cor. of secs. 2 and 3 on the present right bank of the Gila River, at 54.92 chs. N. 0°28' E. from the cor. of secs. 2, 3, 10 and 11.</p>
	<p>General Description</p>
	<p>The area encompassed by this survey is rolling to semi-mountainous, with the elevation ranging from 3350 feet to 4510 ft. above sea level. The soil is very shallow and is a gravelly, sandy loam and extremely rocky.</p> <p>There is a scattered to moderate growth of creosote bush, bunchgrass and cacti throughout the area. Widely scattered cottonwoods and a moderate growth of mesquite is found along the Gila River.</p>

General Description

CHAINS

Drainage within the area is in a northerly and southerly direction, draining into the Gila River which enters the township on the east boundary of section 1 and flows in a westerly direction, leaving on the north boundaries of section 4.

Track roads, graded roads, and U.S. Highway No. 666 and State Highway No. 75 which traverses through the eastern portion of the area, provides access throughout the Tp.

There are a few inhabitants in the town of Guthrie, situated in the north portion of secs. 2 and 3. Also a few other inhabitants are located in section 1.

Principle use of the land is for cattle grazing.

1A

898K 4902

INDEX DIAGRAM

Township 6 S., Range 30 E.

		18	16		10
6	5 17	4 14	3 12	2 9 11	1 3 8
7	8	9	10	11 7 10	12 3 6
18	17	16	15	14 5	13 1
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Sec. 3 -- Page 19

Subdivision of Sec. 4 -- Page 21

Meanders, Gila River -- Page 24

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Howard H. Thomas	Surveying Technician
Ira M. Thiessen	Surveying Technician
Ronald G. Williams	Surveying Aid
Martin W. Fuller	Surveying Aid
Jerrold L. Jones	Surveying Aid

32

CERTIFICATE OF SURVEY

I, Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 4th day of March, 1968, I have dependently resurveyed a portion of the east boundary and subdivisional lines, surveyed subdivisions in Sections 3 and 4, meandered and traversed the Gila River in Sections 2, 3 and 4 and surveyed accretion land, Township 6 South, Range 30 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 12, 1969
(Date)

Louis D. Gilbert
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date SEP 4 1970

BUREAU OF LAND MANAGEMENT,
Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the east boundary and subdivisional lines, the survey of subdivisions in Sections 3 and 4, meanders and traverse of the Gila River in Sections 2, 3 and 4 and the survey of accretion land, Township 6 South, Range 30 East, Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert

having been critically examined and found correct, are hereby approved.

SEP 17 1971
(Date)

Clark L. Lamm
(Chief, Division of Engineering)
Cadastral Survey

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Engineering)
Cadastral Survey~~