

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY

OF A

PORTION OF THE EAST AND SOUTH BOUNDARIES

AND

SUBDIVISIONAL LINES

AND THE

SURVEY OF SUBDIVISIONS IN SECTIONS

2, 9, 11, 12, 13, 14, 15, 23, 25, 27, 32, 34 and 35

TOWNSHIP 8 SOUTH, RANGE 31 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Kenneth D Herman Cadastral Surveyor

Gary T. Oviatt Cadastral Surveyor

Jerrold E. Knight Cadastral Surveyor

Under special instructions dated December 14, 19 67, which provided for the surveys included under Group Number 462, approved December 14, 1967, and assignment instructions dated December 14, 19 67.

Survey commenced December 20, 19 67

Survey completed January 30, 19 68

1A

BOOK 4911 INDEX DIAGRAM

Township 8 South, Range 31 East

6	5	4 30	3 27	23 2 22	16 1 5 15
7	8	29 9 28	27 10 26	22 11 21	13 12 4 12
18	17	16	25 15 25	20 14 19	11 13 3 11
19	20	21	22 24	18 23 18	10 24 2 9
30	29 32	28	27	17 26 16	9 25 8
31	32 32 6	31 33	34	35 5	7 36

Subdivision

	<u>Page</u>		<u>Page</u>
Sec. 2 - - - -	33	Section 23 - - - -	54
Sec. 9 - - - -	36	" 25 - - - -	55
Sec. 11 - - - -	38	" 27 - - - -	56
Sec. 12 - - - -	41	" 32 - - - -	57
Sec. 13 - - - -	44	" 34 - - - -	58
Sec. 14 - - - -	47	" 35 - - - -	59
Sec. 15 - - - -	51		

Township 8 South, Range 31 East
Gila and Salt River Meridian, Arizona

CHAINS

The east and north boundaries, the east three miles of the south boundary and a portion of the subdivisional lines were surveyed in 1882 by T. F. White. The west three miles of the south boundary were surveyed and the south boundary of sections 34 and 35 was resurveyed in 1910 by H. F. DuVal. The west boundary was surveyed and the west one and one-half miles of the north boundary were resurveyed in 1931 by C. E. Hunter. The boundaries of section 32 were surveyed and the south boundary of section 32 resurveyed by George M. Boofer in 1956. The west one mile and the east four miles of the south boundary, the south two miles of the east boundary and the west two miles of the north boundary were resurveyed in 1961-62 by Cazier and Murphy, who also completed the survey of the subdivisional lines the same year.

The north boundaries of sections 2 and 3 were resurveyed concurrently under this same group by Herman and Oviatt. The record thereof is included in the field notes of Township 7 South, Range 31 East.

The following notes are those of a dependent resurvey of the north four and one-half miles of the east boundary, the east one-half mile on the south boundary of section 35 and one mile on the south boundary of section 32 and portions of the subdivisional lines, designed to restore the corners in their true original location according to the best available evidence; and, the survey of subdivisions in sections 2, 9, 11, 12, 13, 14, 15, 23, 25, 27, 32, 34 and 35 of Township 8 South, Range 31 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated December 14, 1967.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner is monumented with a standard iron post 30 inches long, 2-1/2 inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the Southeast corner of the township is: Latitude 32°41'11" North, and Longitude, 109°06'57.4" West, as taken from the survey plat accepted March 13, 1963, Township 8 South, Range 31 East.

The mean magnetic declination was found to be 13° East.

Dependent Resurvey, Portions of the East Boundary
Township 8 South, Range 31 East

Reestablishment of the Resurvey executed
by Cazier and Murphy in 1961

Beginning at the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp., monumented by an iron post 2-1/2 ins. diam., set 18 ins. in the ground, in a collar of stone, with a wooden post, 4x4 ins. squared, 40 ins. above ground alongside, brass cap mkd.

Dep. Res., Portion East Boundary, T. 8 S., R. 31 E.

CHAINS	
	<p style="text-align: center;">T8S R31E R32E 1/4 S25 S30 1961</p> <p>N. 0°05' W., bet. secs. 25 and 30.</p> <p>Over rolling land, through moderate undergrowth.</p>
6.40	Power line, bears S. 86°39' E. and N. 86°39' W.
18.20	Wash, 25 lks. wide, 10 ft. banks, drains W.
20.05	Point for the N 1/16 sec. cor. of secs. 25 and 30, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T8S R31E R32E N 1/16 S25 S30 1967</p> <p>Raise a mound of stone W. of the cor.</p>
38.40	Whitefield Wash, 150 lks. wide, 15 ft. banks, drains N. 5° E.
40.10	The cor. of secs. 19, 24, 25 and 30, monumented by an iron post 2-1/2 ins. diam., set 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T8S R31E R32E S24 S19 S25 S30 1961</p> <p>Land, rolling. Soil, clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
	<p style="text-align: center;">Reestablishment of the Survey executed by T. F. White in 1882</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.</p> <p>N. 0°02' E., bet. secs. 19 and 24.</p> <p>Over rolling land, through moderate undergrowth.</p>
9.20	Confluence of washes, drains N. 15° E., from SE. and W.
36.50	Telephone line, bears S. 55° E. and N. 55° W.
40.10	The 1/4 sec. cor. of secs. 19 and 24, monumented by a volcanic rock, 17x6x5 ins., loosely set in a mound of stone, no legible markings. This is accepted as the best remaining evidence of the original cor.; not remonumented.

Dep. Res., Portion East Boundary, T. 8 S., R. 31 E.

CHAINS	
	N. 0°14' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
6.30	Fence, bears S. 20° E. and N. 20° W., 200 lks.; thence N.
8.30	Wash, 40 lks. wide, 4 ft. deep, drains N. 80° E.
37.70	Power line, bears S. 30° E. and N. 30° W., 20 lks.; thence N.
40.00	The cor. of secs. 13, 18, 19 and 24, monumented by an iron rod, 1 in. diam., set alongside a fence cor. of fences bearing N. and W., this is accepted as best existing evidence of the original cor. position; not re-monumented.
	from which
	A windmill, bears S. 31°59' E., 7.86 chs. dist.
	Land, rolling.
	Soil, gravelly clay loam.
	Timber, none.
	Undergrowth, creosote bush and bunch grass.
	N. 0°09' W., bet. secs. 13 and 18.
	Over rolling land, through moderate undergrowth.
10.20	Power line, bears S. 65° E. and N. 65° W.
10.70	R/W fence, bears S. 65° E. and N. 65° W., 2½ lks.; thence S. 65° E., S. and N. 65° W.
11.60	Center of U.S. Highway No. 70, bears S. 65° E. and N. 65° W.
12.20	R/W fence, bears S. 65° E. and N. 65° W.
14.50	Enter cultivated field, bears E. and W.
18.00	Telegraph line, bears S. 65° E. and N. 65° W.
18.60	Southern Pacific Railroad on a curve, bears S. 51°18' E. and N. 84°16' W., continue across cultivated field along the E. side of a cement lined ditch.
40.03	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.
55.60	Fence, bears S. 40° E. and N. 40° W.; leave cultivated field.
63.20	Left bank of the Gila River, bears S. 40° E. and W.
65.30	Right bank of the Gila River, bears S. 40° E. and W.
73.90	Enter cultivated land, bears E. and W.
80.06	The cor. of secs. 7, 12, 13 and 18, which is a fence cor. of fences bearing N., E. and W. This position has long been recognized as the cor. by adjacent land owners, and is accepted as the best existing evidence of the position of the original cor.; not monumented.

Dep. Res., Portion East Boundary, T. 8 S., R. 31 E.

CHAINS	
	<p>Land, rolling to nearly level. Soil, gravelly clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
	<p>North, bet. secs. 7 and 12.</p> <p>Over cultivated land.</p>
19.70	Fence, bears E. and W.
20.50	Old paved highway, bears E. and W.
21.20	Telephone line, bears E. and W.
21.30	Concrete irrigation ditch, 15 lks. wide, 2 ft. deep, drains W.
25.70	Power line, bears E. and W., 9 lks. dist.; thence E., S. and W.
32.80	Fence, bears S. 75° E. and N. 75° W.; leave cultivated field.
35.80	State Highway No. 75, bears S. 75° E. and N. 75° W.
36.90	Fence, bears S. 75° E. and N. 75° W.; enter moderate undergrowth.
40.16	The ¼ sec. cor. of secs. 7 and 12, monumented by a granite stone, 12x6x4 ins., showing above the ground mkd. ¼ on W. face; not remonumented.
	<p style="text-align: center;">—————</p> <p>N. 0°03' W., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
20.07	Point for the N 1/16 sec. cor. of secs. 7 and 12, at proportionate dist.; not monumented.
25.70	Wash, 40 lks. wide, 3 ft. deep, drains S. 75° W.
32.50	Enter wash, 50 lks. wide, 6 ft. deep, drains SW., from N,
34.60	Leave wash, drains S., from N. 30° E.
40.14	The cor. of secs. 1, 6, 7 and 12, monumented by an unmkd. sandstone, 10x6x4 ins., set 8 ins. in the ground, mound of stone W.; not remonumented.
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears N. 1 lk. dist., fences bear N., E. and S. 5° W.</p> <p>Land, nearly level. Soil, gravelly clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>

Dep. Res., Portion East Boundary, T. 8 S., R. 31 E.

CHAINS	
40.17	<p>N. 0°03' W., bet. secs. 1 and 6.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Along a N. and S. fence.</p> <p>The ¼ sec. cor. of secs. 1 and 6, monumented by a sandstone, 14x10x4 ins., loosely set, mkd. ¼ on one face.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R31E R32E ¼ S 1 S 6 1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Deposit glass in hole, at base of iron post.</p> <p>The cor. is located under a N. and S. fence.</p>
5.50	<p>N. 0°06' E., beginning new measurement.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
20.00	<p>Waters Wash, 25 lks. wide, 4 ft. deep, drains S. 30° W.</p>
40.07	<p>Small ridge, bears NE. and SW.; desc. N. slope.</p>
40.07	<p>The cor. of Tps. 7 and 8 S., Rs. 31 and 32 E., monumented by an iron post 3 ins. diam., set in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R31E <u>S36 S31</u> R32E S 1 S 6 T8S 1914</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears W., 1 lk. dist., fences bear S. and W.</p> <p>Land, nearly level to gently rolling.</p> <p>Soil, gravelly clay loam.</p> <p>Timber, none.</p> <p>Undergrowth, creosote bush and bunch grass.</p>
	<p style="text-align: center;">Dependent Resurvey, Portions of the South Boundary Township 8 South, Range 31 East</p>
	<p style="text-align: center;">Reestablishment of the Resurvey executed by Cazier and Murphy in 1961</p> <hr/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., set 22 ins. in the ground, brass cap mkd.</p>

Dep. Res., Portion South Boundary, T. 8 S., R. 31 E.

CHAINS		
	<p style="text-align: center;">T8S R31E $\frac{S35}{S 2} \frac{S36}{S 1}$ T9S 1961</p> <p>The cor. is located 13 lks. South of an E. and W. fence. N. 89°59' W., bet. secs. 2 and 35.</p> <p>Over nearly level land, along an E. and W. fence.</p>	
10.30	Fence cor., of fences bearing E., S. and W.	
16.00	Underground pipe line, bears N. 1° E. and S. 1° W.	
20.11	Point for the E 1/16 sec. cor. of secs. 2 and 35, at proportionate dist.	
	<p style="text-align: center;">T8S R31E E 1/16 $\frac{S35}{S 2}$ T9S 1968</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears W., 12½ lks. dist., fences bear E., S. and irregularly W.</p>	
25.40	Underground pipe line, bears S. 40° E. and N. 40° W.	
40.22	The ¼ sec. cor. of secs. 2 and 35, monumented by an iron post 2½ ins. diam., projecting 16 ins. above the ground in a mound of stone, brass cap mkd.	
	<p style="text-align: center;">T8S R31E $\frac{1}{4} \frac{S35}{S 2}$ T9S 1961</p> <p>Land, nearly level. Soil, gravelly clay loam. Timber, none. Undergrowth, bunch grass and shad scale.</p>	
<p>Reestablishment of the Survey executed by G. M. Boofer in 1956</p> <hr style="width: 30%; margin: auto;"/>		
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.</p>	
	<p style="text-align: center;">T8S R31E $\frac{S32}{S 5} \frac{S33}{S 4}$ T9S 1956</p> <p>S. 89°55' W., bet. secs. 5 and 32.</p>	

Dep. Res., Portion South Boundary, T. 8 S., R. 31 E.

CHAINS	
	Over rolling land, through moderate undergrowth.
3.90	Fence, bears N. 50° E. and S. 50° W.
22.80	Spur, slopes N. 35° E.; desc. W. slope.
36.80	Wash, 20 lks. wide, 3 ft. deep, drains N.
39.91	The ¼ sec. cor. of secs. 5 and 32, monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, mound of stone N., brass cap mkd.
	$\frac{1}{4} \frac{S32}{S 5}$ 1956
	<hr style="width: 20%; margin: auto;"/> S. 89°53' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
7.90	Wash, 10 lks. wide, 2 ft. deep, drains N.
23.00	Wash, 20 lks. wide, 2 ft. deep, drains N.
38.10	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
40.30	The cor. of secs. 5, 6, 31 and 32, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.
	$\begin{array}{c} T8S R31E \\ \hline S31 S32 \\ S 6 S 5 \\ T9S \\ 1956 \end{array}$
	The cor. is located on the E. edge of a wash, 30 lks. wide, 1 ft. deep, drains NE.
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cat claw and bunch grass.
Dependent Resurvey, Portions of the Subdivisional Lines Township 8 South, Range 31 East	
Reestablishment of the Survey executed by T. F. White in 1882	
	From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.
	N. 0°21' W., bet. secs. 35 and 36.
	Over rolling land, through moderate undergrowth.
0.13	Fence, bears E. and W.
0.85	Graded road, bears E. and W.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
4.50	Graded road, bears N. 75° E. and S. 75° W.
26.70	Dirt landing strip, bears N. 60° E. and S. 60° W.
38.20	Wash, 10 lks. wide, 3 ft. deep, drains N. 30° E., asc. S. slope.
40.01	The ½ sec. cor. of secs. 35 and 36, monumented by an unmkd. volcanic stone, 12x8x7 ins., loosely set, mound of stone W. This is accepted as best remaining evidence of the original cor.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R31E ½ S35 S36 1967
	Bury the orig. cor. stone alongside the iron post.
	Raise a mound of stone W. of the cor.
	<hr style="width: 20%; margin: auto;"/> N. 1°39' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
22.80	Ridge, bears N. 30° E. and S. 30° W.
34.70	Wash, 10 lks. wide, 3 ft. deep, drains N. 35° E.
40.32	The cor. of secs. 25, 26, 35 and 36, monumented by an iron post 2½ ins. diam., projecting 10 ins. above ground in a collar of stone, brass cap mkd.
	T8S R31E S26 S25 S35 S36 1961
	Land, rolling. Soil, sandy clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.
	From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 8 ins. above ground, in a collar of stone, brass cap mkd.
	T8S R31E R32E S25 S30 S36 S31 1961
	N. 89°53' W., bet. secs. 25 and 36.
	Over rolling land, through moderate undergrowth.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS					
40.87	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.				
43.80	Track road, bears N. 5° E. and S. 5° W.				
53.30	Wash, 40 lks. wide, 6 ft. deep, drains N.				
59.60	Track road, bears S. 10° E. and N. 10° W.				
67.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.				
81.74	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass</p>				
	N. 2°05' E., bet. secs. 25 and 26.				
	Over rolling land, through moderate undergrowth.				
16.50	Wash in Woods Canyon, 80 lks. wide, 2 ft. deep, drains NE.				
19.70	Wash, 40 lks. wide, 4 ft. deep, drains NE.				
34.40	Spur, slopes S. 65° E.				
40.09	Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.				
43.30	Spur, slopes E.				
51.10	Power line, bears S. 86°39' E. and N. 86°39' W.				
80.18	<p>The cor. of secs. 23, 24, 25 and 26, monumented by a volcanic stone, 12x9x6 ins., firmly set in a mound of stone, no legible markings. This is accepted as best remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R31E</p> <table border="1" style="margin: auto;"> <tr> <td>S23</td> <td>S24</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> </table> <p>1968</p> </div> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>	S23	S24	S26	S25
S23	S24				
S26	S25				
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.				

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>N. 89°57' W., bet. secs. 24 and 25.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
22.10	<p>Track road, bears N. and S. 10° E.</p>
39.40	<p>Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; unable to find any remaining evidence of the original cor.</p>
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T8S R31E $\frac{1}{4}$ $\frac{S24}{S25}$ 1968</p>
48.60	<p>Wash, 130 lks. wide, 15 ft. deep, drains N. 10° W.</p>
52.90	<p>Wash in Woods Canyon, 100 lks. wide, 10 ft. deep, drains N. 5° E.</p>
76.40	<p>Wash, 30 lks. wide, 2 ft. deep, drains N.</p>
78.80	<p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
	<p>N. 1°24' W., bet. secs. 23 and 24.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
10.10	<p>Wash, 20 lks. wide, 1 ft. deep, drains N. 60° E.</p>
34.30	<p>Track road, bears N. 30° E. and S. 30° W.</p>
36.10	<p>Underground pipe line, bears N. 10° E. and S. 20° W.</p>
40.33	<p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; unable to find any remaining evidence of the original cor.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T8S R31E $\frac{1}{4}$ $\frac{S23}{S24}$ 1967</p>
	<p>Raise a mound of stone W. of the cor.</p>
58.00	<p>Enter wash, 50 lks. wide, 8 ft. deep, drains N. from SW.</p>
77.20	<p>Telephone line, bears S. 63°10' E. and N. 63°10' W</p>
77.70	<p>Leave same wash, drains N. 30° W.</p>
80.66	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a lava rock, 12x9x8 ins., firmly set, mkd. 3 notches on S. and 1 notch on E. faces; not remonumented.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
<p>0.20 5.30 33.00 40.58</p>	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp. N. 89°39' W., bet. secs. 13 and 24. Over rolling land, through moderate undergrowth. Power line, bears N. and S. Fence, bears S. 10° E. and N. 10° W., 3 lks. dist.; thence E. and S. 10° E. Draw, drains N. The ¼ sec. cor. of secs. 13 and 24, monumented by a quartz rock, 13x8x6 ins., loosely set, no legible markings, mound of stone N. This is accepted as best remaining evidence of the original cor.; not remonumented.</p>
<p>8.60 24.80 35.70 40.07</p>	<p>N. 89°31' W., beginning new measurement. Over rolling land, through moderate undergrowth. Telephone line, bears N. 47° E. and S. 47° W. Wash in Woods Canyon, 50 lks. wide, 12 ft. deep, drains N Underground pipe line, bears N. and S. 15° E. The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
<p>10.00 39.00 39.80</p>	<p>N. 0°17' E., bet. secs. 13 and 14. Over rolling land, through moderate undergrowth. Underground pipe line on a curve, bears S. 40° E. and N. 30° E. Wash, 30 lks. wide, 2 ft. deep, drains W.; track road in bottom of wash, bears E. and W. The ¼ sec. cor. of secs. 13 and 14, monumented by a quartz rock, 15x8x6 ins., set 8 ins. in the ground, mkd. ¼ on W. face. At the corner point Set the iron post 16 ins. in the ground in a collar of stone, brass cap mkd. T8S R31E ¼ S14 S13 1967 Bury the orig. cor. stone alongside the iron post. The cor. is located 2 lks. East of a fence cor.; fences bear N. and W.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	N. 0°10' E., beginning new measurement. Over rolling land, through moderate undergrowth.
16.70	Underground pipe line, bears S. 50° E. and N. 50° W., 1.10 chs. dist., thence N. 10° W.
20.06	Point for the N 1/16 sec. cor. of secs. 13 and 14, at proportionate dist. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd. T8S R31E N 1/16 S14 S13 1968 The cor. falls on a W. slope, approximately 3.60 chs. South of U.S. Highway No. 70.
23.00	R/W fence, bears N. 72° E. and S. 72° W.
23.70	U.S. Highway No. 70, bears N. 72° E. and S. 72° W.
24.60	R/W fence, bears N. 72° E. and S. 72° W.
25.20	Power line, bears N. 72° E. and S. 72° W.
25.80	Telegraph line, bears N. 82°53' E. and N. 57°23' W.
25.90	Southern Pacific Railroad, on a curve, bears N. 82°53' E. and N. 57°23' W.
26.10	Enter corral, bears E. and W.
28.20	Leave corral, bears E. and W.; enter cultivated field.
35.60	Fence, bears N. 80° E. and S. 80° W.; leave cultivated field.
36.80	Left bank of the Gila River, bears N. 65° E. and S. 65° W.
38.20	Right bank of the Gila River, bears N. 65° E. and S. 65° W.
40.12	Point for the cor. of secs. 11, 12, 13 and 14, at pro- portionate dist.; unable to find any remaining evidence of the original cor.; not monumented. Land, rolling to nearly level. Soil, rocky clay to sandy clay loam. Timber, cotton wood along river banks. Undergrowth, creosote bush, cat claw and bunch grass.
	From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp. N. 89°42' W., bet. secs. 12 and 13. Over nearly level land, across cultivated land.
11.50	Graded farm road, bears N. and S.; leave cultivated land.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
11.70	Fence, bears N. and S.; asc. E. slope.
15.00	Spur, slopes S.; desc. W. slope.
16.00	Telephone line, bears S. 85° E. and N. 85° W.
20.00	Fence, bears N. and S.; enter farm yard.
28.00	Leave farm yard, enter cultivated field.
40.09	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.
40.40	Fence, bears N. and S.
41.10	Irrigation canal, bears N. and S.
46.60	Fence, bears N. 22° E. and S. 22° W.
57.70	Fence, bears N. 22° E. and S. 22° W.
60.135	Point for the W 1/16 sec. cor. of secs. 12 and 13, at proportionate dist.; not monumented.
	Leave cultivated field; thence along right bank of the Gila River, bears E. and W.
74.90	Leave right bank of the Gila River, bears E. and S. 65° W.; enter moderate undergrowth.
80.18	The point for the cor. of secs. 11, 12, 13 and 14.
	Land, nearly level. Soil, sandy clay loam. Timber, scattered cotton wood around farm houses. Undergrowth, creosote bush.
	N. 0°10' W., bet. secs. 11 and 12.
	Over nearly level land, through moderate undergrowth.
0.02	Fence, bears E. and W.
0.40	Man made dyke, bears E. and W.
0.80	Irrigation ditch, bears E. and W.; enter cultivated field.
15.80	Fence, bears E. and W.; leave cultivated field, thence over rolling land, through moderate undergrowth.
17.40	Old highway, bears S. 85° E. and N. 36° W.
19.50	Power line, bears S. 89°47' E. and N. 36°32' W.
19.60	Telephone line, bears S. 89°47' E. and N. 36°32' W.
20.06	Point for the S 1/16 sec. cor. of secs. 11 and 12, at proportionate dist.

Dep. Res., Portion Subdivisional Lines, T: 8 S., R. 31 E.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E S 1/16 S11 S12 1968</p> <p>Raise a mound of stone W. of the cor.</p>
23.80	Graded road, bears S. 60° E. and N. 60° W.
37.90	Wash, 30 lks. wide, 3 ft. deep, drains SW.
39.30	Graded road, bears SE. and NW.
40.12	<p>The 1/2 sec. cor. of secs. 11 and 12, monumented by a lava stone, 16x8x5 ins., set 10 ins. in the ground, mkd. 1/2 on W. face.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E 1/2 S11 S12 1968</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°01' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
7.50	Wash, 30 lks. wide, 2 ft. deep, drains S. 25° W.
19.98	Point for the N 1/16 sec. cor. of secs. 11 and 12, at proportionate dist.; not monumented.
25.00	Fence, bears S. 60° E. and N. 60° W.
26.90	State Highway No. 75, bears S. 50°55' E. and N. 50°55' W.
28.70	Fence, bears S. 50°55' E. and N. 50°55' W.
39.96	<p>The cor. of secs. 1, 2, 11 and 12, monumented by a wooden stake, 3 ins. diam., 3 ft. long, set in a mound of stone, stake is weathered, no legible markings. I accept this as best remaining evidence of the original cor.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E S 2 S 1 S11 S12 1968</p> <p>Bury the wooden stake alongside the iron post.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling and nearly level. Soil, rocky clay and sandy loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
9.30	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 89°52' W., bet. secs. 1 and 12.</p> <p>Over rolling land, through moderate undergrowth.</p>
20.08	<p>Wash, 50 lks. wide, 8 ft. deep, drains S.</p> <p>Point for the E 1/16 sec. cor. of secs. 1 and 12, at proportionate dist.</p>
40.16	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E E 1/16 <u>S 1</u> S12 1968</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E 1/4 <u>S 1</u> S12 1968</p>
60.24	<p>Raise a mound of stone N. of the cor.</p> <p>Point for the W 1/16 sec. cor. of secs. 1 and 12, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E W 1/16 <u>S 1</u> S12 1968</p> <p>from which</p> <p style="padding-left: 40px;">A cedar post 4 ins. diam., projecting 3 ft. above the ground, bears South, 12 lks. dist.</p>
80.32	<p>Raise a mound of stone N. of the cor.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, rolling. Soil, rocky and sandy clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>N. 0°03' E., bet. secs. 1 and 2.</p> <p>Over nearly level land, through moderate undergrowth.</p>
11.40	<p>Waters Wash, 70 lks. wide, 3 ft. deep, drains S. 70° W.</p>
40.01	<p>Point for the ¼ sec. cor. of secs. 1 and 2, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.</p>
58.70	<p>Sand Wash, 65 lks. wide, 6 ft. deep, drains S. 35° W.</p>
67.40	<p>Graded road, bears N. 65° E. and S. 65° W.</p>
69.70	<p>Wash, 150 lks. wide, 2 ft. deep, drains S. 65° W.</p>
80.14	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 7 S., R. 31 E., under this same group.</p> <p>Land, nearly level. Soil, rocky clay and sandy loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
<p>Reestablishment of the Survey executed by Cazier and Murphy in 1961</p> <hr/>	
	<p>From the cor. of secs. 25, 26, 35 and 36.</p>
	<p>S. 89°50' W., bet. secs. 26 and 35.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
13.20	<p>Underground pipe line, bears N. 1° E. and S. 1° W.</p>
19.73	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p>T8S R31E E 1/16 $\frac{S26}{S35}$ 1968</p>
	<p>Raise a mound of stone N. of the cor.</p>
39.46	<p>The ¼ sec. cor. of secs. 26 and 35, monumented by an iron post 2½ ins. diam., projecting 16 ins. above the ground in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{1}{4}$ $\frac{S26}{S35}$ 1961</p>
	<p>S. 89°50' W., beginning new measurement.</p>
	<p>Over rolling land, through moderate undergrowth.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
39.43	<p>Through wash area in Woods Canyon, drains irregular E. by triangulation.</p> <p>The cor. of secs. 26, 27, 34 and 35, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E <u>S27 S26</u> <u>S34 S35</u> 1961</p> <p>The cor. is located on N. edge of wash in Woods Canyon.</p> <p>End of triangulation.</p> <p>Land, rolling. Soil, rocky and sandy clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
<p>Reestablishment of the Survey executed by T F. White in 1882</p> <hr/>	
3.70	<p>N. 0°39' E., bet. secs. 26 and 27.</p> <p>Over gently rolling land, through wash area.</p> <p>Leave Woods Canyon, bears irregular E. and W.</p>
40.20	<p>Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E ¼ <u>S27 S26</u> 1968</p> <p>Raise a mound of stone W. of the cor.</p>
55.30	<p>Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.</p>
56.10	<p>Power line, bears S. 86°39' E. and N. 86°39' W.</p>
80.40	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E <u>S22 S23</u> <u>S27 S26</u> 1968</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, none. Undergrowth, cacti and bunch grass.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°59' W., bet. secs. 23 and 26.
	Over gently rolling land, through moderate undergrowth.
11.60	Underground pipe line, bears S. 20° E. and N. 20° W.
16.00	E. rim of mesa, bears N. and S.; desc. W. slope.
20.21	Point for the E 1/16 sec. cor. of secs. 23 and 26, at proportionate dist.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	T8S R31E
	E 1/16 $\frac{S23}{S26}$
	1968
20.90	Wash, 30 lks. wide, 2 ft. deep, drains N.; asc. E. slope.
25.70	W. rim of mesa, bears SE. and NW.; enter nearly level land.
40.42	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.
47.30	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E.
80.84	The cor. of secs. 22, 23, 26 and 27.
	Land, rolling to nearly level.
	Soil, rocky clay loam.
	Timber, none.
	Undergrowth, creosote bush, cacti and bunch grass.
	N. 0°42' W., bet. secs. 22 and 23.
	Over nearly level land, through moderate undergrowth.
19.10	Leave level land; enter rolling land, bears NE. and SW.
34.80	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° E.
39.60	Draw, drains NE.
40.20	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R31E
	¼
	S22 S23
	1968
	Raise a mound of stone W. of the cor.
	The cor. is located on a SE. slope.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
61.90	Old fence line, bears N. 30° E. and S. 30° W.
72.70	Wash, 20 lks. wide, 2 ft. deep, drains N. 85° E.
80.40	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T8S R31E $\frac{S15}{S22} \frac{S14}{S23}$ 1968</p>
	The cor. is located on a S. slope.
	<p>Land, nearly level to rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	From the cor. of secs. 13, 14, 23 and 24.
	S. 89°50' W., bet. secs. 14 and 23.
	Over rolling land, through moderate undergrowth.
0.30	Telephone line, bears N. and S.
0.40	Wash, 30 lks. wide, 6 ft. deep, drains N.
6.40	Telephone line, bears S. 63°10' E. and N. 63°10' W.
16.70	Draw, drains N.
19.96	Point for the E 1/16 sec. cor. of secs. 14 and 23, at proportionate dist.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T8S R31E E 1/16 $\frac{S14}{S23}$ 1968</p>
	Set a wooden post 3 ins. diam., 3 ft. long, alongside the iron post.
39.92	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; unable to find any remaining evidence of the original cor.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T8S R31E $\frac{1}{4} \frac{S14}{S23}$ 1968</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>Set a cedar post 3 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Raise a mound of stone N. of the cor.</p>
47.80	Wash, 40 lks. wide, 2 ft. deep, drains N. 30° W.
74.30	Wash, 20 lks. wide, 2 ft. deep, drains N. 50° E.
79.84	The cor. of secs. 14, 15, 22 and 23.
	<p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>N. 0°01' E., bet. secs. 14 and 15.</p> <p>Over rolling land, through moderate undergrowth.</p>
5.10	Wash, 20 lks. wide, 2 ft. deep, drains E.
16.60	R/W fence, bears N. 55°42' E. and S. 55°42' W.
18.50	Center of U.S. Highway No. 70, bears N. 55°42' E. and S. 55°42' W.
20.10	<p>Point for the S 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E S 1/16 S15 S14 1968</p>
	<p>Raise a mound of stone W. of the cor.</p>
20.20	R/W fence, bears N. 55°42' E. and S. 55°42' W.
37.20	Telephone line, bears S. 63°13' E. and N. 63°13' W.
40.20	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T8S R31E 1/4 S15 S14 1968</p>
43.70	Wash, 20 lks. wide, 2 ft. deep, drains N. 84° E.
45.50	Wash, 30 lks. wide, 2 ft. deep, drains S. 85° E.
60.30	Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E N 1/16 S15 S14 1968</p> <p>Raise a mound of stone W. of the cor.</p>
63.30	Fence, bears N. 23° E. and S. 23° W.
80.40	<p>The cor. of secs. 10, 11, 14 and 15, monumented by a volcanic rock, 12x7x8 ins., showing above the ground, mkd. 4 notches on S. and 2 notches on E. faces, mound of stone W., from which the remains of an original bearing tree:</p> <p style="padding-left: 40px;">A limb on a dead juniper, bears S. 63° E., 335 lks. dist., mkd. TV111SRXXX1E X1V.</p> <p>This cor. is not remonumented.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>From the point for the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89°53' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through moderate undergrowth.</p>
4.00	Approximate dist. to underground pipe line, bears S. 10° E. and N. 10° W.
18.20	Fence, bears E. and W. curving N.
20.04	Point for the E 1/16 sec. cor. of secs. 11 and 14, at proportionate dist.; not monumented.
21.70	Right bank of the Gila River, bears S. 60° E. and N. 60° W.
23.90	Left bank of the Gila River, bears S. 60° E. and N. 60° W.
29.70	Southern Pacific Railroad, bears S. 57°23' E. and N. 57°23' W.
30.00	Telegraph line, bears S. 57°23' E. and N. 57°23' W.
31.20	Wash, 80 lks. wide, 4 ft. deep, drains N. 15° E.
40.08	<p>The ¼ sec. cor. of secs. 11 and 14, monumented by an old weathered post, 3 ft. long, set in a mound of stone; this is accepted as best remaining evidence of the original cor.; not remonumented.</p> <p>from which</p> <p style="padding-left: 40px;">A bench mark, bears N. 28°48' W., 18.29 chs. dist., monumented by a brass tablet 3½ ins. diam., set in a cement block, mkd. AGK BM 1955.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°41' W., beginning new measurement.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	Over nearly level land, through moderate undergrowth.
1.80	Graded road, bears S. 28° E. and N. 28° W.
3.50	Asc. E. slope, over rolling land.
20.50	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° E.
32.60	Fence, bears N. 32° E. and S. 32° W.
36.60	Ridge, bears S. 10° E. and N. 10° W.; desc. W. slope.
40.03	The cor. of secs. 10, 11, 14 and 15.
	Land, nearly level to rolling.
	Soil, sandy clay loam to rocky.
	Timber, none.
	Undergrowth, creosote bush and bunch grass.
	N. 0°07' E., bet. secs. 10 and 11.
	Over rolling land, through moderate undergrowth.
	Ascend S. slope of a volcanic hill.
16.90	Top of hill, bears SE. and NW.; desc. N. slope.
35.30	Graded road at the base of hill, bears S. 85° E. and N. 85° W.; asc. S. slope.
40.00	The ¼ sec. cor. of secs. 10 and 11, monumented by a volcanic rock, 9x8x10 ins., showing above the ground, mkd. ¼ on W. face, mound of stone W.; not remonumented.
	N. 0°32' W., beginning new measurement.
	Over rolling land, through moderate undergrowth.
8.50	Spur, slopes W.; desc. N. slope.
36.50	Telegraph line, bears S. 38°57' E. and N. 38°57' W.
37.90	Southern Pacific Railroad, bears S. 38°57' E. and N. 38°57' W., bottom of desc.; thence over nearly level land.
40.02	Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.
	Land, rolling.
	Soil, rocky to sandy loam.
	Timber, none.
	Undergrowth, creosote bush, cacti and bunch grass.
	From the cor. of secs. 1, 2, 11 and 12.
	N. 89°01' W., bet. secs. 2 and 11.
	Over gently rolling land, through moderate undergrowth.
14.20	Fence, bears S. 50°50' E. and N. 50°50' W.

Dep. Res., Portion Subdivisional Lines T. 8 S., R. 31 E.

CHAINS	
16.60	State Highway No. 75, bears S. 50°50' E. and N. 50°50' W.
18.90	Fence, bears S. 50°50' E. and N. 50°50' W.
19.70	Waters Wash, 110 lks. wide, 8 ft. deep, drains S. 10° W.
20.11	Point for the E 1/16 sec. cor. of secs. 2 and 11, at proportionate dist.; this point falls in an unsafe position, impractical to monument.
20.31	Point selected for the witness E 1/16 sec. cor. of secs. 2 and 11. Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T8S R31E E 1/16 $\xrightarrow{\text{S } 2}$ W S11 C 1968</p>
	Raise a mound of stone N. of the cor.
24.50	Wash, 30 lks. wide, 4 ft. deep, drains S. 10° W.
32.10	Telephone line, bears S. 20°48' E. and N. 20°48' W.
33.50	Old paved highway, bears S. 21° E. and N. 21° W.
34.30	Fence, bears S. 21° E. and N. 21° W.
34.60	Power line, bears S. 20°48' E. and N. 20°48' W.
38.40	Underground pipe line, bears S. 21° E. and N. 21° W.
40.22	The ¼ sec. cor. of secs. 2 and 11, monumented by a granite stone, 6x6x4 ins., showing above the ground, mkd. ¼ on N. face; not remonumented. The cor. is located under a fence bearing E. and W.
	<p style="text-align: center;">_____</p> <p>S. 89°24' W., beginning new measurement.</p>
	Over gently rolling land, through moderate undergrowth.
20.00	Fence, bears N. and S.
27.90	Right bank of the Gila River, bears SE. and NW.
29.60	Left bank of the Gila River, bears SE. and NW.
39.95	The point for the cor. of secs. 2, 3, 10 and 11. Land, gently rolling. Soil, rocky loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
8.00	N. 0°09' E., bet. secs. 2 and 3. Over nearly level land, through moderate undergrowth. Left bank of the Gila River, bears S. 38° E. and N. 38° W.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
9.90	Right bank of the Gila River, bears S. 38° E. and N. 38° W.
12.30	Fence, bears S. 40° E. and N. 40° W.
25.10	Track road, bears SE. and NW.
31.30	Power line, bears S. 60° E. and N. 60° W.
36.30	Sand Wash, 250 lks. wide, 4 ft. deep, drains N. 70° W.
40.02	<p>Point for the ½ sec. cor. of secs. 2 and 3, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.</p> <p>The cor. point is located alongside a fence cor. of fences bearing N. 85° E. and S. 53° E.</p>
49.10	Underground pipe line, bears S. 54° E. and N. 54° W.
51.70	Fence, bears S. 50°50' E. and N. 50°50' W.
54.00	Center of State Highway No. 75, bears S. 50°50' E. and N. 50°50' W.
56.50	Fence, bears S. 50°50' E. and N. 50°50' W.
60.03	Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.; not monumented.
63.90	Little Sand Wash, 100 lks. wide, 4 ft. deep, drains SW.
76.90	Telephone line, bears S. 37°58' E. and N. 37°58' W.
80.04	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. in diam., set, mkd. and witnessed as described in the field notes of the concurrent resurvey of T. 7 S., R. 31 E., under this same group.</p> <p>Land, nearly level. Soil, rocky and sandy clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
12.40	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°45' W., bet. secs. 22 and 27.</p> <p>Over nearly level land, through moderate undergrowth.</p>
40.47	<p>Point for the ½ sec. cor. of secs. 22 and 27, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p>
	<p>T8S R31E ½ $\frac{S22}{S27}$ 1968</p>
	<p>Raise a mound of stone N. of the cor.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
80.94	<p>Continue over nearly level land.</p> <p>The cor. of secs. 21, 22, 27 and 28, monumented by an iron post 2½ ins. in diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{S21}{S28} \frac{S22}{S27}$ 1961</p> <p>Land, level. Soil, rocky clay loam. Timber, none. Undergrowth, shade scale and bunch grass.</p>
24.60 27.50 30.10 40.00 47.30 60.40 80.00	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°31' W., bet. secs. 15 and 22.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>R/W fence, bears N. 55°42' E. and S. 55°42' W.</p> <p>U.S. Highway No. 70, bears N. 55°42' E. and S. 55°42' W.</p> <p>R/W fence, bears N. 55°42' E. and S. 55°42' W.</p> <p>Point for the ¼ sec. cor. of secs. 15 and 22, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{1}{4} \frac{S15}{S22}$ 1968</p> <p>Raise a mound of stone N. of the cor.</p> <p>Fence, bears N. 75° E and S. 74° W.</p> <p>Wash, 25 lks. wide, 2 ft. deep, drains N. 60° E.</p> <p>The cor. of secs. 15, 16, 21 and 22, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{S16}{S21} \frac{S15}{S22}$ 1961</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
	<p>N. 0°05' W., bet. secs. 15 and 16.</p> <p>Over rolling land, through moderate undergrowth.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
39.10	Wash, 100 lks. wide, 3 ft. deep, drains N. 30° E.
40.30	<p>Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{1}{4}$ S16 S15 1968</p> <p>Raise a mound of stone W. of the cor.</p>
50.10	Spur, slopes E.
60.45	<p>Point for the N 1/16 sec. cor. of secs. 15 and 16, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E N 1/16 S16 S15 1968</p> <p>Raise a mound of stone W. of the cor.</p>
66.70	Draw, drains E.
71.50	Telephone line, bears S. 85°06' E. and N. 85°06' W.
78.80	Wash, 50 lks. wide, 3 ft. deep, drains E.
80.60	<p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; unable to find any remaining evidence of the original cor.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T8S R31E S 9 S10 S16 S15 1968</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none; Undergrowth, creosote bush and bunch grass.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°41' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through moderate undergrowth.</p>
9.00	Wash, 20 lks. wide, 2 ft. deep, drains N.
20.03	Point for the E 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.; not monumented.
40.06	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
58.40	Top of ridge, bears SE. and NW.; desc. W. slope.
60.09	Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.; not monumented.
67.50	Wash, 100 lks. wide, 4 ft. deep, drains N.; asc. E. slope.
80.12	The cor. of secs. 9, 10, 15 and 16.
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	N. 0°05' W., bet. secs. 9 and 10.
	Over rolling land, through moderate undergrowth.
40.30	Point for the ¼ sec. cor. of secs. 9 and 10, at proportionate dist.; unable to find any remaining evidence of the original cor.; not monumented.
55.70	Fence, bears N. 85° E. and S. 85° W.
80.60	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, mound of stone W., brass cap mkd.
	<p style="text-align: center;">T8S R31E S 4 S 3 S 9 S 10 1962</p>
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	From the point for the cor. of secs. 2, 3, 10 and 11.
	N. 89°42' W., bet. secs. 3 and 10.
	Over rolling land, through moderate undergrowth.
1.90	Southern Pacific Railroad, bears S. 35°57' E. and N. 35°57' W.
2.80	Telegraph line, bears S. 35°57' E. and N. 35°57' W.
6.00	Spur, slopes N.
8.10	Enter wash area, drains N. 20° E.
15.60	Leave wash area, drains N. 20° E.
19.30	Fence, bears N. 30° E. and S. 30° W.
39.91	The ¼ sec. cor. of secs. 3 and 10, monumented by a lava rock, 10x4x5 ins. showing above the ground, mkd. ¼ on N. face, mound of stone N.; not remonumented.
	The cor. is located 3 lks. NE. of a fence cor., fences bear N. and SE.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>S. 89°53' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
20.90	Wash, 20 lks. wide, 2 ft. deep, drains N. 40° E.
24.10	Graded road, bears S. 40° E. and N. 40° W.
40.08	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>
	<p>S. 89°27' W., bet. secs. 9 and 16.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
15.10	Wash, 35 lks. wide, 3 ft. deep, drains S. 30° E.
32.20	Same wash, 35 lks. wide, 3 ft. deep, drains N. 50° E.
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 16, at proportionate dist.; unable to find any remaining evidence of the orig. cor.</p> <p>Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T8S R31E $\frac{1}{4} \frac{S 9}{S16}$ 1968</p>
44.30	Same wash, 30 lks. wide, 3 ft. deep, drains irregularly E. from N. 10° W.
49.30	Same wash, 30 lks. wide, 3 ft. deep, drains N 30° E.
57.30	Enter same wash area, drains S. 60° E. from irregularly W.
60.06	<p>Point for the W $\frac{1}{16}$ sec. cor. of secs. 9 and 16, at proportionate dist.</p> <p>Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T8S R31E W $\frac{1}{16}$ $\frac{S 9}{S16}$ 1968</p>
	<p>The cor. is located on N. edge of wash.</p>
65.00	Leave wash area, drains irregular E. from NW.
77.30	Draw, drains irregularly NE.
80.08	<p>The cor. of secs. 8, 9, 16 and 17, monumented by an iron post $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p style="text-align: center;">T8S R31E $\frac{S\ 8}{S17} \frac{S\ 9}{S16}$ 1962</p> <p>Land, high rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p style="text-align: center;">Reestablishment of the Survey executed by Cazier and Murphy in 1962</p> <hr/> <p>From the cor. of secs. 8, 9, 16 and 17. N. 0°09' W., along the W. bdy. of sec. 9. Over rolling land, through moderate undergrowth. Desc. N. slope.</p> <p>9.10 Wash, 25 lks. wide, 3 ft. deep, drains S. 60° E.; asc. S. slope.</p> <p>20.23 Point for the S 1/16 sec. cor. of sec. 9, only, at proportionate dist. Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{S\ 1/16}{S\ 9}$ 1968</p> <p>Raise a mound of stone E. of the cor.</p> <p>23.70 Spur, slopes SE.; desc. N. slope.</p> <p>30.30 Draw, drains NE.</p> <p>38.10 Fence, bears E. and W.</p> <p>40.01 The $\frac{1}{4}$ sec. cor. of sec. 8, only, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{1}{4}$ $S\ 8$ 1962</p> <p>40.46 The $\frac{1}{4}$ sec. cor. of sec. 9, only, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{1}{4}$ $S\ 9$ 1962</p> <hr/> <p>N. 0°06' W., beginning new measurement.</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	Over rolling land, through moderate undergrowth.
16.60	Wash, 25 lks. wide, 2 ft. deep, drains E.; asc. S. slope.
20.21	Point for the N 1/16 sec. cor. of sec. 9, only, at proportionate dist. Set the iron post 20 ins. in the ground, brass cap mkd. <div style="text-align: center;"> T8S R31E N 1/16 S 9 1968 </div>
	Raise a mound of stone E. of the cor.
23.60	Draw, drains SE.
33.30	Spur, slopes E.; desc. N. slope.
39.57	The cor. of secs. 5 and 8, only, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd. <div style="text-align: center;"> T8S R31E S 5 S 9 S 8 1962 </div>
	The cor. is located on a steep N. slope.
39.90	Draw, drains irregularly N.
40.42	The cor. of secs. 4 and 9, only, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd. <div style="text-align: center;"> T8S R31E S 5 S 4 S 9 1962 </div>
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	From the cor. of secs. 3, 4, 9 and 10. S. 89°36' W., bet. secs. 4 and 9. Over rolling land, through moderate undergrowth. Topography as recorded in the 1962 survey.
1.90	Wash, 40 lks. wide, 2 ft. deep, drains NE.
33.60	Wash, 80 lks. wide, 2 ft. deep, drains N. for 2 chs., thence NE.
40.02	The ¼ sec. cor. of secs. 4 and 9, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>T8S R31E</p> <p>$\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$</p> <p>1962</p> <hr/> <p>S. 89°33' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>11.00 Begin ascending NE. slope.</p> <p>20.07 Point for the W 1/16 sec. cor. of secs. 4 and 9, at proportionate dist.; not monumented.</p> <p>40.00 Draw, drains irregularly N.</p> <p>40.14 The cor. of secs. 4 and 9.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>East, West and North Boundaries, Section 32</p>
	<p>Reestablishment of the Survey executed by Geo. M. Boofer in 1956</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.</p> <p>N. 0°05' W., bet. secs. 32 and 33.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>1.90 Fence, bears N. 50° E. and S. 50° W.</p> <p>37.00 Wash, 20 lks. wide, 2 ft. deep, drains NW.</p> <p>40.18 The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, monumented by an iron post 2½ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4}$ S32 S33 1956</p> <hr/> <p>N. 0°11' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>39.96 The cor. of secs. 28, 29, 32 and 33, monumented by an iron post 2½ ins. diam., firmly set in the ground, mound of stone W., brass cap mkd.</p> <p style="text-align: center;">T8S R31E S29 S28 S32 S33 1956</p>

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
	<p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp.</p> <p>N. 0°12' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through moderate undergrowth.</p>
0.60	Wash, 30 lks. wide, 1 ft. deep, drains NE.
7.80	Wash, 50 lks. wide, 2 ft. deep, drains NE.
21.00	Wash, 50 lks. wide, 3 ft. deep, drains S. 60° E.
39.86	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 32, monumented by an iron post 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S31 S32 1956 </div>
	<p>N. 0°13' W., beginning new measurement.</p> <p>Over rolling land, through moderate undergrowth.</p>
19.00	Wash, 40 lks. wide, 5 ft. deep, drains S. 70° E.; asc. SW. slope.
40.06	<p>The cor. of secs. 29, 30, 31 and 32, monumented by an iron post 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <div style="text-align: center;"> T8S R31E S30 S29 S31 S32 1956 </div>
	<p>The cor. is located on a SW. slope.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°43' W., bet. secs. 29 and 32.</p> <p>Over mountainous land, through moderate undergrowth.</p>
4.90	Wash, 50 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.
10.60	Draw, drains SE.

Dep. Res., Portion Subdivisional Lines, T. 8 S., R. 31 E.

CHAINS	
39.95	The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by an iron post $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.
	$\frac{1}{4} \frac{S29}{S32}$ 1956
	S. $89^{\circ}45'$ W., beginning new measurement.
	Over mountainous land, through moderate undergrowth.
4.00	Top of mountain, bears SE. and NW.; desc. SW. slope.
16.30	Draw, drains S. 20° E., asc. SE. slope.
30.00	Top of mountain, bears SE. and NW.; desc. SW. slope.
40.32	The cor. of secs. 29, 30, 31 and 32.
	Land, mountainous. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
Subdivision of Sections Township 8 South, Range 31 East	
Subdivision, Section 2	
	From the $\frac{1}{4}$ sec. cor. of secs. 2 and 11.
	N. $0^{\circ}15'$ E., on the N. and S. centerline of sec. 2.
	Over rolling land, through moderate undergrowth.
1.20	Graded road, bears NE. and NW.
3.80	Power line, bears S. 58° E. and N. 58° W.
5.40	Underground pipe line, bears S. 30° E. and N. 30° W.
16.80	Fence, bears S. 55° E. and N. 55° W.
18.80	State Highway No. 75, bears S. 55° E. and N. 55° W.
19.70	Graded road, bears S. 50° E. and N. 50° W.
20.80	Fence, bears S. 55° E. and N. 55° W.
21.10	Telephone line, bears S. 30° E. and N. 40° W.
39.10	Sand Wash, 140 lks. wide, 5 ft. deep, drains S. 70° W.; track road in bottom of wash.
39.45	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 2, at intersection with the E. and W. centerline of sec. 2. This cor. falls in bottom of Sand Wash in an unsafe position, impractical to set.
40.05	Point selected for the witness Center $\frac{1}{4}$ sec. cor. of sec. 2.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> W C T8S R31E C ¼ S 2 ↓ 1968 </p> <p>Set a black willow post 4 ins. diam., 5 ft. long, alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
51.20	Wash, 60 lks. wide, 4 ft. deep, drains S. 30° W., from E.
54.30	Graded road, bears N. 50° E. and S. 50° W.
59.47	Point for the C-N 1/16 sec. cor. of sec. 2.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> C N 1/16 S 2 C 1968 </p> <p>Raise a mound of stone W. of the cor.</p>
71.30	Spur, slopes SW.; desc. N. slope.
79.55	<p>The ¼ sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., set, mkd. and witnessed as described in the concurrent resurvey of T. 7 S., R. 31 E., under this same group.</p> <p>Land, rolling. Soil, gravelly clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>From the point for the ¼ sec. cor. of secs. 1 and 2.</p> <p>N. 89°49' W., on the E. and W. centerline of sec. 2.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
40.00	Sand Wash, 140 lks. wide, 5 ft. deep, drains S. 70° W.
40.07	True point for the Center ¼ sec. cor. of sec. 2, from which its witness cor., bears N. 0°15' E., 60 lks. dist.
51.50	Telephone line, bears S. 38° E. and N. 38° W.
60.08	Point for the C-W 1/16 sec. cor. of sec. 2.
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> W 1/16 C ————— C S 2 1968 </p>

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>from which</p> <p>A water pipe 1½ ins. diam., bears N. 25° W., 2 lks. dist.</p> <p>Raise a mound of stone N. of the cor.</p>
63.30	Fence, bears S. 50° E. and N. 50° W.
65.70	State Highway No. 75, bears S. 50° E. and N. 50° W.
68.00	Fence, bears S. 50° E. and N. 50° W.
68.40	Underground pipe line, bears S. 50° E. and N. 50° W.
80.09	The point for the ¼ sec. cor. of secs. 2 and 3.
	<p>Land, gently rolling. Soil, gravelly clay and sandy loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>Subdivision of the NW¼, Section 2</p> <hr/>
	<p>From the C-W 1/16 sec. cor. of sec. 2.</p> <p>N. 0°14' E., on the N. and S. centerline of the NW¼ of sec. 2.</p> <p>Over rolling land, through moderate undergrowth.</p>
11.20	Telephone line, bears S. 38° E. and N. 38° W.
20.03	Point for the NW 1/16 sec. cor. of sec. 2 at intersection with the E. and W. centerline of the NW¼ sec. 2.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>NW 1/16 S 2 1968</p>
	<p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located on a SE. slope.</p>
20.90	Spur, slopes SW. from the E.; desc. N. slope.
40.05	The point for the W 1/16 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., previously described in the field notes of the concurrent resurvey of T. 7 S., R. 31 E., under this same group.
	<p>From the C-N 1/16 sec. cor. of sec. 2.</p> <p>N. 89°49' W., on the E. and W. centerline of the NW¼ of sec. 2.</p> <p>Over rolling land, through moderate undergrowth.</p>
17.00	Spur, slopes S.
20.05	The NW 1/16 sec. cor. of sec. 2.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
21.00	Spur, slopes SW.
26.70	Telephone line, bears S. 38° E. and N. 38° W.
40.10	The point for the N 1/16 sec. cor. of secs. 2 and 3.
<p>Subdivision, Section 9</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°04' W., on the N. and S. centerline of sec. 9.</p>	
20.20	Point for the C-S 1/16 sec. cor. of sec. 9; not monumented.
40.40	Point for the Center 1/4 sec. cor. of sec. 9, at intersection with the E. and W. centerline of sec. 9; not monumented.
42.60	Enter wash, 20 lks. wide, 2 ft. deep, drains irregularly N.
46.60	Fence, bears N. 72° E. and S. 72° W.
49.00	Leave same wash, drains N. 30° E. from S.
60.59	Point for the C-N 1/16 sec. cor. of sec. 9; not monumented.
70.40	Wash, 100 lks. wide, 4 ft. deep, drains N. 60° E.
80.78	The 1/4 sec. cor. of secs. 4 and 9.
	<p>Land, rolling. Soil, rocky loam. Timber, none. Undergrowth, creosote bush, cacti and bunchgrass.</p>
	<p>From the point for the 1/4 sec. cor. of secs. 9 and 10.</p> <p>S. 89°31' W., on the E. and W. centerline of sec. 9.</p> <p>Over rolling land, through moderate undergrowth.</p>
18.60	Draw, drains NE.
40.01	The point for the Center 1/4 sec. cor. of sec. 9.
42.30	Wash, 15 lks. wide, 2 ft. deep, drains N. 30° E.
60.065	Point for the C-W 1/16 sec. cor. of sec. 9.
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">W 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S 9</p> <p style="text-align: center;">1968</p>
	Raise a mound of stone N. of the cor.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
61.00	Draw, drains N. 20° E.
69.20	Fence, bears N. 70° E. and S. 70° W.
80.12	The ¼ sec. cor. of sec. 9.
	Land, rolling. Soil, rocky loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
Subdivision of the SW¼, Section 9	
	From the W 1/16 sec. cor. of secs. 9 and 16.
	N. 0°09' W., on the N. and S. centerline of the SW¼ of sec. 9.
	Over rolling land, through moderate undergrowth.
20.23	Point for the SW 1/16 sec. cor. of sec. 9, at the intersection with the E. and W. centerline of the SW¼ of sec. 9.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	SW 1/16 S 9 1968
	Raise a mound of stone W. of the cor.
40.46	The C-W 1/16 sec. cor. of sec. 9.
	From the point for the C-S 1/16 sec. cor. of sec. 9.
	S. 89°28' W., on the E. and W. centerline of the SW¼ of sec. 9.
	Over rolling land, through moderate undergrowth.
16.00	Begin asc. E. slope.
20.06	The SW 1/16 sec. cor. of sec. 9.
38.00	Spur, slopes SE., desc. W. slope.
40.11	The S 1/16 sec. cor. of sec. 9.
Subdivision of the NW¼, Section 9	
	From the C-W 1/16 sec. cor. of sec. 9.
	N. 0°09' W., on the N. and S. centerline of the NW¼ of sec. 9.
1.40	Draw, drains N. 20° E.
1.90	Fence, bears E. and W.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
9.50	Draw, drains N. 10° E.
20.18	Point for the NW 1/16 sec. cor. of sec. 9, at intersection with the E. and W. centerline of the NW¼ of sec. 9. Set the iron post 22 ins. in the ground, brass cap mkd. NW 1/16 S 9 1968 Raise a mound of stone W. of the cor.
22.00	Wash, 30 lks. wide, 3 ft. deep, drains N. 70° E.
33.40	Spur, slopes E.
40.35	The point for the W 1/16 sec. cor. of secs. 4 and 9.
	From the point for the C-N 1/16 sec. cor. of sec. 9. S. 89°33' W., on the E. and W. centerline of the NW¼ of sec. 9. Over rolling land, through moderate undergrowth.
16.00	Draw, drains N. 20° E.
18.90	Spur, slopes S.
20.055	The NW 1/16 sec. cor. of sec. 9.
23.30	Wash, 30 lks. wide, 3 ft. deep, drains irregularly E.
25.60	Wash, drains SE.
27.70	Same wash; drains N. 30° E.
39.20	Wash, 10 lks. wide, 5 ft. deep, drains S.
40.11	The N 1/16 sec. cor. of sec. 9.
	Subdivision, Section 11
	From the ¼ sec. cor. of secs. 11 and 14. N. 0°09' W., on the N. and S. centerline of sec. 11. Over nearly level land, through moderate undergrowth.
5.70	Fence, bears S. 50° E. and N. 50° W.
6.70	Telegraph line, bears S. 49°44' E. and N. 49°44' W.
7.70	Southern Pacific Railroad, bears S. 49°44' E. and N. 49°44' W.
20.05	Point for the C-S 1/16 sec. cor. of sec. 11; not monumented.
36.10	Left bank of the Gila River, bears SE. and NW.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
37.50	Right bank of the Gila River, bears SE. and NW.
40.10	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 11, at intersection with the E. and W centerline of sec. 11; not monumented.
42.60	Fence, bears S 75° E. and N. 75° W.; enter cultivated land.
58.60	Leave cultivated land, bears S. 65° E. and N. 65° W.
61.90	Waters Wash, 40 lks. wide, 4 ft. deep, drains S. 60° W.
62.30	Fence, bears N. 60° E. and S. 60° W.
68.20	Track road, bears N. 40° E. and S. 40° W.
74.90	Track road, bears E. and W.
80.62	The $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Land, rolling. Soil, gravelly and sandy loam. Timber, none. Undergrowth, creosote bush, sage and bunch grass.
	From the $\frac{1}{4}$ sec. cor. of secs. 11 and 12.
	N. 89°53' W., on the E. and W. centerline of sec. 11.
	Over rolling land, through moderate undergrowth.
0.80	Graded road, bears SE. and NW.
5.00	Wash, 30 lks. wide, 2 ft. deep, drains S. 25° W.
15.40	Telephone line, bears S. 40° E. and N. 40° W.
16.20	Power line, bears S. 30° E. and N. 30° W.
20.06	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 11.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	E $\frac{1}{16}$
	C ————— C
	S11
	1968
	Raise a mound of stone N. of the cor.
23.80	Old paved highway, bears S. 20° E. and N. 20° W.
24.60	Fence, bears S. 20° E. and N. 20° W.
24.90	Underground pipe line, bears S. 30° E. and N. 30° W.
29.30	Irrigation ditch, bears N. and S., enter cultivated land.
37.50	Leave cultivated land, bears SE. and NW.
37.90	Fence, bears S. 40° E. and N. 40° W.


Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
40.12	The point for the Center $\frac{1}{4}$ sec. cor. of sec. 11.
43.00	Right bank of the Gila River, bears SE. and NW.
45.20	Left bank of the Gila River, bears SE. and NW.
58.70	Southern Pacific Railroad, bears S. 30° E. and N. 30° W.
59.70	Telegraph line, bears S. 30° E. and N. 30° W.
70.00	Ridge, bears N. and S.
79.89	The $\frac{1}{4}$ sec. cor. of secs. 10 and 11.
	Land, rolling. Soil, gravelly and sandy loam. Timber, none. Undergrowth, creosote bush and bunch grass.
<p>Subdivision of the SE$\frac{1}{4}$, Section 11</p> <hr/>	
	From the point for the E 1/16 sec. cor. of secs. 11 and 14. N. 0°11' W., on the N. and S. centerline of the SE $\frac{1}{4}$ of sec. 11.
	Over nearly level land, through moderate undergrowth.
6.20	Fence, bears S. 60° E. and N. 60° W.; enter cultivated land.
18.00	Fence, bears S. 65° E. and N. 65° W.; leave cultivated land, thence over rolling land.
20.065	Point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 11.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	SE 1/16 S11 1968
	Raise a mound of stone W. of the cor.
20.20	Power line, bears N. 54° E. and S. 54° W.
26.30	Wash, 30 lks. wide, 4 ft. deep, drains SW.
27.90	Underground pipe line, bears S. 42° E. and N. 42° W.
28.70	Fence, bears SE. and N. 35° W.
31.10	Old paved highway, on a curve, bears SE. and N. 35° W.
40.13	The C-E 1/16 sec. cor. of sec. 11.
	From the S 1/16 sec. cor. of secs. 11 and 12. N. 89°54' W., on the E. and W. centerline of the SE $\frac{1}{4}$ of sec. 11.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	Over nearly level land.
0.40	Telephone line, bears S. 40° E. and N. 40° W.
5.30	Power line, bears S. 30° E. and N. 30° W.
9.60	Old paved highway, bears S. 80° E. and N. 50° W.
11.10	Fence, bears E. and NW.
11.90	Underground pipe line, bears S. 60° E. and N. 60° W.
14.10	Fence, bears N. 30° E. and S. 30° W.
16.10	NW. cor. of large brick house, bears S. 50 lks. dist.
18.40	Track road, bears N. and S.
20.055	The SE 1/16 sec. cor. of sec. 11.
20.50	Power line, bears N. 54° E. and S. 54° W.
27.50	Wash, 30 lks. wide, 4 ft. deep, drains SW.
34.50	Right bank of the Gila River, bears N. and S.
36.30	Left bank of the Gila River, bears N. and S.
40.11	The point for the C-S 1/16 sec. cor. of sec. 11.
Subdivision, Section 12	
From the point for the ¼ sec. cor. of secs. 12 and 13. N. 0°04' W., on the N. and S. centerline of section 12.	
Over cultivated land, along a canal dyke, bearing N. and S.	
3.90	Irrigation canal, bears NW., curving S.; leave cultivated land, enter dense undergrowth.
11.00	Fence, bears N. 30° E. and S. 30° W.
11.80	Old paved highway, on a curve, bears NE. and N. 80° W.; leave dense undergrowth; enter rolling land.
18.80	Power line, bears E. and W.
19.90	Telephone line, bears S. 89°47' E. and N. 89°47' W.
40.15	Point for the Center ¼ sec. cor. of sec. 12, at intersection with the E. and W. centerline of sec. 12; not monumented.
43.20	Old bladed road, bears NE. and SW.
45.50	Fence, bears S. 75° E. and N. 75° W.
47.10	State Highway No. 75, bears S. 75° E. and N. 75° W.
48.70	Fence, bears S. 75° E. and N. 75° W.
60.17	Point for the C-N 1/16 sec. cor. of sec. 12.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
80.19	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;">  </div> <p>Raise a mound of stone W. of the cor. The cor. is located on an E. slope. The 1/4 sec. cor. of secs. 1 and 12. Land, level to rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
<p>8.50 11.00 16.50 20.07 21.90 25.00 40.15 44.40 60.25 74.30 75.30 80.35</p>	<p>From the 1/4 sec. cor. of secs. 7 and 12 on the E. bdy. of the Tp. N. 89°42' W., on the E. and W. centerline of sec. 12. Over nearly level land, through moderate undergrowth. Wash, 40 lks. wide, 10 ft. deep, drains N. 80° W. Fence, bears S. 75° E and N. 75° W. State Highway No. 75, bears S. 75° E. and N. 75° W. Point for the C-E 1/16 sec. cor. of sec. 12; not monumented. Fence, bears S. 75° E. and N. 75° W. Wash, 50 lks. wide, 12 ft. deep, drains S. The point for the Center 1/4 sec. cor. of sec. 12. Old bladed road, bears NE. and SW. Point for the C-W 1/16 sec. cor. of sec. 12; not monumented. Wash, 30 lks. wide, 4 ft. deep, drains SW. Graded road, bears N. 10° E. and S. 10° W. The 1/4 sec. cor. of secs. 11 and 12. Land, nearly level to rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
	<p style="text-align: center;">Subdivision of the NE 1/4, Section 12</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the C-E 1/16 sec. cor. of sec. 12.</p>

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>N. 0°02' W., on the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 12.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
1.00	<p>State Highway No. 75, bears S. 75° E. and N. 75° W.</p>
2.70	<p>Fence, bears S. 75° E. and N. 75° W.</p>
4.70	<p>Wash, 100 lks. wide, 15 ft. deep, drains S. 80° W.</p>
20.045	<p>Point for the NE 1/16 sec. cor. of sec. 12, at intersection with the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 12.</p>
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">NE 1/16 S12 1968</p>
	<p>Raise a mound of stone W. of the cor.</p>
40.09	<p>The E 1/16 sec. cor. of secs. 1 and 12.</p>
	<p>From the point for the N 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p>
	<p>N. 89°46' W., on the E. and W. centerline of the NE$\frac{1}{4}$ of sec. 12.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
6.30	<p>Fence, bears N. 20° E. and S. 20° W.</p>
8.50	<p>Wash, 40 lks. wide, 4 ft. deep, drains S. 30° W.</p>
20.07	<p>The NE 1/16 sec. cor. of sec. 12.</p>
27.90	<p>Wash, 30 lks. wide, 5 ft. deep, drains S. 30° W.</p>
29.20	<p>Wash, 40 lks. wide, 6 ft. deep, drains S. 20° W.</p>
40.16	<p>The C-N 1/16 sec. cor. of sec. 12.</p>
	<p style="text-align: center;">Subdivision of the NW$\frac{1}{4}$, Section 12</p>
	<p>From the point for the C-W 1/16 sec. cor. of sec. 12.</p>
	<p>N. 0°03' W., on the N. and S. centerline of the NW$\frac{1}{4}$ of sec. 12.</p>
	<p>Over rolling land, through moderate undergrowth.</p>
1.00	<p>Fence, bears irregularly NE. and SW.</p>
10.40	<p>Wash, 30 lks. wide, 3 ft. deep, drains SW.</p>
12.60	<p>Fence, bears S. 75° E. and N. 75° W.</p>
14.20	<p>State Highway No. 75, bears S. 75° E. and N. 75° W.</p>

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
15.90	Fence, bears S. 75° E. and N. 75° W.
19.97	Point for the NW 1/16 sec. cor. of sec. 12, at intersection with the E. and W. centerline of the NW¼ of sec. 12.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	NW 1/16 S12 1968
	Raise a mound of stone W. of the cor.
39.95	The W 1/16 sec. cor. of secs. 1 and 12.
	From the C-N 1/16 sec. cor. of sec. 12.
	N. 89°48' W., on the E. and W. centerline of the NW¼ of sec. 12.
	Over rolling land, through moderate undergrowth.
13.70	Wash, 20 lks. wide, 3 ft. deep, drains S.
20.10	The NW 1/16 sec. cor. of sec. 12.
27.00	Fence, bears S. 50°50' E. and N. 50°50' W.
29.90	State Highway No. 75, bears S. 50°50' E. and N. 50°50' W.
32.90	Fence, bears S. 50°50' E. and N. 50°50' W.
40.20	The point for the N 1/16 sec. cor. of secs. 11 and 12.
	Subdivision, Section 13
	From the ¼ sec. cor. of secs. 13 and 24.
	N. 0°11' E., on the N. and S. centerline of section 13.
	Over gently rolling land, through moderate undergrowth.
2.50	Fence, bears N. 10° E. and S. 10° W.
13.90	Telephone line, bears N. 47° E. and S. 47° W.
24.80	Enter wash area, drains N.
37.90	Leave wash area, drains NW.
40.00	Point for the Center ¼ sec. cor. of sec. 13, at intersection with the E. and W. centerline of sec. 13; not monumented.
40.70	R/W fence, bears S. 30° E. and N. 30° W.
42.20	U.S. Highway No. 70, bears S. 30° E. and N. 30° W.
43.60	R/W fence, bears S. 30° E. and N. 30° W.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
43.90	Power line, bears S. 30° E. and N. 30° W.
45.90	Telegraph line, bears S. 32°43' E. and N. 32°43' W.
46.10	Southern Pacific Railroad, bears S. 32°43' E. and N. 32°43' W.
48.00	Wash in Woods Canyon, 100 lks. wide, 3 ft. deep, drains N. 10° E.
51.10	Fence, bears N. 30° E. and S. 30° W.
58.20	Left bank of the Gila River, bears N. 30° E. and S. 30° W.
59.60	Right bank of the Gila River, bears N. 30° E. and S. 30° W.
60.025	Point for the C-N 1/16 sec. cor. of sec. 13; not monumented.
61.30	Fence, bears S. 50° E. and N. 60° W.
62.00	Enter cultivated field, bears E. and W.
68.10	Fence, bears E. and W.
68.30	Irrigation ditch, bears E. and W.
80.05	The point for the 1/4 sec. cor. of secs. 12 and 13.
	Land, nearly level. Soil, sandy clay loam. Timber, cottonwood around river banks. Undergrowth, sage and grass.
	From the point for the 1/4 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	N. 89°44' W., on the E. and W. centerline of section 13.
	Over nearly level land, through moderate undergrowth.
0.20	Concrete ditch, bears S. and N., 12 lks. to end.
4.20	Fence, bears S. 54° E. and N. 54° W.
35.10	Fence, bears S. 32° E. and N. 32° W.
35.90	Southern Pacific Railroad, bears S. 32°43' E. and N. 32°43' W.
36.30	Telegraph line, bears S. 32°43' E. and N. 32°43' W.
37.40	Power line, bears S. 30° E. and N. 30° W.
38.50	U.S. Highway No. 70, bears S. 30° E. and N. 30° W.
39.40	R/W fence, bears S. 30° E. and N. 30° W.
40.33	The point for the Center 1/4 sec. cor. of sec. 13.


Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
41.60	Wash, 40 lks. wide, 4 ft. deep, drains NW.
44.40	Wash in Woods Canyon, 50 lks. wide, 4 ft. deep, drains N.
59.60	Fence, bears S. 20° E. and N. 20° W.
60.36	Point for the C-W 1/16 sec. cor. of sec. 13.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	W 1/16
	C ————— C
	S13
	1968
	Raise a mound of stone N. of the cor.
69.00	Underground pipe line, bears N. 10° E. and S. 10° W.
72.00	Track road, bears NE. and SW., curving to W.
80.39	The ¼ sec. cor. of secs. 13 and 14.
	Land, nearly level.
	Soil, sandy clay loam.
	Timber, none.
	Undergrowth, creosote bush and bunch grass.
Subdivision of the NW¼, Section 13	
From the C-W 1/16 sec. cor. of sec. 13.	
N. 0°11' E., on the N. and S. centerline of the NW¼ of sec. 13.	
Over nearly level land, through moderate undergrowth.	
0.20	Fence, bears S. 20° E. and N. 20° W.
7.20	Track road, bears N. 60° E. and S. 60° W.
20.04	Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E and W. centerline of the NW¼ of sec. 13.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	NW 1/16
	S13
	1968
	Raise a mound of stone W. of the cor.
20.80	Fence, bears SE. and NW.
23.30	R/W fence, bears S. 70° E. and S. 70° W.
24.10	U.S. Highway No. 70, bears S. 70° E. and S. 70° W.
24.20	Power line, bears SE. and NW.
24.90	R/W fence, bears S. 70° E. and S. 70° W.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
26.80	Telegraph line, bears S. 60° E. and S. 82°53' W.
27.10	Southern Pacific Railroad on a curve, bears S. 60° E. and S. 82°58' W.
37.60	Left bank of the Gila River, bears SE. and W.
39.20	Right bank of the Gila River, bears SE. and W.
40.07	The point for the W 1/16 sec. cor. of secs. 12 and 13.
<p>From the point for the C-N 1/16 sec. cor. of sec. 13.</p>	
<p>N. 89°43' W., on the E. and W. centerline of the NW¼ of sec. 13.</p>	
<p>Over nearly level land.</p>	
1.30	Right bank of the Gila River, bears S. 70° E. and N. 70° W.
6.90	Left bank of the Gila River, bears E. and N. 50° W.
9.20	Southern Pacific Railroad, bears S. 45° E. and N. 60° W.
10.10	Telegraph line, bears S. 45° E. and N. 60° W.
11.80	R/W fence, bears S. 45° E. and N. 60° W.
13.00	U.S. Highway No. 70, bears S. 45° E. and N. 60° W.
14.30	R/W fence, bears S. 45° E. and N. 60° W.
15.90	Power line, bears SE. and NW.
19.20	Fence, bears SE. and NW.
20.04	The NW 1/16 sec. cor. of sec. 13.
37.90	Draw, drains NW.
40.08	The N 1/16 sec. cor. of secs. 13 and 14.
<p>Subdivision, Section 14</p> <hr style="width: 20%; margin: auto;"/>	
<p>From the ¼ sec. cor. of secs. 14 and 23.</p>	
<p>N. 0°07' E, on the N. and S. centerline of sec. 14.</p>	
<p>Over rolling land, through moderate undergrowth.</p>	
14.80	Wash, 100 lks. wide, 2 ft. deep, drains N., 300 lks. dist., thence NW.
16.80	Telephone line, bears S. 63°13' E. and N. 63°13' W.
22.00	Wash, 100 lks. wide, 2 ft. deep, drains NW., 200 lks. dist., thence N.
28.10	Wash, 200 lks. wide, 2 ft. deep, drains N., 100 lks. dist., thence NE.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
40.03	<p>Point for the Center $\frac{1}{4}$ sec. cor. of sec. 14, at intersection with the E. and W. centerline of sec. 14.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8S R31E C+$\frac{1}{4}$ S14 1968</p> <p>Set a mesquite post 3$\frac{1}{2}$ ins. diam., 4 ft. long, alongside the iron post.</p>
42.30	<p>Wash, 30 lks. wide, 1 ft. deep, drains E.</p>
43.60	<p>R/W fence, bears N. 55°42' E. and S. 55°42' W.</p>
45.50	<p>U.S Highway No. 70, bears N. 55°42' E. and S. 55°42' W.</p>
51.60	<p>Access road to highway yard, bears N. 25°56' E. and S. 25°56' W.; enter rest area.</p>
55.10	<p>Leave rest area.</p>
56.70	<p>Fence, bears NE. and SW.</p>
57.00	<p>Fence, bears S 80° E. and N. 80° W.; enter highway maintenance yard.</p>
58.80	<p>Leave highway maintenance yard.</p>
60.06	<p>Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 14.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;">  <p style="margin-left: 100px;">C N 1/16 S14 C 1968</p> </div> <p>from which</p> <p style="margin-left: 40px;">SE. cor. of a frame building in highway dept. yard, bears N. 89°19' E., 390 lks. dist.</p> <p style="margin-left: 40px;">NW. cor. of a frame building in highway dept. yard, bears S. 88°11' E., 180 lks. dist.</p>
75.30	<p>Wash, 100 lks. wide, 2 ft. deep, drains NE.</p>
77.50	<p>Graded road, bears irregularly E and NW.</p>
80.09	<p>The $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>From the $\frac{1}{2}$ sec. cor. of secs. 13 and 14.</p> <p>N. $89^{\circ}53'$ W., on the E. and W. centerline of sec. 14.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Along an E. and W. fence line.</p>
10.00	Fence cor., bears North, 18 lks. dist.; fences bear N and E.
11.00	Track road, bears NW. and SE. curving E.
14.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
20.03	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 14.
	<p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">E $\frac{1}{16}$</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S14 1968</p>
	The cor. is located on a NE. slope.
22.60	Ridge, bears N. and S.
30.40	Wash, 150 lks. wide, 3 ft. deep, drains NW.
35.40	Ridge, bears N. and S.
40.06	The Center $\frac{1}{2}$ sec. cor. of sec. 14.
45.50	R/W fence, bears N. $55^{\circ}42'$ E. and S. $55^{\circ}42'$ W.
48.10	U.S. Highway No. 70, bears N. $55^{\circ}42'$ E. and S. $55^{\circ}42'$ W.
49.80	Access road to highway yard, bears N. 40° E. and S. 40° W.
50.80	R/W fence, bears N. $55^{\circ}42'$ E. and S. $44^{\circ}42'$ W.
63.10	Wash, 10 lks. wide, 3 ft. deep, drains irregularly N., 300 lks. dist., thence NE.
80.03	<p>The $\frac{1}{2}$ sec. cor. of secs. 14 and 15.</p> <p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>Subdivision of the NE$\frac{1}{4}$, Section 14</p> <hr/> <p>From the C-E $\frac{1}{16}$ sec. cor. of sec. 14.</p> <p>N. $0^{\circ}08'$ E., on the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 14.</p> <p>Over rolling land, through moderate undergrowth.</p>

Subdivision of Sections, T 8 S., R. 31 E.

CHAINS	
0.60	Wash, 5 lks. wide, 1 ft. deep, drains E.
12.00	Track road, bears NW. and SE.
14.20	Wash, 200 lks. wide, 3 ft. deep, drains irregularly E.
16.20	R/W fence, bears N. 62°31' E. and S. 62°31' W.
17.00	U.S. Highway No. 70, bears N. 62°31' E. and S. 62°31' W.
17.90	R/W fence, bears N. 62°31' E. and S. 62°31' W.
20.05	Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. centerline of the NE½ of sec. 14. Set the iron post 22 ins. in the ground, brass cap mkd. NE 1/16 S14 1968 Raise a mound of stone W. of the cor.
20.20	Track road, bears N. 80° E. and S. 80° W.
20.25	Power line, bears N 80° E. and S 80° W.
21.10	Telephone line, bears N. 80° E. and S. 80° W.
24.00	Track road, bears SE. and NW.
26.00	Graded road, bears S. 60° E. and N. 60° W.
28.00	Telephone line, bears S. 10° E. and N. 10° W.
30.60	Track road, bears S. 30° E. and N. 30° W.
33.00	Telegraph line, bears S. 57°23' E. and N. 57°23' W.
33.50	Southern Pacific Railroad, bears S. 57°23' E. and N. 57°23' W.
36.80	Left bank of the Gila River, bears S. 60° E. and N. 60° W.
39.00	Right bank of the Gila River, bears S. 60° E. and N. 60° W.
40.10	The point for the E 1/16 sec. cor. of secs. 11 and 14.
	From the N 1/16 sec. cor. of secs. 13 and 14.
	N. 89°54' W., on the E. and W. centerline of the NE½ of sec. 14.
	Over rolling land, through moderate undergrowth.
0.50	Power line, bears N. and S.
1.20	Underground pipe line, bears S. 10° E. and N. 10° W.
2.00	Wash, 50 lks. wide, 1 ft. deep, drains N.
8.40	R/W fence, bears N. 73° E. and S. 73° W.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
11.20	U. S. Highway No. 70, bears N. 73° E. and S. 73° W.
12.90	Wash, 200 lks. wide, 3 ft. deep, drains N.
14.20	R/W fence, bears N. 73° E. and S. 73° W.
17.10	Graded road, bears S. 30° E. and N. 30° W.
20.03	The NE 1/16 sec. cor. of sec. 14.
20.50	Track road, bears N. 80° E. and S. 80° W.
27.00	Track road, bears NW. and SE., 200 lks. dist.; thence N. 80° E.
30.30	Telephone line, bears N. 50° E. and S. 50° W.
30.50	Track road, bears N. and S.
31.20	Wash, 10 lks. wide, 2 ft. deep, drains N.; power line, bears NE. and SW.
31.60	Fence, bears E. and W.; enter highway maintenance yard.
34.00	Track road, bears NE. and SW.
39.60	Fence, bears N. and S.; leave highway maintenance yard.
40.05	The C-N 1/16 sec. cor. of sec. 14.
<p>Subdivision, Section 15</p> <hr/> <p>From the ¼ sec. cor. of secs. 15 and 22.</p> <p>N. 0°04' W., on the N. and S. centerline of sec. 15.</p> <p>Over gently rolling land, through moderate undergrowth.</p> <p>1.40 Fence, bears N. 80° E. and S. 80° W.</p> <p>20.13 Point for the C-S 1/16 sec. cor. of sec. 15.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p style="margin: 0;">C</p> <p style="margin: 0;">S 1/16 S15</p> <p style="margin: 0;">C</p> <p style="margin: 0;">1968</p> </div> <p>Raise a mound of stone W. of the cor.</p> <p>40.00 Wash, 25 lks. wide, 2 ft. deep, drains N. 75° E.</p> <p>40.26 Point for the Center ¼ sec. cor. of sec. 15, at intersection with the E. and W. centerline of sec. 15.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E C ¼+S15 1968</p>	

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
57.30	Telephone line, bears S. 63°10' E. and N. 63°10' W.
60.38	Point for the C-N 1/16 sec. cor. of sec. 15, not monumented.
80.50	The point for the ¼ sec. cor. of secs. 10 and 15.
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	From the ¼ sec. cor. of secs. 14 and 15.
	S. 89°36' W., on the E. and W. centerline of sec. 15.
	Over gently rolling land, through moderate undergrowth.
1.30	Wash, 20 lks. wide, 2 ft. deep, drains NE., from NW.
6.00	Telephone line, bears S. 63°10' E. and N. 63°10' W.
8.50	Fence, bears N. 24° E. and S. 24° W.
9.20	Wash, 20 lks. wide, 2 ft. deep, drains NE.
20.02	Point for the C-E 1/16 sec. cor. of sec. 15.
	Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.
	E 1/16
	C ————— C S15 1968
39.80	Wash, 25 lks. wide, 2 ft. deep, drains N. 75° E.
40.04	The Center ¼ sec. cor. of sec. 15.
60.06	Point for the C-W 1/16 sec. cor. of sec. 15.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	W 1/16
	C ————— C S15 1968
	Raise a mound of stone N. of the cor.
79.30	Wash, 60 lks. wide, 3 ft. deep, drains N. 30° E.
80.08	The ¼ sec. cor. of secs. 15 and 16.
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	Subdivision of the NE¼, Section 15 _____

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	From the C-E 1/16 sec. cor. of sec. 15.
	North, on the N. and S. centerline of the NE $\frac{1}{4}$ of sec. 15.
	Over gently rolling land, through moderate undergrowth.
6.60	Wash, 30 lks. wide, 4 ft. deep, drains E., 100 lks., thence NE.
7.30	Telephone line, bears S. 63°10' E. and N. 63°10' W.
20.11	Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E. and W. centerline of the NE $\frac{1}{4}$ of sec. 15.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	NE 1/16 S 15 1968
	Raise a mound of stone W. of the cor.
40.22	The point for the E 1/16 sec. cor. of secs. 10 and 15.
	From the N 1/16 sec. cor. of secs. 14 and 15.
	S. 89°37' W., on the E. and W. centerline of the NE $\frac{1}{4}$ of sec. 15.
	Over gently rolling land, through moderate undergrowth.
1.10	Fence, bears N. 20° E. and S. 20° W.
20.02	The NE 1/16 sec. cor. of sec. 15.
40.05	Point for the C-N 1/16 sec. cor. of sec. 15.
	Subdivision of the NW $\frac{1}{4}$, Section 15

	From the C-W 1/16 sec. cor. of sec. 15.
	N. 0°01' W., on the N. and S. centerline of the NW $\frac{1}{4}$ of sec. 15.
	Over gently rolling land, through moderate undergrowth.
20.13	Point for the NW 1/16 sec. cor. of sec. 15, at intersection with the E. and W. centerline of the NW $\frac{1}{4}$ of sec. 15.
	Set the iron post 20 ins. in the ground, brass cap mkd.
	NW 1/16 S 15 1968
	Raise a mound of stone W. of the cor.
27.50	Telephone line, bears S. 63°10' E. and N. 63°10' W.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
30.00	Begin asc. steep SW. slope of high ridge, bears SE. and NW.
40.26	The point for the W 1/16 sec. cor. of secs. 10 and 15.
	<p>From the point for the C-N 1/16 sec. cor. of sec. 15.</p> <p>S. 89°37' W., on the E. and W. centerline of the NW$\frac{1}{4}$, sec. 15.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
5.30	Telephone line, bears S. 63°10' E. and N. 63°10' W.
20.01	The NW 1/16 sec. cor. of sec. 15.
29.80	Wash, 100 lks. wide, 4 ft. deep, drains N.
40.04	The N 1/16 sec. cor. of secs. 15 and 16.
	<p style="text-align: center;">Subdivision, Section 23</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.</p> <p>N. 1°03' W., on the N. and S. centerline of sec. 23.</p> <p>Over nearly level land.</p>
32.00	Enter moderate undergrowth, bears E. and W.
40.24	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 23, at intersection with the E. and W. centerline of sec. 23; not monumented.
48.50	Wash, 10 lks. wide, 2 ft. deep, drains NE.
66.80	Wash, 20 lks. wide, 2 ft. deep, drains NW.
80.50	The $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
	<p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p> <hr/> <p>From the $\frac{1}{4}$ sec. cor. of secs. 23 and 24.</p> <p>S. 89°56' W., on the E. and W. centerline of sec. 23.</p> <p>Over rolling land, through moderate undergrowth.</p>
17.80	Bend in wash, 15 lks. wide, 5 ft. deep, drains N., 100 lks. dist., thence E.
20.075	<p>Point for the C-E 1/16 sec. cor. of sec. 23.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E E 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S23 1968</p>

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	Raise a mound of stone N. of the cor.
40.15	The point for the Center $\frac{1}{4}$ sec. cor. of sec. 23.
40.60	Wash, 40 lks. wide, 3 ft. deep, drains N.
63.20	Track road, bears N. 30° E. and S. 20° W.
78.00	Wash, 15 lks. wide, 2 ft. deep, drains irregularly NW.
80.15	The $\frac{1}{4}$ sec. cor. of secs. 22 and 23.
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
<p>Subdivision, Section 25</p> <hr style="width: 20%; margin: auto;"/>	
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36. N. 1°01' E., on the N. and S. centerline of section 25. Over rolling land, through moderate undergrowth.
14.40	Track road, bears N. 25° E. and S. 25° W.
15.60	Track road, bears NE. and SW.
40.07	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 25, at intersection with the E. and W. centerline at sec. 25; not monumented.
48.70	Power line, bears S. 86°39' E., and N. 86°39' W.
60.115	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 25. Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">C N 1/16 S25 C 1968</p>
	Set a wooden post, 4 x 4 ins. squared, 30 ins. long, alongside the iron post.
79.90	Spur, slopes S. 40° W.
80.16	The $\frac{1}{4}$ sec. cor. of secs. 24 and 25.
	Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	From the $\frac{1}{4}$ sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp. N. 89°56' W., on the E. and W. centerline of Section 25.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	Over rolling land, through moderate undergrowth.
0.20	Track road, bears N. and S.
18.60	Whitefield Wash, drains N. 30° E.
29.90	Track road, bears irregularly NE. and S. 35° W.
40.11	The point for the Center ¼ sec. cor. of sec. 25.
57.00	Wash in Woods Canyon, drains N. 25° E.
80.25	The point for the ¼ sec. cor. of secs. 25 and 26.
	Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, creosote bush, sage brush and bunch grass.
<p>Subdivision, Section 27</p> <hr/>	
	From the ¼ sec. cor. of secs. 27 and 34.
	N. 0°21' E., on the N. and S. centerline of sec. 27.
	Over nearly level land, through moderate undergrowth.
0.90	Fence, bears E. and W.
4.60	Graded road, bears N. 60° W. and S. 60° E.
5.80	Underground pipe line, bears S. 70°11' E. and N. 70°11' W.
9.60	Wash in Woods Canyon, 200 lks. wide, 5 ft. deep, drains E.
38.90	Draw, drains NE.
40.13	Point for the Center ¼ sec. cor. of sec. 27, at intersection with the E. and W. centerline of sec. 27.
	Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.
	<p>T8S R31E C ¼+S27 1968</p>
58.40	Power line, bears S. 86°39' E. and N. 86°39' W.
80.24	The ¼ sec. cor. of secs. 22 and 27.
	Land, nearly level. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	From the ¼ sec. cor. of secs. 26 and 27.
	S. 89°53' W., on the E. and W. centerline of sec. 27.
	Over nearly level land, through moderate undergrowth.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
37.60	Draw, drains NE.
40.24	The Center $\frac{1}{4}$ sec. cor. of sec. 27.
80.52	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28; monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 10 ins. above the ground, in a collar of stone, brass cap mkd.
	T8S R31E $\frac{1}{4}$ S28 S27 1961
	Land, nearly level. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	Subdivision, Section 32 <hr/> From the $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the S. bdy. of the Tp. N. $0^{\circ}10'$ W., on the N. and S centerline of sec. 32. Over rolling land, through moderate undergrowth.
23.70	Confluence of washes, 20 lks. wide, 2 ft. deep, drains N., from S. 10° W. and N. 20° E.
30.00	Leave wash area, drains NE.
39.99	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 32, at intersection with the E. and W. centerline of sec. 32.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	T8S R31E C $\frac{1}{4}$ +S32 1968
	Raise a mound of stone W. of the cor.
47.00	Wash, 50 lks. wide, 3 ft. deep, drains N. 75° E.
49.40	Wash, 30 lks. wide, 4 ft. deep, drains E.; asc. steep S. slope of mountain.
79.20	Top of mountain, bears SE. and NW.; thence along top of mountain.
79.99	The $\frac{1}{4}$ sec. cor. of secs. 29 and 32.
	Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.
	From the $\frac{1}{4}$ sec. cor. of secs. 32 and 33. S. $89^{\circ}41'$ W., on the E. and W. centerline of sec. 32.

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>Over rolling land, through moderate undergrowth.</p> <p>Descend gentle W. slope.</p>
1.20	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
27.00	Wash, 50 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.
39.96	The Center $\frac{1}{4}$ sec. cor. of sec. 32.
	Continue ascent.
80.25	The $\frac{1}{4}$ sec. cor. of secs. 31 and 32.
	<p>Land, rolling.</p> <p>Soil, rocky clay loam.</p> <p>Timber, none.</p> <p>Undergrowth, creosote bush, cacti and bunch grass.</p>
<p>Subdivision, Section 34</p> <hr/>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 3 and 34, on the S. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.</p>
	<p>T8S R31E $\frac{1}{4}$ $\frac{S34}{S3}$ T9S 1961</p>
	<p>N. 0°05' W., on the N. and S. centerline of sec. 34.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Along an old abandoned N. and S. fence line.</p>
5.40	Wash, 15 lks. wide, 2 ft. deep, drains E.
23.80	Draw, drains E.
39.96	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 34, at intersection with the E. and W. centerline of sec. 34.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>T8S R31E C $\frac{1}{4}$+ S34 1968</p>
	Raise a mound of stone W. of the cor.
44.70	Wash, 25 lks. wide, 3 ft. deep, drains N. 30° E.
80.00	The $\frac{1}{4}$ sec. cor. of secs. 27 and 34, monumented by an iron post 2 $\frac{1}{2}$ ins. diam., projecting 10 ins. above the ground, in a collar of stone, brass cap mkd.
	<p>T8S R31E $\frac{1}{4}$ $\frac{S27}{S34}$ 1961</p>

Subdivision of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>The cor. is located 90 lks. S. of an E. and W. fence.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush and bunch grass.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p> <p>West, on the E. and W. centerline of sec. 34.</p> <p>Over rolling land, through moderate undergrowth.</p>
5.80	Wash, 20 lks. wide, 2 ft. deep, drains N. 50° E.
7.20	Fence, bears N. 30° E. and S. 30° W.
39.97	The Center $\frac{1}{4}$ sec. cor. of sec. 34.
45.50	Wash, 30 lks. wide, 4 ft. deep, drains N. from NW.
51.10	Same wash, 30 lks. wide, 4 ft. deep, drains NE.
80.02	<p>The $\frac{1}{4}$ sec. cor. of secs. 33 and 34, monumented by an iron post 2$\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E $\frac{1}{4}$ S33 S34 1961</p> <p>The cor. is located 110 lks. S. of a dirt road, bearing N. 70° E. and S. 70° W.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>Subdivision, Section 35</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp.</p> <p>N. 0°26' W., on the N. and S. centerline of sec. 35.</p> <p>Over rolling land, through moderate undergrowth.</p>
5.40	Wash, 35 lks. wide, 4 ft. deep, drains N. 60° E.
16.30	Fence, bears S. 40° E. and N. 40° W.
17.00	Underground pipe line, bears S. 40° E. and N. 40° W.
25.10	Wash, 25 lks. wide, 8 ft. deep, drains N. 25° E.
40.00	Point for the Center $\frac{1}{4}$ sec. cor. of sec. 35, at intersection with the E. and W. centerline of sec. 35; not monumented.
80.20	The $\frac{1}{4}$ sec. cor. of secs. 26 and 35.

Subdivisions of Sections, T. 8 S., R. 31 E.

CHAINS	
	<p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
15.20	<p>From the $\frac{1}{4}$ sec. cor. of secs. 35 and 36. S. $89^{\circ}59'$ W., on the E. and W. centerline of sec. 35. Over rolling land, through moderate undergrowth. Underground pipe line, bears N. 1° E. and S. 1° W.</p>
20.16	<p>Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 35. Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">E $\frac{1}{16}$</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S35 1968</p>
23.80	<p>Raise a mound of stone N. of the cor. Wash, 40 lks. wide, 10 ft. deep, drains N.</p>
28.75	<p>Wash, 40 lks. wide, 10 ft. deep, drains N. 20° E.</p>
40.32	<p>The point for the Center $\frac{1}{4}$ sec. cor. of sec. 35.</p>
59.90	<p>Underground pipe line on a curve, bears S. 40° E. and N. 49° W.</p>
60.40	<p>Fence, bears S. 40° E. and N. 40° W.</p>
80.10	<p>The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, monumented by an iron post $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T8S R31E</p> <p style="text-align: center;">$\frac{1}{4}$</p> <p style="text-align: center;">S34 S35</p> <p style="text-align: center;">1961</p> <p>Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, creosote bush, cacti and bunch grass.</p>
	<p>General Description</p>
	<p>The area surveyed in Township 8 South, Range 31 East lies adjacent to Duncan, Arizona. The land within the township is rolling hills. The elevation ranges from 3,500 feet above sea level in the northeast portion of the township to 4,400 feet at the highest point in section 32.</p> <p>The soil of the township is rocky, gravelly and sandy clay loam. The vegetation consists of creosote, cacti and bunch grass.</p>

Subdivisions of Sections, T. 8 S., R. 31 E.

CHAINS

The Gila River enters the township at the northeast portion of section 13, meanders northwesterly and leaves at the north boundary in section 4. The Southern Pacific Railroad parallels the Gila River. State Highway No. 75 enters the township on the east boundary in section 12, traverses northwesterly and leaves at the north boundary in section 3. U.S. Highway No. 70 enters the township at the east boundary in section 13, traverses northwest for approximately 1½ miles, curves to the southwest to a point near the ¼ section corner of sections 21 and 22.

There are residences along the Gila River area. The State Highway Department has a maintenance station in section 14. There is a Landing Air Strip in section 36 and underground pipe lines in several sections.

The drainage in the south part of the township is northeasterly and the northeast portion is southwesterly to the Gila River.

Land is used primarily for grazing except along the Gila River, it is under cultivation.

62

	CHAINS		

CERTIFICATE OF SURVEY

(X)(We), Kenneth D. Herman, Gary T. Oviatt and Jerrold E. Knight , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of December , 19 67 , (X)(We) have dependently resurveyed portions of the east and south boundaries and portions of the subdivisional lines and the survey of subdivisions in sections 2, 9, 11, 12, 13, 14, 15, 23, 25, 27, 32, 34 and 35 in Township 8 South, Range 31 East,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by (X)(me), (us) and under (X)(my) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 5, 1969 (Date) Kenneth D Herman (Cadastral Surveyor)
November 5, 1969 (Date) Gary T. Oviatt (Cadastral Surveyor)
November 5, 1969 (Date) Jerrold E. Knight (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JAN 6 1971

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the east and south boundaries, portions of the subdivisional lines and the survey of subdivisions in sections 2, 9, 11, 12, 13, 14, 15, 23, 25, 27, 32, 34 and 35 in Township 8 South, Range 31 East of the Gila and Salt River Meridian, Arizona, executed by Kenneth D. Herman, Gary T. Oviatt and Jerrold E. Knight, having been critically examined and found correct, are hereby approved.

JAN 12 1972 (Date) Clark F. Shuman (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626