

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

DEPENDENT RESURVEY AND SUBDIVISION

OF SECTION 28

TOWNSHIP 5 NORTH, RANGE 31 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Gary T. Oviatt,

Cadastral Surveyor

Under special instructions dated May 6, 19 69, which provided for the surveys included under Group Number 457, approved May 6, 1969, and assignment instructions dated May 6, 19 69.

Survey commenced May 20, 19 69

Survey completed June 26, 19 69

Township 5 North, Range 31 East
Gila and Salt River Meridian, Arizona

CHAINS

The west boundary and the subdivisional lines were surveyed in 1883 by W. R. Fitzgerald. The north 3 miles of the west boundary were resurveyed in 1916 by W. B. Kimmel. A portion of the west boundary and sections 7, 16 and 17 were resurveyed and subdivisions in sections 7, 16 and 17 were surveyed in 1965 by L. Murphy.

The following field notes are those of a dependent resurvey of the boundaries of section 28, designed to restore the corners in their true original location according to the best available evidence, and the survey of the subdivisions of section 28, Fractional Township 5 North, Range 31 East, Gila and Salt River Meridian, Arizona.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 6, 1969.

The geographic position of the southeast corner of section 28, as scaled from U.S.G.S. Quadrangle Alpine, Ariz. - New Mexico, scale 1:62500, dated 1958 is: Latitude 33°47'30" North and Longitude 109°04'18.9" West.

The mean magnetic declination was found to be: 13½° East.

Dependent Resurvey of the Boundaries of Section 28
Township 5 North, Range 31 East
Gila and Salt River Meridian, Arizona

Reestablishment of the Survey executed
by W. R. Fitzgerald in 1883

The cor. of secs. 27, 28, 33 and 34, monumented by a lava stone, 30 x 15 x 10 ins., firmly set 24 ins. in the ground, in a collar of stone, mkd. 1 notch on S. and 2 notches on E. edges.

from which

A pine (snag), 22 ins. diam., bears N. 18° E., 110 lks. dist., mkd. with a partially healed over blaze, illegible scribe marks. (Record: N. 20° E., 113 lks. dist.).

At the corner point

Set the iron post 6 ins. in the ground over an X chiseled on bedrock, mound of stone to top, brass cap mkd.

T5N R31E
S28 | S27
S33 | S34
1969

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS	
	<p>from which</p> <p>A pine, 10 ins. diam., bears N. $51\frac{1}{2}^{\circ}$ E., 91 lks. dist., mkd. T5NR31E S27 BT.</p> <p>A pine, 5 ins. diam., bears S. 75° E., 106 lks. dist., mkd. T5NR31E S34 BT.</p> <p>A pine, 7 ins. diam., bears N. 72° W., 77 lks. dist., mkd. T5NR31E S28 BT.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <p>The cor. is located approx. 250 lks. N. of a track road bearing E. and W.</p> <p>N. $0^{\circ}05'$ E., bet. secs. 27 and 28.</p> <p>Over gently rolling land, through moderate timber.</p>
9.90	Track road, bears S. 60° E. and N. 60° W.
20.06	<p>Point for the S $1/16$ sec. cor. of secs. 27 and 28, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T5N R31E S $1/16$ S28 S27 1969</p> </div>
	<p>from which</p> <p>A pine, 10 ins. diam., bears N. $23\frac{1}{2}^{\circ}$ E., 6 lks. dist., mkd. S $1/16$ S27 BT.</p> <p>A pine, $7\frac{1}{2}$ ins. diam., bears S. 42° W., 25 lks. dist., mkd. S $1/16$ S28 BT.</p> <p>Raise a mound of stone W. of the corner.</p> <p>The cor. is located 50 lks. E. of a track road, bearing S. 10° E. and N. 10° W.</p>
25.60	Track road, bears N. 30° E. and S. 30° W.
25.80	Southeast shore of small lake, bears N. 30° E. and S. 10° W.; cross lake by triangulation.
30.09	Point for the N-S $1/64$ sec. cor. of secs. 27 and 28, at proportionate dist. This cor. falls in the middle of a lake; not monumented.
	Continue across lake.
32.80	North shore of same lake, bears E. and W. End of triangulation.
33.40	Fence, bears S. 60° E. and N. 60° W. for 40 lks., thence N. 8° W.

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS

- 36.70 Track road, bears S. 60° E. and N. 60° W.
- 40.12 The $\frac{1}{2}$ sec. cor. of secs. 27 and 28, monumented by an unmkd. record size stone, 14 x 10 x 4 ins., set in a mound of stone, and verified by the remains of an original bearing tree:
- A pine, 12 ins. diam., bears N. 75° E., 24 lks. dist., mkd. S BT.
- At the corner point
- Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
- T5N R31E
 $\frac{1}{2}$
S28 | S27
1969
- from which
- A pine, 6 ins. diam., bears N. 60° W., 25 lks. dist., mkd. T5NR31E $\frac{1}{2}$ S28 BT.
- Bury the record size stone alongside the iron post.
- Set a steel fence post 6 ft. long, alongside the cor.
- The cor. is located 157 lks. E. of a N. and S. fence, and 140 lks. E. of a track road paralleling the fence.
-
- N. 0°38' W., beginning new measurement.
- Over gently rolling land, through moderate timber.
- 10.05 Point for the S-N $\frac{1}{64}$ sec. cor. of secs. 27 and 28, at proportionate dist.; not monumented.
- 20.10 Point for the N $\frac{1}{16}$ sec. cor. of secs. 27 and 28, at proportionate dist.
- Set the iron post 24 ins. in the ground, brass cap mkd.
- T5N R31E
N $\frac{1}{16}$
S28 | S27
1969
- from which
- A pine, 8 ins. diam., bears S. 52 $\frac{1}{2}$ ° E., 65 $\frac{1}{2}$ lks. dist., mkd. N $\frac{1}{16}$ S27 BT.
- A pine, 10 ins. diam., bears S. 64 $\frac{1}{2}$ ° W., 27 lks. dist., mkd. N $\frac{1}{16}$ S28 BT.
- Set a steel fence post 6 ft. long, alongside the iron post.

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS	<p>Raise a mound of stone W. of the corner.</p> <p>27.90 Fence, bears S. 80° E. and N. 80° W.</p> <p>30.15 Point for the N-N 1/64 sec. cor. of secs. 27 and 28, at proportionate dist.; not monumented.</p> <p>35.18 Point for the N-N-N 1/256 sec. cor. of secs. 27 and 28, at proportionate dist.; not monumented.</p> <p>38.70 Fence cor., fences bear N. 40° E. and S. 5° W., enter open meadow, edge bears NE. and SW.</p> <p>40.21 The cor. of secs. 21, 22, 27 and 28, monumented by an iron pipe 2 ins. diam., with a brass cap mkd. LS 5704 T5N R31E secs. 21, 22, 27 and 28 in their right quadrants and 1966.</p> <p>from which the original bearing trees:</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. 70½° E., 113 lks. dist., markings visible but not legible. (Record: N. 30° E., 113 lks. dist.).</p> <p style="padding-left: 40px;">A pine, 25 ins. diam., bears S. 82¾° E., 92 lks. dist., mkd. with cut in blaze, mks. destroyed. (Record: S. 20° E., 92 lks. dist.).</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="2">T5N R31E</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> <tr> <td colspan="2">1969</td> </tr> </table> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 55½° E., 62 lks. dist., mkd. T5NR31E S22 BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 55¾° E., 23 lks. dist., mkd. T5NR31E S27 BT.</p> <p style="padding-left: 40px;">A pine, 7½ ins. diam., bears S. 28¾° W., 68 lks. dist., mkd. T5NR31E S28 BT.</p> <p>Bury the local cor. inverted alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, bunchgrass and scrub oak.</p>	T5N R31E		S21	S22	S28	S27	1969	
T5N R31E									
S21	S22								
S28	S27								
1969									
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°24' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land, through moderate timber.</p>								

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS

- 7.70 Track road, bears SE. and NW.
- 17.20 Top of hill, bears N. and S.; desc. W. slope.
- 19.73 Point for the E 1/16 sec. cor. of secs. 28 and 33, at proportionate dist.
- Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
- T5N R31E
E 1/16 $\frac{S28}{S33}$
1969
- from which
- A pine, 10 ins. diam., bears N. 30° E., 90 lks. dist., mkd. E 1/16 S28 BT.
- A pine, 11 ins. diam., bears S. 42 $\frac{3}{4}$ ° W., 42 lks. dist., mkd. E 1/16 S33 BT.
- 31.20 Power line, bears N. 30° E. and S. 30° W.
- 31.80 Head of a ravine, drains SE.; asc. E. slope.
- 39.47 Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original corner.
- Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
- T5N R31E
 $\frac{1}{4}$ $\frac{S28}{S33}$
1969
- from which
- A pine, 12 ins. diam., bears S. 61° E., 39 $\frac{1}{2}$ lks. dist., mkd. T5NR31E $\frac{1}{4}$ S33 BT.
- A pine, 10 ins. diam., bears N. 20° W., 32 lks. dist., mkd. T5NR31E $\frac{1}{4}$ S28 BT.
- Set a steel fence post 6 ft. long, alongside the iron post.
- 45.10 Graded road, Forest Service No. 281, bears N. 40° E. and S. 40° W.
- 59.20 Point for the W 1/16 sec. cor. of secs. 28 and 33, at proportionate dist.
- Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd,

T5N R31E
W 1/16 $\frac{S28}{S33}$
1969

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS

from which

A pine, 6 ins. diam., bears S. $61\frac{1}{2}^\circ$ E., 40 lks. dist., mkd. W 1/16 S33 BT.

A pine, 14 ins. diam., bears N. $15\frac{1}{2}^\circ$ W., 40 lks. dist., mkd. W 1/16 S28 BT.

69.40 Ravine, drains SE.

78.94 Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original corner.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T5N R31E
S29 | S28
S32 | S33
1969

from which

A pine, 10 ins. diam., bears S. $40\frac{1}{2}^\circ$ E., 110 lks. dist., mkd. T5NR31E S33 BT.

A pine, 6 ins. diam., bears S. $34\frac{1}{2}^\circ$ W., 104 lks. dist., mkd. T5NR31E S32 BT.

A pine, 8 ins. diam., bears N. $27\frac{1}{4}^\circ$ W., $68\frac{1}{2}$ lks. dist., mkd. T5NR31E S29 BT.

The $\frac{1}{4}$ sec. cor. of secs. 32 and 33, bears S. $3^\circ 46'$ W., 40.04 chs. dist., as determined from the remains of the original bearing tree:

An Alligator Juniper, 22 ins. diam., bears N. 60° W., 20 lks. dist., mkd. $\frac{1}{4}$ S BT.
(Record: cedar).

At the corner point

Set the iron post over an X chiseled in solid rock, mound of stone to top, brass cap mkd.

T5N R31E
 $\frac{1}{4}$
S32 | S33
1969

from which

A pine, 10 ins. diam., bears S. $25\frac{3}{4}^\circ$ E., 55 lks. dist., mkd. $\frac{1}{4}$ S33 BT.

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., bears N. $89^\circ 20'$ W., 158.56 chs. dist., monumented by a scattered mound of stone, from which the remains of the original bearing trees:

A pine, 22 ins. in diam., bears N. $7\frac{1}{2}^\circ$ W., 11 lks. dist., mkd. T5NR30E S25 BT.

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T5N	
R30E	R31E
S25	S30
S36	S31
1969	

from which

A fir, 10 ins. diam., bears N. $43\frac{1}{2}^{\circ}$ E.,
30 lks. dist., mkd. T5NR31E S30 BT.A fir, 12 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ E.,
64 lks. dist., mkd. T5NR31E S31 BT.A fir, 13 ins. diam., bears S. $45\frac{1}{2}^{\circ}$ W.,
60 lks. dist., mkd. T5NR30E S36 BT.

Raise a mound of stone W. of the corner.

Set a steel fence post 6 ft. long, alongside
the iron post.These control lines were fully retraced, and careful
search was made for evidence of intervening corners,
none of which was recovered.Set a steel fence post 6 ft. long, alongside the iron
post.The corner is located on a S. slope, 150 lks. N. of a
wash, 10 lks. wide, 2 ft. deep, drains E.Land, gently rolling.
Soil, rocky clay loam.
Timber, pine, juniper and oak.
Undergrowth, bunchgrass and scrub oak.N. $0^{\circ}43'$ W., bet. secs. 28 and 29.

Over rolling land, through moderate timber.

Ascend SE. slope.

10.30 Top of ridge, bears N. 70° E. and S. 70° W.; desc. N.
slope.19.97 Point for the S $\frac{1}{16}$ sec. cor. of secs. 28 and 29, at
proportionate dist.

Set the iron post 22 ins. in the ground, brass cap mkd.

T5N R31E	
S $\frac{1}{16}$	
S29	S28
1969	

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS	
	<p>from which</p> <p>A pine, 7 ins. diam., bears S. $78\frac{1}{2}^{\circ}$ E., 47 lks. dist., mkd. S 1/16 S28 BT.</p> <p>A pine, 6 ins. diam., bears N. $78\frac{1}{2}^{\circ}$ W., 21 lks. dist., mkd. S 1/16 S29 BT.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
23.70	Graded road, bears E. and W., Forest Service No. 281C.
25.60	Fence cor., fences bear N., N. 80° E. and SW.; enter meadow, edge bears E. and W.
26.50	Long Cienega Wash (dry), drains NE.
28.60	Fence cor., fences bear NE., S. and W.; enter moderate timber, edge bears E. and W.; asc. S. slope.
29.96	Point for the N-S 1/64 sec. cor. of secs. 28 and 29, at proportionate dist.; not monumented.
33.20	Jeep road, bears N. 70° E. and S. 70° W.
34.955	Point for the N-N-S 1/256 sec. cor. of secs. 28 and 29, at proportionate dist.; not monumented.
39.30	Top of ridge, bears E. and W.; desc. N. slope.
39.95	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original corner.
	<p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T5N R31E $\frac{1}{4}$ S29 S28 1969</p>
	<p>from which</p> <p>A pine, 16 ins. diam., bears S. 41° E., 67 lks. dist., mkd. T5NR31E S28 BT.</p> <p>A fir, 10 ins. diam., bears N. $83\frac{1}{2}^{\circ}$ W., 79 lks. dist., mkd. T5NR31E S29 BT.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
42.00	Ravine, drains E.; asc. S. slope.
42.60	Logging road, bears E. and W.
49.94	Point for the S-N 1/64 sec. cor. of secs. 28 and 29, at proportionate dist.; not monumented.
56.10	Top of ridge, bears E. and W.; desc. N. slope.
59.93	Point for the N 1/16 sec. cor. of secs. 28 and 29, at proportionate dist.

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T5N R31E
N 1/16
S29 | S28
1969

from which

A pine, 10 ins. diam., bears N. 40½° E., 78 lks. dist., mkd. N 1/16 S28 BT.

A pine, 12 ins. diam., bears S. 62¾° W., 42 lks. dist., mkd. N 1/16 S29 BT.

Set a steel fence post 6 ft. long, alongside the iron post.

63.80 A jeep road, bears S. 60° E. and N. 60° W.

66.30 A jeep road, bears S. 60° E. and N. 60° W.

70.20 Enter open meadow; edge bears SE. and NW.

71.00 An abandoned fence, bears SE. and NW.

75.60 Wash, 5 lks. wide, 1 ft. deep, drains SE.

76.14 A power line, bears S. 30° E. and N. 30° W.

79.90 Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original corner.

Set the iron post 24 ins. in the ground, brass cap mkd.

T5N R31E
S20 | S21
S29 | S28
1969

from which

A pine, 6 ins. diam., bears N. 50¾° E., 38 lks. dist., mkd. T5NR31E S21 BT.

A pine, 7 ins. diam., bears S. 25½° E., 40 lks. dist., mkd. T5NR31E S28 BT.

A pine, 10 ins. diam., bears S. 34½° W., 10 lks. dist., mkd. T5NR31E S29 BT.

A pine, 10 ins. diam., bears N. 15½° W., 6 lks. dist., mkd. T5NR31E S20 BT.

The cor. of secs. 16, 17, 20 and 21, bears N. 0°22' W., 79.90 chs. dist., monumented by an iron post firmly set in a mound of stone with a steel fence post set alongside, brass cap mkd.

T5N R31E
S17 | S16
S20 | S21
1965

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS

from which

A pine, 16 ins. diam., bears N. 60° E.,
17 lks. dist., mkd. T5NR31E S16 BT.

A pine, 12 ins. diam., bears S. 67° E.,
54 lks. dist., mkd. T5NR31E S21 BT.

A pine, 21 ins. diam., bears S. 76° W.,
111 lks. dist., mkd. T5NR31E S20 BT.
(Record: 114 lks.).

A pine, 22 ins. diam., bears N. 30° W.,
107 lks. dist., mkd. T5NR31E S17 BT.

The cor. of secs. 19, 24, 25 and 30, on the W. bdy.
of Tp., bears N. 89°55' W., 157.55 chs. dist., monu-
mented by a stump hole of a fallen and rotten Aspen,
11 ins. diam., mkd. T5NR30E S24 on one side and S25
on another side. This is the only remaining evi-
dence of the original corner.

At the corner point

Set the iron post 24 ins. in the ground, brass
cap mkd.

T5N	
R30E	R31E
S24	S19
S25	S30
1969	

from which

A Fir, 8 ins. diam., bears N. 57½° E.,
38½ lks. dist., mkd. T5NR31E S19 BT.

A Fir, 7 ins. diam., bears S. 78° E.,
42 lks. dist., mkd. T5NR31E S30 BT.

A Fir, 10 ins. diam., bears S. 32¾° W.,
33 lks. dist., mkd. T5NR30E S25 BT.

A Fir, 7 ins. diam., bears N. 82½° W.,
26 lks. dist., mkd. T5NR30E S24 BT.

Bury scribed portion of Aspen tree alongside
the iron post.

Raise a mound of stone W. of the corner.

Set a steel fence post 6 ft. long, alongside
the iron post.

These control lines were fully retraced, and care-
ful search was made for evidence of intervening
corners, none of which was recovered.

Raise a mound of stone W. of the corner.

Set a steel fence post 6 ft. long, alongside the iron
post.

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS	
	<p>The cor. is located at the N. edge of open meadow, bears SE. and NW.; 15 lks. S. of an abandoned fence and 150 lks. S. of Forest Service Road No. 281, bearing SE. and NW.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, bunchgrass and scrub oak.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28. S. 89°11' W., bet. secs. 21 and 28. Over nearly level open meadow land.</p>
2.00	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° E.
5.01	Point for the E-E-E 1/256 sec. cor. of secs. 21 and 28, at proportionate dist.; not monumented.
10.02	Point for the E-E 1/64 sec. cor. of secs. 21 and 28, at proportionate dist.; not monumented.
13.30	Fence, bears N. and S.; enter moderate timber; asc. E. slope.
18.50	Jeep road, bears irregularly N. and S.
20.04	Point for the E 1/16 sec. cor. of secs. 21 and 28, at proportionate dist. Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T5N R31E E 1/16 $\frac{S21}{S28}$ 1969.</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 21½° E., 52 lks. dist., mkd. E 1/16 S21 BT.</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 34½° W., 40 lks. dist., mkd. E 1/16 S28 BT.</p>
	<p>Raise a mound of stone N. of the corner. Set a steel fence post 6 ft. long, alongside the iron post.</p>
25.40	Jeep road, bears S. 20° E. and N. 20° W.
30.50	Jeep road, bears N. 20° E. and S. 20° W.
32.80	Graded road, Forest Service No. 281D, bears N. 30° E. and S. 30° W.
40.00	Logging road, bears S. 20° E. and N. 20° W., 100 lks. to dead end.

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS	
40.08	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 28, monumented by an unmkd. sandstone, 18 x 11 x 4 ins. found 4 ins. below surface, verified from the remains of the original bearing tree:</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. 30° W., 12 lks. dist., mkd. with cut in blaze with S.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T5N R31E. $\frac{1}{4}$ $\frac{S21}{S28}$ 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. $\frac{3}{4}$° E., 66½ lks. dist., mkd. T5NR31E S21 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 5¾° W., 40½ lks. dist., mkd. T5NR31E S28 BT.</p> <p>Deposit unmkd. stone in the mound of stone N. of the corner.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89°01' W., beginning new measurement.</p> <p>Over rolling land, through moderate timber.</p> <p>Continue ascending.</p>
12.00	<p>Top of spur, slopes S.; desc. SW. slope.</p>
19.77	<p>Point for the W 1/16 sec. cor. of secs. 21 and 28, at proportionate dist.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T5N R31E W 1/16 $\frac{S21}{S28}$ 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 33° E., 20½ lks. dist., mkd. W 1/16 S28 BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 14° W., 42 lks. dist., mkd. W 1/16 S21 BT.</p> <p>The cor. is located 11.40 chs. N. of Forest Service Road No. 281, bearing S. 75° E. and N. 75° W.</p>

Dep. Res., Portion Subdivisional Lines, T. 5 N., R. 31 E.

CHAINS	
31.40	Ravine, drains S.; asc. SE. slope.
35.30	Fence, bears SE. and NW.
35.90	Top of spur, slopes S.; desc. SW. slope.
38.00	Graded road, Forest Service No. 281, bears SE. and NW.
39.55	The cor. of secs. 20, 21, 28 and 29.
	Land, nearly level to rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, bunchgrass and scrub oak.
	Subdivision of Section 28, T. 5 N., R. 31 E.
	From the $\frac{1}{4}$ sec. cor. of secs. 28 and 33. N. $0^{\circ}40'$ W., on the N-S centerline of sec. 28. Over gently rolling land, through moderate timber.
13.60	Graded road, Forest Service No. 281, bears N. 55° E. and S. 55° W.
20.02	Point for the C-S $1/16$ sec. cor. of sec. 28.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	$\begin{array}{c} C \\ \\ S\ 1/16 \quad \quad S28 \\ \\ C \\ 1969 \end{array}$
	from which
	A pine, 9 ins. diam., bears S. $29\frac{1}{2}^{\circ}$ E., 56 lks. dist., mkd. C-S $1/16$ S28 BT.
	A pine, 7 ins. diam., bears N. $68\frac{1}{2}^{\circ}$ W., 42 lks. dist., mkd. C-S $1/16$ S28 BT.
	Raise a mound of stone W. of the corner.
	Set a steel fence post 6 ft. long, alongside the iron post.
20.90	Graded road, Forest Service No. 281C, bears SE. and NW.
33.20	Power line, bears S. 26° E. and N. 26° W.
35.03	Point for the C-N-N-S $1/256$ sec. cor. of sec. 28.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	$\begin{array}{c} S28 \\ C-N-N-S \\ 1/256 \\ 1969 \end{array}$

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS		
	<p>from which</p> <p>A pine, 11 ins. diam., bears N. 81° E., 107½ lks. dist., mkd. C-N-N-S 1/256 S28 BT.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>	
36.80	Fence, bears S. 80° W. and N. 80° E. for 100 lks., thence N. 5° W.; enter open meadow.	
40.04	<p>Point for the center ¼ sec. cor. of sec. 28, at intersection with the E-W centerline of sec. 28.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C ¼ + S28 1969</p>	
	<p>from which</p> <p>A pine, 10 ins. diam., bears S. 39° E., 166½ lks. dist., mkd. C ¼ S28 BT.</p> <p>Set a fence post 6 ft. long, alongside the iron post.</p>	
43.00	Long Cienega Wash, 5 lks. wide, 2 ft. deep, drains NE.	
45.06	<p>Point for the C-S-S-N 1/256 sec. cor. of sec. 28.</p> <p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S28 C-S-S-N 1/256 1969</p>	
	<p>from which</p> <p>Fence cor., bears N. 77½° E., 92 lks. dist., fences bear N. and E.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <p>The cor. is located 16½ lks. W. of a fence bearing S. 5° E. and N. 5° W.</p>	
48.00	Fence cor.; fences bear E., S. 5° E. and W.	
50.08	Point for the C-S-N 1/64 sec. cor. of sec. 28; not monumented.	
54.20	Track road, bears E. and W.	
55.10	<p>Point for the C-N-S-N 1/256 sec. cor. of sec. 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 C-N-S-N 1/256 1969</p>	

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
	<p>Raise a mound of stone W. of the corner.</p>
	<p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
57.30	<p>Graded road, Forest Service No. 281, bears S. 30° E. and N. 30° W.</p>
57.70	<p>Fence, bears S. 30° E. and N. 30° W.; enter moderate timber.</p>
60.12	<p>Point for the C-N 1/16 sec. cor. of sec. 28.</p>
	<p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p>
	<div style="text-align: center;"> <p>C</p> <p> </p> <p>N 1/16 S28</p> <p> </p> <p>C</p> <p>1969</p> </div>
	<p>from which</p>
	<p>A pine, 10 ins. diam., bears N. 48$\frac{3}{4}$° E., 52 lks. dist., mkd. CN 1/16 S28 BT.</p>
	<p>A pine, 7$\frac{1}{2}$ ins. diam., bears N. 16° W., 92 lks. dist., mkd. CN 1/16 S28 BT.</p>
	<p>A fence cor., bears N. 41° W., 108 lks. dist.; fences bear S. 55° E. and S. 30° E.</p>
	<p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
	<p>The cor. is located 86 lks. E. of Forest Service Road No. 281.</p>
60.45	<p>Fence, bears S. 55° E. and N. 55° W.</p>
63.10	<p>Jeep road, bears E. and W.</p>
67.90	<p>Graded road, Forest Service No. 281D, bears NE. and SW.</p>
68.15	<p>Fence, bears S. 60° E. and N. 60° W.</p>
80.20	<p>The $\frac{1}{4}$ sec. cor. of secs. 21 and 28.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, rocky clay loam.</p>
	<p>Timber, pine, juniper and oak.</p>
	<p>Undergrowth, bunchgrass and scrub oak.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 27 and 28.</p>
	<p>S. 89°17' W., on the E-W centerline of sec. 28.</p>
	<p>Over gently rolling land, through moderate timber.</p>
1.40	<p>Track road, bears S. 8° E. and N. 8° W.</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
1.56	Fence, bears S. 8° E. and N. 8° W.
10.00	Point for the C-E-E 1/64 sec. cor. of sec. 28; not monumented.
11.80	Leave timber; enter open meadow, bears N. and S.
13.80	Wash, 10 lks. wide, 2 ft. deep, drains SE. into lake.
15.005	Point for the C-W-E-E 1/256 sec. cor. of sec. 28; not monumented.
20.01	Point for the C-E 1/16 sec. cor. of sec. 28; not monumented.
22.20	Fence, bears SE. and NW.; leave meadow, enter moderate timber, bears SE. and NW.
23.10	Track road, bears SE. and NW.
30.01	Point for the C-W-E 1/64 sec. cor. of sec. 28; not monumented.
34.30	Graded road, Forest Service No. 281, bears N. 10° E. and S. 10° W.
35.015	Point for the C-W-W-E 1/256 sec. cor. of sec. 28.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	S28 C-W-W-E 1/256 1969
	from which
	A pine, 6 ins. diam., bears N. 11½° E., 95 lks. dist., mkd. CWWE 1/256 S28 BT.
	A pine, 10 ins. diam., bears S. 27¾° E., 25 lks. dist., mkd. CWWE 1/256 S28 BT.
	Set a steel fence post 6 ft. long, alongside the iron post.
39.20	Fence, bears S. 5° E. and N. 5° W.; enter open meadow.
40.02	The center ¼ sec. cor. of sec. 28.
43.40	Power line, bears S. 26° E. and N. 26° W.
47.30	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains NE.
49.905	Point for the C-E-W 1/64 sec. cor. of sec. 28; not monumented.
59.79	Point for the C-W 1/16 sec. cor. of sec. 28; not monumented.
60.70	Fence, bears NE. and SW.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
63.70	Fence, bears N. 10° E. and S. 10° W.; enter moderate timber.
64.73	<p>Point for the C-E-W-W 1/256 sec. cor. of sec. 28.</p> <p>Set the iron post over an X chiseled on solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">S28 C-E-W-W 1/256 1969</p> <p>from which</p> <p style="text-align: center;">A pine, 7 ins. diam., bears N. 53½° W., 37 lks. dist., mkd. CEWW 1/256 S28 BT.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
69.67	<p>Point for the C-W-W 1/64 sec. cor. of sec. 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 C-W-W 1/64 1969</p> <p>from which</p> <p style="text-align: center;">A pine, 10 ins. diam., bears N. 21° E., 131 lks. dist., mkd. CWW 1/64 S28 BT.</p> <p>Raise a mound of stone N. of the corner.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
70.70	Track road, bears N. 20° E. and S. 20° W.
74.615	Point for the C-W-W-W 1/256 sec. cor. of sec. 28; not monumented.
79.56	<p>The ¼ sec. cor. of secs. 28 and 29.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, bunchgrass and scrub oak.</p>
<p>Subdivision of NE ¼ Section 28</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-E 1/16 sec. cor. of sec. 28.</p> <p>N. 0°39' W., on the N-S centerline of the NE¼ of sec. 28.</p>	

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS		
	Over nearly level land, across open meadow.	
5.02	Point for the C-S-S-NE 1/256 sec. cor. of sec. 28. Set the iron post 24 ins. in the ground, brass cap mkd. S28 C-S-S-NE 1/256 1969	
	Raise a mound of stone W. of the corner.	
	Set a steel fence post 6 ft. long, alongside the iron post.	
8.40	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains SE.	
10.04	Point for the C-S-NE 1/64 sec. cor. of sec. 28; not monumented.	
20.09	Point for the NE 1/16 sec. cor. of sec. 28, at intersection with the E-W centerline of the NE 1/4 of sec. 28. Set the iron post 24 ins. in the ground, brass cap mkd. NE1/16 S28 1969	
	Raise a mound of stone W. of the corner.	
	Set a steel fence post 6 ft. long, alongside the iron post.	
24.90	Fence, bears NE. and SW.; enter moderate timber.	
25.90	Track road, bears NE. and SW.; asc. S. slope.	
30.13	Point for the C-N-NE 1/64 sec. cor. of sec. 28; not monumented.	
35.155	Point for the C-N-N-NE 1/256 sec. cor. of sec. 28. Set the iron post 24 ins. in the ground, brass cap mkd. S28 C-N-N-NE 1/256 1969	
	from which	
	A pine, 12 1/2 ins. diam., bears N. 3 1/4° E., 48 lks. dist., mkd. CNNNE 1/256 S28 BT.	
	A pine, 14 ins. diam., bears S. 25 1/2° W., 50 1/2 lks. dist., mkd. CNNNE 1/256 S28 BT.	
	Raise a mound of stone W. of the corner.	
	Set a steel fence post 6 ft. long, alongside the iron post.	

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
40.18	The E 1/16 sec. cor. of secs. 21 and 28.
	From the N 1/16 sec. cor. of secs. 27 and 28.
	S. 89°15' W., on the E-W centerline of the NE $\frac{1}{4}$ of sec. 28.
	Over gently rolling land, through moderate timber.
3.60	Low ridge, bears N. and S.; desc. W. slope.
6.70	Fence, bears S. 10° E. and N. 10° W.; enter open meadow.
9.50	Wash, 10 lks. wide, 1 ft. deep, drains S. 20° W.
10.015	Point for the C-E-NE 1/64 sec. cor. of sec. 28; not monumented.
20.03	The NE 1/16 sec. cor. of sec. 28.
30.04	Point for the C-W-NE 1/64 sec. cor. of sec. 28; not monumented.
36.60	Fence, bears NE. and SW.; leave meadow, enter moderate timber.
39.58	Fence, bears S. 55° E. and N. 55° W.
40.05	The C-N 1/16 sec. cor. of sec. 28.
	From the point for the C-E-NE 1/64 sec. cor. of sec. 28.
	N. 0°38'30" W., on the N-S centerline of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28.
	Over nearly level land, across open meadow.
10.05	Point for the NE-NE 1/64 sec. cor. of sec. 28, at intersection with the E-W centerline of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	S28
	NE-NE
	1/64
	1969
	Raise a mound of stone W. of the corner.
	Set a steel fence post 6 ft. long, alongside the iron post.
15.075	Point for the C-N-NE-NE 1/256 sec. cor. of sec. 28; not monumented.
20.10	The point for the E-E 1/64 sec. cor. of secs. 21 and 28.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
	<p>From the point for the N-N 1/64 sec. cor. of secs. 27 and 28.</p> <p>S. 89°13' W., on the E-W centerline of the NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 28.</p> <p>Over gently rolling land, through moderate timber.</p> <p>0.70 Fence, bears N. 5° E. and S. 5° W.; enter open meadow.</p> <p>5.01 Point for the C-E-NE-NE 1/256 sec. cor. of sec. 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 C-E-NE-NE 1/256 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 8° E., 71 lks. dist., mkd. CENENE 1/256 S28 BT.</p> <p>Raise a mound of stone N. of the corner.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <p>8.50 Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.</p> <p>10.02 The NE-NE 1/64 sec. cor. of sec. 28.</p> <p>16.30 Fence, bears N. 25° E. and S. 25° W.</p> <p>20.04 The point for the C-N-NE 1/64 sec. cor. of sec. 28.</p>
	<p>From the C-E-NE-NE 1/256 sec. cor. of sec. 28.</p> <p>N. 0°38' W., on the N-S centerline of the NE$\frac{1}{4}$NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, across open meadow.</p> <p>3.00 Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.</p> <p>5.025 Point for the NE-NE-NE 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the NE$\frac{1}{4}$NE$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 NE-NE-NE 1/256 1969</p> <p>Raise a mound of stone W. of the corner.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
10.05	The point for the E-E-E 1/256 sec. cor. of secs. 21 and 28.
	From the point for the N-N-N 1/256 sec. cor. of secs. 27 and 28.
	S. 89°12' W., on the E-W centerline of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28.
	Over nearly level land, across open meadow.
0.33	Fence, bears N. 5° E. and S. 5° W.
4.20	Wash, 10 lks. wide, 2 ft. deep, drains S. 40° W.
5.01	The NE-NE-NE 1/256 sec. cor. of sec. 28.
10.02	Point for the C-N-NE-NE 1/256 sec. cor. of sec. 28.
	From the point for the C-E-E 1/64 sec. cor. of sec. 28.
	N. 0°39' W., on the N-S centerline of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28.
	Over nearly level land, through scattered timber.
5.025	Point for the C-S-SE-NE 1/256 sec. cor. of sec. 28.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	S28
	C-S-SE-NE
	1/256
	1969
	from which
	A pine, 7 $\frac{1}{2}$ ins. diam., bears S. 63 $\frac{3}{4}$ ° W., 25 $\frac{1}{2}$ lks. dist., mkd. CSSENE 1/256 S28 BT.
	Raise a mound of stone W. of the corner.
10.05	Point for the SE-NE 1/64 sec. cor. of sec. 28, at intersections with the E-W centerline of SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28; not monumented.
	Thence enter open meadow, bears E. and W.
19.30	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.
20.10	The point for the C-E-NE 1/64 sec. cor. of sec. 28.
	From the point for the S-N 1/64 sec. cor. of secs. 27 and 28.
	S. 89°16' W., on the E-W centerline of the SE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28.
	Over gently rolling land, through moderate timber.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS		
4.00	Fence, bears S. 15° E. and N. 15° W.	
10.01	The point for the SE-NE 1/64 sec. cor. of sec. 28.	
	Leave timber; enter open meadow, bears NE. and SW.	
12.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 20° W.	
15.015	The point for the C-W-SE-NE 1/256 sec. cor. of sec. 28; not monumented.	
19.00	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
20.02	The point for the C-S-NE 1/64 sec. cor. of sec. 28.	
	From the C-W-E-E 1/256 sec. cor. of sec. 28.	
	N. 0°39' W., on the N-S centerline of the SW¼SE¼NE¼ of sec. 28.	
	Over gently rolling land, through scattered timber.	
5.025	Point for the SW-SE-NE 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the SW¼SE¼NE¼ of sec. 28.	
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.	
	S28 SW-SE-NE 1/256 1969	
6.80	Leave timber; enter open meadow, bears E. and SW.	
7.00	Wash, 10 lks. wide, 1 ft. deep, drains SE., from NE. and NW.	
10.05	The point for the C-W-SE-NE 1/256 sec. cor. of sec. 28.	
	From the C-S-SE-NE 1/256 sec. cor. of sec. 28.	
	S. 89°16'30" W., on the E-W centerline of the SW¼SE¼NE¼ of sec. 28.	
	Over gently rolling land, through moderate timber.	
4.50	Wash, 10 lks. wide, 1 ft. deep, drains SE.	
5.005	The SW-SE-NE 1/256 sec. cor. of sec. 28.	
10.01	The C-S-S-NE 1/256 sec. cor. of sec. 28.	
	From the point for the C-W-E 1/64 sec. cor. of sec. 28.	
	N. 0°40' W., on the N-S centerline of the SW¼NE¼ of sec. 28.	
	Over gently rolling land, through moderate timber.	

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
3.40	Track road, bears E. and W.
4.00	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains NE.
4.20	Fence, bears S. 75° E. and N. 75° W.
5.025	Point for the C-S-SW-NE 1/256 sec. cor. of sec. 28; not monumented.
10.05	Point for the SW-NE 1/64 sec. cor. of sec. 28, at intersection with the E-W centerline of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28; not monumented.
13.70	Wash, 5 lks. wide, $\frac{1}{2}$ ft. deep, drains S. 75° E.
20.10	The point for the C-W-NE 1/64 sec. cor. of sec. 28.
	<p>From the point for the C-S-NE 1/64 sec. cor. of sec. 28.</p> <p>S. 89°16' W., on the E-W centerline of the SW$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, across open meadow.</p>
10.01	The point for the SW-NE 1/64 sec. cor. of sec. 28.
14.50	Fence, bears S. 30° E. and N. 30° W.
15.015	Point for the C-W-SW-NE 1/256 sec. cor. of sec. 28; not monumented. This cor. falls in the middle of a graded road, Forest Service No. 281, bears S. 30° E. and N. 30° W.
17.50	NE. cor. of cabin, bears N., 30 lks. dist.
20.02	The point for the C-S-N 1/64 sec. cor. of sec. 28.
	<p>From the C-W-W-E 1/256 sec. cor. of sec. 28.</p> <p>N. 0°40' W., on the N-S centerline of the SW$\frac{1}{4}$SW$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, through moderate timber.</p>
4.00	Long Cienega Wash, 10 lks. wide, 1 ft. deep, drains NE.
4.90	Fence, bears S. 85° E. and N. 85° W.
5.02	Point for the SW-SW-NE 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the SW $\frac{1}{4}$ SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 28.
	Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.
	<p>S28 SW-SW-NE 1/256 1969</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. in diam., bears S. 72½° E., 39½ lks. dist., mkd. SWSWNE 1/256 S28 BT.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
10.00	Graded road, Forest Service No. 281, bears S. 30° E. and N. 30° W.
10.04	The point for the C-W-SW-NE 1/256 sec. cor. of sec. 28.
	<hr/> <p>From the point for the C-S-SW-NE 1/256 sec. cor. of sec. 28.</p> <p>S. 89°16' W., on the E-W centerline of the SW¼SW¼NE¼ of sec. 28.</p> <p>Over nearly level land, through moderate timber.</p>
2.90	Fence, bears S. 20° E. and N. 20° W.
3.50	Graded road, Forest Service No. 281, bears S. 20° W. and N. 30° W.
5.005	The SW-SW-NE 1/256 sec. cor. of sec. 28.
	Leave timber; enter open meadow, bears N. and S.
6.30	Fence, bears S. 85° E. and N. 85° W.
9.85	Fence, bears S. 5° E. and N. 5° W.
10.01	The C-S-S-N 1/256 sec. cor. of sec. 28.
	<hr/> <p style="text-align: center;">Subdivision of SE¼ of Section 28</p> <hr style="width: 20%; margin: auto;"/> <p>From the E 1/16 sec. cor. of secs. 28 and 33.</p> <p>N. 0°18' W., on the N-S centerline of the SE¼ of sec. 28.</p> <p>Over gently rolling land, through moderate timber.</p>
20.04	<p>Point for the SE 1/16 sec. cor. of sec. 28, at intersection with the E-W centerline of the SE¼ of sec. 28.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S28 SE 1/16 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 26° W., 42 lks. dist., mkd. SE 1/16 S28 BT.</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
	Raise a mound of stone W. of the corner.
30.06	Point for the C-N-SE 1/64 sec. cor. of sec. 28; not monumented.
35.075	Point for the C-N-N-SE 1/256 sec. cor. of sec. 28.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	S28 C-N-N-SE 1/256 1969
	from which
	A pine, 10 ins. diam., bears S. 67½° W., 27 lks. dist., mkd. CNNSE 1/256 S28 BT.
	A pine, 10 ins. diam., bears N. 58½° W., 30 lks. dist., mkd. CNNSE 1/256 S28 BT.
37.80	Track road, bears S. 80° E. and N. 80° W.
38.30	Fence, bears S. 80° E. and N. 80° W.; enter open meadow.
40.09	The point for the C-E 1/16 sec. cor. of sec. 28.
	From the S 1/16 sec. cor. of secs. 27 and 28.
	S. 89°21' W., on the E-W centerline of the SE¼ of sec. 28.
	Over gently rolling land, through moderate timber.
0.50	Track road, bears S. 10° E. and N. 10° W.
1.30	Fence, bears irregularly N. and S.
1.80	Along S. shore of a small lake, bears N. and W.
3.80	Leave S. shore of a small lake, bears E. and NW.
5.20	Fence, bears irregularly N. and S.
5.70	Track road, bears S. 20° E. and N. 20° W.
9.94	Point for the C-E-SE 1/64 sec. cor. of sec. 28; not monumented.
19.88	The SE 1/16 sec. cor. of sec. 28.
32.60	Graded road, Forest Service No. 281, bears S. 25° E. and N. 35° W.
33.30	Powerline, bears S. 26° E. and N. 26½° W.
39.10	Graded road, Forest Service No. 281C, bears SE. and NW.
39.76	The C-S 1/16 sec. cor. of sec. 28.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
<p>4.30</p> <p>5.40</p> <p>8.00</p> <p>10.02</p> <p>14.50</p> <p>15.035</p> <p>19.00</p> <p>20.05</p>	<p>From the point for the C-E-SE 1/64 sec. cor. of sec. 28.</p> <p>N. 0°06' W., on the N-S centerline of the NE¼SE¼ of sec. 28.</p> <p>Over gently rolling land, through moderate timber.</p> <p>Track road, bears irregularly E. and W.</p> <p>Fence, bears E. and W.; leave timber, enter open meadow.</p> <p>S. shore of small lake, bears SE. and N. 60° W.</p> <p>Cross lake by triangulation.</p> <p>Point for the NE-SE 1/64 sec. cor. of sec. 28, at intersection with the E-W centerline of the NE¼SE¼ of sec. 28. This point falls in a lake and was not monumented.</p> <p>N. shore of small lake, bears SE. and NW. End of triangulation.</p> <p>Point for the C-N-NE-SE 1/256 sec. cor. of sec. 28; not monumented.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains SE.</p> <p>The point for the C-E-E 1/64 sec. cor. of sec. 28.</p>
<p>9.97</p> <p>11.70</p> <p>13.80</p> <p>14.70</p> <p>14.955</p> <p>19.94</p>	<p>From the point for the N-S 1/64 sec. cor. of secs. 27 and 28.</p> <p>S. 89°17' W., on the E-W centerline of the NE¼SE¼ of sec. 28.</p> <p>Thence across lake.</p> <p>The point for the NE-SE 1/64 sec. cor. of sec. 28.</p> <p>W. shore of small lake, bears S. 30° E. and N. 30° W.</p> <p>Fence, bears SE. and NW.; enter moderate timber.</p> <p>Track road, bears N. and S.</p> <p>Point for the C-W-NE-SE 1/256 sec. cor. of sec. 28; not monumented.</p> <p>The point for the C-N-SE 1/64 sec. cor. of sec. 28.</p>
	<p>From the point for the C-W-NE-SE 1/256 sec. cor. of sec. 28.</p> <p>N. 0°11'30" W., on the N-S centerline of the NW¼NE¼SE¼ of sec. 28.</p> <p>Over gently rolling land, through moderate timber.</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
.1.10	Track road, on a curve, bears S. and N. 70° W.
1.70	Fence, bears SE. and NW.; leave timber, enter open meadow.
5.015	Point for the NW-NE-SE 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 28.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	S28 NW-NE-SE 1/256 1969
	Raise a mound of stone W. of the corner.
	Set a steel fence post 6 ft. long, alongside the iron post.
10.03	The point for the C-W-E-E 1/256 sec. cor. of sec. 28.
	From the point for the C-N-NE-SE 1/256 sec. cor. of sec. 28.
	S. 89°17' W., on the E-W centerline of the NW $\frac{1}{4}$ NE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 28.
	Over nearly level land, across lake area with no defined banks.
3.50	Leave lake area; enter open meadow, bears N. and S.
4.995	The NW-NE-SE 1/256 sec. cor. of sec. 28.
6.90	Fence, bears SE. and NW.; leave meadow, enter moderate timber.
7.80	Track road, bears S. 30° E. and N. 30° W.
9.99	The C-N-N-SE 1/256 sec. cor. of sec. 28.
	Subdivision of SW $\frac{1}{4}$, Section 28
	From the W 1/16 sec. cor. of secs. 28 and 33.
	N. 0°41' W., on the N-S centerline of the SW $\frac{1}{4}$ of sec. 28.
	Over rolling land, through moderate timber.
	Ascend S. slope of ridge bearing E. and W.
12.80	Top of ridge, bears E. and W.; desc. N. slope.
20.02	Point for the SW 1/16 sec. cor. of sec. 28, at intersection with the E-W centerline of the SW $\frac{1}{4}$ of sec. 28.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 SW 1/16 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 36½° E., 49½ lks. dist., mkd. SW 1/16 S28 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 60½° W., 32 lks. dist., mkd. SW 1/16 S28 BT.</p> <p>Raise a mound of stone W. of the corner.</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p>
24.90	Graded road, Forest Service No. 281C, bears E. and W.
29.95	Fence, bears irregularly E. and W.
30.03	Point for the C-N-SW 1/64 sec. cor. of sec. 28; not monumented.
	End of descent; enter open meadow, bears E. and W.
33.00	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains N. 70° E.
35.035	Point for the C-N-N-SW 1/256 sec. cor. of sec. 28; not monumented.
40.04	The point for the C-W 1/16 sec. cor. of sec. 28.
	<p>From the C-S 1/16 sec. cor. of sec. 28.</p> <p>S. 89°21' W., on the E-W centerline of the SW¼ of sec. 28.</p> <p>Over rolling land, through moderate timber.</p> <p>Ascend along a NE. slope.</p>
19.75	The SW 1/16 sec. cor. of sec. 28.
29.63	Point for the C-W-SW 1/64 sec. cor. of sec. 28; not monumented.
39.51	The S 1/16 sec. cor. of secs. 28 and 29.
	<p>From the point for the C-W-SW 1/64 sec. cor. of sec. 28.</p> <p>N. 0°42' W., on the N-S centerline of the NW¼SW¼ of sec. 28.</p> <p>Over rolling land, through moderate timber.</p> <p>Descend N. slope.</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
4.05	Graded road, Forest Service No. 281C, bears E. and W.
9.97	Fence, bears N. 75° E. and S. 75° W.; end of descent, enter open meadow.
9.99	Point for the NW-SW 1/64 sec. cor. of sec. 28, at intersection with the E-W centerline of the NW 1/4 SW 1/4 of sec. 28; not monumented.
12.00	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains N. 60° E.
14.99	Point for the C-N-NW-SW 1/256 sec. cor. of sec. 28. Set the iron post 24 ins. in the ground, brass cap mkd. S28 C-N-NW-SW 1/256 1969
15.90	Fence, bears N. 70° E. and S. 70° W.; leave meadow, enter moderate timber; asc. S. slope.
19.99	The C-W 1/64 sec. cor. of sec. 28.
	From the point for the C-N-SW 1/64 sec. cor. of sec. 28. S. 89°20' W., on the E-W centerline of the NW 1/4 SW 1/4 of sec. 28.
	Over nearly level land, through moderate timber.
4.94	Point for the C-E-NW-SW 1/256 sec. cor. of sec. 28. Set the iron post 22 ins. in the ground, brass cap mkd. S28 C-E-NW-SW 1/256 1969
	Set a fence post 6 ft. long, alongside the iron post.
	The cor. is located 110 lks. S. of a fence bearing N. 70° E. and S. 70° W.
9.88	The point for the NW-SW 1/64 sec. cor. of sec. 28.
10.05	Fence, bears N. 70° E. and S. 70° W.; leave timber, enter open meadow.
14.82	Point for the C-W-NW-SW 1/256 sec. cor. of sec. 28. Set the iron post 24 ins. in the ground, brass cap mkd. S28 C-W-NW-SW 1/256 1969

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
	Set a steel fence post 6 ft. long, alongside the iron post.
15.20	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains N. 50° E.
19.76	The point for the N-S 1/64 sec. cor. of secs. 28 and 29.
	<p>From the C-E-NW-SW 1/256 sec. cor. of sec. 28.</p> <p>N. 0°41' W., on the N-S centerline of the NE$\frac{1}{4}$NW$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, across open meadow.</p> <p>1.10 Fence, bears N. 70° E. and S. 70° W.</p> <p>2.50 Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains N. 70° E.</p> <p>5.002 Point for the NE-NW-SW 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the NE$\frac{1}{4}$NW$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 28.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 NE-NW-SW 1/256 1969</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <p>8.40 Fence, bears N. 70° E. and S. 70° W.; leave open meadow, enter moderate timber.</p> <p>10.004 The C-E-W-W 1/256 sec. cor. of sec. 28.</p>
	<p>From the point for the C-N-N-SW 1/256 sec. cor. of sec. 28.</p> <p>S. 89°18'30" W., on the E-W centerline of the NE$\frac{1}{4}$NW$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, through open meadow.</p> <p>4.94 The NE-NW-SW 1/256 sec. cor. of sec. 28.</p> <p>9.88 The C-N-NW-SW 1/256 sec. cor. of sec. 28.</p>
	<p>From the C-W-NW-SW 1/256 sec. cor. of sec. 28.</p> <p>N. 0°42'30" W., on the N-S centerline of the NW$\frac{1}{4}$NW$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, across open meadow.</p>

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
0.50	Long Cienega Wash, 5 lks. wide, 1 ft. deep, drains N. 50° E.
4.00	Fence, bears N. 70° E. and S. 70° W.; leave meadow, enter moderate timber.
5.00	Point for the NW-NW-SW 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 28.
	Set the iron post 12 ins. in the ground, mound of stone to top, brass cap mkd.
	S28 NW-NW-SW 1/256 1969
	from which
	A pine, 8 ins. diam., bears N. 11° E., 32 lks. dist., mkd. NWNWSW 1/256 S28 BT.
	A pine, 10 ins. diam., bears S. 53° W., 20 $\frac{1}{2}$ lks. dist., mkd. NWNWSW 1/256 S28 BT.
	Set a steel fence post 6 ft. long, alongside the iron post.
10.00	The point for the C-W-W-W 1/256 sec. cor. of sec. 28.
	From the C-N-NW-SW 1/256 sec. cor. of sec. 28. S. 89°18'30" W., on the E-W centerline of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 28.
	Over gently rolling land, through moderate timber.
1.90	Fence, bears N. 70° E. and S. 70° W.
4.94	The NW-NW-SW 1/256 sec. cor. of sec. 28.
9.88	The point for the N-N-S 1/256 sec. cor. of secs. 28 and 29.
	Subdivision of NW $\frac{1}{4}$, Section 28
	From the point for the C-W 1/16 sec. cor. of sec. 28. N. 0°41' W., on the N-S centerline of the NW $\frac{1}{4}$ of sec. 28.
	Over gently rolling land, across open meadow.
0.98	Fence, bears NE. and SW.; leave meadow, enter moderate timber.
2.00	NE. cor. of abandoned log cabin, bears E., 18 lks. dist.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
5.01	Point for the C-S-S-NW 1/256 sec. cor. of sec. 28; not monumented.
7.70	Fence, bears E. and W.
9.00	Track road, bears N. 75° E. and S. 75° W.
10.02	Point for the C-S-NW 1/64 sec. cor. of sec. 28; not monumented.
20.04	Point for the NW 1/16 sec. cor. of sec. 28, at intersection with the E-W centerline of the NW 1/4 of sec. 28. Set the iron post 22 ins. in the ground, brass cap mkd.
	S28 NW 1/16 1969
	from which
	A pine, 12 ins. diam., bears N. 64 3/4° E., 79 lks. dist., mkd. NW 1/16 S28 BT.
	A pine, 12 ins. diam., bears N. 68 1/2° W., 105 lks. dist., mkd. NW 1/16 S28 BT.
	Set a steel fence post 6 ft. long, alongside the iron post.
22.40	Fence, bears S. 70° E. and N. 70° W.; leave timber, enter open meadow.
23.90	Power line, bears S. 58° E. and N. 58° W.
27.80	Fence, bears S. 60° E. and N. 60° W.; leave meadow, enter moderate timber.
28.80	Graded road, Forest Service No. 281, bears S. 60° E. and N. 60° W.
	Ascend S. slope of ridge, bears E. and W.
33.30	Fence, bears S. 60° E. and N. 60° W.
40.08	The W 1/16 sec. cor. of secs. 21 and 28.
	From the C-N 1/16 sec. cor. of sec. 28.
	S. 89°09' W., on the E-W centerline of the NW 1/4 of sec. 28.
	Over nearly level land, through moderate timber.
0.40	Fence, bears S. 30° E. and N. 30° W.
0.90	Graded road, Forest Service No. 281, bears S. 30° E. and N. 30° W.
1.30	Fence, bears S. 30° E. and N. 30° W.
8.30	Wash, 5 lks. wide, 1 ft. deep, drains S. 60° E.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
9.89	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 28.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 C-E-NW 1/64 1969</p>
13.30	Set a steel fence post 6 ft. long, alongside the iron post.
14.60	Power line, bears S. 26° E. and N. 58° W.
14.60	Fence, bears S. 60° E. and N. 60° W.
19.78	The NW 1/16 sec. cor. of sec. 28.
29.67	Ascend moderate NE. slope of a ridge, bearing SE. and NW. Point for the C-W-NW 1/64 sec. cor. of sec. 28; not monumented.
39.56	The N 1/16 sec. cor. of secs. 28 and 29.
7.90	<p>From the point for the C-E-W 1/64 sec. cor. of sec. 28.</p> <p>N. 0°40' W., on the N-S centerline of the SE$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28.</p> <p>Over nearly level land, across open meadow.</p> <p>Fence, bears E. and W.; leave meadow, enter moderate timber.</p>
10.03	Point for the SE-NW 1/64 sec. cor. of sec. 28; not monumented.
11.60	Track road, bears N. 70° E. and S. 70° W.
13.15	Power line, bears S. 26° E. and N. 26° W.
15.045	<p>Point for the C-N-SE-NW 1/256 sec. cor. of sec. 28.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 C-N-SE-NW 1/256 1969</p>
18.30	<p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <p>The cor. is located 89 lks. E. of a powerline, bearing S. 26° E. and N. 26° W.</p> <p>Fence, bears S. 70° E. and N. 70° W.</p>
20.06	The C-E-NW 1/64 sec. cor. of sec. 28.

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
<p>From the point for the C-S-N 1/64 sec. cor. of sec. 28. S. 89°13' W., on the E-W centerline of the SE$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28. Over gently rolling land, through scattered timber.</p> <p>1.60 Power line, bears N. 70° E. and S. 70° W.</p> <p>8.30 Power line, bears S. 26° E. and N. 26° W.</p> <p>9.885 The point for the SE-NW 1/64 sec. cor. of sec. 28.</p> <p>16.00 Track road, bears N. 70° E. and S. 70° W.</p> <p>19.77 The point for the C-S-NW 1/64 sec. cor. of sec. 28.</p>	
<p>From the C-W-W 1/64 sec. cor. of sec. 28. N. 0°42' W., on the N-S centerline of the SW$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28. Over gently rolling land, through moderate timber.</p> <p>1.70 Track road, bears NE-SW.</p> <p>5.005 Point for the C-S-SW-NW 1/256 sec. cor. of sec. 28; not monumented.</p> <p>10.01 Point for the SW-NW 1/64 sec. cor. of sec. 28, at intersection with the E-W centerline of the SW$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28; not monumented.</p> <p>20.03 The point for the C-W-NW 1/64 sec. cor. of sec. 28.</p>	
<p>From the point for the C-S-NW 1/64 sec. cor. of sec. 28. S. 89°11' W., on the E-W centerline of the SW$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28. Over gently rolling land, through moderate timber.</p> <p>4.945 Point for the C-E-SW-NW 1/256 sec. cor. of sec. 28; not monumented.</p> <p>9.89 The point for the SW-NW 1/64 sec. cor. of sec. 28.</p> <p>19.78 The point for the S-N 1/64 sec. cor. of secs. 28 and 29.</p>	
<p>From the C-E-W-W 1/256 sec. cor. of sec. 28. N. 0°41'30" W., on the N-S centerline of the SE$\frac{1}{4}$SW$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28. Over gently rolling land, through moderate timber.</p> <p>5.005 Point for the SE-SW-NW 1/256 sec. cor. of sec. 28, at intersection with the E-W centerline of the SE$\frac{1}{4}$SW$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28.</p>	

Subdivision of Section 28, T. 5 N., R. 31 E.

CHAINS	
10.01	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S28 SE-SW-NW 1/256 1969</p> <p>Set a steel fence post 6 ft. long, alongside the iron post.</p> <p>The cor. is located 18 lks. W. of a track road, bearing NE. and S.</p> <p>The point for the C-E-SW-NW 1/256 sec. cor. of sec. 28.</p>
1.80 4.80 4.945 9.89	<p>From the point for the C-S-S-NW 1/256 sec. cor. of sec. 28.</p> <p>S. 89°14' W., on the E-W centerline of the SE$\frac{1}{4}$SW$\frac{1}{4}$NW$\frac{1}{4}$ of sec. 28.</p> <p>Over gently rolling land, across open meadow.</p> <p>Fence, bears N. and S.; leave meadow, enter moderate timber.</p> <p>Track road, bears NE. and S.</p> <p>The SE-SW-NW 1/256 sec. cor. of sec. 28.</p> <p>The point for the C-S-SW-NW 1/256 sec. cor. of sec. 28.</p>
General Description	
<p>The center of section 28, Township 5 North, Range 31 East, lies 5 miles southeast of Alpine, Arizona and 2 miles south of Luna Lake. The elevation in section 28 ranges from 7,800 to 8,200 ft. above sea level.</p> <p>There is a moderate growth of timber throughout the section, consisting of pine, juniper and oak. There is a good growth of bunchgrass. The soil in the section is rocky clay loam. There is one small lake south of the $\frac{1}{4}$ sec. corner of sections 27 and 28.</p> <p>There is good access to this section from U.S. Highway 260. The main road is a maintained bladed road entering the section at the northwest corner and leaving the section at the $\frac{1}{4}$ section corner of sections 28 and 33. The drainage is to the southeast and southwest.</p> <p>There are a few cabins in the center of the section, being occupied in season.</p> <p>The primary use in this section is grazing.</p>	

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Ira M. Thiessen	Cadastral Surveyor
Ronald G. Williams	Cadastral Surveyor
Martin W. Fuller	Survey Aid
Victor E. Templeton	Survey Aid
Doyle L. Herbert	Survey Aid
David M. Dettmer	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~We~~, Gary T. Oviatt, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of May, 19 69, (I) ~~We~~ have made a dependent resurvey of the boundaries and survey of the subdivisions in section 28, Township 5 North, Range 31 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~us~~ and under (my) ~~our~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 10, 1970
(Date)

Gary T. Oviatt
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JAN 19 1971

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of the boundaries and survey of the subdivisions in Section 28, Township 5 North, Range 31 East, Gila and Salt River Meridian, Arizona,

executed by Gary T. Oviatt, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

FEB 14 1972
(Date)

Clark F. Summ
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____ is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) GPO 849 - 626

1A

BOOK 4913

INDEX DIAGRAM

Township 5 North, Range 31 East,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21 11	22	23	24
30	29 7	28	2 27	26	25
31	32	4 33	34	35	36

- Subdivision of sec. 28 ----- Page 13
- Subdivision of NE $\frac{1}{4}$, sec. 28 ----- Page 17
- Subdivision of SE $\frac{1}{4}$, sec. 28 ----- Page 24
- Subdivision of SW $\frac{1}{4}$, sec. 28 ----- Page 27
- Subdivision of NW $\frac{1}{4}$, sec. 28 ----- Page 31