

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY

OF THE

EAST AND WEST BOUNDARIES

AND A

PORTION OF THE NORTH BOUNDARY

AND

SUBDIVISIONAL LINES

AND

SURVEY

OF

SUBDIVISIONS IN CERTAIN SECTIONS,

TOWNSHIP 13 SOUTH, RANGE 29 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Gary T. Oviatt, Cadastral Surveyor

Under special instructions dated November 20, 19 68, which provided for the surveys
included under Group Number 465, approved November 21, 1968,
and assignment instructions dated November 21, 19 68.

Survey commenced December 9, 19 68

Survey completed May 5, 19 69

177

BOOK 4922

INDEX DIAGRAM

Township 13 South, Range 29 East 12

12	6 53 52	5 42 52	4 35 41	3 27 34	2 20 26	1 5 19
10	7 50 50	8 40 49	9 34 39	10 26 33	11 19 25	12 5 18
10	18 48 47	17 38 47	16 32 38	15 24 32	14 17 23	13 4
8	19 46 45	20	21 31 37	22 23 30	23 16 22	24 3 16
7	30 44 44	29 37	28 29 36	27 22 29	26 15 21	25 2 14
6	31 43	32 35	33 28	34 20	35 13	36 1

- Subdivision of sec. 1 -- Page 53
- " " " 4 -- Page 55
- " " " 5 -- Page 56
- " " " 7 -- Page 57
- " " " 8 -- Page 58
- " " " 10 -- Page 60
- " " " 14 -- Page 60
- " " " 15 -- Page 62
- " " " 17 -- Page 64
- " " " 19 -- Page 64
- " " " 25 -- Page 67
- " " " 27 -- Page 68

Township 13 South, Range 29 East
Gila and Salt River Meridian, Arizona

CHAINS

The west boundary was surveyed in 1882 by T. F. White. The south, east and north boundaries and subdivisional lines were surveyed in 1883 by R. C. Powers. The north boundary was retraced in 1884 by L. Wolfley. The south boundary was resurveyed in 1913 by J. F. Hesse. The north boundary was resurveyed in 1963 by Paul Bauer.

The following notes are those of a dependent resurvey of the east and west boundaries, a portion of the north boundary and a portion of the subdivisional lines, designed to restore the corners in their true original location according to the best available evidence, and a survey of subdivisions in certain sections.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated November 20, 1968.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Each corner was monumented with a standard iron post 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of the township is: Latitude 32°14'58.5" North and Longitude 109°19'46.6" West, as determined by traverse from USC&GS Triangulation Station "OLGA" located in section 14.

The mean magnetic declination was found to be: 13½° East.

Dependent Resurvey, East Boundary
Township 13 South, Range 29 East

Reestablishment of the Survey executed
by R. C. Powers in 1883

Beginning at the cor. of Tps. 13 and 14 S., Rs. 29 and 30 E., monumented by an iron post 3 ins. diam., projecting 8 ins. above the ground, brass cap mkd.

T13S
R29E S36 | S31 R30E
S 1 | S 6
T14S
1913

The cor. is located at a fence cor.; fences bear S., W. and N. 2° W.

N. 2°03' W., bet. secs. 31 and 36.

Over nearly level land, through moderate undergrowth; along the W. side of a track road bearing N. 2° W.

40.26

Point for the ½ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the

Dep. Res., East Boundary, T. 13 S., R. 29 E.

CHAINS		
80.52	<p>orig. cor.; not monumented. This cor. point is located 2 lks. East of a fence bearing S. 2° E. and N. 2° W.</p> <p>The cor. of secs. 25, 30, 31 and 36, monumented by an old wooden stake, 2 x 2 x 24 ins., set 12 ins. in the ground, located at a fence cor.; fences bear S. 2° E., and bears NW. for 63 lks., thence N. and SW. This position has long been recognized as the cor. by adjacent land owners, and is accepted as the best existing evidence of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E R30E S25 S30 S36 S31 1968</p> </div> <p>Bury the wooden stake alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cat claw and grass.</p>	
0.30 19.60 20.01 40.02	<p>N. 0°18' W., bet. secs. 25 and 30.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Track road, bears S. 2° E. and W.</p> <p>Field Dyke, bears E. and W.</p> <p>Point for the S 1/16 sec. cor. of secs. 25 and 30, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E R30E S 1/16 S25 S30 1968</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears West, 75 lks. dist.; fences bear N. and W.</p> <p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>Point for the 1/2 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E R30E 1/2 S25 S30 1968</p> </div>	

Dep. Res., East Boundary, T. 13 S., R. 29 E.

CHAINS	
	<p>Set a wooden post, 2 x 4 ins. squared, 6 ft. long, alongside the iron post.</p> <p>The cor. is located 67 lks. East of a fence bearing N. and S.</p>
60.03	<p>Point for the N 1/16 sec. cor. of secs. 25 and 30, at proportionate dist.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E R30E N 1/16 S25 S30 1968</p>
	<p>Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p> <p>The cor. is located 53 lks. East of a fence bearing N. and S.</p>
80.04	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a concrete post, 4 ins. square, projecting 20 ins. above the ground, with a metal tag attached to the S. face, mkd. SEC COR 19 24 25 30. The monument is located at a fence cor.; fences bear N. 1°47' E., E. and W. This cor. position has long been recognized as the cor. by adjacent land owners and is accepted as the best existing evidence of the position of the orig. cor.; not remonumented.</p>
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cat claw and grass.</p>
	<p>N. 0°21' E., bet. secs. 19 and 24.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
2.00	<p>Enter cultivated field, bears N. 1°50' E. and W.</p>
40.32	<p>Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented. This point is located 100 lks. West of a fence bearing N. 1°47' E. and S. 1°47' W.</p>
65.00	<p>Underground telephone line, bears S. 75° E. and N. 75° W.</p>
70.60	<p>Power line, bears S. 75° E. and N. 75° W.</p>
70.70	<p>Right-of-way fence, bears S. 75° E. and N. 75° W.; leave cultivated field; enter moderate undergrowth.</p>
72.20	<p>Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.</p>
73.90	<p>Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.</p>

Dep. Res., East Boundary, T. 13 S., R. 29 E.

CHAINS	
75.90	State Highway 86, bears S. 75° E. and N. 75° W.
78.40	Telegraph line, bears S. 75° E. and N. 75° W.
79.10	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
79.50	Graded road, bears S. 75° E. and N. 75° W.
79.80	Telephone line, bears S. 75° E. and N. 75° W.
80.50	Right-of-way fence, bears S. 75° E. and N. 75° W.
80.64	The cor. of secs. 13, 18, 19 and 24, monumented by an iron post 2½ ins. diam., projecting 4 ins. above the ground, brass cap mkd.
	T13S R29E R30E <u>S13</u> <u>S18</u> <u>S24</u> <u>S19</u> 1963
	A concrete post, 4 ins. square, is alongside the iron post.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, grass and scattered cat claw.
	N. 0°21' E., bet. secs. 13 and 18.
	Over nearly level land, through moderate undergrowth.
0.10	Drainage ditch, drains S. 75° E.
0.80	Track road, bears S. 75° E. and N. 75° W.
1.10	Power line, bears S. 75° E. and N. 75° W.
12.00	Telephone line, bears S. 75°30' E. and N. 75°30' W.
41.08	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
79.90	Track road, bears N. 65° E. and S. 65° W.
82.16	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13S R29E R30E <u>S12</u> <u>S 7</u> <u>S13</u> <u>S18</u> 1968
	Set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.

Dep. Res., East Boundary, T. 13 S., R. 29 E.

CHAINS

Land, nearly level.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cat claw and grass.

N. 0°21' E., bet. secs. 7 and 12.

Over nearly level land, through moderate undergrowth.

41.08 Point for the $\frac{1}{2}$ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R29E R30E
 $\frac{1}{2}$
S12 | S 7
1968

Set a wooden post, 4 x 6 ins. squared, 3 ft. long, alongside the iron post.

43.20 Earth dyke for erosion control, bears SE. and SW.

81.00 Fence, bears E. and W.

82.16 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R29E R30E
S 1 | S 6
S12 | S 7
1968

from which

A fence cor., bears S. 23° E., 128 lks. dist.;
fences bear N., E. and W.

Set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.

Land, nearly level.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cat claw and grass.

N. 0°21' E., bet. secs. 1 and 6.

Over nearly level land, through low undergrowth.

41.08 Point for the $\frac{1}{2}$ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res., East Boundary, T. 13 S., R. 29 E.

CHAINS

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R29E R30E
1/2
S 1 | S 6
1968

Set a wooden post, 2 x 4 ins. squared, 5 ft. long, alongside the iron post.

The cor. is located 26 lks. West of a N. and S. fence.

61.62

Point for the N 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.

Set the iron post 21 ins. in the ground, brass cap mkd.

T13S
R29E R30E
N 1/16
S 1 | S 6
1968

Set a wooden post, 2 x 5 ins. squared, 4 ft. long, alongside the iron post.

The cor. is located 13 lks. West of a N. and S. fence.

82.16

The cor. of Tps. 12 and 13 S., Rs. 29 and 30 E., monumented by an iron post 2 1/2 ins. diam., projecting 16 ins. above the ground, brass cap mkd.

T12S
R29E R30E
S36 | S31
S 1 | S 6
T13S
1963

The cor. is located under a N. and S. fence.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, grass and scattered cat claw.

Dependent Resurvey, West Boundary
Township 13 South, Range 29 East

Reestablishment of the Survey executed
by T. F. White in 1882

From the cor. of Tp. 13 S., Rs. 28 and 29 E., monumented by an iron post 3 ins. diam., projecting 10 ins. above the ground, brass cap mkd.

T13S
R28E | R29E
S36 | S31
S 1 | S 6
R28E R29E
T14S
1914

Dep. Res., West Boundary, T. 13 S., R. 29 E.

CHAINS	
	N. 0°02' E., bet. secs. 31 and 36.
	Over nearly level land, through scattered undergrowth.
40.17	The $\frac{1}{2}$ sec. cor. of secs. 31 and 36, as determined from a wooden stake, 2 x 2 x 24 ins., set 5 ins. in the ground, originally set in a pit 5 $\frac{1}{2}$ ft. North of the cor.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13S R28E R29E $\frac{1}{2}$ S36 S31 1969
	Bury the wooden stake and set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.
	N. 0°30' E., beginning new measurement.
	Over nearly level land.
1.60	Wash, 10 lks. wide, 1 ft. deep, drains NE.
40.17	The cor. of secs. 25, 30, 31 and 36, monumented by a water pipe, 1 in. diam., projecting 4 ins. above the ground, with a charred stake, 1 x 1 x 20 ins., set alongside. This position has been recognized by local land owners as the cor. position and is accepted as the best existing evidence of the position of the orig. cor.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13S R28E R29E S25 S30 S36 S31 1969
	Bury the water pipe and the wooden stake and set a wooden post, 4 ins. square, 4 $\frac{1}{2}$ ft. long, alongside the iron post.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered cat claw.
	N. 0°01' W., bet. secs. 25 and 30.
	Over nearly level land, through scattered undergrowth.
20.10	Wash, 30 lks. wide, 1 ft. deep, drains NE.
40.24	Point for the $\frac{1}{2}$ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res., West Boundary, T. 13 S., R. 29 E.

CHAINS		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R28E R29E ½ S25 S30 1969</p> <p>Set a round wooden post, 2 ins. diam., 3 ft. long, alongside the iron post.</p>	
74.80	Underground gas line, bears E. and W.	
80.20	Track road, bears S. 79° E. and N. 79° W.	
80.48	<p>The cor. of secs. 19, 24, 25 and 30, monumented by a concrete post, 4 ins. square, projecting 4 ins. above the ground and with a water pipe 1 in. diam. and a steel fence post alongside. This position has long been recognized by local land owners and is accepted as the best existing evidence of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R28E R29E S24 S19 S25 S30 1969</p> <p>from which</p> <p style="padding-left: 40px;">The SW. cor. fence post of a fence surrounding a natural gas pumping station, bears N. 77°15' E., 135 lks. dist.</p> <p>Set the concrete post, the water pipe and the steel fence post alongside the iron post.</p> <p>Raise a mound of stone W. of the corner.</p> <p>The cor. is located 45 lks. NW. of intersection of track roads, bearing N., S. 79° E. and N. 79° W.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered cat claw and grass.</p>	
	<p>North, bet. secs. 19 and 24.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
28.00	Wash, 20 lks. wide, 1 ft. deep, drains NE.	
40.26	<p>The ½ sec. cor. of secs. 19 and 24, monumented by a concrete post, 4 ins. square, projecting 9 ins. above the ground. This position has long been recognized by local land owners and is accepted as the best existing evidence of the position of the orig. cor.</p>	

Dep. Res., West Boundary, T. 13 S., R. 29 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R28E R29E
 $\frac{1}{2}$
S24 | S19
1969

Bury the cement post alongside the iron post.

The cor. is located on the W. side of a track road, bearing N. and S.

 N. 0°17' E., beginning new measurement.

Over nearly level land.

20.05 Point for the N 1/16 sec. cor. of secs. 19 and 24, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R28E R29E
N 1/16
S24 | S19
1969

Set a wooden post, 2 ins. diam., 4 ft. long, alongside the iron post.

32.80 Underground gas line, bears S. 86° E. and N. 86° W.

39.50 Wash, 20 lks. wide, 1 ft. deep, drains E.

39.80 Power line, bears W. and E., 45 lks. dist.; thence N.

39.90 Earth dyke for erosion control, bears E. and W.

40.10 The point for the cor. of secs. 13, 18, 19 and 24 is adjacent to a fence cor.; fences bear N. and W. This point was shown me by interested property owners and is accepted as the best available evidence of the position of the orig. cor.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R28E R29E
S13 | S18
S24 | S19
1969

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, cat claw and grass.

Dep. Res., West Boundary, T. 13 S., R. 29 E.

CHAINS	
	N. 0°20' W., bet. secs. 13 and 18. Over nearly level cultivated land.
38.70	Fence cor., bears East, 11 lks. dist.; fences bear E. and S.
39.70	Field dyke, bears E. and W.
40.03	Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist., falls in a graded road, bears E. and W.; there is no remaining evidence of the orig. cor. Set the iron post 45 ins. below the surface of the ground, brass cap mkd. <div style="text-align: center;"> T13S R28E R29E ¼ S13 S18 1969 </div> from which An iron post, set 24 ins. in the ground, for a reference monument, bears S. 45° E., 45.5 lks. dist., with brass cap mkd. T13S R29E S18 RM 30 FT 1969 and an arrow pointing to the cor. Set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post. An iron post, set 24 ins. in the ground, for a reference monument, bears S. 0°20' E., 30.3 lks. dist., with the brass cap mkd. T13S R28E R29E S13 S18 RM 20 FT 1969 and an arrow pointing to the cor. Set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post.
40.30	Concrete lined irrigation ditch, bears E. and W.
60.10	Graded road, bears E. and W.
60.40	Concrete lined irrigation ditch, bears E. and W.
79.30	Graded road, bears E. and W.
79.60	Field dyke, bears E. and W.
79.90	Fence, bears N. 87° E. and S. 87° W.; leave cultivated field, enter moderate undergrowth.
80.06	Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented. Land, nearly level. Soil, sandy clay loam. No timber; no undergrowth.
	N. 0°20' W., bet. secs. 7 and 12. Over nearly level land, through moderate undergrowth.

Dep. Res., West Boundary, T. 13 S., R. 29 E.

CHAINS	
22.80	Power line, bears S. 75° E. and N. 75° W.
22.90	Right-of-way fence, bears S. 75° E. and N. 75° W.
23.80	Frontage road, bears S. 75° E. and N. 75° W.
24.80	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
26.50	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
27.60	Right-of-way fence, bears S. 75° E. and N. 75° W.
28.60	State Highway 86, bears S. 75° E. and N. 75° W.
31.00	Telegraph line, bears S. 75° E. and N. 75° W.
31.70	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
32.30	Telephone line, bears S. 75° E. and N. 75° W.
33.40	Right-of-way fence, bears S. 75° E. and N. 75° W.
33.80	Graded road, bears S. 75° E. and N. 75° W.
34.40	Power line, bears S. 75° E. and N. 75° W.
40.03	The $\frac{1}{2}$ sec. cor. of secs. 7 and 12, monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 6 ins. above the ground, brass cap mkd.
	<p style="text-align: center;">T13S R28E R29E $\frac{1}{2}$ S12 S 7 1963</p>
	<p>This cor. was set in 1963 under group 378 and was inadvertently omitted from the field note record. The original wooden stake dimly mkd. was found deposited alongside the iron post; this cor. is therefore accepted and I stamp 1969 on the brass cap.</p>
	<p>from which</p>
	<p>USC&GS Triangulation Station "COTTON", bears S. 83°19' W., 26.33 chs. dist., monumented by a standard brass cap set in a cement block, 12 ins. square, projecting 4 ins. above the ground, mkd. COTTON 1960.</p>
	<p>An elevation station, bears S. 0°8' E., 9.86 chs. dist., monumented by a tablet 3 ins. diam., set in a concrete block, projecting 6 ins. above the ground, mkd. Elev. 3691.72 STA. 3543 + 44.46 1962.</p>
	<p style="text-align: center;">—————</p> <p>N. 0°23' E., beginning new measurement.</p>
	<p>Over nearly level land.</p>
2.90	Track road, bears S. 10° E. and N.; thence along roadway.

Dep. Res., West Boundary, T. 13 S., R. 29 E.

CHAINS

- 35.20 Track road, bears S., NE. and NW.
 - 37.80 Fence, bears E. and W.
 - 40.11 Point for the cor. of secs. 1, 6, 7 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.
- Set the iron post 24 ins. in the ground, brass cap mkd.

T13S
R28E R29E
S 1 | S 6
S12 | S 7
1969

from which

A well, bears N. 69°37' E., 2.58 chs. dist.

Set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.

Land, nearly level.
Soil, sandy clay loam.
No timber; Undergrowth, cat claw and grass.

N. 0°23' E., bet. secs. 1 and 6.
Over nearly level land, through moderate undergrowth.

- 1.70 Fence, bears E. and W.
- 19.80 Track road, bears E. and S. 20° W.
- 20.20 Fence, bears E. and W.
- 40.11 Point for the ¼ sec. cor. of secs. 1 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
- 80.22 The cor. of Tps. 12 and 13 S., Rs. 28 and 29 E., monumented by an iron post 2½ ins. diam., projecting 4 ins. above the ground, with a wooden post, 4 ins. square, set alongside and projecting 4 ft. above the ground, brass cap mkd.

T12S
R28E R29E
S36 | S31
S 1 | S 6
T13S
1963

Land, nearly level.
Soil, sandy clay loam.
No timber; Undergrowth, creosote bush, cat claw and grass.

Dependent Resurvey, Portion North Boundary
Township 13 South, Range 29 East

Dep. Res., Portion North Bdy., T. 13 S., R. 29 E.

CHAINS

Reestablishment of the Survey executed
by Paul Bauer in 1963

From the cor. of Tps. 12 and 13 S., Rs. 29 and 30 E.
N. 88°57' W., bet. secs. 1 and 36.

Over nearly level land, through moderate undergrowth.

20.02 Point for the E 1/16 sec. cor. of secs. 1 and 36, at
proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T12S R29E
E 1/16 $\frac{S36}{S 1}$
T13S
1968

Set a wooden post, 4 ins. square, 3 ft. long, alongside
the iron post.

40.04 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented by an iron
post 2 $\frac{1}{2}$ ins. diam., projecting 10 ins. above the ground,
brass cap mkd.

T12S R29E
 $\frac{1}{4}$ $\frac{S36}{S 1}$
T13S
1963

Dependent Resurvey, Portion Subdivisional Lines
Township 13 South, Range 29 East

Reestablishment of the Survey executed
by R. C. Powers in 1883

From the cor. of secs. 35 and 36 only, on the S. bdy. of
the Tp., monumented by an iron post 3 ins. diam., pro-
jecting 8 ins. above the ground, brass cap mkd.

T13S
R29E $\frac{S35}{S 2} \frac{S36}{S 1}$
T14S
1913

The cor. is located at a cor. of fences, bearing NE.,
E. and W.

N. 1°28' W., bet. secs. 35 and 36.

Over nearly level land, through moderate undergrowth.

39.95 Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at propor-
tionate dist.; there is no remaining evidence of the
orig. cor.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S35 S36 1969</p> <p>Set a wooden post, 2 ins. square, 5 ft. long, alongside the iron post.</p> <p>79.70 Field dyke, bears E. and W.</p> <p>79.90 The point for the cor. of secs. 25, 26, 35 and 36, is adjacent to a fence cor.; fences bear N. 0°14' E. and N. 89°33' E. This point was shown me by interested property owners and is accepted as the best available evidence of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E <u>S26 S25</u> <u>S35 S36</u> 1969</p> <p>from which</p> <p style="padding-left: 40px;">A well with a pump operated by a gas engine, bears N. 26° E., 320 lks. dist. The water is used for irrigation.</p> <p>Deposit glass at the base of the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89°32' W., bet. secs. 25 and 36.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>0.30 Along the south side of a track road, bearing E. and W.</p> <p>0.80 Fence, bears NE. and SW.</p> <p>42.13 The point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36 is located at a cor. of fences; fences bear N. 0°35' E. and S. 89°33' W. This point was shown me by interested property owners and is accepted as the best available evidence of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ <u>S25</u> S36 1969</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>S. 89°33' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>Enter cultivated field, bears N. and W.; thence along a fence bearing S. 89°33' W.</p>
40.13	<p>The cor. of secs. 25, 26, 35 and 36.</p> <p>Land, nearly level.</p> <p>Soil, sandy clay loam.</p> <p>No timber; Undergrowth, creosote and cat claw, 1st half.</p>
	<p>N. 0°14' E., bet. secs. 25 and 26.</p> <p>Over nearly level land.</p> <p>Enter cultivated field, bears N. and E.; thence alongside a graded road, bearing N.</p>
39.20	<p>Drainage ditch, drains E.</p>
39.70	<p>Field dyke, bears E. and W.; enter moderate undergrowth.</p>
39.89	<p>The point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26, is located at a cor. of fences; fences bear S. 0°14' W., W. and N. 1°46' W. This point was shown me by interested property owners and is accepted as the best available evidence of the orig. cor. position.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E $\frac{1}{4}$ S26 S25 1969</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0°24' E., beginning new measurement.</p> <p>Over nearly level land, through moderate undergrowth.</p>
0.10	<p>Graded road, bears E., S. and W.</p>
40.90	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A fence cor., bears N. 65°13' W., 143 lks. dist.; fences bear E., S. 1°46' E. and N. 1°46' W.</p>
	<p style="padding-left: 40px;">A fence cor., bears N. 56°50' W., 155 lks. dist.; fences bear S. 1°46' E. and S. 89° W.</p>
	<p>Land, nearly level.</p> <p>Soil, sandy clay loam.</p> <p>No timber; Undergrowth, creosote and cat claw, 2nd half.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp.
	N. 88°58' W., bet. secs. 24 and 25.
	Over nearly level land alongside an E. and W. fence.
0.40	Fence cor.; fences bear E., S. and N. 89° W.
34.60	Track road, bears SE. and NW.
41.00	Concrete irrigation ditch, bears E. and S.
41.41	The ¼ sec. cor. of secs. 24 and 25, monumented by a concrete post, 4 ins. square, projecting 2 ins. above the ground. This has long been recognized as the cor. position by local land owners and is accepted as the best available evidence of the orig. cor. position; not re-monumented. The cor. is located under a fence bearing S. 89° E. and W.
	<hr/> S. 89°04' W., beginning new measurement.
	Over nearly level land, through scattered undergrowth.
0.30	Graded road, bears N. and S. and W.; thence, along the S. side of graded road.
40.01	The point for the cor. of secs. 23, 24, 25 and 26. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered cat claw.
	N. 0°58' W., bet. secs. 23 and 24.
	Over nearly level land, through scattered undergrowth.
0.60	Fence, bears E. and W.
1.10	Graded road, bears E. and W.
2.70	Track road, bears E. and W.
25.60	Track road, bears NE. and SW.
40.91	The ¼ sec. cor. of secs. 23 and 24, monumented by a concrete post, 4 ins. square, projecting 5 ins. above the ground. This position has long been recognized as the cor. by local land owners and is accepted as the best available evidence of the orig. cor. position; not re-monumented.
	<hr/> N. 0°56' E., beginning new measurement.
	Over nearly level land.
28.80	Field dyke, bears N. 80° E. and S. 80° W.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
39.92	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a concrete post, 4 ins. square, projecting 5 ins. above the ground. This position has long been recognized as the cor. by local land owners and is accepted as the best available evidence of the orig. cor. position; not re-monumented.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over nearly level land, through moderate undergrowth.</p>
0.40	Underground gas line, bears E. and W.
1.70	Field dyke, bears E. and W.
6.00	Underground telephone line, bears N. 75° E. and S. 75° W.
10.80	Power line, bears S. 75° E. and N. 75° W.
10.90	Right-of-way fence, bears S. 75° E. and N. 75° W.
11.70	Paved access road, bears S. 75° E. and N. 75° W.
13.30	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
15.00	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
17.00	State Highway 86, bears S. 75° E. and N. 75° W.
19.50	Telegraph line, bears S. 75° E. and N. 75° W.
20.10	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
20.40	Railroad siding (Olga), bears S. 75° E. and N. 75° W.
21.10	Telephone line, bears S. 75° E. and N. 75° W.
23.30	Right-of-way fence, bears S. 75° E. and N. 75° W.
23.60	Graded road, bears S. 75° E. and N. 75° W.
24.60	Power line, bears S. 75° E. and N. 75° W.
32.70	Telephone line, bears S. 75°30' E. and N. 75°30' W.
40.78	<p>The $\frac{1}{2}$ sec. cor. of secs. 13 and 14, monumented by a granite stone, 5 x 4 x 3 ins., projecting 3 ins. above the ground, mkd. $\frac{1}{2}$ on W. face; not re-monumented.</p> <p>from which</p> <p>USC&GS Triangulation Station "OLGA", bears S. 8°58' W., 21.78 chs. dist., monumented by a brass tablet $3\frac{1}{2}$ ins. diam., set in a concrete post, projecting 3 ins. above the ground, mkd. OLGA 1960.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS					
40.15	<p>The cor. is located 140 lks. East of a N. and S. fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°33' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented by a granite stone, 8 x 4 x 4 ins., lying loose on the ground, mkd. 1 notch on E. and 4 notches on S. faces.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S11</td> <td style="padding: 0 5px;">S12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S14</td> <td style="padding: 0 5px;">S13</td> </tr> </table> <p>1969</p> </div> <p>Bury the orig. cor. stone and set a steel fence post, 6 ft. long, alongside the iron post.</p> <p>The cor. is located 154 lks. East of a N. and S. fence.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>	S11	S12	S14	S13
S11	S12				
S14	S13				
41.06	<p>From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.</p> <p>S. 89°20' W., bet. secs. 12 and 13.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S12</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S13</td> </tr> </table> <p>1969</p> </div> <p>from which</p> <p style="padding-left: 40px;">A stock pond, bears S. 63°22' E., 7.90 chs. dist.</p> <p>Set a round wooden post, 2½ ins. diam., 3½ ft. long, alongside the iron post.</p>	¼	S12		S13
¼	S12				
	S13				
82.12	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>				

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
<p>41.67</p>	<p>N. 0°50' E., bet. secs. 11 and 12.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S11 S12 1969</p> <p>Set a steel fence post, 6 ft. long, alongside the iron post.</p> <p>81.80 Fence, bears E. and W.</p> <p>83.34 Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E S 2 S 1 ----- S11 S12 1969</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 57°40' W., 283 lks. dist.; fences bear E., S. and with an old abandoned fence line bearing N.</p> <p>Set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
<p>40.69</p>	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 89°52' W., bet. secs. 1 and 12</p> <p>Over nearly level land, through low undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ $\frac{S 1}{S12}$ 1969</p> <p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>The cor. is located 135 lks. North of an E and W. fence.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
81.38	<p>The cor. of secs. 1, 2, 11 and 12.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered creosote bush and grass.</p>
41.67	<p>N. 1°18' E., bet. secs. 1 and 2.</p> <p>Over nearly level land, through low undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S 2 S 1 1969</p> <p>The cor. is located 314 lks. East of an old abandoned fence line, bearing N. and S.</p>
83.43	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T12S R29E <u>S35 S36</u> S 2 S 1 T13S R29E 1963</p> <p>The cor. is located 394 lks. East of an old abandoned fence line, bearing N. and S.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, grass.</p>
41.49	<p>From the cor. of secs. 34 and 35, only, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 7 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E <u>S34 S35</u> S 3 S 2 T14S 1913</p> <p>The cor. is located under a fence bearing E. and W.</p> <p>N. 0°31' W., bet. secs. 34 and 35.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 34 and 35, as determined from a redwood stake, 1 x 1 x 12 ins., set 4 ins. in the ground, originally set in a pit 5$\frac{1}{2}$ ft. North of the cor.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E

$\frac{1}{2}$
S34 | S35
1969

Bury the redwood stake and set a wooden post, 2 ins. square, 3½ ft. long, alongside the iron post.

N. 0°14' E., beginning new measurement.

Over nearly level land.

40.31

The point for the cor. of secs. 26, 27, 34 and 35, is located at a cor. of fences; fences bear N. 0°30' W. and S. 89°49' W. This point was shown me by interested property owners and is accepted as the best available evidence of the orig. cor. position.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E

S27 | S26
S34 | S35
1969

Deposit glass at the base of the iron post.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush, cacti and cat claw.

From the cor. of secs. 25, 26, 35 and 36.

N. 88°48' W., bet. secs. 26 and 35.

Over nearly level land, through moderate undergrowth.

39.43

Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E

$\frac{1}{4}$ $\frac{S26}{S35}$
1969

Set a wooden post, 4 ins. diam., 4 ft. long, alongside the iron post.

78.86

The cor. of secs. 26, 27, 34 and 35.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush, cacti and cat claw.</p>
	<p>N. 0°30' W., bet. secs. 26 and 27.</p> <p>Over nearly level land, along a fence bearing N. 0°30' W. Enter cultivated field, bears N. and W.</p>
7.30	Bend in fence; fences bear N. 7° E. and S. 0°30' E.
9.90	Graded road, bears N. 7° E. and S. 7° W.
38.40	Field dyke, bears S. 89° E. and N. 89° W.
38.60	Fence, bears S. 89° E. and N. 89° W.
39.00	Graded road, bears E. and W.
39.50	Concrete lined irrigation ditch, bears E. and W.; con- tinue over cultivated field.
39.81	Point for the ¼ sec. cor. of secs. 26 and 27, at propor- tionate dist.; there is no remaining evidence of the orig. cor. This point falls in a cultivated field; not monumented.
	<p>from which</p> <p style="padding-left: 40px;">An iron post, set 24 ins. in the ground, for a reference monument, bears S. 45° E., 172.7 lks. dist., with brass cap mkd. T13S R29E S26 RM 114 FT 1969 and an arrow pointing to the cor. point.</p> <p style="padding-left: 40px;">An iron post, set 22 ins. in the ground, for a reference monument, bears S. 0°30' E., 121.2 lks. dist., with brass cap mkd. T13S R29E S26 S27 RM 80 FT 1969, and an arrow pointing to the cor. point.</p>
59.50	Track road, bears E. and W.
59.60	Concrete lined irrigation ditch, bears E. and W.
79.30	Fence, bears E. and W.; leave cultivated field, enter moderate undergrowth.
79.62	Point for the cor. of secs. 22, 23, 26 and 27, at pro- portionate dist. falls in a graded road, bearing E. and W.; there is no remaining evidence of the orig. cor.; not monumented.
	<p>Land, nearly level. Soil, sandy clay loam. No timber; No undergrowth.</p>
	<p>From the point for the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°38' W., bet. secs. 23 and 26.</p> <p>Over nearly level land, through moderate undergrowth.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
1.30	Fence, bears S. 1°46' E. and N. 1°46' W. about 20 lks. to fence bearing irregularly E. & W., with bladed E.-W. road on N. side of the fence.
40.00	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented. This cor. point is located 25 lks. South of an E. and W. fence.
56.00	Fence, bears N. 89° E. and S. 89° W.; thence along the S. side of a graded road, bearing E. and W.
80.00	The point for the cor. of secs. 22, 23, 26 and 27. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush.
	N. 0°13' E., bet. secs. 22 and 23. Over nearly level land, through moderate undergrowth.
19.70	W. edge of clearing, bears N. and E.
39.70	Leave clearing, bears S. and E.; thence through moderate undergrowth.
39.81	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
79.62	The cor. of secs. 14, 15, 22 and 23, monumented by a water pipe 1 in. diam., projecting 12 ins. above the ground. This cor. point has long been recognized by local land owners and local surveyors as the position of the sec. cor. and is accepted as the best existing evidence of the orig. cor. position; not remonumented. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
	From the cor. of secs. 13, 14, 23 and 24. S: 89°30' W., bet. secs. 14 and 23. Over nearly level land, along the South side of an underground gas line.
19.10	Track road, bears N. and S.
36.70	Graded road, bears N. and S.
39.30	Power line, bears N. and S.
39.82	Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
79.64	The cor. of secs. 14, 15, 22 and 23.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>N. 0°01' W., bet. secs. 14 and 15.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
0.60	Underground gas line, bears E. and W.
27.00	Underground telephone line, bears S. 75° E. and N. 75° W.
33.00	Power line, bears S. 75° E. and N. 75° W.
34.00	Right-of-way fence, bears S. 75° E. and N. 75° W.
35.40	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
37.10	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
39.20	State Highway 86, bears S. 75° E. and N. 75° W.
41.60	Telegraph line, bears S. 75° E. and N. 75° W.
41.63	Point for the ¼ sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T13S R29E ¼ S15 S14 1969</p>
	from which
	<p>A Railroad right-of-way marker, bears S. 77°10' W., 187 lks. dist., which is a steel rail, projecting 4 ft. above the ground, mkd. R. R. PROPERTY LINE on N. face.</p>
	Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.
42.40	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
43.00	Telephone line, bears S. 75° E. and N. 75° W.
43.70	Graded road, bears S. 75° E. and N. 75° W.
43.80	Right-of-way fence, bears S. 75° E. and N. 75° W.
44.90	Power line, bears S. 75° E. and N. 75° W.
54.10	Center of a circular stock pond.
54.90	Dyke, bears E. and W.
61.50	Telephone line, bears S. 38½° E. and N. 38½° W.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
62.445	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E N 1/16 S15 S14 1969</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears N. 50°09' W., 208 lks. dist.; fences bear E. and S. 5° W.</p> <p>The cor. is located 56 lks. East of a track road bearing N. and S.</p> <p>Set a wooden post, 2 x 4 ins. squared, 4 ft. long, alongside the iron post.</p>
63.80	<p>Fence, bears E. and W.</p>
83.26	<p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E S10 S11 S15 S14 1969</p> <p>The cor. is located 42 lks. East of a track road bearing N. and S.</p> <p>Set a wooden post, 2 x 6 ins. squared, 4 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 88°49' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through moderate undergrowth.</p>
1.54	<p>Fence, bears N. and S.</p>
40.03	<p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E 1/4 <u>S11</u> S14 1969</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
80.06	<p>Set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.</p> <p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
41.63	<p>N. 0°03' W., bet. secs. 10 and 11.</p> <p>Over nearly level land, through low undergrowth; along a track road, bearing N. and S.</p> <p>Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E ½ S10 S11 1969</p>
83.26	<p>Set a 4 in. x 4 in. wooden post, 3 ft. long, alongside the iron post.</p> <p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E S 3 S 2 S10 S11 1969</p> <p>The cor. is located 15 lks. East of a track road bearing N. and S.</p> <p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and grass.</p>
2.40	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 88°54' W., bet. secs. 2 and 11.</p> <p>Over nearly level land, through low undergrowth.</p> <p>An abandoned fence line, bears N. and S.</p>
40.67	<p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>


Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
81.34	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ $\frac{S\ 2}{S11}$ 1969</p> <p>Set a wooden post, 4 ins. square, 3½ ft. long, alongside the iron post.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered cat claw and grass.</p>
37.10	<p>N. 2°09' E., bet. secs. 2 and 3.</p> <p>Over nearly level land, through low undergrowth.</p> <p>Track road, bears NE. and SW.</p>
41.66	<p>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S 3 S 2 1969</p> <p>The cor. is located 140 lks. East of a track road bearing N. and S.</p> <p>Set a wooden post, 3 x 6 ins. squared, 4 ft. long, alongside the iron post.</p>
83.42	<p>The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 8 ins. above the ground, with a wooden post, 4 ins. square, projecting 3½ ft. above the ground alongside, brass cap mkd.</p> <p style="text-align: center;">T12S R29E $\frac{S34}{S\ 3}$ $\frac{S35}{S\ 2}$ 1963</p> <p>The cor. is located at a cor. of fences; fences bear N., NE. and N. 88°57' W.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, grass.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS

From the cor. of secs. 33 and 34 only, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 12 ins. above the ground, brass cap mkd.



The cor. is located under a fence bearing E. and W.

N. 1°29' W., bet. secs. 33 and 34.


Over nearly level land, through moderate undergrowth.

41.34

The point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, as determined from the remains of an old redwood stake, found 10 ins. below the surface alongside a wooden post, 2 x 4 ins. squared, projecting 3 ft. above the ground. The stake was originally set in a pit 5 $\frac{1}{2}$ ft. North of the cor.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.



Deposit the remains of the old redwood stake and reset the wooden post, 2 x 4 ins. squared, 4 ft. long, alongside the iron post.

N. 0°03' W., beginning new measurement.


Over nearly level land.

40.18

The point for the cor. of secs. 27, 28, 33 and 34, as determined from a redwood stake, 1 x 1 x 17 ins., projecting 2 ins. above the ground; originally set in a pit 5 $\frac{1}{2}$ ft. SE. of the cor.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.



Bury the redwood stake and set a wooden post, 2 x 4 ins. squared, 5 ft. long, alongside the iron post.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
42.78	<p>From the cor. of secs. 26, 27, 34 and 35. S. 89°49' W., bet. secs. 27 and 34. Over nearly level land along a fence bearing S. 89°49' W. The point for the $\frac{1}{2}$ sec. cor. of secs. 27 and 34, is located at a fence cor.; fences bear N. 1°30' E. and N. 89°49' E. This point was shown me by interested property owners and is accepted as the best available evidence of the orig. cor. position. At the corner point Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{2}$ $\frac{S27}{S34}$ 1969</p>
38.23	<p>S. 89°59' W., beginning new measurement. Over nearly level land. The cor. of secs. 27, 28, 33 and 34. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
39.00	<p>N. 0°14' E., bet. secs. 27 and 28. Over nearly level land, through moderate undergrowth. Drainage ditch, drains E.</p>
39.50	<p>Field dyke, bears E. and W.</p>
39.53	<p>The point for the $\frac{1}{2}$ sec. cor. of secs. 27 and 28, is located at a fence cor.; fences bear N. 0°30' E. and W. This point was shown me by interested property owners and is accepted as the best available evidence of the orig. cor. position. Set the iron post 24 ins. in the ground, brass cap mkd.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS

T13S R29E

$\frac{1}{2}$
S28|S27
1969

N. 0°14' E., beginning new measurement.

Over nearly level land.

Enter cultivated field, bears N. and W.; thence along a graded road bearing N. and S.

15.06 Point for the N-S-N 1/256 sec. cor. of secs. 27 and 28, at proportionate dist.; falls in an intersection of roads bearing N., E. and S.

Set the iron post 10 ins. below the surface of the ground, brass cap mkd.

T13S R29E
N-S-N
1/256
S28|S27
1969

from which

An iron post, set 24 ins. in the ground, for a reference monument, bears S. 45° E., 27.3 lks. dist., mkd. T13S R29E S27 RM 18 FT 1969 and an arrow pointing to the cor. The reference monument is located under an E. and W. fence.

A railroad spike in a fence cor. post, bears S. 14°15' E., 20 lks. dist.; fences bear E. and S. 0°30' W.

Continue along E. side of the graded road.

39.90 Graded road, bears E., S. and W.

40.15 The cor. of secs. 21, 22, 27 and 28, monumented by a concrete post, 4 ins. square, projecting 8 ins. above the ground, is located at a fence cor.; fences bear N. 0°30' E. and E. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position; not remonumented.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush and cat claw, first half mile.

From the point for the cor. of secs. 22, 23, 26 and 27.

S. 89°56' W., bet. secs. 22 and 27.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	Over nearly level land, along a graded road bearing E. and W.
25.70	Leave graded road, curves NW.; fence, bears S. 89°20' E. and N. 89°20' W.
39.40	Same graded road, curves W. from NE.
39.80	Power line, bears N. and S.
39.90	Fence, bears S. 1°30' W. and bears N. 1°30' E., 16 lks. dist. to fence cor.; fences bear S. 89°20' E., S. 1°30' W. and S. 89°40' W.
39.98	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
40.70	Drainage ditch, drains N.; enter cultivated field, bears N. and S.; continue along S. side of E. and W. fence.
79.96	The cor. of secs. 21, 22, 27 and 28.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw, 1st half to N. only.
	N. 0°19' W., bet. secs. 21 and 22.
	Over nearly level land, along the W. side of a N. and S. fence.
	Continue over cultivated fields.
39.50	Track road, bears S. and W.
39.80	Fence, bears W. and bears E., 37 lks. dist. to fence cor.; fences bear N. 0°40' E., S. and W.; leave cultivated fields, enter moderate undergrowth.
40.82	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
79.30	Underground gas line, bears E. and W.
81.64	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
	from which
	Fence cor., bears S. 23°11' E., 210 lks. dist.; fences bear E. and S. 0°40' W.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw, 2nd half.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS		
	From the cor. of secs. 14, 15, 22 and 23.	
	N. 88°39' W., bet. secs. 15 and 22.	
	Over nearly level land, along gas line right-of-way.	
8.60	Center of underground gas line, bears E. and W.	
17.20	Leave gas line right-of-way, bears E. and W.; enter moderate undergrowth.	
36.60	Fence, bears N. and S., 175 lks. dist. to fence cor.; fences bear N. and W.	
37.90	Power line, bears N. and S.	
40.36	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.	
79.80	Power line, bears N. and S.	
80.72	The point for the cor. of secs. 15, 16, 21 and 22.	
	Land, nearly level.	
	Soil, sandy clay loam.	
	No timber; Undergrowth, creosote bush and cat claw.	
	N. 0°18' E., bet. secs. 15 and 16.	
	Over nearly level land, through moderate undergrowth.	
40.82	Point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.	
52.60	Power line, bears S. 75° E. and N. 75° W.	
53.50	Right-of-way fence, bears S. 75° E. and N. 75° W.	
55.00	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.	
56.70	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.	
58.80	State Highway 86, bears S. 75° E. and N. 75° W.	
61.20	Telegraph line, bears S. 75° E. and N. 75° W.	
61.90	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.	
62.30	Graded road, bears S. 75° E. and N. 75° W.	
62.60	Telephone line, bears S. 75° E. and N. 75° W.	
63.40	Right-of-way fence, bears S. 75° E. and N. 75° W.	
64.60	Power line, bears S. 75° E. and N. 75° W.	
79.04	Fence, bears E. and W.	
81.64	The cor. of secs. 9, 10, 15 and 16, monumented by an old redwood stake, 1 x 2 ins. diam., 18 ins. long, and is accepted as the best remaining evidence of the orig. cor.	
	At the corner point	

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>Set the iron post 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{S\ 9}{S16} \frac{S10}{S15}$ 1969</p> <p>Set a wooden post, 4 ins. square, 4½ ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>N. 89°47' W., bet. secs. 10 and 15.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
0.40	<p>Track road, bears N. and S.</p>
17.60	<p>Telephone line, bears S. 38½° E. and N. 38½° W.</p>
20.06	<p>Point for the E 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E E 1/16 $\frac{S10}{S15}$ 1969</p>
	<p>Set a wooden post, 2 x 4 ins. squared, 4 ft. long, alongside the iron post.</p>
40.12	<p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E $\frac{1}{4} \frac{S10}{S15}$ 1969</p>
	<p>Set a wooden post, 4 ins. square, 4½ ft. long, alongside the iron post.</p>
	<p>The cor. is located 397 lks. North of an E. and W. fence.</p>
80.24	<p>The cor. of secs. 9, 10, 15 and 16.</p>
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>N. 0°48' W., bet. secs. 9 and 10.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
41.93	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E</p>
	<p style="text-align: center;">$\frac{1}{4}$</p>
	<p style="text-align: center;">S 9 S10</p>
	<p style="text-align: center;">1969</p>
	<p>Set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post.</p>
76.20	<p>Telephone line, bears S. 42° E. and N. 42° W.</p>
83.86	<p>Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E</p>
	<p style="text-align: center;">S 4 S 3</p>
	<p style="text-align: center;">S 9 S10</p>
	<p style="text-align: center;">1969</p>
	<p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p>
	<p>Land, nearly level.</p>
	<p>Soil, sandy clay loam.</p>
	<p>No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 89°20' W., bet. secs. 3 and 10.</p>
	<p>Over nearly level land, through low undergrowth.</p>
0.15	<p>Track road, bears N. and S.</p>
11.70	<p>Track road, bears S. 80° E. and N. 80° W.</p>
40.66	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E</p>
	<p style="text-align: center;">$\frac{1}{4}$ S 3</p>
	<p style="text-align: center;">S10</p>
	<p style="text-align: center;">1969</p>
	<p>Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p>
	<p>Enter moderate undergrowth, bears N. and S.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS

81.32 The cor. of secs. 3, 4, 9 and 10.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush and cat claw.

N. 3°02' E., bet. secs. 3 and 4.

Over nearly level land, through moderate undergrowth.

41.98 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E

$$\begin{array}{c} \frac{1}{4} \\ S\ 4\ | \ S\ 3 \\ 1969 \end{array}$$

Set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post.

84.01 The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by an iron post 2 $\frac{1}{2}$ ins. diam., projecting 9 ins. above the ground, with a wooden post, 4 ins. square, projecting 3 $\frac{1}{2}$ ft. above the ground alongside, brass cap mkd.

T12S R29E

$$\begin{array}{c} S33\ | \ S34 \\ S\ 4\ | \ S\ 3 \\ 1963 \end{array}$$

The cor. is located under a fence bearing S. 88°57' E. and N. 88°57' W.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush and cat claw.

From the cor. of secs. 32 and 33 only, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 8 ins. above the ground, brass cap mkd.

$$\begin{array}{c} T13S \\ R29E\ \underline{S32\ | \ S33} \\ S\ 5\ | \ S\ 4 \end{array}$$
T14S
1913

The cor. is located under an E. and W. fence.

N. 0°25' W., bet. secs. 32 and 33.

Over nearly level land, through moderate undergrowth.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
41.34	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E $\frac{1}{4}$ S32 S33 1969</p>
	<p>Set a wooden post, 2 x 4 ins. squared, 4 ft. long, alongside the iron post.</p>
82.68	<p>The cor. of secs. 28, 29, 32 and 33, as determined from a redwood stake, 1 x 1 x 12 ins., projecting 2 ins. above the ground, originally set in a pit $5\frac{1}{2}$ ft. SE. of the cor.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E <u>S29 S28</u> S32 S33 1969</p>
	<p>Bury the wood stake and set a wooden post, 4 ins. square, 4 ft. long, alongside the cor.</p>
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>N. $89^{\circ}31'$ W., bet. secs. 28 and 33.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
40.11	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E $\frac{1}{4}$ <u>S28</u> S33 1969</p>
	<p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p>
80.22	<p>The cor. of secs. 28, 29, 32 and 33.</p>
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
40.05	<p>N. 0°56' E., bet. secs. 28 and 29.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The ¼ sec. cor. of secs. 28 and 29, monumented by a concrete post, 4 ins. square, projecting 4 ins. above the ground, located at a fence cor.; fences bear N. 0° 50' W. and S. 89°10' E. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S29 S28 1969</p> <p>Bury the concrete post alongside the iron post.</p>
39.92	<p>N. 0°50' W., beginning new measurement.</p> <p>Over nearly level land, along a N. and S. fence.</p> <p>Enter SW. cor. of cultivated field, bears N. and E.</p> <p>The cor. of secs. 20, 21, 28 and 29, monumented by a concrete post, 4 ins. square, projecting 5 ins. above the ground, located under a fence bearing S. 0°50' E. and N. 0°50' W. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position; not remonumented.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
0.30 0.50 40.23 80.00 80.46	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°19' W., bet. secs. 21 and 28.</p> <p>Over nearly level cultivated land.</p> <p>Drainage ditch, drains N.</p> <p>Track road, bears N. and S.</p> <p>Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p> <p>Graded road, bears N. and S.</p> <p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; no undergrowth.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS		
	From the point for the cor. of secs. 15, 16, 21 and 22.	
	S. 88°11' W., bet. secs. 16 and 21.	
	Over nearly level land, through moderate undergrowth.	
40.35	The ¼ sec. cor. of secs. 16 and 21, monumented by a concrete post, 4 ins. diam., projecting 2 ins. above the ground, located at a fence cor.; fences bear S. and W. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position; not remonumented.	
	N. 89°15' W., beginning new measurement.	
	Over nearly level land, along an E. and W. fence, on the N. edge of gas line right-of-way.	
40.18	The cor. of secs. 16, 17, 20 and 21, monumented by a concrete post, 4 ins. square, projecting 6 ins. above the ground, located at a fence cor.; fences bear S. 89° 15' E. and N. 0°38' W. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position; not remonumented.	
	Land, nearly level.	
	Soil, sandy clay loam.	
	No timber; Undergrowth, creosote bush and cat claw to the N. only.	
	N. 0°38' W., bet. secs. 16 and 17.	
	Over nearly level land, along a N. and S. fence.	
15.00	Graded road, bears NE., curving N. and bears SW., curving S.	
39.96	The ¼ sec. cor. of secs. 16 and 17, monumented by a concrete post, 4 ins. square, projecting 8 ins. above the ground, located at a fence cor.; fences bear S. 0°38' E. and W. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position; not remonumented.	
	N. 1°06' W., beginning new measurement.	
	Over nearly level land, along the West side of a graded road bearing N. and S.	
35.34	Power line, bears S. 75° E. and N. 75° W.	
35.48	Right-of-way fence, bears S. 75° E. and N. 75° W.	
35.68	Underground telephone line, bears S. 75° E. and N. 75° W.	
38.85	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.	

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
39.56	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
40.01	<p>Point for the cor. of secs. 8, 9, 16 and 17, as determined from information shown on Arizona Highway Department location maps of the Benson-Steins Pass Highway, (Interstate 10). These maps consist of roll 3 (STA. 3440+00 to 3705+00) of Luzena-State Line Section dated May, 1958 and Sheet 10 (STA. 3630+00 to 3660+00) of Fed. Road Div. No. 7, Project No. I 10-6(18)368 of the Benson-Steins Pass Highway.</p> <p>At the corner point</p> <p>Set the iron post 30 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T13S R29E} \\ \text{S } 8 \text{ S } 9 \\ \hline \text{S17 S16} \\ 1969 \end{array}$ <p>from which</p> <p>A highway marker bears N. 87°24' E., 32.9 lks. dist., monumented by a standard tablet, set 6 ins. below the surface under a metal plate, located on the north shoulder of the west bound lane of Interstate 10; tablet mkd. P.O.T. 3649+03.07.</p> <p>A highway marker bears S. 23°54' E., 41.4 lks. dist., monumented by a standard tablet, set 6 ins. below the surface under a metal plate and located near the north edge of the west bound lane of Interstate 10; tablet mkd. ELEV STA.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
41.49	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 86°16' W., bet. secs. 9 and 16.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 16, monumented by an iron pipe 1 in. diam., projecting 4 ins. above ground. This cor. point is accepted by local surveyors and was tied to by the Arizona Highway Dept. on the location maps of Interstate 10, and is accepted as the best remaining evidence of the original corner position.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T13S R29E} \\ \frac{1}{4} \text{ S } 9 \\ \hline \text{S16} \\ 1969 \end{array}$ <p>Set the 1 in. iron pipe and a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>The cor. is located in a N-S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°32' W., beginning new measurement.</p>
12.50	Power line, bears S. 75° E. and N. 75° W.
16.715	Southern Pacific Railroad R.O.W., bears S. 75° E. and N. 75° W.
16.73	Right-of-way fence, bears S. 75° E. and N. 75° W.
20.15	Telephone line, bears S. 75° E. and N. 75° W.
20.55	Track road, bears S. 75° E. and N. 75° W.
22.75	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
25.24	Telegraph line, bears S. 75° E. and N. 75° W.
34.44	State Highway 86, bears S. 75° E. and N. 75° W.
40.74	The cor. of secs. 8, 9, 16 and 17.
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>N. 0°10' W., bet. secs. 8 and 9.</p> <p>Over nearly level land, through moderate undergrowth.</p>
1.37	State Highway 86, bears S. 75° E. and N. 75° W.
4.05	Telegraph line, bears S. 75° E. and N. 75° W.
4.71	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
5.40	Telephone line, bears S. 75° E. and N. 75° W.
5.75	Graded road, bears S. 75° E. and N. 75° W.
6.25	Right-of-way fence, bears S. 75° E. and N. 75° W.
6.28	Southern Pacific Railroad R.O.W., bears S. 75° E. and N. 75° W.
7.40	Power line, bears S. 75° E. and N. 75° W.
39.70	Point for the ¼ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{2}$ S 8 S 9 1969</p>
79.40	<p>Set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>The cor. of secs. 4, 5, 8 and 9, as determined from a wooden stake, 1 x 1 x 16 ins., projecting 8 ins. above the ground, originally set in a pit 5½ ft. SE. of the cor.</p>
	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E S 5 S 4 S 8 S 9 1969</p>
	<p>from which</p> <p style="padding-left: 40px;">A water pipe, 1 in. diam., bears S. 45° E., 8.3 lks. dist.</p>
	<p>Bury the wooden stake and set a wooden post, 4 ins. square, 4 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p>
	<p>S. 81°13' W., bet. secs. 4 and 9.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
5.14	<p>Telephone line, bears S. 42° E. and N. 42° W.</p>
40.92	<p>Fence, bears S. 0°40' E. and N. 0°40' W.</p>
41.07	<p>The ¼ sec. cor. of secs. 4 and 9, as determined from a redwood stake, 1 x 1½ x 18 ins., projecting 1 in. above the ground, originally set in a pit 5½ ft. East of the cor.</p>
	<p>At the corner point</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T13S R29E $\frac{1}{4}$ S 4 S 9 1969</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS		
40.61	<p>from which</p> <p>A water pipe, 1 in. diam., bears East, 8.3 lks. dist.</p> <p>Bury the redwood stake and set a wooden post, 4 ins. square, 3 ft. long, alongside the iron post.</p> <hr/> <p>S. 89°10' W., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>	
40.54	<p>N. 0°53' E., bet. secs. 4 and 5.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 5, as determined from a wooden stake, 1 x 1 x 18 ins., projecting 8 ins. above the ground, dimly mkd. S on S. face, originally set in a pit 5$\frac{1}{2}$ ft. North of the cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S 5 S 4 1969</p> <p>Bury the wooden stake and set a wooden post, 4 ins. square, 5$\frac{1}{2}$ ft. long, alongside the iron post.</p> <hr/>	
52.02	<p>N. 5°31' E., beginning new measurement.</p> <p>Over nearly level land.</p> <p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented by an iron post 2$\frac{1}{2}$ ins. diam., projecting 8 ins. above the ground, with a wooden post, 4 ins. square, projecting 20 ins. above the ground alongside, brass cap mkd.</p> <p style="text-align: center;">T12S R29E <u>S32 S33</u> S 5 S 4 T13S R29E 1963</p>	

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>from which</p> <p>A fence cor., bears N. 25° E., 147 lks. dist.; fences bear S. 88° E. and N. 10° W.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., pro- jecting 6 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;"> T13S R29E <u>S31</u> <u>S32</u> S 6 S 5 T14S 1913 </p> <p>The cor. is located under an E. and W. fence. N. 0°24' W., bet. secs. 31 and 32.</p> <p>Over nearly level land, through moderate undergrowth.</p>
40.40	<p>Point for the ¼ sec. cor. of secs. 31 and 32, at propor- tionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;"> T13S R29E ¼ S31 S32 1969 </p>
80.80	<p>The cor. of secs. 29, 30, 31 and 32, as determined from a weathered wooden stake, 2 x 2 x 24 ins., lying loose on the ground, originally set in a pit 5½ ft. SE. of the cor.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> T13S R29E S30 S29 S31 S32 1969 </p> <p>Bury the remains of the wooden stake alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>

Dep. Res., Portion Subdivisional Lines; T. 13 S., R. 29 E.

CHAINS		
19.36	<p>N. 78°30' W., bet. secs. 30 and 31.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Point for the E 1/16 sec. cor. of secs. 30 and 31, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E</p> <p>E 1/16 $\frac{S30}{S31}$</p> <p>1969</p> </div>	
38.72	<p>Set a wooden post, 4 ins. diam., 3 ft. long, alongside the iron post.</p> <p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T13S R29E</p> <p>1/4 $\frac{S30}{S31}$</p> <p>1969</p> </div>	
50.20	<p>Set a steel fence post, 6 ft. long, alongside the iron post.</p> <p>Wash, 15 lks. wide, 3 ft. deep, drains NE.</p>	
73.00	<p>Track road, bears N. and S.</p>	
76.59	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>	
40.41	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°26' W., bet. secs. 29 and 30.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p>	
79.70	<p>Track road, bears E., SE. and N. 79° W.</p>	
80.82	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a concrete post, 4 ins. square, projecting 4 ins. above the ground. This position has long been recognized as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position.</p> <p>At the corner point</p>	

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS

Set the iron post 26 ins. in the ground, brass cap mkd.

T13S R29E
 $\frac{S19}{S30} | \frac{S20}{S29}$
 1969

from which

A fence cor., bears N. 30°10' E., 65.2 lks. dist.,
 fences bear E. and N. 0°25' W.

A well with a gas engine pump, bears N. 44°30' E.,
 249 lks. dist. The water is used for irrigation.

Bury the concrete post alongside the iron post.

Raise a mound of stone W. of the cor.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush and cat claw.

N. 78°38' W., bet. secs. 19 and 30.

Over nearly level land, through moderate undergrowth.

19.22 Point for the E 1/16 sec. cor. of secs. 19 and 30, at
 proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E
 E 1/16 $\frac{S19}{S30}$
 1969

The cor. is located 90 lks. North of a track road, bears
 S. 79° E. and N. 79° W.

Deposit glass at the base of the iron post.

38.44 The 1/4 sec. cor. of secs. 19 and 30, monumented by a
 concrete post, 4 ins. square, projecting 4 ins. above the
 ground. This position has long been recognized as the
 cor. by local land owners and is accepted as the best
 existing evidence of the orig. cor. position.

At the corner point.

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E
 $\frac{1}{4} \frac{S19}{S30}$
 1969

The cor. is located 74 lks. North of a track road, bears
 S. 79° E. and N. 79° W.

Bury the concrete post and set an iron pipe, 3 ins. diam.,
 4 ft. long, alongside the iron post.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
<p>0.90</p> <p>37.20</p> <p>37.48</p>	<p>N. 78°38' W., beginning new measurement.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Track road, bears NE. and SW.</p> <p>Track road, bears N. and S.</p> <p>The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
<p>40.40</p> <p>60.60</p>	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°04' W., bet. secs. 19 and 20.</p> <p>Over nearly level land, along a fence bearing N. 0°25' W.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ S19 S20 1969</p> <p>from which</p> <p style="padding-left: 40px;">A well with a gas engine pump, bears S. 88°10' E., 102 lks. dist. The water is used for irrigation.</p> <p>The cor. is located 24 lks. West of a fence bearing S. 0°25' E. and N. 0°25' W.</p> <p>Raise a mound of broken blocks of concrete W. of the cor.</p> <p>Point for the N 1/16 sec. cor. of secs. 19 and 20, at proportionate dist.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E N 1/16 S19 S20 1969</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located 12 lks. West of a fence bearing S. 0°25' E. and N. 0°25' W.</p>
<p>80.80</p>	<p>The point for the cor. of secs. 17, 18, 19 and 20, is located at a fence cor.; fences bear N. 89°43' E. and S. 0°25' E. This position is harmoniously related to other accepted cor. points located at fence cors. which have long been accepted by local land owners and is accepted as the best available evidence of the orig. cor. position.</p>

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{S18}{S19} \frac{S17}{S20}$ 1969</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
<p>0.20</p> <p>40.17</p>	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°42' W., bet. secs. 17 and 20.</p> <p>Over nearly level land, along an underground gas line right-of-way, bears E. and W.</p> <p>Graded road, bears N. and bears S., 50 lks. dist., to an intersection of graded roads bearing N., E., S. and W.</p> <p>The point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 20, is located at a fence cor.; fences bear N. 0°30' W. and S. 89°43' W. This position has long been accepted as the cor. by local land owners and is accepted as the best existing evidence of the orig. cor. position.</p>
<p>39.71</p>	<p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4} \frac{S17}{S20}$ 1969</p> <p>Deposit glass at the base of the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89°43' W., beginning new measurement.</p> <p>Over nearly level land, along an E. and W. fence.</p>
<p>0.70</p>	<p>The cor. of secs. 17, 18, 19 and 20.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw 2nd half to the N. only.</p> <p style="text-align: center;">_____</p> <p>N. 78°55' W., bet. secs. 18 and 19.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains N.</p>

Dep. Res., Portion Subdivisional Lines; T. 13 S., R. 29 E.

CHAINS	
11.00	Underground gas line, bears S. 86° E. and N. 86° W.
37.70	Track road, bears N. and S.
38.33	Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T13S R29E $\frac{1}{4} \frac{S18}{S19}$ 1969</p>
	from which
	A stock pond, bears S. 19°45' W., 8.00 chs. dist.
	Set a wooden post, 4 ins. diam., 3 ft. long, alongside the iron post.
47.91	Point for the E-W 1/64 sec. cor. of secs. 18 and 19, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T13S R29E E-W 1/64 $\frac{S18}{S19}$ 1969</p>
	Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.
57.49	Point for the W 1/16 sec. cor. of secs. 18 and 19, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T13S R29E W 1/16 $\frac{S18}{S19}$ 1969</p>
	Set a wooden post, 2 ins. square, 4 ft. long, alongside the iron post.
73.60	Wash, 40 lks. wide, 1 ft. deep, drains NE.
75.09	Power line, bears N. from W.
75.54	The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
	From the cor. of secs. 17, 18, 19 and 20.
	N. 0°25' W., bet. secs. 17 and 18.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	Over nearly level land, through moderate undergrowth.
2.00	Underground gas line, bears S. 86° E. and N. 86° W.
40.39	Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T13S R29E $\frac{1}{4}$ S18 S17 1969</p>
	The cor. is located 2 lks. East of a cor. of fences bearing N. 79°10' W. and N. 0°25' W.
	Deposit glass at the base of the iron post.
80.78	The cor. of secs. 7, 8, 17 and 18, monumented by an iron pipe, 1 in. diam., projecting 6 ins. above the ground. The cor. point is verified by rotted remains of a wooden stake in a pit 5½ ft. SE.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T13S R29E $\frac{1}{4}$ S 7 S 8 S18 S17 1969</p>
	Bury the iron pipe and stake alongside the iron post.
	Deposit glass at the base of the cor.
	The cor. is located 1 lk. West of a N. and S. fence.
	Land, nearly level.
	Soil, sandy clay loam.
	No timber; Undergrowth, creosote bush and cat claw.
	From the cor. of secs. 8, 9, 16 and 17.
	N. 89°42' W., bet. secs. 8 and 17.
	Over nearly level land, through moderate undergrowth.
1.73	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
8.16	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
13.86	Right-of-way fence, bears S. 75° E. and N. 75° W.
17.15	Underground telephone line, bears S. 75° E. and N. 75° W.
17.86	Power line, bears S. 75° E. and N. 75° W.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
39.64	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4}$ $\frac{S\ 8}{S17}$ 1969</p> <p>Set a wooden post, 4 ins. diam., 3 ft. long, alongside the iron post.</p>
66.70	Wash, 15 lks. wide, 4 ft. deep, drains N.
79.28	<p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
<p>N. 79°27' W., bet. secs. 7 and 18.</p> <p>Over nearly level land, through moderate undergrowth.</p>	
1.20	Wash, 20 lks. wide, 1 ft. deep, drains N.
15.00	Wash, 5 lks. wide, 3 ft. deep, drains N., 8.00 chs. dist. to center of a circular pond; leave moderate undergrowth.
34.00	Graded road, bears N. and S.
34.40	Fence, bears N. and S.
38.26	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.
55.90	Track road, bears N. and S.
57.70	Track road, bears NE. and SW.
59.30	Fence around a stock pond, bears N. 60° E. and S. 60° W.
62.20	East side of stock pond.
69.20	West side of stock pond.
70.60	Fence, bears N. 87° E. and N. 87° W.; enter moderate undergrowth.
75.32	<p>The point for the cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°50' W., bet. secs. 7 and 8.</p>	

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
	Over nearly level land, along a N. and S. fence.
16.80	Power line, bears S. 75° E. and N. 75° W.
16.90	Right-of-way fence, bears S. 75° E., S. 0°50' E. and N. 75° W.
17.70	Frontage road, (paved) bears S. 75° E. and N. 75° W.
18.70	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
20.50	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
22.60	State Highway 86, bears S. 75° E. and N. 75° W.
24.70	Telegraph line, bears S. 75° E. and N. 75° W.
25.50	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
26.30	Telephone line, bears S. 75° E. and N. 75° W.
26.60	Graded road, bears S. 75° E. and N. 75° W.
27.07	Southern Pacific Railroad R.O.W. and R.O.W. fence, bears S. 75° E. and N. 75° W.
28.30	Power line, bears S. 75° E. and N. 75° W.
40.16	The $\frac{1}{2}$ sec. cor. of secs. 7 and 8, as determined from a redwood stake, 1 x 1 x 18 ins., originally set in a pit 5 $\frac{1}{2}$ ft. North of the cor. A water pipe, 1 in. diam., projecting 8 ins. above the ground, was found alongside the redwood stake.
	At the corner point
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T13S R29E $\frac{1}{2}$ S 7 S 8 1969
	Bury the redwood stake and the water pipe alongside the iron post.
	Raise a mound of stone W. of the cor.

	N. 3°10' E., beginning new measurement.
	Over nearly level land.
44.28	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{S\ 6}{S\ 7} \frac{S\ 5}{S\ 8}$ 1969</p> <p>Set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>	
38.64	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 85°59' W., bet. secs. 5 and 8.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4} \frac{S\ 5}{S\ 8}$ 1969</p> <p>Set a wooden post, 3 x 6 ins. squared, 3 ft. long, alongside the iron post.</p>	
77.28	<p>The cor. of secs. 5, 6, 7 and 8.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>	
38.83	<p>N. 82°51' W., bet. secs. 6 and 7.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T13S R29E $\frac{1}{4} \frac{S\ 6}{S\ 7}$ 1969</p> <p>Set a round wooden post, 2½ ins. diam., 3 ft. long, alongside the iron post.</p>	

Dep. Res., Portion Subdivisional Lines, T. 13 S., R. 29 E.

CHAINS	
50.80	Track road, bears N. and S.
68.60	Track road, bears NE. and SW.
71.30	Fence, bears N. and S.
76.49	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered creosote bush 1st half.
44.24	From the cor. of secs. 5, 6, 7 and 8. N. 1°44' E., bet. secs. 5 and 6. Over nearly level land, through moderate undergrowth. Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the orig. cor. Set the iron post 24 ins. in the ground, brass cap mkd. T13S R29E $\frac{1}{2}$ S 6 S 5 1969 Raise a mound of stone W. of the cor. 88.40 The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented by an iron post 2 $\frac{1}{2}$ ins. diam., projecting 10 ins. above the ground with a wooden post, 4 ins. square, projecting 40 ins. above the ground alongside, brass cap mkd. T12S R29E S31 S32 S 6 S 5 T13S R29E 1963 Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
	Subdivision of Section 1, T. 13 S., R. 29 E.
41.37	From the $\frac{1}{4}$ sec. cor. of secs. 1 and 12. N. 0°48' E., on the N. and S. center line of sec. 1. Over nearly level land, through low undergrowth. Point for the center $\frac{1}{4}$ sec. cor. of sec. 1, at intersection with the E. and W. center line of sec. 1.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS

Set the iron post 24 ins. in the ground, brass cap mkd.

T13S R29E
C 1/2 — S 1
1969

Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.

62.05 Point for the C-N 1/16 sec. cor. of sec. 1.

Set the iron post 24 ins. in the ground, brass cap mkd.

C
N 1/16 | S 1
C
1969

Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.

82.77 The 1/4 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., monumented by an iron post 2 1/2 ins. diam., projecting 10 ins. above the ground, brass cap mkd.

T12S R29E
1/4 — S36
S 1
T13S
1963

Land, nearly level.
Soil, sandy clay loam.
No timber; Undergrowth, grass.

From the 1/4 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.

N. 89°25' W., on the E. and W. center line of Sec. 1.

Over nearly level land, through low undergrowth.

20.18 Point for the C-E 1/16 sec. cor. of sec. 1.

Set the iron post 24 ins. in the ground, brass cap mkd.

C — E 1/16 — C
S 1
1969

Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.

40.36 The center 1/4 sec. cor. of sec. 1.

80.67 The 1/4 sec. cor. of secs. 1 and 2.

Land, nearly level.
Soil, sandy clay loam.
No timber; Undergrowth, grass.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	<p>Subdivision, NE$\frac{1}{4}$ of Section 1</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the C-E 1/16 sec. cor. of sec. 1.</p> <p>N. 0°34' E., on the N. and S. center line of the NE$\frac{1}{4}$ of sec. 1.</p> <p>Over nearly level land, through low undergrowth.</p>
20.60	<p>Point for the NE 1/16 sec. cor. of sec. 1, at intersection with the E. and W. center line of the NE$\frac{1}{4}$ of sec. 1.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 1 1969</p> <p>Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.</p>
41.24	<p>The E 1/16 sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp.</p>
	<p>From the N 1/16 sec. cor. of secs. 1 and 6, on the E. bdy. of the Tp.</p> <p>N. 89°14' W., on the E. and W. center line of the NE$\frac{1}{4}$ of sec. 1.</p> <p>Over nearly level land, through low undergrowth.</p>
20.10	<p>The NE 1/16 sec. cor. of sec. 1.</p>
40.20	<p>The C-N 1/16 sec. cor. of sec. 1.</p>
	<p>Subdivision of Section 4, T. 13 S., R. 29 E.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 4 and 9.</p> <p>N. 3°10' E., on the N. and S. center line of sec. 4.</p> <p>Over nearly level land, through moderate undergrowth.</p>
1.50	<p>Fence, bears S. 0°40' E. and N. 0°40' W.</p>
44.24	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 4, at intersection with the E. and W. center line of sec. 4.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p>C $\frac{1}{4}$ ——— S 4</p> <p style="margin-left: 100px;"> </p> <p style="margin-left: 100px;">1969</p>


Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	<p>Set a wooden post, 2 x 3 ins. squared, 4 ft. long, alongside the iron post.</p> <p>46.70 Dim track road, bears S. 42° E. and N. 42° W.</p> <p>46.80 Telephone line, bears S. 42° E. and N. 42° W.</p> <p>91.06 The ¼ sec. cor. of secs. 4 and 33, on the N. bdy. of the Tp., monumented by an iron post 2½ ins. diam., projecting 6 ins. above the ground, brass cap mkd.</p> <p style="text-align: center;">T12S R29E ¼ $\frac{S33}{S4}$ T13S R29E 1963</p> <p>The cor. is located under a fence bearing S. 88°57' E. and N. 88°57' W.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the ¼ sec. cor. of secs. 3 and 4.</p> <p>S. 84°18' W., on the E. and W. center line of sec. 4.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>38.50 Telephone line, bears S. 42° E. and N. 42° W.</p> <p>38.60 Dim track road, bears S. 42° E. and N. 42° W.</p> <p>40.56 The center ¼ sec. cor. of sec. 4.</p> <p>43.50 Fence, bears S. 0°40' E. and N. 0°40' W.</p> <p>83.21 The ¼ sec. cor. of secs. 4 and 5.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>Subdivision of Section 5, T. 13 S., R. 29 E.</p>
	<p>From the ¼ sec. cor. of secs. 5 and 8.</p> <p>N. 2°37' E., on the N. and S. center line of sec. 5.</p> <p>Over nearly level land, through moderate undergrowth.</p> <p>42.31 Point for the center ¼ sec. cor. of sec. 5, at intersection with the E. and W. center line of sec. 5.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C¼ $\frac{S5}{1969}$</p>


Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	Set a wooden post, 2 x 4 ins. squared, 4 ft. long, alongside the iron post.
90.42	The $\frac{1}{4}$ sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp., monumented by an iron post $2\frac{1}{2}$ ins. diam., projecting 9 ins. above the ground, with a granite stone, 5 x 8 x 11 ins. alongside, brass cap mkd.
	<p style="text-align: center;">T12S R29E $\frac{1}{4}$ $\frac{S32}{S 5}$ T13S 1963</p>
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
	From the $\frac{1}{4}$ sec. cor. of secs. 4 and 5.
	N. $83^{\circ}11'$ W., on the E. and W. center line of sec. 5.
	Over nearly level land, through moderate undergrowth.
37.49	The center $\frac{1}{4}$ sec. cor. of sec. 5.
76.92	The $\frac{1}{4}$ sec. cor. of secs. 5 and 6.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
Subdivision of Section 7, T. 13 S., R. 29 E.	
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18.
	N. $0^{\circ}40'$ E., on the N. and S. center line of sec. 7.
	Over nearly level land, through low undergrowth.
6.30	Fence, bears S. 80° E. and N. 80° W.
14.50	Underground telephone line, bears S. 75° E. and N. 75° W.
19.70	Power line, bears S. 75° E. and N. 75° W.
19.80	Right-of-way fence, bears S. 75° E. and N. 75° W.
20.60	Frontage road (paved), bears S. 75° E. and N. 75° W.
21.70	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
23.40	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
25.40	State Highway 86, bears S. 75° E. and N. 75° W.
27.80	Telegraph line, bears S. 75° E. and N. 75° W.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
28.50	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
28.90	Graded road, bears S. 75° E. and N. 75° W.
29.20	Telephone line, bears S. 75° E. and N. 75° W.
30.00	Right-of-way fence, bears S. 75° E. and N. 75° W.
31.10	Power line, bears S. 75° E. and N. 75° W.
39.87	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E. and W. center line of sec. 7.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	
	<p>Set a wooden post, 3 ins. diam., 3 ft. long, alongside the iron post.</p>
75.80	Track road, bears NE. and SW.
82.20	<p>The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, scattered creosote bush and grass.</p>
<p>From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.</p>	
	<p>N. 79°30' W., on the E. and W. center line of sec. 7.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>
37.21	The center $\frac{1}{4}$ sec. cor. of sec. 7.
61.10	Track road, bears N. and S.
74.00	Power line, bears N. and S.
74.30	Track road, bears N. and S. 10° E.
74.98	<p>The $\frac{1}{4}$ sec. cor. of secs. 7 and 12.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
<p>Subdivision of Section 8, T. 13 S., R. 29 E.</p>	
<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 17.</p>	
	<p>N. 0°32' E. on the N. and S. center line of sec. 8.</p>
	<p>Over nearly level land, through moderate undergrowth.</p>

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
5.80	Underground telephone line, bears S. 75° E. and N. 75° W.
6.10	Power line, bears S. 75° E. and N. 75° W.
6.70	Right-of-way fence, bears S. 75° E. and N. 75° W.
8.20	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
9.90	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
11.90	State Highway 86, bears S. 75° E. and N. 75° W.
14.35	Telegraph line, bears S. 75° E. and N. 75° W.
15.05	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
15.50	Graded road, bears S. 75° E. and N. 75° W.
15.70	Telephone line, bears S. 75° E. and N. 75° W.
16.62	Southern Pacific Railroad R.O.W. and R.O.W. fence, bears S. 75° E. and N. 75° W.
17.70	Power line, bears S. 75° E. and N. 75° W.
39.92	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 8, at intersection with the E. and W. center line of sec. 8.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	
	<p>Set a wooden post, 2 x 4 ins. squared, 3 ft. long, alongside the iron post.</p>
81.88	<p>The $\frac{1}{4}$ sec. cor. of secs. 5 and 8.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>N. 89°18' W., on the E. and W. center line of sec. 8.</p> <p>Over nearly level land, through moderate undergrowth.</p>
39.08	The center $\frac{1}{4}$ sec. cor. of sec. 8.
59.30	Wash, 20 lks. wide, 1 ft. deep, drains N.
79.68	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>Subdivision of Section 10, T. 13 S., R. 29 E.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 15. N. $0^{\circ}24'$ W., on the N. and S. center line of sec. 10. Over nearly level land, through moderate undergrowth.</p>
28.60	Telephone line, bears S. 42° E. and N. 42° W.
41.76	<p>Point for the center $\frac{1}{4}$ sec. cor. of sec. 10, at intersection with the E. and W. center line of sec. 10.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
83.54	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11. N. $89^{\circ}34'$ W., on the E. and W. center line of sec. 10. Over nearly level land, through moderate undergrowth.</p>
40.40	The center $\frac{1}{4}$ sec. cor. of sec. 10.
52.30	Telephone line, bears S. 42° E. and N. 42° W.
80.77	<p>The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>Subdivision of Section 14, T. 13 S., R. 29 E.</p>
	<p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p>

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	N. 0°08' E., on the N. and S. center line of sec. 14. Over nearly level land, through moderate undergrowth.
0.40	Underground gas line, bears E. and W.
17.10	Underground telephone line, bears S. 75° E. and N. 75° W.
21.90	Power line, bears S. 75° E. and N. 75° W.
22.00	Right-of-way fence, bears S. 75° E. and N. 75° W.
24.30	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
26.00	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
28.10	State Highway 86, bears S. 75° E. and N. 75° W.
30.60	Telegraph line, bears S. 75° E. and N. 75° W.
31.15	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
31.40	Railroad siding, bears S. 75° E. and N. 75° W.
31.90	Telephone line, bears S. 75° E. and N. 75° W.
32.50	Graded road, bears S. 75° E. and N. 75° W.
32.70	Right-of-way fence, bears S. 75° E. and N. 75° W.
33.90	Power line, bears S. 75° E. and N. 75° W.
41.19	Point for the center ¼ sec. cor. of sec. 14, at intersection with the E. and W. center line of sec. 14; not monumented.
43.10	Telephone line, bears S. 75½° E. and N. 75½° W.
61.63	Point for the C-N 1/16 sec. cor. of sec. 14. Set the iron post 24 ins. in the ground, brass cap mkd. <div style="text-align: center;"> <p>C</p> <p>N 1/16 S14</p> <p>C</p> <p>1969</p> </div> Set a wooden post, 4 ins. diam., 4 ft. long, alongside the iron post.
63.20	Fence, bears E. and W.
82.08	The ¼ sec. cor. of secs. 11 and 14. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
	From the ¼ sec. cor. of secs. 13 and 14. N. 89°53' W., on the E. and W. centerline of sec. 14.


Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	Over nearly level land, through moderate undergrowth.
1.40	Fence, bears N. and S.
30.70	Telephone line, bears S. 75½° E. and N. 75½° W.
39.72	The point for the center ¼ sec. cor. of sec. 14.
67.40	Power line, bears S. 75° E. and N. 75° W.
71.76	Right-of-way fence, bears S. 75° E. and N. 75° W.
72.50	Graded road, bears S. 75° E. and N. 75° W.
74.80	Telephone line, bears S. 75° E. and N. 75° W.
76.40	Railroad siding, bears S. 75° E. and N. 75° W.
77.40	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
79.64	The ¼ sec. cor. of secs. 14 and 15.
	Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
Subdivision of Section 15, T. 13 S., R. 29 E.	
	From the point for the ¼ sec. cor. of secs. 15 and 22. N. 0°07' E., on the N. and S. center line of sec. 15.
	Over nearly level land, through moderate undergrowth.
37.90	Underground telephone line, bears S. 75° E. and N. 75° W.
41.23	Point for the center ¼ sec. cor. of sec. 15, at intersection with the E. and W. center line of sec. 15; not monumented.
42.60	Power line, bears S. 75° E. and N. 75° W.
43.74	Right-of-way fence, bears S. 75° E. and N. 75° W.
45.25	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
46.93	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
49.00	State Highway 86, bears S. 75° E. and N. 75° W.
51.40	Telegraph line, bears S. 75° E. and N. 75° W.
52.10	Southern Pacific Railroad, bears S. 75° E. and N. 75° W.
52.50	Graded road, bears S. 75° E. and N. 75° W.
52.80	Telephone line, bears S. 75° E. and N. 75° W.
53.60	Right-of-way fence, bears S. 75° E. and N. 75° W.
54.80	Power line, bears S. 75° E. and N. 75° W.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
78.50	Fence, bears E. and W.
82.47	<p>The $\frac{1}{4}$ sec. cor. of secs. 10 and 15.</p> <p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p>
	<p>N. $89^{\circ}12'$ W., on the E. and W. center line of sec. 15.</p>
	<p>Over nearly level land.</p>
0.10	Telegraph line, bears S. 75° E. and N. 75° W.
9.40	State Highway 86, bears S. 75° E. and N. 75° W.
17.80	Center of west bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
20.13	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 15, falls on the S. shoulder of the west bound lanes.
	Set the iron post 28 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T13S R29E</p>
	<p style="text-align: center;">C $\frac{E \ 1/16}{S15}$ C</p>
	<p style="text-align: center;">1969</p>
	from which
	<p>An iron post, set 24 ins. in the ground, for a reference monument, bears N. 45° E., 1.83 chs. dist., with the brass cap mkd. T13S R29E S15 RM 120.8 FT 1969 and an arrow pointing to the cor.</p>
	<p>An iron post, set 28 ins. in the ground, for a reference monument, bears N. 45° W., 3.16 chs. dist., with the brass cap mkd. T13S R29E S15 RM 208.6 FT 1969 and an arrow pointing to the cor.</p>
	<p>A bench mark, bears N. $39^{\circ}55'30''$ W., 6.90 chs. dist., monumented by a standard tablet, 3 ins. diam., set in a concrete block, 12 ins. square, projecting 5 ins. above the ground, mkd. B 331 + 1953.</p>
24.52	Center of east bound lanes of Interstate 10, bears S. 75° E. and N. 75° W.
30.33	Right-of-way fence, bears S. 75° E. and N. 75° W.
34.13	Power line, bears S. 75° E. and N. 75° W.
36.73	Power line, bears N. and S.
36.80	Fence, bears N. and S.
40.26	The point for the center $\frac{1}{4}$ sec. cor. of sec. 15.
48.25	Underground telephone line, bears S. 75° E. and N. 75° W.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS		
80.50	The point for the $\frac{1}{4}$ sec. cor. of secs. 15 and 16. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.	
Subdivision of Section 17, T. 13 S., R. 29 E.		
	From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20. N. $0^{\circ}28'$ W., on the N. and S. center line of sec. 17. Over nearly level land, through moderate undergrowth, along a N. and S. fence.	
0.30	Underground gas line, bears E. and N. 88° W.	
40.20	Point for the center $\frac{1}{4}$ sec. cor. of sec. 17, at intersection with the E. and W. center line of sec. 17. Set the iron post 24 ins. in the ground, brass cap mkd.	
		
	The cor. is located 2.5 lks. East of a cor. of fences bearing E. and S. Deposit glass at the base of the iron post.	
80.40	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.	
From the $\frac{1}{4}$ sec. cor. of secs. 16 and 17. West, on the E. and W. center line of sec. 17. Over nearly level land, through moderate undergrowth, along an E. and W. fence.		
0.60	Power line, bears N. and S.	
40.08	The center $\frac{1}{4}$ sec. cor. of sec. 17.	
79.75	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.	
Subdivision of Section 19, T. 13 S., R. 29 E.		
From the $\frac{1}{4}$ sec. cor. of secs. 19 and 30.		

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS


N. $0^{\circ}01'$ W., on the N. and S. center line of sec. 19.

Over nearly level land, through scattered undergrowth.

1.60 Track road, bears NE. and SW.

40.33 Point for the center $\frac{1}{2}$ sec. cor. of sec. 19, at intersection with the E. and W. center line of sec. 19.


Set the iron post 24 ins. in the ground, brass cap mkd.



Set a wooden post, 2 x 4 ins. squared, 4 ft. long, alongside the iron post.

60.46 Point for the C-N $1/16$ sec. cor. of sec. 19.

Set the iron post 24 ins. in the ground, brass cap mkd.



Set a wooden post, 3 x 5 ins. squared, $3\frac{1}{2}$ ft. long, alongside the iron post.

78.00 Underground gas line, bears E. and W.

80.59 The $\frac{1}{2}$ sec. cor. of secs. 18 and 19.

Land, nearly level.

Soil, sandy clay loam.

No timber; Undergrowth, creosote bush and cat claw.

From the $\frac{1}{2}$ sec. cor. of secs. 19 and 20.

N. $78^{\circ}44'$ W., on the E. and W. center line of sec. 19.


Over nearly level land, through moderate undergrowth.

0.80 Wash, 15 lks. wide, 1 ft. deep, drains N.

38.40 The center $\frac{1}{2}$ sec. cor. of sec. 19.

57.65 Point for the C-W $1/16$ sec. cor. of sec. 19.

Set the iron post 22 ins. in the ground, brass cap mkd.



Set a wooden post, 2 x 4 ins. squared, $4\frac{1}{2}$ ft. long, alongside the iron post.



Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
64.00	Wash, 10 lks. wide, 2 ft. deep, drains NE.
75.75	Track road, bears N. and S.
75.85	The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp. Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw.
Subdivision NW $\frac{1}{4}$ of Section 19 <hr style="width: 20%; margin: auto;"/> From the C-W 1/16 sec. cor. of sec. 19. N. 0°06' E., on the N. and S. center line of the NW $\frac{1}{4}$ of sec. 19. Over nearly level land, through scattered undergrowth.	
20.09	Point for the NW 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the NW $\frac{1}{4}$ of sec. 19.
	Set the iron post 24 ins. in the ground, brass cap mkd. NW 1/16 S19 1969
	Set a wooden post, 4 ins. square, 5 ft. long, alongside the iron post.
36.20	Underground gas line, bears S. 86° E. and N. 86° W.
40.18	The W 1/16 sec. cor. of secs. 18 and 19.
From the C-N 1/16 sec. cor. of sec. 19. N. 78°50' W., on the E. and W. center line of the NW $\frac{1}{4}$ of sec. 19. Over nearly level land, through moderate undergrowth.	
9.60	Point for the C-E NW 1/64 sec. cor. of sec. 19.
	Set the iron post 22 ins. in the ground, brass cap mkd. C-E-NW 1/64 S19 1969
	Set a wooden post, 4 ins. square, 4 $\frac{1}{2}$ ft. long, alongside the iron post.
19.20	The NW 1/16 sec. cor. of sec. 19.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
37.32	The N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.
Subdivision of Section 25, T. 13 S., R. 29 E.	
From the 1/4 sec. cor. of secs. 25 and 36.	
N. 0°14' E., on the N. and S. center line of sec. 25.	
Over nearly level cultivated land, along a fence bearing N. 0°35' E.	
19.98	Point for the C-S 1/16 sec. cor. of sec. 25.
Set the iron post 24 ins. in the ground, brass cap mkd.	
<p style="text-align: center;">C S 1/16 S25 C 1969</p>	
from which	
A fence cor., bears N. 8°20' E., 109 lks. dist.; fences bear E. and S. 0°35' W.	
39.96	Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E. and W. center line of sec. 25. This point falls in a cultivated field. The owner of this land preferred not to have this point monumented.
81.13	The 1/4 sec. cor. of secs. 24 and 25.
Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw 1st 1/4 mile to the E. only.	
From the 1/4 sec. cor. of secs. 25 and 30, on the E. bdy. of the Tp.	
S. 89°26' W., on the E. and W. center line of sec. 25.	
Over nearly level land, through scattered undergrowth.	
0.67	Fence, bears N. and S.; enter cultivated land, bears N. and S.
41.60	Irrigation ditch, drains N.
41.75	The point for the center 1/4 sec. cor. of sec. 25.
57.60	Wash, 30 lks. wide, 2 ft. deep, drains NE.
64.50	Track road, bears N. 10° E. and S. 10° W.
81.76	Graded road, bears N. and S.
81.86	The 1/4 sec. cor. of secs. 25 and 26.

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw last ½ mile to the N. only.</p>
	<p>Subdivision of Section 27, T. 13 S., R. 29 E.</p>
	<p>From the ¼ sec. cor. of secs. 27 and 34.</p>
	<p>N. 1°29' E., on the N. and S. center line of sec. 27.</p>
	<p>Over nearly level land, along a fence bearing N. 1°30' E.</p>
20.30	<p>Fall 1.7 lks. West of a fence cor.; fences bear N. 1°30' E., E. and S. 1°30' W.</p>
39.20	<p>Fall 3 lks. West of a fence cor.; fences bear N. 1°30' E., E. and S. 1°30' W.</p>
39.73	<p>Point for the center ¼ sec. cor. of sec. 27, at intersection with the E. and W. center line of sec. 27.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<div style="text-align: center;">  </div>
	<p>The cor. is located 3.5 lks. West of a fence bearing N. 1°30' E. and S. 1°30' W.</p>
	<p>Deposit glass at the base of the iron post.</p>
54.73	<p>Point for the C-N-S-N 1/256 sec. cor. of sec. 27.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<div style="text-align: center;">  </div>
	<p>from which</p>
	<p style="padding-left: 40px;">A fence cor., bears S. 18°34' E., 14.5 lks. dist.; fences bear N. 1°30' E., S. 1°30' W. and W.</p>
79.73	<p>The point for the ¼ sec. cor. of secs. 22 and 27.</p>
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw, full mile to the W. only.</p>
	<p>From the point for the ¼ sec. cor. of secs. 26 and 27.</p>
	<p>S. 89°41' W., on the E. and W. center line of sec. 27.</p>
	<p>Over cultivated land.</p>

Survey of Section Subdivision, T. 13 S., R. 29 E.

CHAINS	
32.00	Leave cultivated land; enter farm yard.
40.10	Enter corral, bears N. and S.
41.30	Power line, bears N. and S.
41.35	Leave corral, bears N. 1°30' E. and S. 1°30' W.
41.39	The center $\frac{1}{4}$ sec. cor. of sec. 27.
	Enter moderate undergrowth, bears N. and S.
42.00	Wash, 15 lks. wide, 3 ft. deep, drains N.
74.70	Field dyke, bears NE. and SW.
76.90	Wash, 40 lks. wide, 3 ft. deep, drains NE.
80.51	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	<p>Land, nearly level. Soil, sandy clay loam. No timber; Undergrowth, creosote bush and cat claw 2nd half.</p>
General Description	
<p>The elevation in Township 13 South, Range 29 East, ranges from 3,540 to 3,860 ft. above sea level. The land is nearly level throughout the township. The soil is sandy clay loam which supports a moderate growth of creosote bush, cat claw, grass and scattered mesquite.</p>	
<p>The Southern Pacific Railroad enters the township at the east boundary of section 24, bears N. 75° W. and leaves at the west boundary of section 7. Interstate 10, parallels the railroad. Numerous graded and track roads provide good access through the township.</p>	
<p>The majority of the water used comes from wells. There are settlers in portions of the township. The general drainage is Northeast. The south portion of the township is under cultivation and the north portion is used for grazing.</p>	

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Howard H. Thomas	Cadastral Surveyor
Ronald G. Williams	Cadastral Surveyor
Ira M. Thiessen	Surveying Technician
Martin W. Fuller	Surveying Aid
Victor E. Templeton	Surveying Aid
David G. Jaramillo	Surveying Aid
Doyle L. Herbert	Surveying Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Gary T. Oviatt, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 20th day of November, 19 68, (I) ~~(We)~~ have dependently resurveyed the east and west boundaries and a portion of the north boundary and subdivisional lines, and surveyed subdivisions in certain sections, Township 13 South, Range 29 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 18, 1970 (Date) Gary T. Oviatt (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date JAN 4 1971

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of the east and west boundaries and a portion of the north boundary and the subdivisional lines, and the survey of subdivisions in certain sections, Township 13 South, Range 29 East, Gila and Salt River Meridian, Arizona, executed by Gary T. Oviatt, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

FEB 22 1972 (Date) [Signature] (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.