

Form 9180-6  
(April 1965)  
(formerly 4-679)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

DEPENDENT RESURVEY

OF A

PORTION OF THE EAST BOUNDARY

AND

SUBDIVISIONAL LINES

SURVEY

OF

SUBDIVISIONS IN SECTIONS 11, 12, 13 and 14

METES AND BOUNDS SURVEY

OF

LOT 13 IN SECTION 12,

TOWNSHIP 10 NORTH, RANGE 21 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Gary T. Oviatt Cadastral Surveyor

Ira M. Thiessen Cadastral Surveyor

Under special instructions dated May 28, 19 69, which provided for the surveys included under Group Number 508, approved May 28, 1969, and assignment instructions dated May 29, 19 69, and July 11, 1969.

Survey commenced June 30, 19 69

Survey completed August 26, 19 69

1A

BOOK 4936

# INDEX DIAGRAM

Township 10 North, Range 21 East,

6	5	4	3	2 23	1 14	
7	8	9	10 21	11 12 19	12 10	3
18	17	16	15 17	14 7 15	13 5	1
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Subdivision of Sec. 11 -- Page 24

" " " 12 -- Page 30

" " " 13 -- Page 42

" " " 14 -- Page 59

Metes and Bounds Survey of Lot 13, Section 12 -- Page 67

Township 10 North, Range 21 East  
Gila and Salt River Meridian, Arizona

## CHAINS

The boundaries and subdivisional lines were surveyed in 1883 by O. D. Wheeler. The north boundary of the White Mountain Indian Reservation through sections 30, 31, 32 and 33 was surveyed in 1887 by C. H. Wallace. The same portion of the White Mountain Indian Reservation was resurveyed in 1906 by J. B. Wright. The south and west boundaries and a portion of the subdivisional lines and the north boundary of the Fort Apache Indian Reservation, (formerly called White Mountain Indian Reservation) through sections 30, 31, 32 and 33 were resurveyed in 1915 by S. E. Blout. The north boundary was resurveyed in 1921 by Kinsey and Blout.

The following notes are those of a dependent resurvey of a portion of the east boundary and subdivisional lines, designed to restore the corners in their true original location according to the best available evidence, and a survey of subdivisions in sections 11, 12, 13 and 14, and a metes and bounds survey of Lot 13 in section 12, Township 10 North, Range 21 East, Gila and Salt River Meridian, Arizona. The mean high water line of Fools Hollow Lake as shown on the plat of survey was determined by using a combination of field data and an enlargement of aerial photo ETC-8-162 dated 7-16-68.

This survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated May 28, 1969. The direction of all lines were determined by solar observations and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of section 13, as scaled from Army Map Service Quadrangle HOLBROOK, Arizona, 1960, scale 1:250,000 is: Latitude 34°15'25" North and Longitude 110°03'24" West.

The mean magnetic declination was found to be 14° East.

---

Dependent Resurvey, Portion East Boundary  
Township 10 North, Range 21 East

---

Reestablishment of the Survey executed  
by O. D. Wheeler in 1883

---

The cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented by a water pipe. 1 in. diam., set flush with the ground, and substantiated by the remains of an original bearing tree:

A juniper branch, 14 ins. diam., bears S. 30° E.,  
117 lks. dist., mkd. T10N R22E S19 BT.

At the corner point .

Dep. Res., Portion East Boundary, T. 10 N., R. 21 E.

## CHAINS

Set the iron post 8 ins. below the surface of the ground, brass cap mkd.

T10N  
R21E R22E  
S13 | S18  
S24 | S19  
1969

from which

An iron post, set 24 ins. in the ground, for a reference monument, bears S. 45° E., 34.8 lks. dist., with brass cap mkd. T10N R22E S19 RM 23 FT 1969 and an arrow pointing to the cor.

An iron post, set 22 ins. in the ground, for a reference monument, bears S. 45° W., 34.8 lks. dist., with brass cap mkd. T10N R21E S24 RM 23 FT 1969 and an arrow pointing to the cor.

A re-bar,  $\frac{1}{2}$  in. diam., bears S. 49°25' W., 100 ft. dist., origin unknown.

A re-bar,  $\frac{1}{2}$  in. diam., bears S. 49°25' W., 175 ft. dist., origin unknown.

Deposit the 1 in. water pipe alongside the iron post. N. 0°30' W., bet. secs. 13 and 18.

Over nearly level land, through scattered undergrowth.

- 0.18 Power line, bears N. 61°32' E. and S. 61°32' W.
- 0.22 Forest Service Road No. 43, paved, bears N. 78°19' E. and S. 78°19' W.
- 0.72 Fence cor.; fences bear S. 88° W. and N. 0°30' W.
- 10.00 Fall 1.6 lks. East of a pipe,  $\frac{3}{4}$  ins. diam., located underneath a N. and S. fence.
- 19.99 The S 1/16 sec. cor. of secs. 13 and 18, monumented by a steel pin,  $\frac{1}{2}$  in. diam., projecting 3 ins. above the ground. This cor. is locally accepted; not remonumented.
- The cor. is located underneath a N. and S. fence.
- 39.98 The  $\frac{1}{4}$  sec. cor. of secs. 13 and 18, monumented by a steel pin,  $\frac{1}{2}$  in. diam., projecting 1 in. above the ground set in a cement base, located underneath a N. and S. fence. This cor. is locally accepted and is the best remaining evidence of the orig. cor. position; not remonumented.
- 
- N. 0°32' W., beginning new measurement.
- Over gently rolling land.
- 19.99 Point for the N 1/16 sec. cor. of secs. 13 and 18, at proportionate dist.; not monumented.
- 39.98 The cor. of secs. 7, 12, 13 and 18, monumented by a steel pin,  $\frac{1}{2}$  in. diam., projecting 1 in. above the ground set in a cement base, located underneath a N. and S. fence. This cor. is locally accepted and is the best remaining evidence of the orig. cor. position; not remonumented.

## Dep. Res., Portion East Boundary, T. 10 N., R. 21 E.

CHAINS	
	<p>Land, nearly level to gently rolling. Soil, rocky clay loam. Timber, scattered juniper and pine. Undergrowth, grass and scrub oak.</p>
	<p>N. 0°04' E., bet. secs. 7 and 12.</p> <p>Over gently rolling land, through low undergrowth.</p>
9.995	<p>Point for the S-S 1/64 sec. cor. of secs. 7 and 12, at proportionate dist., falls in a track road bearing E. and W.</p> <p>Set the iron post 6 ins. below the surface of the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R21E R22E S-S 1/64 S12   S 7 1969</p> <p>from which</p> <p>An iron post, set 22 ins. in the ground, for a reference monument, bears N. 0°04' E., 22.7 lks. dist., with brass cap mkd. T10N R21E R22E S 7 S12 RM 15 FT 1969 and an arrow pointing to the cor.</p> <p>An iron post, set 24 ins. in the ground, for a reference monument, bears N. 45° W., 22.7 lks. dist., with brass cap mkd. T10N R21E S12 RM 15 FT 1969 and an arrow pointing to the cor.</p>
10.20	Fence cor.; fences bear E., S. 0°30' E., W. and NW.
10.80	Graded road, bears N. 35° W. and S. 35° E., curving S.; enter moderate timber, bears E. and NW.
17.60	S. rim overlooking Fools Hollow Lake, bears S. 75° E. and N. 75° W.; desc. steep N. slope.
18.50	Mean high water line on the S. shore of Fools Hollow Lake, bears S. 75° E. and N. 75° W.; thence over water by triangulation.
19.99	Point for the S 1/16 sec. cor. of secs. 7 and 12, at proportionate dist., falls in the middle of Fools Hollow Lake; not monumented.
21.70	Mean high water line on the N. shore of Fools Hollow Lake, bears S. 75° E. and N. 75° W., end of triangulation; asc. steep S. slope.
23.60	N. rim overlooking Fools Hollow Lake, bears S. 75° E. and N. 75° W.; thence over gently rolling land, along a fence bearing N.
38.80	Jeep road, bears E. and W., curving N.
39.98	The 1/2 sec. cor. of secs. 7 and 12, monumented by a basalt stone, 17 x 11 x 7 ins., set 9 ins. in the ground, mkd. 1/2 on W. face, mound of stone W.

Dep. Res., Portion East Boundary, T. 10 N., R. 21 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N  
R21E R22E

$\frac{1}{2}$   
S12 | S 7  
1969

from which

A juniper, 12 ins. diam., bears S.  $54\frac{1}{2}^{\circ}$  W., 37  
lks. dist., mkd. T10N R21E  $\frac{1}{2}$  S12 BT.

Deposit the original cor. stone in the mound of stone  
W. of the cor.

Set a steel fence post,  $5\frac{1}{2}$  ft. long alongside the iron  
post.

Raise a mound of stone W. of the cor.

The cor. is located under a N. and S. fence.

---

N.  $0^{\circ}11'$  W., beginning new measurement.

Over gently rolling land, through moderate timber.

Continue along N. and S. fence.

40.14

The cor. of secs. 1, 6, 7 and 12, monumented by an unmkd.  
basalt stone, 17 x 10 x 6 ins., loosely set and with a  
mound of stone W. The basalt stone is located at a cor.  
of fences extending E. and S., and is accepted as the  
best remaining evidence of the original cor. position.

At the corner point

Set the iron post 20 ins. in the ground, brass cap mkd.

T10N  
R21E R22E

S 1 | S 6  
S12 | S 7  
1969

Bury the unmarked cor. stone alongside the iron post.

Set a steel fence post,  $5\frac{1}{2}$  ft. long, alongside the iron  
post.

Land, gently rolling.

Soil, rocky clay loam.

Timber, pine and juniper.

Undergrowth, bunch grass.

---

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

## CHAINS

Dependent Resurvey, Portion Subdivisional Lines  
Township 10 North, Range 21 EastReestablishment of the Survey executed  
by O. D. Wheeler in 1883From the cor. of secs. 13, 18, 19 and 24, on the E. bdy.  
of the Tp.

N. 89°58' W., bet. secs. 13 and 24.

Over gently rolling land, through moderate timber.

0.34 Power line, bears N. 61°32' E. and S. 61°32' W.

1.08 Forest Service Road No. 43, bears N. 78°19' E. and S.  
78°19' W.20.18 Point for the E 1/16 sec. cor. of secs. 13 and 24, at  
proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

	T10N R21E
E 1/16	$\frac{S13}{S24}$
	1969

from which

A juniper, 25 ins. diam., bears S. 29° E., 181 lks.  
dist., mkd. E 1/16 S24 BT.A pine, 10 ins. diam., bears N. 12½° W., 51 lks.  
dist., mkd. E 1/16 S13 BT.A re-bar, ½ in. diam., bears S. 89°58' E., 28 lks.  
dist.

Raise a mound of stone N. of the cor.

26.90 Forest Service Road No. 43, paved, bears S. 84° E. and  
N. 84° W.30.27 A steel pin, ½ in. diam., projecting 2 ins. above the  
ground, origin unknown.

31.50 Power line, bears S. 53° E. and N. 53° W.

40.36 The point for the ¼ sec. cor. of secs. 13 and 24 falls  
in Forest Service Road No. 43, bears N. 85° E. and S.  
85° W., curving NW. The cor. point was determined from  
two steel pins, ½ in. diam., established as reference  
points in 1957 by a registered Civil Engineer. The  
steel pins, bear S. 4°30' E., 100 ft. and 150 ft. dist.,  
respectively.

At the corner point

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS

Set a copper weld,  $\frac{3}{8}$  ins. diam., 18 ins. long, flush with the top of pavement, top of copper weld mkd.

$$\frac{1}{4} \frac{S13}{S24}$$

from which

A pine, 6 ins. diam., bears N.  $22\frac{1}{2}^\circ$  E., 150 $\frac{1}{2}$  lks. dist., mkd. T10N R21E  $\frac{1}{4}$  S13 BT.

A pine, 8 ins. diam., bears S.  $6\frac{1}{4}^\circ$  E., 117 $\frac{1}{2}$  lks. dist., mkd. T10N R21E  $\frac{1}{4}$  S24 BT.

A re-bar,  $\frac{1}{2}$  in. diam., bears S.  $33^\circ 05'$  E., 146.8 lks. dist., set in a mound of stone with a sandstone, 18 x 14 x 7 ins., mkd.  $\frac{1}{4}$  on N. face alongside. A Forest Service employee set and mkd. this stone in 1967. There is no evidence to support this position as being the original cor. point.

---

N.  $89^\circ 52'$  W., beginning new measurement.

Over gently rolling land.

- 0.50 Leave pavement, bears N.  $85^\circ$  E. and NW.
- 7.00 Fools Hollow Wash, 30 lks. wide, 2 ft. deep, drains NE.
- 8.50 Track road, bears N. and S.
- 10.057 Point for the E-W  $1/64$  sec. cor. of secs. 13 and 24, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

$$\begin{array}{r} \text{T10N R21E} \\ \text{E-W } 1/64 \quad \frac{S13}{S24} \\ 1969 \end{array}$$

from which

A pine, 8 ins. diam., bears S.  $14\frac{1}{2}^\circ$  E., 103 $\frac{1}{2}$  lks. dist., mkd. EW  $1/64$  S24 BT.

A pine,  $7\frac{1}{2}$  ins. diam., bears N.  $49\frac{3}{4}^\circ$  W., 49 lks. dist., mkd. EW  $1/64$  S13 BT.

Raise a mound of stone N. of the cor.

- 11.50 Track road, bears NE. and SW.
- 20.11 5 Point for the W  $1/16$  sec. cor. of secs. 13 and 24, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

$$\begin{array}{r} \text{T10N R21E} \\ \text{W } 1/16 \quad \frac{S13}{S24} \\ 1969 \end{array}$$



Dep. Res., Portion Subdivisional Lines, T. 10 N.; R. 21 E.

CHAINS					
	<p>from which</p> <p>A pine, 8 ins. diam., bears S. 9° W., 13 lks. dist., mkd. W 1/16 S24 BT.</p> <p>A pine, 8 ins. diam., bears N. 70½° W., 52½ lks. dist., mkd. W 1/16 S13 BT.</p> <p>Raise a mound of stone N. of the cor.</p>				
33.40	Track road, bears N. and S.				
38.00	Forest Service Road No. 43, paved, bears N. 68° E. and S. 68° W.				
39.40	Ponderosa Parkway, bears N. and S.				
40.23	<p>The cor. of secs. 13, 14, 23 and 24, monumented by a steel pin, ½ in. diam., projecting 5 ins. above the ground. This pin is recognized by local land owners and local surveyors as the cor. and is accepted as the best available evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T10N R21E</p> <table border="1" style="margin: auto;"> <tr> <td>S14</td> <td>S13</td> </tr> <tr> <td>S23</td> <td>S24</td> </tr> </table> <p>1969</p> </div> <p>from which</p> <p>A pine, 10 ins. diam., bears N. 55½° E., 212 lks. dist., mkd. T10N R21E S13 BT.</p> <p>A pine, 10 ins. diam., bears S. 70½° E., 204½ lks. dist., mkd. T10N R21E S24 BT.</p> <p>Junction of paved roads, bears S. 60° E., 95 lks. dist.; roads bear N., N. 68° E. and S. 89°15' W.</p> <p>Bury the steel pin alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak.</p>	S14	S13	S23	S24
S14	S13				
S23	S24				
3.40	<p>N. 0°17' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through moderate undergrowth, along the E. boundary of Show Low Country Club Estates.</p> <p>Malapai Dr., bears W., from Ponderosa Parkway.</p>				
18.10	Meadow View Lane, bears W., from Ponderosa Parkway.				
20.02	The S 1/16 sec. cor. of secs. 13 and 14, monumented by a pipe, 1 in. diam., projecting 3 ins. above the ground,				

## Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

## CHAINS

adjacent to a fence cor.; fences bear N., S. and W. This position is accepted as the S 1/16 sec. cor. by local residents and is a cor. of the Show Low Country Club Estates.

At the corner point

Set the iron post 22 ins. in the ground, brass cap mkd.

T10N R21E

S 1/16

S14|S13

1969

from which

A pine, 7 ins. diam., bears N.  $43\frac{1}{2}^{\circ}$  W.,  $33\frac{1}{2}$  lks. dist., mkd. S 1/16 S14 BT.

Bury the pipe alongside the iron post.

Raise a mound of stone W. of the cor.

The cor. is located 43 lks. West of a graded road bearing N. and S.

Leave Show Low Country Club Estates, bears S.  $0^{\circ}17'$  E. and S.  $89^{\circ}29'$  W.; enter moderate undergrowth.

34.00 Fence cor.; fences extend S. and W.

35.50 Graded road, bears S. and N.  $70^{\circ}$  W.

36.10 Power line, bears S.  $53^{\circ}$  E. and N.  $53^{\circ}$  W.

39.96 The  $\frac{1}{2}$  sec. cor. of secs. 13 and 14, monumented by a granite stone, 14 x 10 x 5 ins., set 6 ins. in the ground in a mound of stone, mkd.  $\frac{1}{2}$  on W. face and a X on top, from which the remains of the orig. bearing trees:

A pine, 14 ins. diam., bears S.  $7^{\circ}$  E., 24 lks. dist., mkd.  $\frac{1}{2}$  S BT. (Record: Juniper, S.  $30^{\circ}$  E., 22 lks. dist.).

A juniper, 22 ins. diam., bears S.  $88^{\circ}$  W., 155 lks. dist., mkd. BT. (Record: Yellow Pine, S.  $89^{\circ}$  W., 151 lks. dist.).

At the corner point

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R21E

$\frac{1}{2}$

S14|S13

1969

from which

A juniper, 12 ins. diam., bears S.  $25\frac{1}{2}^{\circ}$  W., 30 lks. dist., mkd. T10N R21E  $\frac{1}{2}$  S14 BT.

A fence cor., bears N.  $77^{\circ}$  E., 37.5 lks. dist., with fences extending N., E. and W.

## Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

## CHAINS

Bury the orig. cor. stone alongside the iron post.

N.  $0^{\circ}02'$  E., beginning new measurement.

Over gently rolling land.

- 0.10 Fence, bears E. and W.
- 10.03 Point for the S-N  $1/64$  sec. cor. of secs. 13 and 14, at proportionate dist.; not monumented.
- 18.10 Fence, bears E. and W.
- 20.06 The N  $1/16$  sec. cor. of secs. 13 and 14, monumented by a pipe, 1 in. diam., projecting 2 ins. above the ground. This position is accepted by local residents as the N  $1/16$  sec. cor. point.

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E  
N  $1/16$   
S14|S13  
1969

Bury the pipe alongside the iron post.

Raise a mound of stone W. of the cor.

The cor. is located 8 lks. East of a N. and S. fence.

- 30.09 Point for the N-N  $1/64$  sec. cor. of secs. 13 and 14, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E  
N-N  $1/64$   
S14|S13  
1969

from which

A pine, 10 ins. diam., bears N.  $48^{\circ}$  E., 205 lks. dist., mkd. N-N  $1/64$  S13 BT.

A pine, 8 ins. diam., bears S.  $22\frac{1}{2}^{\circ}$  W., 93 lks. dist., mkd. N-N  $1/64$  S14 BT.

Raise a mound of stone W. of the cor.

The cor. is located 1 lk. West of a N. and S. fence.

- 32.50 Wash, 10 lks. wide, 2 ft. deep, drains NE. into Fools Hollow Lake.

- 33.80 Graded road, bears N.  $40^{\circ}$  E. and S.  $40^{\circ}$  W.

- 40.12 The cor. of secs. 11, 12, 13 and 14, monumented by a granite stone, 12 x 9 x 4 ins., firmly set in a mound of stone, mkd. 1 notch on E. and 4 notches on S. faces.

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E  
 $\frac{S11}{S14} | \frac{S12}{S13}$   
 1969

from which

A pine, 8 ins. diam., bears N.  $61\frac{1}{2}^\circ$  E., 30 lks. dist., mkd. T10NR21E S12 BT.

A pine, 9 ins. diam., bears S.  $52^\circ$  E., 37 lks. dist., mkd. T10NR21E S13 BT.

A pine,  $7\frac{1}{2}$  ins. diam., bears S.  $36\frac{3}{4}^\circ$  W.,  $58\frac{1}{2}$  lks. dist., mkd. T10NR21E S14 BT.

A pine,  $7\frac{1}{2}$  ins. diam., bears N.  $32\frac{1}{2}^\circ$  W., 40 lks. dist., mkd. T10NR21E S11 BT.

Bury the orig. cor. stone alongside the iron post.

Raise a mound of stone W. of the cor.

The cor. is located underneath a N. and S. fence.

Land, gently rolling.  
 Soil, rocky clay loam.  
 Timber, pine, juniper and oak.  
 Undergrowth, grass and scrub oak.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp.

N.  $89^\circ 28'$  W., bet. secs. 12 and 13.

Over nearly level land, through open meadow.

5.80 Fence, bears N. and S.; enter cultivated field.

9.98 Point for the E-E  $\frac{1}{64}$  sec. cor. of secs. 12 and 13, at proportionate dist.; not monumented.

14.30 Fence, bears N. and S.; leave cultivated field, enter scattered timber, bears SE. and NW

19.96 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 12 and 13, at proportionate dist.

Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.

T10N R21E  
 E  $\frac{1}{16}$   $\frac{S12}{S13}$   
 1969

from which

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
	<p>A fence cor., bears N. <math>18\frac{3}{4}^{\circ}</math> W., 12 lks. dist., with fences extending N., S. and W.</p>
20.00	Fence, bears N. and S.
29.94	<p>Point for the W-E <math>1/64</math> sec. cor. of secs. 12 and 13, at proportionate dist.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T10N R21E W-E <math>1/64</math> <math>\frac{S12}{S13}</math> 1969</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. <math>33^{\circ}</math> W., <math>67\frac{1}{2}</math> lks. dist., mkd. WE <math>1/64</math> S12 BT.</p> <p>Fence cor., bears N. <math>33^{\circ}</math> W., 9.5 lks. dist., with fences extending E. and S. An open pipe, <math>\frac{1}{2}</math> in. diam., is adjacent to this fence cor.</p> <p>A re-bar, <math>\frac{1}{2}</math> in. diam., projecting 4 ins. above the ground, bears N. <math>0^{\circ}15'</math> E., 24 lks. dist.</p>
30.00	Fence, bears N. and S.
34.80	Graded road, bears S. $30^{\circ}$ E. and N. $30^{\circ}$ W.
36.30	Mean high water line on E. shore of Fools Hollow Lake, bears S. $30^{\circ}$ E. and N. $30^{\circ}$ W.; thence across Fools Hollow Lake by triangulation.
39.92	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 12 and 13 falls in Fools Hollow Lake. George Sohn, registered Civil Engineer recorded finding the original cor. in 1957. A fence cor. projecting 3 ft. above the waters surface, with fence lines extending south and west, bears a close relationship to the position recorded by Sohn and is accepted as the best remaining evidence of the original cor. position, not remonumented.</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. <math>10\frac{1}{2}^{\circ}</math> E., 3.60 chs. dist., mkd. T10NR21E <math>\frac{1}{4}</math> S12 BT.</p> <p>A pine, 7 ins. diam., bears N. <math>3\frac{1}{2}^{\circ}</math> W., 4.68 chs. dist., mkd. T10NR21E <math>\frac{1}{4}</math> S12 BT.</p> <p style="text-align: center;">_____</p> <p>S. <math>89^{\circ}46'</math> W., beginning new measurement.</p> <p>Continue across lake, by triangulation.</p>
10.025	Point for the E-W $1/64$ sec. cor. of secs. 12 and 13, at proportionate dist., falls in Fools Hollow Lake; not monumented.
20.05	Point for the W $1/16$ sec. cor. of secs. 12 and 13, at proportionate dist., falls in Fools Hollow Lake, impracticable to monument.

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS									
22.10	Mean high water line on the W. shore of Fools Hollow Lake bears N. and S.; end of triangulation.								
22.25	<p>Point selected for the witness W 1/16 sec. cor. of secs. 12 and 13.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T10N R21E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 20px;">W</td> <td style="padding-right: 20px;">W 1/16</td> <td style="text-align: center;"> <math>\frac{S12}{S13}</math> </td> <td style="padding-left: 20px;">→</td> </tr> <tr> <td>C</td> <td></td> <td style="text-align: center;">1969</td> <td></td> </tr> </table> </div> <p>from which</p> <p>A pine, 8 ins. diam., bears S. 8° W., 139 lks. dist., mkd. WC W 1/16 S13 BT.</p> <p>A pine, 12 ins. diam., bears N. 79° W., 109 lks. dist., mkd. WC W 1/16 S12 BT.</p>	W	W 1/16	$\frac{S12}{S13}$	→	C		1969	
W	W 1/16	$\frac{S12}{S13}$	→						
C		1969							
28.10	Mean high water line on S. shore of a small cove, bears N. 70° E. and S. 70° W.; thence across cove.								
30.075	Point for the W-W 1/64 sec. cor. of secs. 12 and 13, at proportionate dist., falls in a cove draining into Fools Hollow Lake; not monumented.								
33.20	Mean high water line on N. shore of a small cove, bears N. 70° E. and S. 70° W.; enter rolling land.								
37.00	Graded road, bears NE. and SW.								
40.10	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, nearly level to rolling. Soil, rocky clay loam. Timber, scattered to moderate pine, juniper and oak. Undergrowth, grass and scrub oak.</p>								
5.01	<p>N. 0°21' W., bet. secs. 11 and 12.</p> <p>Over rolling land, through moderate timber.</p> <p>Point for the S-S-S 1/256 sec. cor. of secs. 11 and 12, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T10N R21E</p> <p>S-S-S 1/256</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding-right: 10px;">S11</td> <td style="padding-right: 10px;">S12</td> </tr> <tr> <td colspan="2" style="text-align: center;">1969</td> </tr> </table> </div> <p>from which</p> <p>A fence cor., bears S. 45° E., 3 lks. dist., with fences extending N., S. and E.</p> <p>Raise a mound of stone W. of the cor.</p>	S11	S12	1969					
S11	S12								
1969									

## Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
10.02	Point for the S-S 1/64 sec. cor. of secs. 11 and 12, at proportionate dist.; not monumented.
20.04	Point for the S 1/16 sec. cor. of secs. 11 and 12, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T10N R21E S 1/16 S11 S12 1969</p>
	from which
	<p style="padding-left: 40px;">A juniper, 7½ ins. diam., bears S. 65° W., 97½ lks. dist., mkd. S 1/16 S11 BT.</p>
	<p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 87° W., 70 lks. dist., mkd. S 1/16 S11 BT.</p>
	Raise a mound of stone W. of the cor.
	The cor. is located 6 lks. West of a N. and S. fence.
21.30	S. bank of Spillway, bears S. 66° E. and N. 66° W.
22.50	N. bank of Spillway, bears S. 66° E. and N. 66° W.
25.05	Point for the S-N-S 1/256 sec. cor. of secs. 11 and 12, at proportionate dist.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T10N R21E S-N-S 1/256 S11 S12 1969</p>
	from which
	<p style="padding-left: 40px;">A juniper, 7 ins. diam., bears N. 51° E., 39 lks. dist., mkd. S-N-S 1/256 S12 BT.</p>
	<p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 51° W., 59½ lks. dist., mkd. S-N-S 1/256 S11 BT.</p>
	Raise a mound of stone W. of the cor.
	The cor. is located 11½ lks. West of a cor. of fences extending N. 75° E., S. 66° E. and S.
30.06	Point for the N-S 1/64 sec. cor. of secs. 11 and 12, at proportionate dist.; not monumented.
40.08	The ¼ sec. cor. of secs. 11 and 12, as determined from the original bearing rocks.
	<p style="padding-left: 40px;">A basalt boulder, 76 x 84 x 93 ins., bears N. 62°30' E., 78 lks. dist., mkd. X ¼ BR. (Record: N. 65° E.).</p>
	<p style="padding-left: 40px;">A basalt boulder, 72 x 72 x 60 ins., bears N. 27° W., 57 lks. dist., mkd. X ¼ BR. (Record: N. 20° W.).</p>

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
	<p>At the corner point</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T10N R21E  <math>\frac{1}{2}</math>            S11   S12            1969</p> <p>Set a steel fence post, 5½ ft. long, alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°18' W., beginning new measurement.</p> <p>Over rolling land.</p> <p>1.00 Show Low Creek, 30 lks. wide, 2 ft. deep, course W.; asc. rocky S. slope.</p> <p>17.00 Top of asc., thence over gently rolling land.</p> <p>40.01 The cor. of secs. 1, 2, 11 and 12, monumented by a basalt stone, 24 x 24 x 7 ins., firmly set in a mound of stone, mkd. 1 notch on E. and 5 notches on S. faces, from which an original bearing tree:</p> <p style="padding-left: 40px;">A juniper, 52 ins. diam., bears S. 65½° W., 9 lks. dist., mkd. T10NR21E S11 BT.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T10N R21E  <u>S 2   S 1</u>  <u>S11   S12</u>            1969</p> <p>Deposit the orig. cor. stone in the mound of stone around the iron post.</p> <p>Land, rolling.            Soil, rocky clay loam.            Timber, pine, juniper and oak.            Undergrowth, grass and scrub oak.</p>
40.19	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 89°25' W., bet. secs. 1 and 12.</p> <p>Over gently rolling land, through moderate timber, along the N. side of an old abandoned fence line.</p> <p>The ¼ sec. cor. of secs. 1 and 12, monumented by a basalt stone, 22 x 12 x 3 ins., set 6 ins. in the ground, mkd. ¼ on N. face, mound of stone S., from which the remains of the original bearing trees:</p>



## Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

## CHAINS

A pine (snag), 10 ins. diam., bears S.  $89^{\circ}$  W., 23 lks. dist., mkd.  $\frac{1}{4}$  S BT. (Record: 27 lks. dist.).

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E

$\frac{1}{4}$   $\frac{S 1}{S12}$

1969

from which

A juniper, 14 ins. diam., bears S.  $71\frac{1}{2}^{\circ}$  E., 56 lks. dist., mkd. T10NR21E  $\frac{1}{4}$  S12 BT.

The cor. is located 18 lks. North of an old abandoned fence line bearing E. and W.

Deposit the orig. cor. stone in a mound of stone N. of the iron post.

S.  $89^{\circ}43'$  W., beginning new measurement.

Over gently rolling land.

25.10 Fence, bears N.  $20^{\circ}$  E. and S.  $20^{\circ}$  W.; end of abandoned fence.

38.40 E. rim of canyon, bears S. and N.  $50^{\circ}$  W.; desc. W. slope.

40.16 The cor. of secs. 1, 2, 11 and 12.

Land, gently rolling.

Soil, rocky clay loam.

Timber, pine and juniper.

Undergrowth, small juniper and pine and grass.

From the cor. of secs. 13, 14, 23 and 24.

S.  $89^{\circ}15'$  W., bet. secs. 14 and 23.

Over gently rolling land, through moderate timber, along the S. boundary of Show Low Country Club Estates.

18.60 E. portion of Fairway Drive Loop, bears N. and S.

20.205 Point for the E  $\frac{1}{16}$  sec. cor. of secs. 14 and 23, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E

E  $\frac{1}{16}$   $\frac{S14}{S23}$

1969

from which

A pine, 7 ins. diam., bears S.  $14\frac{1}{2}^{\circ}$  E., 170 lks. dist., mkd. E  $\frac{1}{16}$  S23 BT.

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
	<p>A pine, 10 ins. diam., bears S. <math>18\frac{1}{2}^{\circ}</math> W., 111 lks. dist., mkd. E 1/16 S23 BT.</p> <p>A bench mark, bears S. <math>61^{\circ}35'</math> E., 171 lks. dist., monumented by a brass tablet, 3 ins. diam., set in a cement block, 9 ins. square, projecting 5 ins. above the ground, tablet mkd. C 141 1935.</p> <p>A pipe, <math>\frac{1}{2}</math> in. diam., projecting 3 ins. above the ground, bears N. <math>76^{\circ}39'</math> E., 133 lks. dist.</p>
20.70	Track road, bears N. and S.
40.41	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor. Cor. point falls in the center of a paved road which is the W. portion of the Fairway Dr. Loop.</p> <p>Set a copper weld, <math>\frac{3}{4}</math> in. diam., 18 ins. long, flush with the pavement, mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math> <math>\frac{S14}{S23}</math> 1969                 </div> <p>from which</p> <p>A pine, 9 ins. diam., bears S. <math>30\frac{1}{2}^{\circ}</math> E., 103 lks. dist., mkd. T10NR21E <math>\frac{1}{4}</math> S23 BT.</p> <p>A pine, 14 ins. diam., bears S. <math>21\frac{3}{4}^{\circ}</math> W., 95 lks. dist., mkd. T10NR21E <math>\frac{1}{4}</math> S23 BT.</p> <p>The cor. is located 47 lks. North of Forest Service Road No. 43, bearing N. <math>89^{\circ}15'</math> E. and S. <math>89^{\circ}15'</math> W.</p>
42.30	Right-of-way fence, bears S. $25^{\circ}$ E. and N. $25^{\circ}$ W.
43.80	State Highway No. 160, bears S. $25^{\circ}$ E. and N. $25^{\circ}$ W.
45.32	Right-of-way fence, bears N. $25^{\circ}$ W. and bears S. $25^{\circ}$ E. for 4 lks. to a cor. of fences extending S. $25^{\circ}$ E., S. $89^{\circ}20'$ W. and N. $25^{\circ}$ E.
48.30	Power line, bears S. $25^{\circ}$ E. and N. $25^{\circ}$ W.
60.62	SW. cor. of Show Low Country Club Estates.
80.82	<p>The cor. of secs. 14, 15, 22 and 23, monumented by an unmkd. sandstone, 18 x 8 x 7 ins., set in a mound of stone alongside a cor. of fences extending N. <math>0^{\circ}32'</math> E., N. <math>89^{\circ}20'</math> E. and S. <math>0^{\circ}32'</math> W.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;">                     T10N R21E  <math>\frac{S15}{S22}   \frac{S14}{S23}</math>                      1969                 </div> <p>from which</p>

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
	<p>A pine, 7 ins. diam., bears N. 57° E., 16 lks. dist., mkd. T10NR21E S14 BT.</p> <p>A pine, 9 ins. diam., bears S. 36° E., 13 lks. dist., mkd. T10NR21E S23 BT.</p> <p>A pine, 8 ins. diam., bears S. 37° W., 17½ lks. dist., mkd. T10NR21E S22 BT.</p> <p>A pine, 10 ins. diam., bears N. 23½° W., 21 lks. dist., mkd. T10NR21E S15 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak.</p>
<p>10.205</p> <p>17.60</p> <p>21.10</p> <p>30.00</p> <p>40.82</p>	<p>N. 0°36' E., bet. secs. 14 and 15.</p> <p>Over rolling land, through moderate timber; along a N. and S. fence.</p> <p>Point for the S-S 1/64 sec. cor. of secs. 14 and 15, at proportionate dist.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T10N R21E S-S 1/64 S15   S14 1969</p> <p>from which</p> <p>A pine, 7 ins. diam., bears S. 30° W., 32 lks. dist., mkd. S-S 1/64 S15 BT.</p> <p>Raise a mound of stone W. of the cor.</p> <p>The cor. is located 1 lk. East of a N. and S. fence.</p> <p>Bagnal Wash, 30 lks. wide, 3 ft. deep, drains irregularly NE.</p> <p>Dim track road, bears NE. and SW.</p> <p>Fence, bears East and bears West for 3 lks. to a cor. of fences extending East and S. 0°32' W.</p> <p>The ¼ sec. cor. of secs. 14 and 15, monumented by a sandstone, 18 x 10 x 6 ins., firmly set in a mound of stone mkd. ¼ on W. face and a X on top, from which the remains of the old original bearing trees:</p>

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
	<p>The center of the stump hole of a fallen pine, bears S. <math>18\frac{1}{2}^{\circ}</math> E., 49 lks. dist.; fallen pine, 18 ins. diam., mkd. <math>\frac{1}{4}</math> S BT. (Record: SE., 49 lks. dist.).</p>
	<p>The center of the stump hole of a fallen pine, bears N. <math>17^{\circ}</math> W., 49 lks. dist.; fallen pine, 15 ins. diam., mkd. with an open blaze. (Record: N. <math>29^{\circ}</math> W., 49 lks. dist.).</p>
	<p>This cor. was not remonumented.</p>
	<p>N. <math>0^{\circ}05'</math> E., beginning new measurement.</p>
	<p>Over gently rolling land.</p>
20.08	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15, at proportionate dist.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T10N R21E N 1/16 S15 S14 1969</p>
	<p>from which</p>
	<p>A pine, 6 ins. diam., bears N. <math>89\frac{1}{2}^{\circ}</math> W., <math>47\frac{1}{2}</math> lks. dist., mkd. N 1/16 S15 BT.</p>
	<p>Raise a mound of stone W. of the cor.</p>
20.90	<p>Graded road, bears N. <math>70^{\circ}</math> E., curving NE. and S. <math>70^{\circ}</math> W., curving SW.</p>
30.12	<p>Point for the N-N 1/64 sec. cor. of secs. 14 and 15, at proportionate dist.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T10N R21E N-N 1/64 S15 S14 1969</p>
	<p>from which</p>
	<p>A pine, 7 ins. diam., bears N. <math>84^{\circ}</math> E., <math>62\frac{1}{2}</math> lks. dist., mkd. N-N 1/64 S14 BT.</p>
	<p>A pine, 9 ins. diam., bears S. <math>88^{\circ}</math> W., 135 lks. dist., mkd. N-N 1/64 S15 BT.</p>
	<p>Raise a mound of stone W. of the cor.</p>
40.10	<p>Fence, bears E. and W.; enter clearing, bears N. and W.</p>
40.16	<p>The cor. of secs. 10, 11, 14 and 15, monumented by a sandstone, 24 x 10 x 6 ins., loosely set in a mound of stone, mkd. 2 notches on E. and 4 notches on S. faces, and with a water pipe, <math>1\frac{1}{2}</math> ins. diam., alongside.</p>

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E  
 $\frac{S10}{S15} \frac{S11}{S14}$   
 1969

from which

A juniper, 8 ins. diam., bears N. 75° E., 45 lks. dist., mkd. T10NR21E S11 BT.

A juniper, 10 ins. diam., bears S. 32½° E., 53 lks. dist., mkd. T10NR21E S14 BT.

Bury the orig. cor. stone and water pipe alongside the iron post.

Raise a mound of stone W. of the cor.

Land, rolling to gently rolling.  
 Soil, rocky clay loam.  
 Timber, pine, juniper and oak.  
 Undergrowth, grass and scrub oak.

From the cor. of secs. 11, 12, 13 and 14.

West, bet. secs. 11 and 14.

Over gently rolling land, through moderate timber.

7.90 Dim track road, bears irregularly N. and S.

10.02 Point for the E-E 1/64 sec. cor. of secs. 11 and 14, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E  
 E-E 1/64  $\frac{S11}{S14}$   
 1969

from which

A juniper, 6 ins. diam., bears N. 3¾° E., 25 lks. dist., mkd. E-E 1/64 S11 BT.

A juniper, 8 ins. diam., bears S. 75° E., 42½ lks. dist., mkd. E-E 1/64 S14 BT.

Raise a mound of stone N. of the cor.

20.04 Point for the E 1/16 sec. cor. of secs. 11 and 14, at proportionate dist.

Set the iron post 22 ins. in the ground, brass cap mkd.

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
	<p style="text-align: center;">T10N R21E</p> <p style="text-align: center;">E 1/16 <math>\frac{S11}{S14}</math> 1969</p> <p>from which</p> <p style="text-align: center;">A pine, 15 ins. diam., bears S. 6° W., 51 lks. dist., mkd. E 1/16 S14 BT.</p> <p>Raise a mound of stone N. of the cor.</p>
20.50	Ravine, drains NW.
30.06	Point for the W-E 1/64 sec. cor. of secs. 11 and 14, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T10N R21E</p> <p style="text-align: center;">W-E 1/64 <math>\frac{S11}{S14}</math> 1969</p> <p>from which</p> <p style="text-align: center;">A pine, 11 ins. diam., bears S. 46° E., 51 lks. dist., mkd. W-E 1/64 S14 BT.</p> <p>Raise a mound of stone N. of the cor.</p>
30.50	Ravine, drains N. 20° W.
39.50	Bagnal Wash, 30 lks. wide, 1 ft. deep, drains N. from SW.
40.08	The 1/4 sec. cor. of secs. 11 and 14, monumented by a pine stump, 30 ins. diam., no mks., from which the remains of an old original bearing tree:
	<p>A pine stump, 11 ins. diam., bears S. 48° E., 15 lks. dist., mkd. BT. (Record: S. 37° E., 15 lks.).</p>
	This cor. was not remonumented.
	<p>_____</p> <p>S. 89°46' W., beginning new measurement.</p>
	Over rolling land.
2.20	Bagnal Wash, 20 lks. wide, 1 ft. deep on a bend, drains SE., from S. 30° W.
3.80	Track road, bears N. 30° E. and S. 30° W.
10.02	Point for the E-W 1/64 sec. cor. of secs. 11 and 14, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T10N R21E</p> <p style="text-align: center;">E-W 1/64 <math>\frac{S11}{S14}</math> 1969</p>

Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS

from which

A pine, 6 ins. diam., bears S. 49° W., 17 lks.  
dist., mkd. E-W 1/64 S14 BT.

A pine, 6 ins. diam., bears N. 61½° W., 37 lks.  
dist., mkd. E-W 1/64 S11 BT.

Raise a mound of stone N. of the cor.

10.30 Fence, bears N. and S.

12.40 Graded road, bears S. 15° E. and N. 15° W.

17.50 Power line, bears S. 53° E. and N. 53° W.

19.30 Telephone line, bears N. 1½° E. and S. 1½° W.

20.04 Point for the W 1/16 sec. cor. of secs. 11 and 14, at  
proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T10N R21E  
W 1/16  $\frac{S11}{S14}$   
1969

from which

A juniper, 6 ins. diam., bears N. 68½° E., 114 lks.  
dist., mkd. W 1/16 S11 BT.

A pine, 7½ ins. diam., bears S. 59° E., 116½ lks.  
dist., mkd. W 1/16 S14 BT.

Set a steel fence post, 5½ ft. long, alongside the iron  
post.

Raise a mound of stone N. of the cor.

23.80 Graded road, bears N. 55° E. and S 55° W.

30.06 Point for the W-W 1/64 sec. cor. of secs. 11 and 14, at  
proportionate dist.; not monumented.

34.30 Right-of-way fence, bears S. 8° E. and N. 8° W.

35.80 State Highway No. 160, bears S. 8° E. and N. 8° W.

37.30 Right-of-way fence, bears S. 8° E. and N. 8° W.

40.08 The cor. of secs. 10, 11, 14 and 15.

Land, gently rolling to rolling.  
Soil, rocky clay loam.  
Timber, pine, juniper and oak.  
Undergrowth, grass and scrub oak.

N. 0°30' W., bet. secs. 10 and 11.

Over gently rolling land, through a clearing to the W.

## Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
17.00	Power line, bears S. 53° E. and N. 53° W.
19.40	Right-of-way fence, bears S. 8° E. and N. 8° W., curving NW.; leave clearing, bears S. and W.
20.00	Track road, bears E. and W.
20.14	Point for the S 1/16 sec. cor. of secs. 10 and 11, at proportionate dist.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	T10N R21E S 1/16 S10 S11 1969
	from which
	A juniper, 38 ins. diam., bears N. 21° E., 60 lks. dist., mkd. S 1/16 S11 BT.
	A pine, 7½ ins. diam., bears S. 32½° E., 78½ lks. dist., mkd. S 1/16 S11 BT.
	Set a steel fence post, 5 ft. long, alongside the iron post.
32.60	State Highway No. 160, bears S. 8° E. and N. 8° W., curving NW.
36.40	Right-of-way fence, bears S. 8° E. and N. 8° W., curving NW.; enter moderate timber.
40.28	The ¼ sec. cor. of secs. 10 and 11, monumented by a sandstone, 18 x 11 x 6 ins., set 8 ins. in the ground, mkd. ¼ on W. face, mound of stone E., from which the remains of the original bearing trees:
	A pine, 25 ins. diam., bears N. 35° W., 104 lks. dist., mkd. ¼ S BT.
	At the corner point
	Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	T10N R21E ¼ S10 S11 1969
	from which
	A juniper, 10 ins. diam., bears S. 59½° E., 34½ lks. dist., mkd. T10NR21E ¼ S11 BT.
	A pine, 7 ins. diam., bears S. 86½° W., 84 lks. dist., mkd. T10NR21E ¼ S10 BT.
	Deposit the orig. cor. stone in the mound of stone around the iron post.



## Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS					
	<p>N. 0°13' E.; beginning new measurement.</p> <p>Over gently rolling land.</p> <p>5.90 Telephone line, bears S. 25° E. and N. 25° W.</p> <p>6.70 Track road, bears E. and W.</p> <p>10.20 Graded road, bears S. 60° E. and N. 60° W.</p> <p>22.60 Ravine, drains SE.</p> <p>37.90 Ravine, drains SE.</p> <p>39.75 The cor. of secs. 2, 3, 10 and 11, monumented by a sandstone, 24 x 13 x 8 ins., set 12 ins. in the ground, mkd. 2 notches on E. and 5 notches on S. faces, mound of stone W., from which the remains of the old original bearing trees:</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 50° E., 144 lks. dist., mks. visible but not legible.</p> <p style="padding-left: 40px;">The center of a stump hole of a fallen pine, bears N. 30° W., 136 lks. dist., fallen pine, 25 ins. diam., mkd. BT.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T10N R21E</p> <table border="1" style="margin: auto;"> <tr> <td>S 3</td> <td>S 2</td> </tr> <tr> <td>S10</td> <td>S11</td> </tr> </table> <p>1969</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 25° E., 128 lks. dist., mkd. T10NR21E S2 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 24½° W., 9½ lks. dist., mkd. T10NR21E S10 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 54° W., 22½ lks. dist., mkd. T10NR21E S3 BT.</p> <p>Deposit the orig. cor. stone in a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak.</p>	S 3	S 2	S10	S11
S 3	S 2				
S10	S11				
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°57' W., bet. secs. 2 and 11.</p> <p>Over rolling land, through moderate timber; desc. W. slope.</p>				


Dep. Res., Portion Subdivisional Lines, T. 10 N., R. 21 E.

CHAINS	
13.90	Show Low Creek, 30 lks. wide, 2 ft. deep, course NW.; asc. E. slope.
34.50	W. rim of canyon, bears SE. and NW., thence over gently rolling land.
40.06	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 2 and 11, monumented by a basalt stone, 22 x 14 x 8 ins., firmly set in a mound of stone, mkd. <math>\frac{1}{4}</math> on N. face and with a re-bar, 5/8 ins. diam.; alongside, from which the old original bearing trees:</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 1° E., 29 lks. dist., mkd. X <math>\frac{1}{4}</math> S. (Record: S. 2° E.).</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears N. 51° W., 55 lks. dist., mkd. <math>\frac{1}{4}</math> S BT. (Record: N. 48° W.).</p> <p>At the corner point</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T10N R21E</p> <p><math>\frac{1}{4}</math> <math>\frac{S 2}{S11}</math></p> <p>1969</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 55<math>\frac{1}{2}</math>° W., 55 lks. dist., mkd. T10NR21E <math>\frac{1}{4}</math> S11 BT.</p> <p>Deposit the orig. cor. stone and re-bar in the mound of stone alongside the iron post.</p>
	<hr style="width: 20%; margin: auto;"/> <p>S. 89°39' W., beginning new measurement.</p>
	Over gently rolling land.
39.87	<p>The cor. of secs. 2, 3, 10 and 11.</p> <p>Land, rolling to gently rolling. Soil, rocky clay loam. Timber, pine and juniper. Undergrowth, grass.</p>
	<hr/> <p>Subdivision of Section 11, T. 10 N., R. 21 E.</p> <hr/>
	From the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.
	N. 0°18' W., on the N. and S. center line of sec. 11.
	Over rolling land, through moderate timber.
0.30	Wash, 30 lks. wide, 1 ft. deep, drains E.
20.05	Point for the C-S 1/16 sec. cor. of sec. 11.

## Subdivision of Section 11, T. 10 N., R. 21 E.

## CHAINS

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.



from which

A water pipe,  $1\frac{1}{2}$  ins. diam., projecting 8 ins. above the ground, bears N.  $66^{\circ}22'$  W., 1.7 lks. dist., origin unknown.


Set a steel fence post, 5 ft. long, alongside the iron post.

27.00 Track road, bears NE. and SW.

37.70 Fence, bears NE. and SW.

40.10 Point for the center  $\frac{1}{4}$  sec. cor. of sec. 11, at intersection with the E. and W. center line of sec. 11.

Set the iron post 22 ins. in the ground in a collar of stone, brass cap mkd.



from which

A pine, 10 ins. diam., bears S.  $31\frac{1}{2}^{\circ}$  W.,  $56\frac{1}{2}$  lks. dist., mkd. C  $\frac{1}{2}$  S11 BT.

A juniper,  $7\frac{1}{2}$  ins. diam., bears N.  $68^{\circ}$  W., 109 lks. dist., mkd. C  $\frac{1}{2}$  S11 BT.

A water pipe,  $1\frac{1}{2}$  ins. diam., projecting 6 ins. above the ground, bears S.  $85^{\circ}$  W., 3.4 lks. dist., origin unknown.

44.40 Wash, 20 lks. wide, 2 ft. deep, drains N.  $80^{\circ}$  W.

80.13 The  $\frac{1}{4}$  sec. cor. of secs. 2 and 11.

Land, rolling.

Soil, rocky clay loam.

Timber, pine, juniper and oak.

Undergrowth, grass and scrub oak.

From the  $\frac{1}{4}$  sec. cor. of secs. 11 and 12.

N.  $89^{\circ}57'$  W., on the E. and W. center line of sec. 11.

Over rolling land, through moderate timber.

Subdivision of Section 11, T. 10 N., R. 21 E.

CHAINS	
7.30	Bagnal Wash, 20 lks. wide, 2 ft. deep, drains N. 10° W.; asc. E. slope.
18.90	W. rim of canyon, bears SE. and NW., thence over gently rolling land.
20.025	<p>Point for the C-E 1/16 sec. cor. of sec. 11.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">E 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S11</p> <p style="text-align: center;">1969</p>
	The cor. is located alongside a water pipe, 1½ ins. diam., projecting 9 ins. above the ground, origin unknown.
	Raise a mound of stone N. of the cor.
37.50	Fence, bears NE. and SW.
40.05	The center ¼ sec. cor. of sec. 11.
60.165	<p>Point for the C-W 1/16 sec. cor. of sec. 11.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">W 1/16</p> <p style="text-align: center;">C ————— C</p> <p style="text-align: center;">S11</p> <p style="text-align: center;">1969</p>
	from which
	A pine, 6 ins. diam., bears S. 42½° W., 35 lks. dist., mkd. C-W 1/16 S11 BT.
	A juniper, 7 ins. diam., bears N. 41° W., 66½ lks. dist., mkd. C-W 1/16 S11 BT.
	Raise a mound of stone N. of the cor.
62.60	Wash, 20 lks. wide, 2 ft. deep, drains N.
74.60	Graded road, bears S. 25° E. and N. 25° W.
77.30	Telephone line, bears S. 25° E. and N. 25° W.
80.28	The ¼ sec. cor. of secs. 10 and 11.
	<p>Land, rolling to gently rolling.</p> <p>Soil, rocky clay loam.</p> <p>Timber, pine and juniper.</p> <p>Undergrowth, grass and scrub oak.</p>
Subdivision of the SE¼ of Section 11	
<hr style="width: 20%; margin: auto;"/> <p>From the E 1/16 sec. cor. of secs. 11 and 14.</p>	

## Subdivision of Section 11, T. 10 N., R. 21 E.

CHAINS	
	N. 0°17' W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 11.
	Over rolling land, through moderate timber.
8.90	Spur, slopes SW.; desc. NW. slope.
10.02	Point for the C-S-SE 1/64 sec. cor. of sec. 11.
	Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	<p style="text-align: center;">C-S-SE 1/64 S11 1969</p>
	from which
	<p style="text-align: center;">A pine, 16 ins. diam., bears S. 61° E., 27 lks. dist., mkd. C-S-SE 1/64 S11 BT.</p>
12.40	Fence, bears N. 50° E. and S. 50° W.
16.10	Bagnol Wash, 20 lks. wide, 1 ft. deep, drains NE.
20.04	Point for the SE 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ of sec. 11.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">SE 1/16 S11 1969</p>
	Raise a mound of stone W. of the cor.
20.60	Fence, bears E. and W.
34.90	Track road, bears N. 80° E. and S. 80° W.
40.09	The C-E 1/16 sec. cor. of sec. 11.
10.01	<p>From the S 1/16 sec. cor. of secs. 11 and 12.</p> <p>N. 89°59' W., on the E. and W. center line of the SE<math>\frac{1}{4}</math> of sec. 11.</p> <p>Over rolling land, through moderate undergrowth.</p> <p>Point for the C-E-SE 1/64 sec. cor. of sec. 11.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-E-SE 1/64 S11 1969</p> <p>from which</p> <p style="text-align: center;">A pine, 15 ins. diam., bears N. 56° E., 65 lks. dist., mkd. C-E-SE 1/64 S11 BT.</p>

Subdivision of Section 11, T. 10 N., R. 21 E.

CHAINS	
	<p>A pine, 7½ ins. diam., bears S. 39° E., 22½ lks. dist., mkd. C-E-SE 1/64 S11 BT.</p> <p>Raise a mound of stone N. of the cor.</p> <p>10.50 Fence, bears N. 50° E. and S. 50° W.</p> <p>15.80 Bagnol Wash, 30 lks. wide, 1 ft. deep, drains NE.; asc. E. slope.</p> <p>20.02 The SE 1/16 sec. cor. of sec. 11.</p> <p>23.10 W. rim of canyon, bears NE. and SW., thence over gently rolling land.</p> <p>40.05 The C-S 1/16 sec. cor. of sec. 11.</p>
	<p>From the E-E 1/64 sec. cor. of secs. 11 and 14.</p> <p>N. 0°21' W., on the N. and S. center line of the SE¼SE¼ of sec. 11.</p> <p>Over rolling land, through moderate timber; desc. NW. slope.</p> <p>10.02 Point for the SE-SE 1/64 sec. cor. of sec. 11, at intersection with the E. and W. center line of the SE¼SE¼ of sec. 11.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SE-SE 1/64 S11 1969</p> <p>from which</p> <p>A pine, 13 ins. diam., bears N. 39½° E., 66 lks. dist., mkd. SE-SE 1/64 S11 BT.</p> <p>A pine, 8 ins. diam., bears S. 61½° W., 26 lks. dist., mkd. SE-SE 1/64 S11 BT.</p> <p>Raise a mound of stone W. of the cor.</p> <p>20.04 The C-E-SE 1/64 sec. cor. of sec. 11.</p>
	<p>From the point for the S-S 1/64 sec. cor. of secs. 11 and 12.</p> <p>N. 89°59' W., on the E. and W. center line of the SE¼SE¼ of sec. 11.</p> <p>Over rolling land, through moderate timber.</p> <p>2.40 Track road, bears N. 10° E. and S. 10° W.</p> <p>9.00 Crest of ridge, bears N. 10° E. and S. 10° W.; desc. W. slope.</p>

Subdivision of Section 11, T. 10 N., R. 21 E.

CHAINS	
10.015	The SE-SE 1/64 sec. cor. of sec. 11.
20.03	The C-S-SE 1/64 sec. cor. of sec. 11.
<hr/> Subdivision of the SW $\frac{1}{4}$ of Section 11 <hr/>	
	From the W 1/16 sec. cor. of secs. 11 and 14.
	N. 0°23' W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 11.
	Over gently rolling land, through moderate timber.
1.70	Power line, bears S. 53° E. and N. 53° W.
3.90	Graded road, bears NE. and SW.
4.60	Telephone line, bears S. 25° E. and N. 25° W.
16.90	Graded road, bears S. 25° E. and N. 25° W.
20.08	Point for the SW 1/16 sec. cor. of sec. 11, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ of sec. 11.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	SW 1/16 S11 1969
	from which
	A pine, 8 ins. diam., bears S. 20° E., 20 $\frac{1}{2}$ lks. dist., mkd. SW 1/16 S11 BT.
	A pine, 16 ins. diam., bears N. 23° W., 67 lks. dist., mkd. SW 1/16 S11 BT.
	Raise a mound of stone W. of the cor.
27.30	Ravine, 4 ft. deep, drains N. 25° W.
40.17	The C-W 1/16 sec. cor. of sec. 11.
<hr/> From the C-S 1/16 sec. cor. of sec. 11. <hr/>	
	S. 89°55' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 11.
	Over gently rolling land, through moderate timber.
3.80	Track road, bears N. 30° E. and S. 30° W.
10.04	Point for the C-E-SW 1/64 sec. cor. of sec. 11.

Subdivision of Section 11, T. 10 N., R. 21 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">C-E-SW 1/64 S11 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 24½° W., 33½ lks. dist., mkd. C-E-SW 1/64 S11 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 57° W., 86 lks. dist., mkd. C-E-SW 1/64 S11 BT.</p>
11.20	Fence, bears N. and S.
18.30	Ravine, 4 ft. deep, drains N. 25° W.
20.08	The SW 1/16 sec. cor. of sec. 11.
22.70	Graded road, bears S. 25° E. and N. 25° W.
26.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 25° W.
27.50	Telephone line, bears S. 25° E. and N. 25° W.
37.40	Right-of-way fence, bears S. 8° E. and N. 8° W.
38.90	State Highway No. 160, bears S. 8° E. and N. 8° W.
40.16	The S 1/16 sec. cor. of secs. 10 and 11.
Subdivision of Section 12, T. 10 N., R. 21 E.	
	<p>From the ¼ sec. cor. of secs. 12 and 13.</p> <p>N. 0°14' W., on the N. and S. center line of sec. 12.</p> <p>Over Fools Hollow Lake by triangulation.</p>
3.20	Mean high water line on the N. shore of Fools Hollow Lake, bears N. 70° E. and S. 70° W.; end of triangulation, thence over gently rolling land, through moderate timber.
4.40	Track road, bears N. 10° E. and S. 10° W.
9.80	Same road, bears SE. and NW.
9.94	Point for the C-S-S 1/64 sec. cor. of sec. 12.
	<p>Set the iron post 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S-S 1/64 S12 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 56° E., 34½ lks. dist., mkd. C-S-S 1/64 S12 BT.</p>



## Subdivision of Section 12, T. 10 N., R. 21 E.

## CHAINS

A pine, 10 ins. diam., bears S.  $64^{\circ}$  W., 42 lks. dist., mkd. C-S-S  $1/64$  S12 BT.

A pipe,  $\frac{1}{2}$  in. diam., projecting 3 ins. above the ground, bears N.  $21^{\circ}53'$  W., 12.6 lks. dist. Origin unknown.

Set a steel fence post, 5 ft. long, alongside the iron post.

19.88 Point for the C-S  $1/16$  sec. cor. of sec. 12.

Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.

C  
S  $1/16$  | S12  
C  
1969

from which

A pine, 8 ins. diam., bears N.  $27\frac{1}{2}^{\circ}$  E., 49 lks. dist., mkd. C-S  $1/16$  S12 BT.

A pine, 8 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  E., 40 lks. dist., mkd. C-S  $1/16$  S12 BT.

The cor. is located 75 lks. West of a graded road bearing S.  $5^{\circ}$  E. and N., curving to the E.

24.85 Point for the C-S-N-S  $1/256$  sec. cor. of sec. 12.

Set the iron post 24 ins. in the ground, brass cap mkd.

C-S-N-S  $1/256$   
S12  
1969

from which

A pine, 10 ins. diam., bears S.  $23\frac{1}{2}^{\circ}$  E., 131 lks. dist., mkd. C-S-N-S  $1/256$  S12 BT.

A juniper, 12 ins. diam., bears N.  $57\frac{1}{2}^{\circ}$  W., 45 lks. dist., mkd. C-S-N-S  $1/256$  S12 BT.

A re-bar,  $\frac{1}{2}$  in. diam., projecting 1 in. above the ground, bears N.  $27^{\circ}$  W., 22.3 lks. dist. Origin unknown.



Raise a mound of stone W. of the cor.

25.70 Graded road, bears W. and E., curving SE.

27.80 S. rim overlooking Fools Hollow Lake, bears S.  $70^{\circ}$  E. and N.  $70^{\circ}$  W.; desc. steep N. slope.

29.82 Point for the C-N-S  $1/64$  sec. cor. of sec. 12; not monumented.

Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
30.70	Mean high water line on the S. shore of Fools Hollow Lake, bears S. 70° E. and N. 70° W.; thence by triangulation.
38.90	Mean high water line on the N. shore of Fools Hollow Lake, bears SE. and W.; asc. steep S. slope.
39.50	N. rim overlooking Fools Hollow Lake, bears SE. and W.; end of triangulation, thence over gently rolling land.
39.76	Point for the center ¼ sec. cor. of sec. 12, at intersection with the E. and W. center line of sec. 12.  Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.
	
	from which  A pine, 12 ins. diam., bears N. 42½° W., 76 lks. dist., mkd. C ¼ S12 BT.
57.90	Jeep road, bears N. 70° E. and S. 70° W.
80.14	The ¼ sec. cor. of secs. 1 and 12.  Land, gently rolling and steep around lake. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak south of the lake.
	From the ¼ sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.  N. 89°46' W., on the E. and W. center line of sec. 12.  Over gently rolling land, through moderate timber.
0.60	Jeep road, bears N. and S.
20.07	Point for the C-E 1/16 sec. cor. of sec. 12; not monumented.
40.14	The center ¼ sec. cor. of sec. 12.  Thence along the N. rim overlooking Fools Hollow Lake.
50.18	Point for the C-E-W 1/64 sec. cor. of sec. 12; not monumented.
60.22	Point for the C-W 1/16 sec. cor. of sec. 12.  Set the iron post 6 ins. in the ground, over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.
	

## Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
	<p>from which</p> <p>A pine, 15 ins. diam., bears N. 24½° W., 62 lks. dist., mkd. C-W 1/16 S12 BT.</p>
60.30	N. rim, overlooking Fools Hollow Lake, 40 ft. high, bears E. and NW.; desc. W. slope.
61.00	N. end of Fools Hollow Dam, bears S. 44° W., 7.50 chs. dist.; desc. into Show Low Creek.
70.26	Point for the C-W-W 1/64 sec. cor. of sec. 12; not monumented.
73.90	Show Low Creek, 30 lks. wide, 1 ft. deep, drains N. 80° W.; continue desc.
77.20	Fence, bears irregularly N. and S.
80.30	The ¼ sec. cor. of secs. 11 and 12.
	<p>Land, gently rolling to broken. Soil, rocky clay loam. Timber, pine and juniper. Undergrowth, grass and scrub oak last 10.00 chs.</p>
	<p style="text-align: center;">Subdivision of the SE¼ of Section 12</p> <hr style="width: 20%; margin: auto;"/> <p>From the E 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0°05' W., on the N. and S. center line of the SE¼ of sec. 12.</p> <p>Over gently rolling land, through open meadow, along the E. side of a N. and S. fence.</p>
9.97	Point for the C-S-SE 1/64 sec. cor. of sec. 12; not monumented.
10.10	Fence, bears East and bears West for 10 lks. to a cor. of fences extending East and South.
14.955	Point for the C-N-S-SE 1/256 sec. cor. of sec. 12.
	<p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-N-S-SE 1/256 S12 1969</p>
	<p>from which</p> <p>A fence cor., bears N. 25° W., 16 lks. dist., with fences extending E. and S.</p> <p>An open pipe, ¾ in. diam., projecting 20 ins. above the ground, bears N. 20½° W., 13.5 lks. dist. Origin unknown.</p>

Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
15.10	Fence, bears E. and W.
15.80	Graded road, bears S. 85° E. and N. 85° W.
16.10	Enter moderate timber, bears E. and W.
19.94	Point for the SE 1/16 sec. cor. of sec. 12, at intersection with the E. and W. center line of the SE 1/4 of sec. 12; not monumented.
20.40	Fence, bears irregularly E. and W. along the S. rim overlooking Fools Hollow Lake; desc. steep N. slope.
21.10	Mean high water line on S. shore of Fools Hollow Lake, bears irregularly E. and W.; thence by triangulation.
28.00	Mean high water line on the N. shore of Fools Hollow Lake, bears SE. and SW.; asc. steep S. slope.
28.60	N. rim overlooking Fools Hollow Lake, bears SE. and SW.; end of triangulation, thence over gently rolling land.
39.87	The point for the C-E 1/16 sec. cor. of sec. 12.
From the point for the S 1/16 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.	
N. 89°37' W., on the E. and W. center line of the SE 1/4 of sec. 12.	
Over Fools Hollow Lake by triangulation.	
10.01	Point for the C-E-SE 1/64 sec. cor. of sec. 12, falls in Fools Hollow Lake; not monumented.
10.70	Mean high water line on the S. shore of Fools Hollow Lake, bears S. 75° E. and N. 75° W.; end of triangulation; asc. steep N. slope.
20.02	The point for the SE 1/16 sec. cor. of sec. 12.
24.00	S. rim overlooking Fools Hollow Lake, bears S. 75° E. and N. 75° W.; thence over gently rolling land, through moderate timber.
35.30	Graded road, bears S. 55° E. and N. 55° W.
39.30	Graded road, bears S. 5° E. and N. curving E.
40.04	The C-S 1/16 sec. cor. of sec. 12.
From the point for the E-E 1/64 sec. cor. of secs. 12 and 13.	
N. 0°01' W., on the N. and S. center line of the SE 1/4 SE 1/4 of sec. 12.	
Over nearly level land, through open field.	

## Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
9.98	<p>Point for the SE-SE 1/64 sec. cor. of sec. 12, at intersection with the E. and W. center line of the SE<math>\frac{1}{4}</math>SE<math>\frac{1}{4}</math> of sec. 12.</p> <p>Set the iron post over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">SE-SE 1/64 S12 1969</p> <p>from which</p> <p style="text-align: center;">A re-bar, <math>\frac{1}{2}</math> in. diam., bears S. 60° E., 1.5 lks. dist. Origin unknown.</p>
10.04	Fence, bears E. and W.
14.975	<p>Point for the C-N-SE-SE 1/256 sec. cor. of sec. 12.</p> <p>Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-N-SE-SE 1/256 S12 1969</p> <p>from which</p> <p style="text-align: center;">A re-bar, <math>\frac{1}{2}</math> in. diam., bears N. 60° E., 1.5 lks. dist. Origin unknown.</p>
15.60	Graded road, bears S. 85° E. and N. 85° W.
18.40	S. rim overlooking Fools Hollow Lake, bears S. 75° E. and N. 75° W.; desc. steep N. slope, through moderate timber.
19.30	Mean high water line on S. shore of Fools Hollow Lake, bears S. 75° E. and N. 75° W.
19.97	The point for the C-E-SE 1/64 sec. cor. of sec. 12.
	<p>From the S-S 1/64 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp.</p> <p>N. 89°31' W., on the E. and W. center line of the SE<math>\frac{1}{4}</math>SE<math>\frac{1}{4}</math> of sec. 12.</p> <p>Over nearly level land, through open field, along track road bearing E. and W.</p>
5.70	Fence, bears N. and S., end of road.
9.99	The SE-SE 1/64 sec. cor. of sec. 12.
19.98	The point for the C-S-SE 1/64 sec. cor. of sec. 12.

Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
	<p>Subdivision of the SW<math>\frac{1}{4}</math> of Section 12</p> <hr/> <p>From the true point for the W 1/16 sec. cor. of secs. 12 and 13.</p> <p>N. 0°17' W., on the N. and S. center line of the SW<math>\frac{1}{4}</math> of sec. 12.</p> <p>Over Fools Hollow Lake by triangulation.</p>
4.99	Point for the C-S-S-SW 1/256 sec. cor. of sec. 12 identical with angle point No. 5, lot 13, falls in Fools Hollow Lake; not monumented.
9.98	Point for the C-S-SW 1/64 sec. cor. of sec. 12, falls in Fools Hollow Lake; not monumented.
19.96	Point for the SW 1/16 sec. cor. of sec. 12, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ of sec. 12 identical with angle point No. 6, lot 13, falls in Fools Hollow Lake; not monumented.
29.94	Point for the C-N-SW 1/64 sec. cor. of sec. 12, falls in Fools Hollow Lake; not monumented.
38.80	Mean high water line on the N. shore of Fools Hollow Lake, bears E. and NW.; asc. steep S. slope.
39.40	N. rim overlooking Fools Hollow Lake, bears E. and NW., 70 lks. dist. to the N. edge of Fools Hollow Lake Dam; end of triangulation.
39.92	The C-W 1/16 sec. cor. of sec. 12.
	<p>From the C-S 1/16 sec. cor. of sec. 12.</p> <p>West, on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 12.</p> <p>Over gently rolling land, through moderate timber.</p>
5.015	<p>Point for the C-E-E-SW 1/256 sec. cor. of sec. 12.</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">C-E-E-SW 1/256 S12 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7<math>\frac{1}{2}</math> ins. diam., bears S. 47° W., 55<math>\frac{1}{2}</math> lks. dist., mkd. C-E-E-SW 1/256 S12 BT.</p> <p style="padding-left: 40px;">A re-bar, <math>\frac{1}{2}</math> ins. diam., bears N. 26<math>\frac{1}{2}</math>° W., 14.7 lks. dist. Origin unknown.</p>
10.03	Point for the C-E-SW 1/64 sec. cor. of sec. 12.

## Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
	<p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">C-E-SW 1/64 S12 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. <math>1\frac{1}{2}^{\circ}</math> E., 59 lks. dist., mkd. C-E-SW 1/64 S12 BT.</p> <p style="padding-left: 40px;">A pine, <math>7\frac{1}{2}</math> ins. diam., bears N. <math>44^{\circ}</math> W., 32 lks. dist., mkd. C-E-SW 1/64 S12 BT.</p> <p style="padding-left: 40px;">A re-bar, <math>\frac{1}{2}</math> in. diam., bears N. <math>28\frac{1}{2}^{\circ}</math> W., 10.5 lks. dist. Origin unknown.</p>
11.20	Track road, bears N. and S.
16.50	Mean high water line on the E. shore of Fools Hollow Lake, bears S. $25^{\circ}$ E. and N. $25^{\circ}$ W.; thence over lake by triangulation.
20.06	The point for the SW 1/16 sec. cor. and angle point No. 6, Lot 13, sec. 12.
28.30	Mean high water line on the W. shore of Fools Hollow Lake, bears N. $15^{\circ}$ E. and S. $15^{\circ}$ W.; end of triangulation, thence over rolling land, through moderate timber.
28.70	Track road, bears N. $15^{\circ}$ E. and S. $15^{\circ}$ W.
30.10	Point for the C-W-SW 1/64 sec. cor. of sec. 12.
	<p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">C-W-SW 1/64 S12 1969</p>
31.00	N. rim of spillway, bears S. $66^{\circ}$ E. and N. $66^{\circ}$ W.
31.615	Point for angle point No. 1, Lot 13, hereinafter described.
33.10	Center of spillway, drains N. $66^{\circ}$ W.
35.20	S. rim of spillway, bears S. $66^{\circ}$ E. and N. $66^{\circ}$ W.
40.14	The S 1/16 sec. cor. of secs. 11 and 12.
	<p>From the C-E-SW 1/64 sec. cor. of sec. 12.</p> <p>N. <math>0^{\circ}17'</math> W., on the N. and S. center line of the NE<math>\frac{1}{4}</math>SW<math>\frac{1}{4}</math> of sec. 12.</p> <p>Over gently rolling land, through moderate timber.</p>
4.98	Point for the C-S-NE-SW 1/256 sec. cor. of sec. 12.

Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S-NE-SW 1/256 S12 1969</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 15 ins. diam., bears N. 62½° E., 44 lks. dist., mkd. C-S-NE SW 1/256 S12 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 84° W., 21 lks. dist., mkd. C-S-NE-SW 1/256 S12 BT.</p> <p style="padding-left: 40px;">A re-bar, ½ in. diam., projecting 1 in. above the ground, bears N. 30¾° W., 13 lks. dist. Origin unknown.</p> <p>Raise a mound of stone W. of the cor.</p>	
5.90	Graded road, bears E. and W.	
9.96	Point for the NE-SW 1/64 sec. cor. of sec. 12, at intersection with the E. and W. center line of the NE¼SW¼ of sec. 12; not monumented.	
10.10	S. rim overlooking Fools Hollow Lake, bears S. 70° E. and N. 70° W.; desc. N. slope.	
12.10	Mean high water line on the S. shore of Fools Hollow Lake, bears S. 70° E. and N. 70° W.; over lake by triangulation.	
18.10	Mean high water line on the N. shore of Fools Hollow Lake, bears E. and W.; end of triangulation, asc. steep N. slope.	
19.10	N. rim overlooking Fools Hollow Lake, bears E. and W.	
19.92	The point for the C-E-W 1/64 sec. cor. of sec. 12.	
	<p>From the point for the C-N-S 1/64 sec. cor. of sec. 12.</p> <p>N. 89°53' W., on the E. and W. center line of the NE¼SW¼ of sec. 12.</p> <p>Over rolling land, through moderate timber; asc. N. slope.</p>	
7.00	S. rim overlooking Fools Hollow Lake, bears S. 70° E. and N. 70° W., thence over gently rolling land.	
10.04	The point for the NE-SW 1/64 sec. cor. of sec. 12.	
18.50	Mean high water line on the E. shore of Fools Hollow Lake, bears S. 5° E. and N. 5° W.; thence over lake by triangulation.	
20.08	The point for the C-N-SW 1/64 sec. cor. of sec. 12.	
	<p>From the point for the E-W 1/64 sec. cor. of secs. 12 and 13.</p>	



## Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
	N. 0°14' W., on the N. and S. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 12.
	Over Fools Hollow Lake by triangulation.
6.50	Mean high water line on the E. side of Fools Hollow Lake, bears S. 25° E. and N. 25° W.; end of triangulation, thence over rolling land, through moderate timber.
9.96	Point for the SE-SW 1/64 sec. cor. of sec. 12, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 12; not monumented.
14.80	Track road, bears E. and W.
19.92	The C-E-SW 1/64 sec. cor. of sec. 12.
	From the C-S-S 1/64 sec. cor. of sec. 12.
	S. 89°51' W., on the E. and W. center line of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 12.
	Over rolling land, through moderate timber.
0.20	Track road, bears SE. and NW.
5.01	Point for the C-E-SE-SW 1/256 sec. cor. of sec. 12.
	Set the iron post over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">C-E-SE-SW 1/256 S12 1969</p>
	from which
	A pine, 10 ins. diam., bears S. 25° E., 53 $\frac{1}{2}$ lks. dist., mkd. C-E-SE-SW 1/256 S12 BT.
	A pine, 10 ins. diam., bears S. 64 $\frac{1}{2}$ ° W., 66 lks. dist., mkd. C-E-SE-SW 1/256 S12 BT.
	A re-bar, $\frac{1}{2}$ in. diam., projecting 2 ins. above the ground, bears N. 17 $\frac{1}{4}$ ° W., 8.9 lks. dist. Origin unknown.
10.02	The point for the SE-SW 1/64 sec. cor. of sec. 12.
12.80	Mean high water line on the E. shore of Fools Hollow Lake, bears S. 25° E. and N. 25° W.; thence over lake by triangulation.
20.05	The point for the C-S-SW 1/64 sec. cor. of sec. 12.
	From the point for the W-W 1/64 sec. cor. of secs. 12 and 13.
	N. 0°18' W., on the N. and S. center line of the SW $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 12.

Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
	Over cove by triangulation.
1.50	N. bank of cove, bears N. 70° E. and S. 70° W.; end of triangulation, thence over gently rolling land, through moderate timber.
4.10	Graded road, bears N. 60° E. and S. 60° W.
4.90	Fence, bears W. and bears E. for 97 lks. to a cor. of fences extending N. and W.
5.00	Point for the C-S-SW-SW 1/256 sec. cor. of sec. 12; not monumented.
10.00	Point for the SW-SW 1/64 sec. cor. of sec. 12, at intersection with the E. and W. center line of the SW¼SW¼ of sec. 12; not monumented.
11.00	Fence, bears SE. and NW.
11.019	Intersect line 2-3 of Lot 13 at a point from which angle point No. 3, bears S. 46°36' E., 148 lks. dist., hereinafter described.
16.80	S. side of spillway, bears S. 66° E. and N. 66° W.
19.40	N. side of spillway, bears S. 66° E. and N. 66° W.
20.00	The C-W-SW 1/64 sec. cor. of sec. 12.
	From the point for the C-S-SW 1/64 sec. cor. of sec. 12. S. 89°54' W., on the E. and W. center line of the SW¼SW¼ of sec. 12.
	Over Fools Hollow Lake, by triangulation.
6.00	Mean high water line on the W. shore of Fools Hollow Lake, bears S. 25° E. and N. 25° W.; end of triangulation, thence over rolling land, through moderate timber.
8.80	Graded road, bears S. 10° E. and N. 35° W.
8.965	Point for angle point No. 3, Lot 13, hereinafter described,
9.09	Fence, bears N. 45° W., and bears S. 45° E. for 5 lks. dist., to a cor. of fences extending S. and N. 45° W.
10.035	The point for the SW-SW 1/64 sec. cor. of sec. 12.
20.03	Fence, bears N. and S.
20.07	The point for the S-S 1/64 sec. cor. of secs. 11 and 12.
	From the C-W-SW 1/64 sec. cor. of sec. 12.
	N. 0°18' W., on the N. and S. center line of the NW¼SW¼ of sec. 12.

## Subdivision of Section 12, T. 10 N., R. 21 E.

CHAINS	
	Over rolling land, through moderate timber.
1.90	Fence, bears W. and bears E. for 10 lks. to a cor. of fences extending N. and W.
4.97	Fence, bears E. and W.
5.00	Point for the C-S-NW-SW 1/256 sec. cor. of sec. 12. Set the iron post 24 ins. in the ground, brass cap mkd.  C-S-NW-SW 1/256 S12 1969  from which  A pine, 13 ins. diam., bears N. 82½° E., 107 lks. dist., mkd. C-S-NW-SW 1/256 S12 BT.  A fence cor., bears S. 72° E., 9 lks. dist.; fences bear S. and W.  A steel pin, ½ in. diam., bears S. 36½° E., 14.5 lks. dist. Origin unknown.  Raise a mound of stone W. of the cor.
10.00	Point for the NW-SW 1/64 sec. cor. of sec. 12, at intersection with the E. and W. center line of the NW¼SW¼ of sec. 12; not monumented.
15.00	Descend into Show Low Creek.
19.40	Show Low Creek; 30 lks. wide, 1 ft. deep, drains N. 80° W.; asc. S. slope.
20.00	The point for the C-W-W 1/64 sec. cor. of sec. 12.
	From the point for the C-N-SW 1/64 sec. cor. of sec. 12. N. 89°53' W., on the E. and W. center line of the NW¼SW¼ of sec. 12.  Over Fools Hollow Lake, by triangulation.
5.20	Mean high water line on the W. shore of Fools Hollow Lake, bears S. 5° E. and N. 5° W.; end of triangulation, thence over rolling land, through moderate timber.
7.50	Track road, bears S. 10° E. and N. 10° W.
10.04	The point for the NW-SW 1/64 sec. cor. of sec. 12.
15.20	Fence, bears S. 30° E. and N. 30° W.
20.08	The point for the N-S 1/64 sec. cor. of secs. 11 and 12.

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
	Subdivision of Section 13, T. 10 N., R. 21 E.
	From the $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	N. $0^{\circ}13'$ W., on the N. and S. center line of sec. 13.
	Over rolling land, through moderate timber.
0.10	N. edge of Forest Service Road No. 43, bears N. $85^{\circ}$ E. and S. $85^{\circ}$ W., curving NW.
2.60	Fence, bears E. and W.
6.70	Power line, bears S. $53^{\circ}$ E. and N. $53^{\circ}$ W.
9.995	Point for the C-S-S $\frac{1}{64}$ sec. cor. of sec. 13.
	Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	S13 C-S-S $\frac{1}{64}$ 1969
	from which
	A pine, 8 ins. diam., bears S. $41^{\circ}$ E., 31 lks. dist., mkd. C-S-S $\frac{1}{64}$ S13 BT.
19.80	Fence, bears E. and W.
19.99	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 13; not monumented.
29.985	The C-N-S $\frac{1}{64}$ sec. cor. of sec. 13. This point is located at a Cor. of Fools Hollow Lake Resort-Unit 1, and is monumented by a re-bar, $\frac{1}{2}$ in. diam., projecting 3 ins. above the ground, with a metal cap, $1\frac{1}{2}$ ins. diam., unmkd.; not remonumented.
	Thence along the west boundary of Fools Hollow Lake Resort-Unit 1.
33.20	Ashurst Drive, bears E. to Hawley Street.
39.98	The center $\frac{1}{4}$ sec. cor. of sec. 13, monumented by a steel pin, $\frac{5}{8}$ in. diam., projecting 3 ins. above the ground. This cor. was established by George Sohn, a registered Engineer, in 1957 and is accepted as the center $\frac{1}{4}$ sec. cor. of sec. 13; not remonumented.
	<hr style="width: 20%; margin: 0 auto;"/> N. $0^{\circ}12'$ W., beginning new measurement.
	Enter Fools Hollow Lake Resort-Unit 1 Subdivision.
5.042	Point for the C-S-S-N $\frac{1}{256}$ sec. cor. of sec. 13; not monumented.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
10.085	Point for the C-S-N 1/64 sec. cor. of sec. 13; not monumented.
11.30	Wash, 20 lks. wide, 5 ft. banks, drains N. 70° W.
15.127	Point for the C-N-S-N 1/256 sec. cor. of sec. 13.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	S13 C-N-S-N 1/256 1969
	from which
	A re-bar, ½ in. diam., projecting 3 ins. above the ground, bears N. 25°26' E., 34.4 lks. dist.
	Leave Fools Hollow Lake Resort-Unit 1 Subdivision.
20.17	Point for the C-N 1/16 sec. cor. of sec. 13.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	C N 1/16   S13 C 1969
	from which
	A re-bar, ½ in. diam., projecting 2 ins. above the ground, bears N. 24°33' E., 29.3 lks. dist. Origin unknown.
	Set a steel fence post, 5 ft. long, alongside the iron post.
	Leave moderate timber, bears E. and W.; enter open meadow.
35.30	Mean high water line on the S. shore of Fools Hollow Lake, bears E. and W., thence over lake by triangulation.
40.34	The ¼ sec. cor. of secs. 12 and 13.
	Land, rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak.
	From the ¼ sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	N. 89°59' W., on the E. and W. center line of sec. 13.
	Over rolling land, through scattered timber.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
7.80	Power line, bears N. 80° E. and S. 80° W.
11.30	Irrigation ditch, 10 lks. wide, 2 ft. deep, drains N.
20.08	Point for the C-E 1/16 sec. cor. of sec. 13; not monumented.
30.14	Intersect a re-bar, ½ in. diam., projecting 2 ins. above the ground, located underneath a fence bearing N. and S.
30.50	Graded road, bears N. and S.
30.90	Fence, bears N. and S.; enter Fools Hollow Lake Resort-Unit 1.
40.16	The center ¼ sec. cor. of sec. 13.
	N. 89°54' W., beginning new measurement.
	Thence along a boundary of Fools Hollow Resort-Unit 1; enter moderate timber.
5.035	Point for the C-E-E-W 1/256 sec. cor. of sec. 13.
	Set the iron post 22 ins. in the ground in a collar of stone, brass cap mkd.
	S13 C-E-E-W 1/256 1969
	from which
	A pine, 11 ins. diam., bears N. 54½° W., 69 lks. dist., mkd. C-E-E-W 1/256 S13 BT.
	A re-bar, ½ in. diam., projecting 3 ins. above the ground, with cap mkd. PE 5178 1 64, bears S. 45° W., 1 lk. dist. Origin unknown.
	Leave Fools Hollow Lake Resort-Unit 1.
9.40	Track road, bears N. 25° E. and S. 25° W.
10.07	Point for the C-E-W 1/64 sec. cor. of sec. 13.
	Set the iron post 24 ins. in the ground in a collar of stone, brass cap mkd.
	S13 C-E-W 1/64 1969
	from which
	A re-bar, ½ in. diam., projecting 3 ins. above the ground, bears N. 40°22' E., 45.2 lks. dist. Origin unknown.
	A steel fence post, projecting 4 ft. above the ground, bears NW., 2 lks. dist.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
13.90	Fools Hollow Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.
14.80	Track road, bears S. 30° E. and N. 30° W.
15.105	Point for the C-W-E-W 1/256 sec. cor. of sec. 13; not monumented.
17.622	Point for the 1/1024 sec. cor. of sec. 13.
	Set the iron post 10 ins. in the ground, mound of stone to top, brass cap mkd.
	1/1024 1969
	Set a steel fence post, 5 ft. long, alongside the iron post.
20.14	Point for the C-W 1/16 sec. cor. of sec. 13.
	Set the iron post 22 ins. in the ground in a collar of stone, brass cap mkd.
	W 1/16
	C ————— C S13 1969
	from which
	A pine, 10 ins. diam., bears S. 9½° W., 75 lks. dist., mkd. C-W 1/16 S13 BT.
24.80	Track road, bears N. and S.
30.21	Point for the C-W-W 1/64 sec. cor. of sec. 13; not monumented.
40.28	The ¼ sec. cor. of secs. 13 and 14.
	Land, rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak.
Subdivision of the NE¼ of Section 13	
	From the point for the C-E 1/16 sec. cor. of sec. 13.
	N. 0°23' W., on the N. and S. center line of the NE¼ of sec. 13.
	Over gently rolling land, through scattered timber.
4.90	Fence, bears E. and W.
5.00	SE. cor. of a stock pond, 290 lks. in diam.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
7.90	NE. cor. of same stock pond.
10.80	Fence, bears W., and bears E. for 2 lks. to a cor. of fences extending N. and W.
10.90	Power line, bears E. and W.
14.50	A fence cor., bears East, 3 lks. dist.; fences extend N., E. and S.
20.08	Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE 1/4 of sec. 13; not monumented.
22.50	Fence cor.; fences extend N. 0°23' W., E. and S.
26.30	Fence cor.; fences extend N. 0°23' W., E. and S. 0°23' E.
28.60	Fence cor.; fences extend E., S. 0°23' E. and W.; enter cemetery.
31.80	Fence cor.; fences extend N., E. and W.; leave cemetery.
31.90	S. side of a pond, 290 lks. wide, bears E. and W.
34.70	N. side of same pond, bears E. and W.; thence along N. and S. fence.
40.16	The E 1/16 sec. cor. of secs. 12 and 13.
	From the point for the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.
	N. 89°43' W., on the E. and W. center line of the NE 1/4 of sec. 13.
	Over rolling land, through moderate timber.
10.00	Leave moderate timber, bears SE. and NW.; enter open field.
13.70	Graded road, bears S. 60° E. and N. 60° W.
20.00	Fence, bears N. and S.
20.02	The point for the NE 1/16 sec. cor. of sec. 13.
30.03	Point for the C-W-NE 1/64 sec. cor. of sec. 13.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">S13 C-W-NE 1/64 1969</p>
	from which
	<p style="text-align: center;">A fence cor., bears North, 21 lks. dist.; fences extend N., E. and S.</p>
30.10	Power line, bears N. and S.



## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
30.40	Graded road, bears N. and S.
30.80	Fence, bears N. and S.
40.04	The C-N 1/16 sec. cor. of sec. 13.
Subdivision of the SE $\frac{1}{4}$ of Section 13	
From the E 1/16 sec. cor. of secs. 13 and 24.	
N. 0°22' W., on the N. and S. center line of the SE $\frac{1}{4}$ of sec. 13.	
Over rolling land, through scattered timber.	
9.995	Point for the C-S-SE 1/64 sec. cor. of sec. 13.
Set the iron post 24 ins. in the ground, brass cap mkd.	
C-S-SE 1/64 S13 1969	
from which	
A pine, 8 ins. diam., bears S. 27° E., 163 lks. dist., mkd. C-S-SE 1/64 S13 BT.	
Raise a mound of stone W. of the cor.	
11.00	Fence, bears E. and W.
19.99	Point for the SE 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ of sec. 13; not monumented.
39.98	The point for the C-E 1/16 sec. cor. of sec. 13.
From the S 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp.	
N. 89°59' W., on the E. and W. center line of the SE $\frac{1}{4}$ of sec. 13.	
Over rolling land, through scattered timber.	
20.13	The point for the SE 1/16 sec. cor. of sec. 13.
30.20	Fence, bears N. and S.
30.60	Graded road, bears N. and S.
30.90	Fence, bears N. and S.
40.26	The point for the C-S 1/16 sec. cor. of sec. 13.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
	Subdivision of the SW $\frac{1}{4}$ of Section 13
	-----
	From the W 1/16 sec. cor. of secs. 13 and 24.
	N. 0°15' W., on the N. and S. center line of the SW $\frac{1}{4}$ of sec. 13.
	Over rolling land, through moderate timber.
6.50	Forest Service Road No. 43, bears N. 70° E. and S. 70° W.
18.40	Track road, bears SE. and NW.
20.00	Point for the SW 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ of sec. 13.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	S13
	SW
	1/16
	1969
	from which
	A pine, 9 ins. diam., bears S. 18° W., 15 $\frac{1}{2}$ lks. dist., mkd. SW 1/16 S13 BT.
	A pine, 9 ins. diam., bears N. 33 $\frac{1}{2}$ ° W., 48 lks. dist., mkd. SW 1/16 S13 BT.
	Raise a mound of stone W. of the cor.
20.55	Fence, bears E. and W.
21.70	Power line, bears S. 53° E. and N. 53° W.
22.70	Fence, bears S. 40° E. and N. 40° W.
25.00	Fence, bears N. 15° E. and S. 15° W.
29.985	Point for the C-N-SW 1/64 sec. cor. of sec. 13; not monumented.
34.977	Point for the C-N-N-SW 1/256 sec. cor. of sec. 13; not monumented.
39.25	Fence, bears E. and W.
39.97	The C-W 1/16 sec. cor. of sec. 13.
	-----
	From the point for the C-S 1/16 sec. cor. of sec. 13.
	N. 89°49' W., on the E. and W. center line of the SW $\frac{1}{4}$ of sec. 13.
	Over rolling land, through moderate timber, along an E. and W. fence.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
10.065	<p>Point for the C-E-SW 1/64 sec. cor. of sec. 13.</p> <p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S13 C-E-SW 1/64 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 1° W., 42 lks. dist., mkd. C-E-SW 1/64 S13 BT.</p> <p>The cor. is located 35 lks. South of a fence bearing irregularly E. and W.</p>
12.40	Fence, bears S., and bears N. for 40 lks. to a cor. of fences extending E., S. and W.
13.10	Track road, bears N. and S.
14.50	Fools Hollow Wash, 40 lks. wide, 2 ft. deep, drains N. 30° W.
18.90	Power line, bears S. 53° E. and N. 53° W.
20.13	The SW 1/16 sec. cor. of sec. 13.
21.70	Track road, bears SE. and NW.
26.30	Same road, bears N. 30° E. and S. 30° W.
27.80	Wash, 20 lks. wide, 1 ft. deep, drains N.
38.50	Fence, bears S., and bears N. for 13 lks. to a cor. of fences extending N., S. and irregularly E.
39.80	Graded road, bears N. and S.
40.26	The S 1/16 sec. cor. of secs. 13 and 14.
0.35	<p>From the C-E-SW 1/64 sec. cor. of sec. 13.</p> <p>N. 0°13' W., on the N. and S. center line of the NE<math>\frac{1}{4}</math>SW<math>\frac{1}{4}</math> of sec. 13.</p> <p>Over rolling land, through moderate timber.</p>
9.995	Fence, bears irregularly E. and W.
14.992	<p>Point for the NE-SW 1/64 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE<math>\frac{1}{4}</math>SW<math>\frac{1}{4}</math> of sec. 13; not monumented.</p> <p>Point for the C-N-NE-SW 1/256 sec. cor. of sec. 13.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S13 C-N-NE-SW 1/256 1969</p>

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS		
	<p>from which</p> <p>A re-bar, <math>\frac{1}{2}</math> in. diam., projecting 2 ins. above the ground, bears N. <math>43^{\circ}07'</math> E., 46 lks. dist. Origin unknown.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p>	
18.70	Track road, bears N. $25^{\circ}$ E. and S. $25^{\circ}$ W.	
19.99	The C-E-W $1/64$ sec. cor. of sec. 13.	
<hr/>		
	<p>From the C-N-S <math>1/64</math> sec. cor. of sec. 13.</p> <p>N. <math>89^{\circ}52'</math> W., on the E. and W. center line of the <math>NE\frac{1}{4}SW\frac{1}{4}</math> of sec. 13.</p> <p>Over rolling land, through moderate timber.</p>	
10.067	The point for the NE-SW $1/64$ sec. cor. of sec. 13.	
11.70	Track road, bears N. and S.	
15.10	Point for the C-W-NE-SW $1/256$ sec. cor. of sec. 13; not monumented.	
15.30	Fools Hollow Wash, 20 lks. wide, 2 ft. deep, drains N. $20^{\circ}$ E.	
19.70	Fence, bears irregularly N. and S.	
20.134	The point for the C-N-SW $1/64$ sec. cor. of sec. 13.	
<hr/>		
	<p>From the point for the C-W-NE-SW <math>1/256</math> sec. cor. of sec. 13.</p> <p>N. <math>0^{\circ}13'</math> W., on the N. and S. center line of the <math>NW\frac{1}{4}NE\frac{1}{4}SW\frac{1}{4}</math> of sec. 13.</p> <p>Over gently rolling land, through scattered timber.</p>	
0.50	Fools Hollow Wash, 20 lks. wide, 2 ft. deep, drains N. $20^{\circ}$ E.	
4.995	Point for the NW-NE-SW $1/256$ sec. cor. of sec. 13, at intersection with the E. and W. center line of the $NW\frac{1}{4}NE\frac{1}{4}SW\frac{1}{4}$ of sec. 13; not monumented.	
6.40	Track road, bears S. $60^{\circ}$ E. and NW.	
9.99	The point for the C-W-E-W $1/256$ sec. cor. of sec. 13.	
<hr/>		
	<p>From the C-N-NE-SW <math>1/256</math> sec. cor. of sec. 13.</p> <p>N. <math>89^{\circ}53'</math> W., on the E. and W. center line of the <math>NW\frac{1}{4}NE\frac{1}{4}SW\frac{1}{4}</math> of sec. 13.</p> <p>Over gently rolling land, through open wash area draining N.</p>	

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
0.60	Track road, bears N. 10° E. and S. 10° W.
2.60	Track road, bears SE. and NW.
4.30	Fools Hollow Wash, 20 lks. wide, 2 ft. deep, drains N.; leave wash area, enter moderate timber.
5.033	The point for the NW-NE-SW 1/256 sec. cor. of sec. 13.
7.55	Point for the 1/1024 sec. cor. of sec. 13.
	Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.
	1/1024 1969
	Set a steel fence post, 5 ft. long, alongside the iron post.
8.90	Fence, bears irregularly N. and S.
10.067	The point for the C-N-N-SW 1/256 sec. cor. of sec. 13.
Subdivision of the NW¼ of Section 13	
From the C-W 1/16 sec. cor. of sec. 13.	
N. 0°05' W., on the N. and S. center line of the NW¼ of sec. 13.	
Over gently rolling land, through moderate timber.	
9.80	Track road, bears E. and W., curving NW.
10.055	Point for the C-S-NW 1/64 sec. cor. of sec. 13.
	Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	S13 C-S-NW 1/64 1969
	Set a steel fence post, 5 ft. long, alongside the iron post.
15.083	Point for the C-N-S-NW 1/256 sec. cor. of sec. 13.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	C-N-S-NW 1/256 S13 1969
	from which

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
	<p>A pine, 8 ins. diam., bears S. <math>38\frac{1}{2}^{\circ}</math> E., 67 lks. dist., mkd. C-N-S-NW 1/256 S13 BT.</p> <p>A pine, 6 ins. diam., bears N. <math>86^{\circ}</math> W., 23 lks. dist., mkd. C-N-S-NW 1/256 S13 BT.</p> <p>A re-bar, <math>\frac{1}{2}</math> in. diam., bears N. <math>60^{\circ}</math> E., 30.1 lks. dist. Origin unknown.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
20.11	<p>Point for the NW 1/16 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NW <math>\frac{1}{4}</math> of sec. 13.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S13 1969</p> <p>from which</p> <p>A pine, 8 ins. diam., bears S. <math>27\frac{1}{2}^{\circ}</math> E., 55 lks. dist., mkd. NW 1/16 S13 BT.</p> <p>A pine, 16 ins. diam., bears N. <math>61\frac{3}{4}^{\circ}</math> W., <math>48\frac{1}{2}</math> lks. dist., mkd. NW 1/16 S13 BT.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>
26.60	<p>Mean high water line on the W. shore of Fools Hollow Lake, bears S. <math>15^{\circ}</math> E. and N. <math>15^{\circ}</math> W., thence over lake by triangulation.</p>
30.17	<p>Point for the C-N-NW 1/64 sec. cor. of sec. 13, falls in Fools Hollow Lake; not monumented.</p>
40.23	<p>The true point for the W 1/16 sec. cor. of secs. 12 and 13, from which its witness cor. bears S. <math>89^{\circ}46'</math> W., 220 lks. dist.</p>
	<p>From the C-N 1/16 sec. cor. of sec. 13.</p> <p>S. <math>89^{\circ}56'</math> W., on the E. and W. center line of the NW <math>\frac{1}{4}</math> of sec. 13.</p> <p>Over gently rolling land, through scattered timber.</p>
2.50	<p>Track road, bears S. <math>80^{\circ}</math> E. and N. <math>80^{\circ}</math> W.</p>
5.022	<p>Point for the C-E-E-NW 1/256 sec. cor. of sec. 13; not monumented.</p>
8.10	<p>Mean high water line on the E. shore of Fools Hollow Lake, bears N. and S., thence over lake by triangulation.</p>
10.045	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 13 falls in Fools Hollow Lake; not monumented.</p>

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
18.70	Mean high water line on the W. shore of Fools Hollow Lake, bears S. 15° E. and N. 15° W.; enter moderate timber.
20.09	The NW 1/16 sec. cor. of sec. 13.
22.602	Point for the 1/1024 sec. cor. of sec. 13.
	Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
	1/1024
	1969
	from which
	A pine, 6 ins. diam., bears N. 46½° E., 5 lks. dist., mkd. 1/1024 BT.
	A pine, 7 ins. diam., bears N. 40½° W., 9 lks. dist., mkd. 1/1024 BT.
	A re-bar, ½ in. diam., bears N. 68° E., 25.6 lks. dist. Origin unknown.
25.115	Point for the C-E-W-NW 1/256 sec. cor. of sec. 13.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	C-E-W-NW
	1/256
	S13
	1969
	from which
	A re-bar, ½ in. diam., bears N. 72¾° E., 25.6 lks. dist. Origin unknown.
	Set a steel fence post, 5 ft. long, alongside the iron post.
	Raise a mound of stone N. of the cor.
25.30	Track road, bears irregularly N. and S.
30.14	Point for the C-W-NW 1/64 sec. cor. of sec. 13; not monumented.
40.19	The N 1/16 sec. cor. of secs. 13 and 14.
	From the C-E-W 1/64 sec. cor. of sec. 13.
	N. 0°08' W., on the N. and S. center line of the SE¼NW¼ of sec. 13.
	Over gently rolling open land.
5.035	Point for the C-S-SE-NW 1/256 sec. cor. of sec. 13; not monumented.
8.30	Mean high water line on the S. shore of Fools Hollow Lake bears NE. and SW., curving W., thence over lake by triangulation.

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
10.07	Point for the SE-NW 1/64 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13 falls in Fools Hollow Lake; not monumented.
15.105	Point for the C-N-SE-NW 1/256 sec. cor. of sec. 13 falls in Fools Hollow Lake; not monumented.
20.14	The point for the C-E-NW 1/64 sec. cor. of sec. 13.
<hr/> From the point for the C-S-N 1/64 sec. cor. of sec. 13. N. 89°59' W., on the E. and W. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13.	
Over rolling land, through moderate timber, through Fools Hollow Lake Resort-Unit 1.	
2.51	Leave Fools Hollow Lake Resort-Unit 1, bears N. and S.
5.025	Point for the C-E-SE-NW 1/256 sec. cor. of sec. 13; not monumented.
9.50	Mean high water line on the E. shore of Fools Hollow Lake, bears NE. and SW., thence over lake by triangulation.
10.05	The point for the SE-NW 1/64 sec. cor. of sec. 13.
16.40	Mean high water line on the W. shore of Fools Hollow Lake, bears N. 20° W. and S. 20° E., curving E.; enter gently rolling land, through scattered timber.
17.595	Point for the 1/1024 sec. cor. of sec. 13.
Set the iron post 24 ins. in the ground, brass cap mkd.  1/1024 1969	
from which	
A re-bar, $\frac{1}{2}$ in. diam., bears N. 54°12' E., 33.8 lks. dist., projecting 3 ins. above the ground in a collar of stone. Origin unknown.	
Set a steel fence post, 5 ft. long, alongside the iron post.	
Raise a mound of stone N. of the cor.	
20.11	The C-S-NW 1/64 sec. cor. of sec. 13.
<hr/> From the point for the C-E-SE-NW 1/256 sec. cor. of sec. 13. N. 0°12' W., on the N. and S. center line of the NE $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13.	
Over rolling land, through moderate timber.	



Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
3.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 80° W.
5.037	Point for the NE-SE-NW 1/256 sec. cor. of sec. 13, at intersection with the E. and W. center line of the NE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{4}$ of sec. 13, not monumented.
10.075	The point for the C-E-E-NW 1/256 sec. cor. of sec. 13.
<hr/> From the C-N-S-N 1/256 sec. cor. of sec. 13.	
S. 89°57' W., on the E. and W. center line of the NE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{4}$ of sec. 13.	
Over rolling land, through moderate timber, along a boundary of Fools Hollow Lake Resort-Unit 1.	
0.60	Track road, bears N. and S.
2.512	Point for the 1/1024 sec. cor. of sec. 13.
Set the iron post 22 ins. in the ground in a collar of stone, brass cap mkd.	
<p style="text-align: center;">1/1024 1969</p>	
from which	
<p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 20° W., 19 lks. dist., mkd. 1/1024 BT.</p>	
<p style="padding-left: 40px;">A re-bar, 5/8 in. diam., bears North 3.2 lks. dist., projecting 4 ins. above the ground. Origin unknown.</p>	
Set a steel fence post, 5 ft. long, alongside the iron post.	
Leave Fools Hollow Lake Resort-Unit 1.	
5.025	The point for the NE-SE-NW 1/256 sec. cor. of sec. 13.
8.00	Mean high water line on the E. shore of Fools Hollow Lake, bears N. 10° E. and S. 10° W., thence over lake by triangulation.
10.05	The point for the C-N-SE-NW 1/256 sec. cor. of sec. 13.
<hr/> From the C-E-E-W 1/256 sec. cor. of sec. 13.	
N. 0°09' W., on the N. and S. center line of the SE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{4}$ of sec. 13.	
Over rolling land, through moderate timber, along a boundary of Fools Hollow Lake Resort-Unit 1.	
2.30	Track road, bears N. 70° E. and S. 70° W.
5.04	Point for the SE-SE-NW 1/256 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SE $\frac{1}{2}$ SE $\frac{1}{2}$ NW $\frac{1}{4}$ of sec. 13.

## Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S13 SE-SE-NW 1/256 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears N. 39° E., 30 lks. dist., mkd. SE-SE-NW 1/256 S13 BT.</p> <p style="padding-left: 40px;">A pine, 11 in. diam., bears S. 35½° W., 42 lks. dist., mkd. SE-SE-NW 1/256 S13 BT.</p> <p style="padding-left: 40px;">A re-bar 5/8 in. diam., bears N. 6°20' W., 1.8 lks. dist., projecting 3 ins. above the ground. Origin unknown.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Leave Fools Hollow Resort-Unit 1.</p> <p>10.08 The point for the C-E-SE-NW 1/256 sec. cor. of sec. 13.</p> <hr/> <p>From the point for the C-S-S-N 1/256 sec. cor. of sec. 13.</p> <p>N. 89°55' W., on the E. and W. center line of the SE¼SE¼ NW¼ of sec. 13.</p> <p>Over rolling land, through moderate timber.</p> <p>2.515 Point for the 1/1024 sec. cor. of sec. 13.</p> <p>Set the iron post 26 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">1/1024 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 12½° W., 8½ lks. dist., mkd. 1/1024 BT.</p> <p style="padding-left: 40px;">A re-bar, 5/8 in. diam., bears N. 45° W., 0.4 lks. dist., projecting 3 ins. above the ground. Origin unknown.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>5.03 The SE-SE-NW 1/256 sec. cor. of sec. 13.</p> <p>10.06 The point for the C-S-SE-NW 1/256 sec. cor. of sec. 13.</p> <hr/> <p>From the point for the C-W-W 1/64 sec. cor. of sec. 13.</p> <p>N. 0°01' W., on the N. and S. center line of the SW¼NW¼ of sec. 13.</p>	

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
	Over rolling land, through moderate timber.
10.04	Point for the SW-NW 1/64 sec. cor. of sec. 13, at intersection with the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13; not monumented.
15.06	Point for the C-N-SW-NW 1/256 sec. cor. of sec. 13; not monumented.
20.08	The point for the C-W-NW 1/64 sec. cor. of sec. 13.
	From the C-S-NW 1/64 sec. cor. of sec. 13.
	N. 89°58' W., on the E. and W. center line of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13.
	Over rolling land, through moderate timber.
1.60	Track road, bears SE. and NW.
5.03	Point for the C-E-SW-NW 1/256 sec. cor. of sec. 13; not monumented.
5.40	Track road, bears irregularly N. and S.
10.06	The point for the SW-NW 1/64 sec. cor. of sec. 13.
20.12	The point for the S-N 1/64 sec. cor. of secs. 13 and 14.
	From the point for the C-E-SW-NW 1/256 sec. cor. of sec. 13.
	N. 0°02' W., on the N. and S. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13.
	Over rolling land, through moderate timber.
2.70	Track road, bears N. and S. 30° E.
5.025	Point for the NE-SW-NW 1/256 sec. cor. of sec. 13, at intersection with the E. and W. center line of NE $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13; not monumented.
10.05	The C-E-W-NW 1/256 sec. cor. of sec. 13.
	From the C-N-S-NW 1/256 sec. cor. of sec. 13.
	West, on the E. and W. center line of the NE $\frac{1}{4}$ SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13.
	Over rolling land, through moderate timber.
2.515	Point for the 1/1024 sec. cor. of sec. 13.
	Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.
	1/1024
	1969

Subdivision of Section 13, T. 10 N., R. 21 E.

CHAINS	
	<p>from which</p> <p>A re-bar, <math>\frac{1}{2}</math> in. diam., bears N. <math>66^{\circ}</math> E., 30.2 lks. dist., projecting 8 ins. above the ground. Origin unknown.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p>
5.03	The point for the NE-SW-NW $\frac{1}{256}$ sec. cor. of sec. 13.
5.20	Track road, bears irregularly N. and S.
10.06	The point for the C-N-SW-NW $\frac{1}{256}$ sec. cor. of sec. 13.
<hr/>	
	<p>From the point for the C-W-NW <math>\frac{1}{64}</math> sec. cor. of sec. 13. N. <math>0^{\circ}03'</math> W., on the N. and S. center line of the NW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 13.</p> <p>Over rolling land, through moderate timber.</p>
10.045	Point for the NW-NW $\frac{1}{64}$ sec. cor. of sec. 13, at intersection with the E. and W. center line of the NW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 13; not monumented.
10.10	An abandoned fence line, bears E. and W.
15.10	Track road, bears E. and W.
18.00	Mean high water line on the S. shore of a cove, bears N. $70^{\circ}$ E. and S. $70^{\circ}$ W.; thence over cove by triangulation.
20.09	The point for the W-W $\frac{1}{64}$ sec. cor. of secs. 12 and 13.
<hr/>	
	<p>From the point for the C-N-NW <math>\frac{1}{64}</math> sec. cor. of sec. 13. S. <math>89^{\circ}52'</math> W., on the E. and W. center line of the NW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 13.</p> <p>Over Fools Hollow Lake by triangulation.</p>
2.60	Mean high water line on the W. side of Fools Hollow Lake, bears S. $20^{\circ}$ E. and N. $20^{\circ}$ W., thence over rolling land, through moderate timber.
5.02	Point for the C-E-NW-NW $\frac{1}{256}$ sec. cor. of sec. 13.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p>C-E-NW-NW  <math>\frac{1}{256}</math>                      S13                      1969</p>
	<p>from which</p> <p>A pine, 9 ins. diam., bears N. <math>81^{\circ}</math> E., 44 lks. dist., mkd. C-E-NW-NW <math>\frac{1}{256}</math> S13 BT.</p>

## Subdivision of Section 13, T. 10 N., R. 21 E.

## CHAINS

A pine, 9 ins. diam., bears S.  $64\frac{1}{2}^{\circ}$  E.,  $51\frac{1}{2}$  lks. dist., mkd. C-E-NW-NW 1/256 S13 BT.

Set a steel fence post, 5 ft. long, alongside the iron post.

Raise a mound of stone N. of the cor.

- 6.90 Track road, bears irregularly N. and S.  
 10.04 The point for the NW-NW 1/64 sec. cor. of sec. 13.  
 20.07 Fence, bears irregularly N. and S.  
 20.08 The N-N 1/64 sec. cor. of secs. 13 and 14.

## Subdivision of Section 14, T. 10 N., R. 21 E.

From the  $\frac{1}{4}$  sec. cor. of secs. 14 and 23.

N.  $0^{\circ}07'$  E., on the N. and S. center line of sec. 14.

Over rolling land, through Show Low Country Club Estates subdivision.

Along the W. portion of the Fairway Dr. Loop, bearing N. from Forest Service Road No. 43.

- 6.50 W. portion of the Fairway Dr. Loop, on a curve, bears N.  $15^{\circ}$  E. and S.  
 20.22 Point for the C-S 1/16 sec. cor. of sec. 14; not monumented.  
 40.30 Fence, bears E. and W.  
 40.44 The center  $\frac{1}{4}$  sec. cor. of sec. 14, monumented by a pipe,  $\frac{3}{4}$  in. diam., projecting 10 ins. above the ground. This cor. was established by a registered Land Surveyor and is recognized as the center  $\frac{1}{4}$  by local land owners; not remonumented.  
 from which  
 A fence cor., bears S.  $57^{\circ}$  W., 23 lks. dist., with fences extending E. and S.  
 N.  $0^{\circ}07'$  E., beginning new measurement.  
 Leave Show Low Country Club Estates.  
 20.08 Point for the C-N 1/16 sec. cor. of sec. 14; not monumented.  
 23.60 Wash, 30 lks. wide, 10 ft. banks, drains NW.  
 27.00 Power line, bears S.  $53^{\circ}$  E. and N.  $53^{\circ}$  W.  
 30.12 Point for the C-N-N 1/64 sec. cor. of sec. 14; not monumented.

Subdivision of Section 14, T. 10 N., R. 21 E.

CHAINS	
36.90	Fence, bears irregularly E. and W.
40.16	<p>The ½ sec. cor. of secs. 11 and 14.</p> <p>Land, rolling. Soil, rocky clay loam. Timber, pine, juniper and oak. Undergrowth, grass and scrub oak.</p>
	<p>From the ½ sec. cor. of secs. 13 and 14.</p>
	<p>N. 89°59' W., on the E. and W. center line of sec. 14.</p>
	<p>Over rolling land, through moderate timber.</p>
4.10	<p>Power line, bears S. 53° E. and N. 53° W.</p>
10.03	<p>Point for the C-E-E 1/64 sec. cor. of sec. 14.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S14 C-E-E 1/64 1969</p>
	<p>from which</p>
	<p>A pine, 9 ins. diam., bears S. 9½° W., 89 lks. dist., mkd. C-E-E 1/64 S14 BT.</p>
	<p>A juniper, 6 ins. diam., bears N. 78½° W., 83 lks. dist., mkd. C-E-E 1/64 S14 BT.</p>
	<p>An open pipe, 1 in. diam., projecting 2 ins. above the ground, bears S. 40½° W., 2 lks. dist. Origin unknown.</p>
17.60	<p>Graded road, bears N. and S., curving SE.</p>
20.06	<p>The C-E 1/16 sec. cor. of sec. 14, monumented by a pipe, ¾ in. diam., projecting 4 ins. above the ground, set in a collar of stone. This cor. was established by a registered Land Surveyor and is recognized as the cor. by local land owners.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S14</p> <p style="text-align: center;">C ————— C E 1/16 1969</p>
	<p>from which</p>
	<p>A pine, 10 ins. diam., bears N. 5° E., 70 lks. dist., mkd. C-E 1/16 S14 BT.</p>
	<p>A fence cor., bears S. 30° W., 34 lks. dist., with fences extending S. and W.</p>

## Subdivision of Section 14, T. 10 N., R. 21 E.

## CHAINS

Bury the iron pipe alongside the iron post.

Raise a mound of stone N. of the cor.

---

S. 89°50' W., beginning new measurement.

- 2.10 Power line, bears S. and W.  
 2.80 Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.  
 20.08 The center  $\frac{1}{4}$  sec. cor. of sec. 14.

---

S. 89°47' W., beginning new measurement.

- 16.20 Graded road, bears N. and S.  
 20.03 Point for the C-W 1/16 sec. cor. of sec. 14; not monumented.  
 20.20 Telephone line, bears N. 1 $\frac{1}{2}$ ° E. and S. 1 $\frac{1}{2}$ ° W.  
 21.60 Right-of-way fence, bears S. 25° E. and N. 25° W.  
 23.10 State Highway No. 160, bears S. 25° E. and N. 25° W.  
 23.60 Right-of-way fence, bears S. 25° E. and N. 25° W.  
 24.30 Bagnol Wash, 50 lks. wide, 2 ft. deep, drains NE.  
 40.06 The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15.

Land, rolling.  
 Soil, rocky clay loam.  
 Timber, pine, juniper and oak.  
 Undergrowth, grass and scrub oak.

---

Subdivision of the NE $\frac{1}{4}$  of Section 14

---

From the C-E 1/16 sec. cor. of sec. 14.

N. 0°04' E., on the N. and S. center line of the NE $\frac{1}{4}$  of sec. 14.

Over rolling land, through moderate timber.

- 0.90 Track road, bears S. 60° E. and N. 60° W.  
 2.90 Wash, 20 lks. wide, 1 ft. deep, drains NE.  
 11.80 Power line, bears S. 53° E. and N. 53° W.  
 20.05 Point for the NE 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NE $\frac{1}{4}$  of sec. 14.

## Subdivision of Section 14, T. 10 N., R. 21 E.

CHAINS		
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S14 NE 1/16 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 54<math>\frac{3}{4}</math>° E., 73 lks. dist., mkd. NE 1/16 S14 BT.</p> <p>Raise a mound of stone W. of the cor.</p> <p>40.11 The E 1/16 sec. cor. of secs. 11 and 14.</p>	
	<hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 14.</p> <p>S. 89°58' W., on the E. and W. center line of the NE<math>\frac{1}{4}</math> of sec. 14.</p> <p>Over rolling land, through moderate timber.</p> <p>0.01 Fence, bears irregularly N. and S.</p> <p>7.30 Wash, 20 lks. wide, 1 ft. deep, drains N. 20° E.</p> <p>8.90 Graded road, bears N. 30° E. and S. 15° W.</p> <p>10.025 Point for the C-E-NE 1/64 sec. cor. of sec. 14.</p> <p>Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">S14 C-E-NE 1/64 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 56<math>\frac{3}{4}</math>° E., 34 lks. dist., mkd. C-E-NE 1/64 S14 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 27° W., 65<math>\frac{1}{2}</math> lks. dist., mkd. C-E-NE 1/64 S14 BT.</p> <p>20.05 The NE 1/16 sec. cor. of sec. 14.</p> <p>30.08 Point for the C-W-NE 1/64 sec. cor. of sec. 14.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S14 C-W-NE 1/64 1969</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 77<math>\frac{3}{4}</math>° E., 27<math>\frac{1}{2}</math> lks. dist., mkd. C-W-NE 1/64 S14 BT.</p>	



Subdivision of Section 14, T. 10 N., R. 21 E.

CHAINS	
<p>30.80</p> <p>38.70</p> <p>40.11</p>	<p>Set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Power line, bears S. 53° E. and N. 53° W.</p> <p>Wash, 10 lks. wide, 1 ft. deep, drains NW.</p> <p>The point for the C-N 1/16 sec. cor. of sec. 14.</p>
<p>20.12</p> <p>0.10</p> <p>20.12</p>	<p style="text-align: center;">Subdivision of the SE<math>\frac{1}{4}</math> of Section 14</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0°03' W., on the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 14.</p> <p>Over rolling land, through moderate timber.</p> <p>Through Show Low Country Club Estates.</p> <p>The SE 1/16 sec. cor. of sec. 14, monumented by a pipe, <math>\frac{3}{4}</math> ins. diam., projecting <math>\frac{1}{2}</math> in. above the ground, set in a collar of stone. This cor. was established by a registered Land Surveyor and is recognized as the cor. by local land owners.</p> <p>At the corner point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S14 SE 1/16 1969</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 16<math>\frac{1}{2}</math>° E., 62<math>\frac{1}{2}</math> lks. dist., mkd. SE 1/16 S14 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N. 2<math>\frac{3}{4}</math>° W., 10 lks. dist.; fences bear N. and E.</p> <p>Bury the iron pipe and set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p> <hr/> <p>N. 0°05' W., beginning new measurement.</p> <p>Fence, bears E. and W.</p> <p>The C-E 1/16 sec. cor. of sec. 14.</p>
	<p>From the S 1/16 sec. cor. of secs. 13 and 14.</p>

## Subdivision of Section 14, T. 10 N., R. 21 E.

CHAINS	
	<p>S. 89°29' W., on the E. and W. center line of the SE<math>\frac{1}{4}</math> of sec. 14.</p> <p>Over rolling land, through moderate timber.</p> <p>Along the S. side of an E. and W. fence, along a boundary of Show Low Country Club Estates.</p> <p>20.12 The SE 1/16 sec. cor. of sec. 14.</p> <hr/> <p>S. 89°32' W., beginning new measurement.</p> <p>Enter Show Low Country Club Estates Subdivision.</p> <p>1.90 E. portion of the Fairway Dr. Loop, bears N. and S.</p> <p>3.80 Enter Golf Course, bears N. and S.</p> <p>17.80 Leave Golf Course, bears N. and S.</p> <p>18.20 W. portion of the Fairway Dr. Loop, bears N. and S.</p> <p>20.14 The point for the C-S 1/16 sec. cor. of sec. 14.</p>
	<p style="text-align: center;">Subdivision of the NW<math>\frac{1}{4}</math> of Section 14</p> <hr/> <p>From the point for the C-W 1/16 sec. cor. of sec. 14.</p> <p>N. 0°06' E., on the N. and S. center line of the NW<math>\frac{1}{4}</math> of sec. 14.</p> <p>Over rolling land, through moderate timber.</p> <p>10.00 Telephone line, bears N. 1<math>\frac{1}{2}</math>° E. and S. 1<math>\frac{1}{2}</math>° W.</p> <p>10.50 Draw, drains N. 80° E.</p> <p>18.50 Bagnol Wash, 20 lks. wide, 1 ft. deep, drains E.</p> <p>20.08 Point for the NW 1/16 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NW<math>\frac{1}{4}</math> of sec. 14.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S14 NW 1/16 1969</p> <p>The cor. is located 24 lks. West of a telephone line bearing N. 1<math>\frac{1}{2}</math>° E. and S. 1<math>\frac{1}{2}</math>° W.</p> <p>Set a steel fence post, 5 ft. long, alongside the iron post.</p> <p>Raise a mound of stone W. of the cor.</p>

## Subdivision of Section 14, T. 10 N., R. 21 E.

## CHAINS

- 30.12 Point for the C-N-NW 1/64 sec. cor. of sec. 14.
- Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
- S14  
C-N-NW  
1/64  
1969
- from which
- A pine, 8 ins. diam., bears S. 22° W., 20 lks. dist., mkd. C-N-NW 1/64 S14 BT.
- A juniper, 6 ins. diam., bears N. 25° W., 22 lks. dist., mkd. X BT.
- The cor. is located 52 lks. West of a telephone line bearing N. 1½° E. and S. 1½° W.
- 30.20 Wash, 10 lks. wide, 1 ft. deep, drains E.
- 40.16 The W 1/16 sec. cor. of secs. 11 and 14.
- 
- From the point for the C-N 1/16 sec. cor. of sec. 14.
- S. 89°47' W., on the E. and W. center line of the NW¼ of sec. 14.
- Over rolling land, through moderate timber.
- 3.30 Wash, 10 lks. wide, 2 ft. deep, drains N. 30° W.
- 10.02 Point for the C-E-NW 1/64 sec. cor. of sec. 14; not monumented.
- 10.20 Fence, bears N. 30° E. and S. 30° W.
- 13.40 Bagnal Wash, 100 lks. wide, 2 ft. deep, drains NE.
- 16.60 Fence, bears N. and S.
- 17.50 Graded road, bears N. and S.
- 19.80 Telephone line, bears N. 1½° E. and S. 1½° W.
- 20.04 The NW 1/16 sec. cor. of sec. 14.
- 29.30 Right-of-way fence, bears S. 15° E. and N. 15° W.
- 30.065 Point for the C-W-NW 1/64 sec. cor. of sec. 14.
- Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.
- S14  
C-W-NW  
1/64  
1969
- from which

Subdivision of Section 14, T. 10 N., R. 21 E.

CHAINS	
	A pine, 6 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ E., 24 lks. dist., mkd. C-W-NW $\frac{1}{64}$ S14 BT.
30.80	State Highway No. 160, bears S. $15^{\circ}$ E. and N. $15^{\circ}$ W.
32.30	Right-of-way fence, bears S. $15^{\circ}$ E. and N. $15^{\circ}$ W.
40.09	The N $\frac{1}{16}$ sec. cor. of secs. 14 and 15.
<hr/>	
	From the point for the C-E-NW $\frac{1}{64}$ sec. cor. of sec. 14. N. $0^{\circ}06'30''$ E., on the N. and S. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
	Over rolling land, through moderate timber.
6.60	Track road, bears SE. and NW.
10.04	Point for the NE-NW $\frac{1}{64}$ sec. cor. of sec. 14, at intersection with the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	S14 NE-NW $\frac{1}{64}$ 1969
	Set a steel fence post, 5 ft. long, alongside the iron post.
10.90	Bagnal Wash, 80 lks. wide, 2 ft. deep, drains E.
14.10	Power line, bears S. $53^{\circ}$ E. and N. $53^{\circ}$ W.
20.08	The E-W $\frac{1}{64}$ sec. cor. of secs. 11 and 14.
<hr/>	
	From the point for the C-N-N $\frac{1}{64}$ sec. cor. of sec. 14. S. $89^{\circ}46'$ W., on the E. and W. center line of the NE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 14.
	Over rolling land, through moderate timber.
4.20	Wash, 20 lks. wide, 2 ft. deep, drains N. $30^{\circ}$ W.
5.50	Power line, bears S. $53^{\circ}$ E. and N. $53^{\circ}$ W.
10.02	The NE-NW $\frac{1}{64}$ sec. cor. of sec. 14.
12.10	Bagnal Wash, 100 lks. wide, 2 ft. deep, drains N. $10^{\circ}$ E.
16.00	Fence, bears N. $20^{\circ}$ E. and S. $20^{\circ}$ W.
16.80	Graded road, bears N. $20^{\circ}$ E. and S. $20^{\circ}$ W.
19.52	Telephone line, bears N. $1\frac{1}{2}^{\circ}$ E. and S. $1\frac{1}{2}^{\circ}$ W.
20.04	The C-N-NW $\frac{1}{64}$ sec. cor. of sec. 14.
<hr/>	

Subdivision of Section 14, T. 10 N., R. 21 E.

CHAINS	
	<p>From the C-W-NW 1/64 sec. cor. of sec. 14.</p>
	<p>N. 0°06' E., on the N. and S. center line of the NW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 14.</p>
	<p>Over rolling land, through moderate timber.</p>
2.80	<p>Right-of-way fence, bears S. 15° E. and N. 15° W.</p>
10.04	<p>Point for the NW-NW 1/64 sec. cor. of sec. 14, at intersection with the E. and W. center line of the NW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 14.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">S14 NW-NW 1/64 1969</p>
	<p>from which</p>
	<p style="text-align: center;">A juniper, 7 ins. diam., bears S. 38<math>\frac{1}{2}</math>° E., 41 lks. dist., mkd. NW-NW 1/64 S14 BT.</p>
	<p>Raise a mound of stone W. of the cor.</p>
12.10	<p>Graded road, bears NE. and SW.</p>
20.08	<p>The point for the W-W 1/64 sec. cor. of secs. 11 and 14.</p>
	<p>From the C-N-NW 1/64 sec. cor. of sec. 14.</p>
	<p>S. 89°47' W., on the E. and W. center line of the NW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 14.</p>
	<p>Over rolling land, through moderate timber.</p>
10.02	<p>The NW-NW 1/64 sec. cor. of sec. 14.</p>
11.20	<p>Graded road, bears NE. and SW.</p>
11.60	<p>Right-of-way fence, bears S. 15° E. and N. 15° W.</p>
13.10	<p>State Highway No. 160, bears S. 15° E. and N. 15° W.</p>
14.60	<p>Right-of-way fence, bears S. 15° E. and N. 15° W.</p>
20.04	<p>The N-N 1/64 sec. cor. of secs. 14 and 15.</p>
<p>Metes and Bounds Survey of Lot 13, Section 12</p>	
	<p>From the C-W-SW 1/64 sec. cor. of sec. 12.</p>
	<p>West, on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 12.</p>
0.715	<p>Point selected for a witness point.</p>


Metes and Bounds Survey of Lot 13, Section 12

CHAINS	
	<p>Set the iron post over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">W P S12 1969</p>
0.95	N. rim of spillway, bears S. 66° E. and N. 66° W.; desc. into spillway.
1.515	Point for angle point No. 1, Lot 13, falls in Fools Hollow Lake spillway.
	<p>Set a steel fence post, 5 ft. long, 16 ins. in the ground</p> <p>Thence, South, with line 1-2, Lot 13.</p>
0.80	Center of spillway, drains N. 66° W.
1.60	S. rim of spillway, bears S. 66° E. and N. 66° W.; thence over gently rolling land, through moderate timber.
1.80	Point selected for a witness point.
	<p>Set the iron post over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">W P S12 1969</p>
4.00	Fence cor., bears SE., 8 lks. dist.; fences bear S. and N. 66° W.
7.50	Point for angle point No. 2, Lot 13.
	<p>Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T10N R21E S12 AP2 1969</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 37½° E., 24½ lks. dist., mkd. AP2 S12 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S. 49½° E., 8 lks. dist., with fences extending N. and S. 45° E.</p> <p>Thence, S. 46°36' E., with line 2-3, Lot 13.</p>
0.22	Fence, bears S. 45° E. and N. 45° W.
2.152	Intersect the N. and S. center line of the SW¼SW¼ of sec. 12, at a point from which the point for the SW-SW 1/64 sec. cor. of sec. 12, bears S. 0°18' E., 1.019 chs. dist.
3.632	Point for angle point No. 3, Lot 13, on the E. and W. center line of the SW¼SW¼ of sec. 12, and 1,915 ft. westerly from the C-S-S 1/64 sec. cor. of sec. 12.

## Metes and Bounds Survey of Lot 13, Section 12

## CHAINS

Set the iron post 18 ins. in the ground in a collar of stone, brass cap mkd.



from which

A pine, 7 ins. diam., bears S.  $68\frac{1}{2}^{\circ}$  E., 72 lks. dist., mkd. AP3 S12 BT.


A fence cor., bears S.  $60\frac{1}{2}^{\circ}$  W.,  $9\frac{1}{2}$  lks. dist.; fences bear S. and N.  $45^{\circ}$  W.

Thence, South, with line 3-4, Lot 13.

Along a N. and S. fence.

5.00 Point for angle point No. 4, Lot 13, on the E. and W. center line of the  $SE\frac{1}{4}SW\frac{1}{4}SW\frac{1}{4}$  of sec. 12.

Set the iron post 20 ins. in the ground in a collar of stone, brass cap mkd.



from which

A pine, 20 ins. diam., bears S.  $52^{\circ}$  E., 108 lks. dist., mkd. AP4 S12 BT.

A fence cor., bears S.  $56^{\circ}$  W., 8 lks. dist.; fences bear N. and W.

Thence, N.  $89^{\circ}50'$  E., with line 4-5, Lot 13, on the E. and W. center line of the  $SE\frac{1}{4}SW\frac{1}{4}SW\frac{1}{4}$  of sec. 12.

0.30 Graded road, on a curve, bears N. and SW.

5.00 Mean high water line on the W. shore of Fools Hollow Lake, bears S.  $15^{\circ}$  E. and N.  $15^{\circ}$  W., thence over lake by calculated course and dist.

8.99 The point for angle point No. 5, Lot 13, identical with the point for the C-S-S-SW  $1/256$  sec. cor. of sec. 12, hereinbefore described.

Thence, N.  $0^{\circ}17'$  W., with line 5-6, Lot 13, on the N. and S. center line of the  $SW\frac{1}{4}$  of sec. 12.

Over water, by triangulation.

4.99 The point for the C-S-SW  $1/64$  sec. cor. of sec. 12, hereinbefore described.

Metes and Bounds Survey of Lot 13, Section 12

<p>CHAINS</p>	<p>14.97 The point for angle point No. 6, Lot 13, identical with the point for the SW 1/16 sec. cor. of sec. 12, herein-before described.</p> <p>Thence, West, with line 6-1, Lot 13, on the E. and W. center line of the SW<math>\frac{1}{4}</math> of sec. 12.</p> <p>Continue over water, by triangulation.</p> <p>8.24 Mean high water line on the W. shore of Fools Hollow Lake, bears N. 15° E. and S. 15° W.; end of triangulation, thence over rolling land, through moderate timber.</p> <p>8.64 Track road, bears N. 15° E. and S. 15° W.</p> <p>10.04 The C-W-SW 1/64 sec. cor. of sec. 12, and point of beginning.</p>
	<p>General Description</p>
	<p>The portion of Township 10 North, Range 21 East, included in this survey, lies approximately 3 miles NW. of Show Low, Arizona. Fools Hollow Lake is located within portions of the area surveyed. Private land owners have developed most of the patented land and built both permanent and summer homes. A Golf Course is located within the Show Low Country Club Estates in section 14.</p> <p>The approximate elevation in the area surveyed, ranges from 6,100 ft. to 6,300 ft. above sea level. The spillway at Fools Hollow Lake is 6,256 ft. in elevation. The land is rolling. The soil is rocky clay loam, which supports a moderate growth of pine, juniper and oak, with a good growth of grass.</p> <p>The access to the area surveyed is very good. State Highway No. 160, traverses northwesterly through the west portion of section 11 and 14. The major use of the land is for recreation.</p>





