

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE DEPENDENT RESURVEY OF

A PORTION OF THE NORTH AND WEST BOUNDARIES

A PORTION OF THE SUBDIVISIONAL LINES

A PORTION OF THE SUBDIVISION OF SECTIONS 4, 7 AND 8

AND

THE RETRACEMENT OF A PORTION OF THE SUBDIVISIONAL LINES

AND

THE SURVEY OF SUBDIVISIONS IN SECTIONS 4, 7 AND 8

AND

THE SURVEY OF THE SOUTH BOUNDARY OF

THE SALT RIVER INDIAN RESERVATION

TOWNSHIP 1 NORTH, RANGE 5 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Boyd S. Owens

Cadastral Surveyor

Paul G. Bauer

Cadastral Surveyor

Under special instructions dated May 11, 19 62, which provided for the surveys Amended Supplemental Special Instructions, dated March 9, 1972, approved April 12, included under Group Number 372, approved May 16, 1962, 1972

and assignment instructions dated May 23, 19 62,
April 13, 19 72

Survey commenced May 24, 19 62

Survey completed May 11, 19 72

1A

check index

BOOK 4938

INDEX DIAGRAM

Township 1 North, Range 5 East

		4	2		
6	5	14 4	11 8	²⁵ 24 2	1
22	23	13	25		
5	7	20 8	9 9	25	12
18	18		10	11	
9	18	16 17	16	15	14
26					13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Section 9 - Page 26

" " " 4 - " 26

" " " 7 - " 31

" " " 8 - " 40

Survey of the South Boundry of the Salt River Indian Reservation -- page 49

Township 1 North, Range 5 East
Gila and Salt River Meridian, Arizona

CHAINS

The south boundary, the Gila and Salt River Base Line, was surveyed in 1867 by W. H. Pierce. The north, east and west boundaries and subdivisional lines were surveyed in 1868 by W. F. Ingalls. Part of the north and west boundaries and the sections north of the Salt River were dependently resurveyed and subdivided by L. D. Chillson in 1888. The north boundary and part of the west boundary and the sections north of the Salt River were dependently resurveyed and subdivided in 1910 by R. A. Farmer. Part of the west boundary was retraced in 1931 by F. E. Joy.

The following notes are those of a dependent resurvey of a portion of the north and west boundaries, a portion of the subdivisional lines and a portion of the section subdivision of certain sections designed to restore the corners in their true original location according to the best available evidence; the retracement of a portion of the subdivisional lines, survey of the subdivision of secs. 4, 7 and 8, and the survey of the South Boundary of the Salt River Indian Reservation, Township 1 North, Range 5 East, Gila and Salt River Meridian, Arizona.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated May 11, 1962, and the Amended Supplemental Special Instructions dated March 9, 1972. The direction of the lines were determined by solar observations and all lines refer to the true meridian.

Under the Special Instructions dated May 11, 1962, the boundaries of sections 4, 7 and 8 were resurveyed and the sections subdivided. Preparation of the Final Returns for these surveys executed in May and June 1962 have been held in abeyance pending an official determination of the location of the South Boundary of the Salt River Indian Reservation in T. 1 N., R. 5 E. Since the 1962 surveys, flooding of the Salt River has destroyed all evidence of some corners set within the channels; certain other corners have been removed or replaced by other parties and certain man-made changes and improvements have occurred. During the 1972 survey, no attempt was made to retrace all the lines surveyed in 1962 to note improvements, such as power lines and roads nor to determine the present status of all corners established in the 1962 survey. In many areas the banks of the Salt River were undefined due to earth fills, excavations, floods, etc., except as recorded in the notes. To control the survey of the South Boundary of the Salt River Indian Reservation, it was found necessary to retrace portions of the 1962 survey, replace certain lost corners and retrace other section lines for closures.

These notes represent a combination of the 1962 and 1972 surveys. Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, all corners were monumented with a standard iron post, 30 inches long, 2½ inches diameter, flanged at the base and with a brass cap riveted to the top.

Township 1 North, Range 5 East
Gila and Salt River Meridian, Arizona

CHAINS

The geographic position of the southeast corner of Section 3, as determined by traverse from USC&GS triangulation station "LEHI" located in Sec. 4, is: Latitude 33°27'05.2" N. and Longitude 111°49'18.3" W.

The mean magnetic declination was found to be 14° East.

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,
TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM., ARIZONA

Reestablishment of the Survey executed
by R. A. Farmer in 1910

Beginning at the cor. of secs. 2 and 3 on the N. bdy. of the Tp., monumented by a steel pin set in concrete in the head wall of an irrigation ditch. This cor. description and subsequent ties was furnished by the Maricopa County Highway Dept. and considered the best available evidence of the original cor. position; not remonumented.

from which

A $\frac{3}{4}$ in. water pipe, projecting 2 ins. above ground, bears N. 88°16' E., 12.8 lks. dist.

The cor. of secs. 34 and 35, T. 2 N., R. 5 E., bears S. 89°46' E., 1.43 chs. dist., reportedly monumented by a Government Land Office brass cap set 18 ins. below the surface of a paved road bearing E. and W. about 1.00 ch., thence S. This cor. located under a patch in the N. edge of a paved road was pointed out by a resident in the area and verified by ties furnished by the Maricopa County Highway Dept.

From the cor. of secs. 34 and 35, T. 2 N., R. 5 E.

A nail in a large Eucalyptus tree, bears NE., 55.5 lks. dist.

A N-S powerline, bears West, 82.4 lks. dist.

S. 88°16' W., along the N. bdy. of sec. 3.

Over nearly level farm land, along a fence bearing W.

- 8.14 Proportionate point for the meander cor. of sec. 34, T. 2 N., R. 5 E., set on the left bank of the Salt River in 1910. There is no remaining evidence of this cor.; not monumented.
- 8.56 Fence cor.; fence bears N. and E.
- 15.00 Enter gravel pit.
- 17.10 Gravel road, bears S. from pit.

Dependent Resurvey of a Portion of the North Boundary,
Township 1 North, Range 5 East

CHAINS	
18.70	Leave gravel pit.
19.23	Point for Angle Point No. 53, on the South Boundary of the Salt River Indian Reservation, hereinafter described.
19.83	Proportionate point for the meander cor. of sec. 34, T. 2 N., R. 5 E., set on the East shore of an island during the 1910 survey; there is no remaining evidence of this cor.; not monumented.
20.55	Graded road, bears N. and S.; thence, along remnants of a fence bearing W.
38.56	The $\frac{1}{4}$ sec. cor. of sec. 34, T. 2 N., R. 5 E., bears South 04 lks. dist., monumented by a 3 in. open pipe, firmly set, projecting 2 ft. above ground, with $\frac{1}{4}$ Sec. 34 painted on S. side. The cor. is located in an E-W fence line; not remonumented.
38.94	Fence cor.; fence bears S. and E.
39.00	Telephone line, bears N. and S.
39.30	Graded road, bears N. and S.
39.84	N. end of fence bearing S.
40.52	Point for the $\frac{1}{4}$ sec. cor. of sec. 3 at proportionate dist.; there is no remaining evidence of the original cor.; not remonumented. This cor. was not found or re-established during the 1910 resurvey.
59.96	N. end of fence bearing S.
62.70	Enter Salt River bottom, bears N. 30° E. and S. 30° W.
68.47	Proportionate point for the meander cor. of sec. 34, T. 2 N., R. 5 E., set on the west shore of an island in 1910. There is no remaining evidence of this cor.; not monumented.
	Continue over Salt River bottom, drains S. 30° W.
78.51	The cor. of secs. 33 and 34, T. 2 N., R. 5 E., monumented by a 3 in. open pipe, firmly set, projecting 18 ins. above ground; not remonumented.
80.43	Proportionate point for the meander cor. of sec. 33, T. 2 N., R. 5 E., set on the right bank of the Salt River in 1910. There is no remaining evidence of this cor.; not monumented.
81.04	The cor. of secs. 3 and 4 on the N. bdy. of the Tp., monumented by a wooden stake, 2 ins. square, 16 ins. long, harmoniously related to existing corners and locally accepted. I accept this as the best remaining evidence of the original cor. position.
	At the cor. point

Dependent Resurvey of a Portion of the North Boundary,
Township 1 North, Range 5 East

CHAINS	
	<p>Set the iron post 24 ins. in the ground and in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T2N R5E S33 S 4 S 3 T1N R5E 1962</p> <p>Set the wooden stake alongside the iron post.</p> <p>Note: The N. bdy. of sec. 3 was resurveyed in 1972 and the cor. of secs. 3 and 4 was found in good condition as set in 1962.</p> <p>No 1/16 sec. cors. as set by Farmer in 1910, along the S. bdy. of sec. 34, were found.</p> <p>Land, nearly level to gravelly river bottom. Soil, sandy gravel loam. No timber; undergrowth, creosote and sage brush.</p> <hr/> <p>S. 88°18' W., along the N. bdy. of sec. 4.</p> <p>Ascend 10 ft. over Salt River bank facing SE.</p>
.50	Top of bank, thence over nearly level land.
17.47	The E. 1/16th sec. cor. of sec. 33, T. 2 N., R. 5 E., monumented by an iron post 1 in. diam., projecting 6 ins. above ground and in a mound of stone, mkd. No. 1 1/16 S33 1910.
20.00	Bee Line Highway bears N. 30° W. circling to NE., and S. 30° E.; about 1.00 ch. to junction with N. Country Club Drive.
21.60	Enter McDowell Road, bears S. 88°18' W. and SE. on curve.
37.47	The 1/2 sec. cor. of sec. 33, T. 2 N., R. 5 E., monumented by an iron pin in an iron receptacle in the center of McDowell Road.
39.97	The N. 1/2 sec. cor. of sec. 4, monumented by an iron pin in an iron receptacle in the center of McDowell Road.
	<hr/> <p>S. 88°18' W., along the N. bdy. of sec. 4, beginning new measurement.</p> <p>Continue along the center of McDowell Road.</p>
17.50	Proportionate point for the W. 1/16th sec. cor. of sec. 33, falls in the center of McDowell Road and was not located or remonumented.
37.50	The cor. of secs. 32 and 33, on the S. bdy. of T. 2 N., R. 5 E., monumented by an iron pin in an iron receptacle in the center of McDowell Road.

Dependent Resurvey of a Portion of the North Boundary,
Township 1 North, Range 5 East

CHAINS						
40.02	<p>The cor. of secs. 4 and 5, T. 1 N., R. 5 E., monumented by an iron pin in an iron receptacle in the center of McDowell Road.</p> <p>Land, nearly level. Soil, sandy. No timber.</p>					
<p>DEPENDENT RESURVEY OF A PORTION OF THE WEST BOUNDARY, TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM., ARIZONA</p>						
<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p>						
	<p>The cor. of secs. 1, 6, 7 and 12, monumented by an iron post, 36 ins. long, 1 in. diam., set 4 ins. below the surface of the road; the brass cap was broken off and found in the hole alongside the iron post.</p> <p>At the cor. point</p> <p>Set the iron post 8 ins. below the surface of the road, brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr><td>T1N</td></tr> <tr><td>R4E R5E</td></tr> <tr><td>S 1 S 6</td></tr> <tr><td>S12 S 7</td></tr> <tr><td>1962</td></tr> </table> </div> <p>from which</p> <p>An Army Map Service brass cap set in concrete, bears N. 77° E., 103.5 lks. dist.</p> <p>A "X" cut in concrete headwall, bears S. 34° 30' E., 79 lks. dist.</p> <p>A "X" cut in concrete headwall of irrigation ditch, bears S. 47°08' W., 94.5 lks. dist.</p> <p>A fence corner post, bears N. 3°05' E., 104 lks. dist.</p> <p>Bury the original 1 in. iron post alongside the cor.</p> <p>Note: This cor. was checked in 1972 and found to be an unmarked brass cap set in a receptacle in the center of McKellips Road, bearing E. & W.</p> <p>S. 0°23' W., bet. secs. 7 and 12.</p> <p>Over nearly level land, down dirt road bearing S.</p>	T1N	R4E R5E	S 1 S 6	S12 S 7	1962
T1N						
R4E R5E						
S 1 S 6						
S12 S 7						
1962						
.70	<p>Irrigation ditch, bears E. and W., continue down dirt road bearing S.</p>					
20.00	<p>Record course and dist. for the N. 1/16 sec. cor. of secs. 7 and 12. Unable to locate any evidence of the original cor.</p>					

Dependent Resurvey of a Portion of the West Boundary,
Township 1 North, Range 5 East

CHAINS

At the cor. point

Set the iron post 18 ins. below the surface of the road,
brass cap mkd.

N 1/16
S12 | S 7
1962

from which

An iron post, 30 ins. long, 2½ ins. diam., set
20 ins. in the ground for a reference monument,
bears S. 45° W., 78 lks. dist., brass cap mkd.

T1N R4E
N 1/16 S 12
RM →
51.5 ft.
1962

An iron post, 30 ins. long, 2½ ins. diam., set
20 ins. in the ground for a reference monument,
bears N. 45° W., 78 lks. dist., brass cap mkd.

T1N R4E
N 1/16 S 12
RM →
51.5 ft.
1962

40.00

Record course and dist., for the ¼ sec. cor. of secs. 7
and 12. Unable to locate any remaining evidence of the
original cor.

At the cor. point

Set the iron post 18 ins. below the surface of the road,
brass cap mkd.

T1N
R4E R5E
¼
S12 | S 7
1962

from which


An iron post, 30 ins. long, 2½ ins. diam., set
20 ins. in the ground for a reference monument,
bears S. 45° W., 78 lks. dist., brass cap mkd.

T1N R4E
¼
S 12
RM →
51.5 ft.
1962

Dependent Resurvey of a Portion of the West Boundary,
Township 1 North, Range 5 East

CHAINS

An iron post, 30 ins. long, 2½ ins. diam., set
20 ins. in the ground for a reference monument,
bears N. 45° W., 78 lks. dist., brass cap mkd.




In 1931 F. E. Joy retraced from the cor. of secs. 13, 18,
19 and 24 to the ¼ sec. cor. of secs. 7 and 12. He did
not reestablish the S 1/16 sec. cor. or the meander cor.
of secs. 7 and 12. Since Farmer's survey in 1910, estab-
lishing these cors. was not correlated with corners south
of the Salt River, the 1910 record was used in determin-
ing the position of these lost corners.

60.00

Record course and dist. for the S. 1/16th sec. cor. of
secs. 7 and 12. Unable to locate any remaining evidence
of the original cor.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.



Set a redwood post, 4 ins. square, 5 ft. long, 24 ins.
in the ground alongside the iron post.

End of dirt road, bears N.

60.60

Fence, bears E. and W.

62.00


Enter Salt River bottom.

62.88

Record course and dist. for the meander cor. of secs. 7
and 12. Unable to locate any evidence of the original
cor.

At the cor. point

Set the iron post 25 ins. in the ground, brass cap mkd.



Reestablishment of the Survey executed by
W. F. Ingalls in 1868 and retraced by F. E.
Joy in 1931

From the meander cor. of secs. 7 and 12.

S. 0°34' E., bet. secs. 7 and 12, beginning new measure-
ment.

Continue over Salt River bottom, through scattered
tamarisk.

Dependent Resurvey of a Portion of the West Boundary,
Township 1 North, Range 5 East

CHAINS

7.235 Point for the S-S 1/64th sec. cor. of secs. 7 and 12.
Set the iron post 24 ins. in the ground, brass cap mkd.

T1N
R4E R5E
S-S 1/64
S12 | S 7
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground, alongside the iron post.

17.35 The cor. of secs. 7, 12, 13 and 18, monumented by two 3/4 in. iron pipes set in a mound of stone, accepted locally and is the best remaining evidence of the original cor. position.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N
R4E R5E
S12 | S 7
S13 | S18
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the cor.

Bury the iron pipes alongside the cor.

from which

USC&GS triangulation station, TEMPE BUTTE AIRWAY BEACON, bears S. 76°58'31" W., 202.72 chs. dist.; Lat., 33°25'41.532" N.; Long., 111°56'06.364" W.

Note: This sec. corner was destroyed during the 1965-66 floods. This cor. was needed for control of the survey of the South Boundary of the Salt River Indian Reservation and was reestablished in 1972 by using the 1962 survey data from the North and East.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N
R4E R5E
S12 | S 7
S13 | S18
1972

Raise a mound of stone W. of the cor.

Land, nearly level.

Soil, heavy clay loam on N. 60.00 chs., sand and gravel on remainder in river bottom.

Timber, scattered palo verde and salt cedar.

Dependent Resurvey of a Portion of the West Boundary,
Township 1 North, Range 5 East

CHAINS	
	S. 1°42' E., bet. secs. 13 and 18. Over rocky Salt River bottom, draining W.
6.91	Point for Angle Point No. 1 on the South Boundary of the Salt River Indian Reservation, hereinafter described.
12.70	Leave Salt River bottom, bears E. and W., thence through farm land.
41.16	The ½ sec. cor. of secs. 13 and 18, monumented by a re-bar pointed out by a local surveyor and verified by a tie furnished by the Photogrammetry Division of the Arizona Highway Dept. from which A fence cor. bears West 02 lks. dist.; fence bears N., S. and W. <hr/> S. 0°50' W., beginning new measurement. Continue through fenced farm land.
39.91	The cor. of secs. 13, 18, 19 and 24, monumented by a blank brass cap set in a receptacle at the intersection of University Drive, bearing E. and W., and Price Road bearing S. Land, river bottom on N. 14.00 chs., farm land on remainder. Soil, rocky sandy loam in river bottom, sandy clay loam on remainder. No timber; Undergrowth, grass, alfalfa-brush along fence lines.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES
TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM., ARIZONA

Reestablishment of the Survey executed
by W. F. Ingalls in 1868

The cor. of secs. 8, 9, 16 and 17, monumented by a Bureau of Reclamation iron post, 1 in. diam.; firmly set, projecting 4 ins. above the ground, properly mkd., is locally accepted by property owners and the Dept. of Public Works, Mesa, Arizona and is accepted as the best remaining evidence of the original cor. position.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
S 8 | S 9
S17 | S16
1962

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
	<p>Set a redwood post, 4 ins. square, 5 ft. long, 24 ins. in the ground, alongside the cor.</p>	
	<p>Invert and set the Reclamation iron post alongside the cor.</p>	
	<p>Note: This cor. was checked in 1972 and found to be an unmarked brass cap in a receptacle in the center of Alma School Road.</p>	
	<p>N. 0°27' W., bet. secs. 8 and 9.</p>	
	<p>Along Alma School Road.</p>	
<p>17.00</p>	<p>Telephone line, bears N. 1° E. and S. 1° W.</p>	
<p>40.32</p>	<p>The 1/2 sec. cor. of secs. 8 and 9, monumented by a 3/4 in. iron pipe, set 8 ins. below the surface of the roadway. This cor. was pointed out by Mr. Beals, an adjacent property owner and is also accepted by the Dept. of Public Works at Mesa, Ariz.</p>	
	<p>At the cor. point</p>	
	<p>Set the iron post 15 ins. below the surface of the road, brass cap mkd.</p>	
	<p style="text-align: center;">T1N R5E 1/2 S 8 S 9 1962</p>	
	<p>from which</p>	
	<p>An "X" cut in concrete headwall, bears N. 61°52' E., 36.8 lks. dist.</p>	
	<p>A railroad spike on fence cor. brace, bears S. 47° 18' W., 38.4 lks. dist.</p>	
	<p>An "X" cut in concrete headwall, bears N. 41°27' W., 23.1 lks. dist.</p>	
	<p>Bury the iron pipe alongside the cor.</p>	
	<p>Note: This cor. was checked in 1972 and found to be an unmarked brass cap in a receptacle at the intersection of McLellan Road bearing E. and Alma School Road bearing N. and S.</p>	
	<p>N. 0°27' W., bet. secs. 8 and 9, beginning new measurement.</p>	
	<p>Along Alma School Road bearing generally N. and S. (unpaved in 1962).</p>	
<p>20.26</p>	<p>Point for the N. 1/16th sec. cor. of secs. 8 and 9.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
N 1/16
S 8 | S 9
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.

Cor. is located on E. side of Alma School Road bearing irregularly N. and S. (Enter Salt River bottom).

30.39 Point for the N-N 1/64 sec. cor. of secs. 8 and 9.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
N-N 1/64
S 8 | S 9
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.

40.52 Point for the cor. of secs. 4, 5, 8 and 9, established latitudinally on line bet. the $\frac{1}{4}$ sec. cor. of secs. 4 and 9, and the $\frac{1}{4}$ sec. cor. of secs. 5 and 8., and determined longitudinally by projecting line from the cor. of secs. 8, 9, 16 and 17, through the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.

At the cor. point

Set the iron post 8 ins. below the surface of a dirt road, brass cap mkd.

T1N R5E
S 5 | S 4
S 8 | S 9
1962

from which

An Army Map Service brass cap set in concrete, bears N. $4^{\circ}45'$ E., 372.5 lks. dist.

A fence post, bears S. $20^{\circ}50'$ E., 93 lks. dist.

A redwood post, 4 ins. square, 5 ft. long, set 24 ins. in the ground, mkd. RM, bears SW., 91 lks. dist.

Land; nearly level.
Soil, clay loam on S. 60.00 chains, gravel on remainder.
No timber; Farmland on W. side of road on S. 60 chs.

Reestablishment of the Survey
executed by R. A. Farmer in 1910

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
	<p>From the cor. of secs. 3 and 4 on the N. bdy. of the Tp. S. 0°23' W., bet. secs. 3 and 4. Over nearly level Salt River bottom through heavy salt cedar.</p>	
1.40	<p>Record course and dist. for the meander cor. of secs. 3 and 4. Unable to locate any evidence of the original cor.</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p>T1N R5E S 4 S 3 <hr style="width: 50px; margin: 0 auto;"/>MC 1962</p>	
	<p>Reestablishment of the Survey executed by W. F. Ingalls in 1868</p> <hr style="width: 50%; margin: 0 auto;"/>	
	<p>From the meander cor. of secs. 3 and 4.</p>	
	<p>S. 1°04' E., beginning new measurement.</p>	
	<p>Continue over Salt River bottom through scattered salt cedar.</p>	
18.20	<p>East edge of pavement on N. Country Club Drive, bears S. and N. circling to NW.</p>	
20.50	<p>West edge of pavement on N. Country Club Drive.</p>	
37.00	<p>Leave Salt River bottom; continue along W. side of N. Country Club Drive.</p>	
39.90	<p>The ¼ sec. cor. of secs. 3 and 4, monumented by an iron pin, 1 in. diam., set flush with the ground and in a mound of stone. This cor. is locally accepted and is the best remaining evidence of the original cor. position.</p>	
	<p>At the cor. point</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p>T1N R5E ¼ S 4 S 3 1962</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, West of the cor.</p>	
	<p>Bury the iron pin alongside the cor.</p>	
	<p>Note: A check in 1972 failed to reveal any evidence of this cor. The point is marked by a wooden hub - paneled for aerial photography.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS	
	<p>S. 0°08' E., bet. secs. 3 and 4, beginning new measurement.</p>
	<p>Over nearly level land.</p>
25.00	<p>West edge of pavement on N. Country Club Drive.</p>
39.98	<p>The cor. of secs. 3, 4, 9 and 10, monumented by an iron pin set in a receptacle at intersection of N. Country Club Drive and McKellips Road.</p>
	<p>Land, nearly level. Soil, sandy and gravel on the N. ½ mile, sandy clay loam on S. ½ mile. Timber, heavy salt cedar on N. 2.00 chains, scattered to widely scattered on remainder.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10.</p>
	<p>S. 89°12' W., bet. secs. 4 and 9.</p>
	<p>Along improved dirt road, bearing E. and W. (This road is now paved (McKellips Road) for about the E. 20 chs. where the road curves to the NW.)</p>
38.08	<p>The ¼ sec. cor. of secs. 4 and 9, monumented by an iron pin set in concrete. This cor. is locally accepted by interested land owners and the Dept. of Public Works at Mesa, Ariz.</p>
	<p>At the cor. point</p>
	<p>Set the iron post 4 ins. below the surface of a dirt road, brass cap mkd.</p>
	<p style="text-align: center;">T1N R5E $\frac{1}{4}$ $\frac{S\ 4}{S\ 9}$ 1962</p>
	<p>from which</p>
	<p>An "X" cut in concrete headwall, bears S. 82°32' E., 42 lks. dist.</p>
	<p>A telephone pole, bears S. 33°40' E., 56 lks. dist.</p>
	<p>Deposit the iron pin alongside the cor.</p>
	<p>S. 89°54' W., bet. secs. 4 and 9, beginning new measurement.</p>
	<p>Along dirt road, bearing E. and W.</p>
2.50	<p>Leave road, desc. about 15 ft. over bank of Salt River, facing NW., thence over Salt River bottom.</p>
9.66	<p>Point for the E-W 1/64 sec. cor. of secs. 4 and 9.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 4 E-W 1/64 S 9 1962</p> <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post</p> <p>Note: A check in 1972 revealed this cor. was destroyed by the 1965-66 floods.</p>	
19.32	<p>Point for the W. 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 4 W 1/16 S 9 1962</p> <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p>	
28.98	<p>Point for the W-W 1/64 sec. cor. of secs. 4 and 9.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">S 4 W-W 1/64 S 9 1962</p> <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p>	
38.64	<p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, nearly level on E. 1/2 mile, bottom of Salt River on W. 1/2 mile. Soil, heavy clay loam on E. 1/2 mile, rocky and sandy on W. 1/2 mile. Timber, deciduous and evergreens bordering roadway on E. 1/2 mile, salt cedar on W. 1/2 mile.</p>	
	<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p> <hr/> <p>From the cor. of secs. 4 and 5 on the N. bdy. of the Tp. S. 0°23' W., bet. secs. 4 and 5.</p> <p>Along improved dirt road bearing S. (Alma School Road, now paved).</p>	
19.81	<p>Proportionate dist. for the N. 1/16 sec. cor. of secs. 4 and 5. Unable to locate any evidence of the original cor.; not monumented.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS

39.65 The 1/2 sec. cor. of secs. 4 and 5, monumented by a regulation iron post, 1 in. diam., filled with concrete, set 10 ins. below the surface of the road. The brass cap was missing from this cor. post.

At the cor. point

Set the iron post 8 ins. below the surface of the road, brass cap mkd.

T1N R5E

1/2
S 5 | S 4
1962

from which

Fence cor., bears S. 13°47' E., 93 lks. dist.

Steel rod in NE. cor. of cement head box, bears S. 44°26' W., 72 lks. dist.

Fence cor., bears N. 75°25' W., 48 lks. dist.

Bury the original iron post alongside the cor.

S. 0°23' W., bet. secs. 4 and 5, beginning new measurement.

Continue along Alma School Road, bearing N. and S.

20.01 The S. 1/16 sec. cor. of secs. 4 and 5, monumented by a 1 in. iron rod in a small mound of stone. Accepted as the best remaining evidence of the original cor. position.

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E

S 1/16
S 5 | S 4
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.

Bury the iron rod alongside the cor.

21.40 Record course and dist. for the meander cor. of secs. 4 and 5. Unable to locate any evidence of the original cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E

S 5 | S 4

M C
1962

Raise a mound of stone, 3 ft. base, 2 ft. high, North of the cor.

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS	
	<p>Deposit glass in the hole alongside the iron post.</p> <hr/> <p>Reestablishment of the Survey executed by W. F. Ingalls in 1868.</p> <hr/> <p>From the meander cor. of secs. 4 and 5. S. 13°29' E., beginning new measurement. Over Salt River bottom.</p>
8.82	<p>Point for the S-S 1/64 sec. cor. of secs. 4 and 5. Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R5E S-S 1/64 S 5 S 4 1962</p> <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground, alongside the iron post.</p>
19.07	<p>The cor. of secs. 4, 5, 8 and 9. Land, nearly level roadway on N. 61.00 chs., rolling bottom of Salt River on remainder. Soil, clay loam on N. 61.00 chs., gravel and sand on remainder. Timber, scattered cottonwoods and willows along roadway on N. 61.00 chs., scattered salt cedar on remainder.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20, monumented by a brass cap set in an iron receptacle in the NE. part of the pavement at the intersection of Dobson Road and University Drive. N. 0°37' E., bet. secs. 17 and 18. Along the West side of Dobson Road.</p>
11.50	<p>End Dobson Road; graded dirt road, along S. side of Tempe Canal, bears N. 65° E., and S. 65° W.</p>
12.40	<p>Center of Tempe Canal parallels road, continue over cultivated farm land.</p>
39.60	<p>Irrigation ditch, 10 lks. wide, 3 ft. deep, bears E. and W.</p>
40.00	<p>Graded dirt road, bears E. and W.</p>
40.29	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented by a 3/4 in. iron rod, set in fence line, bearing E. and W. This cor. has long been used by adjacent land owners and is accepted as the best remaining evidence of the original cor. position.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS

At the cor. point

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
 $\frac{1}{2}$
S18 | S17
1962

Bury the iron rod alongside the cor.

N. 1°01' E., bet. secs. 17 and 18, beginning new measurement.

Over cultivated farm land.

35.30 Leave cultivated fields.

35.60 Dirt road, bears irregularly N. 70° E. and W.

35.87 Fence, 4 strand barb wire, parallels road, enter Salt River bottom, through dense salt cedars.

39.30 Leave salt cedars bearing N. 70° E. and S. 70° W.

40.28 Point for the cor. of secs. 7, 8, 17 and 18 at proportionate dist.; there is no remaining evidence of the original cor.

Set the iron post 24 ins. in the ground, and in a collar of stone, brass cap mkd.

T1N R5E
S 7 | S 8
S18 | S17
1962

Note: This sec. cor. was destroyed by the 1965-66 floods. This corner was needed for control of the South Boundary of the Salt River Indian Reservation and was replaced using the 1962 survey data.

Set the iron post 26 ins. in the ground, brass cap mkd.

T1N R5E
S 7 | S 8
S18 | S17
1972

Set a wooden fence post, 4 ins. diam., 5 ft. long, 24 ins. in the ground alongside the iron post.

Land, mostly cultivated farming land.

Soil, clay loam on S. 76.00 chs., sandy and gravel on remainder.

Timber, heavy growth of salt cedar near N. end of mile.

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
	<p>From the cor. of secs. 8, 9, 16 and 17. N. 89°41' W., bet. secs. 8 and 17. Over nearly level land.</p>	
1.00	<p>Fence, barbed wire, bears N. and S., thence over level farm land along the S. edge of ditch bearing E. and W.</p>	
41.40	<p>Proportionate point for the 1/4 sec. cor. of secs. 8 and 17; unable to locate any evidence of the original cor. Set the iron post 24 ins. below the surface of the farm land, brass cap mkd.</p> <p style="text-align: center;"> T1N R5E S 8 1/4 ——— S17 1962 </p> <p>from which</p> <p style="padding-left: 40px;">An "X" cut on S. edge of cement lined irrigation ditch, bears N. 45° E., 10 lks. dist.</p> <p style="padding-left: 40px;">An "X" cut on S. edge of cement lined irrigation ditch, bears N. 45° W., 10 lks. dist.</p> <p>Continue over cultivated farm land.</p>	
62.10	<p>Point for the W. 1/16 sec. cor. of secs. 8 and 17. Set the iron post 24 ins. below the surface of the farm land, brass cap mkd.</p> <p style="text-align: center;"> T1N R5E W 1/16 S 8 ——— S17 1962 </p>	
73.00	<p>Unimproved dirt road, bears N. 70° E. and S. 70° W.</p>	
75.00	<p>Enter Salt River bottom through moderate salt cedar.</p>	
78.00	<p>Leave salt cedars, bearing S. 70° W. and N. 70° E. about 2.00 chs. to end.</p>	
82.80	<p>The cor. of secs. 7, 8, 17 and 18. Land, mostly cultivated farm land. Soil, clay loam on E. 75.00 chs., sandy and gravel on remainder. Timber, moderate salt cedar along edge of Salt River.</p>	
	<p>From the cor. of secs. 7, 8, 17 and 18. N. 89°55' W., bet. secs. 7 and 18. Over Salt River bottom through scattered palo verde and scattered undergrowth.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS	
16.40	Ascend over narrow island bearing E. and W.
20.71	<p>Point for the E. 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 24 ins. in the ground and in a collar of stone, brass cap mkd.</p> $\begin{array}{r} \text{T1N R5E} \\ \text{E } 1/16 \quad \frac{\text{S } 7}{\text{S18}} \\ 1962 \end{array}$ <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p> <p>Continue along N. side of island.</p>
41.42	<p>Proportionate point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 18; unable to locate any evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground and in a collar of stone, brass cap mkd.</p> $\begin{array}{r} \text{T1N R5E} \\ \frac{1}{4} \quad \frac{\text{S } 7}{\text{S18}} \\ 1962 \end{array}$ <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p>
42.00	Leave island, enter Salt River bottom.
51.78	<p>Point for the E-W 1/64 sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> $\begin{array}{r} \text{T1N R5E} \\ \text{E-W } 1/64 \quad \frac{\text{S } 7}{\text{S18}} \\ 1962 \end{array}$ <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p>
62.14	<p>Point for the W. 1/16 sec. cor. of secs. 7 and 18.</p> <p>Set the iron post 24 ins. in the ground and in a collar of stone, brass cap mkd.</p> $\begin{array}{r} \text{T1N R5E} \\ \text{W } 1/16 \quad \frac{\text{S } 7}{\text{S18}} \\ 1962 \end{array}$ <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p>
72.50	Point for the W-W 1/64 sec. cor. of secs. 7 and 18.

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
82.70	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R5E W-W 1/64 $\frac{S 7}{S 18}$ 1962</p> <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p> <p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.</p> <p>Land, slightly broken bottom of the Salt River. Soil, gravel and sand. Timber, widely scattered palo verde. Undergrowth, creosote brush and weeds.</p>	
	<p style="text-align: center;">Reestablishment of the Survey executed by R. A. Farmer in 1910</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8, monumented by an iron post, projecting 6 ins. above ground, brass cap mkd.</p> <p style="text-align: center;">T1N S 6 S 5 S 7 S 8 R5E 1910</p> <p>from which</p> <p style="text-align: center;">Corps of Army Engineers Station, a 3½ in. brass cap set in concrete, bears S. 19°27' W., 39 lks. dist., mkd. TT-X-4 1960 Army Map Service.</p> <p>S. 0°21' W., bet. secs. 7 and 8.</p> <p>Over nearly level land, through scattered grass and weeds.</p> <td> <p>18.10</p> <p>The Witness N. 1/16 sec. cor. of secs. 7 and 8, a 1 in. iron post, projecting 6 ins. above ground, brass cap mkd. No. 6 in N. 1/16 S 7 in W. S 8 in E. W C 1910 in S.</p> <p>Enter Salt River bottom.</p> </td>	<p>18.10</p> <p>The Witness N. 1/16 sec. cor. of secs. 7 and 8, a 1 in. iron post, projecting 6 ins. above ground, brass cap mkd. No. 6 in N. 1/16 S 7 in W. S 8 in E. W C 1910 in S.</p> <p>Enter Salt River bottom.</p>
20.00	<p>True point for the N. 1/16 sec. cor. of secs. 7 and 8., this point was not monumented.</p>	
23.77	<p>Point for the meander cor. of secs. 7 and 8 at record dist.; unable to locate any evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R5E S 7 S 8 M C 1962</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS

Reestablishment of the Survey executed
by W. F. Ingalls in 1868

From the meander cor. of secs. 7 and 8.

S. 2°41' E., beginning new measurement.

Continue over Salt River bottom.

6.28 Point for the S-N 1/64 sec. cor. of secs. 7 and 8.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
S-N $\frac{1}{64}$
S 7 | S 8
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.

16.33 Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8 at proportionate dist., there is no remaining evidence of the original cor.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
 $\frac{1}{4}$
S 7 | S 8
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.

26.41 Point for the N-S 1/64 sec. cor. of secs. 7 and 8.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
N-S $\frac{1}{64}$
S 7 | S 8
1962

Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post

36.49 Point for the S. 1/16 sec. cor. of secs. 7 and 8.

Set the iron post 24 ins. in the ground, brass cap mkd.

T1N R5E
S $\frac{1}{16}$
S 7 | S 8
1962

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS						
56.65	<p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p> <p>Land, slightly broken river bottom on S. 62.00 chs., nearly level sandy land on remainder. Soil, sandy and gravel. Timber, widely scattered palo verde.</p>					
<p>Reestablishment of the survey executed by R. A. Farmer in 1910</p>						
19.99	<p>From the cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.</p> <p>East, bet. secs. 6 and 7.</p> <p>Over nearly level land, along dirt road bearing E. (McKellips Road, now paved).</p> <p>Point for the W. 1/16 sec. cor. of secs. 6 and 7 at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set the iron post 8 ins. below the surface of the road, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R5E</p> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">W 1/16</td> <td style="border-left: 1px solid black; padding-left: 10px; text-align: center;"> $\frac{S\ 6}{S\ 7}$ </td> </tr> <tr> <td></td> <td style="text-align: center;">1962</td> </tr> </table> </div> <p>from which</p> <p>An "X" cut in the headwall of a concrete lined ditch, bears S. 45° E., 82 lks. dist.</p> <p>An "X" cut in the headwall of a concrete lined ditch, bears S. 45° W., 82 lks. dist.</p>	W 1/16	$\frac{S\ 6}{S\ 7}$		1962	
W 1/16	$\frac{S\ 6}{S\ 7}$					
	1962					
39.98	<p>The 1/4 sec. cor. of secs. 6 and 7, monumented by a G.L.O. iron post, 1 in. diam., firmly set but badly deteriorated.</p> <p>At the cor. point</p> <p>Set the iron post 14 ins. below the surface of the road, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R5E</p> <table style="margin: auto;"> <tr> <td style="padding-right: 10px;">1/4</td> <td style="border-left: 1px solid black; padding-left: 10px; text-align: center;"> $\frac{S\ 6}{S\ 7}$ </td> </tr> <tr> <td></td> <td style="text-align: center;">1962</td> </tr> </table> </div> <p>from which</p> <p>An "X" cut in a cement headwall, bears S. 72°15' W., 65 lks. dist.</p> <p>The most southerly post in a N-S fence line, bears N. 70°40' W., 51.5 lks. dist.</p>	1/4	$\frac{S\ 6}{S\ 7}$		1962	
1/4	$\frac{S\ 6}{S\ 7}$					
	1962					

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS	
	<p>Bury the original iron post alongside the cor.</p> <p>The cor. is located at intersection of dirt road bearing W. and along the E. side of a dirt road bearing N. and S. (McKellips Road bearing W., now paved).</p> <hr/> <p>East, bet. secs. 6 and 7, beginning new measurement.</p> <p>Over cultivated land.</p>
19.99	Point for the E. 1/16 sec. cor. of secs. 6 and 7 at proportionate dist. falls in cotton field; there is no remaining evidence of the original cor.; not monumented.
26.30	Leave cultivated land, bears NE. and SW.; enter nearly level sandy land.
39.58	Fence, bears N. and S. for about 10 lks., thence SW.
39.98	The cor. of secs. 5, 6, 7, and 8.
	<p>Land, nearly level.</p> <p>Soil, clay loam on W. 66.00 chs., sandy on remainder.</p> <p>No timber; undergrowth, cotton on cultivated land, weeds and sparse grass on remainder.</p> <hr/> <p>From the cor. of secs. 5, 6, 7 and 8.</p> <p>East, bet. secs. 5 and 8.</p> <p>Over nearly level sandy land.</p>
1.30	Dirt road, bears N. 70° E., and S. 70° W.
5.30	Old dirt road, bears N. 70° E. and S. 70° W.
6.90	Dim road, bears S. 70° E. and N. 70° W.
20.015	The W. 1/16 sec. cor. of secs. 5 and 8, monumented by an iron post 1 in. diam., projecting 4 ins. above ground, mkd. No. 2 1/16 S 5 in N. S 8 1910 in S.
40.03	The 1/4 sec. cor. of secs. 5 and 8, monumented by a steel rod, 1/2 in. diam., firmly set among old lath and wooden hubs. This is accepted as the best remaining evidence of the original cor. position.
	<p>At the cor. point</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R5E</p> <p>1/4 $\frac{S 5}{S 8}$</p> <p>1962</p> </div> <p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p> <p>Bury the steel rod alongside the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
59.03	<p>The cor. is located on the West side of a dirt road bearing N. and S.</p> <p>Record course and dist. for the meander cor. of secs. 5 and 8. Unable to locate any remaining evidence of the original cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	$\begin{array}{r} \text{T1N R5E} \\ \hline \text{S } 5 \\ \text{S } 8 \\ \hline 1962 \end{array} \text{ MC}$	
	<hr/> <p>Reestablishment of the Survey executed by W. F. Ingalls in 1868</p> <hr/>	
	<p>From the meander cor. of secs. 5 and 8.</p> <p>N. 89°54' E., beginning new measurement.</p> <p>Continue over Salt River bottom.</p>	
3.29	<p>Point for the E. 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	$\begin{array}{r} \text{E } 1 \text{ S } 5 \\ \hline 16 \text{ S } 8 \\ \hline 1962 \end{array}$	
14.435	<p>Set a redwood post, painted red, 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 5 and 8.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	$\begin{array}{r} \text{E-E } 1 \text{ S } 5 \\ \hline 64 \text{ S } 8 \\ \hline 1962 \end{array}$	
25.58	<p>Set a redwood post, painted red; 4 ins. square, 5 ft. long, 24 ins. in the ground alongside the iron post.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, slightly broken river bottom.</p> <p>Soil, sandy and gravel.</p> <p>Timber, widely scattered palo verde.</p>	
	<hr/> <p>RETRACEMENT OF A PORTION OF THE SUBDIVISIONAL LINES, TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM., ARIZONA</p> <hr/>	
	<p>Retracement of the Survey executed by W. F. Ingalls in 1868</p> <hr/>	

Retracement of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS

For Informational Purposes Only.

From the cor. of secs. 2 and 3 on the N. bdy. of the Tp.

S. 0°04' W., bet. secs. 2 and 3.

Along W. side of oiled road bearing S.

42.20

The $\frac{1}{2}$ sec. cor. of secs. 2 and 3, reportedly monumented by a $\frac{3}{4}$ in. iron post set .3 ft. below the surface of a paved road bearing N. and S. (N. Mesa Drive), and verified by ties provided by the Maricopa County Highway Dept.

from which

SSE. to X in W. end of Wier Box, 132.2 lks. dist.

South to line of poles to the East, 24.2 lks. dist.

East to a fence line to the North, 55.8 lks. dist.

S. 0°04' W., bet. secs. 2 and 3, beginning new measurement.

Along N. Mesa Drive.

.60

Intersection of N. Mesa Drive and Lehi Road.

41.31

The cor. of sec's. 2, 3, 10 and 11, monumented by a blank cap set in a receptacle at the intersection of McKellips Road and N. Mesa Drive.

From the cor. of secs. 2, 3, 10 and 11.

S. 89°50' W., bet. secs. 3 and 10.

Along the center of McKellips Road.

40.06

The $\frac{1}{2}$ sec. cor. of secs. 3 and 10, monumented by a blank cap in a receptacle at the intersection of McKellips Road and N. Center.

S. 89°50' W., bet. secs. 3 and 10, beginning new measurement.

Along the center of McKellips Road.

40.00

The cor. of secs. 3, 4, 9 and 10.

From the $\frac{1}{2}$ sec. cor. of secs. 9 and 10, monumented by a blank cap set in a receptacle at the intersection of N. Country Club Drive and McLellan Road.

N. 0°24' E., bet. secs. 9 and 10.

Along N. Country Club Drive.

Retracement of a Portion of the Subdivisional Lines
Township 1 North, Range 5 East

CHAINS		
40.08	The cor. of secs. 3, 4, 9 and 10.	
	From the cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp.	
	N. 89°41' E., bet. secs. 18 and 19.	
	Along the center of University Drive.	
41.06	The ¼ sec. cor. of secs. 18 and 19, monumented by a blank cap in a receptacle at the intersection of paved University Drive and Evergreen Road, which is a dirt road bearing S.	
	N. 89°41' E., bet. secs. 18 and 19, beginning new measurement.	
	Along the center of University Drive.	
39.94	The cor. of secs. 17, 18, 19 and 20.	
	<p>SURVEY OF A PORTION OF THE SUBDIVISION OF SECTION 9, TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM., ARIZONA</p>	
	For Informational Purposes Only.	
	From the ¼ sec. cor. of secs. 9 and 10.	
	S. 89°12' W., along the E-W centerline of sec. 9.	
	Along the center of McLellan Road.	
38.04	The center ¼ sec. cor. of sec. 9, monumented by a blank cap in a receptacle in the center of McLellan Road.	
	S. 89°12' W., along the E-W centerline of sec. 9, beginning new measurement.	
	Along the center of McLellan Road.	
38.05	The ¼ sec. cor. of secs. 8 and 9.	
	<p>SURVEY OF PARTIAL SUBDIVISION, SECTIONS 4, 7 AND 8 TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM., ARIZONA</p>	
	<p>Subdivision, Section 4</p>	
	<p>Reestablishment of the Survey executed by R. A. Farmer in 1910.</p>	
	From the ¼ sec. cor. of secs. 4 and 5.	

Survey of Partial Subdivision, Section 4
Township 1 North, Range 5 East

CHAINS	
	N. 89°57' E. on the E-W centerline of sec. 4. Over nearly level land.
.22	Fence, bears N. and S., enter cultivated land.
4.55	Leave cultivated land.
20.06	The C-W 1/16 sec. cor. of sec. 4, monumented by an iron post 1 in. diam., projecting 8 ins. above ground, brass cap mkd. No. 8 in N. 1/16 S4 in center 1910 in S.
	—————
	N. 89°57' E., beginning new measurement. Continue over nearly level land.
15.56	Record distance for the meander corner set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor. Set the iron post 24 ins. in the ground, brass cap mkd. T1N R5E S 4 MC 1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor. N. 89°57' E., continuing measurement with original survey.
20.14	Point for the center 1/4 sec. cor. of sec. 4 at intersection with line from the N. Set the iron post 20 ins. in the ground, brass cap mkd. T1N R5E C 1/4 S 4 1962
	Set a redwood post 5 ft. long, 4 ins. square, alongside the cor. The E. 1/2 of the E-W centerline of sec. 4 was not surveyed.
	—————
	Reestablishment of the Survey executed by R. A. Farmer in 1910
	—————
	From the 1/4 sec. cor. of sec. 4 on the N. bdy. of the Tp. S. 0°08' W., on the N-S centerline of sec. 4.

Survey of Partial Subdivision, Section 4
Township 1 North, Range 5 East

CHAINS	
	<p>Over S. lane of McDowell Road, continuing over nearly level land.</p>
20.70	<p>The C-N 1/16 sec. cor. of sec. 4, monumented by an unmarked GLO iron post, 1 in. diam., set 4 ins. below the surface. The iron post was badly bent. This post was probably set by R. A. Farmer in 1910.</p> <p>At the cor. point</p> <p>Set the iron post 6 ins. below the surface, brass cap mkd.</p> <p style="text-align: center;">T1N R5E C-N 1/16 S 4 1962</p> <p>from which</p> <p style="padding-left: 40px;">A nail in a corner fence post, bears S. 86° 52' E., 37.6 lks. dist.</p> <p style="padding-left: 40px;">An "X" cut in concrete headwall, bears S. 66° 03' W., 48 lks. dist.</p> <p>Bury the original iron post alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0°08' W., beginning new measurement.</p>
17.92	<p>Record distance for the meander cor. set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R5E S 4 MC 1962</p> <p>S. 0°08' W., continuing measurement with original survey.</p>
20.00	<p>The center ¼ sec. cor. of sec. 4.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 3°57' E., on original survey, beginning new measurement.</p> <p>Over Salt River bottom.</p>
20.02	<p>Point for the C-S 1/16 sec. cor. of sec. 4.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S 1/16 S 4 1962</p>

Survey of Partial Subdivision, Section 4
Township 1 North, Range 5 East

CHAINS	
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
30.03	Point for the C-S-S 1/64 sec. cor. of sec. 4.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">C-S-S 1/64 S 4 1962</p>
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
39.00	Leave Salt River bottom, asc. over river bank about 30 ft. high, facing NW.
40.04	The 1/2 sec. cor. of secs. 4 and 9.
	<p>Land, nearly level on N 1/2 mile, river bottom S 1/2 mile. Soil, sandy clay loam N 1/2 mile, rocky & sandy on S 1/2 mile. No timber; undergrowth, sagebrush and creosote brush.</p>
Subdivision, SW 1/4 Section 4	
Reestablishment of the Survey executed by R. A. Farmer in 1910	
	From the C-W 1/16 sec. cor. of sec. 4.
	S. 0°23' W., on the N-S centerline of the SW 1/4 of sec. 4.
	Over nearly level land.
1.60	Fence, bears E. and W.
1.80	Unimproved road, bears E. and W.; continue over sandy Salt River bottom.
15.92	Record bearing and distance for the meander cor. set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T1N R5E S 4 MC 1962</p>
	S. 8°43' E., on original survey, beginning new measurement.
4.10	Point for the SW 1/16 sec. cor. of sec. 4 at intersection with the E-W centerline of the SW 1/4 of sec. 4.

Survey of Partial Subdivision, Section 4
Township 1 North, Range 5 East

CHAINS		
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 4 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
14.20	<p>Point for the C-S-SW 1/64 sec. cor. of sec. 4.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">1/64 C-S-SW S 4 1962</p>	
24.30	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p> <p>The W 1/16 sec. cor. of secs. 4 and 9.</p> <p>Land, mostly sandy river bottom. Soil, sandy & gravel. No timber; undergrowth, weeds, creosote brush and sagebrush.</p>	
<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p> <hr/>		
3.70	<p>From the S 1/16 sec. cor. of secs. 4 and 5.</p> <p>East, on the E-W center line of the SW$\frac{1}{2}$ of sec. 4.</p> <p>Over nearly level land.</p> <p>Record bearing and distance for the meander cor. of sec. 4, set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor.</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T1N R5E S 4 <hr style="width: 50px; margin: 0 auto;"/>MC 1962</p>	
16.98	<p>N. 89°54' E., on original survey, beginning new measurement.</p> <p>Over Salt River bottom.</p> <p>The SW 1/16 sec. cor. of sec. 4.</p>	

Survey of Partial Subdivision, Section 4
Township 1 North, Range 5 East

CHAINS	
27.47	<p>Point for the C-E-SW 1/64 sec. cor. of sec. 4.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-E-SW 1/64 S 4 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
37.96	<p>The C-S 1/16 sec. cor. of sec. 4.</p> <p>Land, mostly bottom land of the Salt River. Soil, sandy & rocky. No timber; undergrowth, creosote brush, weeds and sagebrush.</p> <hr/> <p>From the S-S 1/64 sec. cor. of secs. 4 and 5.</p> <p>N. 89°53' E. on the E-W center line of the SW$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 4.</p> <p>Over Salt River bottom.</p>
10.08	<p>Point for the SW-SW 1/64 sec. cor. of sec. 4.</p> <p>Set the iron post .25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW-SW 1/64 S 4 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.16	<p>The C-S-SW 1/64 sec. cor. of sec. 4.</p> <hr/> <p>N. 89°53' E., on the E-W centerline of the SE$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 4, beginning new measurement.</p>
10.08	<p>Point for the SE-SW 1/64 sec. cor. of sec. 4.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SE-SW 1/64 S 4 1962</p>
20.16	<p>The C-S-S 1/64 sec. cor. of sec. 4.</p>
<p>Subdivision, Section 7</p>	
<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p>	

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS	
	From the $\frac{1}{4}$ sec. cor. of secs. 7 and 12 on the W. bdy. of the Tp.
	S. $89^{\circ}59'$ E., on the E-W centerline of sec. 7.
.50	Enter cultivated land.
19.97	Point for the C-W $\frac{1}{16}$ sec. cor. of sec. 7 at proportionate dist.; there is no remaining evidence of the original cor.
	Set the iron post 15 ins. below the surface of a cultivated field, brass cap mkd.
24.20	Irrigation ditch, drains S.
24.40	Unimproved farm road, bears N. and S.
30.00	Leave cultivated land, bears N. and S.
30.20	Dirt road, bears N. & S.
30.30	Fence, bears N. and S.
35.00	Fence, bears N. 26° E. and S. 26° W.
38.10	Dirt road, bears N. 30° E. and S. 30° W.
39.94	The center $\frac{1}{4}$ sec. cor. and meander cor. of sec. 7 set on the right bank of the Salt River in 1910, monumented by an iron post, 1 in. diam., badly corroded, firmly set, projecting 4 ins. above ground, brass cap mkd.
	At the cor. point.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
	Bury the original cor. alongside the iron post.
	<hr style="width: 20%; margin: 0 auto;"/>
	S. $89^{\circ}54'$ E., on original survey, beginning new measurement.

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS	
	Over nearly level land, through sandy Salt River bottom.
10.23	Point for the C-W-E 1/64 sec. cor. of sec. 7. Set the iron post 22 ins. in the ground, brass cap mkd. C-W-E 1/64 S 7 1962 Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
20.46	Point for the C-E 1/16 sec. cor. of sec. 7. Set the iron post 25 ins. in the ground, brass cap mkd. C-E 1/16 S 7 1962 Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
30.69	Point for the C-E-E 1/64 sec. cor. of sec. 7. Set the iron post 24 ins. in the ground, brass cap mkd. C-E-E 1/64 S 7 1962 Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
40.92	The 1/4 sec. cor. of secs. 7 and 8. Land, slightly rolling bottom of Salt River on E. 50 chs. cultivated on remainder. Soil, sandy & gravel. No timber; undergrowth, weeds & creosote brush.
10.085	From the center 1/4 sec. cor. and meander cor. of sec. 7. S. 1°55' E., on the N-S centerline of sec. 7 on original survey. Over sandy Salt River bottom. Point for the C-N-S 1/64 sec. cor. of sec. 7. Set the iron post 25 ins. in the ground, brass cap mkd. S 7 C-N-S 1/64 1962 Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
20.17	Point for the C-S 1/16 sec. cor. of sec. 7.

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS	
	<p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>C</p> <p>S 1/16 S 7</p> <p> </p> <p>C</p> <p>1962</p> </div> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
30.255	<p>Point for the C-S-S 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>S 7</p> <p>C-S-S</p> <p>1/64</p> <p>1962</p> </div> <p>Raise a mound of stone W. of the cor.</p>
40.34	<p>The 1/2 sec. cor. of secs. 7 and 18.</p> <p>Land; rolling bottom of the Salt River. Soil, sandy and gravelly. No timber; undergrowth, weeds, creosote brush and sage brush.</p>
<p>Subdivision, SW 1/4 Section 7</p>	
<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p> <hr/>	
9.50	<p>From the C-W 1/16 sec. cor. of sec. 7.</p> <p>S. 0°23' W., on the N-S centerline of the SW 1/4 of sec. 7.</p> <p>Over cultivated land.</p> <p>Leave cultivated land, bears E. and W.; enter moderate willows.</p>
9.90	<p>Unimproved dirt road, bears E. and W.</p>
10.05	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 10 ins. below the surface on S. edge of dirt road, brass cap mkd.</p> <div style="text-align: center;"> <p>C-N-SW 1/64</p> <p>S 7</p> <p>1962</p> </div>
11.27	<p>The meander cor. set on the right bank of the Salt River in 1910, monumented by a 1 in. iron post, badly corroded, projecting 4 ins. above ground, brass cap mkd.</p> <div style="text-align: center;"> <p>MC 1910 in S.</p> <p>1/16 S7 SRIR in N.</p> </div>

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS

At the cor. point

Set the iron post 25 ins. in the ground, brass cap mkd.

T1N R5E
S 7
MC
1962

Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.

There is no remaining evidence of the original bearing tree.

Bury the original iron post alongside the cor.

S. 1°20' E., on original survey, beginning new measurement.

2.60 Enter Salt River bottom, bears N. 70° E. and S. 70° W.

8.83 Point for the SW 1/16 sec. cor. of sec. 7 at intersection with the E-W centerline of the SW 1/4 of sec. 7.

Set the iron post 25 ins. in the ground, brass cap mkd.

SW 1/16
S 7
1962

Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.

18.93 Point for the C-S-SW 1/64 sec. cor. of sec. 7.

Set the iron post 25 ins. in the ground, brass cap mkd.

C-S-SW 1/64
S 7
1962

Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.

29.03 The W 1/16 sec. cor. of secs. 7 and 18.

Land, mostly sandy bottom of the Salt River.
Soil, sandy.
No timber; undergrowth, willows, salt cedar, creosote brush, weeds and sage brush.

Reestablishment of the Survey executed by
R. A. Farmer in 1910

From the S 1/16 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS		
	<p>East, on the E-W centerline of the SW$\frac{1}{4}$ of sec. 7.</p>	
	<p>Over Salt River bottom.</p>	
4.40	<p>Record course and dist. for the meander cor. set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor.</p>	
	<p>Set the iron post 25 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T1N R5E S 7 MC 1962</p>	
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
	<hr/> <p>S. 89°46' E., on original survey, beginning new measurement.</p>	
	<p>Continue over sandy Salt River bottom.</p>	
15.85	<p>The SW 1/16 sec. cor. of sec. 7.</p>	
26.105	<p>Point for the C-E-SW 1/64 sec. cor. of sec. 7.</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">C-E-SW 1/64 S 7 1962</p>	
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
36.36	<p>The C-S 1/16 sec. cor. of sec. 7.</p>	
	<hr/> <p>From the C-N-SW 1/64 sec. cor. of sec. 7.</p>	
	<p>S. 89°53' E., on the E-W centerline of the NE$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 7.</p>	
	<p>Over nearly level land.</p>	
3.00	<p>Enter Salt River bottom, bears N. 70° E. and S. 70° W.</p>	
10.185	<p>Point for the NE-SW 1/64 sec. cor. of sec. 7.</p>	
	<p>Set the iron post 26 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">NE-SW 1/64 S 7 1962</p>	
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
	<p>Continue over sandy Salt River bottom.</p>	

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS	
20.37	<p>The C-N-S 1/64 sec. cor. of sec. 7.</p> <hr/> <p>From the S-S 1/64 sec. cor. of secs. 7 and 12 on the W. bdy. of the Tp.</p> <p>S. 89°52' E. on the E-W centerline of the SW$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 7.</p> <p>Over sandy Salt River bottom.</p>
10.14	<p>Point for the SW-SW 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW-SW 1/64 S 7 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.44	<p>The C-S-SW 1/64 sec. cor. of sec. 7.</p> <hr/> <p>S. 89°52' E. on the E-W centerline of the SE$\frac{1}{4}$SW$\frac{1}{4}$ of sec. 7.</p> <p>Over Salt River bottom.</p>
10.30	<p>Point for the SE-SW 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R5E SE-SW 1/64 S 7 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.60	<p>The C-S-S 1/64 sec. cor. of sec. 7.</p> <hr/> <p style="text-align: center;">Subdivision, SE$\frac{1}{4}$, Section 7</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 7.</p> <p>S. 2°18' E., on the N-S centerline of the SE$\frac{1}{4}$, sec. 7.</p> <p>Over sandy Salt River bottom.</p>
10.085	<p>Point for the C-N-SE 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-N-SE 1/64 S 7 1962</p>

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS		
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
20.17	<p>Point for the SE 1/16 sec. cor. of sec. 7 at the intersection with the E-W centerline of the SE 1/4 of sec. 7.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">SE 1/16 S 7 1962</p>	
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
40.34	<p>The E 1/16 sec. cor. of secs. 7 and 18.</p> <p>Land, nearly level bottom of the Salt River. Soil, sandy & gravelly. No timber; undergrowth, creosote brush, weeds and sage brush.</p>	
	<p>From the C-S 1/16 sec. cor. of sec. 7.</p> <p>S. 89°53' E., on the E-W centerline of the SE 1/4 of sec. 7.</p> <p>Over nearly level Salt River bottom.</p>	
10.295	<p>Point for the C-W-SE 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">C-W-SE 1/64 S 7 1962</p>	
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
20.59	<p>The SE 1/16 sec. cor. of sec. 7.</p>	
30.885	<p>Point for the C-E-SE 1/64 sec. cor. of sec. 7.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">C-E-SE 1/64 S 7 1962</p>	
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
41.18	<p>The S 1/16 sec. cor. of secs. 7 and 8.</p> <p>Land, nearly level bottom of Salt River. Soil, sandy & gravelly. No timber; undergrowth, creosote brush, weeds and sage brush.</p>	

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS	
	<p>From the C-N-S 1/64 sec. cor. of sec. 7.</p> <p>S. 89°53' E., on the E-W centerline of the NW$\frac{1}{4}$SE$\frac{1}{4}$ of sec. 7.</p> <p>Over sandy Salt River bottom.</p>
10.26	<p>Point for the NW-SE 1/64 sec. cor. of sec. 7.</p>
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">NW-SE 1/64 S 7 1962</p>
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.52	<p>The C-N-SE 1/64 sec. cor. of sec. 7.</p>
	<hr/> <p>S. 89°53' E. on the E-W centerline of the NE$\frac{1}{4}$SE$\frac{1}{4}$ of sec. 7.</p>
	<p>Over sandy Salt River bottom.</p>
10.26	<p>Point for the NE-SE 1/64 sec. cor. of sec. 7.</p>
	<p>Set the iron post 25 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">NE-SE 1/64 S 7 1962</p>
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.52	<p>The N-S 1/64 sec. cor. of secs. 7 and 8.</p>
<hr/> <p>Calculated Adjusted 1910 Meanders, Right Bank of the Salt River, SW$\frac{1}{4}$ Section 7</p> <hr/>	
<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p> <hr/>	
<p>For Informational Purposes only.</p>	
<p>Beginning at the meander cor. of secs. 7 and 12 on the W. bdy. of the Tp.</p>	
<p>Upstream with the calculated adjusted meander of the Right Bank of the Salt River.</p>	
<p>N. 56°53' E., 5.25 chs. Intersect the meander cor. set on the E-W centerline of the SW$\frac{1}{4}$ of sec. 7.</p>	

Survey of Partial Subdivision, Section 7
Township 1 North, Range 5 East

CHAINS	
	<p>N. 60°44' E., 17.88 chs. Intersect the meander cor. set on the N-S centerline of the SW$\frac{1}{4}$ of sec. 7.</p>
	<p>N. 40°34' E., 7.60 chs.</p>
	<p>N. 80°28' E., 7.37 chs.</p>
	<p>N. 72°28' E., 6.27 chs.</p>
	<p>N. 38°36' E., 3.05 chs. Intersect the meander cor. of sec. 7 which is also the center $\frac{1}{4}$ sec. cor. of sec. 7.</p>
<p>Subdivision, Section 8</p>	
<p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p>	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 5 and 8.</p>
	<p>S. 0°23' W., on the N-S centerline of sec. 8.</p>
	<p>Over nearly level sandy land.</p>
<p>10.08</p>	<p>Point for the C-N-N 1/64 sec. cor. of sec. 8.</p>
	<p>Set the iron post 25 ins. in the ground, brass cap mkd.</p>
	<p>C-N-N 1/64 S 8 1962</p>
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
<p>13.37</p>	<p>Record bearing and distance for the meander cor. set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor.</p>
	<p>Set the iron post 25 ins. in the ground, brass cap mkd.</p>
	<p>T1N R5E S 8 <hr/>MC 1962</p>
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
	<p>S. 3°20' E., on the N-S centerline of sec. 8, on original survey, beginning new measurement.</p>

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	Over rocky and sandy Salt River bottom.
6.79	Point for the C-N 1/16 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	C-N
	1/16
	S 8
	1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
16.87	Point for the C-S-N 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	C-S-N
	1/64
	S 8
	1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
26.95	Point for the center 1/4 sec. cor. of sec. 8 at inter-
	section with the E-W centerline of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	T1N R5E
	C 1/4
	S 8
	1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
37.05	Point for the C-N-S 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	C-N-S
	1/64
	S 8
	1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
47.15	Point for the C-S 1/16 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	C-S
	1/16
	S 8
	1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS		
62.30	Fence, bears E. and W., enter farm land.	
66.30	Wash, 50 lks. wide, 6 ft. banks, drains N. 80° W.	
66.90	Unimproved dirt road, bears E. and W.	
67.25	Cement lined irrigation ditch, flows W.	
67.35	The ¼ sec. cor. of secs. 8 and 17.	
	Land, mostly Salt River bottom land. Soil, sandy & gravelly. No timber; undergrowth, weeds, creosote brush, salt cedar and sage brush.	
	From the ¼ sec. cor. of secs. 7 and 8. S. 89°43' E., on the E-W centerline of sec. 8. Over sandy Salt River bottom.	
10.23	Point for the C-W-W 1/64 sec. cor. of sec. 8.	
	Set the iron post 25 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">C-W-W 1/64 S 8 1962</p>	
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.	
20.46	Point for the C-W 1/16 sec. cor. of sec. 8.	
	Set the iron post 25 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">C-W 1/16 S 8 1962</p>	
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.	
30.69	Point for the C-E-W 1/64 sec. cor. of sec. 8.	
	Set the iron post 25 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">C-E-W 1/64 S 8 1962</p>	
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.	
40.92	The C¼ sec. cor. of sec. 8.	
51.77	Point for the C-W-E 1/64 sec. cor. of sec. 8.	

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	<p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-W-E 1/64 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
62.62	<p>Point for the C-E 1/16 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-E 1/16 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
63.16	Fence, bears N. and S., enter nearly level farm land.
68.10	Irrigation ditch, drains NW.
69.80	Fence, bears N. and S.
84.00	Fence, bears N. and S.
84.10	Irrigation ditch, drains S. about 30 lks., thence W.
84.32	<p>The 1/4 sec. cor. of secs. 8 and 9.</p> <p>Land, nearly level - river and overflow land on W. 60 chs., farm land on remainder. Soil, sandy and gravelly. No timber; undergrowth, creosote brush, weeds, sage brush and salt cedar.</p>
Subdivision, NE 1/4 Section 8	
10.10	<p>From the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>S. 1°17' E. on the N-S centerline of the NE 1/4 sec. 8.</p> <p>Over sandy Salt River bottom.</p> <p>Point for the C-N-NE 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-N-NE 1/64 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS		
20.20	<p>Point for the NE 1/16 sec. cor. of sec. 8 at intersection with the E-W centerline of the NE¼ of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
30.305	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S-NE 1/64 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
40.41	<p>The C-E 1/16 sec. cor. of sec. 8.</p>	
11.22	<p>From the C-N 1/16 sec. cor. of sec. 8.</p> <p>S. 89°55' E., on the E-W centerline of the NE¼ of sec. 8.</p> <p>Over sandy Salt River bottom.</p> <p>Point for the C-W-NE 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-W-NE 1/64 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>	
22.44	<p>The NE 1/16 sec. cor. of sec. 8.</p>	
33.44	<p>Point for the C-E-NE 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-E-NE 1/64 S 8 1962</p>	
44.30	<p>Road, bears N. and S. (Alma School Road, now paved.)</p>	
44.44	<p>The N 1/16 sec. cor. of secs. 8 and 9.</p>	

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	<p>From the C-N-N 1/64 sec. cor. of sec. 8.</p> <p>S. 89°58' E., on the E-W centerline of the NW$\frac{1}{4}$NE$\frac{1}{4}$ of sec. 8.</p>
2.50	Over sandy Salt River bottom.
11.29	Point for the NW-NE 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	NW-NE 1/64 S 8 1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
22.58	The C-N-NE 1/64 sec. cor. of sec. 8.
	<hr style="width: 20%; margin: auto;"/>
	East, on the E-W centerline of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 8.
	Over sandy Salt River bottom.
11.075	Point for the NE-NE 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	NE-NE 1/64 S 8 1962
20.10	Dirt road, bears N. and S. 15° E. (Note: The road through this area has been changed since the 1962 survey and is now paved. (Alma School Road).
22.15	The N-N 1/64 sec. cor. of secs. 8 and 9.
	<hr style="width: 20%; margin: auto;"/>
	From the C-S-N 1/64 sec. cor. of sec. 8.
	S. 89°49' E., on the E-W centerline of the SW $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 8.
	Over sandy Salt River bottom.
11.03	Point for the SW-NE 1/64 sec. cor. of sec. 8.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	SW-NE 1/64 S 8 1962
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
22.06	The C-S-NE 1/64 sec. cor. of sec. 8.

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	<p>Subdivision, NW$\frac{1}{4}$ Section 8</p> <hr/> <p>Reestablishment of the Survey executed by R. A. Farmer in 1910</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>S. 0°23' W., on the N-S centerline of the NW$\frac{1}{4}$ of sec. 8.</p> <p>Over nearly level sandy overflow land.</p>
15.66	<p>Record bearing and distance for the meander cor. set on the right bank of the Salt River in 1910. There is no remaining evidence of the original cor.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N-R5E S 8 MC 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p> <hr/> <p>S. 2°43' E., on original survey, beginning new measurement.</p>
4.42	<p>Point for the NW 1/16 sec. cor. of sec. 8 at intersection with the E-W centerline of the NW$\frac{1}{4}$ of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 8 1962</p> <p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
14.48	<p>Point for the C-S-NW 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-S-NW 1/64 S 8 1962</p>
24.54	<p>The C-W 1/16 sec. cor. of sec. 8.</p> <hr/> <p>From the true point for the N 1/16 sec. cor. of secs. 7 and 8.</p> <p>S. 89°48' E., on the E-W centerline of the NW$\frac{1}{4}$ of sec. 8.</p>

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	Over nearly level Salt River bottom land.
20.24	The NW 1/16 sec. cor. of sec. 8.
30.35	Point for the C-E-NW 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">C-E-NW 1/64 S 8 1962</p>
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
40.46	The C-N 1/16 sec. cor. of sec. 8.
	<hr/>
	From the S-N 1/64 sec. cor. of secs. 7 and 8.
	S. 89°46' E., on the E-W centerline of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 8.
	Over nearly level Salt River bottom land.
11.225	Point for the SW-NW 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">SW-NW 1/64 S 8 1962</p>
	Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.
20.45	The C-S-NW 1/64 sec. cor. of sec. 8.
	<hr/>
	S. 89°46' E., on the E-W centerline of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 8.
	Over sandy Salt River bottom.
10.17	Point for the SE-NW 1/64 sec. cor. of sec. 8.
	Set the iron post 25 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">SE-NW 1/64 S 8 1962</p>
20.34	The C-S-N 1/64 sec. cor. of sec. 8.
	<hr/>
	Subdivision, SW $\frac{1}{4}$ Section 8
	<hr/>
	From the C-W 1/16 sec. cor. of sec. 8.

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	<p>S. 3°00' E., on the N-S centerline of the SW$\frac{1}{2}$ of sec. 8. Over sandy Salt River bottom.</p>
10.095	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 8. Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-N-SW 1/64 S 8 1962</p>
20.19	<p>Point for the SW 1/16 sec. cor. of sec. 8, at intersection with the E-W centerline of the SW$\frac{1}{2}$ of sec. 8. Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">SW 1/16 S 8 1962</p>
33.30	<p>Leave Salt River bottom, enter cultivated land; dirt road along edge of cultivated land, bears N. 50° E. and S. 50° W.</p>
40.37	<p>The W 1/16 sec. cor. of secs. 8 and 17.</p>
10.285	<hr/> <p>From the S 1/16 sec. cor. of secs. 7 and 8. S. 89°42' E., on the E-W centerline of the SW$\frac{1}{2}$ of sec. 8. Over sandy Salt River bottom.</p> <p>Point for the C-W-SW 1/64 sec. cor. of sec. 8. Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-W-SW 1/64 S 8 1962</p>
20.57	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p> <p>The SW 1/16 sec. cor. of sec. 8.</p>
30.855	<p>Point for the C-E-SW 1/64 sec. cor. of sec. 8. Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-E-SW 1/64 S 8 1962</p>
41.14	<p>The C-S 1/16 sec. cor. of sec. 8.</p>

Survey of Partial Subdivision, Section 8
Township 1 North, Range 5 East

CHAINS	
	<p>From the N-S 1/64 sec. cor. of secs. 7 and 8.</p> <p>S. 89°43' E., on the E-W centerline of the NW¹/₄SW¹/₄ of sec. 8.</p> <p>Over sandy Salt River bottom.</p>
10.26	<p>Point for the NW-SW 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NW-SW 1/64 S 8 1962</p>
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.52	<p>The C-N-SW 1/64 sec. cor. of sec. 8.</p>
	<hr/> <p>S. 89°43' E., on the E-W centerline of the NE¹/₄SW¹/₄ of sec. 8.</p> <p>Over sandy Salt River bottom.</p>
10.26	<p>Point for the NE-SW 1/64 sec. cor. of sec. 8.</p> <p>Set the iron post 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">NE-SW 1/64 S 8 1962</p>
	<p>Set a redwood post, 5 ft. long, 4 ins. square, alongside the cor.</p>
20.52	<p>The C-N-S 1/64 sec. cor. of sec. 8.</p>
<hr/> <p>SURVEY OF THE SOUTH BOUNDARY OF THE SALT RIVER INDIAN RESERVATION THROUGH TOWNSHIP 1 NORTH, RANGE 5 EAST, G&SRM, ARIZONA</p> <hr/>	
<p>By memorandum dated January 17, 1969, the Secretary of the Interior determined the South Boundary of the Salt River Indian Reservation as in the South Channel of the Salt River. By memorandum dated November 17, 1971, the Assistant Secretary, Public Land Management, designated the location of the South Boundary of the Salt River Indian Reservation as the South Channel as it existed during the 1965-66 floods.</p>	
<p>The line, as surveyed, is not a permanently fixed boundary as its location is subject to movement in order to accommodate to "the middle of (the Salt River)," which is designated in the Executive Order of June 14, 1879 as the south boundary of the reservation.</p>	
<p>The approximate South Boundary of the Salt River Indian Reservation through T. 1 N., R. 5 E., was determined by use of aerial photos. Considering the channels, their depth and nature and the river changes, this is considered the best solution for placing the boundary in its</p>	

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
	<p>intended position. This survey is made running out the predetermined courses and distances and refer to the true cardinal directions.</p> <p>At Angle Point No. 1 on the West bdy. of the Tp.</p> <p>Set the iron post 26 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T1N R 4E R 5E SRIR AP 1 S 13 S 18 1972</p> </div> <p>from which</p> <p style="padding-left: 40px;">The cor. of secs. 7, 12, 13 and 18, bears N. 1°42' W., 6.91 chs. dist.</p> <p>Raise a mound of stone NE of the cor.</p> <p><u>Through sec. 18.</u></p> <p>S. 79°22' E., along the South Boundary of the Salt River Indian Reservation.</p> <p>Over sandy and rocky Salt River bottom.</p>
8.815	<p>Point for Angle Point No. 2.</p> <p>Set the iron post 27 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>SRIR AP 2 S18 T1N R5E 1972</p> </div> <p>Raise a mound of stone N. of the cor.</p>
6.52	<p>S. 87°43' E.</p> <p>Point for Angle Point No. 3.</p> <p>Set the iron post 30 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>SRIR AP 3 S 18 T1N R5E 1972</p> </div> <p>Set a cottonwood post, 7 ft. long, 7 ins. diam., along-side the cor.</p>

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

N. 83°34' E.

8.36 Point for Angle Point No. 4.

Set the iron post 24 ins. in the ground, and in a collar of stone, brass cap mkd.

SRIR
AP 4

S 18
T1N R5E
1972

N. 73°21' E.

7.29 Point for Angle Point No. 5.

Set the iron post 27 ins. in the ground, brass cap mkd.

SRIR
AP 5

S 18
T1N R5E
1972

Raise a mound of stone N. of the cor.

N. 69°14' E.

5.25 Point for Angle Point No. 6.

Set the iron post 28 ins. in the ground, brass cap mkd.

SRIR
AP 6

S 18
T1N R5E
1972

Raise a mound of stone N. of the cor.

N. 87°45' E.

8.07 Point for Angle Point No. 7.

Set the iron post 28 ins. in the ground, brass cap mkd.

SRIR
AP 7

S 18
T1N R5E
1972

Set a wooden post, 5 ft. long, 2 ins. thick, 6 ins. wide, alongside the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS		
	S. 88°46' E.	
10.73	Point for Angle Point No. 8.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">SRIR AP 8</p> <hr style="width: 10%; margin: auto;"/>	
	<p style="text-align: center;">S 18 T1N R5E 1972</p>	
	Set a board, 6 ft. long, 6 ins. wide, 2 ins. thick, along side the cor.	
	<hr style="width: 20%; margin: auto;"/>	
	N. 82°38' E.	
12.00	Graded road, bears N. and S.	
15.54	Point for Angle Point No. 9.	
	Set the iron post 24 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">SRIR AP 9</p> <hr style="width: 10%; margin: auto;"/>	
	<p style="text-align: center;">S 18. T1N R5E 1972</p>	
	Raise a mound of stone N. of the cor.	
	<hr style="width: 20%; margin: auto;"/>	
	N. 82°28' E.	
6.68	Point for Angle Point No. 10.	
	Set the iron post 22 ins. in the ground, brass cap mkd.	
	<p style="text-align: center;">SRIR AP 10</p> <hr style="width: 10%; margin: auto;"/>	
	<p style="text-align: center;">S 18 T1N R5E 1972</p>	
	Raise a mound of stone NW. of the cor.	
	<hr style="width: 20%; margin: auto;"/>	
	N. 68°04' E.	
2.125	Intersect the line bet. secs. 7 and 18.	
	Set the iron post 30 ins. in the ground for a witness point, brass cap mkd.	
	<p style="text-align: center;">T1N R5E W S 7 P S 18 1972</p>	

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

from which

The cor. of secs: 7, 8, 17 and 18, bears
S. 89°55' E., 4.37 chs. dist.

Raise a mound of stone N. of the cor.

Through sec. 7.

N. 68°04' E., continuing measurement.

6.75 Intersect the line bet. secs. 7 and 8.

Set the iron post 26 ins. in the ground for a witness
point, brass cap mkd.

T1N R5E
W P
S 7 | S 8
1972

from which

The cor. of secs. 7, 8, 17 and 18, bears S. 2°
41' E., 1.74 chs. dist.

Raise a mound of stone W. of the cor.

Through sec. 8.

N. 68°04' E., continuing measurement.

9.36 Point for Angle Point No. 11.

Set the iron post 26 ins. in the ground, brass cap mkd.

SRIR
AP 11
S 8
T1N R5E
1972

Raise a mound of stone NW. of the cor.

N. 45°19' E.




4.11 Point for Angle Point No. 12.

Set the iron post 22 ins. in the ground, brass cap mkd.

SRIR
AP 12
S 8
T1N R5E
1972

Set a board, 6 ft. long, 4 ins. wide and 2 ins. thick,
alongside the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
	N. 50°05' E.
4.25	Point for Angle Point No. 13.
	Set the iron post 26 ins. in the ground, brass cap mkd.
	<div style="text-align: center;">  <p>SRIR AP 13 S 8 T1N R5E 1972</p> </div>
	Set a wooden post, 6 ft. long, 5 ins. diam., alongside the cor.
	<hr/>
	N. 43°59' E.
9.98	Point for Angle Point No. 14.
	Set the iron post 30 ins. in the ground, brass cap mkd.
	<div style="text-align: center;">  <p>SRIR AP 14 S 8 T1N R5E 1972</p> </div>
	Raise a mound of stone NW. of the cor.
	<hr/>
	N. 47°13' E.
11.50	Point for Angle Point No. 15.
	Set the iron post 26 ins. in the ground, brass cap mkd.
	<div style="text-align: center;">  <p>SRIR AP 15 S 8 T1N R5E 1972</p> </div>
	Raise a mound of stone NW. of the cor.
	<hr/>
	N. 43°57' E.
9.20	Enter gravel pit.
10.90	Point for Angle Point No. 16.
	Set the iron post 22 ins. in the ground, brass cap mkd.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

SRIR
AP 16

S 8
T1N R5E
1972

Raise a mound of stone NW. of the cor.

N. 46°10' E.

5.36 Point for Angle Point No. 17.

Set the iron post 22 ins. in the ground, brass cap mkd.

SRIR
AP 17

S 8
T1N R5E
1972

Raise a mound of stone NW. of the cor.

N. 41°46' E.

7.25 Leave gravel pit, about 15 ft. deep.

7.33 Point for Angle Point No. 18.

Set the iron post 30 ins. in the ground, brass cap mkd.

SRIR
AP 18

S 8
T1N R5E
1972

Set a board, 5 ft. long, 6 ins. wide, 2 ins. thick, along
side the cor.

N. 50°43' E.




8.01 Point for Angle Point No. 19.

Set the iron post flush with the surface, brass cap mkd.

SRIR
AP 19

S 8
T1N R5E
1972

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS		
	<p>The cor. is located in the W. track of a bladed road bearing S. and N. 100 ft. to junction of bladed roads bearing N., E., S. and W.</p>	
	<hr/> <p>N. 49°51' E.</p>	
7.66	<p>Point for Angle Point No. 20.</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">SRIR AP 20</p>  <p style="text-align: center;">S. 8 T1N R5E 1972</p>	
	<p>Raise a mound of stone NW. of the cor.</p>	
	<hr/> <p>N. 64°24' E.</p>	
8.10	<p>Graded road, bears N. 73° E. and S. 73° W.</p>	
10.33	<p>Point for Angle Point No. 21.</p>	
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">SRIR AP 21</p>  <p style="text-align: center;">S 8 T1N R5E 1972</p>	
	<p>Raise a mound of stone NW. of the cor.</p>	
	<hr/> <p>N. 59°20' E.</p>	
5.16	<p>Point for Angle Point No. 22.</p>	
	<p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">SRIR AP 22</p>  <p style="text-align: center;">S. 8 T1N R5E 1972</p>	
	<p>Raise a mound of stone NW. of the cor.</p>	
	<hr/> <p>N. 69°49' E.</p>	
5.09	<p>Point for Angle Point No. 23.</p>	

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

Set the iron post 28 ins. in the ground, brass cap mkd.

SRIR
AP 23

S 8
T1N R5E
1972

Raise a mound of stone NW. of the cor.

N. 65°01' E.

2.30 Track road, bears S. 85° E. and N. 85° W.

7.80 Graded road, bears N. 60° E. and S. 60° W.

8.28 Point for Angle Point No. 24.

Set the iron post flush with the surface, brass cap mkd.

SRIR
AP 24

S 8
T1N R5E
1972

The cor. is located in the edge of a graded road, bears
N. 60° E. and S. 60° W.

N. 74°59' E.

2.96 Power line, bears N. and S.

3.60 Alma School Road, bears N. 10° W. and S.

4.206 Intersect the line bet. secs. 8 and 9.

Unable to set an iron post for the witness point. Chisel
an "X" in solid concrete at the cor. point.




from which

An "X" cut on the S. side of a cement cylinder,
supporting a telephone pole, bears N. 70°53' E.,
19.7 lks. dist.



An "X" cut on the W. side of the cement cylinder,
bears N. 56°50' E., 18.7 lks. dist.

The $\frac{1}{2}$ sec. cor. of secs. 8 and 9, bears S. 0°27'
E., 24.00 chs. dist. The N $\frac{1}{16}$ sec. cor. of
secs. 8 and 9 set in 1962 was not found at the
time of the 1972 survey.





Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
	<p><u>Through sec. 9.</u></p> <p>N. 74°59' E., continuing measurement.</p>
4.42	Telephone line, bears N. and S.; enter gravel pit.
7.06	Point for Angle Point No. 25.
	<p>Set the iron post flush with the surface, brass cap mkd.</p> <div style="text-align: center;"> <p>SRIR AP 25</p>  <p>S 9 T1N R5E 1972</p> </div>
	N. 68°10' E.
	Over bottom of gravel pit being worked at this time.
5.13	Point for Angle Point No. 26.
	Set the iron post flush with the surface, brass cap mkd.
	<div style="text-align: center;"> <p>SRIR AP 26</p>  <p>S 9 T1N R5E 1972</p> </div>
	N. 57°58' E.
6.99	Point for Angle Point No. 27.
	This point falls in a working pit area where gravel is presently being removed, and was not monumented.
	N. 54°27' E.
1.60	Leave gravel pit; continue along channel of the Salt River.
6.22	Point for Angle Point No. 28.
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<div style="text-align: center;"> <p>SRIR AP 28</p>  <p>S 9 T1N R5E 1972</p> </div>
	Raise a mound of stone NW. of the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
11.47	<p>N. 55°25' E.</p> <p>Point for Angle Point No. 29.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;">  <p>SRIR AP 29</p> <p>S 9 T1N R5E 1972</p> </div> <p>Raise a mound of stone NW. of the cor.</p> <hr/>
.286	<p>N. 63°38' E.</p> <p>Intersect the line bet. secs. 4 and 9.</p> <p>Since this point is located in close proximity to Angle Point No. 29, no witness point was set.</p> <p>From point of intersection</p> <p style="padding-left: 40px;">The W 1/16 sec. cor. of secs. 4 and 9, bears S. 89°54' W., 9.02 chs. dist.</p> <hr/>
7.49	<p><u>Through sec. 4.</u></p> <p>N. 63°38' E., continuing measurement.</p> <p>Point for Angle Point No. 30.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;">  <p>SRIR AP 30</p> <p>S 4 T1N R5E 1972</p> </div> <p>Raise a mound of stone NW. of the cor.</p> <hr/>
2.60	<p>N. 53°29' E.</p> <p>Centerline of paved 4 lane road (McKellips Road) on gentle curve, bears S. 63½° E. and N. 63½° W. Note: This road has been built since the 1962 survey.</p>
5.90	<p>Point for Angle Point No. 31.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p>

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
	<div style="text-align: center;">  <p>SRIR AP 31 S 4 T1N R5E 1972</p> </div> <p>Raise a mound of stone NW. of the cor.</p> <hr/> <p>N. 24°47' E.</p> <p>4.70 Enter gravel pit.</p> <p>10.21 Point for Angle Point No. 32.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;">  <p>SRIR AP 32 S 4 T1N R5E 1972</p> </div> <p>Raise a mound of stone NW. of the cor.</p> <hr/> <p>N. 42°35' E.</p> <p>4.50 Leave gravel pit.</p> <p>8.80 Enter gravel pit.</p> <p>11.52 Point for Angle Point No. 33.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;">  <p>SRIR AP 33 S 4 T1N R5E 1972</p> </div> <p>The cor. is located on the W. slope of a gravel pile.</p> <hr/> <p>N. 48°47' E.</p> <p>6.57 Point for Angle Point No. 34.</p> <p>Set the iron post flush with the surface, brass cap mkd.</p> <div style="text-align: center;">  <p>SRIR AP 34 S 4 T1N R5E 1972</p> </div>

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

The cor. is located in vacated access road leading to
gravel pit.

N. 43°19' E.

.90

Leave gravel pit.

4.99

Point for Angle Point No. 35.

Set the iron post 24 ins. in the ground, brass cap mkd.

SRIR
AP 35

S 4
T1N R5E
1972

Raise a mound of stone NW. of the cor.

N. 24°06' E.

8.10

Enter gravel pit.

11.48

Point for Angle point No. 36.

Set the iron post 24 ins. in the ground, brass cap mkd.

SRIR
AP. 36

S 4
T1N R5E
1972

from which

USC&GS triangulation station "LEHI", bears
N. 31°50'49" W., .25.977 chs. dist., monumented
by a standard disk set in a cement cylinder,
marked Lehi 1963. Lat. 33°27'47.1158" N., and
Long. 111°50'40.6993" W.

Raise a mound of stone NW. of the cor.

N. 45°14' E.

11.35

Leave gravel pit.

12.50

Point for Angle Point No. 37.

Set the iron post 24 ins. in the ground, brass cap mkd.

SRIR
AP 37

S 4
T1N R5E
1972

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
	Raise a mound of stone NW. of the cor. <hr style="width: 20%; margin: 10px auto;"/>
	S. 88°15' E.
2.892	Intersect the line bet. secs. 3 and 4.
	Set the iron post 28 ins. in the ground for a witness point, brass cap mkd.
	T1N R5E W P S 4 S 3 1972
	from which
	The ¼ sec. cor. of secs. 3 and 4, bears S. 1°04' E., 11.059 chs. dist.
	Raise a mound of stone W. of the cor.
	<u>Through sec. 3.</u>
	S. 88°15' E., continuing measurement.
4.22	Centerline of Country Club Drive, bears N. and S.
12.00	Track road, bears N. 55° E. and S. 55° W.
16.97	Point for Angle Point No. 38.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	SRIR AP 38 <hr style="width: 10%; margin: 5px auto;"/> S 3 T1N R5E 1972
	Raise a mound of stone N. of the cor.
	<hr style="width: 20%; margin: 10px auto;"/> S. 43°44' E.
4.85	Point for Angle Point No. 39.
	Set the iron post 24 ins. in the ground, brass cap mkd.
	SRIR S 3 AP 39 T1N R5E 1972
	Raise a mound of stone and concrete blocks NE. of the cor.
	<hr style="width: 20%; margin: 10px auto;"/>


Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

S. 16°52' E.

2.05 Point for Angle Point No. 40.

Set the iron post 24 ins. in the ground, brass cap mkd.




Raise a mound of stone and concrete blocks E. of the cor.

S. 2°49' E.

3.18 Point for Angle Point No. 41.

Set the iron post 22 ins. in the ground, mound of stone
to top, brass cap mkd.




Raise a mound of stone and concrete blocks NE. of the cor.

S. 42°01' E.

2.63 Chain link fence, bears E. and W.

2.95 Point for Angle Point No. 42.

Set the iron post 24 ins. in the ground, brass cap mkd.




Raise a mound of stone NE. of the cor.

S. 87°47' E.

2.35 Point for Angle Point No. 43.

Set the iron post 20 ins. in the ground, mound of stone
to top, brass cap mkd.



Raise a mound of stone N. of the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS	
.78	<p>N. 65°52' E.</p> <p>Chain link fence, bears E. and W.</p> <p>Point for Angle Point No. 44.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> SRIR AP 44 S 3 T1N R5E 1972 </p> <p>Raise a mound of stone NW. of the cor.</p> <hr/>
2.05	<p>N. 49°26' E.</p> <p>Point for Angle Point No. 45.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> SRIR AP 45 S 3 T1N R5E 1972 </p> <p>Raise a mound of stone NW. of the cor.</p> <hr/>
2.20	<p>N. 62°59' E.</p> <p>Point for Angle Point No. 46</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> SRIR AP 46 S 3 T1N R5E 1972 </p> <p>Raise a mound of stone NW. of the cor.</p> <hr/>
1.97	<p>N. 71°13' E.</p> <p>Point for Angle Point No. 47.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;"> SRIR AP 47 S 3 T1N R5E 1972 </p>

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

Raise a mound of stone N. of the cor.

N. 74°30' E.

3.41 Point for Angle Point No. 48.

Set the iron post 24 ins. in the ground, brass cap mkd.

SRIR
AP 48

S 3

T1N R5E
1972

Set a wooden post, 5 ft. long, 4 ins. square, alongside
the cor.

N. 71°08' E.

2.10 Gravel road, bears N. 2° E. and S. 2° W.

2.57 Power line, bears N. 2° E. and S. 2° W.

4.17 Point for Angle point No. 49.

Set the iron post 20 ins. in the ground, mound of stone
to top, brass cap mkd.

SRIR
AP 49

S 3

T1N R5E
1972

Raise a mound of stone NW. of the cor.

N. 58°03' E.

.15 Enter gravel pit.

3.18 Point for Angle Point No. 50.

Set the iron post 24 ins. in the ground, brass cap mkd.

SRIR
AP 50

S 3

T1N R5E
1972

Raise a mound of stone NW. of the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East


CHAINS

The cor. is located on the S. side of a 8 ft. high mound
of large river stones and sand.

N. 44°18' E.

5.98 Point for Angle Point No. 51.

Set the iron post 22 ins. in the ground, brass cap mkd.




Raise a mound of stone NW. of the cor.

N. 18°46' E.

5.50 Leave gravel pit; fence line bears E. and W.

14.02 Point for Angle Point No. 52.

Set the iron post 24 ins. in the ground, brass cap mkd.



Raise a mound of stone NW. of the cor.

N. 28°30' E.

10.69 Fence, bears N. and S.


11.80 Graded gravel road, bears N. and S.

12.50 Continue along W. edge of gravel pit.

15.14 Intersect the N. bdy. of sec. 3.

Point for Angle Point No. 53.

Set the iron post 25 ins. in the ground, brass cap mkd.



Survey of the South Boundary of the Salt River Indian
Reservation through Township 1 North, Range 5 East

CHAINS

from which

The cor. of secs. 2 and 3, bears N. 88°16' E.,
19.23 chs. dist.

Raise a mound of stone W. of the cor.

General Description

The land surveyed under this group lies in or in close proximity to the N. edge of Mesa, Arizona. The Salt River meanders from the N. bdy. of sec. 3, southwesterly through the central portion of the surveyed area. The river bed and overflow channels varies in width from about $\frac{1}{2}$ mile along the W. bdy. up to $1\frac{1}{2}$ miles in certain areas within the surveyed sections.

Numerous residential and commercial developments are located in the E. and S. portion of sec. 3, the SE. and NW $\frac{1}{4}$'s of sec. 4, throughout sec. 9 excluding the NW $\frac{1}{4}$ NW $\frac{1}{4}$ and the southern portions of secs. 8 and 18.

The soil along the river is mostly valuable deposits of sand and gravel. At present, sand and gravel operations are removing deposits in secs. 3, 4, 8 and 9 with excavation work visible throughout the Salt River bottom land. Adjacent land is either developed for residential or commercial use, or under cultivation.

Current land fills in secs. 3 and 4 have destroyed much of the evidence of the old Salt River channels and will undoubtedly influence subsequent river flows.

BOOK 4938

Form 9180-8
(March 1969)



UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Leonard W. Murphy	Cadastral Surveyor
Wallace R. Ott	Surveying Technician
Gary T. Oviatt	" "
Gary W. Rutledge	" "
Daniel R. Bauer	Surveying Aid
Dennis L. Twitchell	" "
Jack R. Bowker	" "
Harry K. Smith	" "
Martin W. Fuller	" "
Hutch Noline	" "

CERTIFICATE OF SURVEY

(We), Boyd S. Owens and Paul G. Bauer, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 11th day
 of May, 1962, (~~IX 104528~~) and Amended Supplemental Special
 Instructions bearing the date of March 9, 1972, we have made a dependent
 resurvey of a portion of the North and West boundaries, a portion of the
 subdivisional lines, a portion of the section subdivision, retraced a portion
 of the subdivisional lines, surveyed subdivisions in Sections 4, 7 and 8 and
 surveyed the South Boundary of the Salt River Indian Reservation, Township
 1 North, Range 5 East,
 of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (we), (us) and under (my)
 (our) direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

<u>June 22, 1972</u> (Date)	 Boyd S. Owens (Cadastral Surveyor)
<u>June 22, 1972</u> (Date)	 Paul G. Bauer (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date JUN 26 1972

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the North and West boundaries, a portion of the subdivisional lines, a portion of the section subdivisions, a retracement of a portion of the subdivisional lines, the survey of subdivisions in Sections 4, 7 and 8 and the survey of the South Boundary of the Salt River Indian Reservation, Township 1 North, Range 5 East, Gila and Salt River Meridian, Arizona,

executed by Boyd S. Owens and Paul G. Bauer,
 having been critically examined and found correct, are hereby approved.

<u>AUG 17 1972</u> (Date)	 (Chief, Division of Cadastral Survey)
------------------------------	---

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 , is a true copy of the original field notes.

<u>(Date)</u>	(Chief, Division of Cadastral Survey) GPO 849-626
---------------	---