Form 9180-6 (April 1965) (formerly 4-679)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

	OF THE RETRACEMENT A	ND SURVEY OF	
-	A PORTION OF THE SUBDI	VISIONAL LINES	
Printer 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	COMPLETING THE SU	BDIVISION	
	OF		
	TOWNSHIP 8 SOUTH, R.	ANGE 9 EAST	

		,	
	,		
			**

		, , , , , , , , , , , , , , , , , , , 	Meridian,
In the State of	Arizona		•
	EXECUT	ED BY	
Gary T. Oviatt	Cad	astral Surveyor	
dary 1. Oviate	Cau	astrar surveyor	
<u> </u>			
			
Under special instructi	ons dated January 29	, 1970 , which provided for	the surveys
included under Group N	umber <u>468</u> , ap	proved January 29, 1970	 ,
and assignment instruct	ions dated February 6	, 19 70	
	Survey commenced February	11 . 19 70	

March 12

Survey completed __

_____, 19 70

BOOK 4939

INDEX DIAGRAM

Townsh	ip 8 South	1	, Range	9 Eas	t	,
6	5	4	8 12	13	2 12	1
7	8	9	10 10	11	9	12
18	17	16	15 8	8	14 7	13
19	20	21	22	6	28 5	24
30	29	28	3 27	4	26	25
31	32	38	84	1	35	36

Township 8 South, Range 9 East Gila and Salt River Meridian, Arizona

CHAINS

The south and west boundaries were surveyed in 1883 by R. C. Powers. The west boundary was surveyed again in 1887 by R. C. Powers. The east boundary was surveyed in 1911 by H. F. DuVal. The south 2 miles of the east boundary and the south and west boundaries were resurveyed in 1913 by Wright and Elliott, who in the same year surveyed the north boundary and a portion of the subdivisional lines. The east boundary was resurveyed in 1919 by Thorn, Muscott and Wilson.

The following field notes are those of a retracement of a portion of the subdivisional lines and a survey completing the subdivision of Township 8 South, Range 9 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 29, 1970.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes. Unless described, each corner was monumented with a standard iron post 30 inches long, $2\frac{1}{2}$ inches diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the southeast corner of Section 26 is: Latitude 32°41'25.2" North and Longitude 111°22' 41.2" West, as determined by a traverse from U.S.C.&G.S. Triangulation Station "NEWMAN", located in sec. 22.

The mean magnetic declination was found to be: 13½° East

Retracement of a Portion of the Subdivisional Lines
Township 8 South, Range 9 East

Retracement of the Survey Executed by Wright and Elliott in 1913

Beginning at the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post 3 ins. diam., projecting 8 ins. above the ground, brass cap mkd.

T8S R9E <u>\$34</u> | <u>\$35</u> <u>\$ 3</u> | <u>\$ 2</u> <u>\$ 795</u> 1913

N. 0°01' W., bet. secs. 34 and 35.

Over rolling land, through moderate undergrowth.

The ½ sec. cor. of secs. 34 and 35, monumented by an iron post 1 in. diam., projecting 15 ins. above the ground, set in a mound of stone, brass cap mkd.

\$34 | \$35 1913 Retracement, Portion of Subdivisional Lines, T. 8 S., R. 9 E.

	Metr	acement, forcion of bubble to be a series of the series of
	CHAINS	
		N. 0°01' W., beginning new measurement.
		Over rolling land.
	40.08	The cor. of secs. 26, 27, 34 and 35, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
		T8S R9E <u>S27 S26</u> <u>S34 S35</u> 1913
		Land, rolling. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti.
		From the cor. of secs. 25, 26, 35 and 36, monumented by an iron post 2 ins. diam., projecting 12 ins. above the ground, brass cap mkd.
		T8S R9E <u>S26 S25</u> S35 S36 1913
	• • • •	N. 89°51' W., bet. secs. 26 and 35.
		Over rolling land, through moderate undergrowth.
•	18.60	Draw, drains SE., from W.
	23.80	Draw, drains E., from N. 60° W.; asc. steep E. slope.
	35.80	Top of rocky spur, slopes N. 30° E.; desc. W. slope.
	39.10	Gulch, 10 lks. wide, 2 ft. deep, drains NE.; asc. E. slope.
	40.07	The ½ sec. cor. of secs. 26 and 35, monumented by an iron post 1 in. diam., firmly set in a mound of stone, brass cap mkd.
		S26 . <u>½</u> S35 1913
		N. 89°41' W., beginning new measurement.
		Over mountainous land.
	12.20	Top of ridge, bears North and S. 20° E.; desc. steep W. slope.
	31.00	Draw, drains S. 20° W.; asc. gradual E. slope.
	40.02	The cor. of secs. 26, 27, 34 and 35.

Retracement, Port	ion of	Subdivisional	Lines,	T.	8	S.,	R.	9	Ε.
-------------------	--------	---------------	--------	----	---	-----	----	---	----

_	, ,	Retracement, Portion of Subdivisional Lines, T. 8 S., R. 9 E
	CHAINS	Land, rolling and mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, none.
		N. 89°44' W., bet. secs. 27 and 34.
	·	Over rolling land, through moderate undergrowth.
	11.00	Asc. along S. slope of Picacho Mountains. Draw, drains S. 20° E.
	27.90	Spur, slopes S. 10° E.
	34.20	Draw, drains S.
	38.40	Rocky spur, slopes S.
	40.16	The ½ sec. cor. of secs. 27 and 34, monumented by an iron post 1 in. diam., firmly set in a mound of stone, brass cap mkd.
		S27
		- 1/4 S34
		1913
		S. 89°56' W., beginning new measurement.
		Continue along S. slope of mountain.
	8.70	High spur, slopes S. 10° W.; desc. W. slope.
	30.50	Draw, drains SW.
	39.90	The cor. of secs. 27, 28, 33 and 34, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
		T8S R9E <u>\$28</u> \$27 \$33 \$34 1913
	`	Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti.
		N. 0°02' W., bet. secs. 27 and 28.
		Over mountainous land, through moderate undergrowth.
		Asc. S. slope.
	9.00	Draw, 100 1ks. wide, 2 ft. deep, drains SW.
ĺ		
		.

, R	etracement, Portion of Subdivisional Lines, T. 8 S., R. 9 E
40.15	The ½ sec. cor. of secs. 27 and 28, monumented by an iron post 1 in. diam., firmly set in a mound of stone, brass cap mkd.
	s 28 s 27 1913
	The cor. is located at the base of a steep ledge, bears NE. and SW.
	N. 0°31' W., beginning new measurement.
0.00	Over mountainous land.
2.20	Top of sheer ledge, bears NE. and SW., thence along a W. slope.
37.30	Spur, slopes W.; desc. N. slope.
39.89	The cor. of secs. 21, 22, 27 and 28, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T8S R9E <u>S21 S22</u> <u>S28 S27</u> 1913
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	Completion Survey, Subdivisional Lines Township 8 South, Range 9 East
د	From the cor. of secs. 26, 27, 34 and 35.
	N. 0°01' W., bet. secs. 26 and 27.
	Asc. S. Slope of Picacho Mountain.
40.00	Point for the ½ sec. cor. of secs. 26 and 27.
	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
	T8S R9E 527 S26 1970
	The cor. is located on a steep and rocky S. slope of Pichacho Mountains.
47.50	Spur, slopes S. 80° E., for 50 lks. to center of a saddle bet. two prominent rocky knolls.

Co	ompletion	Survey,	Subdivisional	Lines,	Т.	8	S.,	R.	9	Ε.

52.70 59.60 68.20 High spur, slopes S. 70° E.; thence along an E. slope. High rocky outcropping, slopes E.; desc. steep NE. slope. 75.00 Draw, drains NE. 80.00 Point for the cor. of secs. 22, 23, 26 and 27. Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S27 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. Draw, drains S. 26.50 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. Foint for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 \$23 \$23 \$24 \$25 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. Draw, drains SE., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		Completion Survey, Subdivisional Lines, T. 8 S., R. 9 E.
High spur, slopes S. 70° E.; thence along an E. slope. 88.20 Point for the cor. of secs. 22, 23, 26 and 27. Set the fron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. Jraw, drains S. Draw, drains S. 28.50 Spur, slopes S. 36.40 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. TSS R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. Draw, drains S., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	CHAINS	
High rocky outcropping, slopes E.; desc. steep NE. slope. 75.00 Draw, drains NE. Point for the cor. of secs. 22, 23, 26 and 27. Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. Jraw, drains S. Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. Jeep trail, bears irregularly SE. and NW. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23/ S26 1970 Spur, slopes S. 75.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. Draw, drains SE., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	1	
Draw, drains NE. Foint for the cor. of secs. 22, 23, 26 and 27. Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. 14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE, and NN. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains SE.; thence asc. E. slope. Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	59.60	High spur, slopes S. 70° E.; thence along an E. slope.
Point for the cor. of secs. 22, 23, 26 and 27. Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. 14.70 Draw, drains S. Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 ½ S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains SE., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	68.20	High rocky outcropping, slopes E.; desc. steep NE. slope.
Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an Iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. Draw, drains S. Spur, slopes S. 36.40 Draw, drains SE. Jeep trail, bears irregularly SE. and NW. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. Draw, drains SE., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	75.00	Draw, drains NE.
mound of stone to top, brass cap mkd. T8S R9E S22 S23 S27 S26 1970 Land, mountainous. Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. Draw, drains S. Spur, slopes S. 36.40 Draw, drains SE. Jeep trail, bears irregularly SE. and NW. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. Draw, drains SE., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	80.00	Point for the cor. of secs. 22, 23, 26 and 27.
S22 S23 S27 S26 1970		Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
Soil, rocky loam. Timber, palo verde; Undergrowth, cacti. From the cor. of secs. 23, 24, 25 and 26, monumented by an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. 14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains SE., 100 lks. to draw, draining E. The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		<u>\$22 \$23</u> \$27 \$26
an iron post 2 ins. diam., firmly set in a mound of stone, brass cap mkd. T8S R9E S23 S24 S26 S25 1913 N. 89°42' W., bet. secs. 23 and 26. Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. 14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. Jeep trail, bears irregularly SE. and NW. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 ½ S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		Soil, rocky loam.
S23 S24 S26 S25 S25 S26 S25 S26 S25 S25 S26 S25 S26 S25 S26 S25 S26 S25 S26 S26		an iron post 2 ins. diam., firmly set in a mound of stone,
Over mountainous land, through moderate undergrowth. Asc. SE. slope. 3.70 Draw, drains S. 14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23/S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		<u>\$23 \$24</u> <u>\$26 \$25</u>
Asc. SE. slope. 3.70 Draw, drains S. 14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23/S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		N. 89°42' W., bet. secs. 23 and 26.
3.70 Draw, drains S. 14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	`	Over mountainous land, through moderate undergrowth.
14.70 Draw, drains S. 28.50 Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 ½ S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		Asc. SE. slope.
Spur, slopes S. 36.40 Draw, drains SE. 38.50 Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 526 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	3.70	Draw, drains S.
Jeep trail, bears irregularly SE. and NW. Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	14.70	Draw, drains S.
Jeep trail, bears irregularly SE. and NW. 40.04 Point for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	28.50	Spur, slopes S.
Foint for the ½ sec. cor. of secs. 23 and 26. Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E ½ S23 526 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 1ks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	36.40	Draw, drains SE.
Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd. T8S R9E S23 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	38.50	Jeep trail, bears irregularly SE. and NW.
T8S R9E 1 S23 2 S26 1970 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	40.04	Point for the ½ sec. cor. of secs. 23 and 26.
\$\frac{1}{4} \frac{\frac{\frac{523}}{\frac{526}{1970}}}{\frac{526}{1970}}\$ 50.80 Spur, slopes S. 71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		l
71.50 Draw, drains S. 80° E.; thence asc. E. slope. 75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.		$\frac{1}{4} \frac{\text{S23}}{\text{S26}}$
75.80 Draw, drains SE., 100 lks. to draw, draining E. 80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	50.80	Spur, slopes S.
80.08 The cor. of secs. 22, 23, 26 and 27. Land, mountainous.	71.50	Draw, drains S. 80° E.; thence asc. E. slope.
Land, mountainous.	75.80	Draw, drains SE., 100 lks. to draw, draining E.
	80.08	The cor. of secs. 22, 23, 26 and 27.
Soil, rocky. Timber, palo verde; Undergrowth, cacti.		Soil, rocky.

Completion Survey, Subdivisional Lines, T. 8 S., R. 9 E.

CHAINS	N. 89°52' W., bet. secs. 22 and 27.
	Over mountainous land, through moderate undergrowth.
•	Asc. steep E. slope.
27.60	Spur, slopes SE.
40.16	Point for the ½ sec. cor. of secs. 22 and 27.
	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
	T8S R9E \$\frac{1}{2} \frac{\text{S22}}{\text{S27}} 1970
40.30	Draw, drains S. 60° E.
47.80	Top of Picacho Mountain, bears N. and S.; desc. over steep cliffs on W. slope.
72.30	Draw, drains N. 60° W.; asc. rocky NE. slope.
80.32	The cor. of secs. 21, 22, 27 and 28 hereinbefore described.
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	From the cor. of secs. 22, 23, 26 and 27.
	N. 0°01' W., bet. secs. 22 and 23.
	Over mountainous land, through moderate undergrowth.
٠	Asc. SE. slope.
2.30	Draw, drains S. 80° E.
9.70	Draw, drains SE.; begin asc. steep SW. slope.
25.30	Rocky spur, slopes SE., cont. asc.
39.00	Deep ravine, drains S. 70° E.
40.00	Point for the ½ sec. cor. of secs. 22 and 23.
	Set the iron post 2 ins. in the ground over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.
į	T8S_R9E
	\$22 \$23 1970
49.70	Spur, slopes S. 30° E.
57.90	Draw, drains S. 30° E.
	•

 	Completion Survey, Subdivisional Lines, T. 8 S., R. 9 E.
CHAINS	
64.40	Spur, slopes S. 30° E.; thence along an E. slope.
78.40	Draw, drains E.; thence asc. S. slope.
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
•	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
•	T8S R9E <u>S15 S14</u> S22 S23 1970
	The cor. is located on a steep S. slope.
`	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
•	From the cor. of secs. 13, 14, 23 and 24, monumented by an iron post 2 ins. diam., firmly set in a mound of stone brass cap mkd. $ \begin{array}{c ccccccccccccccccccccccccccccccccccc$
	N. 89°42' W., bet. secs. 14 and 23.
•	Over mountainous land, through moderate undergrowth.
	Desc. NW. slope.
22.20	Draw, drains N. 60° E.; asc. E. slope.
37.50	Spur, slopes SE.
40.10	Point for the ½ sec. cor. of secs. 14 and 23.
	Set the iron post 4 ins. in the ground over an "X" chiseled in solid rock, mound of stone to top, brass cap mkd.
	T8S R9E ½ <u>S14</u> 523 1970
44.60	Spur, slopes N. 70° E.
63.10	Spur, slopes SE.
80.20	The cor. of secs. 14, 15, 22 and 23.
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.

Completion :	Survey,	Subdivisional	Lines,	T.	8	S.,	R.	9	Ε.
--------------	---------	---------------	--------	----	---	-----	----	---	----

	Completion survey, Subdivisional Lines, 1. 6 5., K. 9 E.
CHAINS	N. 89°54' W., bet. secs. 15 and 22.
	Over mountainous land, through moderate undergrowth.
	Asc. E. slope.
7.40	Ridge on top of Picacho Mountain, bears N. 60° E. and S. 60° W.; thence along a N. slope.
23.70	High spur, slopes N. 30° W., from NEWMAN Peak; desc. SW. slope.
37.00	Draw, drains NW.; asc. NE. slope.
40.13	Point for the ½ sec. cor. of secs. 15 and 22.
	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
	T8S R9E ½ S15 S22 1970
	from which
	U.S.C.&G.S. Triangulation Station, NEWMAN, bears S. 75°37'45" E., 19.436 chs. dist., monumented by a brass tablet, 3 ins. diam., set in solid rock, mkd. NEWMAN 1935. Latitude 32°43'06.753" N.; Longitude 111°23'59.572" W. The station is located on Newman Peak, being the highest point on the Picacho Mountain range.
45.40	Rocky knoll on a spur, slopes NW., desc. steep W. slope along a spur sloping irregularly W.
61.70	Draw, drains NW.
80.26	The cor. of secs. 15, 16, 21 and 22, monumented by an iron post 2 ins. diam., projecting 12 ins. above ground, set in a mound of stone, brass cap mkd.
	T8S R9E S16 S15 S21 S22 1913
	This cor. is located approximately 3.00 chs. NE. of a prominent rock, 100 ft. high.
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	From the cor. of secs. 14, 15, 22 and 23.
	N. 0°01' W., bet. secs. 14 and 15.
	Over mountainous land, through moderate undergrowth.
	Asc. S. slope.

Completion	Survey.	Subdivisional	Lines	Т.	8	S	R	9 E	

	Completion Survey, Subdivisional Lines, 1. 6 S., R. 9 E.
CHAINS	
3.50	Top of Picacho Mountain, bears N. 60° E. and S. 60° W.; desc. NW. slope.
16.60	Rocky spur, slopes NW., desc. steep and ledgy N. slope.
38.50	Point selected for the witness & sec. cor. of secs. 14 and 15.
	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
	T8S R9E
	S15 [₹] S14 W C 1970
40.00	True point for the ½ sec. cor. of secs. 14 and 15, falls in a draw draining N. 10° E.; impractical to monument.
45.40	Draw, drains NW.; asc. S. slope.
61.60	Spur, slopes N. 70° W.; desc. N. slope.
73.00	Rocky spur, slopes NW.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set the iron post 4 ins. in the ground to solid rock, mound of stone to top, brass cap mkd.
·	T8S R9E S10 S11 S15 S14 1970
	from which
۰	A bearing rock, bears S. 44° E., 30 lks. dist., mkd. + BR S 14. (BR forms part of rocky ledge).
	The cor. is located 26 lks. North of a vertical ledge 15 ft. high.
3	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	From the cor. of secs. 11, 12, 13 and 14, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T8S R9E S11 S12 S14 S13 1913
	N. 89°43' W., bet. secs. 11 and 14.
	Over mountainous land, through moderate undergrowth.

Completion Survey,	Subdivisional Lin	es, T.	8 S.,	K	уE.

	Completion Bulvey, Bubalvisional Bines, 1. 6 50, 10. 9 20
CHAINS	
•	Asc. along a S. slope.
13.80	Draw, drains SE.; thence asc. E. slope.
34.50	Top of Picacho Mountain, bears N. 15° E. and S.; desc. steep W. slope.
40.01	Point for the ½ sec. cor. of secs. 11 and 14.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T8S R9E
	½ <u>S11</u> S14
	1970
67.90	Rocky outcropping, slopes NW.
75.70	Draw, drains NW.
80.02	The cor. of secs. 10, 11, 14 and 15.
	Land, mountainous.
	Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	rimber, paro verde, ondergrowth, edetr.
•	N. 89°44' W., bet. secs. 10 and 15.
	Over mountainous land, through moderate undergrowth.
	Desc. W. slope.
3.80	Draw, drains N.; asc. NE. slope.
12.50	Spur, slopes N. 10° W.
21.20	Spur, slopes N. 55° W., desc. steep ledgy W. slope.
25.70	Base of spur, bears N. and S.; desc. gradual W. slope.
40.11	Point for the ½ sec. cor. of secs. 10 and 15.
	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
	T8S R9E
	\frac{1}{4} \frac{\text{S10}}{\text{S15}} \\ 1970
45.50	Draw, drains NW.
80.00	Track road, bears irregularly SE. and NW.
80.22	The cor. of secs. 9, 10, 15 and 16, monumented by an iron post 2 ins. diam., projecting 12 ins. above the ground, set in a mound of stone, brass cap mkd.
9	
	,
l	

Completion Survey, Subdivisional Lines, T. 8 S., R. 9 E.

CHAINS	
	T8S R9E S 9 S10 S16 S15 1913
	Land, mountainous to gently rolling. Soil, rocky.
	Timber, palo verde; Undergrowth, cacti.
٠	From the cor. of secs. 10, 11, 14 and 15.
	N. 0°01' W., bet. secs. 10 and 11.
	Over mountainous land, through moderate undergrowth.
	Desc. N. slope.
2.90	Draw, drains N. 55° W.
12.80	Draw, drains W.; asc. SW. slope.
31.50	Spur, slopes N. 80° W.; desc. steep N. slope.
39.95	Main wash in a draw, 5 lks. wide, 1 ft. deep, drains W.
40.00	Point for the ½ sec. cor. of secs. 10 and 11.
	Set the iron post 8 ins. in the ground, mound of stone to top, brass cap mkd.
	T8S R9E
	\$10 \$11 1970
	Ascend SW. slope.
46.40	Spur, slopes W.; desc. NW. slope.
68.50	Wash, 20 1ks. wide, 2 ft. deep, drains S. 60° W.; asc. S. slope.
75.00	Spur, slopes S. 60° E.
78.20	Deep ravine, drains S. 60° E.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	Set the iron post over an "X" chiseled on solid rock, mound of stone to top, brass cap mkd.
	T8S R9E S 3 S 2 S10 S11 1970
	Land, mountainous.

	Completion Survey, Subdivisional Lines, T. 8 S., R. 9 E.
CHAINS	From the cor. of secs. 1, 2, 11 and 12, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T8S R9E S 2 S 1 S11 S12 1913
	N. 89°47' W., bet. secs. 2 and 11.
	Over mountainous land, through moderate undergrowth.
	Ascend E. slope of Picacho Mountains.
11.80	Draw, drains NE.
22.40	Top of Picacho Mountains, bears N. and S.; desc. W. slope.
40.23	Point for the ½ sec. cor. of secs. 2 and 11.
	Set the iron post 4 ins. in the ground mound of stone to top, brass cap mkd.
,	T8S R9E S 2 S11 1970
60.20	Draw, drains SW.; asc. SE. slope.
74.60	Spur, slopes S.
80.46	The cor. of secs. 2, 3, 10 and 11.
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
• , , ,	N. 89°41' W., bet. secs. 3 and 10:
	Over mountainous land, through moderate undergrowth.
	Ascend along SE. slope.
1.50	Ravine, drains S. 50° E.; asc. NE. slope.
5.70	Spur, slopes S. 50° E.; desc. SW. slope.
11.70	Draw, drains S.; asc. along a S. slope.
40.19	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	Set the iron post 4 ins. in the ground, mound of stone to top, brass cap mkd.
	T8S R9E

Completion Survey, Subdivisional Lines, T. 8 S., R. 9 E.

CHAINS	
45.80	Spur, slopes N. 60° E.; desc. NW. slope.
61.20	Draw, drains N. 15° W.; asc. NE. slope.
78.30	Top of ridge, bears SE. and NW.; desc. SW. slope.
80.38	The cor. of secs. 3, 4, 9 and 10, monumented by an iron post, 2 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T8S R9E S 4 S 3 S 9 S10 1913
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	From the cor. of secs. 2, 3, 10 and 11.
	N. 0°08' E., bet. secs. 2 and 3.
	Over mountainous land, through moderate undergrowth.
	Ascend steep S. slope.
22.50	Spur, slopes S. 80° W.; thence along a W. slope.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set the iron post 6 ins. in the ground, mound of stone to top, brass cap mkd.
	T8S_R9E
	s 3 s 2 1970
53.20	Spur, slopes NW.; desc. steep NE. slope.
79.56	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by an iron post, 3 ins. diam., firmly set in a mound of stone, brass cap mkd.
	T7S R9E S34 S35 S 3 S 2 T8S 1913
	Land, mountainous. Soil, rocky. Timber, palo verde; Undergrowth, cacti.
	General Description
	The area surveyed in Township 8 South, Range 9 East is located approximately 6 miles East of Picacho, Arizona

General Description T. 8 S., R. 9 E. CHAINS and is located in the Picacho Mountain Range. The elevation in the area surveyed ranges from 1,900 ft. to 4,508.ft. above sea level, being at its highest point at Newman Peak located in section 22. The land is steep and mountainous. The soil is shallow and rocky. The vegetation consists of moderate Palo Verde and cacti and scattered cat claw. A fair amount of grass is on the north slopes. The top of Newman Peak can be reached by a marked foot trail leading up the west face of the Peak. (An old airway beacon on top of Newman Peak has been removed).

Form 9180-8 (March 1969)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES		CAPACITY
Ira M. Thiessen		Cadastral Surveyor
Harry K. Smith		Surveying Aid
Andrew W. Messer		Surveying Aid
Woodrow J. Fields		Surveying Aid
Carlos Mayo		Surveying Aid
Rodney A. Carter		Surveying Aid
		<u>:</u>
	_	· .

CERTIFICATE OF SURVEY

(I) (Week), Gary T. Oviatt	, HEREBY
CERTIFY upon honor that, in pursuance of special ins	structions bearing date of the 29th day
of January , 1970 , (I) (West have ret	raced a portion of the subdivisional
lines and completed the survey of the s	ubdivisional lines of Township 8 South,
Range 9 East	
	•
of the Gila and Salt River Meridian,	in the State of Arizona , which
are represented in the foregoing field notes as having	
(xour) direction; and that said survey has been made it	
tions, the Manual of Instructions for the Survey of the	
specific manner described in the foregoing field notes	
specific mainer described in the total grand and	
,	^ ° .
	y J. Quatt
(Date)	(Cadastral Surveyor)
	(C. J. A. 1 Sumayor)
(Date)	(Cadastral Surveyor)
CERTIFICATE OF	APPROVAL
SUBMITTED FOR APPROVAL Date 1971	BUREAU OF LAND MANAGEMENT Washington, D.C.
The foregoing field notes of the retracement or	f a portion of the subdivisional lines
and the completion survey of the subdi-	visional lines of Township 8 South, Rang
9 East of the Gila and Salt River Meri	
9 East of the Gila and Salt River Meri	
9 East of the Gila and Salt River Merio	
	dian, Arizona,
executed by Gary T. Oviatt	dian, Arizona,
executed by Gary T. Oviatt having been critically examined and found correct,	dian, Arizona,
executed by Gary T. Oviatt having been critically examined and found correct,	dian, Arizona, are hereby approved. MAST Summ
executed by Gary T. Oviatt having been critically examined and found correct, 7 1972 (Date) CERTIFICATE OF	are hereby approved. Label La
executed by Gary T. Oviatt having been critically examined and found correct,	are hereby approved. **Chief, Division of Cadastral Survey)* **TRANSCRIPT* field notes of the above-described surveys in
executed by Gary T. Oviatt having been critically examined and found correct, 7 1972 (Date) CERTIFICATE OF	are hereby approved. Label La