

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 21 NORTH, RANGES 6, 7 and 8 EAST

Multiple horizontal lines for handwritten notes.

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Louis D. Gilbert, Cadastral Surveyor

Horizontal lines for signature and name.

Under special instructions dated July 1, 1970, which provided for the surveys
included under Group Number 527, approved July 1, 1970,
and assignment instructions dated July 20, 1970.

Survey commenced July 21, 19 70

Survey completed September 23, 19 70

BOOK 4967

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 21 N. R. 6 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 21 N. R. 7 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 21 N. R. 8 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 21 North, Range 6 East
 Township 21 North, Range 7 East
 Township 21 North, Range 8 East
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 1, 1970 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination is 14½° E.

Township 21 North, Range 6 East, G&SR M., Arizona
 The east boundary and subdivisional lines were surveyed in 1878 by J. L. Harris.

Remonumentation, T. 21 N., R. 6 E., Arizona

The cor. of secs. 13, 18, 19 and 24, T. 21 N., Rs. 6 and 7 E., monumented by a granite stone, 13 x 6 x 5 ins., firmly set 6 ins. in the ground, in a mound of stone, mkd. 3 notches on S. face and 3 notches on N. face (record calls for a pine post), from which the orig. bearing trees

A pine, 28 ins. diam., bears N. 17° E., 37 lks. dist., mkd. with an overgrown blaze.

A stump hole, bears S. 73° W., 70 lks. dist.

A pine, 25 ins. diam., bears N. 41° W., 82 lks. dist., mkd. with an overgrown blaze.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 14 ins. in the ground, in a mound of stone, brass cap mkd.

T21N
 R6E R7E
 S13|S18
 S24|S19
 1970

from which

A pine, 22 ins. diam., bears S. 30° E., 18 lks. dist., mkd. T21N R7E S19 BT.

A pine, 20 ins. diam., bears S. 82° W., 51 lks. dist., mkd. T21N R6E S24 BT.

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

Bury the orig. cor. stone in the mound of stone alongside the iron post.

Cor. is 2 lks. E. of a five-strand barbed wire fence bearing N. and S.

The cor. of secs. 13, 14, 23 and 24, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A pine stump, 30 ins. diam., bears S. 41° E., 110 lks. dist., no mks.

A pine, 25 ins. diam., bears S. 25° W., 28 lks. dist., mkd. with a burned blaze.

A stump hole, bears N. 80° W., 41 lks. dist.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 23 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E
 S14|S13
 S23|S24
 1970

from which

A pine, 12 ins. diam., bears N. 86° E., 41 lks. dist., mkd. T21N R6E S13 BT.

A pine, 22 ins. diam., bears S. 70° E., 69 lks. dist., mkd. T21N R6E S24 BT.

A pine, 6 ins. diam., bears N. 35° W., 76 lks. dist., mkd. X BT.

Raise a mound of stone W. of the iron post.

Cor. is S. 86° W., 8 lks. dist., from a fence cor., from which fences bear N., E. and S. 23° E.

The ¼ sec. cor. of secs. 13 and 14, reestablished by record dist. from the orig. bearing trees

A pine, 24 ins. diam., bears S. 34° E., 33 lks. dist., mkd. X.
 (Note: record bearing S. 24° E.).

A pine, 24 ins. diam., bears N. 65° W., 11 lks. dist., mkd. with an overgrown blaze.
 (Note: record bearing West).

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

T21N R6E

$\frac{1}{4}$

S14|S13

1970

Raise a mound of stone E. of the iron post.

Cor. is 1 lk. E. of a four-strand barbed wire fence bearing N. and S.

The cor. of secs. 22, 23, 26 and 27, monumented by a rotted post, set in a mound of stone, from which the orig. bearing trees

A pine, 20 ins. diam., bears N. 85° E., 24 lks. dist., mkd. NRVIEXXIII.
(Note: record dist. 6 lks.).

A pine, 20 ins. diam., bears S. 27° W., 44 lks. dist., mkd. TXXINRVIEXXVII.

A pine, 25 ins. diam., bears N. 13° W., 70 lks. dist., mkd. with an overgrown blaze.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E

S22|S23

S27|S26

1970

from which

A pine, 17 ins. diam., bears S. 50° E., 28 lks. dist., mkd. T21N R6E S26 BT.

Bury the remnants of the orig. cor. post alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, reestablished by record course and dist. from the orig. bearing trees

A burned pine stump, bears N. 20° E., 57 lks. dist., no mks.

A dead pine, 35 ins. diam., bears S. 60° W., 91 lks. dist., mkd. $\frac{1}{4}$ S.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E

$\frac{1}{4}$

S22|S23

1970

from which

Remonumentation, T. 21 N., R. 6 E., Arizona

<p>CHAINS</p>	<p>A pine, 5 ins. diam., bears S. 65° E., 11 lks. dist., mkd. X BT.</p> <hr/> <p>The ¼ sec. cor. of secs. 14 and 23, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees</p> <p style="padding-left: 40px;">A stump hole, bears S. 32° E., 90 lks. dist.</p> <p style="padding-left: 40px;">A pine, 33 ins. diam., bears N. 65° W., 57 lks. dist., mkd. with an overgrown blaze.</p> <p>At the cor. point</p> <p>Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T21N R6E ¼ $\frac{S14}{S23}$ 1970</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 30° W., 34 lks. dist., mkd. X BT.</p> <p>Raise a mound of stone N. of the iron post.</p> <hr/> <p>The ¼ sec. cor. of secs. 14 and 15, monumented by a mound of stone, verified by record course and dist. from an orig. bearing tree</p> <p style="padding-left: 40px;">A pine stump, 30 ins. diam., bears N. 10° E., 31 lks. dist., no mks.</p> <p style="padding-left: 40px;">Unable to find any evidence of the other orig. bearing tree.</p> <p>At the cor. point</p> <p>Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T21N R6E ¼ $\frac{S15}{S14}$ 1970</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 20° E., 11 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 68° W., 28 lks. dist., mkd. ¼ S15 BT.</p> <p>Cor. is 25 lks. W. of a power line bearing N. and S.</p> <hr/>
---------------	---

Remonumentation, T. 21 N., R. 6 E., Arizona

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A fallen pine, 30 ins. diam., bears N. 45° E., 81 lks. dist., mkd. $\frac{1}{4}$ S BT.

A stump hole, bears S. 48° W., 68 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E

$\frac{1}{4}$ $\frac{S15}{S22}$

1970

from which

A pine, 5 ins. diam., bears N. 22° E., 17 lks. dist., mkd. X BT.

A pine, 9 ins. diam., bears S. 50° W., 47 lks. dist., mkd. $\frac{1}{4}$ S22 BT.

Raise a mound of stone N. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 15 and 16, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A pine stump, 36 ins. diam., bears North, 62 lks. dist., no mks.

A pine stump, 32 ins. diam., bears S. 21° E., 124 lks. dist., no mks.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R6E

$\frac{1}{4}$ S16|S15

1970

from which

A pine, 9 ins. diam., bears N. 60° E., 29 lks. dist., mkd. $\frac{1}{4}$ S15 BT.

A pine, 12 ins. diam., bears S. 21° W., 8 lks. dist., mkd. $\frac{1}{4}$ S16 BT.

Remonumentation, T. 21 N., R. 7 E., Arizona

CHAINS

Township 21 North, Range 7 East, G&SR M., Arizona

The west boundary and subdivisional lines were surveyed in 1878 by J. L. Harris.

Remonumentation, T. 21 N., R. 7 E., Arizona

The $\frac{1}{4}$ sec. cor. of secs. 1 and 6, T. 21 N., Rs. 6 and 7 E., reestablished by record course and dist. from the orig. bearing trees

A pine, 27 ins. diam., bears N. 78° W., 15 lks. dist., mkd. $\frac{1}{4}$ S B.

A stump hole, bears S. 76° E., 82 lks. dist.

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N
R6E R7E
 $\frac{1}{4}$
S1|S6
1970

from which

A pine, 6 ins. diam., bears N. 50° E., 46 lks. dist., mkd. X BT.

Cor. is 7 lks. W. of a four-strand barbed wire fence bearing N. and S.

The cor. of secs. 22, 23, 26 and 27, reestablished by record course and dist. from the orig. bearing trees

A pine, 30 ins. diam., bears N. 45° E., 35 lks. dist., mkd. RVIIEXXIII.

A fallen pine, bears S. 65° E., 62 lks. dist., no mks.

A pine, 36 ins. diam., bears S. 63° W., 89 lks. dist., mkd. E XXVII.

A pine, 38 ins. diam., bears N. $66\frac{1}{2}^\circ$ W., 187 lks. dist., mkd. with an overgrown blaze.
(Note: record dist. 194 lks.)

At the cor. point

Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R7E
S22|S23
S27|S26
1970

Cor. is N. 57° W., 9 lks. dist., from a fence cor., from which fences bear E. and S. 12° W., for 20 lks. dist., thence S.

Remonumentation, T. 21 N., R. 7 E., Arizona

CHAINS

The cor. of secs. 16, 17, 20 and 21, monumented by a granite stone, 22 x 14 x 8 ins., set 4 ins. in the ground, mkd. 4 notches on E. face and 3 notches on S. face, with a + on top (record calls for a post), from which the orig. bearing trees

A pine, 25 ins. diam., bears N. 12° E., 25 lks. dist., mkd. with an overgrown blaze.

A rotted and fallen pine, bears S. 40° E., 107 lks. dist., mkd. TXXINRVIEXXI.

A pine, 25 ins. diam., bears S. 34° W., 14 lks. dist., mkd. with an overgrown blaze.

A pine, 23 ins. diam., bears N. 51° W., 205 lks. dist., mkd. TXXINRVIIE.

At the cor. point

Set the iron post, 20 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R7E
 S17|S16
 S20|S21
 1970

from which

A pine, 10 ins. diam., bears S. 60° E., 80 lks. dist., mkd. T21N R7E S21 BT.

Bury orig. cor. stone in the collar of stone alongside the iron post.

The cor. of secs. 8, 9, 16 and 17, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A pine, 32 ins. diam., bears N. 52° E., 75 lks. dist., mkd. with an overgrown blaze.

A pine stump, 20 ins. diam., bears S. 6½° W., 112 lks. dist., no mks.

A pine, 38 ins. diam., bears N. 80° W., 60 lks. dist., mkd. TXXINRVIIESVIII.

Unable to find any evidence of the other orig. bearing tree.

Remonumentation, T. 21 N., R. 7 E., Arizona

CHAINS

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T21N R7E

S 8 | S 9

S17 | S16

1970

from which

A pine, 27 ins. diam., bears S. 70° E., 51 lks. dist., mkd. T21N R7E S16 BT.

A pine, 12 ins. diam., bears S. 23° W., 25 lks. dist., mkd. X BT.

Raise a mound of stone W. of the iron post.

Cor. is N. 70° W., 5 lks. dist., from a fence cor., from which fences bear S. and W.

The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented by a granite stone, 14 x 10 x 8 ins., firmly set 6 ins. in the ground, mkd. $\frac{1}{4}$ on N. face and with a + on top, with mound of stone to the N. (record calls for a post), from which an orig. bearing tree

A pine stump, 50 ins. diam., bears N. 76° W., 85 lks. dist., no mks.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T21N R7E

$\frac{1}{4}$ S18

S19

1970

from which

A pine 10 ins. diam., bears N. 45° E., 6 lks. dist., mkd. $\frac{1}{4}$ S BT.

A pine, 16 ins. diam., bears S. 57° W., 17 lks. dist., mkd. $\frac{1}{4}$ S BT.

Remonumentation, T. 21 N., R. 7 E., Arizona

CHAINS

Rebuild the mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 18, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A pine, 27 ins. diam., bears N. 12° E., 41 lks. dist., mkd. with an overgrown blaze.

A pine stump, 30 ins. diam., bears S. 39° W., 84 lks. dist., no mks.

At the cor. point

Set the iron post, 18 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R7E

$$\frac{1}{4} \begin{array}{c} \text{S } 7 \\ \text{S } 18 \\ 1970 \end{array}$$

from which

A pine, 8 ins. diam., bears S. 36° E., 35 lks. dist., mkd. X BT.

Cor. is 2 lks. S. of an abandoned fence bearing E. and W.

The cor. of secs. 4, 5, 8 and 9, monumented by a mound of stone, verified by record course and dist. from the orig. bearing trees

A fallen pine, 26 ins. diam., bears N. 79° E., 47 lks. dist., no mks.

A rotted pine stump, bears S. 80° E., 59 lks. dist., no mks.

A fallen pine, 30 ins. diam., bears S. 84° W., 27 lks. dist., mkd. TXXINRVIIIE.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T21N R7E

$$\begin{array}{c} \text{S } 5 \mid \text{S } 4 \\ \text{S } 8 \mid \text{S } 9 \\ 1970 \end{array}$$

Remonumentation, T. 21 N., R. 7 E., Arizona

CHAINS

from which

A pine, 12 ins. diam., bears N. 62° E., 26 lks. dist., mkd. T21N R7E S4 BT.

A pine, 6 ins. diam., bears S. 79° E., 18 lks. dist., mkd. X BT.

A pine, 14 ins. diam., bears S. 30° W., 27 lks. dist., mkd. T21N R7E S8 BT.

A pine, 10 ins. diam., bears N. 49° W., 14 lks. dist., mkd. T21N R7E S5 BT.

Raise a mound of stone W. of the iron post.

Cor. is N. 14° W., 37 lks. dist., from a fence cor., from which fences bear N. and E.

Remonumentation, T. 21 N., R. 8 E., Arizona

<p>CHAINS</p>	<p>Township 21 North, Range 8 East, G&SR M., Arizona</p> <p>The subdivisional lines were surveyed in 1879 by J. L. Harris, and a portion were resurveyed in 1902 by Caudle and Caudle, who also resurveyed the east boundary.</p> <hr/> <p style="text-align: center;">Remonumentation, T. 21 N., R. 8 E., Arizona</p> <hr/> <p>The $\frac{1}{4}$ sec. cor. of secs. 19 and 24, T. 21 N., Rs. 8 and 9 E., monumented by a broken limestone, 24 x 16 x 10 ins., firmly set 8 ins. in the ground, mkd. $\frac{1}{4}$ on W. face, from which the orig. bearing trees</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears S. 85° E., 16 lks. dist., mkd. $\frac{1}{4}$ S19 BT.</p> <p style="padding-left: 40px;">A pinon, 20 ins. diam., bears S. 80° W., 28 lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p> <p>At the cor. point</p> <p>Set the iron post, 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T21N R8E R9E $\frac{1}{4}$ S24 S19 1970</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>The $\frac{1}{4}$ sec. cor. of secs. 13 and 18, T. 21 N., Rs. 8 and 9 E., monumented by a limestone, 16 x 10 x 6 ins., set in a mound of stone, mkd. $\frac{1}{4}$ on W. face, from which the orig. bearing trees</p> <p style="padding-left: 40px;">A cedar, 16 ins. diam., bears S. 55° E., 85 lks. dist., no mks.</p> <p style="padding-left: 40px;">A pinon, 22 ins. diam., bears S. 56°40' W., 150 lks. dist., mkd. $\frac{1}{4}$ S BT.</p> <p>At the cor. point</p> <p>Set the iron post, 16 ins. in the ground, in a mound of stone, brass cap mkd.</p> <p style="text-align: center;">T21N R8E R9E $\frac{1}{4}$ S13 S18 1970</p> <p>Bury the orig. cor. stone in the mound of stone alongside the iron post.</p> <hr/> <p>The cor. of secs. 23 and 24, only, monumented by a sandstone, 20 x 6 x 5 ins., firmly set 12 ins. in the ground, in a mound of stone, mkd. 1 notch on E. face and 2 notches on S. face, from which an orig. bearing tree</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears N. 79°46' W., 179 lks. dist., mkd. TXXIN.</p> <p>Unable to find any evidence of the other orig. bearing tree.</p> <p>At the cor. point</p>
---------------	---

Remonumentation, T. 21 N., R. 8 E., Arizona

<p>CHAINS</p>	<p>Set the iron post, 24 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;"> T21N R8E <u>S23 S24</u> S26 1970 </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 12° E., 127 lks. dist., mkd. T21N R8E S24 BT.</p> <p>Bury the orig. cor. stone alongside the iron post.</p> <hr/> <p>The cor. of secs. 22, 23, 26 and 27, monumented by a limestone, 18 x 14 x 6 ins., firmly set 6 ins. in the ground, in a mound of stone, mkd. 2 notches on E. face and 2 notches on S. face, from which the orig. bearing trees</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears N. 84°50' E., 30 lks. dist., mkd. with dim illegible scribe mks.</p> <p style="padding-left: 40px;">A pine, 24 ins. diam., bears S. 17° E., 75 lks. dist., mkd. NR8E.</p> <p style="padding-left: 40px;">A pine, 30 ins. diam., bears S. 17° W., 50 lks. dist., mkd. with an overgrown blaze.</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 12°08' W., 60 lks. dist., mkd. with an overgrown blaze.</p> <p>At the cor. point</p> <p>Set the iron post, 12 ins. in the ground, in a mound of stone, brass cap mkd.</p> <p style="text-align: center;"> T21N R8E <u>S22 S23</u> <u>S27 S26</u> 1970 </p> <p>Bury the orig. cor. stone in the mound of stone alongside the iron post.</p> <p>Cor. is 3 lks. W. of a four-strand barbed wire fence bearing N. and S.</p> <hr/> <p>The cor. of secs. 14, 15, 22 and 23, monumented by a sandstone, 14 x 8 x 4 ins., firmly set 8 ins. in the ground, mkd. 2 notches on E. face and 3 notches on S. face, with mound of stone to the W., from which an orig. bearing tree</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears N. 20° W., 75 lks. dist., mkd. NRVIIIEXV.</p> <p style="padding-left: 40px;">Unable to find any evidence of the other orig. bearing tree.</p> <p>At the cor. point</p> <p>Set the iron post, 22 ins. in the ground, brass cap mkd.</p>
----------------------	--

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

T21N R8E
 S15|S14
 S22|S23
 1970

from which

A pine, 14 ins. diam., bears N. 10° E., 66 lks. dist., mkd. T21N R8E S14 BT.

An oak, 4 ins. diam., bears S. 80° E., 46 lks. dist., mkd. X BT.

An oak, 10 ins. diam., bears S. 68° W., 26 lks. dist., mkd. T21N R8E S22 BT.

Rebuild the mound of stone W. of the iron post.

Bury the orig. cor. stone alongside the iron post.

Cor. is S. 35° W., 6 lks. dist., from a fence cor., from which fences bear S. and W.

The cor. of secs. 9, 10, 15 and 16, monumented by a pine post, 2 ft. long, 4 ins. squared, mkd. $\frac{1}{4}$ S. on one face, from which the orig. bearing trees

A pine stump, 24 ins. diam., bears N. 25° E., 144 lks. dist., no mks.
 (Note: record dist. 148 lks.).

A pine stump, 46 ins. diam., bears S. 56½° E., 118 lks. dist., no mks.

A pine, 36 ins. diam., bears S. 18° W., 105 lks. dist., mkd. with an overgrown blaze.
 (Note: record dist. 97 lks.).

A pine stump, 36 ins. diam., bears N. 24½° W., 221 lks., no mks.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T21N R8E
 S 9|S10
 S16|S15
 1970

from which

A pine, 12 ins. diam., bears N. 67° E., 74 lks. dist., mkd. T21N R8E S10 BT.

A pine, 30 ins. diam., bears S. 35° E., 200 lks. dist., mkd. T21N R8E S15 BT.

A pine, 25 ins. diam., bears N. 56° W., 158 lks. dist., mkd. T21N R8E S9 BT.

Raise a mound of stone W. of the iron post.

Bury the orig. cor. post alongside the iron post.

Cor. is 11 lks. E. of a four-strand barbed wire fence bearing N. and S.

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

The cor. of secs. 28 and 29 only, monumented by a limestone, 28 x 12 x 6 ins., firmly set 6 ins. in the ground, mkd. 4 notches on E. face and 2 notches on W. face, from which the orig. bearing trees

A pine, 28 ins. diam., bears N. 8° E., 107 lks. dist., mkd. with an overgrown blaze.

A pine, 23 ins. diam., bears N. 44° W., 86 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T21N R8E
S29|S28
 S32
 1970

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 29 and 30 only, monumented by a limestone, 18 x 10 x 10 ins., firmly set 12 ins. in the ground, mkd. 5 notches on E. face and 1 notch on W. face, from which the orig. bearing trees

A pine, 27 ins. diam., bears N. 57° E., 82 lks. dist., mkd. with an overgrown blaze.

A pine, 30 ins. diam., bears N. 50° W., 135 lks. dist., mkd. T21N R8E S30 BT.

At the cor. point

Set the iron post, 28 ins. in the ground, brass cap mkd.

T21N R8E
S30|S29
 S31
 1970

Raise a mound of stone N. of the iron post.

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 19, 20, 29 and 30, reestablished by record course and dist. from the orig. bearing trees

A pine, 35 ins. diam., bears N. 80° E., 120 lks. dist., mkd. with an overgrown blaze.

A pine stump, 40 ins. diam., bears S. 20° E., 123 lks. dist., no mks.

A pine, 35 ins. diam., bears S. 75° W., 167 lks. dist., mkd. with an overgrown blaze.

A pine, 40 ins. diam., bears N. 62½° W., 104 lks. dist., mkd. NRVIIIEXIX.

At the cor. point

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

Set the iron post, 22 ins. in the ground, brass cap mkd.

T21N R8E
 $\frac{S19}{S30} | \frac{S20}{S29}$
 1970

from which

A pine, 8 ins. diam., bears S. 18° E., 44 lks. dist., mkd. X BT.

The $\frac{1}{4}$ sec. cor. of secs. 19 and 30, reestablished by record course and dist. from an orig. bearing tree

A dead pine, 35 ins. diam., bears N. 18° E., 50 lks. dist., mkd. $\frac{1}{4}$ S.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T21N R8E
 $\frac{1}{4} \frac{S19}{S30}$
 1970

from which

A pine, 8 ins. diam., bears S. 85° W., 19 lks. dist., mkd. $\frac{1}{4}$ S30 BT.

Raise a mound of stone N. of the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 19 and 20, reestablished by record course and dist. from the orig. bearing trees

A pine, 30 ins. diam., bears S. 58° E., 137 lks. dist., mkd. $\frac{1}{4}$ S.

A pine stump, 30 ins. diam., bears S. 77 $\frac{1}{2}$ ° W., 78 lks. dist., no mks.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T21N R8E
 $\frac{1}{4} \frac{S19}{S20}$
 1970

from which

A pine, 12 ins. diam., bears N. 35° W., 27 lks. dist., mkd. $\frac{1}{4}$ S19 BT.

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

The $\frac{1}{4}$ sec. cor. of secs. 17 and 20, monumented by a limestone, 22 x 15 x 4 ins., set in a mound of stone, mkd. $\frac{1}{4}$ on N. face, from which the orig. bearing trees

A pine, 25 ins. diam., bears S. 50° W., 68 lks. dist., mkd. $\frac{1}{4}$ S.

A pine, 30 ins. diam., bears N. 67 $\frac{3}{4}$ ° W., 83 lks. dist., mkd. $\frac{1}{4}$ S. (record, N. 79° W.).

At the cor. point

Set the iron post, 22 ins. in the ground, brass cap mkd.

T21N R8E

$\frac{1}{4}$ $\frac{S17}{S20}$

1970

Bury the orig. cor. stone in the mound of stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 17 and 18, reestablished by record course and dist. from the orig. bearing trees

A pine stump, 20 ins. diam., bears S. 6° E., 256 lks. dist., no mks.

A pine, 37 ins. diam., bears S. 29 $\frac{1}{2}$ ° W., 74 lks. dist., mkd. $\frac{1}{4}$ S.

At the cor. point

Set the iron post, 26 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R8E

$\frac{1}{4}$ S18 | S17

1970

Cor. is S. 45° E., 62 lks. dist., from a fence cor., from which fences bear N., E. and S.

The $\frac{1}{4}$ sec. cor. of secs. 8 and 17, monumented by a mound of stone, verified by record course and dist. from an orig. bearing tree

A pine stump, 25 ins. diam., 3 ft. high, bears S. 5° E., 134 lks. dist., mkd. BT.

Unable to find any evidence of the other original bearing tree.

At the cor. point

Set the iron post, 22 ins. in the ground, in a collar of stone, brass cap mkd.

T21N R8E

$\frac{1}{4}$ $\frac{S 8}{S17}$

1970

Remonumentation, T. 21 N., R. 8 E., Arizona

CHAINS

from which

A local cor., a sandstone, 8 x 6 x 6 ins.
above ground, bears S. 34° E., 20 lks. dist.,
freshly mkd. $\frac{1}{4}$ on N. face.

A pine, 17 ins. diam., bears S. 19° W., 67 lks.
dist., mkd. T21N R8E $\frac{1}{4}$ S17 BT.

A pine, 12 ins. diam., bears N. 72° W., 49 lks.
dist., mkd. T21N R8E $\frac{1}{4}$ S8 BT.

Cor. is N. 34° W., 14 lks. dist., from a fence cor.,
from which fences bear N. 20° E., and N. 82° W.

19

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1970, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 21 North, Ranges 6, 7 and 8 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 2, 1970

(Date)

Louis D. Gilbert

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL

Date NOV 16 1970

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 21 North, Ranges 6, 7 and 8 East, all of the Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

MAY 21 1973

(Date)

Clark F. Sumner

(Chief, Division of Cadastral Survey)

~~CERTIFICATE OF TRANSCRIPT~~

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

~~(Date)~~

~~(Chief, Division of Cadastral Survey) GPO 849-626~~