

Form 9180-6  
(April 1965)  
(formerly 4-679)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

TOWNSHIP 22 NORTH, RANGES 3, 8 and 9 EAST

[Lined area for field notes]

Of the Gila and Salt River Meridian,

In the State of Arizona.

EXECUTED BY

Louis D. Gilbert, Cadastral Surveyor

[Lined area for signature and date]

Under special instructions dated July 1, 1970, which provided for the surveys  
included under Group Number 527, approved July 1, 1970,  
and assignment instructions dated July 20, 1970.

Survey commenced July 21, 1970

Survey completed September 23, 1970

BOOK 4968

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

1A

Form 9180-29  
(March 1965)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION  
CORNER MONUMENTS

Tp. 22 N. R. 3 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 22 N. R. 8 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 22 N. R. 9 E. Mer. G&SR

6	5	4	3	2	1
3	3				
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

13

Township 22 North, Range 3 East  
 Township 22 North, Range 8 East  
 Township 22 North, Range 9 East  
 Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners by agreement with the U. S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The approval of the Special Instructions on July 1, 1970 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base, with a brass cap riveted to the top.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories. The mean magnetic declination is 14½° E.

Township 22 North, Range 3 East, G&SR M., Arizona

The south boundary was resurveyed in 1941 by H. M. Muscott and C. F. Warner.

Re monumentation, T. 22 N., R. 3 E., Arizona

The ¼ sec. cor. of secs. 6 and 31, Tps. 21 and 22 N., R. 3 E., reestablished by course and dist. from reference monuments set by the Forest Service. The orig. iron post cor. was destroyed during new road construction. Before destruction, however, the road contractor had Forest Service Cadastral Surveyor Willford E. Roeder set monuments to reference the cor. point.

At the cor. point

Set the iron post, 12 ins. below the surface of the new road, brass cap mkd.

T22N R3E  
 ¼  $\frac{S31}{S6}$   
 T21N  
 1970

from which

A pine, 18 ins. diam., bears N. 86½° E., 209 lks. dist., mkd. T22N R3E ¼ S31 BT.

A pine, 8 ins. diam., bears S. 55° W., 178 lks. dist., mkd. with small x at the bottom of the tree. (This BT was marked with the concurrence of the land owner.)

Remonumentation, T. 22 N., R. 8 E., Arizona

CHAINS

Township 22 North, Range 8 East, G&SR M., Arizona

The east boundary was resurveyed in 1902 by F. B. Jacobs.

Remonumentation, T. 22 N., R. 8 E., Arizona

The cor. of secs. 1 and 12 only, on the E. bdy., monumented by a malpais stone, 14 x 10 x 8 ins., firmly set 12 ins. in the ground, mkd. 5 notches on S. face and 1 notch on N. face, from which the orig. bearing trees

A pine, 45 ins. diam., bears S. 65° W., 16 lks. dist., mkd. T22N R8E.  
 (Note: record bearing and dist., S. 38° W., 15 lks.).

A pine, 20 ins. diam., bears N. 30° W., 107 lks. dist., mkd. T22N R8E S1 BT.  
 (Note: record bearing and dist., N. 28° W., 104 lks.).

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T22N  
 R8E R9E  
 $\frac{S \ 1}{S12} | S6$   
 1970

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 22 N., R. 9 E., Arizona

CHAINS

Township 22 North, Range 9 East, G&SR M., Arizona

The subdivisional lines were surveyed in 1902 by F. B. Jacobs.

Remonumentation, T. 22 N., R. 9 E., Arizona

The cor. of secs. 5, 6, 7 and 8, monumented by a rotted pine post, 6 ins. long, 3 ins. diam., sharpened at one end, buried below the surface of the ground, no mks., from which the orig. bearing trees

A pine, 45 ins. diam., bears N. 30 3/4° E., 252 lks., mkd. with an overgrown blaze.

A pine, 40 ins. diam., bears S. 78 1/4° E., 258 lks. dist., mkd. with an overgrown blaze.

A pine, 36 ins. diam., bears S. 10 1/2° W., 119 lks. dist., mkd. T22N R.

Unable to find any evidence of the other orig. bearing tree.

At the cor. point

Set the iron post, 26 ins. in the ground, brass cap mkd.

T22N R9E  
 S6 | S5  
 S7 | S8  
 1970

Bury the orig. cor. post alongside the iron post.

The 1/4 sec. cor. of secs. 6 and 7, monumented by a pine post, 3 ins. squared, 48 ins. long, firmly set 24 ins. in the ground, mkd. 1/4 S6 on N. face and S7 on S. face, from which the orig. bearing trees

A pine, 18 ins. diam., bears S. 34 1/2° W., 40 lks. dist., mkd. with an overgrown blaze.

A pine, 28 ins. diam., bears N. 28 1/2° W., 19 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set the iron post, 24 ins. in the ground, brass cap mkd.

T22N R9E  
 1/4 S6  
 S7  
 1970

Bury the orig. cor. post alongside the iron post.

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
For Township 22 North, Range 3 East:	
Gordon Long	Cadastral Surveyor
Fred Roeder	Cadastral Surveyor
For Township 22 North, Ranges 8 and 9 East:	
Jerry Craig	Surveying Technician
Timothy Armi	Surveying Aid
Eric Eichenauer	Surveying Aid
(All U. S. Forest Service personnel)	

6

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Louis D. Gilbert, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of July, 1970, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 22 North, Ranges 3, 8 and 9 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 2, 1970 (Date) Louis D. Gilbert (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date NOV 16 1970

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 22 North, Ranges 3, 8 and 9 East, all of the Gila and Salt River Meridian, Arizona,

executed by Louis D. Gilbert, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

MAY 21 1973 (Date) Clark F. Lamm (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-826