



119

BOOK 4972

INDEX DIAGRAM

Township 7 South, Range 27 East

6	5	4	3	2	1
7	8	9	10 19	11 11	12 5
18	17 25	16 24	17 15 17	11 14 10	4 13 4
19	20 25	22 21 22	16 22 15	9 23 8	3 24 1
30	29	21 28 20	14 27 13	7 26	25
31	32	33	12 34	6 35	36

Township 7 South, Range 27 East  
Gila and Salt River Meridian, Arizona

CHAINS

The township boundaries, subdivisional lines and meanders of the Gila River were surveyed in 1875 by T. F. White. The north boundary was resurveyed in 1895 by P. Contzen. The east boundary was resurveyed in 1931 by C. E. Hunter. The south boundary, west boundary, the west 5 miles of the north boundary and a portion of the subdivisional lines were resurveyed in 1957 by D. E. Harding. A portion of the north boundary was resurveyed in 1964-67 by L. Murphy and P. Bauer. A portion of the subdivisional lines and meanders of the Gila River were resurveyed in 1965-66 by P. Bauer and R. Johnson.

The following field notes are those of a dependent resurvey of a portion of the subdivisional lines of Township 7 South, Range 27 East, Gila and Salt River Meridian, Arizona, designed to restore the corners in their true original location according to the best available evidence.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated August 24, 1970. The direction of all lines were determined by solar observation and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes. Unless described, each corner was monumented with a standard iron post, 30 inches long, 2½ inches in diameter, flanged at the base and with a brass cap riveted to the top.

The geographic position of the corner of sections 24 and 25 only, on the east boundary of the township, as determined by traverse from U.S.C.&G.S. Bench Mark W 40 located in section 12 is: Latitude 32°48'06.9" North and Longitude 109°31'38.7" West.

The mean magnetic declination was found to be 13° East.

---

Dependent Resurvey  
Portion Subdivisional Lines  
Township 7 South, Range 27 East

---

Reestablishment of the Survey  
executed by T. F. White in 1875

---

Beginning at the cor. of secs. 24 and 25 only, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., firmly set with 6 ins. projecting above ground, brass cap mkd.

T7S  
R27E R28E  
S24 | S30  
S25 |  
1931

from which

The closing cor. of secs. 19 and 30, T. 7 S.,  
R. 28 E., bears N. 0°04' E., 52 lks. dist.,

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS

monumented by an iron post 2 ins. diam.,  
firmly set with 8 ins. projecting above  
ground and with brass cap mkd.

T7S	T7S	
R27E	S19	C C
S24	S30	
	R28E	

1931

N. 89°43' W., bet. secs. 24 and 25.

Over nearly level land, through scattered undergrowth.

40.03 Point for the  $\frac{1}{4}$  sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T7S	R27E
$\frac{1}{4}$	S24
	S25

1970

60.80 Wash, 50 lks. wide, with 5 ft. banks, drains NW.

68.80 Enter same wash, drains W. from NE.

70.70 Same wash, drains SW. from E.

76.20 Same wash, drains NW. from SE.

80.06 The cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.

T7S	R27E
S23	S24
S26	S25

1970

from which

The cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp., bears S. 0°02' E., 159.71 chs. dist., monumented by an iron post 2½ ins. diam., firmly set with 5 ins. projecting above ground, mound of stone W., brass cap mkd.

T7S	R27E
S35	S36
S 2	S 1

T8S  
1957

A careful search was made for evidence of entering corners, none of which was recovered.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>Land, nearly level to gently rolling. Soil, shallow and gravelly clay loam with caliche underpan. Timber, scattered palo verde and mesquite in wash areas. Undergrowth, creosote bush, cacti and scattered grass.</p>
	<p>N. 0°17' E., bet. secs. 23 and 24.</p>
	<p>Over rolling land, through scattered undergrowth.</p>
12.20	<p>Wash, 45 lks. wide, with 6 ft. banks, drains W.</p>
20.10	<p>Wash, 15 lks. wide, 1½ ft. deep, drains S. 25° W.</p>
22.80	<p>Telephone line, bears N. 87° E. and S. 87° W.</p>
39.93	<p>Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E ¼ S23   S24 1970</p>
43.60	<p>Fence, bears S. 77°15' E. and N. 77°15' W.</p>
55.30	<p>Wash, 15 lks. wide, 1 ft. deep, drains NW.</p>
68.80	<p>Wash, 10 lks. wide, 1 ft. deep, drains N. 75° W.</p>
77.70	<p>Wash, 10 lks. wide, 1 ft. deep, drains N. 80° W.</p>
79.86	<p>The cor. of secs. 13, 14, 23 and 24, monumented by pieces of rotten wood in the center of an old mound of stone; there is no remaining evidence of the orig. bearing trees. This point is accepted as the best remaining evidence of the orig. cor. position.</p>
	<p>At the corner point</p>
	<p>Set the iron post 23 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E S14   S13 S23   S24 1970</p>
	<p>Build a mound of stone W. of the cor.</p>
	<p>Land, gently rolling. Soil, shallow and gravelly clay loam with caliche underpan. Timber, scattered palo verde and mesquite in wash areas. Undergrowth, creosote bush, cacti and scattered grass.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>From the cor. of secs. 13 and 24 only, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., firmly set with 6 ins. projecting above ground, brass cap mkd.</p> <p style="text-align: center;">                     T7S                      R27E R28E  <math>\frac{S13}{S24}</math>   S19                      1931                 </p> <p>from which</p> <p>The closing cor. of secs. 18 and 19, T. 7 S., R. 27 E., bears N. 0°02' E., 68 lks. dist., monumented by an iron post 2 ins. diam., firmly set with 8 ins. projecting above ground, mound of stone E., brass cap mkd.</p> <p style="text-align: center;">                     T7S                      R27E R28E                      S13   <math>\frac{S18}{S19}</math> C                      1931                 </p> <p>N. 89°44' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>16.00 Wash, 30 lks. wide, 2 ft. deep, drains S. 25° W.</p> <p>30.00 Wash, 30 lks. wide, 2 ft. deep, drains S. 70° W.</p> <p>39.81 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">                     T7S R27E  <math>\frac{1}{4} \frac{S13}{S24}</math>                      1970                 </p> <p>Build a mound of stone N. of the cor.</p> <p>79.62 The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, gently rolling.                      Soil, shallow and gravelly clay loam with caliche underpan.                      Timber, scattered scrub mesquite.                      Undergrowth, creosote bush, cacti and scattered grass.</p>
	<p>N. 0°01' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land.</p> <p>2.30 Track road, bears N. 75° E. and S. 75° W.</p> <p>11.10 Wash, 15 lks. wide, 1 ft. deep, drains N. 70° W.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
24.30	Wash, 15 lks. wide, 1 ft. deep, drains SW.
39.91	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E <math>\frac{1}{4}</math> S14   S13 1970</p>
61.90	Bennett Wash, 35 lks. wide, 4 ft. deep, drains W.
79.82	<p>The cor. of secs. 11, 12, 13 and 14, monumented by pieces of rotten wood in the center of an old mound of stone; there is no remaining evidence of the orig. bearing trees. This point is accepted as the best remaining evidence of the orig. cor. position.</p> <p>At the corner point</p> <p>Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E S11   S12 S14   S13 1970</p>
	<p>Land, gently rolling. Soil, shallow and gravelly clay loam with caliche underpan. Timber, scattered scrub mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>From the cor. of secs. 12 and 13 only, on the E. bdy. of the Tp., monumented by an iron post 2 ins. diam., firmly set with 10 ins. projecting above ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E R28E S12   S18 S13   1931</p>
	<p>from which</p> <p>The closing cor. of secs. 7 and 18, T. 7 S., R. 28 E., bears North, 72 lks. dist., monumented by an iron post 2 ins. diam., firmly set with 12 ins. projecting above ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E R28E S12   S 7 C S18 C 1931</p>
40.05	<p>West, bet. secs. 12 and 13.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 12 and 13, monumented by an old mound of earth and small stones; there is no remaining evidence of the orig. cor. post or the bearing tree. This point is accepted as the best remaining evidence of the orig. cor. position.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS

At the corner point

Set the iron post 24 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R27E  
 $\frac{1}{2}$   $\frac{S12}{S13}$   
 1970

West, beginning new measurement.

Over nearly level land

19.78

Point for the W 1/16 sec. cor. of secs. 12 and 13, at proportionate dist.

Set the iron post 24 ins. in the ground, brass cap mkd.

T7S R27E  
 $\frac{W 1}{16}$   $\frac{S12}{S13}$   
 1970

from which

USC&GS Bench Mark W 40, bears N. 29°21'46" W., 13.02 chs. dist., monumented by a bronze bench-mark disk set in a square concrete post projecting 6 ins. above ground and is stamped W40 1934. Latitude, 32°49'58.575" N., Longitude, 109°32'29.848" W.

Build a mound of stone N. of the cor.

39.56

The cor. of secs. 11, 12, 13 and 14.

Land, nearly level.

Soil, gravelly clay loam.

Timber, scattered scrub mesquite.

Undergrowth, scattered creosote bush and cacti.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post 2½ ins. diam., firmly set with 5 ins. projecting above ground, mound of stone W., brass cap mkd.

T7S R27E  
 $\frac{S34}{S 3} | \frac{S35}{S 2}$   
 T8S  
 1957

N. 0°01' W., bet. secs. 34 and 35.

Over rolling land, through scattered undergrowth.

32.30

Power line, bears N. 83°16' E. and S. 83°16' W.



## Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

## CHAINS

39.90 Point for the  $\frac{1}{4}$  sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R27E

$\frac{1}{4}$   
S34 | S35  
1970

55.60 Underground pipeline, bears S.  $76^{\circ}38'$  E. and N.  $76^{\circ}38'$  W., and junction of track roads bearing S.  $35^{\circ}$  E., N.  $76^{\circ}38'$  W. and N.  $15^{\circ}$  W.

79.80 Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the orig. cor.

Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R27E

S27 | S26  
S34 | S35  
1970

from which

The  $\frac{1}{4}$  sec. cor. of secs. 25 and 36, bears N.  $89^{\circ}52'$  E., 120.03 chs. dist., monumented by pieces of a rotten wooden post in an old mound of stones. This point is accepted as the best remaining evidence of the orig. cor. position.

At the corner point

Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R27E

$\frac{1}{4}$   $\frac{S25}{S36}$   
1970

A careful search was made for evidence of intervening corners, none of which was recovered.

Build a mound of stone N. of the cor.

Land, rolling.

Soil, shallow and gravelly clay loam with caliche underpan.

Timber, scattered scrub mesquite.

Undergrowth, scattered creosote bush, cacti and grass.

N.  $0^{\circ}13'$  W., bet. secs. 26 and 27.

Over rolling land, through scattered undergrowth.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
5.60	Judia Canyon wash, 20 lks. wide, 1 ft. deep, drains W.
8.40	Track road, bears S. 30° E. and N. 15° W.
12.20	Same road, bears N. 35° E. and S. 20° W.
19.80	Same road, bears S. 75° E. and N. 75° W.
22.80	Bladed road, bears N. 31° E. and S. 31° W.
39.90	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T7S R27E  <math>\frac{1}{4}</math>                  S27   S26                  1970</p>
	Build a mound of stone W. of the cor.
54.70	Fence, bears S. 64°30' E. and N. 64°30' W.
54.85	Track road, parallels fence.
58.05	U. S. Highway 70 and 666, bears S. 64°30' E. and N. 64°30' W.
61.60	Bladed road, bears S. 55° E. and N. 55° W.
61.80	Fence, parallels the bladed road.
69.50	Stock pond, 2.50 chs. diam.
72.00	Wash, 20 lks. wide, 2 ft. deep, drains S. 85° W.
75.30	San Jose Wash, 90 lks. wide, 2 ft. deep, drains N. 80° W.
79.80	Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post 24 ins. in the ground, brass cap mkd.
	<p>T7S R27E                  S22   S23                  S27   S26                  1970</p>
	Build a mound of stone W. of the cor.
	<p>Land, rolling.                  Soil, gravelly clay loam.                  Timber, mesquite and palo verde along the wash areas.                  Undergrowth, scattered creosote bush, cacti and grass.</p>
	From the cor. of secs. 23, 24, 25 and 26.
	S. 89°56' W., bet. secs. 23 and 26.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	Over gently rolling land, through scattered undergrowth.
24.60	Track road, bears N. 5° E. and S. 5° W.
40.05	Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R27E ¼ $\frac{S23}{S26}$ 1970
59.40	Wash, 40 lks. wide, with 3 ft. banks, drains S.
68.70	Track road, bears S. 5° E. and N. 5° W.
80.10	The cor. of secs. 22, 23, 26 and 27.
	Land, gently rolling. Soil, gravelly clay loam. Timber, mesquite and palo verde along wash areas. Undergrowth, scattered creosote bush, cacti and grass.
	N. 0°20' E., bet. secs. 22 and 23.
	Over gently rolling land, through scattered undergrowth.
4.90	Wash, 30 lks. wide, 1 ft. deep, drains SW.
14.20	Telephone line, bears N. 78°30' E. and S. 78°30' W.
39.90	Point for the ¼ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	T7S R27E ¼ $\frac{S22}{S23}$ 1970
40.35	Jeep road, bears S. 60° E. and NW.
41.50	Jeep road, bears S. 30° E. and N. 30° W.
46.40	Wash, 30 lks. wide, 2 ft. deep, drains N. 30° W.
48.00	Wash, 40 lks. wide, 1 ft. deep, drains NW.
61.80	Fence, bears S. 77°15' E. and N. 77°15' W.
66.00	Track road, bears S. 80° E. and N. 85° W.
79.80	The cor. of secs. 14, 15, 22 and 23, monumented by pieces of rotten wood in the center of an old mound of stone.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>from which the remains of the original bearing trees:</p> <p>A mesquite stump, 4 ins. diam., bears S. 70° W., 178 lks. dist.</p> <p>A mesquite stump, 8 ins. diam., bears N. 60° W., 326 lks. dist.</p> <p>A mesquite stump, 3 ins. diam., bears N. 32° W., 69 lks. dist.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R27E  <math>\frac{S15}{S22}   \frac{S14}{S23}</math>                      1970</p> <p>Build a mound of stone W. of the cor.</p> <p>Land, gently rolling.                      Soil, gravelly clay loam.                      Timber, scattered scrub mesquite and with palo verde and mesquite along wash areas.                      Undergrowth, scattered creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>S. 89°52' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>3.00 Track road, bears N. 75° E. and S. 75° W.</p> <p>3.70 Wash, 40 lks. wide, 2 ft. deep, drains NW.</p> <p>16.40 Wash, 25 lks. wide, 3 ft. deep, drains NW.</p> <p>39.99 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T7S R27E  <math>\frac{1}{4} \frac{S14}{S23}</math>                      1970</p> <p>Build a mound of stone N. of the cor.</p> <p>65.60 Wash, 25 lks. wide, 2 ft. deep, drains NW.</p> <p>79.98 The cor. of secs. 14, 15, 22 and 23.</p> <p>Land, gently rolling.                      Soil, gravelly clay loam.                      Timber, scattered scrub mesquite and palo verde.                      Undergrowth, scattered creosote bush, cacti and grass.</p>

## Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>N. 0°03' W., bet. secs. 14 and 15.</p> <p>Over gently rolling land, through scattered undergrowth.</p> <p>12.50 Wash, 20 lks. wide, 1 ft. deep, drains N. 60° E. for 2.00 chs., thence curves to N. 30° W.</p> <p>16.80 Same wash, drains N. 30° W.</p> <p>31.60 Wash, 25 lks. wide, 2 ft. deep, drains W.</p> <p>39.80 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 15 ins. in the ground, mound of stone to top, brass cap mkd.</p> <p style="text-align: center;">T7S R27E <math>\frac{1}{4}</math> S15   S14 1970</p>
	<p>44.00 Bennett Wash, 15 lks. wide, 1 ft. deep, drains S. 80° W., curving SW.</p>
	<p>79.60 The cor. of secs. 10, 11, 14 and 15, monumented by a piece of rotten post, 3 ins. square, 1 ft. long, found 8 ins. under the surface of the ground, alongside an open iron pipe, 2 ins. diam., 36 ins. long, set in a mound of stone. This position has long been used by local surveyors and is accepted as the best remaining evidence of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <p style="text-align: center;">T7S R27E <u>S10   S11</u> <u>S15   S14</u> 1970</p> <p>Bury the piece of rotten post and set the open iron pipe alongside the iron post.</p> <p>Build a mound of stone W. of the cor.</p> <p>Land, gently rolling. Soil, gravelly clay loam. Timber, mesquite and palo verde along wash areas. Undergrowth, scattered creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°55' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>16.50 Track road, bears N. 15° E. and S. 15° W.</p>

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
40.10	<p>The <math>\frac{1}{4}</math> sec. cor. of secs. 11 and 14, monumented by small pieces of rotten wood found below the surface of a low mound of earth and small stones. This is accepted as the best remaining evidence of the position of the orig. cor.</p>
	<p>At the corner point</p>
	<p>Set the iron post 21 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E  <math>\frac{1}{4}</math> <u>S11</u>                S14          1970</p>
	<p>S. 89°10' W., beginning new measurement.</p>
	<p>Over nearly level land, through scattered undergrowth.</p>
39.92	<p>The cor. of secs. 10, 11, 14 and 15.</p>
	<p>Land, nearly level.          Soil, gravelly clay loam.          Timber, widely scattered scrub mesquite.          Undergrowth, scattered creosote bush, cacti and grass.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set with 5 ins. projecting above ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E  <u>S33</u>   <u>S34</u>          S 4   S 3          T8S          1957</p>
	<p>N. 0°13' W., bet. secs. 33 and 34.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
22.60	<p>Power line, bears N. 83°16' E. and S. 83°16' W.</p>
39.88	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p>
	<p>Set the iron post 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E  <math>\frac{1}{4}</math>  <u>S33</u>   <u>S34</u>          1970</p>
	<p>Build a mound of stone W. of the cor.</p>
48.10	<p>Gully, 25 lks. wide, with 13 ft. walls, drains S. 30° W.</p>
67.50	<p>Track road, bears S. 80° E. and N. 80° W.</p>

## Dep. Res., Portion Subdivisional Lines; T. 7 S., R. 27 E.

CHAINS					
70.90	Wash, 10 lks. wide, 2 ft. deep, drains NW.				
76.50	Track road, bears S. 30° E. and N. 30° W.				
79.76	<p>The cor. of secs. 27, 28, 33 and 34, determined by the remains of the original bearing tree.</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., blazed and with illegible scribe marks, bears S. 63°30' W., 105 lks. dist.</p> <p>At the corner point</p> <p>Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R27E</p> <table style="margin: auto;"> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S28</td><td style="padding: 0 5px;">S27</td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S33</td><td style="padding: 0 5px;">S34</td></tr> </table> <p>1970</p> </div> <p>Build a mound of stone W. of the cor.</p> <p>Land, gently rolling.</p> <p>Soil, shallow and gravelly clay loam, with caliche underpan.</p> <p>Timber, scattered mesquite.</p> <p>Undergrowth, scattered creosote bush, cacti and grass.</p>	S28	S27	S33	S34
S28	S27				
S33	S34				
<hr/>					
From the cor. of secs. 26, 27, 34 and 35.					
West, bet. secs. 27 and 34.					
Over gently rolling land, through scattered undergrowth.					
5.10	Graded road, bears S. 30° E. and N. 30° W.				
17.90	Wash, 8 lks. wide, 1 ft. deep, drains NW.				
40.07	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R27E</p> <table style="margin: auto;"> <tr><td style="border-right: 1px solid black; padding: 0 5px;"><math>\frac{1}{4}</math> S27</td><td style="padding: 0 5px;"></td></tr> <tr><td style="border-right: 1px solid black; padding: 0 5px;">S34</td><td style="padding: 0 5px;"></td></tr> </table> <p>1970</p> </div>	$\frac{1}{4}$ S27		S34	
$\frac{1}{4}$ S27					
S34					
44.40	Wash, 12 lks. wide, 1 ft. deep, drains NW.				
56.20	Wash, 15 lks. wide, 2 ft. deep, drains NW.				
62.80	Wash, 20 lks. wide, 1 ft. deep, drains S. 65° W.				
71.30	Power line, bears N. 7°20' E. and S. 7°20' W.				
77.00	Track road, bears S. 61° E. and N. 61° W.				
77.50	Underground pipeline, bears S. 60°58' E. and N. 60°58' W.				
80.14	The cor. of secs. 27, 28, 33 and 34.				

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>Land, gently rolling. Soil, shallow &amp; gravelly clay loam, with caliche underpan. Timber, scattered scrub mesquite. Undergrowth, scattered creosote bush and cacti.</p>
	<p>N. 0°11' W., bet. secs. 27 and 28.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
1:44	Underground pipeline, bears S. 60°58' E. and N. 60°58' W.
1.70	Track road, parallels pipeline.
9.00	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W.
19.90	Wash, 60 lks. wide, 2 ft. deep, drains NW.
33.20	Judia Canyon wash, 15 lks. wide, 1 ft. deep, drains SW., curving W.
38.27	Fence, bears E. and W.
40.12	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 19 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T7S R27E ¼ S28   S27 1970</p>
54.50	Track road, bears S. 87° E. and N. 87° W.
77.64	Telephone line, bears N. 78°31' E. and S. 78°31' W.
80.24	The cor. of secs. 21, 22, 27 and 28, monumented by a stake, 1 x 2 ins. squared, 12 ins. long, set in a mound of stone and with a 2 x 4 in. pole lying alongside. This point has been used by local surveyors and is accepted as the best existing evidence of the position of the original corner.
	At the corner point
	Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T7S R27E S21   S22 S28   S27 1970</p>
	Deposit the squared stake and 2 x 4 in. pole alongside the iron post.
	<p>Land, gently rolling. Soil, gravelly clay loam. Timber, scattered scrub mesquite. Undergrowth, scattered creosote bush and cacti.</p>



## Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	From the cor. of secs. 22, 23, 26 and 27.
	N. 89°52' W., bet. secs. 22 and 27.
	Over gently rolling land, through scattered undergrowth.
5.40	Wash, 12 lks. wide, 2 ft. deep, drains SW.
14.60	Enter San Jose Wash area, bears S. 70° E. and N. 70° W.
17.70	San Jose Wash, 90 lks. wide, 3 ft. deep, drains N. 60° W.
28.30	Leave San Jose Wash area, bears SE. and NW.
35.00	Wash, 30 lks. wide, 2 ft. deep, drains N. 25° E.
40.04	The $\frac{1}{4}$ sec. cor. of secs. 22 and 27, monumented by the rotten remains of a wooden post found in the center of an old mound of earth and stone. This is accepted as the best remaining evidence of the position of the orig. cor.
	At the corner point
	Set the iron post 19 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R27E $\frac{1}{4}$ $\frac{S22}{S27}$ 1970
	Build a mound of stone N. of the cor.
	_____
	N. 89°17' W., beginning new measurement.
2.67	Fence, bears S. 69°30' E. and N. 69°30' W.
3.10	Track road, parallels fence.
11.30	U. S. Highway 70 and 666, bears S. 69°30' E. and N. 69°30' W.
16.60	Wash, 12 lks. wide, with 5 ft. banks, drains N. 25° W.
17.70	Wash, 25 lks. wide, 2 ft. deep, drains N. 25° E.
18.80	Track road, bears S. 69°30' E. and N. 69°30' W.
19.00	Fence, parallels track road.
21.00	Power line, bears N. 7°20' E. and S. 7°20' W.
27.80	Telephone line, bears N. 78°31' E. and S. 78°31' W.
40.08	The cor. of secs. 21, 22, 27 and 28.
	Land, gently rolling. Soil, gravelly clay loam. Timber, scattered scrub mesquite and with palo verde and mesquite along major wash areas. Undergrowth, scattered creosote bush, cacti and grass.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	N. 0°28' E., bet. secs. 21 and 22.
	Over gently rolling land, through scattered undergrowth.
11.50	Fence, bears S. 57° E. and N. 57° W.
11.65	Track road, parallels fence.
16.10	U. S. Highway 70 and 666, bears S. 57° E. and N. 57° W.
18.50	Track road, parallels highway.
18.75	Fence, parallels highway.
31.60	San Jose Wash, 340 lks. wide, 3 ft. deep, drains irreg. W.
34.30	Track road, bears S. 43° E. and N. 43° W.
36.30	Wash, 25 lks. wide, with 6 ft. banks, drains N. 65° W.
39.50	The ¼ sec. cor. of secs. 21 and 22, monumented by the remains of the orig. cor. post set in a mound of earth and stone.
	At the corner point
	Set the iron post 22 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T7S R27E  <math>\frac{1}{2}</math>                      S21   S22                      1970</p>
	Bury the remains of the orig. cor. post alongside the iron post.
	Build a mound of stone W. of the cor.
	<hr style="width: 20%; margin: auto;"/>
	N. 0°15' E., beginning new measurement.
10.00	Wash, 60 lks. wide, 3 ft. deep, drains W.
39.86	Fence, bears S. 77°15' E. and N. 77°15' W. for 14 lks., thence bears W.
40.04	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 22 ins. in the ground, in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T7S R27E                      S16   S15                      S21   S22                      1970</p>
	Land, gently rolling.
	Soil, shallow and gravelly clay loam.
	Timber, mesquite and palo verde along major wash areas.
	Undergrowth, scattered creosote bush, cacti and grass.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
40.09	<p>From the cor. of secs. 14, 15, 22 and 23.                      S. 89°57' W., bet. secs. 15 and 22.                      Over nearly level land, through scattered undergrowth.                      The ¼ sec. cor. of secs. 15 and 22, monumented by an iron post 2½ ins. diam., firmly set with 6 ins. projecting above ground and with mound of stone N., brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E                      ¼ <math>\frac{S15}{S22}</math>                      1966</p>
	<p>N. 89°40' W., beginning new measurement.</p>
11.50	<p>Power line, bears N. 7°20' E. and S. 7°20' W.</p>
40.01	<p>The cor. of secs. 15, 16, 21 and 22.                      Land, nearly level.                      Soil, shallow clay loam.                      Timber, none.                      Undergrowth, scattered creosote bush and cacti.</p>
	<p>North, bet. secs. 15 and 16.</p>
	<p>Over gently rolling land, through scattered undergrowth.</p>
15.90	<p>Wash, 10 lks. wide, 1 ft. deep, drains S. 65° W.</p>
32.10	<p>Track road, bears N. 50° E. and S. 50° W.</p>
32.50	<p>Underground aqueduct, bears N. 50° E. and S. 50° W.</p>
36.50	<p>Track road, bears irreg. SE. and NW.</p>
40.35	<p>The ¼ sec. cor. of secs. 15 and 16, monumented by an open iron pipe, 1 in. diam., 21 ins. long, projecting 9 ins. above ground, in a collar of stone. Found fragments of rotten wood 6 to 18 ins. deep alongside the iron pipe. This corner point has long been used by local surveyors and is accepted as the best available evidence of the position of the orig. cor.</p>
	<p>At the corner point</p>
	<p>Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.</p>
	<p style="text-align: center;">T7S R27E                      ¼ <math>\frac{S16}{S15}</math>                      1970</p>
	<p>Bury the open iron pipe and rotten wood fragments alongside the iron post.</p>

Dep. Res., Portion Subdivisional Lines, T. 7-S., R. 27 E.

CHAINS	
	Build a mound of stone W. of the cor.
	_____
	N. 0°08' E., beginning new measurement.
9.00	Corral fence, bears N. 48° E. and S. 48° W.
11.80	Corral fence, bears S. 21° E. and N. 21° W.
12.00	Track road, bears S. 43° E. and N. 43° W.
18.91	Power line, bears N. 44°30' E. and S. 44°30' W.
19.01	Track road, bears N. 85° E. and S. 85° W.
19.61	Old highway to Clifton, bears N. 44°30' E. and S. 44°30' W.
19.75	Point for the N 1/16 sec. cor. of secs. 15 and 16, at proportionate dist., falls near north edge of the old highway to Clifton.
	Set a railroad spike flush with the surface of the road, top of spike mkd.
	T7S R27E N $\frac{1}{16}$ S16   S15 .1970
	from which
	An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 100 lks. dist., with brass cap mkd. T7S R27E R M 66 ft 1970 and an arrow pointing to the cor.
	An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 0°08' E., 100 lks. dist., with brass cap mkd. T7S R27E R M 66 ft 1970 and an arrow pointing to the cor.
20.95	Track road, bears N. 35° E. and S. 35° W.
30.84	San Jose Canal, 30 lks. wide, 8 ft. deep, flows SW.
33.20	Track road, bears N. and SW.
36.60	Wash, 25 lks. wide, 2 ft. deep, drains S. 10° E.; track road bears N. 10° W. and S.
39.50	The cor. of secs. 9, 10, 15 and 16, monumented by an iron pipe, 2½ ins. diam., projecting 8 ins. above ground, with brass cap mkd.
	T7S R27E S 9   S10 S16   S15 CBS 1960

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>This corner monument was set by G. B. Smith, a city engineer for Safford, Arizona, and is accepted as the best available evidence of the original corner position.</p> <p>Land, gently rolling. Soil, gravelly clay loam. Timber, widely scattered scrub mesquite. Undergrowth, scattered creosote bush, cacti and grass.</p> <hr/> <p>From the cor. of secs. 10, 11, 14 and 15. N. 89°31' W., bet. secs. 10 and 15. Over nearly level land, through scattered undergrowth.</p>
0.35	Newly graded road, bears N. and W., thence along N. edge of same road extending W.
23.90	Underground aqueduct, bears NE. and SW.
26.00	Same road, bears E., S. and W.
33.70	Bladed road, bears SE. and N. 20° W.
39.80	Power line, bears S. 58° E. and N, 58° W.
40.06	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented by an unmarked stone, 12 x 14 x 15 ins., firmly set in a collar of stone. This position has long been recognized by local surveying firms and adjacent landowners and is accepted as the best available evidence of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R27E</p> <p>1/4 <math>\frac{S10}{S15}</math></p> <p>1970</p> </div> <p>The cor. is located 25. lks. N. of a bladed road bearing E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°50' W., beginning new measurement.</p>
1.47	Power line, bears N. 11°30' E. and S. 11°30' W.
15.80	Edge of mesa, bears NE. and SW., desc. NW. slope.
19.935	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15, at proportionate dist.</p> <p>Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.</p>

CHAINS		
	<p>T7S R27E</p> <p>W <math>\frac{1}{16}</math>      <math>\frac{S10}{S15}</math></p> <p>                    1970</p>	
20.64	Old highway to Clifton, bears N. 44°30' E. and S. 44°30' W.	
21.84	Power line, parallels highway.	
21.92	Fence, parallels highway.	
28.20	San Jose Canal, 30 lks. wide, 9 ft. deep, flows S. 40° W.	
28.70	Enter cultivated field, bears N. 40° E. and S. 40° W.	
39.87	The cor. of secs. 9, 10, 15 and 16.	
	<p>Land, nearly level to rolling.</p> <p>Soil, gravelly clay loam excepting the W. 11.00 chs., which is a rich sandy loam.</p> <p>Timber, none, excepting mesquite along San Jose Canal.</p> <p>Undergrowth, scattered creosote bush and cacti.</p>	
	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°58' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land.</p>	
1.70	Track road, bears SE. and NW.	
12.80	Wash, 20 lks. wide, 2 ft. deep, drains NW.	
18.90	Track road, bears S. 15° E. and N. 15° W.	
25.30	Wash, 15 lks. wide, 2 ft. deep, drains SW.	
39.73	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 33 at proportionate dist.; there is no remaining evidence of the original cor.	
	Set the iron post 18 ins. in the ground and in a collar of stone, brass cap mkd.	
	<p>T7S R27E</p> <p><math>\frac{1}{4}</math>      <math>\frac{S28}{S33}</math></p> <p>                    1970</p>	
57.30	Wash, 30 lks. wide, 2 ft. deep, drains S.	
78.80	Wash, 15 lks. wide, 3 ft. deep, drains SW.	
79.46	The cor. of secs. 28, 29, 32 and 33, monumented by an iron post 2 $\frac{1}{2}$ ins. diam., firmly set, projecting 8 ins. above ground, brass cap mkd.	

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS

T7S R27E  
S29 | S28  
S32 | S33  
 1957

Original mound of stone W. of cor.

Land, gently rolling.  
 Soil, gravelly clay loam.  
 Timber, widely scattered mesquite.  
 Undergrowth, scattered creosote bush, cacti and grass.

From the cor. of secs. 28, 29, 32 and 33.

N. 0°15' W., bet. secs. 28 and 29.

Over gently rolling land, through scattered undergrowth.

- 1.10 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 3.00 Wash, 20 lks. wide, 2 ft. deep, drains SW.
- 9.20 Haekel Road, bears N. 44°44' E. and S. 44°44' W.
- 34.50 Underground pipeline, bears S. 80° E. and N. 80° W.
- 34.60 Underground pipeline access road, parallels underground pipeline.
- 39.78 Point for the  $\frac{1}{4}$  sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.  
 Set the iron post 18 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R27E  
 $\frac{1}{4}$   
S29 | S28  
 1970

- 61.50 Telephone line, bears N. 78°31' E. and S. 78°31' W.
- 62.50 Judia Canyon wash, 35 lks. wide, 3 ft. deep, drains W.
- 64.80 Fence, bears S. 85° E. and N. 85° W.
- 79.56 The cor. of secs. 20, 21, 28 and 29, monumented by pieces of rotten wood found in the center of a low mound of earth and stone. This cor. point has been used by local surveyors and is accepted as the best available evidence of the position of the orig. cor.  
 At the corner point  
 Set the iron post 20 ins. in the ground, in a collar of stone, brass cap mkd.

T7S R27E  
S20 | S21  
S29 | S28  
 1970

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>Land, gently rolling. Soil, shallow and gravelly clay loam. Timber, scattered scrub mesquite. Undergrowth, scattered creosote bush and cacti.</p> <hr/> <p>From the cor. of secs. 21, 22, 27 and 28. S. 89°33' W., bet. sec's. 21 and 28. Over gently rolling land, through scattered undergrowth.</p>
9.70	Haekel Road, in approx. center of a 993.5 ft. curve to N. 28°14'30" E. and S. 44°44' W.
19.60	Wash, 15 lks. wide, 2 ft. deep, drains N. 25° W.
24.80	Track road, bears SE. and NW.
30.60	Old bulldozer road, bears S. 40° E. and N. 40° W.
39.58	<p>The ¼ sec. cor. of secs. 21 and 28, monumented by pieces of rotten wood in the center of a low mound of earth and small stones, and is accepted as the best available evidence of the position of the orig. cor.</p> <p>At the corner point</p> <p>Set the iron post 16 ins. in the ground, mound of stone to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R27E</p> <p>¼ <math>\frac{S21}{S28}</math></p> <p>1970</p> </div> <hr/> <p>S. 89°30' W., beginning new measurement.</p>
4.40	Track road, bears S. 43° E. and N. 43° W.
39.98	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, gently rolling. Soil, shallow and gravelly clay loam with caliche underpan. Timber, widely scattered scrub mesquite. Undergrowth, scattered creosote bush and cacti.</p> <hr/> <p>N. 0°42' E., bet. secs. 20 and 21. Over gently rolling land, through scattered undergrowth.</p>
7.70	Underground pipeline, bears N. 20° E. and S. 20° W.
20.145	Point for the S 1/16 sec. cor. of secs. 20 and 21 at proportionate dist.



## Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	Set the iron post, 16 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R27E</p>
	<p style="text-align: center;">S <math>\frac{1}{16}</math></p>
	<p style="text-align: center;">S20 S21</p>
	<p style="text-align: center;">1970</p>
21.80	Wash, 15 lks. wide, 2 ft. deep, drains SW.
40.29	The $\frac{1}{2}$ sec. cor. of secs. 20 and 21, marked by an open iron pipe, 1 in. diam., projecting 6 ins. above the ground; this cor. has long been used by local surveyors and was attested to by a long time resident of adjacent property, accepted as best remaining evidence of orig. cor. position.
	At the corner point
	Set the iron post 18 ins. in the ground over the open pipe, and in a collar of stone, brass cap mkd.
	<p style="text-align: center;">T7S R27E</p>
	<p style="text-align: center;"><math>\frac{1}{2}</math></p>
	<p style="text-align: center;">S20 S21</p>
	<p style="text-align: center;">1970</p>
	<hr style="width: 20%; margin: auto;"/>
	N. 0°12' W., beginning new measurement.
18.745	Point selected for the witness N 1/16 sec. cor. of secs. 20 and 21 falls under a power line, bears N. 48° E. and S. 48° W.
	Set the iron post 14 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T7S R27E</p>
	<p style="text-align: center;">N <math>\frac{1}{16}</math></p>
	<p style="text-align: center;">S20 S21</p>
	<p style="text-align: center;">W C</p>
	<p style="text-align: center;">1970</p>
19.935	True point for the N 1/16 sec. cor. of secs. 20 and 21 at proportionate dist. falls in the S. lane of U. S. Highway 70 and 666, where the cor. position would be impracticable to monument.
20.21	Left turn divider near center of U. S. Highway 70 and 666 for east-bound traffic.
27.10	Enter E. edge of cultivated land, bears N. and W.
39.10	Leave cultivated land, bears S. and W.
39.50	Farm road, bears E. and W.
39.87	The cor. of secs. 16, 17, 20 and 21, marked by the original wooden post, 3½ ins. square, 30 ins. long, with faint scribe mks. found wired upright in a N-S fenceline, 2 lks. N. of a cor. of fences extending N. and W. This cor. position has long been used by local surveyors and was attested to by a long time resident of adjacent property; not remonumented.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	<p>Land, gently rolling to nearly level.                      Soil, shallow and gravelly clay loam in S. <math>\frac{3}{4}</math> mile; sandy loam in N. <math>\frac{1}{4}</math> mile.                      Timber, none.                      Undergrowth, scattered creosote bush and cacti.</p>
	<p>From the cor. of secs. 15, 16, 21 and 22.                      West, bet. secs. 16 and 21.                      Over gentle rolling land, along fence bearing W.</p>
7.60	Wash, 20 lks. wide, 2 ft. deep, drains N. 20° W.
39.90	Point for the $\frac{1}{4}$ sec. cor. of secs. 16 and 21 at proportionate dist.; there is no remaining evidence of the orig. cor.  Set the iron post 20 ins. in the ground, a collar of stone to top, brass cap mkd.
	<p>T7S R27E  <math>\frac{1}{4}</math> <math>\frac{S16}{S21}</math>                      1970</p>
48.30	Wash, 35 lks. wide, 6 ft. deep, drains NW.
53.30	San Jose Wash, 110 lks. wide, 8 ft. banks, drains NW.
56.65	Fence cor.; fence bears E. and S. 42° W.
58.20	Old highway to Clifton, bears NE. and SW.
59.00	Fence cor.; fence bears N. 42° E. and W.
59.85	Point for the W 1/16 sec. cor. of secs. 16 and 21 at proportionate dist.  Set the iron post 24 ins. in the ground, collar of stone to top, brass cap mkd.
	<p>T7S R27E                      W 1/16 <math>\frac{S16}{S21}</math>                      1970</p>
79.10	Fence cor.; fence bears E. and N.; power line, bears N. and S.
79.50	County road, bears N. and S.
79.80	The cor. of secs. 16, 17, 20 and 21.  Land, gently rolling. Soil, sandy loam and rocky. Undergrowth, creosote bush and catclaw. Timber, mesquite.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS	
	From the cor. of secs. 20, 21, 28 and 29.
	N. 89°47' W., bet. secs. 20 and 29.
	Over gently rolling land, through scattered undergrowth.
2.60	Underground pipeline, bears N. 20° E. and S. 20° W.
39.82	Point for the ½ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.
	Set the iron post 16 ins. in the ground, in a collar of stone, brass cap mkd.
	T7S R27E
	½ $\frac{S20}{S29}$
	1970
49.10	Fence, bears S. 47° E. and N. 47° W.
73.80	Judia Canyon wash, 40 lks. wide, 2 ft. deep, drains NW.
79.64	The cor. of secs. 19, 20, 29 and 30, monumented by an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, mound of stone W., brass cap mkd.
	T7S R27E
	S19   S20
	S30   S29
	1957
	Land, gently rolling.
	Soil, shallow and gravelly clay loam.
	Timber, widely scattered scrub mesquite.
	Undergrowth, scattered creosote bush, cacti and grass.
	From the cor. of secs. 16, 17, 20 and 21.
	S. 89°52' W., bet. secs. 17 and 20.
	Over nearly level land.
8.85	San Jose Canal, 30 lks. wide, 8 ft. deep, flows S. 35° W.
14.10	Enter cultivated land, bears N. and S.
39.87	Point for the ½ sec. cor. of secs. 17 and 20, at proportionate dist., falls on cultivated land; there is no remaining evidence of the orig. cor.; not remonumented.
40.20	Irrigation ditch, 10 lks. wide, 3 ft. deep, drains N.
59.18	Fence, bears N. and S.
59.40	Farm road, bears N. and S.
59.53	Fence, bears N. and S.
79.30	Leave cultivated land, bears N. and S.

Dep. Res., Portion Subdivisional Lines, T. 7 S., R. 27 E.

CHAINS

79.74

Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; not monumented.

from which

The cor. of secs. 19, 20, 29 and 30, bears S. 0° 07' W., 79.68 chs. dist., previously described.

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by a brass tablet set in concrete 6 ins. below the surface on the N. shoulder of U. S. Highway 70 and 666, bears N. 89°44' W., 78.78 chs. dist., brass tablet mkd.

T7S  
R26E R27E  
S13 | S18  
S24 | S19  
1957

The S. 1/16 sec. cor. of secs. 7 and 8, bears N. 0°03' W., 99.60 chs. dist., monumented by an iron post 2½ ins. diam., firmly set with 8 ins. projecting above ground, mound of stone W., brass cap mkd.

T7S R27E.  
S  $\frac{1}{16}$   
S 7 | S 8  
1966

A careful search was made for evidence of intervening corners, none of which was recovered.

Land, nearly level.  
Soil, sandy loam.  
Timber, none.  
Undergrowth, none.

General Description

Township 7 South, Range 27 East, is located east of Solomon, Arizona. The portion of this township covered by this survey is mostly gently rolling mesa land. The soil is predominately a shallow clay loam, with a caliche underpan. Scrub mesquite, creosote bush, cacti and scattered grass is the main vegetation. Palo verde and mesquite trees are found along the major wash areas. The elevation ranges from about 2,980 ft. above sea level along the Gila River bottom land, to about 3,460 ft. above sea level in the southeast portion of the township. There was no evidence of mining in the area covered by this survey. U. S. Highway 70 and 666 traverses through the township and numerous track roads were found in the area surveyed.



28

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul G. Bauer, \_\_\_\_\_, HEREBY  
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 24th day  
 of August \_\_\_\_\_, 1970, (I) ~~(We)~~ have dependently resurveyed a  
 portion of the subdivisional lines of Township 7 South, Range 27 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
 are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my)  
~~(our)~~ direction; and that said survey has been made in strict conformity with said special instruc-  
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in  
 specific manner described in the foregoing field notes.

November 18, 1970  
 \_\_\_\_\_  
 (Date)

*Paul G. Bauer*  
 \_\_\_\_\_  
 (Cadastral Surveyor)

\_\_\_\_\_  
 (Date)

\_\_\_\_\_  
 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

**SUBMITTED FOR APPROVAL**  
 NOV 16 1972  
 Date \_\_\_\_\_

BUREAU OF LAND MANAGEMENT  
 Washington, D.C.

The foregoing field notes of the \_\_\_\_\_ dependent resurvey of a portion of the  
 subdivisional lines of Township 7 South, Range 27 East, of the Gila  
 and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Cadastral Surveyor  
 having been critically examined and found correct, are hereby approved.

MAY 9 1973  
 \_\_\_\_\_  
 (Date)

*Clark L. Gumm*  
 \_\_\_\_\_  
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
 \_\_\_\_\_, is a true copy of the original field notes.~~

~~\_\_\_\_\_  
 (Date)~~

~~\_\_\_\_\_  
 (Chief, Division of Cadastral Survey) GPO 849 - 626~~