Form 9180-6 (April 1965) (formerly 4-679)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
REMONUMENTATION OF CERTAIN MILE CORNERS AND ANGLE POINTS
ON THE NORTH AND WEST BOUNDARIES
OF THE
FORT APACHE INDIAN RESERVATION
IN
TOWNSHIPS 6 AND 7 NORTH, RANGES 26 AND 27 EAST,
TOWNSHIPS 8 NORTH, RANGES 22 THROUGH 26 EAST,
TOWNSHIPS 9 NORTH, RANGES 21, 22, 24, AND 25 EAST,
TOWNSHIPS 10 NORTH, RANGES 151/2 THROUGH 21 EAST,
TOWNSHIPS 11 NORTH, RANGES 15, 17, AND 18 EAST
(NORTH BOUNDARY)
AND
TOWNSHIP 42 NORTH, RANGE 152 EAST,
TOWNSHIPS 5 THROUGH 7 AND 10½ NORTH, RANGE 15 EAST,
(WEST BOUNDARY)
CTIA AND SALT RIVER
Of the GILA AND SALT RIVER Meridian,
In the State ofARIZONA
EXECUTED BY
MARLIN G. LIVERMORE II CADASTRAL SURVEYOR
<u>:</u>
Under special instructions datedMarch 25, 1970_, which provided for the surveys
included under Group Number 522, approved March 26, 1970,
and assignment instructions dated <u>March 25</u> , 19 70.
Survey commenced April 6 , 19 70

., 19 <u>70</u>

June 15

Survey completed __

BOOK 4993

INDEX DIAGRAM

Townsh	nip		, Range		,
6	5	4	8	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	84	35	36

PAGE INDEX TO CORNER MONUMENTS NORTH BOUNDARY OF THE FORT APACHE INDIAN RESERVATION

T. 6 N., R. 27 E.	T. 8 N., R. 24 E. (unsurveyed)
AP 9 p. 1 AP 10 p. 2 AP 18 p. 2 AP 28 p. 2	AP 235 p. 16 AP 236 p. 16 AP 238 p. 17 AP 240 p. 17
T. 6 N., R. 26 E. (unsurveyed)	40 Mile Cor p. 18 AP 242 p. 18
AP 35 p. 3 AP 56 p. 3	AP 243 p. 19 AP 244 p. 19 AP 245 p. 19 AP 246 p. 20
T. 7 N., R. 26 E. (unsurveyed)	AP 248 p. 20
AP 66 p. 4	AP 249 p. 20 AP 252 p. 21
T. 7 N., R. 27 E.	AP 254 p. 21
AP 81 p. 4 AP 84 p. 5 AP 97 p. 5 AP 100 p. 5	T. 8 N., R. 23 E. AP 279 p. 21 AP 280 p. 22 AP 281 p. 22 46½ Mile Cor p. 23
T. 7 N., R. 26 E. (unsurveyed)	AP 285 p. 23 AP 280 p. 24
AP 108 p. 6	AP 289 p. 24
T. 8 N., R. 26 E.	AP 291 p. 25 48½ Mile Cor p. 25
AP 111 p. 6	AP 297 p. 26 AP 300 p. 26
AP 112 p. 7 AP 118 p. 7 AP 126 p. 7	T. 8 N., R. 22 E.
AP 127 p. 8 AP 131 p. 8	AP 303 p. 27
AP 133 p. 9 AP 140 p. 9	T. 9 N., R. 22 E.
T. 8 N., R. 25 E. (unsurveyed)	AP 324 p. 28
25 Mile Cor. p. 10	AP 329 p. 28
	AP 338 p. 29 AP 345 p. 29
T. 9 N., R. 25 E.	AP 347 p. 29 AP 352 p. 30
AP 154 p. 10 AP 162 p. 11	AP 355 p. 30
AP 165 p. 11	AP 371 p. 30 AP 373 p. 31
AP 166 p. 11 AP 167 p. 12	AD 202
AP 168 p. 12	AP 393 p. 31 AP 400 p. 32
AP 169 p. 12	AP 407 p. 33
AP 170 p. 12 AP 199 p. 13	AP 409 p. 33
AP 200 p. 13	
AP 206 p. 14	T. 9 N., R. 21 E.
AP 210 p. 14	AP 425 p. 34
T. 9 N., R. 24 E.	AP 426 p. 34
/ Areg Are LT Et	AP 427 p. 35 AP 428 p. 35
AP 216 p. 14	AP 430 p. 36
AP 225 p. 15	AP 431 p. 36
AP 231 p. 15	AP 432 p. 37 AP 436 p. 37
T. 9 N., R. 24 E.	AP 430 p. 37 AP 437 p. 38
AP 234 p. 16	AP 438 p. 38 AP 443 p. 39

PAGE INDEX TO CORNER MONUMENTS NORTH BOUNDARY OF THE FORT APACHE INDIAN RESERVATION

ţ.	T. 9 N., R. 21 E. Continued	T. 10 N., R. 19 E.
	AP 446 p. 40 AP 447 p. 40	AP 625 p. 60 AP 626 p. 60 AP 653 p. 60
	AP 449 p. 41 AP 450 p. 41 AP 451 p. 41 AP 452 p. 42 AP 453 p. 42 AP 455 p. 42 AP 457 p. 43 AP 458 p. 43 AP 460 p. 44 AP 460 p. 44 AP 465 p. 45 AP 468 p. 45 AP 470 p. 46 AP 471 p. 46	T. 10 N., R. 18 E. AP 689 p. 61 AP 690 p. 62 AP 692 p. 62 AP 706 p. 63 AP 708 p. 63 AP 714 p. 63 AP 715 p. 64 AP 716 p. 64 AP 718 p. 65 T. 11 N., R. 18 E.
	T. 10 N., R. 21 E. AP 480 p. 46 AP 482 p. 47	AP 726 p. 65 AP 754 p. 65 AP 755 p. 66 T. 11 N., R. 17 E.
٠.	T. 9 N., R. 21 E. AP 484 p. 47 T. 10 N., R. 21 E.	AP 771 p. 66 AP 784 p. 67 AP 786 p. 67 AP 788 p. 67
AP 485 p. 48 AP 486 p. 48 AP 488 p. 49 AP 489 p. 49 AP 493 p. 50 AP 495 p. 50 AP 500 p. 51 AP 516 p. 52 AP 520 p. 52		T. 10 N., R. 17 E. AP 790 p. 68 AP 792 p. 68 AP 797 p. 68 AP 825 p. 69 AP 828 p. 69 AP 831 p. 70 102 Mile Cor p. 70 AP 833 p. 71 T. 10 N., R. 16 E.
	T. 10 N., R. 20 E. AP 524 p. 53 AP 525 p. 53 AP 536 p. 53 AP 537 p. 54 AP 543 p. 55 AP 544 p. 55	AP 844 p. 71 AP 845 p. 72 AP 871 p. 72 AP 880 p. 72 AP 892 p. 73 T. 10 N., R. 15½ E.
-	AP 548 p. 55 AP 556 p. 56 AP 561 p. 56 AP 569 p. 56 AP 575 p. 57 AP 587 p. 57 AP 590 p. 58 AP 591 p. 58 AP 597 p. 59 AP 604 p. 59	114½ Mile Cor p. 73 115½ Mile Cor p. 74 T. 11 N., R. 15 E. 118½ Mile Cor p. 74

PAGE INDEX TO CORNER MONUMENTS

WEST BOUNDARY OF THE FORT APACHE INDIAN RESERVATION

.. <u>T. 10½ N., R. 15 E.</u>

 $1\frac{1}{2}$ Mile Cor. - - - p. 75

T. 7 N., R. 15 E.

22½ Mile Cor. - - - p. 75

T. 6 N., R. 15 E. (unsurveyed)

 $32\frac{1}{2}$ Mile Cor. - - - p. 76

T. 5 N., R. 15 E. (portion unsurveyed)

35 Mile Cor. - p. 76 37 Mile Cor. - p. 77 37 Mile Cor. - p. 77

T. $4\frac{1}{2}$ N., R. $15\frac{1}{2}$ E. (unsurveyed)

39 Mile Cor. - - p. 78

181



Remonumentation, North and West Boundaries of the Fort Apache Indian Reservation Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the remonumentation of certain mile corners and angle points on the north and west boundaries of the Fort Apache Indian Reservation in Townships 6 and 7 North, Ranges 26 and 27 East, Townships 8 North, Ranges 22 through 26 East, Townships 9 North, Ranges 21, 22, 24, and 25 East, Townships 10 North, Ranges 15½ through 21 East, Townships 11 North, Ranges 15, 17, and 18 East (north boundary), and Township 4½ North, Range 15½ East, Townships 5 through 7 and 10½ North, Range 15 East (west boundary), Gila and Salt River Meridian, Arizona.

A portion of the north boundary of what is now known as the Fort Apache Indian Reservation was originally surveyed as the north boundary of the White Mountain Indian Reservation by W. R. Fitzgerald in 1883 and a portion was surveyed by C. H. Wallace in 1887. This survey was superseded by a resurvey executed by J. B. Wright, U. S. Surveyor, in 1906. The field notes of the 1887 survey are not available. Wright identified and remarked the monuments established by Wallace in 1887. It is not clear if the "old" bearing trees recorded by Wright were established in the 1887 survey or the 1906 resurvey - or both. A portion of the boundary was resurveyed by A. N. Kimmell in 1935. The "old" bearing trees in the following notes are referred to as the original bearing trees.

The west boundary of the Reservation in the townships included in these notes was originally surveyed by John C. Smith in 1890.

The Fort Apache Indian Reservation has common boundaries with the Apache National Forest on the east, the Sit-greaves National Forest on the north and the Tonto National Forest on the west.

In many instances, the found collateral evidence of the old corners was further supported by random line ties to adjacent or neighboring angle points.

The bearings to all bearing trees were determined by use of a solar transit.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 6 North, Range 27 East Gila and Salt River Meridian, Arizona

Angle Point No. 9, which is monumented with a malpais stone, $14\times8\times3$ ins. (record, $20\times10\times10$ ins.), mkd. APNBWMIR 9 on the E. face and BMFR on the N. face, firmly set in a small mound of stone.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A fir, 10 ins. diam., bears S. $54\frac{1}{2}^{\circ}$ E., 23 lks. dist. mkd. AP 9 BT.

CHAINS


A fir, 10 ins. diam., bears N. 66° W., 31 lks. dist. mkd. AP 9 BT

deposit the original corner stone alongside the iron post.

Angle Point No. 10, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which


A spruce, 10 ins. diam., bears S. 78 $3/4^{\circ}$ E., 61 lks. dist., mkd. AP 10 BT.

A fir, 10 ins. diam., bears S. 53 $3/4^{\circ}$ W., 36 lks. dist., mkd. AP 10 FAIR BT.

Angle Point No. 18, which is monumented with the remains of the original tree corner, a deteriorated pine stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A fir, 24 ins. diam., bears S. $56\frac{1}{2}$ ° E., 47 lks. dist., mkd. AP 18 FAIR BT.

A spruce, 8 ins. diam., bears N. $14\frac{1}{2}^{\circ}$ W., 45 lks. dist., mkd. AP 18 BT


raise a mound of stone, 2½ ft., base, 2 ft. high, S. of the corner.

Angle Point No. 28, determined by the remains of the original tree corner, a stump hole, with an aspen stump, scribing illegible, lying alongside.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

CHAINS



1970

from which

A spruce, 14 ins. diam., bears S. 1° E., 22 lks. dist., mkd. AP 28 FAIR BT.

A spruce, 8 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ W., 12 lks. dist., mkd. AP 28 BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 6 North, Range 26 East (unsurveyed) Gila and Salt River Meridian, Arizona

Angle Point No. 35, which is monumented with the remains of the original tree corner, a spruce snag, 18 ins. diam. mkd. AP NB WMIR 3 on the N. face, no other marks visible.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 18 ins in the ground, for a reference monument, bears S. $26\frac{1}{4}^{\circ}$ E., 13 lks. dist., with brass cap mkd. RM AP 35 FAIR 1970, and an arrow pointing to the true corner.

A fir, 10 ins. diam., bears S. 85 $3/4^{\circ}$ W., 29 lks. dist., mkd. AP 35 FAIR BT.

Angle Point No. 56, determined by the remains of the original tree corner, a stump hole, with a rotted aspen, 10 ins. diam., lying alongside, substantiated by the remains of the old bearing trees:

A spruce, 9 ins. diam., bears N. 34° E., 10 lks. dist., mkd. AP 56 BT. (origin unknown)

A spruce, 8 ins. diam., bears S. 34° E., 10 lks. dist., blaze grown over. (origin unknown)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

AP 56
FAIR ANF

from which

A spruce, 10 ins. diam., bears N. 69 $3/4^{\circ}$ E., 24 lks. dist., mkd. AP 56 BT.

Ъ

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 6 North, Range 26 East (unsurveyed) Gila and Salt River Meridian, Arizona

CHAINS

A spruce, 14 ins. diam., bears N. $62\frac{1}{2}^{\circ}$ W., 17 lks. dist., mkd. AP 56 FAIR BT.


raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 7 North, Range 26 East (unsurveyed) Gila and Salt River Meridian, Arizona

Angle Point No. 66, determined by the remains of the original tree corner, a stump hole, with a rotted spruce, mkd. AP NB WMIR 66 on the W. side and BMFR on the E. side lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A spruce, 12 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ E., 67 lks. dist., mkd. AP 66 BT.


A spruce, 8 ins. diam., bears N. 20 $3/4^{\circ}$ W., 58 lks. dist., mkd. AP 66 FAIR BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 7 North, Range 27 East Gila and Salt River Meridian, Arizona

Angle Point No. 81, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.



CHAINS

from which


A spruce, 8 ins. diam., bears S. 40 $3/4^{\circ}$ E., 51 lks. dist., mkd. AP 81 BT.

A spruce, 15 ins. diam., bears N. $1\frac{1}{4}^{\circ}$ W., 72 lks. dist., mkd. AP 81 FAIR BT.

Angle Point No. 84, determined by the remains of the original tree corner, a stump hole, with a rotted aspen, scribe mks. visible but not legible, lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A fir, 8 ins. diam., bears S. $2\frac{1}{2}^{\circ}$ E., 33 lks. dist., mkd. AP 84 BT.

A fir, 11 ins. diam., bears N. 42° W., 17 lks. dist., mkd. AP 84 BT.

Angle Point No. 97, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam., mkd. AP NB WMIR 97 on the W. face and BMFR on the E. face

from which

A pine, 24 ins. diam., bears N. $43\ 3/4^{\circ}$ E., $88\ 1ks$. dist., mkd. AP 97 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins in the ground, for a reference monument, bears EAST, 8 lks. dist., with brass cap mkd. RM AP 97 FAIR 1970, and an arrow pointing to the true corner.

A pine, 24 ins. diam., bears N. 15 $3/4^{\circ}$ W., 83 lks. dist., mkd. AP 97 FAIR BT.

Angle Point No. 100, which is monumented with a lava stone, 36x30x12 ins., mkd. AP NB WMIR on the W. face, firmly set in a small mound of stone.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

CHAINS

AP 100 T7N
R27E
FAIR S 18

deposit the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 3 ft. high, W. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 7 North, Range 26 East (unsurveyed) Gila and Salt River Meridian, Arizona

Angle Point No. 108, which is monumented with the remains of the original tree corner, a deteriorated aspen stump, 8 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.

AP 108 R26E FAIR

1970

from which

A fir, 8 ins. diam., bears S. 76° E., 26 lks. dist., mkd. AP 108 BT.

A pine, 14 ins. diam., bears N. 88° W., 61 lks. dist. mkd. AP 108 FAIR BT.

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 26 East Gila and Salt River Meridian, Arizona

Angle Point No. 111, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

7

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 26 East Gila and Salt River Meridian, Arizona

CHAINS

T8N R26E S 27 AP 111 FAIR

1970

from which


A pine, 20 ins. diam., bears N. 32° E., 74 lks. dist., mkd. AP 111 BT.

A pine, 18 ins. diam., bears S. $24\frac{1}{2}^{\circ}$ E., 117 lks. dist., mkd. AP 111 FAIR BT.

Angle Point No. 112, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A fir, 8 ins. diam., bears S. 24° E., 29 lks. dist., mkd. AP 112 FAIR BT.

A fir, 8 ins. diam., bears N. $25\frac{1}{2}^{\circ}$ W., 24 lks. dist., mkd. AP 112 BT.

raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, S. of the corner.

Angle Point No. 118, which is monumented with the original tree corner, a fir, 24 ins. diam., mkd. with dim scribe mks. on the NE. and SW. faces.

from which

A fir, 18 ins. diam., bears S. 89° E., 56 lks. dist., mkd. AP 118 BT.

A pine, 8 ins. diam., bears SOUTH, 67 lks. dist., mkd. AP 118 FAIR BT.

Angle Point No. 126, which is monumented with the remains of the original tree corner, a deteriorated fir stump, 10 ins. diam., mkd. AP NB WMIR on the W. face and BMFR on the E. face.

At the corner point, the center of the root crown,

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A spruce, 12 ins. diam., bears S. 184° E., 38 lks. dist., mkd. AP 126 BT.

A spruce, 10 ins. diam., bears N. 58 $3/4^{\circ}$ W., 56 lks. dist., mkd. AP 126 FAIR BT.

Angle Point No.127, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A spruce, 20 ins. diam., bears N. 42 $3/4^{\circ}$ E., 36 lks. dist., mkd. AP 127 BT.

A spruce, 8 ins. diam., bears N. 46 $3/4^{\circ}$ W., 42 lks. dist., mkd. AP 127 FAIR BT.

Angle Point No. 131, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

9

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 26 East Gila and Salt River Meridian, Arizona

CHAINS

from which

A pine, 10 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ E., 49 lks. dist., mkd. AP 131 BT.

A pine, 26 ins. diam., bears S. 4° E., 112 lks. dist., mkd. AP 131 FAIR BT.

Angle Point No. 133, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8N R26E S 8 AP 133 FAIR

1970

from which

A pine, 12 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ E., 48 lks. dist., mkd. AP 133 BT.

A pine, 24 ins. diam., bears S. 2° E., 87 lks. dist., mkd. AP 133 FAIR BT.

Angle Point No. 140, determined by the remains of the original tree corner, a deteriorated pine stump, 20 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8N R26E S 7 AP 140 FAIR

1970

from which

A pine, 15 ins. diam., bears S. $21\frac{1}{2}^{\circ}$ E., 96 lks. dist., mkd. AP 140 FAIR BT.

A pine, 20 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ W., 25 lks. dist., mkd. AP 140 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

CHAINS

The 25 Mile Corner, determined by the remains of the original bearing trees:

An aspen, 14 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ E., 32 lks. dist., mkd. NB AP WMIR 25M BT. (record, N. 5° E.)

An aspen, 10 ins. diam., bears S. $51\frac{1}{2}^{\circ}$ W., 10 lks. dist., mkd. NB WMIR 25M BT. (record, S. 42° W.)

A dead aspen, 8 ins. diam., bears N. 42° W., 28 lks. dist., mkd. NB WMIR 25 M. (record, N. 43° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8N R251 25M FAIR

1970

from which

A fir, 10 ins. diam., bears N. $82\frac{1}{2}^{\circ}$ E., 63 lks. dist., mkd. 25 M BT.

A fir, 12 ins. diam., bears S. $66\frac{1}{2}^{\circ}$ W., 17 lks. dist., mkd. 25 M FAIR BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 25 East Gila and Salt River Meridian, Arizona

Angle Point No. 154, determined at the center of a scattered mound of stone, substantiated by the remains of the original bearing trees:

A pine stump, 14 ins. diam., bears S. 65° 40' W., 46 lks. dist., mkd. AP 154 BT.

A pine stump, 12 ins. diam., bears N. 21° 10' W., 49 lks. dist., mkd. AP 154 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R25E S 35 AP 154 FAIR

1970

from which

CHAINS

A pine, 15 ins. diam., bears N. 89° E., 86 lks. dist., mkd. AP 154 BT.

A pine, 16 ins. diam., bears S. 19° W., 32 lks. dist., mkd. AP 154 FAIR BT.

raise a mound of stone, 4 ft. base, 3 ft. high, S. of the corner.

The original corner monument, a malpais stone, 40x20x12 ins., mkd. N BWMIR and BMFR found lying loose some distance down a slope and could not be returned to the true point because of its size.

Angle Point No. 162, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 12 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ E., 130 lks. dist., mkd. AP 162 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, $5\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 162 FAIR 1970, and an arrow pointing to the true corner.

A pine, 14 ins. diam., bears N. 264° W., 105 lks. dist., mkd. AP 162 BT.

Angle Point No. 165, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam., blazed with dim scribe mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears EAST, 11 lks. dist., with brass cap mkd. RM AP 165 FAIR 1970, and an arrow pointing to the true corner.

A pine, 8 ins. diam., bears S. 52 $3/4^{\circ}$ E., 52 lks. dist., mkd. AP 165 FAIR BT.

A pine, 8 ins. diam., bears S. $67\frac{1}{2}^{\circ}$ W., 78 lks. dist., mkd. AP 165 BT.

Angle Point No. 166, which is monumented with the remains of the original tree corner, a pine stump, 26 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 8 ins. diam., bears N. 45° E., 45 lks. dist., mkd. AP 166 FAIR BT.

CHAINS

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears EAST, 9 lks. dist., with brass cap mkd. RM AP 166 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. $75\frac{1}{2}^{\circ}$ W., 66 lks. dist., mkd. AP 166 BT.

Angle Point No. 167, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears EAST, 9 lks. dist., with brass cap mkd. RM AP 167 FAIR 1970, and an arrow pointing to the true corner.

A fir, 12 ins. diam., bears S. $72\frac{1}{2}^{\circ}$ E., 90 lks. dist., mkd. AP 167 BT.

A fir, 14 ins. diam., bears S. $57\frac{1}{4}^{\circ}$ W., 151 lks. dist., mkd. AP 167 BT.

Angle Point No. 168, which is monumented with the remains of the original tree corner, a pine stump, 20 ins. diam., with blazes on the E. and W. sides grown over.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears EAST, 16 lks. dist., with brass cap mkd. RM AP 168 FAIR 1970, and an arrow pointing to the true corner.

A fir, 12 ins. diam., bears S. $3/4^{\circ}$ E., 41 lks. dist., mkd. AP 168 FAIR BT.

A fir, 10 ins. diam., bears S. 584° W., 21 lks. dist., mkd. AP 168 FAIR BT.

Angle Point No. 169, which is monumented with the remains of the original tree corner, a fir stump, 30 ins. diam., mkd. 169 on the S. face, other markings grown over.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears EAST, 7 lks. dist., with brass cap mkd. RM AP 169 FAIR 1970, and an arrow pointing to the true corner.

A fir, 10 ins. diam., bears S. $15\frac{1}{2}^{\circ}$ W., 47 lks. dist., mkd. AP 169 FAIR BT.

A fir, 12 ins. diam., bears N. $29\frac{1}{2}^{\circ}$ W., 39 lks. dist., mkd. AP 169 BT.

Angle Point No. 170, which is monumented with the remains of the original tree corner, a deteriorated aspen stump. This position is harmoniously related to existing evidence of adjacent angle points.

CHAINS

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T9N R25E AP 170 S 34 FAIR

from which


A fir, 20 ins. diam., bears S. $54 \ 3/4^{\circ}$ E., 23 lks. dist., mkd. AP 170 FAIR BT.

A fir, 10 ins. diam., bears N. 63° W., 47 lks. dist., mkd. AP 170 BT.

Angle Point No. 199, determined by the remains of the original tree corner, a stump hole, with a pine, 6 ins. diam., mkd. AP NB WMIR 199 on one side and the other side mkd. BMFR, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., on bedrock in a collar of stone, 6 ft. base, to top, with brass cap mkd.



from which

A pine, 8 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ W., 60 lks. dist., mkd. AP 199 FAIR BT.

A pine, 8 ins. diam., bears N. $23\frac{1}{4}^{\circ}$ W., 20 lks. dist., mkd. AP 199 BT.

Angle Point No. 200, which is monumented with the remains of the original tree corner, a deteriorated aspen stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R25E S 31 AP 200 FAIR

1970

CHAINS

from which

A pine, 8 ins. diam., bears S. 17 $3/4^{\circ}$ W., 60 lks. dist., mkd. AP 200 FAIR BT.

A pine, 8 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., 31 lks. dist., mkd. AP 200 BT

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 206, which is monumented with the original tree corner, a pine, 16 ins. diam., mkd. WMIR 206 on the S. face. Blaze grown over on the N. face.

from which

A pine, 8 ins. diam., bears S. $87\frac{1}{4}^{\circ}$ E., 68 lks. dist., mkd. AP 206 FAIR BT.

A pine, 20 ins. diam., bears N. $62\frac{1}{4}^{\circ}$ W., 22 lks. dist., mkd. AP 206 BT.

Angle Point No. 210, determined by the remains of the original tree corner, a stump hole, with stump mkd. AP NB WMIR 210, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R25E S 31 AP 210 FAIR

1970

from which

A pine, 8 ins. diam., bears N. $51\frac{1}{4}$ ° E., 30 lks. dist., mkd. AP 210 BT.

A pine, 8 ins. diam., bears S. $4 3/4^{\circ}$ E., 30 lks. dist., mkd. AP 210 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.


Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 24 East Gila and Salt River Meridian, Arizona

Angle Point No. 216, determined by the remains of the original tree corner, a stump hole, with a pine, 8 ins. diam., mkd. AP NB WMIR on one side and the other side mkd. BMFR, lying alongside.

At the corner point

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 2 $3/4^{\circ}$ W., 33 lks. dist., mkd. AP 216 FAIR BT.

A pine, 8 ins. diam., bears N. 384° W., 28 lks. dist., mkd. AP 216 BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 24 East (unsurveyed) Gila and Salt River Meridian, Arizona

Angle Point No. 225, determined by the remains of the original tree corner, a stump hole, with stump mkd. AP NB WMIR 225, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 29 $3/4^{\circ}$ E., 119 lks. dist., mkd. AP 225 FAIR BT.

A pine, 12 ins. diam., bears N. 68° W., 39 lks. dist., mkd. AP 225 BT.

Angle Point No. 231, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 8 lks. dist., with brass cap mkd. RM AP 231 1970, and an arrow pointing to the true corner.

A pine, 18 ins. diam., bears N. 71 $3/4^{\circ}$ W., 107 lks. dist., mkd. AP 231 FAIR BT.


A pine, 14 ins. diam., bears N. 20 $3/4^{\circ}$ W., 109 lks. dist., mkd. AP 231 BT.

CHAINS

Angle Point No. 234, which is monumented with the remains of the original tree corner, a burned pine stump, 24 ins. diam., blaze on the S. face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 43° W., 29 lks. dist., mkd. AP 234 FAIR BT.

A pine, 10 ins. diam., bears N. 64° W., 36 lks. dist., mkd. AP 234 BT.


raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 24 East (unsurveyed) Gila and Salt River Meridian, Arizona

Angle Point No. 235, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A pine, 10 ins. diam., bears N. $44\frac{1}{2}^{\circ}$ W., 56 lks. dist., mkd. AP 235 BT.

raise a mound of stone, 2 ft. base, 1 ft. high, E. of the corner.

Angle Point No. 236, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A pine, 10 ins. diam., bears S. $3\frac{1}{4}^{\circ}$ E., 108 lks. dist., mkd. AP 236 FAIR BT.


An oak, 6 ins. diam., bears S. $54 \ 3/4^{\circ} \ W.$, 49 lks. dist., mkd. AP 236 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Angle Point No. 238, determined by the remains of the original tree corner, a stump hole, with a pine, 20 ins. diam., blaze visible but burnt, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 79 $3/4^{\circ}$ E., 98 lks. dist., mkd. AP 238 FAIR BT.

An oak, 6 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ W., 22 lks. dist. mkd. AP 238 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 240, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 12 ins. diam., bears N. $73\frac{1}{4}^{\circ}$ E., 32 lks. dist., mkd. AP 240 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears SOUTH, $4\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP $2\frac{1}{4}$ 0 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears N. 16° W., 35 lks. dist., mkd. AP 240 BT.

CHAINS

The 40 Mile Corner, which is monumented with a malpais stone, 16x12x8 ins., mkd. BMFR on the N. face, set flush with the surface of the ground, substantiated by the remains of the original bearing trees:

A stump hole, bears N. 462° E., 66 lks. dist.


A pine stump, 20 ins. diam., bears S. $42\frac{1}{2}^{\circ}$ E., 32 lks dist. (record, 42 lks.)

A pine stump, 26 ins. diam., bears N. 81° W., 58 lks. dist. (record, 57 lks.)

A stump hole, bears N. $34\frac{1}{2}^{\circ}$ W., 44 lks. dist., a dead pine, 24 ins. diam., lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.



from which

A pine, 10 ins. diam., bears S. 65° E., 16 lks. dist., mkd. 40M FAIR BT.

A pine, 12 ins. diam., bears N. $59\frac{1}{2}^{\circ}$ W., 10 lks. dist., mkd. 40M BT.

deposit the original corner stone alongside the iron post


Angle Point No. 242, determined by the remains of the original tree corner, a stump hole, substantiated by the remains of the original bearing trees:

A stump hole, bears S. 50° E., 26 lks. dist.

A stump hole, bears N. 86° 30' W., 14 lks. dist.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 14 ins. diam., bears S. 26 $3/4^{\circ}$ E., 73 lks. dist., mkd. AP 242 FAIR BT.

A pine, 10 ins. diam., bears N. $87\frac{1}{2}^{\circ}$ W., 103 lks. dist., mkd. AP 242 BT.

CHAINS

raise a mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Angle Point No. 243, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

AP 243 FAIR

1970

from which

A pine, 14 ins. diam., bears S. $61\frac{1}{2}$ ° E., 43 lks. dist., mkd. AP 243 FAIR BT.

A pine, 16 ins. diam., bears N. $33\frac{1}{4}^{\circ}$ W., 105 lks. dist., mkd. AP 243 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 244, which is monumented with the remains of the original tree corner, a stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 8 lks. dist., with brass cap mkd. RM AP 244 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., 53 lks. dist., mkd. AP 244 FAIR BT.

A pine, 12 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ W., 117 lks. dist., mkd. AP 244 BT.

Angle Point No. 245, which is monumented with the remains of the original tree corner, a rotted and deteriorated pine stump, 18 ins. diam. This position is harmoniously related to existing angle points in the area.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, encircled with a mound of stone, $3\frac{1}{2}$ ft. base, to top, with brass cap mkd.

CHAINS

SNF

AP 245 FAIR

1970

from which

An oak, 12 ins. diam., bears N. $61\frac{1}{3}$ ° W., 82 lks. dist., mkd. AP 245 BT.

Angle Point No. 206, which is monumented by an old mound of ctone in a jog in the old Reservation fence line. This position is locally accepted as the point for Angle Point No. 246.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

SNF

AP 246 FAIR

1970

corner.

Angle Point No. 248, which is monumented with the remains of the original tree corner, a burned pine stump, 36 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 12 ins. diam., bears S. 27 $3/4^{\circ}$ E., 273 lks. dist., mkd. AP 248 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 8 lks. dist., with brass cap mkd. RM AP 248 FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 249, which is monumented with the remains of the original tree corner, a pine stump, 18 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 3 lks. dist., with brass cap mkd. RM AP 249 FAIR 1970, and an arrow pointing to the true corner.

A pine, 12 ins. diam., bears S. 7° W., 76 lks. dist., mkd. AP 249 FAIR BT.

A pine, 14 ins. diam., bears N. 50° W., 82 lks. dist. mkd. AP 249 BT.

CHAINS

Angle Point No. 252, which is monumented with the remains of the original tree corner, a deteriorated burnt pine stump, 14 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

SNF AP 252 FAIR

1970

from which

A pine, 8 ins. diam., bears N. 30° E., 56 lks. dist., mkd. AP 252 BT.

A pine, 10 ins. diam., bears S. $53\frac{1}{4}^{\circ}$ W., 168 lks. dist., mkd. AP 252 FAIR BT.

Angle Point No. 254, which is monumented with the original tree corner, a deteriorated, rotted pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

AP 254 FAIR

1970

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 23 East Gila and Salt River Meridian, Arizona

Angle Point No. 279, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

CHAINS

T8N R23E

S 10

AP 279 FAIR

1970

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 280, which is monumented with the remains of the original tree corner, a deteriorated pine stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

T8N R23E S 10

AP 280

FAIR

1970

from which

A pine, 8 ins. diam., bears S. 42° E., 53 lks. dist., mkd. AP 280 FAIR BT.

A pine, 12 ins. diam., bears S. 45° W., 66 lks. dist. mkd. AP 280 FAIR BT.

Angle Point No. 281, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8N R23E S 10

AP 281

FAIR

1970

from which

A pine, 8 ins. diam., bears S. $43\frac{1}{2}$ ° E., 50 lks. dist. mkd. AP 281 FAIR BT.

A pine, 10 ins. diam., bears S. 56° W., 19 lks. dist. mkd. AP 281 FAIR BT.

CHAINS

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the corner.

The $46\frac{1}{2}$ Mile Corner, identical with Angle Point No. 284, which is monumented with a malpais stone, 16x10x8 ins., no mks. visible, loosely set with a steel fence post driven alongside, substantiated by the remains of the original bearing trees:

An oak, 14 ins. diam., bears N. $35\frac{1}{2}^{\circ}$ E., 85 lks. dist. (record, N 33° E.)

A pine stump, 16 ins. diam., bears S. $67\frac{1}{2}^{\circ}$ E., 72 lks. dist. (record, S. 69° E.)

A burnt pine stump, 16 ins. diam., bears S. $11\frac{1}{2}^{\circ}$ E., 15 lks. dist. (record, S. 15° E., 19 lks. dist.)

A stump hole, bears N. $23\frac{1}{2}^{\circ}$ W., 97 lks. dist. (record, N. 26° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T8N R23E S 9 AP 284 FAIR 46½ M

1970

from which

A pine, 16 ins. diam., bears S. $10\frac{1}{4}^{\circ}$ W., 56 lks. dist., mkd. FAIR $46\frac{1}{2}$ M BT.

A pine, 14 ins. diam., bears N. $78\frac{1}{4}^{\circ}$ W., 49 lks. dist., mkd. FAIR $46\frac{1}{2}$ M BT

deposit the original corner stone alongside the iron post, and raise a mound of stone, 2 ft. base, l_2 ft. high. S. of the corner.

Angle Point No. 285, determined by the remains of the original tree corner, a stump hole, substantiated by the remains of the original bearing trees:

An oak stump, 20 ins. diam., bears N. 60° E., 59 lks. dist., blazed with no mks visible.

A stump hole, bears S. 60° W., 62 lks. dist.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

CHAINS

T8N R23E S 9

AP 285 FAIR

1970

from which

A pine, 10 ins. diam., bears S. 24° E., 16 lks. dist., mkd. AP 285 FAIR BT.

A pine, 10 ins. diam., bears N. 81° W., 18 lks. dist., mkd. AP 285 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

original tree corner, a stump hole, substantiated by a private survey monument, a reinforcing steel rod, l in. diam., firmly set in the stump hole with brass cap mkd. WMIR AP 288.

At the corn r point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, over the private survey monument, with brass cap mkd.

8N R23E

AP 288 FAIR

1970

from which

A pine, 8 ins. diam., bears S. 36 3/4° E., 41 lks. dist., mkd. AP 288 FAIR BT.

A pine, 8 ins. diam, bears S. $72\frac{1}{2}^{\circ}$ W., 46 lkdist., mkd. AP 288 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of

Angle Point No. 289, which is monumented with the remains of the original tree corner, a pine stump, 12 ins. diam., substantiated by the remains of the original bearing trees:

A stump hole, bears N. 2° E., 46 lks. dist. (record, N. 4° E.)

A burnt stump, bears N. 48½° E., 46 lks. dist.

At the corner point

Prive a spike nail in the center of the stump.

CHAINS

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. $27\frac{1}{4}^{\circ}$ E., 20 lks. dist., with brass cap mkd. RM AP 289 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. 50° W., 43 lks. dist., mkd. AP 289 FAIR BT.

A pine, 8 ins. diam., bears N. 834° W., 58 lks. dist., mkd. AP 289 FAIR BT.

Angle Point No. 291, determined by the remains of the original tree corner, a stump hole, substantiated by the remains of the original bearing trees:

A pine stump, 24 ins. diam., bears S. 9° W., 108 lks. dist., no mks. visible. (record, S. 10° W.)

An oak stump, 24 ins. diam., bears S. $38\frac{1}{4}^{\circ}$ W., 92 lks. dist., no mks. visible. (record, S. 40° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. $18\frac{1}{2}^{\circ}$ E., 10 lks. dist., mkd. AP 291 FAIR BT.

A pine, 10 ins. diam., bears S. 47° W., 17 lks. dist., mkd. AP 281 FAIR BT.

The original closing corner for secs. 5 and 8, a malpais stone, 12x12x8 ins., bears N. 54° 11' W., 70 lks. dist., with the mks. IR visible on the S. face.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

The $48\frac{1}{2}$ Mile Corner, identical with Angle Point No. 296, which is monumented with a malpais stone, 20x12x8 ins., no mks. visible, loosely set with a steel pin, 12 ins. long, $1\frac{1}{2}$ ins. diam., driven alongside, substantiated by the remains of the old bearing trees:

An oak stump, 14 ins. diam., bears S. 46° E., 88 lks. dist., mkd. M BT. (record, S. $46\frac{1}{2}$ ° E.)


CHAINS

A pine stump, 14 ins. diam., bears S. 584° W., 54 lks. dist., no mks. visible. (record, S. 572° W.)

A deteriorated pine stump, bears N. 59½° W., 33 lks. dist. (record, N. 59° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 72° E., 67 lks. dist., mkd. $48\frac{1}{2}$ M FAIR BT.

A pine, 10 ins. diam., bears S. $29\frac{1}{4}^{\circ}$ W., 69 lks. dist., mkd. $48\frac{1}{2}$ M FAIR BT.

deposit the original corner stone and the steel pin alongside the iron post and raise a mound of stone, 2 ft. base, 1½ ft. high, S. of the corner.

Angle Point No. 297, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Drive a spike nail in the center of the stump.

from which

A pine, 14 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 115 lks. dist., mkd. AP 297 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. $45\frac{1}{4}$ ° W., 16 lks. dist., with brass cap mkd. RM AP 297 FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 300, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 18 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

27

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 23 East Gila and Salt River Meridian, Arizona

CHAINS

T8N R23E

s 6

AP 300 FAIR

1970

from which

A pine, 8 ins. diam., bears S. $63\frac{1}{4}$ ° E., 64 lks. dist., mkd. AP 300 FAIR BT.

A pine, 8 ins. diam., bears S. $4 3/4^{\circ} W.$, 93 lks. dist., mkd. AP 300 FAIR BT.

> Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 8 North, Range 22 East Gila and Salt River Meridian, Arizona

Angle Point No. 303, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Drive a spike nail in the center of the stump.

from which

A pine, 12 ins. diam., bears S. $26\frac{1}{2}^{\circ}$ E., 64 lks. dist., mkd. AP 303 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 19 lks. dist., with brass cap mkd. RM AP 303 FAIR 1970, and an arrow pointing to the true corner.

A pine, 14 ins. diam, bears S. $36\frac{1}{2}^{\circ}$ W., 86 lks. dist., mkd. AP 303 FAIR BT.

> Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 22 East Gila and Salt River Meridian, Arizona

original tree corner, a stump hole, substantiated by a locally established monument, a sandstone, 14x12x10 ins., firmly set in the stump hole, with chisel marks on top.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T9N R22E

S 35

AP 320 FAIR

1970

CHAINS

from which

A pine, 12 ins. diam., bears S. 45 $3/4^{\circ}$ E., 108 lks. dist., mkd. AF 320 FAIR BT.

A pine, 8 ins. diam., bears S. $9\frac{1}{4}^{\circ}$ W., 25 lks. dist., mkd. AP 320 FAIR BT.

deposit the eld corner stone alongside the iron post.

Angle Point No. 324, which is monumented with a sandstone, 18x12x10 ins., mkd. NBWMIR A 324, firmly set in a mound of stone, substantiated by the remains of the original bearing tree:

A stump hole, bears N. 40° E., 28 lks. dist., with the original bearing tree mkd. AP 324 BT, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R22E S 27 AP 324 FAIR

1970

from which

A pine, 10 ins. diam., bears S. 14 $3/4^{\circ}$ E., 10 lks. dist., mkd. AP 32^{4} FAIR BT.

A pine, 8 ins. diam., bears S. $27\frac{1}{4}^{\circ}$ W., 107 lks. dist., mkd. AP 324 FAIR BT.

deposit the original corner stone alongside the iron post.

Angle Point No. 329, determined by the remains of the priginal tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R22E S 27 AP 329 FAIR

1970

from which

A pine, 18 ins. diam., bears S. $73\frac{1}{4}^{\circ}$ W., 84 lks. dist., mkd. AP 329 FAIR BT.

A pine, 16 ins. diam., bears N. $66\frac{1}{2}^{\circ}$ W., 107 lks. dist., mkd. AP 329 FAIR BT.

CHAINS

raise a mound of stone, 2 ft. base, 1 ft. high, S. of the corner.

Angle Point No. 338, determined from the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

from which

A pine, 12 ins. diam., bears S. $59\frac{1}{2}^{\circ}$ W., 132 lks. dist., mkd. AP 338 FAIR BT.

A pine, 8 ins. diam., bears N. 49% W., 43 lks. dist., mkd. AP 338 FAIR BT.

Angle Point No. 345, which is monumented with the remains of the original tree corner, a pine stump, 18 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pinon, 12 ins. diam., bears S. 87° W., 107 lks. dist., mkd. AP 345 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. $2\frac{1}{2}^{0}$ W., 13 lks. dist., with brass cap mkd. RM AP $3\frac{1}{2}$ FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 347, which is monumented with the remains of the original tree corner, a fir stump, 18 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A fir, 10 ins. diam., bears S. $57\frac{1}{2}^{\circ}$ W., 49 lks. dist., mkd. AP 347 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. $83\frac{1}{2}^{\circ}$ W., $17\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP $3\frac{1}{4}$ 7 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears N. $80\frac{1}{4}^{\circ}$ W., 63 lks. dist., mkd. AP $3\frac{1}{4}$ 7 FAIR BT.

CHAINS

Angle Point No. 352, determined by the remains of the original tree corner, a stump hole, with stump mkd. AP 352, other markings grown over, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R22E S 21 AP 352 FAIR

1970

from which


A pine, 16 ins. diam., bears S. 5° E., 7^{4} lks. dist., mkd. AP 352 FAIR BT.

A pinon, 10 ins. diam., bears S. 42° W., 23 lks. dist., mkd. AP 352 FAIR BT.

Angle Point No. 355, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears N. $24\frac{1}{4}$ ° E., 61 lks. dist., mkd. AP 355 BT.

A pine, 10 ins. diam., bears S. 31 $3/4^{\circ}$ E., 88 lks. dist., mkd. AP 355 FAIR BT.

raise a mound of stone, 2 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 371, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam., blazes grown over on the E. and W. faces. This position is harmoniously related to existing evidence of adjacent angle points.

CHAINS


from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 42 $3/4^{\circ}$ W., $17\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 371 FAIR 1970, and an arrow pointing to the true corner.

A cedar, 8 ins. diam., bears N. 78° W., 44 lks. dist., mkd. AP 371 FAIR BT.

Point for Angle Point No. 373, identical with the true point for Corner 4 of HES 207, determined at record bearing and distance from the witness corner 4 of HES 207.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A pine, 30 ins. diam., bears S. $1\frac{1}{2}^{\circ}$ W., 70 lks. dist., mkd. AP 373 FAIR BT.

A pine, 20 ins. diam., bears N. 89° W., 84 lks. dist., mkd. AP 373 FAIR BT.

The witness corner 4 of HES 207 bears N. 51° 38' W., 76 lks. dist., which is monumented with a sandstone, 22xl4x4 ins., mkd. WC 4 HES 207, set 12 ins. in the ground, substantiated by the remains of the old bearing trees:

A pine, 12 ins. diam., bears S. 20° 09' W., 52 lks. dist., no mks. visible.

A pine, 20 ins. diam., bears N. 25° 29' W., 75 lks. dist., no mks. visible. (record 76 lks.)

raise a mound of stone, $2\frac{1}{2}$ ft.base, $2\frac{1}{2}$ ft. high, W. of the corner.

Angle Point No. 393, determined by the remains of the original tree corner, a stump hole, with a rotted pine, 24 ins. diam., lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 22 East Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R22E S 5 AP 393 FAIR

1970

from which

A pine, 8 ins. diam., bears S. $9\frac{1}{2}^{\circ}$ E., 40 lks. dist., mkd. AP 393 FAIR BT.

A cedar, 18 ins. diam., bears S. $70\frac{1}{2}^{\circ}$ W., 63 lks. dist., mkd. AP 393 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, SW. of the corner.

Angle Point No. 400, determined by the remains of the original tree corner, a stump hole, with a cedar, 14 ins. diam., blaze grown over, lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.

T9N R22E S 6 AP 400 FAIR

1970

from which

A pine, 8 ins. diam., bears N. 65° E., 89 lks. dist., mkd. AP 400 FAIR BT.

A pine, 12 ins. diam., bears S. 54° E., 100 lks. dist., mkd. AP 400 FAIR BT.


raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

CHAINS

Angle Point No. 407, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears S. $77\frac{1}{4}^{\circ}$ E., 129 lks. dist., mkd. AP 407 FAIR BT.

A pine, 14 ins. diam., bears S. 52 $3/4^{\circ}$ E., 116 lks. dist., mkd. AP 407 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.


Angle Point No. 409, determined at record distance from the remains of the original bearing trees:

A juniper, 24 ins. diam., bears S. 4° W., 31 lks. dist., mkd. AP 409 BT. (record, SOUTH)

A juniper, 24 ins. diam., bears S. $68\frac{1}{4}^{\circ}$ W., 74 lks. dist., mkd. AP 409 BT. (record, S. 67° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.



1970

from which

A pine, 8 ins. diam., bears N. 73° E., 53 lks. dist., mkd. AP 409 FAIR BT.

CHAINS

A pine, 10 ins. diam., bears S. 70 3/4° E., 47 lks. dist., mkd. AP 409 FAIR BT.

raise a mound of stone, 2 ft. base, 2 ft. high, W. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 21 East Gila and Salt River Meridian, Arizona

Angle Point No. 425, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R21E S 12

> AP 425 FAIR

> > 1970

from which

A pine, 10 ins. diam., bears S. 10° E., 27 lks. dist., mkd. AP 425 FAIR BT.

A pine, 8 ins. diam., bears S. 71 $3/4^{\circ}$ W., 109 lks. dist., mkd. AP 425 FAIR BT.

raise a mound of stone, 2 ft. base, 2 ft. high, SW. of the corner.

Angle Point No. 426, which is monumented with the remains of the original tree corner, a deteriorated pine stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS

T9N R21E S 12

AP 426 FAIR

1970

from which

A pine, 14 ins. diam., bears S. 464° E., 83 lks. dist., mkd. AP 426 FAIR BT.

A pine, 8 ins. diam., bears S. 13 $3/4^{\circ}$ W., 62 lks. dist., mkd. AP 426 FAIR BT.

Angle Point No. 427, determined by the remains of the original tree corner, a stump hole, substantiated by the remains of the original bearing trees:

A stump hole, bears N. 30 3/4° E., 64 lks. dist. (record, N. 32° E., 74 lks.)

A stump hole, bears N. 60 $3/4^{\circ}$ E., 62 lks. dist. (record, N. 64° E., 55 lks.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 14 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ W., 75 lks. dist., mkd. AP 427 FAIR BT.

A pine, 10 ins. diam., bears S. $82\frac{1}{4}^{\circ}$ W., 43 lks. dist., mkd. AP 427 FAIR BT.

raise a small mound of stone SW. of the corner.

Angle Point No. 428, which is monumented with the remains of the original tree corner, a juniper stump, 30 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

CHAINS

from which

A pine, 8 ins. diam., bears S. 3° E., 47 lks. dist., mkd. AP 428 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. $40\frac{1}{4}$ ° W., 43 lks. dist., with brass cap mkd. RM AP 428 FAIR 1970, and an arrow pointing to the true corner.

A pine, 8 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ W., 63 lks. dist., mkd. AP 428 FAIR BT.

Angle Point No. 430, which is monumented with the remains of the original tree corner, a deteriorated juniper stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R21E S 11 AP 430 FAIR

1970

from which

A pine, 14 ins. diam., bears S. 19 $3/4^{\circ}$ E., 18 lks. dist., mkd. AP 430 FAIR BT.

A pine, 8 ins. diam., bears N. $30\frac{1}{2}^{\circ}$ W., 87 lks. dist., mkd. AP 430 FAIR BT.

raise a mound of stone, 2 ft. base, 2 ft. high, NE. of the corner.

Angle Point No. 431, determined by the remains of the original tree corner, a stump hole, with a deteriorated juniper, 30 ins. diam., mkd. NB WMIR 431, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A pine, 14 ins. diam., bears N. 4° E., 61 lks. dist., mkd. AP 431 FAIR BT.

CHAINS


A pine, 8 ins. diam., bears S. 61° W., 32 lks. dist., mkd. AP 431 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

Angle Point No. 432, determined by the remains of the original tree corner, a stump hole, with a pine stump, blazed, no mks. visible, lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 18 ins. diam., bears N. $15\frac{1}{4}^{\circ}$ E., 104 lks. dist., mkd. AP 432 FAIR BT.


A pine, 10 ins. diam., bears N. 26° W., 78 lks. dist., mkd. AP 432 FAIR BT.

raise a mound of stone, 2 ft. base, 2 ft. high, NW. of the corner.

Angle Point No. 436, determined by the remains of the original tree corner, a stump hole with juniper stump lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears S. 28 $3/4^{\circ}$ E., 25 lks. dist., mkd. AP 436 FAIR BT.

A pine, 10 ins. diam., bears S. 20° W., 72 lks. dist., mkd. AP 436 FAIR BT.

CHAINS


Angle Point No. 437, which is monumented with a sandstone 14x12x4 ins., mkd. AP NB WMIR 437, firmly set, with small mound of stone to W., substantiated by the remains of the original bearing trees:

An oak, 8 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ E., 35 lks. dist. (record, S. $72\frac{1}{2}^{\circ}$ E.)

A pine stump, 12 ins. diam., bears S. 234° W., 48 lks. dist. (record, S. 24° 10' W., 49 lks. dist.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A pine, 12 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ W., 13 lks. dist., mkd. AP 437 FAIR BT.

A pine, 8 ins. diam., bears N. 27 $3/4^{\circ}$ W., 115 lks. dist., mkd. AP 437 FAIR BT.

deposit the original corner stone alongside the iron post and raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the corner.

Angle Point No. 438, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A pine, 20 ins. diam., bears S. 504° W., 3 lks. dist., mkd. AP 438 FAIR BT.

A pine, 24 ins. diam., bears N. $20\frac{1}{2}^{\circ}$ W., 127 lks. dist., mkd. AP 438 FAIR BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the corner.


Sec Memo daled 4-22-79 dist 128 183.

CHAINS

Angle Point No. 443, determined by the remains of the original tree corner, a stump hole, with a juniper stump, blaze visible but markings grown over, lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $1\frac{1}{4}$ ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.



from which

A pine, 6 ins. diam., bears S. 36 $3/4^{\circ}$ W., 175 lks. dist., mkd. X BT.

A pine, 14 ins. diam., bears N. 44 $3/4^{\circ}$ W., 46 lks. dist., mkd. AP 443 FAIR BT.

Angle Point No. 444, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam., blaze mks visible on the W. face.

from which

A pine, 8 ins. diam., bears N. 224° E., 30 lks. dist., - Desired mkd. AP 444 FAIR BT.


An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 13° W., 80 lks. dist., with brass cap mkd. RM AP 444 FAIR 1970, and an arrow pointing to the true corner.

A pine, 12 ins. diam., bears S. 48° W., 78 lks. dist., mkd. AP 444 FAIR BT.

Angle Point No. 445, determined by the remains of the original tree corner, a stump hole, with a juniper stump, mkd. R445 lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 42° E., 124 lks. dist., mkd. AP 445 FAIR BT.

Ached 2-25-76

CHAINS

A pine, 8 ins. diam, bears S. $17\frac{1}{2}^{\circ}$ W., 77 lks. dist., mkd. AP 445 FAIR BT.


raise a mound of stone, 2 ft. base, $2\frac{1}{2}$ ft. high, W. of the corner.

Angle Point No. 446, determined by the remains of the original tree corner, a stump hole, substantiated by the remains of an original bearing tree:

A pinon, 6 ins. diam., bears N. 62° W., 42 lks. dist., mkd. AP 446 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a collar of stone, 3 ft. base, to top, with brass cap mkd.



from which

A pinon, 10 ins. diam., bears N. $65\frac{1}{2}^{\circ}$ E., 105 lks. dist., mkd. AP 446 BT.


A pine, 8 ins. diam., bears S. 494° W., 15 lks. dist., mkd. AP 446 FAIR BT.

Angle Point No. 447, determined at record bearing and distance from the remains of an original bearing tree:

A stump hole, bears S. 78° W., 39 lks. dist., with a dead cedar mkd. AP 447 BT, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. $49\frac{1}{4}^{\circ}$ W., 44 lks. dist., mkd. AP 447 FAIR BT.

A pine, 8 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ W., 90 lks. dist., mkd. AP 447 BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 21 East Gila and Salt River Meridian, Arizona

CHAINS

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the corner.

Angle Point No. 449, which is monumented with the remains of the original tree corner, a juniper stump, 16 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 8 ins. diam., bears S. $82\frac{1}{2}^{\circ}$ E., 93 lks. dist., mkd. AP 449 BT.

A pine, 14 ins. diam., bears S. 46° W., 25 lks. dist., mkd. AP 449 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. $71\frac{1}{4}^{\circ}$ W., 16 lks. dist., with brass cap mkd. RM AP 449 FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 450, which is monumented with the original tree corner, a pine, 14 ins. diam., mkd. AP NB WMIR 450 on the S. face and BMFR on the N. face.

from which


A pine, 14 ins. diam., bears S. 74° E., 46 lks. dist., mkd. AP 450 FAIR BT.

A pine, 8 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ W., 91 lks. dist., mkd. AP 450 BT.

Angle Point No. 451, which is monumented with the remains of the original tree corner, a deteriorated, rotted pine stump, 5 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 18 ins. diam., bears S. $3\frac{1}{4}^{\circ}$ E., 116 lks. dist., mkd. AP 451 BT.

A pine, 14 ins. diam., bears N. $84\frac{1}{2}^{\circ}$ W., 87 lks. dist., mkd. AP 451 FAIR BT.

CHAINS

raise a mound of stone, 2 ft. base, 1 ft. high, E. of the corner.

Angle Point No. 452, which is monumented with the remains of the original tree corner, a juniper stump, 18 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Drive a spike nail in the center of the stump.

from which

A pine, 10 ins. diam., bears S. 81 $3/4^{\circ}$ E., 124 lks. dist., mkd. AP 452 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 10° W., $4\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 452 FAIR 1970, and an arrow pointing to the true corner.

A pine, 12 ins. diam., bears N. 89° W., 109 lks. dist., mkd. AP 452 BT.

Angle Point No. 453, which is monumented with the remains of the original tree corner, a pine stump, 18 ins. diam., portion of blaze on the S. face. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Drive a spike nail in the center of the stump.

from which

A pine, 8 ins. diam., bears S. 64° E., 13 lks. dist., mkd. AP 453 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 3 lks. dist., with brass cap mkd. RM AP 453 FAIR 1970, and an arrow pointing to the true corner.

A pine, 14 ins. diam., bears N. $74\frac{1}{2}^{\circ}$ W., 127 lks. dist., mkd. AP 453 BT.

Angle Point No. 455, determined by the remains of the original tree corner, a stump hole, with a juniper stump, lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

CHAINS

T9N R21E S 2 AP 455 FAIR

1970

from which


A pine, 12 ins. diam., bears N. 5 $3/4^{\circ}$ E., 22 lks. dist., mkd. AP 455 BT.

A pine, 16 ins. diam., bears S. 14 $3/4^{\circ}$ W., 90 lks. dist., mkd. AP 455 FAIR BT.

Angle Point No. 457, which is monumented with the remains of the original tree corner, a deteriorated juniper stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 4 $3/4^{\circ}$ E., 45 lks. dist., mkd. AP 457 FAIR BT.

A pine, 10 ins. diam., bears N. $79\frac{1}{4}^{\circ}$ W., 70 lks. dist., mkd. AP 457 BT.

Angle Point No. 458, which is monumented with the remains of the original tree corner, a juniper stump, 30 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Drive a spike nail in the center of the stump.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 5 lks. dist., with brass cap mkd. RM AP 458 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. $47 \ 3/4^{\circ} \ W.$, 23 lks. dist., mkd. AP $458 \ \text{FAIR}$ BT.

A pine, 12 ins. diam., bears N. 17° W., 69 lks. dist., mkd. AP 458 BT.

CHAINS

Angle Point No. 459, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.

T9N R21E S 3 AP 459 FAIR

1970

from which

A pine, 10 ins. diam., bears N. 71° E., 59 lks. dist. mkd. AP 459 BT.

Angle Point No. 460, which is monumented with a sandstone, 18x10x8 ins., mkd. AP WMIR 460, loosely set, substantiated by an original bearing tree:

A dead pine, 18 ins. diam., bears S. 75° E., 3^{4} lks. dist., mkd. AP 460 BT.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R21E S 3 AP 460 FAIR

1970

from which

A pine, 10 ins. diam., bears N. 41 $3/4^{\circ}$ E., 40 lks. dist., mkd. AP 460 BT.

A pine, 24 ins. diam., bears S. 77 $3/4^{\circ}$ E., 90 lks. dist., mkd. AP 460 FAIR.

deposit the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high S. of the corner.

The 64 Mile Corner, determined at record distance from the remains of the original bearing trees:

A stump hole, bears S. 25° E., 26 lks. dist. (record, S. 26° E.)

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 21 East Gila and Salt River Meridian, Arizona

CHAINS

A stump hole, bears S. $19\frac{1}{2}^{\circ}$ W., 80 lks. dist. (record, S. 19° W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a collar of stone, 4 ft. base, to top, with brass cap mkd.

T9N R21E S 3 64M FAIR 1970

from which

A pine, 12 ins. diam., bears N. 6 $3/4^{\circ}$ E., 84 lks. dist., mkd. 64M BT.

A pine, 8 ins. diam., bears S. 14° W., 59 lks. dist., mkd. 64M FAIR BT.

Angle Point No. 465, which is monumented with the remains of the original tree corner, a pine stump, 12 ins. diam., mkd. 465 on the N. face and an old pine log, mkd. BMFR, lying alongside.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 5° E., 3 lks. dist., with brass cap mkd. RM AP 465 FAIR 1970, and an arrow pointing to the true corner.

A pine, 14 ins. diam., bears S. 5° E., 55 lks. dist., mkd. AP 465 FAIR BT.

A pine, 14 ins. diam., bears N. 384° W., 89 lks. dist., mkd. AP 465 BT.

Angle Point No. 468, determined by the remains of the original tree corner, a stump hole, with a juniper stump, 30 ins. diam., lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R21E S 3 AP 468 FAIR

1970

from which

CHAINS

A pine, 12 ins. diam., bears S. $5\frac{1}{2}$ ° E., 72 lks. dist., mkd. AP 468 FAIR BT.

A pine, 14 ins. diam., bears N. 49 $3/4^{\circ}$ W., 28 lks. dist., mkd. AP 468 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 470, which is monumented with the original tree corner, a pine, 30 ins. diam., with blazes grown over on the N. and S. faces. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 16 ins. diam., bears S. 5 $3/4^{\circ}$ W., 43 lks. dist., mkd. AP 470 FAIR BT.

A pine, 14 ins. diam., bears N. 9 $3/4^{\circ}$ W., 94 lks. dist., mkd. AP 470 BT.

Angle Point No. 471, which is monumented with the remains of the original tree corner, a juniper stump, 14 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 16 ins. diam., bears S. 85° E., 75 lks. dist., mkd. AP 471 BT.

A pine, 16 ins. diam., bears S. $31\frac{1}{2}^{\circ}$ W., 99 lks. dist., mkd. AP 471 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 22 $3/4^{\circ}$ W., 11 lks. dist., with brass cap mkd. RM AP 471 FAIR 1970, and an arrow pointing to the true corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 21 East Gila and Salt River Meridian, Arizona

Angle Point No. 480, determined by the remains of the original tree corner, a stump hole, with a juniper stump, 36 ins. diam., mkd. BMIR, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R21E

AP 480 FAIR

1970

CHAINS

from which

A pine, 14 ins. diam., bears N. 11° E., 113 lks. dist., mkd. AP 480 FAIR BT.


A pine, 8 ins. diam., bears S. $53\frac{1}{2}^{\circ}$ W., 67 lks. dist., mkd. AP 480 BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. E. of the corner.

Angle Point No. 482, determined by the remains of the original tree corner, a stump hole, with a juniper, 36 ins. diam., mkd. AP NB lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears N. 4 $3/4^{\circ}$ E., 117 lks. dist., mkd. AP 482 BT.

A pine, 20 ins. diam., bears S. $10\frac{1}{2}^{\circ}$ W., 41 lks. dist., mkd. AP 482 FAIR BT.

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 21 East Gila and Salt River Meridian, Arizona

Angle Point No. 484, determined by the remains of the original tree corner, a stump hole, with a juniper stump, 24 ins. diam., portion of blaze mkd. BT, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R21E S 4 AP 484 FAIR 1970

from which

entation. North Boundary

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 9 North, Range 21 East Gila and Salt River Meridian, Arizona

CHAINS

A pine, 18 ins. diam., bears N. 22° E., 22 lks. dist., mkd. AP 484 BT.

A pine, 14 ins. diam., bears S. $7\frac{1}{4}^{\circ}$ E., 51 lks. dist., mkd. AP 484 FAIR BT.

raise a mound of stone, 2 ft. base, l_2^1 ft. high, S. of the corner.


The original tree was also used as a bearing tree for the 66 Mile Corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 21 East Gila and Salt River Meridian, Arizona

Angle Point No. 485, determined by the remains of the original tree corner, a pine stump, 24 ins. diam., mkd. AP WMIR, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.



from which


An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears NORTH, 13 lks. dist., with brass cap mkd. RM AP 485 FAIR 1968, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. 27° E., 46 lks. dist., mkd. AP 485 BT.

Angle Point No. 486, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 20 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

CHAINS

from which

A pine, 8 ins. diam., bears S. 81½° E., 72 lks. — dist., mkd. AP 486 BT.

1 - 25 - 76

Destroyed

A pine, 18 ins. diam., bears S. $6\frac{1}{2}$ ° W., 156 lks. dist., mkd. AP 486 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 488, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R21E S 33 AP 488 FAIR

1970

from which

A pine, 12 ins. diam., bears S. $77\frac{1}{4}^{\circ}$ E., 82 lks. dist., mkd. AP 488 FAIR BT.

A pine, 8 ins. diam., bears N. $71\frac{1}{2}^{\circ}$ W., 69 lks. dist., mkd. AP 488 BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the corner.

Angle Point No. 489, determined by the remains of the original tree corner, a stump hole, with a deteriorated pine stump, mkd. BMFR lying alongside.

At the corner point.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R21E S 22 AP 489 FAIR

1970

from which

A pine, 14 ins. diam., bears S. $30\frac{1}{2}^{\circ}$ E., 35 lks. dist., mkd. AP 489 BT.

CHAINS

A pine, 14 ins. diam., bears N. 24° W., 67 lks. dist., mkd. AP 489 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 493, which is monumented with the remains of the original tree corner, a pine stump, 20 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Drive a spike nail in the center of the stump.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, $4\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 493 FAIR 1970, and an arrow pointing to the true corner.

A pine, 8 ins. diam., bears S. $\frac{1}{4}$ ° W., 59 lks. dist., mkd. AP 493 FAIR BT.

A pine, 6 ins. diam., bears N. $16\frac{1}{2}$ ° W., 27 lks. dist., mkd. X BT.

Angle Point No. 495, which is monumented with the remains of the original tree corner, a juniper stump, 20 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 10 ins. diam., bears N. $56\frac{1}{2}^{\circ}$ E., 55 lks. dist., mkd. AP 495 BT.


An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears WEST, $3\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 495 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears N. $66\frac{1}{4}^{\circ}$ W., 46 lks. dist., mkd. AP 495 BT.

Angle Point No. 496, which is monumented with the remains of the original tree corner, a deteriorated stump. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.



from which

CHAINS

A pine, 20 ins. diam., bears S. $62\frac{1}{2}^{\circ}$ E., 189 lks. dist., mkd. AP 496 FAIR BT.

A juniper, 10 ins. diam., bears N. 784° W., 76 lks. dist., mkd. AP 496 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

Angle Point No. 500, determined from the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 24 ins. diam., bears N. $41\frac{1}{4}$ ° E., 90 lks. dist., mkd. AP 500 BT.

A pine, 6 ins. diam., bears S. 21° W., 117 lks. dist., mkd. AP 500 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

Angle Point No. 516, determined from the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



1970

from which

CHAINS

A juniper, 10 ins. diam., bears N. 85° W., 115 lks. dist., mkd. AP 516 BT.

A pine, 12 ins. diam., bears N. 75 $3/4^{\circ}$ W., 68 lks. dist., mkd. AP 516 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 518, which is monumented with the remains of the original tree corner, a pine stump, 20 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 18 ins. diam., bears S. 484° E., 65 lks. dist., mkd. AP 518 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears WEST, $3\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 518 FAIR 1970, and an arrow pointing to the true corner.

A pine, 24 ins. diam., bears N. $44\frac{1}{2}$ ° W., 46 lks. dist., mkd. AP 518 FAIR BT.

Angle Point No. 520, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 20 ins. diam., bears N. 55 $3/4^{\circ}$ E., 86 lks. dist., mkd. AP 520 BT.

A pine, 8 ins. diam., bears S. 59 $3/4^{\circ}$ W., 44 lks. dist., mkd. AP 520 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 20 East Gila and Salt River Meridian, Arizona

CHAINS

Angle Point No. 524, which is monumented with a sandstone 24x16x6 ins., mkd. WMIR on the S. face, firmly set, substantiated by the remains of the original bearing trees:

An oak, 18 ins. diam., bears S. $77\frac{1}{4}^{\circ}$ W., 70 lks. dist., mkd. AP 524 BT. (record, S. $76\frac{1}{2}^{\circ}$ E., 69 lks.)

A stump hole, bears S. $78\frac{1}{2}^{\circ}$ E., 28 lks. dist., with a dead pine, 14 ins. diam., mkd. AP 524 BT, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears N. 39° E., 101 lks. dist., mkd. AP 524 BT.

A pine, 12 ins. diam., bears S. 94° W., 20 lks. dist., mkd. AP 524 BT.

deposit the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, SW. of the corner.

Angle Point No. 525, which is monumented with the remains of the original tree corner, a pine stump, 28 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 8 ins. diam., bears N. 19° E., 116 lks. dist., mkd. AP 525 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, $6\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 525 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. $81\frac{1}{4}^{\circ}$ W., $1\frac{1}{4}$ lks. dist., mkd. AP 525 FAIR BT.

Angle Point No. 535, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 20 East Gila and Salt River Meridian, Arizona

CHAINS

TION R20E S 26 AP 535 FAIR

1970

from which

A pine, 18 ins. diam., bears S. $40\frac{1}{4}^{\circ}$ W., 59 lks. dist., mkd. AP 535 FAIR BT.


A pine, 10 ins. diam., bears N. 434° W., 43 lks. dist., mkd. AP 535 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 536, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears S. $6\frac{1}{2}^{\circ}$ E., 51 lks. dist., mkd. AP 536 FAIR BT.

A pine, 10 ins. diam., bears N. 8° W. 49 lks. dist., mkd. AP 536 BT.

Angle Point No. 537, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 30 ins. diam., blaze visible on the N. face.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

TION R20E S 26 AP 537 FAIR

1970

from which

CHAINS

A pine, 14 ins. diam., bears N. 57 $3/4^{\circ}$ E., 92 lks. dist., mkd. AP 537 BT.

A juniper, 14 ins. diam., bears S. $47\%^{\circ}$ W., 70 lks. dist., mkd. AP 537 FAIR BT.

A wood post, 4 ins. square, 2 ft. high, bears S. 61_{4}° W., 33 lks. dist.

Angle Point No. 543, which is monumented with the remains of the original tree corner, a juniper stump, 30 ins. diam., mkd. NBW MIR 543 on the SW. face and BMFR on the NE. face.

from which

A pine, 18 ins. diam., bears S. 14° E., 121 lks. dist., mkd. AP 543 BT.

A pine, 20 ins. diam., bears S. $74~3/4^{\circ}$ W., 125 lks. dist., mkd. AP 543 FAIR BT.

Angle Point No. 544, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam., blazes visible on the N. and S. faces.

from which

A juniper, 20 ins. diam., bears N. $16\frac{1}{2}$ ° E., 112 lks. dist., mkd. AP 544 BT.

A pine, 12 ins. diam., bears S. 73° W., 7^{\downarrow} 1ks. dist. mkd. AP 5^{\downarrow} 4 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set $2\frac{1}{4}$ ins. in the ground, for a reference monument, bears WEST, 7 lks. dist., with brass cap mkd. RM AP $5\frac{1}{4}$ FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 548, which is monumented by a reinforcing steel rod, firmly set in a stump hole, origin unknown. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, over the steel rod,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R20E S 23 AP 548 FAIR

1970

from which

A pine, 14 ins. diam., bears N. 714° E., 99 lks. dist., mkd. AP 548 BT.

CHAINS

A pine, 10 ins. diam., bears S. 4 $3/4^{\circ}$ E., 120 lks. dist., mkd. AP 548 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, SW. of the corner.

Angle Point No. 556, which is monumented with the remains of the original tree corner, a juniper stump, 12 ins. diam., no mks. visible. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 14 ins. diam., bears N. $7\frac{1}{4}$ ° E., 23 lks. dist., mkd. AP 556 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 7 lks. dist., with brass cap mkd. RM AP 556 FAIR 1970, and an arrow pointing to the true corner.

A pine, 15 ins. diam., bears S. 20° W., 93 lks. dist., mkd. AP 556 FAIR BT.

Angle Point No. 561, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

from which

A pine, 12 ins. diam., bears S. 45 $3/4^{\circ}$ E., 78 lks. dist., mkd. AP 561 FAIR BT.

A pine, 16 ins. diam., bears N. 77° W., 124 lks. dist., mkd. AP 561 BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, E. of the corner.

Angle Point No. 569, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 10 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

CHAINS

TION R2OE S 21 AP 569 FAIR

1970

from which

A pine, 10 ins. diam., bears S. 84° E., 80 lks. dist., mkd. AP 569 FAIR BT.


A pine, 8 ins. diam., bears N. $44\frac{1}{2}^{\circ}$ W., 79 lks. dist., mkd. AP 569 BT.

raise a mound of stone, 2 ft. base, 2 ft. high, SE. of the corner.

Angle Point No. 575, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears S. 47 $3/4^{\circ}$ E., 76 lks. dist., mkd. AP 575 FAIR BT.

A pine, 12 ins. diam., bears N. 36° W., 88 lks. dist., mkd. AP 575 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Angle Point No. 587, which is monumented with the remains of the original tree corner, a pine stump, 18 ins. diam., with a log blazed but not legible, lying alongside.

At the corner point

Drive a spike nail in the center of the stump.

from which

A pine, 8 ins. diam., bears S. $48 \mbox{$^\circ$_1}$ E., 44 lks. dist., mkd. AP 587 FAIR BT.

CHAINS


An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 15 lks. dist., with brass cap mkd. RM AP 587 FAIR 1970, and an arrow pointing to the true corner.

A pine, 8 ins. diam., bears N. $73\frac{1}{4}^{\circ}$ W., 121 lks. dist., mkd. AP 587 BT.

Angle Point No. 590, determined by the remains of the original tree corner, a stump hole, with a burned pine, mkd. AP NB WMIR 590 on the SE. and BMFR on the NW. faces, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A pine, 9 ins. diam., bears S. 50° E., 55 lks. dist., mkd. AP 590 FAIR BT.

A pine, 12 ins. diam., bears S. 81 $3/4^{\circ}$ W., 81 lks. dist., mkd. AP 590 BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the corner.

Angle Point No. 591, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 12 ins. diam., no mks. visible, substantiated by the remains of the original bearing trees:

A pine, 24 ins. diam., bears N. 74° W., 22 lks. dist., mkd. AP 591 BT.

A pine, 26 ins. diam., bears N. $11\frac{1}{2}^{\circ}$ W., 37 lks. dist., mkd. AP 591 BT. (record, N. 10° W.)

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

1970

from which

An alligator juniper, 16 ins. diam., bears N. $87\frac{1}{2}^{\circ}$ E., 61 lks. dist., mkd. AP 591 FAIR BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 20 East Gila and Salt River Meridian, Arizona

CHAINS

A pine, 16 ins. diam., bears N. 7 $3/4^{\circ}$ W., 83 lks. dist., mkd. AP 591 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 597, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 17 $3/4^{\circ}$ E., 75 lks. dist., mkd. AP 597 FAIR BT.

A pine, 7 ins. diam., bears N. 49 $3/4^{\circ}$ W., 10 lks. dist., mkd. AP 597 BT.

raise a mound of stone, 2 ft. base, 1 ft. high, S. of the corner.

Angle Point No. 604, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R2OE S 31 AP 604 FAIR

1970

from which

A pine, 14 ins. diam., bears S. 57 $3/4^{\circ}$ W., 80 lks. dist., mkd. AP 604 FAIR BT.

A pine, 10 ins. diam., bears N. 20° W., 10^{4} lks. dist., mkd. AP 60^{4} BT.

CHAINS

The closing cor. of secs. 31 and 36, Tps. 10 N., Rs. 19 and 20 E., monumented with an iron post, 2 ins. diam., firmly set, projecting 6 ins. above the ground, bears S. 85° 30' W., 84 lks. dist., with brass cap mkd. Tlon R19E R20E CC S31 S36 FAIR 1915.

raise a mound of stone, 2 ft. base, 1 ft. high, S. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 19 East Gila and Salt River Meridian, Arizona

Angle Point No. 625, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

311 · ...

A pine, 20 ins. diam., bears N. 51° E., 53 lks. dist., mkd. AP 625 BT.

A pine, 20 ins. diam., bears S. 3 $3/4^{\circ}$ W., 83 lks. dist., mkd. AP 625 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 40 $3/4^{\circ}$ W., $10\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 625 FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 626, which is monumented with the original tree corner, a pine, 30 ins. diam., mkd. R, blaze grown over.

from which

A pine, 8 ins. diam., bears N. $43\ 3/4^{\circ}$ E., 116 lks. dist., mkd. AP 626 BT.

A pine, 14 ins. diam., bears S. $32\frac{1}{2}^{\circ}$ E., 57 lks. dist., mkd. AP 626 FAIR BT.

Angle Point No. 653, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 14 ins. diam., bears N. 17° E., 58 lks. dist., mkd. AP 653 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 27 lks. dist., with brass cap mkd. RM AP 653 FAIR 1970, and an arrow pointing to the true corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 19 East Gila and Salt River Meridian, Arizona

CHAINS

A pine, 10 ins. diam., bears S. $73\frac{1}{4}^{\circ}$ W., 82 lks. dist., mkd. AP 653 FAIR BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 18 East Gila and Salt River Meridian, Arizona

Angle Point No. 689, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R18E S 12 AP 689 FAIR

1970

from which

A pine, 12 ins. diam., bears N. 1° E., 99 lks. dist., mkd. AP 689 BT.

A pine, 14 ins. diam., bears S. $7\frac{1}{2}^{\circ}$ E., 84 lks. dist., mkd. AP 689 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 690, determined by the remains of the original tree corner, a stump hole, with a pine tree, no mks. visible, lying alongside. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R18E S 12 AP 690 FAIR

1970

from which

A pine, 8 ins. diam., bears N. 2 $3/4^{\circ}$ E., 70 lks. dist., mkd. AP 690 BT.

A pine, 10 ins. diam., bears S. 5 $3/4^{\circ}$ W., 86 lks. dist., mkd. AP 690 FAIR BT.


CHAINS

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 692, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 18 ins. diam., bears N. $73\frac{1}{4}^{\circ}$ E., 105 lks. dist., mkd. AP 692 BT.


A pine, 12 ins. diam., bears N. $88\ 3/4^{\circ}$ W., $59\ 1ks$. dist., mkd. AP $692\ FAIR\ BT$.

raise a mound of stone, 3 ft. base, 2 ft. high, SW. of the corner.

Angle Point No. 697, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



from which

A pine, 12 ins. diam., bears N. $39\frac{1}{2}^{\circ}$ E., 88 lks. dist., mkd. AP 697 BT.

A pine, 8 ins. diam., bears S. $13\frac{1}{4}$ ° W., 63 lks. dist., mkd. AP 697 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

CHAINS

Angle Point No. 706, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 30 ins. diam., bears S. 80° E., 82 lks. dist., mkd. AP 706 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, $12\frac{1}{2}$ lks. dist., with brass cap mkd. RM AP 706 FAIR 1970, and an arrow pointing to the true corner.

A pine, 8 ins. diam., bears S. $64\frac{1}{2}^{\circ}$ W., 85 lks. dist. mkd. AP 706 FAIR BT.

Angle Point No. 708, which is monumented with the remains of the original tree corner, a deteriorated pine stump, 24 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point, the center of the root crown,

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R18E S 2

AP 708 ' FAIR

1970

from which

A pine, 8 ins. diam., bears S. 134° E., 67 lks. dist., mkd. AP 708 FAIR BT.

A pine, 8 ins. diam., bears N. $74\frac{1}{4}^{\circ}$ W., 14 lks. dist., mkd. AP 708 BT.

raise a mound of stone, 3 ft. base, 3 ft. high, S. of the corner.

Angle Point No. 714, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam. in line with blazed line trees. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 18 ins. in the ground, in a collar of stone, 3 ft. base, to top, for a reference monument, bears SOUTH, 5 lks. dist., with brass cap mkd. RM AP 714 FAIR 1970, and an arrow pointing to the true corner.

CHAINS

A pine, 14 ins. diam., bears S. 43° W., 87 lks. dist., mkd. AP 714 FAIR BT.

A pine, 8 ins. diam., bears N. 34° W., 94 lks. dist., mkd. AP 714 BT.

Angle Point No. 715, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R18E S 3 AP 715 FAIR

1970

from which

A pine, 14 ins. diam., bears S. $5\frac{1}{2}^{\circ}$ W., 47 lks. dist., mkd. AP 715 FAIR BT.

A pine, 8 ins. diam., bears N. 30 $3/4^{\circ}$ W., 37 lks. dist., mkd. AP 715 BT.

raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, S. of the corner.

Angle Point No. 716, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 12 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 52 lks. dist., mkd. AP 716 BT.

A pine, 14 ins. diam., bears S. 60° W., 127 lks. dist., mkd. AP 716 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

CHAINS

Angle Point No. 718, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R18E S 3 AP 718 FAIR

1970

from which

A pine, 10 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ E., 71 lks. dist., mkd. AP 718 BT.

A pine, 20 ins. diam., bears S. 77 $3/4^{\circ}$ W., 140 lks. dist., mkd. AP 718 FAIR BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 11 North, Range 18 East Gila and Salt River Meridian, Arizona

Angle Point No. 726, which is monumented with the remains of the original tree corner, a pine stump, 24 ins. diam., with blaze marks on the N. face. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 20 ins. diam., bears N. $32\frac{1}{2}^{\circ}$ E., 99 lks. dist., mkd. AP 726 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 5° E., 17 lks. dist., with brass cap mkd. RM AP 726 FAIR 1970, and an arrow pointing to the true corner.

A pine, 8 ins. diam., bears S. 42 $3/4^{\circ}$ W., 81 lks. dist., mkd. AP 726 FAIR BT.

Angle Point No. 754, which is monumented with the remains of the original tree corner, a pine stump, 18 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

CHAINS

Tlln R18E S 32

AP 754 FAIR

1970

from which

A pine, 10 ins. diam., bears S. $38 \ 3/4^{\circ} \ W.$, 90 lks. dist., mkd. AP $754 \ \text{FAIR BT}.$

A pine, 24 ins. diam., bears N. $56\frac{1}{2}$ ° W., 55 lks. dist., mkd. AP 754 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 755, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TIIN R18E S 32 AP 755 FAIR

1970

from which

A pine, 10 ins. diam., bears S. $13\frac{1}{2}^{\circ}$ W., 62 lks. dist., mkd. AP 755 FAIR BT.

A pine, 10 ins. diam., bears N. $84\frac{1}{4}$ ° W., 31 lks. dist., mkd. AP 755 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 11 North, Range 17 East Gila and Salt River Meridian, Arizona

Angle Point No. 771, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 11 North, Range 17 East Gila and Salt River Meridian, Arizona

CHAINS

TllN Rl7E s 36

AP 771 FAIR

1970

from which

A pine, 8 ins. diam., bears N. 274° E., 67 lks. dist., mkd. AP 771 BT.

A pine, 10 ins. diam., bears S. 4° E., 91 lks. dist., mkd. AP 771 FAIR BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the corner.

Angle Point No. 784, which is monumented with the remains of the original tree corner, a pine stump, 12 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 8 ins. diam., bears N. 21½° E., 55 lks. dist., mkd. AP 784 BT.

A pine, 8 ins. diam., bears S. 54 $3/4^{\circ}$ E., 155 lks. dist., mkd. AP 784 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 3 lks. dist., with brass cap mkd. RM AP 784 FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 786, which is monumented with the remains of the original tree corner, a pine stump, 16 ins. diam., blazes visible on the N. and S. faces.

from which

A pine, 12 ins. diam., bears S. $81\frac{1}{2}$ ° E., 102 lks. dist., mkd. AP 786 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 4 lks. dist., with brass cap mkd. RM AP 786 FAIR 1970, and an arrow pointing to the true corner.

A pine, 14 ins. diam., bears N. $33\frac{1}{4}^{\circ}$ W., 72 lks. dist., mkd. AP 786 FAIR BT.

Angle Point No. 788, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 11 North, Range 17 East Gila and Salt River Meridian, Arizona

CHAINS

TllN R17E S 34 AP 788 FAIR 1970

from which

A pine, 16 ins. diam., bears S. 3° E., 107 lks. dist., mkd. AP 788 FAIR BT.

A pine, 18 ins. diam., bears S. 89° W., 75 lks. dist., mkd. AP 788 BT.

raise a mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 17 East Gila and Salt River Meridian, Arizona

Angle Point No. 790, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam. This position is harmoniously related to existing evidence of adjacent angle points.

from which

A pine, 8 ins. diam., bears N. 6 $3/4^{\circ}$ E., 73 lks. dist., mkd. AP 790 BT.

A pine, 14 ins. diam., bears S. $76\frac{1}{2}^{\circ}$ E., 65 lks. dist., mkd. AP 790 FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 10 ins. in the ground, to bedrock, in a collar of stone, $2\frac{1}{2}$ ft. base, to top, for a reference monument, bears SOUTH, 3 lks. dist., with brass cap mkd. RM AP 790 FAIR 1970, and an arrow pointing to the true corner.

Angle Point No. 792, which is monumented with the original tree corner, a pine, 14 ins. diam., mkd. WMIR 792 on the E. face and BMFR on the W. face.

from which

A pine, 10 ins. diam., bears N. 34° E., 41 lks. dist., mkd. AP 792 FAIR BT.

A pine, 14 ins. diam., bears S. 63 $3/4^{\circ}$ W., 140 lks. dist., mkd. AP 792 BT.

Angle Point No. 797, which is monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap mkd.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 17 East Gila and Salt River Meridian, Arizona

CHAINS

TION R17E S 3 AP 797 FAIR

1936

from which new bearing trees:


A pine, 24 ins. diam., bears S. 57° E., 116 lks. dist., mkd. AP 797 FAIR BT.

A pine, 10 ins. diam., bears N. 56° W., 25 lks. dist., mkd. AP 797 BT.

Angle Point No. 825, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 8 ins. diam., bears N. 23 $3/4^{\circ}$ E., 15 lks. dist., mkd. AP 825 BT.

A pine, 8 ins. diam., bears S. $73\frac{1}{2}^{\circ}$ W., 29 lks. dist., mkd. AP 825 FAIR BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the corner.

Angle Point No. 828, determined by the remains of the original tree corner, a stump hole, with a pine, 12 ins. diam., mkd. BMFR on the N. face and AP NB WMIR 828 on the S. face, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

TION R17E

AP 828 FAIR

1970

from which

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 17 East Gila and Salt River Meridian, Arizona

CHAINS

A pine, 18 ins. diam., bears N. $9\frac{1}{2}^{\circ}$ E., 31 lks. dist., mkd. AP 828 BT.

A pine, 8 ins. diam., bears S. 10 $3/4^{\circ}$ E., 78 lks. dist., mkd. AP 828 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Angle Point No. 831, determined by the remains of the original tree corner, a stump hole. This positon is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R17E S 7 AP 831 FAIR

1970

from which

A pine, 8 ins. diam., bears N. $75\frac{1}{2}^{\circ}$ E., 30 lks. dist., mkd. AP 831 BT.

A pine, 24 ins. diam., bears S. 1° W., 102 lks. dist., mkd. AP 831 FAIR BT.

raise a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

The 102 Mile Corner, which is monumented with a granite stone, 14x8x6 ins., no mks. visible, firmly set in a mound of stone, substantiated by the remains of the original bearing trees:

A pine stump, 36 ins. diam., bears N. $16\frac{1}{2}^{\circ}$ E., 69 lks. dist. (record, N. $11\frac{1}{2}^{\circ}$ E., 68 lks.)

A pine, 30 ins. diam., bears S. $55\frac{1}{2}^{\circ}$ E., 25 lks. dist., mkd. WMIR BT. (record, S. $52\frac{1}{2}^{\circ}$ E.)

A stump hole, bears N. 1° W., 108 lks. dist. (record, NORTH)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R17E 102M S 7 FAIR

1970

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 17 East Gila and Salt River Meridian, Arizona

CHAINS

from which

A pine, 10 ins. diam., bears N. $41\frac{1}{2}^{\circ}$ E., 104 lks. dist., mkd. 102M FAIR BT.

A pine, 10 ins. diam., bears S. $17\frac{1}{5}$ ° E., 40 lks. dist., mkd. AP 102M BT.

deposit the original corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

Angle Point No. 833, determined by the remains of the original tree corner, a stump hole, with a pine, 36 ins. diam., mkd. APNB WMIR on the S. face, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, 3 ft. base, to top, with brass cap mkd.



1970

from which

A pine, 10 ins. diam., bears S. 68 $3/4^{\circ}$ E., 55 lks. dist., mkd. AP 833 FAIR BT.

A pine, 10 ins. diam., bears S. 18° W., 94 lks. dist., mkd. AP 833 BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 16 East Gila and Salt River Meridian, Arizona

Angle Point No. 844, determined by the remains of the original tree corner, a stump hole. This position is harmoniously related to existing evidence of adjacent angle points.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, $2\frac{1}{2}$ ft. base, to top, with brass cap mkd.

TION R16E S 1

AP 844 FAIR

1970

from which

A pine, 12 ins. diam., bears S. $50\frac{1}{4}$ ° E., 72 lks. dist., mkd. AP 844 FAIR BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 16 East Gila and Salt River Meridian, Arizona

CHAINS

Angle Point No. 845, which is monumented with the remains of the original tree corner, a pine stump, 30 ins. diam., blazes visible on the N. and S. faces. This position is harmoniously related to existing evidence of adjacent angle points.

from which

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 7 lks. dist., with brass cap mkd. RM AP 845 FAIR 1970, and an arrow pointing to the true corner.

A pine, 13 ins. diam., bears S. 36° W., 89 lks. dist., mkd. AP 845 FAIR BT.

A pine, 14 ins. diam., bears N. $26\frac{1}{2}^{\circ}$ W., 107 lks. dist., mkd. AP 845 BT.

Angle Point No. 871, determined by the remains of the original tree corner, a stump hole, with a pine, 30 ins. diam., mkd. BMFR, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, to top, with brass cap mkd.

TION RL6E S 9 AP 871 FAIR

1970

from which

A fir, 18 ins. diam., bears N. 58 $3/4^{\circ}$ E., 53 lks. dist., mkd. AP 871 BT.

A pine, 8 ins. diam., bears S. 55 $3/4^{\circ}$ W., 35 lks. dist., mkd. AP 871 FAIR BT.

Angle Point No. 880, which is monumented with the remains of the original tree corner, a pine stump, 20 ins. diam., mkd. BMFR on the NE. face and NB. on the SW. face.

from which

A pine, 12 ins. diam., bears N. 74° E., 128 lks. dist., mkd. AP 880 BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, 6 lks. dist., with brass cap mkd. RM AP 880 FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears S. $67\frac{1}{2}^{\circ}$ W., 48 lks. dist., mkd. AP 880 FAIR BT.


Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 16 East Gila and Salt River Meridian, Arizona

CHAINS

Angle Point No. 892, determined by the remains of the original tree corner, a stump hole, with a deteriorated, rotted pine, mkd. BMFR on one side, lying alongside.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.



1970

from which

A pine, 8 ins. diam., bears N. 60° E., 54 lks. dist., mkd. AP 892 FAIR BT.

A pine, 10 ins. diam., bears N. $33\frac{1}{2}^{\circ}$ W., 62 lks. dist., mkd. AP 892 BT.

raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, E. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 15½ East Gila and Salt River Meridian, Arizona

The $11\frac{14}{2}$ Mile Corner, which is monumented with a limestone, in place, $30x2\frac{1}{4}x2\frac{1}{4}$ ins., mkd. WMIR on the SE. face, and $11\frac{14}{2}$ M on the E. face, firmly set, substantiated by the remains of the original bearing trees:

An oak, 14 ins. diam., bears N. 48° E., 20 lks. dist., blaze grown over (record, N. 47° E.)

An oak, 14 ins. diam., bears N. 75° E., 42 lks. dist., blaze grown over.

An oak, 8 ins. diam., bears N. 36° W., 18 lks. dist., blaze grown over. (record, N. 39° W., 19 lks. dist.)

An oak, 14 ins. diam., bears N. $18\frac{1}{2}$ ° W., 29 lks. dist., blaze grown over. (record, N. 21° W., 30 lks. dist.)

from which new bearing trees:

A fir, 16 ins. diam., bears N. 68° E., 46 lks. dist., mkd. $114\frac{1}{2}M$ FAIR BT.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 26 ins. in the ground, for a reference monument, bears SOUTH, $6\frac{1}{2}$ lks. dist., with brass cap mkd. RM $11\frac{1}{2}$ M FAIR 1970, and an arrow pointing to the true corner.

A pine, 10 ins. diam., bears N. $3/4^{\circ}$ W., 72 lks. dist., mkd. AP $114\frac{1}{2}M$ BT.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 10 North, Range 15½ East Gila and Salt River Meridian, Arizona

CHAINS

The 115½ Mile Corner, which is monumented with a granite stone, 24x20x14 ins., mkd. 115½ on the NE. face, set 16 ins. in the ground, in a mound of stone, 3 ft. base, 2 ft. high, substantiated by the remains of the original bearing trees:

A pine, 24 ins. diam., bears S. 89½° E., 34 lks. dist., mkd. NB WMIR 115½M BT. (record, EAST, 33 lks.)

A dead pine stump, 10 ins. diam., bears N. 52° W., 31 lks. dist., mkd. NB WMIR 115½M BT. (record, N. 51¼° W., 32 lks.)

A pine, 24 ins. diam., bears N. 26 $3/4^{\circ}$ W., 31 lks. dist., blazed. (record, N. $26\frac{1}{2}^{\circ}$ W.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TION R15½E S 8 115½M FAIR

1970

from which

A spruce, 8 ins. diam., bears N. $8\frac{1}{2}^{\circ}$ E., 86 lks. dist., mkd. $115\frac{1}{2}$ M BT.

A spruce, 8 ins. diam., bears S. 404° W., 76 lks. dist., mkd. $115\frac{1}{2}M$ FAIR BT.

deposit the original corner stone alongside the iron post and rebuild a mound of stone, 3 ft. base, 2 ft. high, S. of the corner.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 11 North, Range 15 East Gila and Salt River Meridian, Arizona

The 118½ Mile Corner, which is monumented with a granite stone, 24x20x20 ins., mkd. NB WMIR 118½M, firmly set, substantiated by the remains of the original bearing trees:

A pine, 48 ins. diam., bears N. 61° E., 34 lks. dist. mkd. NB WMIR BT. (record, N. $60\frac{1}{2}$ ° E., 32 lks.)

A pine, 36 ins. diam., bears S. 48° W., 81 lks. dist. blaze grown over. (record, S. $46\frac{1}{2}^{\circ}$ W., 80 lks.)

A pine, 40 ins. diam., bears N. 47° W., 53 lks. dist. mkd. NB WMIR BT. (record, N. 52° W., 51 lks.)

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, with brass cap mkd.

Remonumentation, North Boundary of the Fort Apache Indian Reservation in Township 11 North, Range 15 East Gila and Salt River Meridian, Arizona

CHAINS

TllN R15E S 32 118½M FAIR

1970

from which

A pine, 10 ins. diam., bears N. 22° E., 36 lks. dist., mkd. $118\frac{1}{2}$ M BT.

A pine, 10 ins. diam., bears S. 56° W., 31 lks. dist., mkd. $118\frac{1}{2}$ M FAIR BT.

deposit the original corner stone alongside the iron post and raise a mound of stone, 4 ft. base, 3 ft. high, W. of the corner.

Remonumentation, West Boundary of the Fort Apache Indian Reservation in Township 10½ North, Range 15 East Gila and Salt River Meridian, Arizona

The $1\frac{1}{2}$ Mile Corner, which is monumented with a granite stone, 18x12x12 ins., mkd. B $\frac{1}{2}$ on the W. face, with a mound of stone NW. of the corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, with brass cap mkd.

T10½N R15E 1½M S 23 + FAIR 1970

from which

A pine, 14 ins. diam., bears N. 83° E., 69 lks. dist., mkd. $1\frac{1}{2}M$ FAIR BT.

A pine, 18 ins. diam., bears N. $72\frac{1}{4}^{\circ}$ W., 25 lks. dist., mkd. $1\frac{1}{2}$ M BT.

deposit the original corner stone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Remonumentation, West Boundary of the Fort Apache Indian Reservation in Township 7 North, Range 15 East Gila and Salt River Meridian, Arizona


The $22\frac{1}{2}$ Mile Corner, which is monumented with a sandstone, 20x14x6 ins., mkd. WMIR WB, loosely set with a scattered mound of stone SW. of the corner.

At the corner point

Remonumentation, West Boundary of the Fort Apache Indian Reservation in Township 7 North, Range 15 East Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.



from which

A juniper, 12 ins. diam., bears N. $42\frac{1}{2}^{\circ}$ E., 91 lks. dist., mkd. $22\frac{1}{2}$ M FAIR BT.

A juniper, 10 ins. diam., bears S. 42° W., 46 lks. dist., mkd. $22\frac{1}{2}$ M BT.


deposit the original corner stone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Remonumentation, West Boundary of the Fort Apache Indian Reservation in Township 6 North, Range 15 East (unsurveyed) Gila and Salt River Meridian, Arizona

The 32½ Mile Corner, which is monumented with a granite stone, 20x16x16 ins., mkd. WMIR WB 32½, set 6 ins. in the ground, with a mound of stone, 3 ft. base, 2 ft. high. W. of the corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, to bedrock, encircled in a collar of stone, $3\frac{1}{2}$ ft. base, 1 ft. high, with brass cap mkd.



from which

A cedar, 8 ins. diam., bears N. 30° E., 105 lks. dist., mkd. FAIR $32\frac{1}{2}M$ BT.

deposit the original corner stone alongside the iron post.

Remonumentation, West Boundary of the
Fort Apache Indian Reservation in
Township 5 North, Range 15 East (portion unsurveyed)
Gila and Salt River Meridian, Arizona

The 3¹½ Mile Corner, which is monumented with a granite stone, 12x12x10 ins., no mks. visible, loosely set. (record, a conglomerate rock, 13x13x13 ins.) This position is harmoniously related to existing evidence of other mile corners in the area.

Remonumentation, West Boundary of the
Fort Apache Indian Reservation in
Township 5 North, Range 15 East (portion unsurveyed)
Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TNF \ FAIF \ 34\frac{1}{2}\h

from which

A cedar, 8 ins. diam., bears N 21° E., 119 lks. dist., mkd. FAIR 34½M BT.

deposit the granite stone alongside the iron post and raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, E. of the corner.

Corner is situated 208 lks. W. of fence, bearing N. and

The 35 Mile Corner, which is monumented with a granite stone, 22xl4xl0 ins., mkd. WMIR WB 35M on the E., set 3 ins. in the ground.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

TNF FAIR
35M

from which

A cedar, 10 ins. diam., bears N. 76° E., 56 lks. dist., mkd. FAIR 35M BT.

deposit the original corner stone alongside the iron post and raise a mound of stone, E. of the corner.

Corner is situated on north slope, approximately 40 ft. N. of rock cliff 40 ft. high.

The 37 Mile Corner, which is monumented with a sandstone, 18x12x10 ins., with chisel marks W visible only, set 6 ins. in the ground, with a mound of stone, 3 ft. base, 1 ft. high, W. of the corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., $2\frac{1}{4}$ ins. in the ground, with brass cap mkd.

TNF \ FAIF 37M

Remonumentation, West Boundary of the Fort Apache Indian Reservation in Township 5 North, Range 15 East (portion unsurveyed) Gila and Salt River Meridian, Arizona

CHAINS

from which

A cedar, 4 ins. diam., bears S. 52° E., 121 lks. dist., mkd. X BT.

deposit the original corner stone alongside the iron post and rebuild the mound of stone, 2 ft. base, 2 ft. high, E. of the corner.

Corner is situated 10 lks.S.of south edge of wash and 83 lks. west of fence, bearing N. and S.

Remonumentation, West Boundary of the Fort Apache Indian Reservation in Township 4½ North, Range 15½ East(unsurveyed) Gila and Salt River Meridian, Arizona

The 39 Mile Corner, which is monumented with a sandstone, 12x12x10 ins., mkd. WMIR WB 39M, set 8 ins. in the ground with a mound of stone, 6 ft. base, 2 ft. high, N. of the corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

deposit the original corner stone alongside the iron post and rebuild the mound of stone, 3 ft. base, 2 ft. high, E. of the corner.

Form 9180-8 (March 1969)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
William L. McDorman	Surveying Aid
Julian J. Cordova	Surveying Aid
Santiago T. Chavez	Surveying Aid
Raymus R. Albert	Surveying Aid
Curtis K. Albert	Surveying Aid
Daniel Parker	Surveying Aid



CERTIFICATE OF SURVEY

(I) (WK), Marlin G. Livermore II

, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day

of March , 1970, (I) (NE) have remonumented certain mile corners and angle points on the north and west boundaries of the Fort Apache Indian Reservation in Townships 6 and 7 North, Ranges 26 and 27 East, Townships 8 North, Ranges 22 through 26 East, Townships 9 North, Ranges 21, 22, 24, and 2 East, Townships 10 North, Ranges 15½ through 21 East, Townships 11 North, Ranges 15, 17, and 18 East (north boundary) and Township 4½ North, Range 15½ East, Townships 5 through 7 and 10½ North, Range 15 East (west boundary)

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), XXXX and under (my) XXXXX direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 2, 1972
(Date)

(Cadastral Surveyor)

Marlin G. Livermore II

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUDMITTED FOR APPROVAL
Date Jun 1 5 1972

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of certain mile corners and angle points on the north and west boundaries of the Fort Apache Indian Reservation in Townships 6 and 7 North, Ranges 26 and 27 East, Townships 8 North, Ranges 22 through 26 East, Townships 9 North, Ranges 21, 22, 24, and 25 East, Townships 10 North, Ranges 15½ through 21 East, Townships 11 North, Ranges 15, 17, and 18 East (north boundary) and Township 4½ North, Range 15½ East, Townships 5 through 7 and 10½ North, Range 15 East (west boundary), Gila and Salt River Meridian, Arizona

executed by Marlin G. Livermore II, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

SEP 4 1974

(Date)

(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I	CERTIFY	That	the foregoing	transcript	of	the	field	notes	of	the	above-described	surveys	in
			_	_				_					

, is a true copy of the original field notes.

(Chief, Division of Cadastral Survey) 6RQ 849-626

(Date)




United States Department of the Interior

BUREAU OF LAND MANAGEMENT

DENVER SERVICE CENTER DENVER FEDERAL CENTER, BUILDING 50 DENVER. COLORADO 80225

IN REPLY REFER TO 9633.29 (D-401) Group No. 522 Arizona



June 22, 197

. 72. Voorher

Memorandum

To:

SD, Arizona

From:

Chief, Cadastral Survey Examination and Approval Staff

Subject: Erroneous Bearing Tree Location

An erroneous distance to a bearing tree at Angle Point No. 438, Fort Apache Indian Reservation, T. 9 N., R. 21 E., Gila and Salt River Meridian, Arizona, has been discovered.

The field notes of this survey call for the bearing tree in question to be S. $50\frac{1}{4}^{\circ}$ W., 13 lks. distant while the measured distance is actually 128 lks. You are hereby authorized to make a marginal notation on the original field notes showing the correct distance of 128 lks. The duplicate set of field notes, which are in the custody of this office, will also have the appropriate marginal notation

> /Jhief GA L&MO_ ـC.S. Engr. Appr. Prot. T. E.



United States Department of the Interior BUREAU OF INDIAN AFFAIRS

FORT APACHE AGENCY Whiteriver, Arizona 85941

February 25, 1976

FEB 3 / 16

CO Trais management

LO Trais management

Co Trais managemen

Mr. Boyd S. Owens, Chief Branch of Cadastral Survey Arizona State Office Bureau of Land Management 2400 Valley Bank Center Phoenix, Arizona 85073

Dear Mr. Owens:

The following accessories to North Boundary corners were lost due to road construction when the rim road was relocated during 1975. These accessories were within the new road alignment. No corner monuments were disturbed.

Angle Point 444

8 inch diameter yellow pine marked AP 444 FAIR BT which bore N $22\frac{1}{4}^{0}$ E, 50 links distant.

Angle Point 444 is now on the reservation fence and 24 links south of the center line of the new rim road.

Angle Point 461

16 inch diameter yellow pine marked AP 461 which bore N 89 W, 45 links distant.

Angle Point 461 is now on the reservation fence and 24 links south of the center line of the new rim road.

Angle Point 462

12 inch diameter yellow pine marked AP 462 BT which bore S 87 3/4 W, 59 links distant.

Angle Point 462 is now on the reservation fence and 28 links south of the center line of the new rim road.

See letter dated April 8, 1976 for revised descriptions
of Ap 462. - Book 4935



Angle Point 486

8 inch yellow pine marked AP 486 BT which bore S $81\frac{10}{2}$ E, 72 links distant.

Angle Point 486 is now on the reservation fence and 24 links south of the center line of the new rim road.

Angle Point 502

8 inch yellow pine marked AP 502 BT which bore N 21° E, 49 links distant.

Angle Point 502 is now on the reservation fence and 38 links south of the center line of the new rim road.

672 Mile Corner

10 inch yellow pine marked MIR $67\frac{1}{2}$ M BT which bore N 73 $3/4^{\circ}$ E, 58 links distant.

 67^1_2 Mile Corner is now on the reservation fence and 50 links south of the center line of the new rim road.

Angle Point 504

24 inch yellow pine marked AP 504 BT which bore N 5°E, 62 links distant.

Angle Point 504 is now on the reservation fence and 44 links south of the center line of the new rim road.

In addition we found the following while working through this area.

Angle Point 463

A 12 inch yellow pine marked AP 463 FAIR BT bearing S 53E, 35 links distant from the corner was found. This tree was marked in 1970 during the course of the dependent resurvey work, but does not appear in the approved Field Notes for this survey. (See page 24, FIELD NOTES of the DEPENDENT RESURVEY of certain segments of the north and west boundaries of the FORT APACHE INDIAN RESERVATION in executed by Marlin G. Livermore II under special instructions dated March 25, 1970 included under Group Number 522 survey completed June 15, 1970).

Angle Point 462

During the course of the Field Work in 1970 we copied on our Boundary Corner Cards data from the Cadastral Surveyor's Field Book on Accessory location in relation to the corner monuments. For Angle Point 462 we recorded the following:

RM SET $2\frac{1}{2}$ " IP 26" in GD. CAP MKD (Illustration) RM BEARS N 70E, 49.8 LKS. RM SET $2\frac{1}{2}$ " IP 26" in GD. CAP MKD (Illustration) RM BEARS S $21\frac{1}{2}$ E, 33.3 LKS.

In the approved FIELD NOTES orientation of these accessories is described respectively as follows.

BEARS N $66\frac{1}{2}$ E, 32 LKS. DIST. BEARS S $17\frac{1}{2}$ E, 30 LKS. DIST.

When running the survey to establish the boundary line prior to construction of the new reservation boundary fence in September 1975, we were unable to locate the copper-coated steel stake which monumented this corner based upon the approved FIELD NOTES. We did, however, locate the corner based upon the data we had on our Boundary Corner Cards. We do not know the reason for the difference in the bearings and distances between what we copied in 1970 and what was approved in 1972. However, in relation to these two RM's the 1970 data we copied was the correct data.

Sincerely,

Jem Chy Superintendent