

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey of a Portion of the South Boundary

(The Gila and Salt River Base Line)

Township 1 North, Range 14 East

and

Dependent Resurvey of a Portion of the West Boundary

Township 1 North, Range 15 East, with

Establishment of Corners for a Portion of the

East Boundary of Township 1 North, Range 14 East

and the Survey of

A Portion of the Subdivisional Lines

Township 1 North, Range 14 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Harry K. Smith Cadastral Surveyor

Under special instructions dated September 25, 1972, which provided for the surveys included under Group Number 551, approved September 25, 1972, and assignment instructions dated September 26, 1972.

Survey commenced October 12, 1972

Survey completed December 5, 1972

BOOK 4996

INDEX DIAGRAM

Township 1 North, Range 14 East,

6	5	4	3	2	1	
7	8	9	10	11	12	
			36	30	21	12
18	17	16	35 (1/4) 15 34 28	14	19 13	9
			33	28	18	
19	20	21	22	26 23	17 24	8
			32	26	16	
30	29	28	27	25 26	16 25	6
			31	24	15	
31	32	33	34	21 35	12 36	3

Township 1 North, Range 14 East
Gila and Salt River Meridian, Arizona

CHAINS

The following notes are those of the dependent resurvey of a portion of the south boundary (the Gila and Salt River Base Line), Township 1 North, Range 14 East, the dependent resurvey of a portion of the west boundary of Township 1 North, Range 15 East, with the establishment of new corners at 40 and 80 chains intervals, for the south 4 miles of the east boundary of Township 1 North, Range 14 East, and the survey of a portion of the subdivisional lines of Township 1 North, Range 14 East, G&SRM., Arizona.

The Gila and Salt River Base Line through Range 14 East, and the south 3 miles of the east boundary of Township 1 North, Range 14 East, were surveyed in 1899 by Albert T. Colton. The Gila and Salt River Base Line was resurveyed in 1906 by Philip Contzen. The south 3 miles of the east boundary were retraced and the north 3 miles were surveyed by William B. Kimmel in 1923. The found corner on the south 3 miles was altered and new corners on the North 3 miles were set to function for T. 1 N., R. 15 E., only. The south 3 miles of the centerline of T. 1 N., R. 14 E., the W 1/2 mile bet. secs. 22 and 27 and the W 1/2 mile bet. secs. 15 and 22, were surveyed by William B. Kimmel in 1923. A portion of the Gila and Salt River Base Line through Range 14 East was resurveyed in 1967 by Kenneth D. Herman. The N-S centerline of sec. 22 and Tract 37 were surveyed in 1969 by Louis D. Gilbert. Tracts 38, 39, 40 and 41 were surveyed in 1971 by Ray Harpin. Numerous mineral surveys are of record throughout the Township.

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 25, 1972.

The directions of all lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.

Most of the measurements were made with electronic equipment -- the Cubitape Model No. D.M.-60--checked on a known base line for accuracy prior to commencement of the survey.

Before restoring the cors. along the W. bdy. of T. 1 N., R. 15 E., retracements of previous surveys were performed and a diligent search was made for any evidence of the original monuments and other calls of the official record.

Within the portion of the Tp. surveyed, numerous mining claims are of record. Many of these claims are located in active mining areas and a diligent search failed to locate many of the claim corners. Ties to mineral survey corners, which we were unable to locate, were calculated from the approved mineral survey records.

The geographic position of the southeast corner of T. 1 N., R. 14 E., as scaled from U.S. Geological Survey Quadrangle "Inspiration Ariz.", dated 1945, scale 1:24000 is: Latitude, 33°22'44" N., Longitude, 110°52'33" W.

The mean magnetic declination is 14° East.

Dependent Resurvey, Portion of the S. Boundary
 (The Gila and Salt River Base Line)
 T. 1 N., R. 14 E., G&SRM., Arizona

CHAINS	
	<p>Dependent Resurvey, Portion of the S. Boundary (The Gila and Salt River Base Line) T. 1 N., R. 14 E., G&SRM., Arizona</p> <hr/> <p>Reestablishment of the Resurvey Executed by Philip Contzen, Deputy Surveyor, in 1906</p> <hr/> <p>Beginning at the standard 1/4 sec. cor. of sec. 36, T. 1 N., R. 14 E., remonumented in 1967 by Kenneth D. Herman, Cadastral Surveyor, with an iron post, 2 1/2 ins. diam., firmly set in a collar of stone, 3 ft. base, 10 ins. high to top, brass cap mkd.</p> <p style="text-align: center;">S C T1N R14E 1/4 S36</p> <hr style="width: 20%; margin: auto;"/> <p style="text-align: center;">1967</p> <p>from which</p> <p>Cor. No. 1, M.S. 2403, Long Shot lode, bears N. 46° 15' E., 13.95 chs. dist., monumented by an open pipe, 3 ins. diam., projecting 12 ins. above ground, from which a rock in place 2x4x1 ft. above ground, bears S. 68°43' E., 47.4 lks. dist., plainly mkd. BRX 1-2403 LS.</p> <p>The NW. cor. of a metal shed, bears N. 43°09' W., 15.27 chs. dist.</p> <p>The most easterly cor. of a metal shed, bears N. 53°11' W., 16.40 chs. dist.</p> <p>Bubbling Well, a pipe, 18 ins. diam., bears N. 53° 25' W., 16.66 chs. dist.</p> <p>The cor. is on a W. slope, 25 lks. N. of a fenceline bearing E. and W.</p> <p>East along the S. bdy. of sec. 36.</p> <p>Over rolling mountainous terrain, through scattered timber and heavy undergrowth, paralleling an E-W fenceline.</p>
0.90	Track road, bears S. 35° E. and N. 35° W.; also spur, slopes N. 35° W.
4.20	Draw, drains NE.
7.50	Wash, 20 lks. wide, 3 ft. deep, drains N. 30° W.
10.20	Draw, drains S. 55° W.
15.65	The closing cor. of secs. 1 and 6, Tps. 1 S., Rs. 14 and 14 1/2 E., monumented by a granite stone, 6x6x8 ins. projecting above the ground, mkd. with 6 grooves on the E., 6 grooves and CC on S. and 6 grooves on the W. faces, with a mound of stone, 3 1/2 ft. base, 2 ft. high, S. of the cor. The cor. is 16 lks. N. of a fenceline bearing E. and W.; not remonumented.

Dep. Resurvey, Portion of the S. Boundary, T. 1 N., R. 14 E.

CHAINS																	
16.70	Draw, drains S. 55° W.																
20.40	Fence line, bears N. 25° W. and S. 25° E., 11 lks. dist., to a cor. of fences extending E., W. and N. 25° W.; also a ridge, bears S. 25° E. and N. 25° W.																
23.90	Fence line, bears N. 56 1/2° E. and S. 56 1/2° W. 17 lks. dist. to a cor. of fences extending N. 56 1/2° E., E. and W.																
25.00	Draw, drains NE.																
36.10	Smelter Canyon, drains N. 30° E., curving Northwesterly.																
39.95	The standard Tp. cor. of Tps. 1 N., Rs. 14 and 15 E., monumented with a local iron post, 3 ins. diam., firmly set in concrete, projecting 6 ins. above the ground; this position is harmoniously related to existing original corners and is accepted as the best remaining evidence of the original cor. position, a brass cap attached to the top of the pipe is mkd.																
	<table border="0"> <tr><td colspan="2">S C</td></tr> <tr><td colspan="2">T1N</td></tr> <tr><td>S.E. Cor.</td><td>S.W. Cor.</td></tr> <tr><td>Sec. 36</td><td>Sec. 31</td></tr> <tr><td>R14E</td><td>R15E</td></tr> <tr><td colspan="2">-----</td></tr> <tr><td>T1S</td><td>R14 1/2 E</td></tr> <tr><td colspan="2">S 6</td></tr> </table>	S C		T1N		S.E. Cor.	S.W. Cor.	Sec. 36	Sec. 31	R14E	R15E	-----		T1S	R14 1/2 E	S 6	
S C																	
T1N																	
S.E. Cor.	S.W. Cor.																
Sec. 36	Sec. 31																
R14E	R15E																

T1S	R14 1/2 E																
S 6																	
	This cor. was not remonumented.																
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor. for added support.																
	The cor. is on a steep W. slope, 13 lks. N. of a fence-line bearing E. and W.																
	<p>Land, rolling and mountainous. Soil, shallow rocky clay loam. Timber, scattered cedar. Undergrowth, oak brush, mesquite, manzanita, cat claw and cacti.</p>																
	<p>Dependent Resurvey of a Portion of the West Boundary, Township 1 North, Range 15 East, with Establishment of New Corners for Township 1 North, Range 14 East, G&SRM., Arizona</p>																
	<p>Reestablishment of the Retracement and Partial Survey Executed by William B. Kimmel, U.S. Cadastral Engineer, in 1923</p>																
	From the standard Tp. cor. of Tps. 1 N., Rs. 14 and 15 E., heretofore described.																

Dep. Resurvey, Portion of the W. Boundary, T. 1 N., R. 15 E.

CHAINS						
	N. 0°01' E., along the W. bdy. of sec. 31, T. 1 N., R. 15 E.					
	Over heavily rolling terrain, through scattered timber and moderate undergrowth.					
3.90	Draw, drains S. 80° W.; also fenceline, bears S. 18° E. and N. 18° W.					
6.00	Spur, slopes N. 80° W.					
8.00	Draw, drains N. 85° W.					
12.00	Spur, slopes N. 85° W.					
15.90	Draw, drains West.					
19.90	Spur, slopes West					
21.40	Draw, drains westerly.					
25.10	Spur, slopes S. 75° W.					
27.60	Draw, drains SW.					
32.20	Track road, bears S. 65° E. and N. 65° W., 30 lks. dist., to an intersection of roads extending East, curving northerly; spur, slopes N. 65° W.					
32.30	Track road, bears E. curving northerly and W. to intersection.					
38.87	The 1/4 sec. cor. of secs. 31 and 36, T. 1 N., Rs. 14 and 15 E., monumented by a granite stone, 16x13x4 ins., firmly set projecting 6 ins. above the ground, mkd. 1/4 on the W. face, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.					
	This cor. now functions as the 1/4 sec. cor., sec. 31, T. 1 N., R. 15 E. only.					
	At the cor. point					
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, brass cap mkd.					
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-left: 1px solid black; padding-left: 5px;">T1N</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">1/4</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">S31</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">R15E</td></tr> <tr><td style="border-left: 1px solid black; padding-left: 5px;">1972</td></tr> </table>	T1N	1/4	S31	R15E	1972
T1N						
1/4						
S31						
R15E						
1972						
	Rebuild the mound of stone W. of the cor.					
	Deposit the original cor. stone alongside the iron post.					
	The cor. is located on a W. slope.					
	N. 0°06' W., beginning new measurement.					
	Over heavily rolling terrain through scattered timber and moderate undergrowth.					

Dep. Resurvey, Portion of the W. Boundary, T. 1 N., R. 15 E.

CHAINS	
1.13	<p>Point for the 1/4 sec. cor. of sec. 36, T. 1 N., R. 14 E.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N 1/4 S36 R14E 1972</p> <p>from which</p> <p>U.S.M.M. No. 6, identical with Cor. No. 1, M.S. 3254, Blue Bell No. 2 lode, and the NE. Cor., M.S. 299, New York lode, and on line 2-3, M.S. 3243, Onward lode, bears S. 88°39' W., 27.88 chs. dist., monumented by an old cedar post set in a mound of stone, dimly mkd. USMM No. 6 on NW. face and illegible mks. on SW. face.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>The cor. is on a W. slope.</p>
3.30	Power line, bears N. 61° E. and S. 61° W.
7.20	Fenceline, bears N. 50° E. and S. 50° W.
7.40	Spur, slopes N. 40° W.
8.40	Track road, bears SE. and NW.
8.50	Telephone line, bears N. 61° E. and S. 61° W.
13.49	Intersect line 4-1, M.S. 3232, Sulphide No. 1 lode, at a point from which Cor. No. 1 bears S. 33°16' W., 0.03 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
13.70	Power line, bears N. 66°30' E. and S. 66°30' W.
14.80	Power line, bears N. 61° E. and S. 61° W.
21.00	Spur, slopes N. 40° W.
28.00	Power line, bears S. 55° E. and N. 55° W.
28.50	Paved road, bears S. 55° E. and N. 55° W.; thence through residential area near the W. edge of the City of Miami.
38.30	Centerline of Southern Pacific Railroad, bears NE. curving N. and SW. curving W.
39.10	Improved dirt road, bears NE. and SW.
39.71	<p>The cor. of secs. 25, 30, 31 and 36, T. 1 N., Rs. 14 and 15 E., inside a large metal building, monumented by a concrete receptacle, 8 ins. diam., 6 ins. deep, with a metal plate over the top. This position has long been recognized as the cor. by local surveyors and is accepted as the best existing evidence of the original cor. position. This cor. now functions as the cor. of secs. 30 and 31, T. 1 N., R. 15 E., only. Not remonumented.</p> <p>from which</p>

Dep. Resurvey, Portion of the W. bdy. T. 1 N., R. 15 E.

CHAINS														
	<p>The SW. cor. of the large metal building, bears S. 60° W., 21 lks. dist.</p> <p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar. Undergrowth, oak bush, mesquite, manzanita, cat claw and cacti.</p>													
	<p>N. 0°19' E., along the W. bdy. of sec. 30, T. 1 N., R. 15 E.</p>													
0.96	<p>Intersect line 1-2, M.S. 3232, Sho Me No. 2 lode, at a point from which Cor. No. 1, identical with Cor. No. 1, M.S. 3170, Dora Fraction lode, bears N. 85°36' W., 8.54 chs. dist., as calculated from approved mineral survey record. (No cor. found).</p>													
1.42	<p>True point for the cor. of secs. 25 and 36, T. 1 N., R. 14 E., is on a concrete slab, impossible to perpetuate a permanent monument.</p>													
	<p>from which</p>													
	<p>Cor. No. 1, M.S. 2540, Sho Me lode, bears S. 71°47' W., 4.50 chs. dist., as calculated from the approved mineral survey record. This claim lies within the city limits of Miami, Arizona. (No cor. found).</p>													
1.62	<p>Point selected for the witness cor. of secs. 25 and 36, T. 1 N., R. 14 E.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>W C</p> <table border="0"> <tr> <td>T1N</td> <td> </td> <td>T1N</td> </tr> <tr> <td>S25</td> <td> </td> <td>S30</td> </tr> <tr> <td>S36</td> <td> </td> <td></td> </tr> <tr> <td>R14E</td> <td>↓</td> <td>R15E</td> </tr> </table> <p>1972</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor.</p>		T1N		T1N	S25		S30	S36			R14E	↓	R15E
T1N		T1N												
S25		S30												
S36														
R14E	↓	R15E												
9.10	<p>Centerline of U. S. Highway No. 60, bears N. 55° E. and S 55° W.</p>													
11.52	<p>Intersect line 4-1, M.S. 2540, Sho Me lode, at a point from which Cor. No. 1 bears S. 20°39' W., 12.29 chs. dist., as calculated from the approved mineral survey record. (No cor. found).</p>													
12.70	<p>Bloody Tanks Wash, drains N. 60° E.</p>													
15.40	<p>Centerline of old U.S. Highway Nos. 60 and 70, bears NE. and SW.</p>													
21.50	<p>Spur, slopes N. 65° E.</p>													
26.70	<p>Davis Canyon, drains SE.</p>													
27.60	<p>Black top road, bears S. 80° E. and N. 80° W.</p>													

Dep. Resurvey, Portion of the W. bdy., T. 1 N., R. 15 E.

CHAINS

32.30 Black top road, bears SE. and NW.; leave residential area near the west edge of the City of Miami.

32.80 Fenceline, bears NE. and SW.; asc. along broken W. slope.

39.63 The 1/4 sec. cor. of sec. 30, T. 1 N., R. 15 E., monumented with an iron post, 1 in. diam., firmly set in concrete and projecting 12 ins. above the ground, brass cap attached to the top of post mkd.

L.S. 5703 1/4 T1N
 | S30
 | R15E
 1972

This position is harmoniously related to existing original cors. and is accepted as the best existing evidence of the original cor. position, not remonumented.

N. 0°27' E., beginning new measurement.

1.79 Point for the 1/4 sec. cor. of sec. 25, T. 1 N., R. 14 E.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone to top, brass cap mkd.

T1N
1/4 S25
R14E
1972

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

The cor. is on a steep W. slope, 150 lks. E. of a mining road.

8.80 Mining road, bears S. 30° E. and N. 30° W.

14.10 Spur, slopes N. 15° W.

16.20 S. edge of mining pit, bears E. and W.

39.98 Point for the cor. of secs. 19 and 30, T. 1 N., R. 15 E., at proportionate dist.; there is no remaining evidence of the original cor. The cor. point falls in a small leaching pond, impractical to monument.

Land, the S. 15.00 chs., nearly level, remainder, mountainous.

Soil, the S. 15.00 chs., sandy loam, remainder, shallow and rocky.

No timber.

Undergrowth, the S. 15.00 chs., none; the next 40.80 chs. N., medium oak brush, cat claw and cacti; none in the remainder.

Dep. Resurvey, Portion of the W. Bdy., T. 1 N., R. 15 E.

CHAINS																					
	N. 0°27' E., along the W. bdy. of sec. 19, T. 1 N., R. 15 E.																				
	Ascending N. side of open mining pit.																				
1.81	Point for the cor. of secs. 24 and 25, T. 1 N., R. 14 E. Set a fiber glass pipe, 30 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone, 3 ft. base to top, brass cap mkd.																				
	<table border="0"> <tr><td>T1N</td><td> </td><td>T1N</td></tr> <tr><td>S24</td><td> </td><td>S19</td></tr> <tr><td>S25</td><td> </td><td>R15E</td></tr> <tr><td></td><td> </td><td></td></tr> <tr><td>R14E</td><td></td><td></td></tr> <tr><td>1972</td><td></td><td></td></tr> </table>	T1N		T1N	S24		S19	S25		R15E				R14E			1972				
T1N		T1N																			
S24		S19																			
S25		R15E																			
R14E																					
1972																					
26.60	N. edge of mining pit, bears E. and W.; thence through scattered timber and moderate undergrowth.																				
32.70	Pipe line, 14 ins. diam., bears S. 70° E., curving E. and N. 70° W., curving N.																				
33.60	Pipe line, 6 ins. diam., bears N. 82° E. and N. 70° W.																				
33.70	Bladed road, bears N. 82° E. and N. 70° W.																				
35.20	Power line, bears N. 85° E. and S. 85° W.																				
36.70	Paved road, bears S. 78° W. and N. 78° E., curving North.																				
38.20	Centerline of railroad, bears S. 70° E. and N. 70° W.																				
38.40	Centerline of railroad, bears N. 76° E. and S. 76° W.																				
39.00	Centerline of railroad, bears N. 81° W. and E., curving N.																				
39.98	Point for the 1/4 sec. cor. of sec. 19, T. 1 N., R. 15 E., at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.																				
	<table border="0"> <tr><td></td><td> </td><td>T1N</td></tr> <tr><td></td><td> </td><td>1/4 S19</td></tr> <tr><td></td><td> </td><td>R15E</td></tr> <tr><td></td><td></td><td></td></tr> <tr><td></td><td></td><td>1972</td></tr> </table>			T1N			1/4 S19			R15E						1972					
		T1N																			
		1/4 S19																			
		R15E																			
		1972																			
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of the cor.																				
41.70	Center of a gravel road, bears S. 75° E. and N. 75° W.																				
41.81	Point for the 1/4 sec. cor. of sec. 24, T. 1 N., R. 14 E., falls in the gravel road. Set a fiberglass post, 30 ins. long, 2 1/2 ins. diam., 6 ins. below the surface of the road, brass cap mkd.																				
	<table border="0"> <tr><td></td><td></td><td>T1N</td><td> </td></tr> <tr><td>1/4</td><td></td><td>S24</td><td> </td></tr> <tr><td></td><td></td><td>R14E</td><td> </td></tr> <tr><td></td><td></td><td></td><td> </td></tr> <tr><td></td><td></td><td></td><td>1972</td></tr> </table>			T1N		1/4		S24				R14E									1972
		T1N																			
1/4		S24																			
		R14E																			
			1972																		

Dep. Resurvey, Portion of the W. Bdy., T. 1 N., R. 15 E.

CHAINS

from which

An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 45° E., 69.7 lks. dist., with brass cap mkd. RM 46 FT 1972, and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 18 ins. in the ground and in a collar of stone, 2 ft. base to top, for a reference monument, bears N. 45° W., 91 lks. dist., with brass cap mkd. RM T1N R14E ½ S24 60 FT 1972, and an arrow pointing to the cor.

- 42.40 Conveyor, bears E. and W.
- 44.60 Power line, bears S. 85° E. and N. 85° W.
- 44.90 Gravel road, bears irregularly E. and W.
- 55.30 Pipe line, 14 ins. diam., bears N. 51° E. and S. 35° W.
- 55.60 Power line, bears N. 58° E. and S. 58° W.
- 55.70 Power line, bears N. 58° E. and S. 58° W.
- 59.50 Enter ore dump, bears N. 75° E. and S. 75° W.
- 60.50 Power line, bears N. 65° E. and S. 65° W.
- 70.45 Intersect line 3-4, M.S. 3015, Columbus lode, at a point from which Cor. No. 3, on line 3-4, M.S. 3015, Copperopolis lode, bears S. 24°03'13" W., 1.62 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
- 73.10 Intersect line 2-3, M.S. 3015, Old Ironsides lode, at a point from which Cor. No. 2, bears S. 83°33' E., 3.34 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
- 75.10 S. shore of a storage lake, bears N. 60° E. and S. 60° W.; N. edge of ore dump.
- 79.96 Point for the cor. of secs. 18 and 19, T. 1 N., R. 15 E., at proportionate dist.; there is no remaining evidence of the original cor. The cor. point falls in a storage lake; impossible to monument.

Land, mountainous.
Soil, shallow and rocky.
Timber, N. 53 chs., scattered cedar.
Undergrowth, N. 53 chs. moderate oak brush, cat claw, manzanita, mesquite and cacti.

N. 0°27' E., along the W. bdy. of sec. 18, T. 1 N., R. 15 E.

Over a storage lake and through mining area.

- 1.85 True point for the cor. of secs. 13 and 24, T. 1 N., R. 14 E., is located within a storage lake; impossible to monument.

from which

Dep. Resurvey, Portion of the W. Bdy., T. 1 N., R. 15 E.

CHAINS


Cor. No. 3, M.S. 2906, Prospect lode, bears S. 70°37' W., 26.15 chs. dist., monumented by a 4 ins. iron pipe set in cement, steel cap mkd. PROS-3-2906.

Cor. No. 4, M.S. 3015, Old Ironsides lode, bears N. 82°14' W., 18.46 chs. dist., monumented by a 4 ins. iron pipe set in cement, steel cap mkd. OI-4-3015.

5.16 Waterline of storage lake, bears NE. and SW.

5.55 Point selected for the witness cor. of secs. 13 and 24, T. 1 N., R. 14 E.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.



Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the cor.

The witness cor. is located on a small spur, sloping N. 65° E.


5.90 Waterline of the same storage lake and power line, both bear N. 65° E. and S. 65° W.

17.00 N. shore of the same storage lake, bears E. and W. Enter mountainous land, bears E. and W.

20.00 Spur, slopes S. 55° W.

29.41 Intersect line 4-1, M.S. 4730, Webster 44 mill site, at a point from which Cor. No. 4, identical with Cor. No. 4, Webster 34 mill site and Cor. No. 4, Webster 36 mill site, of the same survey, bears S. 40°00'54" W., 3.82 chs. dist., as calculated from the approved mineral survey record. (No cor. found).

39.98 The ¼ sec. cor. of sec. 18, T. 1 N., R. 15 E., monumented with an iron post, 1 in. diam., firmly set in concrete, projecting 4 ins. above the ground, with a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor., brass cap mkd.



from which the original bearing trees

A cedar, 10 ins. diam., bears N. 60°55' E., 180 lks. dist., mkd. ¼ S 18 BT. (Record N. 60½° E).

A cedar, 10 ins. diam., bears S. 61°10' E., 125 lks. dist., mkd. with an overgrown blaze. (Record S. 61½° E., 129 lks. dist.)

Dep. Resurvey, Portion of the W. Bdy., T. 1 N., R. 15 E.

CHAINS

- N. 0°25' E., beginning new measurement.
- 1.87 Point for the ¼ sec. cor. of sec. 13, T. 1 N., R. 14 E.
Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.
- | | |
|---|------|
| ¼ | T1N |
| | S13 |
| | R14E |
| | 1972 |
- from which
- A cedar, 7 ins. diam., bears S. 82°35' W., 102 lks. dist., mkd. ¼ S13 BT.
 - Cor. No. 4, M.S. 4730, Webster 44 mill site, identical with Cor. No. 4, Webster 34 mill site and Cor. No. 4, Webster 36 mill site, of the same survey, bears S. 9°26' W., 15.58 chs. dist., as calculated from the approved mineral survey record.
 - U.S.M.M. No. 9, bears N. 39°46'42" W., 27.34 chs. dist., monumented by a wooden post, 8 ins. diam., firmly set in a mound of stone, 4 ft. base, 1½ ft. high, the post projecting 7 ft. above the mound, there are no visible marks on the partially deteriorated post, from which
 - Cor. No. 3, M.S. 681, Yellow Metal lode, bears S. 39° E., 1.73 chs. dist., as shown on the approved mineral survey record. (No cor. found).
- 25.90 Ridge, bears N. 70° E. and SW.
- 30.26 Intersect line 1-2, M.S. 3574, Gold Dollar lode, at a point from which the southwest end center cor., bears N. 57°55' W., 2.38 chs. dist., monumented with a 4x4 in. squared post, firmly set in a mound of stone, 4 ft. base, 2 ft. high, post projecting 2 ft. above the mound, mkd. SW EC GD 3574 on NE. face.
- 31.20 Spur, slopes N. 80° W.
- 36.70 Spur, slopes N. 15° W.
- 39.90 The cor. of secs. 7 and 18, T. 1 N., R. 15 E., monumented by an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, with a mound of stone, 3 ft. base 2 ft. high, E. of the cor., brass cap mkd.
- | | |
|-----|------|
| | T1N |
| S13 | S 7 |
| | S18 |
| | R15E |
| | 1923 |
- Remark the brass cap to read:
- | | |
|------|------|
| T1N | T1N |
| S13 | S 7 |
| | S18 |
| R14E | R15E |
| | 1972 |
| | 1923 |
- The cor. is in a fenceline bearing E. and W.

Dep. Resurvey, Portion of the W. Bdy., T. 1 N., R. 15 E.

CHAINS

Land, mountainous.
Soil, shallow and rocky.
Timber, N. 63.00 chs., scattered cedar.
Undergrowth, N. 63.00 chs., medium oak brush, mesquite,
manzanita, cat claw and cacti.

N. 0°26' E., along the W. bdy. of sec. 7, T. 1 N., R. 15 E.

Over mountainous land, through medium undergrowth.

1.97 Point for the cor. of secs. 12 and 13, T. 1 N., R. 14 E.

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T1N		T1N
S12		S 7
S13		
R14E		R15E
		1972

from which

The SW. end center, M.S. 3574, Gold Dollar lode, bears S. 11°29' W., 10.55 chs. dist., heretofore described.

The ¼ sec. cor. of sec. 6, T. 1 N., R. 15 E., bears N. 0°26' E., 117.91 chs. dist., monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 3 ft. base, 3 ft. high, E. of the cor., brass cap mkd.

		¼ S 6
		1923

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was found. The positions for the intervening corners fell in an active mining area.

Survey of a Portion of the Subdivisional Lines,
T. 1 N., R. 14 E., G&SRM., Arizona

In the resurvey of a portion of the west boundary of Township 1 North, Range 15 East (east boundary of Township 1 North, Range 14 East), the township line was found to be defective in alignment. Therefore, the first meridional line was projected north from the standard corner of sections 35 and 36 on the south boundary of the township. The fractional measurements of the latitudinal section lines in the first range of sections were placed in the east half mile.

From the standard cor. of secs. 35 and 36, on the S. bdy. of the Tp., monumented in 1967 by Kenneth D. Herman, Cadastral Surveyor, with an iron post, 2½ ins. diam., set on a large smooth rock slab, approximately 100 ft. long and 60 ft. wide, and in a mound of stone, 4 ft. base, 30 ins. high, with brass cap mkd.

S C	
T1N	R14E
S35	S36
	1967

from which

Survey of a Portion of the Subdivisional Lines
T. 1 N., R. 14 E., G&SRM., Arizona

CHAINS	
	<p>Cor. No. 1., M.S. 4684B, Joan Mill Site 43, bears N. 25°59' W., 11.85 chs. dist., monumented by a brass tablet, 2½ ins. top, cemented in a rock ledge, mkd. JMS-43-1-4684B.</p> <p>The NW. cor. of a house, bears N. 15°20' E., 23.42 chs. dist.</p> <p>The NW. cor. of a house, bears N. 16°58' E., 24.81 chs. dist.</p> <p>The NW. cor. of a house, bears N. 22°10' E., 29.65 chs. dist.</p> <p>A concrete water tank, 40 ft. long, 25 ft. wide, with 6 ft. of water, bears N. 23°40' E., 16.70 chs. dist.</p> <p>A steel fence post, cemented in rock, bears S. 52° E., 28 lks. dist.</p> <p>A steel fence post, cemented in rock, bears S. 37° W., 22 lks. dist.</p> <p>North on a sectional guide meridian, bet. secs. 35 and 36.</p> <p>Over rolling land, through scattered timber and moderate undergrowth.</p>
12.10	Spur, slopes S. 85° E.
19.20	Intersect line 4-1, M.S. 4684B, Joan Mill Site 34, at a point from which Cor. No. 1, identical with Cor. No. 4, Joan Mill Site 43, of the same survey, bears S. 31°47' 33" W., 0.93 chs. dist., monumented with an iron post, 1 in. diam., firmly set projecting 3 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, E. of the cor., brass cap mkd. JMS-34-1-JMS-43-4-4684B.
20.90	Centerline of U.S. Highway No. 60, bears N. 60° E. and S. 60° W.
24.20	Power line, bears S. 85° E. and N. 85° W.
24.40	S. fork of Bloody Tanks Wash, stream of water 12 lks. wide, 6 ins. deep, course N. 60° E.
26.20	N. fork of Bloody Tanks Wash, stream of water 20 lks. wide, 6 ins. deep, course N. 60° E.
29.20	Center of a graded road to Bluebird Mine, bears N. 65° E. and S. 65° W.
34.40	Power line, bears E. and W.
40.00	<p>Point for the ¼ sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R14E ¼ S35 S36 1972</p> <p>from which</p> <p>An oak, 7 ins. diam., bears N. 20° E., 62 lks. dist. mkd. ¼ S36 BT.</p> <p>An oak, 7 ins. diam., bears S. 51°03' W., 56 lks. dist., mkd. ¼ S35 BT.</p>

Survey of a Portion of the Subdivisional Lines
T. 1 N., R. 14 E., G&SRM.; Arizona

CHAINS		
	<p>The SE. cor. of a house; bears S. 6°43' W., 6.40 chs. dist.</p>	
	<p>The NE. cor. of a trailer house, bears S. 10°45' W., 8.45 chs. dist.</p>	
	<p>The NE. cor. of the Blue Bird office building, bears S. 37°34' W., 14.23 chs. dist.</p>	
	<p>Cor. No. 1, M.S. 4648B, Joan Mill Site 10, identical with Cor. No. 2, Joan Mill Site 11, Cor. No. 3, Joan Mill Site 23 and Cor. No. 4, Joan Mill Site 22 of the same survey, bears S. 47°12' W., 0.34 chs. dist., monumented with an iron post, 1 in. diam., firmly set in concrete, projecting 8 ins. above the ground, with a mound of stone, 3 ft. base, 2 ft. high, SW. of the cor., brass cap mkd. JMS-11-2-JMS-23-3-JMS-22-4-JMS-10-1-4684B.</p>	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>	
<p>50.36</p>	<p>Intersect line 3-4, M.S. 4684B, Joan Mill Site 10, at a point from which the true point for Cor. No. 3, identical with Cor. No. 4, Joan Mill Site 9, of the same survey bears N. 57°40'40" W., 0.15 chs. dist. A witness cor., bears N. 57°40'40" W., 3.43 chs. dist., monumented with an iron post, 4 ins. diam., firmly set, projecting 2½ ft. above the ground, brass cap attached to top, mkd. JMS-9-4-JMS-10-3-4684B WC.</p>	
<p>79.50</p>	<p>Point selected for the witness cor. of secs. 25, 26, 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.</p>	
	<p style="text-align: center;">T1N R14E</p> <p style="text-align: center;"> $\begin{array}{c} \uparrow \\ \hline \begin{array}{cc} S26 & S25 \\ \hline S35 & S36 \end{array} \end{array}$ </p> <p style="text-align: center;">W C 1972</p>	
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the cor.</p>	
<p>80.00</p>	<p>True point for the cor. of secs. 25, 26, 35 and 36, is located in an ore dump; impractical to monument.</p>	
	<p>from which</p> <p>Cor. No. 2, M.S. 3033, Wedge lode, bears S. 70°52' E., 3.37 chs. dist., monumented by an iron pipe, 3 ins. diam., set in a concrete block, projecting 14 ins. above the surface, steel cap mkd. 3033 in NE. Quadrant.</p> <p>Land, mountainous and rolling. Soil, shallow and rocky. Timber, oak and cedar. Undergrowth, catclaw, manzanita, oak bush and cacti.</p>	

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
	<p>From the true point for the cor. of secs. 25 and 36 on the E. bdy. of the Tp.</p> <p>N. 89°58' W., bet. secs. 25 and 36.</p> <p>Over nearly level land, through residential area near the west edge of the city of Miami.</p>
3.73	Intersect line 4-1, M.S. 2540, Sho Me lode, at a point from which Cor. No. 1 bears S. 20°39' W., 1.51 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
6.70	Bloody Tanks Wash, 120 lks. wide, with 7 ft. banks, drains N. 15° E.
7.30	Centerline of U. S. Highway No.60, bears N. 35° E. and S. 35° W.
14.00	Enter rolling mountainous land, with moderate undergrowth and scattered timber, bears SE. and NW.
22.60	Centerline of Southern Pacific Railroad, bears S. 55° E. and N. 55° W.; leave residential area of the city of Miami, continue over mountainous land.
33.30	Power line, bears N. and S.
39.93	Point for the 1/4 sec. cor. of secs. 25 and 36.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 2 1/2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T1N R14E 1/4 $\frac{S25}{S36}$ 1972</p> <p>from which</p> <p>Cor. No. 1, M.S. 3069, Red Cloud lode, identical with Cor. No. 2 Iron Lode lode, and on line 3-4 Snail lode of the same survey, bears S. 69°55' W., 11.86 chs. dist., monumented by a pine post set in a mound of stone, mkd. 1-3069 RC on W. face and 2-3069 IL on E. face.</p>
48.90	Wash, 30 lks. wide, with 8 ft. banks, drains N. 80° E. from SW.
60.51	Intersect line 3-4, M.S. 3069, Red Cloud lode, at a point from which Cor. No. 3, bears S. 57°13' W., 5.19 chs. dist., as calculated from the approved mineral survey record. (No cor. found)
63.93	Intersect line 1-2, M.S. 3043, Copper Glance Fraction lode, at a point from which Cor. No. 2, bears S. 41°21' W., 12.78 chs. dist., as calculated from the approved mineral survey record. (No cor. found)

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS		
67.90	Spur, slopes N.	
72.64	Intersect line 3-4, M.S. 3043, Copper Glance Fraction lode, at a point from which Cor. No. 3, bears S. 41°21' W., 5.25 chs. dist., as calculated from the approved mineral survey record. (No cor. found).	
72.95	Intersect line 1-2, M.S. 3033, Wedge lode, at a point from which Cor. No. 2, bears S. 73°57' W., 3.78 chs. dist., heretofore described.	
76.98	Intersect line 2-3, M.S. 3033, Wedge lode, at a point from which Cor. No. 2, bears S. 11°48' E., 1.13 chs. dist., heretofore described.	
79.93	<p>True point for the cor. of secs. 25, 26, 35 and 36.</p> <p>Land, E. 14.00 chs., nearly level, remainder, rolling and mountainous. Soil, shallow and rocky. Timber, scattered cedar and oak. Undergrowth, moderate cat claw, manzanita, oak bush and cacti.</p>	
	<p>North, on a sectional guide meridian, bet. secs. 25 and 26.</p>	
	<p>Through active mining area. (Large stock piles and open pit).</p>	
0.99	Intersect line 1-2, M.S. 3033, May lode, at a point from which Cor. No. 1, on line 2-3, M.S. 3033, Wedge lode, bears N. 77°01' E., 2.68 chs. dist., as calculated from the approved mineral survey record. (No cor. found).	
40.00	<p>Point for the 1/4 sec. cor. of secs. 25 and 26.</p> <p>The cor. pt. is in an active congested mining area, impractical to monument.</p>	
80.00	<p>Point for the cor. of secs. 23, 24, 25, and 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., in a mound of stone, 3 1/2 ft. base to top, brass cap mkd.</p>	
	<p>T1N R14E S23 S24 S26 S25 1972</p>	
	<p>Land, mining area. Soil, rocky stockpiles and open pits. No timber or undergrowth.</p>	
	<p>From the cor. of secs. 24 and 25, on the E. bdy. of the Tp., heretofore described.</p>	
	<p>N. 89°59' W., bet. secs. 24 and 25.</p>	
	<p>Through active mining area.</p>	

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
33.10	Bladed mining road, bears SE., curving S., and NW.
37.40	Power line, bears S. 8° E. and N. 8° W.
40.35	Point for the 1/4 sec. cor. of secs. 24 and 25.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, brass cap mkd.
	T1N R14E 1/4 <u>S24</u> S25 1972
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, S. of the cor. for support.
	The cor. is located on a steep S. slope near the E. edge of a mining pit.
80.35	The cor. of secs. 23, 24, 25 and 26.
	Land, mountainous. Soil, shallow and rocky. No timber or undergrowth.
	North, on a sectional guide meridian, bet. secs. 23 and 24.
	Through mining area.
8.10	NW. edge of mining pit.
9.40	Paved road, bears N. 72° E. and S. 72° W.
10.60	Webster Gulch, 70 lks. wide, 4 ft. banks, with 3 ins. of flowing water, course N. 75° E.
11.70	Paved road, bears N. 75° E. and S. 75° W.
17.00	Centerline of Southern Pacific Railroad, bears W. and E., 150 lks. dist., curving N.
17.40	Conveyor, bears N. 60° E. and S. 60° W.
20.30	Power line, bears N. 65° E. and S. 65° W.
21.90	Centerline of Southern Pacific Railroad, on a curve, bears N. 80° E. and S. 70° W.
37.10	Spur, slopes S. 80° E.
39.10	Fence line, bears SE. and NW.
39.20	Track road, bears SE. and NW.
40.00	Point for the 1/4 sec. cor. of secs. 23 and 24.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base to top, brass cap mkd.
	T1N R14E 1/4 S23 S24 1972

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
40.20	Spur, slopes SW.
57.70	Draw, drains SE. curving southerly.
66.70	Spur, slopes N. 50° E.
78.00	Wash, 20 lks. wide, with 4 ft. banks, drains N. 50° E.
80.00	<p>Point for the cor. of secs. 13, 14, 23 and 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 4 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T1N R14E $\frac{S14}{S23} \frac{S13}{S24}$ 1972</p>
	from which
	<p>A cedar, 8 ins. diam., bears N. 0°15' E., 3 lks. dist., mkd. T1N R14E S13 BT.</p>
	<p>A cedar, 4 ins. diam., bears S. 74°10' E., 90 lks. dist., mkd. T1N R14E S24 BT.</p>
	<p>The N. fork of a cedar, 7 ins. diam., bears S. 67° 10' W., 64 lks. dist., mkd. T1N R14E S23 BT.</p>
	<p>Land, the S. 8.00 chs., mining pit area; N. 72.00 chs. rolling and mountainous. Soil, shallow and rocky. No timber in the S. 8.00 chs.; scattered cedar in the N. 72.00 chs. No undergrowth in the S. 8.00 chs.; moderate cat claw, manzanita, oak bush and cacti in the N. 72.00 chs.</p>
	<p>From the true point for the cor. of secs. 13 and 24, on the E. bdy. of the Tp., heretofore described.</p>
	<p>N. 89°56' W., bet. secs. 13 and 24.</p>
	<p>Over storage lake.</p>
2.00	<p>West shore of storage lake, enter mountainous land with scattered timber and medium undergrowth, bears NE. and SW.</p>
9.70	<p>Power line, bears N. 65° E. and S. 65° W., curving southerly.</p>
25.80	<p>Power line, bears N. and S.</p>
38.00	<p>Ridge, bears NE. and SW.</p>
40.97	<p>Point for the 1/4 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T1N R14E $\frac{1}{4} \frac{S13}{S24}$ 1972</p>

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.
	The cor. is located on a steep N. slope.
49.60	Saddle, bears N. 25° E. and S. 25° W., curving westerly.
65.30	Spur, slopes N.
68.30	Track road, bears NE., curving E. and SW., curving W:
75.50	Spur, slopes N.
79.00	Wash, 20 lks. wide, with 8 ft. banks, drains NE.
80.97	The cor. of secs. 13, 14, 23 and 24.
	Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar. Undergrowth, oak bush, manzanita and cacti.
	North, on a sectional guide meridian, bet. secs. 13 and 14.
	Over rolling mountainous land, through scattered timber and moderate undergrowth.
22.50	Ridge, bears E. and W.
37.60	Spur, slopes W. into a small saddle.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	T1N R14E ¼ S14 S13 1972
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
41.70	Wash, 10 lks. wide, 2 ft. deep, drains NE. from S. 5° W.
43.40	Jeep trail, bears N. 30° E. and S. 30° W.; spur, slopes N. 30° E.
48.60	Wash, drains N. 20° E.
54.70	Spur, slopes N. 70° E.
57.00	Draw, drains N. 70° E.
60.00	Spur, slopes N. 70° E.
62.00	Draw, drains N. 25° E.
65.00	Spur, slopes N. 25° E.

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
67.50	Lost Gulch, 30 lks. wide, 4 ft. banks, with 6 ins. of water, course S. 70° E.
69.41	Intersect line 3-4, M.S. 3489, Comanche lode, at a point from which Cor. No. 4, bears N. 49°58' W., 0.34 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
70.00	S. edge of ore dump, bears S. 65° E., curving E. and N. 65° W., curving N. Enter active mining area.
76.20	Mining road, bears E. and W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14.
	Set an iron post, 28 ins. long, 2½ ins. diam., flush with the ground, brass cap mkd.
	<p>T1N R14E <u>S11 S12</u> <u>S14 S13</u> 1972</p>
	from which
	An oak, 10 ins. diam., bears N. 23°55' E., 211 lks. dist., mkd. T1N R14E S12 BT.
	An oak, 8 ins. diam., bears S. 46°50' E., 178 lks. dist., mkd. T1N R14E S13 BT.
	An oak, 6 ins. diam., bears N. 11°30' W., 211 lks. dist., mkd. T1N R14E S11 BT.
	U.S.L.M. No. 2499, bears S. 88°55'30" W., 47.70 chs. dist., monumented by a limestone rock in place, 3½ x4x8 ft. high, dimly mkd. X USLM 2499 on top, and with a mound of stone, 6 ft. base, 5 ft. high, N. alongside the cor.
	The calculated point for Cor. No. 4, M.S. 3489, Comanche lode, bears S. 1°26' W., 10.37 chs. dist.
	The cor. is near the N. edge of a mining area.
	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, oak and cedar. Undergrowth, oak bush, manzanita, cat claw and cacti.</p>
	From the cor. of secs. 12 and 13, on the E. bdy. of the Tp.
	N. 89°57' W., bet. secs. 12 and 13.
	Over rolling mountainous terrain, through moderate undergrowth.

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS		
5.00	Power line, bears N. 43° E. and S. 43° W.	
5.90	Enter mining area, ore heap bears N. 30° E. and S. 30° W:	
6.90	Power line, bears N. 30° E. and S. 30° W., curving west-erly.	
8.90	Mining road, bears N. 30° E., curving N. and S. 30° W., curving W.	
15.92	Intersect line 1-2, M.S. 4358, Oro No. 4 lode, at a point from which Cor. No. 1, bears S. 48°19' E., 7.78 chs. dist., as calculated from the approved mineral survey record. (No cor. found).	
41.51	Point for the ¼ sec. cor. of secs. 12 and 13. The cor. point is in an active congested mining area and is impractical to monument.	
	from which	
	The calculated point for Cor. No. 2, M.S. 2745 and 3668, Cedar Tree lode, bears S. 75°04' W., 8.95 chs. dist. (No cor. found).	
43.46	Intersect line 1-2, M.S. 2745 and 3668, Cedar Tree lode, at a point from which Cor. No. 2 bears S. 70°59' W., 7.08 chs. dist., as calculated from the approved mineral survey record. (No cor. found).	
50.93	Intersect line 2-3, M.S. 2745 and 3668, Cedar Tree lode, at a point from which Cor. No. 2, bears S. 18°35' E., 2.44 chs. dist., as calculated from the approved mineral survey record. (No cor. found).	
81.51	The cor. of secs. 11, 12, 13 and 14.	
	Land, rolling and mountainous. Soil, shallow and rocky. No timber. Undergrowth, oak bush, manzanita, cat claw and cacti in the E. 5.90 chs.	
	From the standard cor. of secs. 34 and 35, on the S. bdy. of the Tp., remonumented in 1967 by Kenneth D. Herman, Cadastral Surveyor, with an iron post, 2½ ins. diam., firmly set in a mound of stone, 3 ft. base, 14 ins. high to top, brass cap mkd.	
	<p style="text-align: center;">S C T1N R14E <u>S34 S35</u> 1967</p>	
	from which	
	Cor. No. 1, M.S. 4694, IL59, identical with Cor. No. 1, Inspiration Mill Site No. IL 76 of the same survey, bears S. 0°03' E., 0.073 chs. dist., monumented with an iron post,	

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS

1 in. diam., firmly set, projecting 8 ins. above the ground, brass cap mkd. IL59-1-IL76-1 4694.

Cor. No. 3, M.S. 4694, Inspiration Mill Site No. IL 77, bears S. 89°48' E., 19.96 chs. dist., monumented by an iron post, 1 in. diam., projecting 6 ins. above ground, brass cap mkd. IL77-3-4694.

Cor. No. 1, M.S. 4698, Bill Shaft No. 3, identical with Cor. No. 3, M.S. 4694, IL 59, bears N. 6°33' W., 4.60 chs. dist., monumented with an iron post, 1 in. diam., projecting 16 ins. above the ground, brass cap mkd. IL59-3-4694-BS3-1-4698.

A pine, 7 ins. diam., bears S. 54° W., 46 lks. dist., mkd. BT.

A pine, 6 ins. diam., bears N. 49° W., 35 lks. dist., mkd. T1N R14E S34 BT.

A well, with a steel pipe casing, 18 ins. diam., projecting 2 ft. above the ground, bears N. 45°41' W., 13.80 chs. dist.

The NE. cor. of an extension of an old house, bears N. 40°36' W., 15.64 chs. dist.

The SE. cor. of a house, bears N. 15°35' W., 19.02 chs. dist.

The cor. is 5 lks. N. of a fenceline bearing E. and W. N. 0°01' W., bet. secs. 34 and 35.

Over rolling mountainous land, through heavy undergrowth and moderate timber.

- 0.60 Small draw, drains S. 85° W.
- 3.70 Spur, slopes S. 70° W.
- 9.60 Fenceline, bears N. 80° E. and S. 80° W.
- 11.80 Spur, slopes N. 85° W.
- 19.70 Track road in the bottom of a draw, bears N. 80° E. and S. 80° W.; draw drains N. 80° E.

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
23.70	Power line, bears E. and S. 70° W.
24.60	Power line, bears E. and S. 70° W.
27.40	Power line, bears N. 65° E. and S. 65° W.
38.70	Ravine, drains S. 80° E.
40.00	Point for the 1/4 sec. cor. of secs. 34 and 35.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.
	T1N R14E 1/4 S34 S35 1972
	from which
	The NE. cor. of a house, bears S. 5°15' W., 5.36 chs. dist.
	A cedar, 10 ins. diam., bears S. 77°52' W., 108 lks. dist., mkd. T1N R14E 1/4 S34 BT.
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of the cor.
43.70	Bladed mining road, bears E. and W. curving N.; enter active mining area, bears E. and W.
59.30	Spur, slopes S. 55° E.
71.00	Leave mining area, enter mountainous land, through moderate undergrowth, and scattered timber.
78.10	Spur, slopes S. 65° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.
	T1N R14E S27 S26 S34 S35 1972
	from which
	A cedar, 6 ins. diam., bears N. 4°55' W., 67 lks. dist., mkd. T1N R14E S27 BT.
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS		
	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar and pine. Undergrowth, oak bush, manzanita, cat claw and cacti.</p>	
	<p>From the true point for the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°58' W., bet. secs. 26 and 35.</p> <p>Over rolling mountainous land, through moderate timber and undergrowth.</p>	
4.29	<p>Intersect line 1-2, M.S. 3033, May lode, at a point from which Cor. No. 2, identical with Cor. No. 1, M.S. 3033, High Point lode, bears S. 77°01' W., 1.99 chs. dist., as calculated from the approved mineral survey record. (No cor. found).</p>	
20.38	<p>Intersect line 2-3, M.S. 3033, Hard Times lode, at a point from which Cor. No. 2, bears S. 9°35' E., 3.61 chs. dist., as calculated from the approved mineral survey record. (No cor. found).</p>	
21.96	<p>Intersect line 1-2, M.S. 3009, Big A Nuff lode, at a point from which Cor. No. 1, bears N. 83°29'13" E., 2.83 chs. dist., as calculated from the approved mineral survey record. (No cor. found).</p>	
38.30	<p>Wash, 20 lks. wide, 2 ft. deep, drains NE.</p>	
39.91	<p>Point for the 1/4 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T1N R14E 1/4 $\frac{S26}{S35}$ 1972</p> <p>from which</p> <p>A pine, 6 ins. diam., bears S. 3°45' W., 135 lks. dist., mkd. 1/4 S35 BT.</p> <p>A pine, 6 ins. diam., bears N. 45°45' W., 134 lks. dist., mkd. 1/4 S26 BT.</p> <p>Cor. No. 3, M.S. 4684, Brand No. 3 lode, identical with cor. No. 4, Brand No. 1 lode of the same survey, bears N. 34°10' W., 11.18 chs. dist., monumented by an iron post, 1 in. diam., projecting 8 ins. above ground, brass cap mkd. BRAND 1-4-4684A and BRAND 3-3-4684A.</p> <p>Cor. No. 2, M.S. 3009, Big A Nuff lode, bears S. 39°12' W., 2.89 chs. dist., monumented by an iron post, 2 1/2 ins. diam., mkd. 1.c.c.co 2-3009.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p>	
73.40	<p>Top of rounded hill.</p>	
79.82	<p>The cor. of secs. 26, 27, 34 and 35.</p>	

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
	Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar and pine. Undergrowth, oak bush, manzanita, cat claw and cacti.
	N. 0°01' W., bet. secs. 26 and 27. Over rolling mountainous land, through moderate timber and undergrowth.
0.80	Track road, bears S. 55° W. and N. 55° E., curving E.
3.40	Fenceline, bears NE. and SW.
9.60	Track road and water pipe, bears N. 80° E. and S. 80° W.
10.60	Liveoak Gulch, 30 lks. wide, 2 ft. deep, drains N. 60° E.
15.70	Track road, bears NE. and SW.
32.57	Intersect line 3-4, M.S. 2880, Barney No. 18 lode, common with the South bdy. of Tract A at a point from which Cor. No. 3, identical with Cor. No. 2, Barney No. 21 lode, the same survey, bears N. 78°05'30" E., 2.15 chs. dist. as calculated from the approved mineral survey record. (No cor. found.)
32.69	Intersect the North bdy. of Tract A, at a point from which the point for the NW. Cor., bears S. 78°58' W., 0.86 chs. dist. as calculated from the approved mineral survey record.
40.00	Point for the 1/4 sec. cor. of secs. 26 and 27. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd. TIN R14E 1/4 S27 S26 1972
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.
	The cor. is 31 lks. E. of a pipe line, bearing N. and S. and under a power line bearing N. 9° E. and S. 9° W.
41.80	Pipe line, bears N. 44° E., curving N. and S. 44° W., curving S.
42.10	Mining road, bears N. 44° E., curving N. and S. 44° W., curving S.
45.00	Track road, bears N. 60° E. and S. 60° W.; spur, slopes S. 60° W.
45.80	Track road, bears NE. and SW.
57.00	Wash in Barney Canyon, with a stream of water, 8 lks. wide, 6 ins. deep, course irregularly E.
58.20	Bladed road, bears W. and S. 70° E., curving N.

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS																
67.30	Spur, slopes W.															
77.90	Top of knoll, descend steep N. slope into Webster Gulch.															
79.69	Point for the closing cor. of secs. 22 and 27, hereinafter described.															
80.00	Point for the cor. of secs. 23 and 26 only.															
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top, brass cap mkd.															
	<table style="margin-left: auto; margin-right: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S22</td><td style="padding: 0 5px;"> </td><td style="padding-left: 5px;">T1N</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding: 0 5px;"> </td><td style="padding-left: 5px;">S23</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding: 0 5px;"> </td><td style="padding-left: 5px;">S26</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding: 0 5px;"> </td><td style="padding-left: 5px;">R14E</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;"></td><td style="padding: 0 5px;"> </td><td style="padding-left: 5px;">1972</td></tr> </table>	S22		T1N			S23			S26			R14E			1972
S22		T1N														
		S23														
		S26														
		R14E														
		1972														
	<p>from which</p> <p style="margin-left: 40px;">A pine, 6 ins. diam., bears S. 74° E., 64 lks. dist., mkd. T1N R14E S26 BT.</p>															
	The cor. is on a steep N. slope.															
	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar and pine. Undergrowth, oak bush, manzanita, spanish bayonet and cacti.</p>															
	From the cor. of secs. 23, 24, 25 and 26.															
	S. 89°59' W., bet. secs. 23 and 26.															
	Through active congested mining area.															
39.92	True point for the 1/4 sec. cor. of secs. 23 and 26, is in an active congested mining area, impractical to monument.															
54.00	W. edge of ore dump, bears NE. and SW.; thence over rolling land.															
56.80	Wash, in bottom of Barney Canyon, course N.															
57.20	Track road, bears N. and S., and power line NE. and SW.															
59.00	Enter moderate timber and undergrowth, bears N. and S. 15° E.															
79.84	The cor. of secs. 23 and 26.															
	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar and pine, W. 21.00 chs. Undergrowth, oak bush and cacti, W. 20.00 chs.</p>															
	N. 0°01' W., bet. secs. 22 and 23.															
	Over rolling mountainous land, through moderate timber and undergrowth.															

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS																
2.80	Bladed road, bears N. 85° E. and S. 85° W.															
3.70	Webster Gulch, 30 lks. wide, 4 ft. deep, course N. 85° E.															
31.20	Ridge, bears S. 60° W. and N. 60° E., curving E.															
39.64	Point for the 1/4 sec. cor. of sec. 22, hereinafter described.															
40.00	Point for the 1/4 sec. cor. of sec. 23. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base to top, brass cap mkd.															
	<table border="0"> <tr><td> </td><td>T1N</td></tr> <tr><td> </td><td>1/4 S23</td></tr> <tr><td> </td><td>R14E</td></tr> </table>		T1N		1/4 S23		R14E									
	T1N															
	1/4 S23															
	R14E															
	1972															
	The cor. is on the N. edge of a wash, 10 lks. wide, 2 ft. deep, drains N. 65° E.															
54.20	Wash, course irregularly E.															
61.20	Small spur, slopes SE.															
79.40	Wash, 15 lks. wide, 3 ft. deep, drains E., curving NE.															
79.59	Point for the closing cor. of secs. 15 and 22, hereinafter described.															
80.00	Point for the cor. of secs. 14 and 23.															
	Set a fiberglass post, 30 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base to top, brass cap mkd.															
	<table border="0"> <tr><td>S15</td><td> </td><td>T1N</td></tr> <tr><td></td><td> </td><td>S14</td></tr> <tr><td></td><td> </td><td>S23</td></tr> <tr><td></td><td> </td><td>R14E</td></tr> <tr><td></td><td></td><td>1972</td></tr> </table>	S15		T1N			S14			S23			R14E			1972
S15		T1N														
		S14														
		S23														
		R14E														
		1972														
	from which															
	A cedar, 5 ins. diam., bears S. 1° E., 95 lks. dist., mkd. T1N R14E S23 BT.															
	Willow Spring, with flowing stream of water, 2 lks. wide, 2 ins. deep, course E., bears N. 71°48' E., 7.20 chs. dist.															
	A rectangular shaped well, 5 ft. x 7 ft., bears S. 53°32' E., 31.80 chs. dist.															
	A well, with a steel pipe casing, 14 ins. diam., projecting 2 ft. above the ground, with a metal plate welded over the top, bears S. 71°36' E., 21.50 chs. dist.															

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar and pine. Undergrowth, oak bush, mesquite, manzanita, cat claw and cacti.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24. S. 89°57' W., bet. secs. 14 and 23. Over rolling mountainous land, through moderate cedar and undergrowth.</p>
21.90	Ridge, bears N. 10° W. and S. 10° E., curving E.
29.50	Draw, drains S.
38.00	Spur, slopes S. 10° E.
39.92	Point for the 1/4 sec. cor. of secs. 14 and 23. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, brass cap mkd.
	<p>T1N R14E 1/4 <u>S14</u> S23 1972</p>
51.00	Draw, drains N. 55° W.
60.00	Willow Spring Gulch, with a flow of water, 20 lks. wide, 4 ins. deep, course S.
63.50	Track road, bears S. 70° E. and N. 70° W., curving west-erly.
79.60	Wash, 15 lks. wide, 3 ft. deep, drains NE.
79.84	The cor. of secs. 14 and 23. Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar. Undergrowth, oak bush, manzanita, cat claw and cacti.
	<p>N. 0°01' W., bet. secs. 14 and 15. Over rolling mountainous land through moderate cedar and undergrowth.</p>
3.00	Wash, course E.
12.80	Top of peak.
23.70	Track road, bears SE. and NW.

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
25.30	Willow Spring Gulch, with a flow of water, 20 lks. wide, 3 ins. deep, course E., curving S.
33.91	Intersect line 2-3, M.S. 4606, Inspiration Mill Site No. 64, at a point from which Cor. No. 2, identical with Cor. No. 3, Inspiration Mill Site No. 63 of the same survey, bears N. 89°28' W., 0.572 chs. dist., monumented with a steel pin, 5/8 ins. diam., firmly set, projecting 2 ins. above the ground, cap mkd. IMS 64-2 IMS 63-3 4606.
40.00	Point for the 1/4 sec. cor. of secs. 14 and 15. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, brass cap mkd.
	T1N R14E 1/4 S15 S14 1972
	from which Cor. No. 2, M.S. 4606, Inspiration Mill Site No. 64, identical with Cor. No. 3 Inspiration Mill Site No. 63 of the same survey, bears S. 5°21' W., 6.11 chs. dist., heretofore described.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
59.05	Intersect line 3-4, M.S. 2736B, Prince Charming Mill Site, at a point from which Cor. No. 3, bears S. 77°02' E., 2.34 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
66.33	Intersect line 1-2, M.S. 2736B, Prince Charming Mill Site at a point from which Cor. No. 1, bears N. 59°46' W., 4.05 chs. dist., monumented with a porphyry rock in place, 4x4x4 ft. above the ground, mkd. PCMS 1 2736B.
69.10	Lost Gulch, with a flow of water, 30 lks. wide, 6 ins. deep, course S. 80° E.
69.50	Track road, bears S. 80° E. and S. 15° W.
77.80	Rocky ridge, bears S. 55° E. and N. 55° W.
80.00	Point for the cor. of secs. 10, 11, 14 and 15.
	Set a fiberglass post, 30 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a collar of stone, 3 ft. base to top, brass cap mkd.
	T1N R14E S10 S11 S15 S14 1972
	from which

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS

Prince Charming Spring, with man made pond, 20 lks. long, 10 lks. wide, water 3 1/2 ft. deep, bears S. 23° W., 15.45 chs. dist.

A spring, with man made pond, 20 ft. long, 7 ft. wide, water 3 ft. deep, bears S. 25°10' W., 24.35 chs. dist.

Cor. No. 1, M.S. 2736B, Prince Charming Mill Site, bears S. 16°44' W., 12.14 chs. dist., heretofore described.

Cor. No. 2, M.S. 2735, Silver Springs lode, bears S. 42°05' W., 5.00 chs. dist., monumented by a cedar post, 4 ins. square, projecting 4 ft. above ground mkd. SS2-2735 on SW face.

Cor. No. 2, M.S. 3249, Diamond H No. 7 lode, on line 3-4, M.S. 2499, Diamond H No. 5 lode, bears S. 69°22' E., 9.70 chs. dist., monumented by a redwood post, 4 ins. square, projecting 18 ins. above ground, mkd. 2-DH7 3249 on N. face, from which a rock in place 5x10x1 ft. above ground, bears N. 34°40' W., 14 lks. dist., mkd. BR + 3249.

The cor. is on a steep N. slope.

Land, rolling and mountainous.

Soil, shallow and rocky.

Timber, cedar.

Undergrowth, oak bush, manzanita, mesquite, cat claw and cacti.

From the cor. of secs. 11, 12, 13 and 14.

S. 89°57' W., bet. secs. 11 and 14.

Through an active mining area.

- 8.14 Intersect line 1-2, M.S. 3250, Alpha lode, at a point from which Cor. No. 2, bears S. 68°51' W., 13.86 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
- 23.41 Intersect line 2-3, M.S. 3250, Alpha lode, at a point from which Cor. No. 2, bears S. 25°18' E., 5.53 chs. dist., as calculated from the approved mineral survey record. (No cor. found).
- 23.76 Intersect line 2-3, M.S. 2499, Diamond H No. 9 lode, at a point from which Cor. No. 3, bears S. 18°03' E., 0.69 chs. dist., as calculated from the approved mineral survey record. (No cor. found).

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
39.93	Point for the 1/4 sec. cor. of secs. 11 and 14, is in an active mining area, presently under expansion. Impractical to monument.
45.00	Leave active mining area, enter scattered timber and moderate undergrowth, bears NE. and SW.
55.90	Draw, drains south.
59.90	Track road, bears S. 70° E. and N. 70° W.
65.50	Draw, drains South.
72.41	Intersect line 2-3, M.S. 3249, Diamond H No. 7 lode, at a point from which Cor. No. 2, bears S. 25°24' E., 3.79 chs. dist., heretofore described.
79.86	The cor. of secs. 10, 11, 14 and 15.
	Land, rolling and mountainous. Soil, shallow and rocky. Timber, W. 35.00 chs., cedar. Undergrowth, W. 35.00 chs., oak bush, manzanita, cat claw, and cacti.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 89°53' W., bet. secs. 27 and 34.
	Over rolling mountainous land, through moderate cedar and heavy undergrowth.
1.00	Track road, bears N. 55° E. and S. 55° W.
3.80	Fenceline, bears NE. and SW.
6.00	Pipe Line, bears NE. and SW.
6.20	Power line, bears N. 70° E. and S. 70° W.
6.80	Fenceline, bears N. 80° E. and S. 80° W.
15.90	Liveoak Gulch, 30 lks. wide, 2 ft. deep, small flow of water, course N. 70° E.
34.60	Spur, slopes S.
38.90	Wash, with a flow of water, 10 lks. wide, 6 ins. deep, course SE.
39.93	Point for the 1/4 sec. cor. of secs. 27 and 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 1/2 ft. base to top, brass cap mkd.
	T1N R14E 1/4 $\frac{S27}{S34}$
	1972
	from which

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS		
	<p>An oak, 3 ins. diam., bears S. 75°40' W., 31 lks. dist., mkd. 1/4 S34 BT.</p> <p>An oak, 4 ins. diam., bears N. 45°40' W., 31 lks. dist., mkd. 1/4 S27 BT.</p> <p>The cor. is on a steep SE. slope.</p>	
59.30	Spur, slopes S. 55° E.	
68.40	Track road on a curve, bears S. 70° W. and S. 20° W. curving W.	
68.60	Ridge, bears NE. and SW.	
75.00	Wash, in bottom of a canyon, 20 lks. wide, 8 ft. banks, with a flow of water, 3 ins. deep, course NE.	
79.65	Fenceline, bears N. and S.	
79.86	The cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 2 ft. base, 2 ft. high, W. of the cor., brass cap mkd.	
	<p style="text-align: center;">T1N R14E <u>S28 S27</u> <u>S33 S34</u> 1923</p>	
	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, scattered juniper and oak. Undergrowth, oak bush, manzanita, cat claw and cacti.</p>	
	<p>From the 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor., brass cap mkd.</p>	
	<p style="text-align: center;">T1N R14E 1/4 <u>S22</u> <u>S27</u> 1969</p>	
	<p>from which</p> <p>U.S.L.M. No. 2652, bears S. 66°43' E., 8.37 chs. dist., monumented with a wooden post, 6 ins. square, firmly set in a mound of stone, 6 ft. base, 2 1/2 ft. high, projecting 3 1/2 ft. above the mound, mkd. U.S.L.M. 2652 on the E. face. (Record, S. 66°42' E., 8.39 chs. dist.)</p> <p>Center of a pond, approximately 2.00 chs. diam., bears S. 12°55' E., 30.70 chs. dist.</p>	

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E

CHAINS	
	<p>Barney Well No. 1, bears S. 8°25' E., 30.05 chs. dist.</p> <p>Barney Well No. 3, bears S. 24°35' W., 30.45 chs. dist.</p> <p>An orig. bearing tree, an oak, 10 ins. diam., bears N. 68°36' W., 100 lks. dist., mkd. with an overgrown blaze.</p> <p>East, bet. secs. 22 and 27.</p> <p>Over rolling mountainous land, through scattered timber and medium undergrowth.</p>
1.90	Spur, slopes N.
3.90	Draw, drains N. 5° W.
6.90	Spur, slopes N.
10.90	Spur, slopes N.
23.60	Track road, bears N. and S. 40° E.
39.94	Point for the closing cor. of secs. 22 and 27, at intersection with the W. bdy. of sec. 26.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground, and in a mound of stone, 4 ft. base to top, brass cap mkd.</p> $\begin{array}{c} \text{T1N} \\ \text{CC } \frac{\text{S22}}{\text{S27}} \text{ S26} \end{array}$ <p>R14E 1972</p> <p>from which</p> <p>The cor. of secs. 23 and 26, bears N. 0°01' W., 31 lks. dist., heretofore described.</p> <p>The cor. is on a steep N. slope.</p> <p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, oak and cedar. Undergrowth, oak bush, manzanita, cat claw and cacti.</p>
	<p>From the 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, brass cap mkd.</p> $\begin{array}{c} 1/4 \frac{\text{S15}}{\text{S22}} \\ 1923 \end{array}$ <p>from which the remains of the original bearing trees</p> <p>An oak, 20 ins. diam., bears N. 6° E., 79 lks. dist., mkd. with an overgrown blaze.</p> <p>An oak stump, 12 ins. diam., bears S. 73° W., 117 lks. dist.</p>

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS		
	<p>East, bet. secs. 15 and 22.</p>	
	<p>Over rolling mountainous land, through scattered timber and medium undergrowth.</p>	
4.30	<p>Descend steep E. slope.</p>	
9.29	<p>Intersect line 2-3, M.S. 4742, Camelback 14 Mill Site, at a point from which Cor. No. 2, identical with Cor. No. 2, Camelback 15 Mill Site of the same survey, bears South, 0.60 chs. dist., as calculated from the approved mineral survey record.</p>	
26.80	<p>Track road, bears S. 15° W. and N. 7° W.</p>	
38.80	<p>Knoll.</p>	
39.82	<p>Point for the closing cor. of secs. 15 and 22, at intersection with the W. bdy. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 1/2 ft. base to top, brass cap mkd.</p>	
	<p style="text-align: center;"> T1N CC S15 S23 S22 R14E 1972 </p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">The cor. of secs. 14 and 23, bears N. 0°01' W., 41 lks. dist., heretofore described.</p>	
	<p>Land, rolling and mountainous. Soil, shallow and rocky. Timber, cedar and oak. Undergrowth, oak bush, manzanita, cat claw and cacti.</p>	
	<p>The point for the E 1/4 sec. cor. of secs. 22 is on the E. bdy. of the sec. and at mid-point bet. the closing cors.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 2 1/2 ft. base to top, brass cap mkd.</p>	
	<p style="text-align: center;"> T1N 1/4 S22 R14E 1972 </p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">The 1/4 sec. cor. of sec. 23, bears N. 0°01' W., 36 lks. dist., heretofore described.</p>	

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS

From the cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 ins. diam., firmly set, projecting 8 ins. above the ground, and in a mound of stone, 1 1/2 ft. base to top, brass cap mkd.

T1N R14E	
S16	S15
S21	S22
1923	

from which the remains of the original bearing trees

A dead oak, 14 ins. diam., bears N. 15° E., 88 lks. dist., mkd. T1N R14E S15 BT.

An oak, 14 ins. diam., busted off 3 ft. above the ground, bears S. 77°30' E., 43 lks. dist., mkd. T1N R14E S22 BT.

The stump hole of a downed cedar, 6 ins. diam., bears S. 37° W., 177 lks. dist., the tree mkd. BT with other illegible markings.

The stump hole of a dead oak, 6 ins. diam., bears N. 46° W., 50 lks. dist., dead oak lying alongside is mkd. with a healed blaze.

The center of a windmill bears N. 39°06' W., 5.01 chs. dist.

Cor. No. 4, M.S. 3560, Oversight Copper lode, bears N. 3°32'30" E., 5286 chs. dist., monumented by a granite stone, 8x12x14 ins. above ground, mkd. with an x on top and 4 3560 on the W. face, with a mound of stone, 3 ft. base, 1 ft. high N. of the cor.

The cor. is in a fenceline bearing N. and S.

N. 0°02' W., bet. secs. 15 and 16.

Over mountainous land, through scattered timber and medium undergrowth.

- | | |
|-------|---|
| 5.00 | Wash, 15 lks. wide, with a flow of water, 4 ins. deep, course N. 65° E. |
| 5.55 | Intersect line 4-1, M.S. 3560, Oversight Copper lode, at a point from which Cor. No. 4, bears N. 50°33' E., 0.473 chs. dist., heretofore described. |
| 6.52 | Intersect line 3-4, M.S. 3560, Oversight Copper lode, at a point from which Cor. No. 4, bears S. 28°37' E., 0.764 chs. dist., heretofore described. |
| 23.50 | Rocky ridge, bears E. and W. |
| 29.50 | Wash, drains N. 65° E. |
| 31.00 | Spur, slopes N. 75° E. |

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
35.60	Wash, drains S. 60° E.
40.00	<p>Point for the 1/4 sec. cor. of secs. 15 and 16.</p> <p>Set a fiberglass post, 30 ins. long, 2 1/2 ins. diam., 2 ins. in the ground, over an X mkd. on solid rock, and in a mound of stone, 3 1/2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T1N R14E 1/4 S16 S15 1972</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 5 ins. diam., bears S. 76°50' E., 32 lks. dist., mkd. 1/4 S15 BT.</p>
41.90	Ridge, bears S. 85° E. and N. 85° W.
51.00	Draw, drains S. 85° E.
59.10	Spur, slopes N. 70° E.
67.20	Descend a steep N. slope.
73.00	Draw, drains NE.
76.00	Spur, slopes NE.
80.00	<p>Point for the cor. of secs. 9, 10, 15 and 16.</p> <p>Set a fiber glass post, 30 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T1N R14E S 9 S10 S16 S15 1972</p> <p>The cor. is 3 lks. E. of a fenceline, bearing N. and S.</p> <p>Land, mountainous. Soil, shallow and rocky. Timber, oak and cedar. Undergrowth, oak bush, manzanita, spanish dagger and cacti.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°39' W., bet. secs. 10 and 15.</p> <p>Over mountainous land with large rock outcroppings, through dense undergrowth and scattered timber.</p>

Survey, Portion of the Subdivisional Lines, T. 1 N., R. 14 E.

CHAINS	
1.00	Top of ridge, bears S. 55° E. and N. 55° W.
13.30	Wash, small flow of water, course S. 60° E.
13.80	Track road, bears S. 5° E. and N. 5° W.
39.91	Point for the 1/4 sec. cor. of secs. 10 and 15.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a collar of stone, 2 1/2 ft. base to top, brass cap mkd.
	<p style="text-align: center;">T1N R14E S10 1/4 S15 1972</p>
	from which
	<p>U.S.M.M. No. 2736 Amd., bears N. 11°17' E., 27.98 chs. dist., monumented with a porphyry rock in place, 2x3x4 ft. above ground, mkd. with an X on top for the exact location and USMM No. 2736 on the northeast face, from which a porphyry rock in place, 4x3x2 ft. above ground, mkd. X 2736 BR, bears N. 34°15' E., 13.3 lks. dist., and a porphyry rock, 6x4x4 ft. above ground, mkd. X 2736 BR, bears N. 74°12' W., 68.3 lks. dist.</p>
	The cor. is on a steep N. slope.
46.40	Rocky spur, slopes N.
58.70	Rocky spur, slopes N.
72.10	Draw, drains N.
74.80	Draw, drains NE.
79.82	The cor. of secs. 9, 10, 15 and 16.
	<p>Land, mountainous. Soil, shallow and rocky. Timber, oak and cedar. Undergrowth, oak bush, manzanita, cat claw, spanish dagger and cacti.</p>
	General Description
	<p>A small portion of the east boundaries of secs. 25 and 36, of T. 1 N., R. 14 E., pass through the western part of the City of Miami, Arizona. The N. and W. boundaries of the area surveyed are adjacent to the Tonto National Forest.</p>
	<p>The area surveyed and resurveyed ranges from mountainous in most areas to nearly level in Bloody Tanks Wash. The elevation varies from 3,425 ft. to 5,250 ft. above sea level. The soil is rocky throughout the Tp. with gravelly loam along the bottoms of most of the washes. The vegetation consists of oak bush, manzanita, cat claw and cacti.</p>

General Description,
T. 1 N., R. 14 E.

CHAINS

There are scattered oak, pine and cedar throughout the Tp. with cottonwood trees along many of the washes.

The general drainage of the Tp. is easterly.

U.S. Highway No. 60, and Bloody Tanks Wash, enter the township on the S. bdy. of sec. 35 and traverse north-easterly leaving the Tp. on the E. bdy. of sec. 25. The Southern Pacific Railroad enters on the E. bdys. of secs. 24 and 36 for mining purposes. There are numerous gravel, track, and mining roads throughout the area. Power lines and water pipe lines are numerous for mining operations.

Water wells are in secs. 23, 27, 34 and 36 and catch ponds are located in secs. 27 and 36. Fresh water springs are in secs. 14 and 15. Mining excavations are evident throughout the surveyed area, with the main interest being copper.

The average of a number of readings along the lines surveyed gives a mean magnetic declination of 14° E. with a range of 1° in local attraction.

CERTIFICATE OF SURVEY

(I) (~~WE~~), Harry K. Smith, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 25th day
 of September, 1972, (I) (~~WE~~) have dependently resurveyed a portion of
 the south boundary (the Gila and Salt River Base Line), Township 1 North,
 Range 14 East, a portion of the west boundary of Township 1 North, Range
 15 East, with new corners established for the south 4 miles of the east
 boundary of Township 1 North, Range 14 East, and surveyed a portion of
 the subdivisional lines of Township 1 North, Range 14 East,

 of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my)
~~XXX~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

February 11, 1974

 (Date)

Harry K. Smith

 (Cadastral Surveyor)

 (Date)

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date FEB 15 1974

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary
 (the Gila and Salt River Base Line), Township 1 North, Range 14 East, a portion
 of the west boundary of Township 1 North, Range 15 East, with new corners estab-
 lished for the south 4 miles of the east boundary of Township 1 North, Range
 14 East, and the survey of a portion of the subdivisional lines of Township
 1 North, Range 14 East, Gila and Salt River Meridian, Arizona.

executed by Harry K. Smith, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

NOV 14 1974

 (Date)

Bernard W. Foley

 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date)

 (Chief, Division of Cadastral Survey) GPO 849-626



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
WASHINGTON, D.C. 20240

IN REPLY REFER TO:

9186 (420)
Group 551,
Arizona

April 22, 1975

Memorandum

To: State Director, Arizona
From: Chief, Division of Cadastral Survey
Subject: T. 1 N., R. 14 E., G&SRM, Arizona

This is in reference to your memorandum dated April 14, 1975, regarding the incorrect lot numbers in Sec. 35, T. 1 N., R. 14 E., as shown on Sheet 7 of the plat accepted November 14, 1974.

The following notation has been added to Sheet 7 of the Duplicate Original plat:

LOT NUMBERS 4, 5, 6 and 7, SECTION 35, ARE ERRONEOUSLY LABELED ON THIS SHEET. REFERENCE SHOULD BE MADE TO SHEET 1 FOR CORRECT LOT NUMBERS. SEE MEMORANDUM 9186 (420), GROUP 551, ARIZONA, DATED APRIL 22, 1975.

An identical notation should be added to Sheet 7 of the Original and Triplicate Original plats.

Roger T. Barron

Acting

ARIZONA STATE OFFICE	
B.L. LAND MANAGEMENT	
APR 24 '75	
CD	_____
ASSOC. SD	_____
PCS	_____
RESOURCES	_____
TECH SER	_____
WGMT SER	_____
PUB. AFF	_____
CF	_____
_____	ACTION
_____	INFO.
_____	SEE ME



Save Energy and You Serve America!