

Form 9180-6  
(April 1965)  
(formerly 4-679)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the  
Corrective Dependent Resurvey  
of a  
Portion of the Subdivisional Lines  
a  
Dependent Resurvey  
of a  
Portion of the Subdivisional Lines  
and a  
Survey  
of  
Subdivision of Sections 20, 21 and 29,  
Township 8 North, Range 29 East

Of the Gila and Salt River Meridian,  
In the State of Arizona

EXECUTED BY

Paul G. Bauer Supv. Cadastral Surveyor

and under supplemental special instructions dated June 27, 1972.  
Under special instructions dated August 30th, 19 71 <sup>^</sup>, which provided for the surveys  
included under Group Number 538, approved August 30, 1971 and June 27, 1972  
and assignment instructions dated Sept. 13, 19 71.

Survey commenced Nov. 8, 19 71

Survey completed Aug. 9, 19 72

1A

BOOK 4998

INDEX DIAGRAM

Township 8 North, Range 29 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	15 20	21 21	17 22	23	24
14	11	20			
30	7 29	19 28	27	26	25
6	4				
31	2 32	33	34	35	36

Subdivision of Sec. 20 -----page 24  
 Subdivision of Sec. 21 -----page 32  
 Subdivision of Sec. 29 -----page 34

Township 8 North, Range 29 East  
Gila and Salt River Meridian, Arizona

## CHAINS

The boundaries and subdivisional lines were surveyed in 1875 by C. B. Foster

A portion of the north boundary (the Second Standard Parallel North) was retraced in 1882 by A. P. Johnson. The north boundary (the Second Standard Parallel North) was resurveyed in 1937 by R. F. Wilson.

The east boundary was retraced in 1883 by A. E. Shoemaker and resurveyed in 1937 by R. F. Wilson.

The south boundary was retraced in 1883 by W. R. Fitzgerald and resurveyed in 1936 by R. F. Wilson.

The west boundary and subdivisional lines were resurveyed in 1937 by R. F. Wilson.

In the 1937 resurvey, the original corner of sections 19, 20, 29 and 30 was not recovered and it was reestablished by proportionate measurement. Other original corners in sections 19, 20, 29, 30, 31, and 32, were not recovered and were reestablished in the same manner in 1937.

Early during the field Phase of the current resurvey of sections 20, 21 and 29 in 1971, under group No. 538, the original corner of sections 19, 20, 29 and 30 was recovered in place, N. 63°05'30" E., 2.910 chains dist., from the 1937 proportional corner.

The land status indicates that secs. 19, 20, 29, 30, 31 and 32 are within the Apache National Forest, except for some patented land in secs. 20 and 29. The record indicates that the patents to these areas were based on the 1875 plat. No patents have been issued that were based on the 1937 plat.

In view of the existing conditions, a corrective dependent resurvey was made of the lines between secs. 31-32, 29-32, 30-31, 29-30, 20-29, 19-30, and 19-20, using the found original cor. of secs. 19, 20, 29 and 30 for control.

The locations of the 1937 iron posts, with respect to the corrected locations were noted and then moved to their new locations. New dates were added to the brass caps and the 1937 accessories to these cors. obliterated.

The following field notes are those of a corrective dependent resurvey of the lines between sections 31/32, 29/32, 30/31, 29/30, 19/30, and 19/20, a dependent resurvey of portions of the lines between sections 21/28, 20/21 and 16/21, designed to restore the corners in their true original locations according to the best available evidence, and a survey of subdivisions in sections 20, 21 and 29 in Township 8 North, Range 29 East, Gila and Salt River Meridian, Arizona.

Corrective Dependent Resurvey, T. 8 N., R. 29 E.

CHAINS

This survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated August 30, 1971, and the Supplemental Special Instructions dated June 27, 1972

The directions of all lines were determined by solar observations and all lines refer to the true meridian. Only the true line bearings and horizontal distances for the surveyed lines are given in these field notes.

The geographic position of the southeast corner of section 29, as scaled from U.S.G.S., Eagar, Arizona Quadrangle, scale 1:24000, dated 1969 is: Latitude 34°03'05" North and Longitude 109°18'00" West.

The mean magnetic declination was found to be 13 1/2° East.

Corrective Dependent Resurvey, Portion of the Subdivisional Lines, Township 8 North, Range 29 East.

Correction of a portion of the resurvey executed by R. F. Wilson in 1937 reestablishing the survey executed by C. B. Foster in 1875.

Beginning at the cor. of secs. 5, 6, 31 and 32, on the south boundary of the township, monumented by an iron post, 2 ins. diam., firmly set, projecting 14 ins. above ground, and in a collar of stone to top, 2 ft. base, brass cap mkd.

T 8N R29E  
 S31|S32  
 S 6|S 5  
 T7N  
 1936

from which

A ponderosa pine, 22 ins. diam., bears N. 8 1/4° E., 94 lks. dist., mkd. T8N R29E S32 BT.

A ponderosa pine, 28 ins. diam., bears S. 67° E., 183 lks. dist., mkd. T7N R29E S5 BT.

A ponderosa pine, 18 ins. diam., bears S. 42° W., 23 lks. dist., mkd. T7N R29E S6 BT.

A ponderosa pine, 15 ins. diam., bears N. 40 1/2° W., 35 lks. dist., mkd. T8N R29E S31 BT.

N. 1°00' W., bet. secs. 31 and 32, over rolling land, through moderate timber.

22.00 Low spur, slopes N. 60° E.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
41.04	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 31 and 32, at proportionate distance, there is no remaining evidence of the orig. cor. From this point, an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, bears S. <math>3^{\circ}02'</math> E., 39.6 lks. dist., brass cap mkd.</p> <p style="text-align: center;"> <math>\frac{1}{4}</math>            S31   S32            1937         </p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. <math>57^{\circ}38'</math> W., 69.5 lks. dist., mkd. with an overgrown blaze.</p> <p>I remove the iron post from its found position and at the corrected cor. point</p> <p>Reset the iron post, 36 ins. long, 1 in. diam., 22 ins. in the ground, collar of stone, 2 ft. base to top, add mks. to the brass cap to read:</p> <p style="text-align: center;">           T8N R29E  <math>\frac{1}{4}</math>            S31   S32            1972            1937         </p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. <math>63^{\circ}</math> E., 5 lks. dist., mkd. T8N R29E <math>\frac{1}{4}</math> S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. <math>18^{\circ}</math> W., 40 lks. dist., mkd. T8N R29E <math>\frac{1}{4}</math> S31 BT.</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, W. of the cor.</p>
41.80	Track road, bears S. $80^{\circ}$ E. and N. $80^{\circ}$ W.
43.40	Draw, drains N. $70^{\circ}$ E.
50.30	Spur, projects E., 4 chs. dist.
59.00	Spur, slopes NE.
66.00	Draw, drains NE.
82.08	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist., there is no remaining evidence of the orig. cor. From this point, an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, bears S. <math>8^{\circ}32'</math> W., 74.8 lks. dist., brass cap mkd.</p> <p style="text-align: center;">           T8N R29E            S30   S29            S31   S32            1937         </p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. <math>28^{\circ}</math> E., 33 lks. dist., mkd. T8N R29E S29 BT.</p>

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

## CHAINS

A ponderosa pine, 18 ins. diam., bears S.  $16\frac{1}{4}^{\circ}$  E.,  
54.5 lks. dist., mkd. T8N R29E S32 BT.

A ponderosa pine, 22 ins. diam., bears S.  $57\frac{1}{2}^{\circ}$  W.,  
84 lks. dist., mkd. T8N R29E S31 BT.

The roothole of a dead and down ponderosa pine, 17  
ins. diam., bears N.  $54\frac{3}{4}^{\circ}$  W., 74 lks. dist., scribe  
mks. not legible.

I obliterate the markings on the bearing trees, remove  
the iron post from its found position and at the correct-  
ed cor. point

Reset the iron post, 36 ins. long, 2 ins. diam., 26 ins.  
in the ground, add mks. to the brass cap to read:

T8N R29E	
S30	S29
S31	S32
1972	
1937	

from which

A ponderosa pine, 14 ins. diam., bears N.  $62^{\circ}$  E.,  
35 lks. dist., mkd. T8N R29E S29 BT.

A ponderosa pine, 11 ins. diam., bears S.  $4\frac{3}{4}^{\circ}$  E.,  
44.5 lks. dist., mkd. T8N R29E S32 BT.

An alligator juniper, 4 ins. diam., bears S.  $72^{\circ}10'$   
W., 50 lks. dist., mkd. T8N R29E S31 BT.

A ponderosa pine, 6 ins. diam., bears N.  $65\frac{3}{4}^{\circ}$  W.,  
56 lks. dist., mkd. T8N R29E S30 BT.

Raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of  
the cor.

Land, gently rolling to rolling.

Soil, rocky clay loam.

Timber, moderate ponderosa pine, scattered juniper.

Undergrowth, scattered grass.

From the cor. of secs. 28, 29, 32 and 33, monumented by  
an iron post, 2 ins. diam., firmly set, projecting 9 ins.  
above ground, brass cap mkd.

T8N R29E	
S29	S28
S32	S33
1937	

from which

An original bearing tree, a dead ponderosa pine, 24  
ins. diam., bears N.  $42\frac{3}{4}^{\circ}$  W., 145 lks. dist., mkd.  
T8N R29E S29 BT.

A ponderosa pine, 12 ins. diam., bears N.  $16^{\circ}30'$  E.,  
62 lks. dist., mkd. T8N R29E S28 BT.

A ponderosa pine, 10 ins. diam., bears S.  $72\frac{3}{4}^{\circ}$  E.,  
21 lks. dist., mkd. T8N R29E S33 BT.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	<p>An alligator juniper, 7 ins. diam., bears S. 41 1/2° W., 38 lks. dist., mkd. T8N R29E S32 BT.</p> <p>N. 84°45' W., bet. secs. 29 and 32.</p> <p>Over rolling and broken N. slope through moderate timber.</p>
1.50	Draw, drains NE.
12.30	Spur, slopes NE.
15.50	Draw, drains NW.
19.20	Wash, 8 lks. wide, 1 ft. deep, drains N. 35° E.
37.10	Large flat spur, slopes N.
38.96	<p>Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist., there is no remaining evidence of the original cor. From this point, an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, in a mound of stone, 2 1/2 ft. base to top, bears S. 8°29' W., 48 lks. dist., brass cap mkd.</p> <p style="text-align: center;">1/4     <math>\frac{S29}{S32}</math></p> <p style="text-align: center;">1937</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 37 1/4° E., 33 lks. dist., mkd. 1/4 S 29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 55 3/4° W., 26 lks. dist., mkd. 1/4 S 32 BT.</p> <p>I obliterate the markings on the bearing trees, remove the iron post from its found position, scatter the mound and at the corrected cor. point.</p> <p>Reset the iron post, 36 ins. long, 1 ins. diam., 22 ins. in the ground, mound of stone, 2 ft. base to top, add mks. to the brass cap to read:</p> <p style="text-align: center;">T8N R29E</p> <p style="text-align: center;">1/4     <math>\frac{S29}{S32}</math></p> <p style="text-align: center;">1972</p> <p style="text-align: center;">1937</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 18 1/4° W., 13 lks. dist., mkd. T8N R29E 1/4 S 32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N. 74° W., 30 lks. dist., mkd. T8N R29E 1/4 S 29 BT.</p>
40.00	Draw, drains N. 20° E.
41.20	Spur, slopes N. 10° E.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
47.20	Wash, 8 lks. wide, 1 ft. deep, drains N. 30° E.
57.00	Draw, drains NE.
63.00	Spur, slopes N. 15° E.
65.90	Draw, drains N. 15° E.
77.92	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, rolling and broken. Soil, rocky loam. Timber, moderate ponderosa pine, scattered juniper. Undergrowth, scattered grass.</p>
	S. 89°17' W., bet. secs. 30 and 31.
	Over rolling N. slope through moderate timber.
8.20	Spur, slopes N.
17.40	Spur, slopes N.
21.20	Dry Canyon, 5 lks. wide, 1 ft. deep, with 2 ins. flowing water, course N. 20° E.
22.00	Small spur, slopes NE.
32.20	Draw, drains NE.
38.90	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the orig. cor. From this point, an iron post, 1 ins. diam., firmly set, projecting 16 ins. above ground, mound of stone, 2 ft. base to top, bears S. 0°18'30" W., 37.3 lks. dist., brass cap mkd.</p>
	$1/4 \frac{S30}{S31}$
	1937
	from which
	<p>A ponderosa pine, 12 ins. diam., bears S. 86° E., 67 lks. dist., mkd. 1/4 S 31 BT.</p>
	<p>A ponderosa pine, 10 ins. diam., bears N. 84 3/4° W., 85 lks. dist., mkd. 1/4 S 30 BT.</p>
	<p>I obliterate the markings on the bearing trees, remove the iron post from its found position, scatter the mound, and at the corrected cor. point</p>
	<p>Reset the iron post, 36 ins. long, 1 ins. diam., 30 ins. in the ground, add mks. to the brass cap to read:</p>
	T8N R29E
	$1/4 \frac{S30}{S31}$
	1972
	1937



Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears N. 36° E., 38 lks. dist., mkd. T8N R29E ¼ S30 BT.</p> <p>A ponderosa pine, 5 ins. diam., bears S. 89° W., 59.5 lks. dist., mkd. T8N R29E ¼ S31 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>The cor. is located 16 lks. north of an old down, forest service telephone line, bearing irreg. E. and W.</p>
47.50	Spur, slopes N.
54.20	Draw, drains NE.
68.00	Rounded knoll.
76.44	<p>The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., projecting 10 ins. above ground, mound of stone, 2 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T8N R28E R29E S25 S30 S36 S31 1937</p>
	<p>from which</p> <p>A ponderosa pine, 20 ins. diam., bears N. 28° E., 39½ lks. dist., mkd. with an overgrown blaze (original record tree as found in 1937 was a yellow pine, 12 ins. diam., N. 28¼° E., 28 lks.)</p> <p>A ponderosa pine, 28 ins. diam., bears N. 69 ¾° E., 135 lks. dist., mkd. T8N R29E S30 BT.</p> <p>A ponderosa pine, 17 ins. diam., bears S. 72 ¾° E., 151 lks. dist., mkd. T8N R29E S31 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N. 11°50' W., 60 lks. dist., mkd. T8N R28E S25 BT.</p> <p>Land, rolling to mountainous. Soil, rocky loam. Timber, moderate ponderosa and jack pine, scattered juniper. Undergrowth, scattered grass.</p>
	<p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 1°30' E., bet. secs. 29 and 30.</p>

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	Over a broken and rolling NE. slope, through moderate timber.
11.30	Draw, drains NE.
14.50	Spur, slopes NE.
21.50	Dry Canyon, 30 lks. wide, with 10 ft. banks, some flowing water, course NE.
28.50	Spur, slopes E.
29.10	Fence, bears S. 85° E. and N. 85° W., spur slopes E.
33.00	Small draw, drains NE.
38.20	Spur, slopes NE.
41.05	Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor. From this point, an iron post, 1 in. diam., firmly set, projecting 24 ins. above ground, mound of stone, 2½ ft. base to top, bears S. 48°47' W., 153.5 lks. dist., brass cap mkd.  <div style="text-align: center;"> <math>\frac{1}{4}</math>                      S30 S29                      1937                 </div> from which  A pinyon pine, 12 ins. diam., bears S. 73¼° E., 14 lks. dist., mkd. $\frac{1}{4}$ S29 BT.  A juniper, 16 ins. diam., bears N. 80° W., 37 lks. dist., mkd. $\frac{1}{4}$ S30 BT.  I obliterate the markings on the bearing trees, remove the iron post, scatter the mound and at the corrected cor. point  Reset the iron post, 36 ins. long, 1 in. diam., 22 ins. in the ground, mound of stone, 2 ft. base to top, add mks. to brass cap to read:  <div style="text-align: center;">                     T8N R29E  <math>\frac{1}{4}</math>                      S30 S29                      1972                      1937                 </div> from which  A ponderosa pine, 14 ins. diam., bears S. 70¼° E., 46 lks. dist., mkd. T8N R29E $\frac{1}{4}$ S29 BT.  A ponderosa pine, 10 ins. diam., bears S. 15° W., 23 lks. dist., mkd. T8N R29E $\frac{1}{4}$ S30 BT.  Desc. slong NE slope.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
45.80	Spur, slopes NE.
61.575	Point for the N 1/16 sec. cor. of secs. 29 and 30, at proportionate dist.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.
	T8N R29E N 1/16 S30 S29 1972
	from which
	A ponderosa pine, 5 ins. diam., bears S. 77½° E., 55.5 lks. dist., mkd. with an X at breast height and BT at the base.
	A ponderosa pine, 7 ins. diam., bears S. 12 3/4° W., 25 lks. dist., mkd. T8N R29E N 1/16 S30 BT.
	A ponderosa pine, 8 ins. diam., bears N. 52 3/4° W., 70 lks. dist., mkd. T8N R29E N 1/16 S30 BT.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.
65.00	Spur, slopes N. 30° E.
71.40	Wash, 15 lks. wide, 2 ft. deep, drains N. 30° E.
82.10	The orig. cor. of secs. 19, 20, 29 and 30, monumented by a limestone, 13x10x8 ins., firmly set in a low mound of stone, 2 ft. diam., mkd. with 5 grooves on E. and 2 grooves on S. faces.
	from which
	A pinyon pine, 8 ins. diam., bears N. 45° E., 11.6 lks. dist., mkd. T VIII N R XXIX E S XX BT. (Record N. 88° E., 12 lks.)
	A pinyon pine stump, 2 ft. high, 5 ins. diam., bears N. 31½° W., 27.5 lks. dist., tree portion lying alongside, mkd. R XXIX S XI (Record N. 1° W., 20 lks. dist.)
	(Note: During the 1937 resurvey of T. 8 N., R. 29 E., a large number of bearing trees were found at great variance in bearing and distance from the record.)

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS

An iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, bears S. 63°05'30" W., 2.91 chs. dist., brass cap mkd.

T8N R29E  
S19|S20  
S30|S29  
1937

from which

An alligator juniper, 24 ins. diam., bears N. 65° E., 114 lks. dist., mkd. T8N R29E S20 BT.

An alligator juniper, 25 ins. diam., bears S. 59½° E., 16 lks. dist., mkd. T8N R29E S29 BT.

A pinyon pine, 18 ins. diam., bears S. 52½° W., 38 lks. dist., mkd. T8N R29E S30 BT.

An alligator juniper, 18 ins. diam., bears N. 41 3/4° W., 81 lks. dist., mkd. T8N R29E S19 BT.

I obliterate the markings on the bearing trees, remove the iron post from its found position and at the original cor. point.

Reset the iron post, 36 ins. long, 2 ins. diam., 32 ins. in the ground, add mks. to brass cap to read:

T8N R29E  
S19|S20  
S30|S29  
1972  
1937

from which

A pinyon pine, 10 ins. diam., bears N. 53° E., 30 lks. dist., mkd. T8N R29E S20 BT.

An alligator juniper, 5 ins. diam., bears S. 43¼° E.,

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS

31 lks. dist., mkd. S29 BT.

A pinyon pine, 6 ins. diam., bears S. 25° W., 38  
lks. dist., mkd. T8N R29E S30 BT.

A juniper, 8 ins. diam., bears N. 52 3/4° W., 29  
lks. dist., mkd. T8N R29E S19 BT.

Bury the orig. cor. stone alongside the iron post.

Land, rolling and mountainous.

Soil, rocky loam.

Timber, moderate ponderosa pine in south one third mile,  
moderate juniper and pinyon pine in remainder.

Undergrowth, scattered grass.

From the cor. of secs. 20, 21, 28 and 29, monumented  
by an iron post, 2 ins. diam., firmly set, projecting 8  
ins. above ground, in a mound of stone, 2 ft. base to  
top, brass cap mkd.

T8N R29E  
S20|S21  
S29|S28  
1937

from which

A juniper, 8 ins. diam., bears N. 20 3/4° E., 20  
lks. dist., mkd. T8N R29E S21 BT.

The 2 ft. stump of a dead and down juniper, 7 ins.  
diam., bears S. 21 1/2° W., 11 lks. dist., mkd.  
T VIII N R XXIX E S XXIX BT.

N. 86°51' W., bet. secs. 20 and 29.

Over mountainous land, through moderate timber.

12.50 Ridge, bears SE and NW.

18.68 Point for the E 1/16 sec. cor. of secs. 20 and 29, at  
proportionate dist.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins.  
in the ground, brass cap mkd.

T8N R29E  
E 1/16 S20  
S29  
1972

from which

A pinyon pine, 10 ins. diam., bears S. 29 3/4° W.,  
59 lks. dist., mkd. E 1/16 S29 BT.

A juniper, 16 ins. diam., bears N. 82 3/4° W., 5  
lks. dist., mkd. E 1/16 S20 BT.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
21.00	<p>Begin desc. over NW. slope.</p>
28.02	<p>Point for the W-E 1/64 sec. cor. of secs. 20 and 29, at proportionate dist.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;"> <math display="block">\begin{array}{r} \text{T8N R29E} \\ \frac{1}{\text{W-E } 64} \quad \frac{\text{S20}}{\text{S29}} \\ 1972 \end{array}</math> </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 32½° W., 26 lks. dist., mkd. W-E 1/64 S29 BT.</p>
	<p style="padding-left: 40px;">A pinyon pine, 9 ins. diam., bears N. 16¼° W., 40.5 lks. dist., mkd. W-E 1/64 S20 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
35.00	<p>Dry Canyon, 20 lks. wide, 1 ft. deep, course N.</p>
37.36	<p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist., there is no remaining evidence of the orig. cor. From this point, an iron post, 1 in. diam., loosely set, with 25 ins. projecting above ground, collar of stone, 2 ft. diam., around base of the iron post, bears S. 63°09' W., 1.462 chs. dist., brass cap mkd.</p>
	<p style="text-align: center;"> <math display="block">\frac{1}{4} \quad \frac{\text{S20}}{\text{S29}} \\ 1937</math> </p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pinyon pine, 10 ins. diam., bears S. 6 3/4° E., 50 lks. dist., mkd. ¼ S29 BT.</p>
	<p>I obliterate the markings on the bearing tree, scatter the mound, remove the iron post from its found position and at the corrected cor. point</p>
	<p>Reset the iron post, 36 ins. long, 1 in. diam., 24 ins. in the ground, mound of stone, 2 ft. base to top, add mks. to the brass cap to read:</p>
	<p style="text-align: center;"> <math display="block">\begin{array}{r} \text{T8N R29E} \\ \frac{1}{4} \quad \frac{\text{S20}}{\text{S29}} \\ 1972 \\ 1937 \end{array}</math> </p>
	<p>from which</p>

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	<p>A ponderosa pine, 6 ins. diam., bears S. 52° E., 51.5 lks. dist., mkd. T8N R29E ¼ S29 BT.</p>
	<p>A ponderosa pine, 14 ins. diam., bears N. 77° W., 50.5 lks. dist., mkd. ¼ S20 BT.</p>
42.40	<p>Track road junction, roads bear N. 25° E., S., and N. 10° W., curving W.</p>
45.90	<p>Wash, 30 lks. wide, with 6 ft. banks drains N. 20° E.</p>
46.70	<p>Point for the E-W 1/64 sec. cor. of secs. 20 and 29, at proportionate dist.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T8N R29E E-W 1/64    <math>\frac{S20}{S29}</math>                   1972</p>
	<p>from which</p>
	<p>A ponderosa pine, 22 ins. diam., bears S. 22° W., 89 lks. dist., mkd. E-W 1/64 S29 BT.</p>
	<p>A pinyon pine, 8 ins. diam., bears N. 49° W., 61 lks. dist., mkd. E-W 1/64 S20 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of the cor.</p>
56.04	<p>Point for the W 1/16 sec. cor. of secs. 20 and 29, at proportionate dist.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. the ground, mound of stone, 3 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T8N R29E W 1/16    <math>\frac{S20}{S29}</math>                   1972</p>
	<p>from which</p>
	<p>A pinyon pine, 10 ins. diam., bears N. 25° E., 45 lks. dist., mkd. W 1/16 S20 BT.</p>
	<p>A pinyon pine, 6 ins. diam., bears S. 19° E., 33 lks. dist., mkd. W 1/16 S29 BT.</p>
56.70	<p>Spur, slopes SE.</p>
61.10	<p>Draw, drains S.</p>
74.72	<p>The cor. of secs. 19, 20, 29 and 30.</p>

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	<p>Land, rolling. Timber, moderate ponderosa pine, scattered pinyon pine and juniper. Soil, rocky loam. Undergrowth, scattered grass.</p> <hr/> <p>S. 89°14' W., bet. secs. 19 and 30.</p> <p>Over mountainous land, through moderate timber.</p>
8.00	Spur, slopes NE.
23.30	Fence, bears N. and S.
30.00	Large spur, slopes N. 30° E.
35.50	Draw, drains NE.
39.79	<p>Point for the <math>\frac{1}{4}</math> sec cor. of secs. 19 and 30, at proportionate dist., there is no remaining evidence of the orig. cor. From this point, an iron post, 1 ins. diam., firmly set, projecting 18 ins. above ground, mound of stone, 2 ft. base to top, bears S. 64°30' W., 130.3 lks. dist., brass cap mkd.</p> <p style="text-align: center;"><math>\frac{1}{4}</math> <math>\frac{S19}{S30}</math></p> <p style="text-align: center;">1937</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 18 ins. diam., bears S. 14° W., 17 lks. dist., mkd. <math>\frac{1}{4}</math> S 30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 2° W., 56 lks. dist., mkd. <math>\frac{1}{4}</math> S 19 BT.</p> <p>I obliterate the markings on the bearing trees, scatter the mound, remove the iron post and at the corrected cor. point</p> <p>Reset the iron post, 36 ins. long, 1 in. diam., 16 ins. in the ground, mound of stone, 2 ft. base to top, add mks. to the brass cap to read:</p> <p style="text-align: center;">T8N R29E <math>\frac{1}{4}</math> <math>\frac{S19}{S30}</math> 1972 1937</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 36 ins. diam., bears S. 5° W., 26 lks. dist., mkd. <math>\frac{1}{4}</math> S30 BT.</p>



Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
	<p>A ponderosa pine, 8 ins. diam., bears N. 34 1/2° W., 41.5 lks. dist., mkd. 1/4 S19 BT.</p>
49.50	Spur, slopes N.
55.00	Leave timber, enter cienega, bears S. 60° E. and N. 60° W.
64.00	Leave cienega, enter timber, bears N. and S. 80° E.
77.98	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented by an iron post, 2 ins. diam., pro- jecting 18 ins. above ground, mound of stone, 2 ft. base to top, brass cap mkd.
	<p style="text-align: center;">T8N R28E R29E S24 S19 S25 S30 1937</p>
	<p>from which</p> <p>A ponderosa pine, 20 ins. diam., bears N. 56 3/4° E., 19 lks. dist., mkd. T8N R29E S19 BT. (Record 53 1/2°)</p> <p>An alligator juniper, 7 ins. diam., bears S. 58 1/4° E., 11 lks. dist., mkd. S30 BT. (record 50 1/2°)</p> <p>A ponderosa pine, 9 ins. diam., bears S. 48° E., 14 lks. dist., scribe mks. visible, not legible. partially overgrown. (Record 45°).</p> <p>A ponderosa pine, 19 ins. diam., bears S. 26 1/4° W., 9 lks. dist., mkd. T8N R28E S25 BT. (Record 34°)</p> <p>An alligator juniper, 10 ins. diam., bears N. 43 1/2° W., 35 lks. dist., mkd. T8N R28E S24 BT.</p> <p>Land, rolling and mountainous. Soil, rocky loam. Timber, moderate ponderosa pine, pinyon pine and juniper. Undergrowth, scattered grass, good grass in cienega.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30. N. 0°40' W., bet. secs. 19 and 20. Over mountainous land through moderate timber.</p>
2.20	Draw, drains SE.
12.30	Ridge, bears N. 70° E. and S. 70° W.
20.04	Point for the S 1/16 sec. cor. of secs. 19 and 20, at proportionate dist.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.

T8N R29E  
S 1/16  
S19|S20  
1972

from which

An alligator juniper, 8 ins. diam., bears S. 67 3/4° E., 48 lks. dist., mkd. S 1/16 S20 BT.

A pinyon pine, 6 ins. diam., bears N. 66 3/4° W., 14.5 lks. dist., mkd. S 1/16 S19 BT.

32.00 Wash, 30 lks. wide, 10 ft. banks, drains NE.

36.50 Spur, slopes NE.

40.08 Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the orig. cor. From this point, an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, bears S. 63°32'30" W., 146.5 lks. dist., brass cap mkd.

1/4  
S19|S20  
1937

from which

A pinyon pine, 16 ins. diam., bears N. 41° E., 17 lks. dist., mkd. 1/4 S20 BT.

A juniper, 12 ins. diam., bears N. 47 1/4° W., 58 lks. dist., mkd. 1/4 S19 BT.

I obliterate the markings on the bearing trees, remove the iron post from its found position and at the corrected cor. point

Reset the iron post, 36 ins. long, 1 ins. diam., 14 ins. in the ground, mound of stone, 3 ft. base to top, add marks to the brass cap to read:

T8N R29E  
1/4  
S19|S20  
1972  
1937

from which

An alligator juniper, 8 ins. diam., bears N. 82 3/4° E., 32 lks. dist., mkd. T8N R29E 1/4 S20 BT.

A ponderosa pine, 8 ins. diam., bears N. 22° W., 47 lks. dist., mkd. 1/4 S19 BT.

Corrective Dependent Resurvey, Portion of the  
Subdivisional Lines, T. 8 N., R. 29 E.

CHAINS	
60.50	Draw, drains N. 30° W.
69.30	Large spur, slopes NW.
80.09	Fence, bears E. and W.
80.16	The cor. of secs. 17, 18, 19 and 20, monumented by an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, brass cap mkd.
	<p style="text-align: center;">T8N R29E S18 S17 S19 S20 1937</p> <p>from which</p> <p>A juniper, 8 ins. diam., bears N. 42½° E., 83 lks. dist., mkd. T8N R29E S17 BT.</p> <p>A pinyon pine, 8 ins. diam., bears S. 27° E., 55 lks. dist., mkd. S20 BT.</p> <p>An alligator juniper, 20 ins. diam., bears S. 78° W., 107 lks. dist., mkd. T8N R29E S19 BT.</p> <p>An alligator juniper, 16 ins. diam., bears N. 54 3/4° W., 153 lks. dist., mkd. T8N R29E S19 BT. (Record 164 lks.)</p> <p>Land, rolling and mountainous. Soil, rocky loam. Timber, moderate to scattered juniper, pinyon pine and ponderosa pine. Undergrowth, scattered to moderate grass.</p>
	<p style="text-align: center;">Dependent Resurvey, Portion Subdivisional Lines Township 8 North, Range 29 East</p> <p style="text-align: center;">Reestablishment of the Resurvey Executed by R. F. Wilson in 1937</p> <hr/> <p>Beginning at the ¼ sec. cor. of secs. 21 and 22, monumented by an iron post, 1 in. diam., firmly set, projecting 20 ins. above ground, mound of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">¼ S21 S22 1937</p> <p>from which</p> <p>A pinyon pine, 12 ins. diam., bears S. 57½° E., 39 lks. dist., mkd. ¼ S22 BT.</p> <p>A juniper, 20 ins. diam., bears N. 89½° W., 40 lks. dist., mkd. ¼ S21 BT. (Record 37 lks.)</p> <p>N. 1°10' E., bet. secs. 21 and 22.</p> <p>Over rolling land, through scattered timber.</p>
7.20	Wash, 10 lks. wide, 1 ft. deep, drains N. 10° W.
20.10	Wash, 10 lks. wide, 1 ft. deep, drains N. 40° W.

Dependent Resurvey, Portion Subdivisional Lines,  
T. 8 N., R. 29 E.

<p>CHAINS 25.40</p>	<p>Track road, bears S. 60° E., and N. 60° W., curving N.</p>
<p>31.20</p>	<p>Wash, 15 lks. wide, 4 ft. banks, drains N. 70° W., curving N.</p>
<p>42.11</p>	<p>Fence, bears N. 38° E. and S. 38° W.</p>
<p>42.32</p>	<p>The cor. of secs. 15, 16, 21 and 22, monumented by an iron post, 1 in. diam., firmly set, projecting 6 ins. above ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R29E S16 S15 S21 S22 1937</p> </div> <p>from which</p> <p>A pinyon pine, 16 ins. diam., bears N. 61½° E., 241 lks. dist., mkd. T8N R29E S15 BT. (Record N. 60½° E., 243 lks.)</p> <p>An alligator juniper, 12 ins. diam., bears S. 82° E., 332 lks. dist., mkd. T8N R29E S22 BT. (Record 335 lks.)</p> <p>A pinyon pine, 18 ins. diam., bears S. 83° W., 455 lks. dist., mkd. T8N R29E S21 BT. (Record S. 81 3/4° W.)</p> <p>A juniper, 16 ins. diam., bears N. 1½° W., 300 lks. dist., mkd. T8N R29E S16 BT. (Record N. 0 3/4° W.)</p> <p>Land, rolling, Soil, rocky loam. Timber, scattered juniper, pinyon pine and ponderosa pine. Undergrowth, scattered to moderate grass.</p> <hr/> <p>S. 89°59' W., bet. secs. 16 and 21.</p> <p>Over rolling land, through scattered timber.</p>
<p>6.70</p>	<p>Wash, 50 lks. wide, 4 ft. banks, drains N. 20° W.</p>
<p>11.10</p>	<p>Abandoned track road, bears N. 25° W. and S. 25° E., curving E.</p>
<p>12.35</p>	<p>Fence, bears S. 80° E. and N. 80° W.</p>
<p>20.24</p>	<p>Point for the E. 1/16 sec. cor. of secs. 16 and 21, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R29E E 1/16 S16 S21 1972</p> </div> <p>from which</p> <p>A juniper, 3 ins. diam., bears N. 65° E., 27 lks. dist., mkd. X BT.</p> <p>A pinyon pine, 5 ins. diam., bears S. 25° W., 22.5 lks. dist., mkd. E 1/16 S21 BT.</p> <p>A stock pond, 120 ft. diam., bears S. 14°02' W., 4.40 chs. dist.</p>

Dependent Resurvey, Portion Subdivisional Lines,  
T. 8 N., R. 29 E.

CHAINS	
32.90	Fence, bears S. 10° E. and N. 10° W.
33.50	Graded road, F. S. No. 285, bears S. 10° E. and N. 10° W.
34.00	Track road, bears irreg: NE. and SW.
34.10	Fence cor., fences extend N., E. and W.
40.48	The ¼ sec. cor. of secs. 16 and 21, monumented by an iron post, 1 in. diam., projecting 3 ins. above ground, brass cap mkd.
	$\frac{1}{4}$ $\frac{S16}{S21}$ 1937
	from which
	The NW. cor. of a log cabin, 16 ft. by 23 ft. in size, with the long side bearing E. and W., bears S. 19°32' E., 49 lks. dist.
	Land, rolling gently. Soil, rocky loam. Timber, scattered juniper and pinyon pine. Undergrowth, moderate grass.
	From the cor. of secs. 28, 29, 32 and 33, previously described.
	N. 0°30' W., bet. secs. 28 and 29.
	Over rolling land, through moderate juniper, pinyon pine, and ponderosa pine.
2.00	Draw, drains NE.
19.40	Wash, 10 lks. wide, 2 ft. deep, drains NE.
25.60	Spur, slopes NE.
31.73	Fence, bears W. and E., 160 lks. to a cor. of fences extending N., SE. and W.
42.55	The ¼ sec. cor. of secs. 28 and 29, monumented by an iron post, 1 ins. diam., firmly set, projecting 7 ins. above ground, brass cap mkd.
	$\frac{1}{4}$ $S29   S28$ 1937
	from which
	A pinyon pine, 11 ins. diam., bears S. 79° E., 74 lks. dist., mkd. ¼ S28 BT.
	A juniper, 10 ins. diam., bears N. 62½° W., 100 lks. dist., mkd. ¼ S29 BT.
	N. 0°30' W., beginning new measurement.
4.40	Wash, 20 lks. wide, 4 ft. banks, drains North from S. 50° W.
7.70	Same wash, 10 lks. wide, ½ ft. deep, drains N. 80° E., curving N., from S.

Dependent Resurvey, Portion Subdivisional Lines,  
T: 8 N.; R. 29 E.

CHAINS		
18.20	Ridge, bears NE. and SW.	
21.22	Point for the N 1/16 sec. cor. of secs. 28 and 29, at proportionate dist.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd:	
	T8N R29E N 1/16 S29 S28 1972	
	from which	
	A pinyon pine, 6 ins. diam., bears S. 81° E., 29 lks. dist., mkd. N 1/16 S28 BT.	
	A pinyon pine, 12 ins. diam., bears N. 55° W., 27 lks. dist., mkd. N 1/16 S29 BT.	
33.40	Wash, 10 lks. wide, 1 ft. deep, drains N. 15° E.	
34.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 30° E.	
37.10	Wash, 5 lks. wide, 1 ft. deep, drains N. 55° E.	
42.44	The cor. of secs. 20, 21, 28 and 29, previously described.	
	Land, rolling and mountainous. Soil, rocky loam. Timber, juniper, pinyon pine and scattered ponderosa pine. Undergrowth, scattered grass.	
	From the ¼ sec. cor. of secs. 21 and 28, monumented by an iron post, 1 ins. diam., firmly set, projecting 9 ins. above ground, brass cap mkd.	
	$\frac{1}{4}$ $\frac{S21}{S28}$ 1937	
	from which	
	A ponderosa pine, 8 ins. diam., bears S. 43½° W., 161 lks. dist., mkd. ¼ S28 BT.	
	A pinyon pine, 7 ins. diam., bears N. 75½° W., 120 lks. dist., mkd. ¼ S21 BT.	
	N. 87°42' W., bet. secs. 21 and 28.	
	Over rolling land.	
3.50	Bladed road, bears NE. and SW.	
4.53	Telephone line, bears N. and S.	

Dependent Resurvey, Portion Subdivisional Lines  
T. 8 N., R. 29 E.

CHAINS	
5.43	Fence, bears N. 70° E. and S. 70° W., enter cottonwood trees, bears N. and S.
6.15	Water Canyon creek, 5 lks. wide, ½ ft. deep, course N. 50° W., curving E. from S. 50° E. curving W.
8.50	Leave cottonwood trees, bears N. and S.
9.18	Power line, bears S. 10° E. and N. 10° W.
19.88	<p>Point selected for the witness W. 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8N R29E W 1/16 ← <math>\frac{S21}{S28}</math> WC 1971</p> <p>from which</p> <p>A juniper, 6 ins. diam., bears N. 36° E., 79 lks. dist., mkd. W 1/16 S21 BT.</p> <p>A pinyon pine, 8 ins. diam., bears S. 64° E., 63 lks. dist., mkd. W 1/16 S28 BT.</p> <p>Raise a mound of stone, 2½ ft. diam., 2 ft. high, N. of the cor.</p>
20.08	Point for the W 1/16 sec. cor. of secs. 21 and 28 at proportionate dist., falls in a wash, 20 lks. wide, 1½ ft. deep, drains N. 70° W., curving N. from S. 70° E., curving S., where a monument cannot be safely perpetuated
21.10	Fence, bears SE. and NW.
25.20	Spur, slopes NW.
32.47	Fence, bears S. 60° E. and N. 60° W.
37.30	Draw, drains NE.
40.16	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>Land, rolling. Soil, rocky loam. Timber, pinyon pine, juniper, and cottonwood along Water Canyon. Undergrowth, scattered grass.</p>
0.90	<p>N. 0°45' E., bet. secs. 20 and 21.</p> <p>Along a broken and steep E. slope, through moderate juniper and pinyon pine.</p> <p>Wash, 20 lks. wide, 2 ft. deep, drains N. 70° E.</p>

Dependent Resurvey, Portion Subdivisional Lines  
T. 8 N., R. 29 E.

CHAINS	
2.60	Spur, slopes SE.
4.63	Fence, bears E. and W.
18.70	Draw, drains N. 60° E.
20.565	Point for the S 1/16 sec. cor. of secs. 20 and 21, at proportionate dist.  Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground, mound of stone, 4 ft. base to top, brass cap mkd.  T8N R29E S 1/16 S20 S21 1972  from which  A pinyon pine, 10 ins. diam., bears N. 78° E., 47 lks. dist., mkd. S 1/16 S21 BT.  A pinyon pine, 8 ins. diam., bears S. 25 3/4° W., 39 lks. dist., mkd. S 1/16 S20 BT.  The cor. is located 35 lks. E. of a cor. of fences bearing irreg. N. and S.
27.50	Large spur, slopes N. 18° E.
38.95	Fence, bears N. 20° E. and S. 20° W.
40.94	Fence, bears irreg. E. and W.
40.97	The witness ¼ sec. cor. of secs. 20 and 21, monumented by an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, brass cap mkd.  W C ¼ S20 S21 1937
41.13	The ¼ sec. cor. of secs. 20 and 21, monumented by a pinyon pine, 5 ins. diam., mkd. ¼ S on W. face.  from which  A ponderosa pine, 14 ins. diam., bears N. 88¼° E., 100 lks. dist., mkd. ¼ S21 BT.  A juniper, 12 ins. diam., bears N. 81° W., 60 lks. dist., mkd. ¼ S20 BT.



Dependent Resurvey, Portion Subdivisional Lines  
T. 8 N., R. 29 E.

CHAINS

Land, mountainous and rolling.  
Soil, rocky loam.  
Timber, pinyon pine and juniper, scattered ponderosa pine.  
Undergrowth, scattered grass.

From the cor. of secs. 16, 17, 20 and 21, monumented by an iron post, 2 ins. diam., projecting 24 ins. above ground, mound of stone, 2½ ft. base to top, brass cap mkd.

T8N R29E  
S17 | S16  
S20 | S21  
1937

from which

A pinyon pine, 12 ins. diam., bears S. 37½° E., 102 lks. dist., mkd. NR XXIX E S XXI BT.

A juniper, 5 ins. diam., bears S. 61½° W., 153 lks. dist., visible mks., not legible, partly overgrown blaze.

N. 87°50' W., bet. secs. 17 and 20.

Over rolling land, through scattered timber, and along S. edge of a lane.

6.70 Wash, 10 lks. wide, 6 ft. banks, drains N.

10.90 End of lane, track road bears S. along W. side of a fence bearing S.

Ascend along fence bearing westerly.

19.07 Point for the E 1/16 sec. cor. of secs. 17 and 20, at proportionate dist.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.

T8N R29E  
E 1/16 S17  
S20  
1972

from which

A juniper, 3 ins. diam., bears S. 32° E., 26 lks. dist., mkd. E 1/16 BT.

A pinyon pine, 4 ins. diam., bears N. 3¼° W., 144 lks. dist., mkd. E 1/16 S17 BT.

A fence cor., bears S. 86°18' E., 50.5 lks. dist., fences bear N., irreg. S. 87° E. and N. 87° W.

Dependent Resurvey, Portion Subdivisional Lines  
T. 8 N., R. 29 E.

CHAINS	
27.50	Draw, drains N. 20° E.
38.14	<p>The ¼ sec. cor. of secs. 17 and 20, monumented by an iron post, 1 in. diam., projecting 18 ins. above ground, mound of stone, 2 ft. base to top, brass cap mkd.</p>
	$\frac{1}{4} \frac{S17}{S20}$ <p>1937</p>
	<p>from which</p> <p>A juniper, 8 ins. diam., bears S. 80°53' W., 316 lks. dist., mkd. ¼ S20 BT.</p> <p>A ponderosa pine, 5 ins. diam., bears N. 10° W., 224 lks. dist., mkd. ¼ S 17 BT. (Record N. 81½° W.)</p> <p>Land, rolling. Soil, rocky loam. Timber, scattered juniper and pinyon pine. Undergrowth, scattered grass.</p>
<p>Subdivision of Section 20, T. 8 N., R. 29 E.</p>	
10.16	<p>From the ¼ sec. cor. of secs. 20 and 29.</p> <p>N. 0°06'30" W., on the N. and S. centerline of sec. 20.</p> <p>Over rolling land, through moderate timber.</p> <p>Point for the C-S-S 1/64 sec. cor. of sec. 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, brass cap mkd.</p>
	$\begin{array}{c} C \\ S-S \ 1/64 \   \ S20 \\ C \\ 1972 \end{array}$
	<p>from which</p> <p>A pinyon pine, 10 ins. diam., bears S. 48½° E., 107 lks. dist., mkd. CSS 1/64 S20 BT.</p> <p>A pinyon pine, 7 ins. diam., bears N. 78° W., 23 lks. dist., mkd. CSS 1/64 S20 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>
12.00	Wash, 30 lks. wide, 2 ft. deep, drains N. 65° E.
13.00	Track road, bears irreg. NE. and SW.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
17.40	Low spur, projects N. 70° E., for 3 chs.
18.19	Wash, 5 lks. wide, 1 ft. deep, drains S. 50° E.
20.32	Point for the C-S 1/16 sec. cor. of sec. 20.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, brass cap mkd.
	C S1/16   S20 C 1972
	from which
	A pinyon pine, 6 ins. diam., bears S. 35½° E., 54 lks. dist., mkd. CS1/16 S20 BT.
	A pinyon pine, 8 ins. diam., bears N. 32° W., 60.5 lks. dist., mkd. CS1/16 S20 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
20.40	Spur, slopes E.
23.50	Draw, drains N. 60° E.
32.10	Draw, drains N. 70° E.
33.70	Low spur, slopes N. 65° E.
36.00	Draw, drains N. 60° E.
38.50	Draw, drains S. 80° E.
40.64	Point for the C 1/4 sec. cor. of sec. 20 at the inter-section with the E. and W. centerline of sec. 20.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, brass cap mkd.
	C ¼   S20 C 1972
	from which
	A pinyon pine, 8 ins. diam., bears N. 40° E., 36 lks. dist., mkd. C¼ S20 BT.
	A pinyon pine, 9 ins. diam., bears N. 58° W., 28 lks. dist., mkd. C¼ S20 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.
44.00	Draw, drains S. 75° E.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
45.70	Spur, slopes E., evidence of prehistoric Indians, rock chippings, pottery sherds, etc.
51.50	Saddle on low ridge, bears N. 70° E. and S. 70° W.
72.95	Power line, bears S. 59° E. and N. 59° W.
80.76	<p>The ¼ sec. cor. of secs. 17 and 20.</p> <p>Land, rolling. Soil, rocky loam. Timber, moderate pinyon pine, scattered juniper. Undergrowth, scattered grass.</p>
	<p>From the ¼ sec. cor. of secs. 20 and 21.</p> <p>N. 87°42' W., on the E. and W. centerline of sec. 20.</p> <p>Over gently rolling land, through moderate pinyon pine and juniper, scattered ponderosa pine.</p>
1.90	Spur, slopes N. 10° W.
15.60	Dry Canyon, 50 lks. wide, 15 ft. banks, drains N. 20° E.
18.97	<p>Point for the C-E 1/16 sec. cor. of sec. 20.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.</p>
	$C \frac{E1/16}{S20} C$ <p>1972</p>
	from which
	<p>A juniper, 8 ins. diam., bears N. 9¼° E., 36 lks. dist., mkd. CE 1/16 S20 BT.</p>
	<p>A pinyon pine, 6 ins. diam., bears S. 8°05' W., 71.5 lks. dist., mkd CE 1/16 S20 BT</p>
	<p>A cor. of fences bears S. 47°26' W., 45 lks. dist., fences extend S. 87°38' E. and N. 5° W.</p>
21.20	Low spur, slopes N. 20° E.
27.00	Draw, drains NE.
28.00	Track road, bears N. 10° E. and S. 10° W.
37.94	The C¼ sec. cor. of sec. 20.
41.50	Small wash, drains NE.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS		
50.90	Spur, slopes NE.	
55.00	Wash, 20 lks. wide, 2 ft. deep, drains N. 60° E.	
56.795	Point for the C-W 1/16 sec. cor. of sec. 20.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, collar of stone, 2 ft. base to top, brass cap mkd.	
	$C \frac{W \ 1/16}{S20} C$ 1972	
	from which	
	An alligator juniper, 8 ins. diam., bears S. 84½° E., 42 lks. dist., mkd. CW 1/16 S20 BT.	
	An alligator juniper, 7 ins. diam., bears S. 70½° W., 24 lks. dist., mkd. CW 1/16 S20 BT.	
66.70	Ridge, bears N. and S.	
72.50	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° E.	
75.65	The ¼ sec. cor. of secs. 19 and 20.	
	Land, rolling to mountainous. Soil, rocky loam. Timber, pinyon pine, juniper. Undergrowth, scattered grass.	
	Subdivision, SE ¼, Sec. 20	
	From the E 1/16 sec. cor. of secs. 20 and 29.	
	N. 0°22' E., on the N. and S. centerline of the SE ¼ of sec. 20.	
	Over rolling and broken NW. slope, through moderate timber.	
7.60	Draw, drains NW.	
15.90	Spur, slopes NW.	
20.43	Point for the SE 1/16 sec. cor. of sec. 20 at intersection with the E. and W. centerline of SE ¼ of sec. 20.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.	
	$SE \ 1/16$ $+$ $S20$ 1972	

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
	<p>from which</p> <p>A pinyon pine, 8 ins. diam., bears N. <math>42\frac{1}{2}^{\circ}</math> E., 29 lks. dist., mkd. SE 1/16 S20 BT.</p> <p>A pinyon pine, 10 ins. diam., bears N. <math>67\frac{1}{2}^{\circ}</math> W., 24.5 lks. dist., mkd. SE 1/16 S20 BT.</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, W. of the cor.</p>
21.90	Dry Canyon, 40 lks. wide, 3 ft. deep, drains E., curving N. from W., curving S.
29.40	Wash, 10 lks. wide, 2 ft. deep, drains N. $60^{\circ}$ E.
40.86	The C-E 1/16 sec. cor. of sec. 20.
	<p>From the S 1/16 sec. cor. of secs. 20 and 21.</p> <p>N. <math>87^{\circ}18'</math> W., on the E. and W. centerline of SE <math>\frac{1}{4}</math> of sec. 20.</p> <p>Over rolling land, through moderate timber.</p>
5.00	Spur, slopes N. $30^{\circ}$ E.
11.00	Begin desc. steep NW. slope.
17.00	Bottom of slope, bears NE. and SW., thence over rolling land.
18.80	The SE 1/16 sec. cor. of sec. 20
24.30	Dry Canyon, 15 lks. wide, 1 ft. deep, drains NE.
26.30	Track road, bears irreg. N. and S.
28.20	Point for the C-W SE 1/64 sec. cor. of sec. 20.
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">C-W-SE 1/64 + S20 1972</p>
	<p>from which</p> <p>A pinyon pine, 10 ins. diam., bears N. <math>46\frac{1}{2}^{\circ}</math> E., 68 lks. dist., mkd. CW SE 1/64 S20 BT.</p> <p>A pinyon pine, 5 ins. diam., bears N. <math>30^{\circ}</math> W., 39 lks. dist., mkd. CW SE 1/64 S20 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
37.60	<p>The C-S 1/16 sec. cor. of sec. 20.</p> <hr/> <p style="text-align: center;">Subdivision, SW<math>\frac{1}{4}</math>, Sec. 20.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>N. 0°25' W., on the N. and S. centerline of the SW<math>\frac{1}{4}</math> of sec. 20.</p> <p>Over rolling land, through moderate timber.</p>
3.00	Draw, drains easterly.
10.09	<p>Point for the C-S-SW 1/64 sec. cor. of sec. 20.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 18 ins. in the ground, collar of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">C-S-SW 1/64 + S20 1972</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 18 ins. diam., bears N. 31<math>\frac{1}{2}</math>° E., 29.5 lks. dist., mkd. CS SW 1/64 S20 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 12 ins. diam., bears S. 72° W., 27 lks. dist., mkd. CS SW 1/64 S20 BT.</p>
20.18	<p>Point for the SW 1/16 sec. cor. of sec. 20 at the intersection with the E. and W. centerline of the SW<math>\frac{1}{4}</math> of sec. 20.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 9 ins. in the ground, mound of stone, 3<math>\frac{1}{2}</math> ft. base to top, brass cap mkd.</p> <p style="text-align: center;">SW 1/16 + S20 1972</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 30° E., 81 lks. dist., mkd. SW 1/16 S20 BT.</p> <p style="padding-left: 40px;">A pinyon pine, 13 ins. diam., bears N. 38° W., 48 lks. dist., mkd. SW 1/16 S20 BT.</p>
27.80	Spur, slopes NE.
38.90	Wash, 20 lks. wide, 1 ft. deep, drains E., curving NE.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
40.37	The C-W 1/16 sec. cor. of sec. 20.
	<hr/> From the C-S 1/16 sec. cor. of sec. 20.
	N. 87°16' W., on the E. and W. centerline of the SW $\frac{1}{4}$ of sec. 20.
	Over mountainous land, through moderate timber.
8.10	Top of knoll, bears NE. and SW.
9.38	Point for the C-E-SW 1/64 sec. cor. of sec. 20.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., flanged at the base, and with a brass cap riveted to the top, 6 ins. in the ground, mound of stone, 4 ft. base to top, brass cap mkd.
	<p style="text-align: center;">C-E-SW 1/64 + S20 1972</p>
	from which
	<p style="padding-left: 40px;">An alligator juniper, 15 ins. diam., bears N. 51° W., 46 lks. dist., mkd. C-E-SW 1/64 S20 BT.</p>
	<p style="padding-left: 40px;">A pinyon pine, 8 ins. diam., bears N. 2° W., 74 lks. dist., mkd. C-E-SW 1/64 S20 BT.</p>
13.50	Saddle on ridge, bears E. and W.
18.76	The SW 1/16 sec. cor. of sec. 20.
28.30	Large spur, slopes N. 25° E.
37.52	The S 1/16 sec. cor. of secs. 19 and 20.
	<hr/> Subdivision of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 20.
	<hr/> From the E-W 1/64 sec. cor. of secs. 20 and 29.
	N. 0°16' W., on the N. and S. centerline of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 20.
	Over rolling land, through moderate timber.
3.50	Draw, drains N. 65° E.
8.30	Spur, slopes E.
9.20	Small drain, drains irreg. E.
10.13	Point for the SE-SW 1/64 sec. cor. of sec. 20 at the intersection with the E. and W. centerline of the SE $\frac{1}{4}$ SW $\frac{1}{4}$ of sec. 20.



Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

## CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, collar of stone, 2 ft. base to top, brass cap mkd.

SE SW 1/64  
+  
S20  
1972

from which

A pinyon pine, 7 ins. diam., bears N. 38° E., 27.5 lks. dist., mkd. SE SW 1/64 S20 BT.

A juniper, 22 ins. diam., bears S. 79° W., 33 lks. dist., mkd. SE SW 1/64 S20 BT.

20.25 The C-E-SW 1/64 sec. cor. of sec. 20.

From the C-S-S 1/64 sec. cor. of sec. 20.

N. 87°04' W., on the E. and W. centerline of the SE¼ SW¼ of sec. 20.

Over rolling land, through moderate timber.

2.20 Wash, 10 lks. wide, 1 ft. deep, drains NE.

3.40 Wash, 15 lks. wide, 1½ ft. deep, drains N. 70° E.

4.60 Track road, bears NE. and SW.

9.365 The SE-SW 1/64 sec. cor. of sec. 20.

11.50 Wash, 10 lks. wide, 1 ft. deep, drains S. 60° E.

18.73 The C-S-SW 1/64 sec. cor. of sec. 20.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
	Subdivision of Section 21, T. 8 N., R. 29 E.
	-----
	From the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.
	N. $0^{\circ}46'$ E., on the N. and S. centerline of sec. 21.
	Over gently rolling land, through scattered timber.
0.57	Graded road, bears N. $55^{\circ}$ E. and S. $55^{\circ}$ W.
2.05	Fence, bears S. $75^{\circ}$ E. and N. $75^{\circ}$ W.
3.70	Saffell Canyon, 25 lks. wide, 6 ft. banks, drains N. $30^{\circ}$ W.
17.00	Telephone line, bears N. $15^{\circ}$ E. and S. $15^{\circ}$ W.
27.30	Fence, bears N. $83^{\circ}$ E. and S. $83^{\circ}$ W.
28.00	Water Canyon, 10 lks. wide, 1 ft. deep, drains N. $30^{\circ}$ E.
28.90	Fence, bears N. $80^{\circ}$ E. and S. $80^{\circ}$ W.
29.50	Fence, bears N. $85^{\circ}$ E. and S. $85^{\circ}$ W.
31.60	Power line, bears S. $59^{\circ}$ E. and N. $59^{\circ}$ W.
41.77	Point for the C $\frac{1}{4}$ sec. cor. of sec. 21 at intersection with the E. and W. centerline of sec. 21.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, brass cap mkd.
	C $\frac{1}{4}$ + S21 1972
	from which
	A cottonwood, 8 ins. diam., bears N. $74^{\circ}40'$ E., 146 lks. dist., mkd. C $\frac{1}{4}$ S21 BT.
	Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, N. of the cor.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
41.85	Fence, bears S. 85° E. and N. 85° W.
53.80	Track road, bears irreg. N. and S.
61.67	Fence, bears N. 75° E. and SW. 55 lks. to a cor. of fences bearing N., NE. and SW.
76.95	Fence, bears N. 85° E. and S. 85° W.
82.96	The ¼ sec. cor. of secs. 16 and 21.
	<p>Land, gently rolling. Soil, sandy loam. Timber, cottonwoods along Water Canyon, scattered juniper and pine. Undergrowth, moderate grass.</p>
	From the ¼ sec. cor. of secs. 21 and 22.
	N. 88°33'30" W., on the E. and W. centerline of sec. 21.
	Over broken and mountainous land, through moderate juniper and pinyon pine.
2.78	Power line, bears N. and S.
3.20	Spur, slopes N.
8.00	Draw, drains N.
13.00	Spur, slopes N.
20.185	Point for the CE 1/16 sec. cor. of sec. 21.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.
	$\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S21} \\ 1972 \end{array}$
	from which
	A pinyon pine, 8 ins. diam., bears S. 28° W., 8 lks. dist., mkd. CE 1/16 S21 BT.
	A pinyon pine, 6 ins. diam., bears N. 30° W., 10.5 lks. dist., mkd. CE 1/16 S21 BT.
24.50	Spur, slopes SW.
34.94	Graded road, F. S. No. 285, bears N. 10° E. and S. 10° W.
35.47	Fence, parallels road.
37.80	Water Canyon, 5 lks. wide, 6 ins. deep, drains N. 10° W.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
40.37	The $C\frac{1}{4}$ sec. cor. of sec. 21.
45.20	Fence, bears irreg. N. and S.
53.60	Ridge, bears N. and S.
58.16	Power line, bears N. and bears S. 25 lks. to main power line bearing S. $59^\circ$ E. and N. $59^\circ$ W.
58.65	Power line, bears S. $59^\circ$ E. and N. $59^\circ$ W.
60.39	Point for the C-W $1/16$ sec. cor. of sec. 21  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.
	$\begin{array}{c} \text{W } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S21} \\ 1972 \end{array}$
	from which  A juniper, 10 ins. diam., bears S. $3^\circ$ W., 109 lks. dist., mkd. C-W $1/16$ S21 BT.  A pinyon pine, 4 ins. diam., bears N. $78^\circ$ W., 40 lks. dist., mkd. with an X at breast height and BT at the base.
60.53	Fence, bears S. $20^\circ$ E. and N. $20^\circ$ W., 2 lks. dist., to a cor. of fences extending S. $20^\circ$ E. and S. $70^\circ$ W.
60.90	Fence, bears N. $70^\circ$ E. and S. $70^\circ$ W.
65.00	Fence, bears irreg. N. and S. curving E.
68.40	Wash, 15 lks. wide, 1 ft. deep, drains N. $30^\circ$ W.
78.80	Wash, 20 lks. wide, 1 ft. deep, drains N. $20^\circ$ E.
80.41	The $\frac{1}{4}$ sec. cor. of secs. 20 and 21.  Land, mountainous to gently rolling. Soil, rocky clay loam. Timber, moderate pinyon and juniper, some cottonwood along Water Canyon. Undergrowth, moderate grass in open areas.
	<hr/> Subdivision of Section 29, T. 8 N., R. 29 E.
	From the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.  N. $0^\circ 33'$ E., on the N. and S. centerline of sec. 29.  Over mountainous land, through moderate to dense timber.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
4.20	Draw, drains N. 30° E.
7.70	Spur, slopes N. 30° E.
13.70	Wash, 15 lks. wide, 2 ft. deep, drains E., curving NE. from W., curving SW.
16.10	Spur, slopes N. 80° E.
19.50	Draw, drains N. 80° E., asc. broken S. slope.
20.80	Fence, bears N. 75° E. and S. 75° W.
38.00	Spur, slopes W., begin desc. steep NW. slope.
41.80	Point for the $C\frac{1}{4}$ sec. cor. of sec. 29 at the intersection with the E. and W. centerline of sec. 29.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.  T8N R29E C $\frac{1}{4}$ + S29 1972  from which  A juniper, 7 ins. diam., bears N. $42\frac{1}{2}$ ° E., 26 lks. dist., mkd. C $\frac{1}{4}$ S29 BT.  A ponderosa pine, 10 ins. diam., bears S. $57\frac{1}{4}$ ° W., 27.5 lks. dist., mkd. C $\frac{1}{4}$ S29 BT.  Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, adjacent to the NW. side of the iron post for support on the steep NW slope.
45.00	Small draw, drains NW.
50.00	Draw, drains NW.
62.68	Point for the CN 1/16 sec. cor. of sec. 29.  Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.  T8N R29E C N1/16   S29 C 1972  from which  A ponderosa pine, 18 ins. diam., bears S. 26° E., 55 lks. dist., mkd. CN 1/16 S29 BT.  A ponderosa pine, 18 ins. diam., bears N. 58° W., 22 lks. dist., mkd. CN 1/16 S29 BT.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>
65.20	<p>Draw, drains N. 20° W.</p>
73.12	<p>Point for the C-N-N 1/64 sec. cor. of sec. 29.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T8N R29E C N-N1/64 S29 C 1972</p>
	<p>from which</p>
	<p>A juniper, 5 ins. diam., bears N. 65½° E., 28 lks. dist., mkd. CNN 1/64 S29 BT.</p>
	<p>A ponderosa pine, 6 ins. diam., bears S. 61° W., 89 lks. dist., mkd. CNN 1/64 S29 BT.</p>
77.40	<p>Dry Canyon, 30 lks. wide, 1 ft. deep, drains N. 60° E.</p>
83.56	<p>The ¼ sec. cor. of secs. 20 and 29.</p>
	<p>Land, mountainous. Soil, rocky loam. Timber, moderate juniper, pinyon pine and ponderosa pine. Undergrowth, sparse grass.</p>
	<p>From the ¼ sec. cor. of secs. 28 and 29.</p>
	<p>N. 85°48' W., on the E. and W. centerline of sec. 29.</p>
	<p>Over mountainous land, through moderate timber.</p>
3.30	<p>Wash, 10 lks. wide, with 4 ft. banks, drains N. 20° W.</p>
7.30	<p>Low ridge, bears NE. and SW.</p>
12.00	<p>Wash, 5 lks. wide, 6 ins. deep, drains N. 30° W.</p>
12.80	<p>Wash, 5 lks. wide, 6 ins. deep, drains NE.</p>
19.07	<p>Point for the C-E 1/16 sec. cor. of sec. 29.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T8N R29E <u>C-E 1/16</u> S29 1972</p>
	<p>from which</p>

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
	<p>A pinyon pine, 7 ins. diam., bears S. 25° E., 13.5 lks. dist., mkd. CE 1/16 S29 BT.</p> <p>The cor. is located 50 lks. S. of the crest of a spur sloping S. 70° E.</p>
31.50	Crest of hill, bears SE and NW., desc. steep and broken W. slope.
38.14	The C ¼ sec. cor. of sec. 29.
45.90	Draw, drains N. 30° E.
50.20	Spur, slopes N. 35° E.
52.50	Draw, drains N. 10° W.
57.27	<p>Point for the C-W 1/16 sec. cor. of sec. 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, collar of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T8N R29E C-W 1/16 S29 1972</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S. 44° E., 27 lks. dist., mkd. CW 1/16 S29 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears N. 41° W., 48.5 lks. dist., mkd. CW 1/16 S29 BT.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N. of the cor.</p>
60.20	Spur, slopes NW.
62.60	Dry Canyon, 30 lks. wide, with 4 ft. banks, drains N. 30° W.
71.50	Flat spur, slopes N. 65° E.
76.40	The ¼ sec. cor. of secs. 29 and 30.
	<p>Land, mountainous. Soil, rocky loam. Timber, moderate to dense, pinyon pine, juniper and ponderosa pine. Undergrowth, sparse grass.</p> <hr/> <p style="text-align: center;">Subdivision, NE ¼ Section 29</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 29.</p> <p>N. 0°03' E., on the N. and S. centerline of the NE¼ of sec. 29.</p>

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
	Over rolling and broken E. slope through moderate timber.
1.10	Spur, slopes S. 70° E.
3.80	Draw, drains NE.
11.70	Draw, drains S. 60° E.
16.40	Spur, slopes SE.
21.04	Point for the NE 1/16 sec. cor. of secs. 29 at the intersection with the E. and W. centerline of the NE $\frac{1}{4}$ of sec. 29.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T8N R29E NE <math>\frac{1}{16}</math> + S29 1972</p>
	from which
	A juniper, 8 ins. diam., bears N. 17° E., 18 lks. dist., mkd. NE 1/16 S29 BT.
	A juniper, 6 ins. diam., bears S. 28 $\frac{1}{2}$ ° E., 30.5 lks. dist., mkd. NE 1/16 S29 BT.
	Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.
	The cor. is located on the N. edge of a small draw draining N. 60° E., from head S. 60° W., 50 lks. dist.
22.00	Ridge, bears NE. and SW.
31.54	Point for the C-N-NE 1/64 sec. cor. of sec. 29.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, 2 $\frac{1}{2}$ ft. base to top, brass cap mkd.
	<p style="text-align: center;">C-N-NE 1/64 + S29 1972</p>
	from which
	A pinyon pine, 12 ins. diam., bears N. 41° E., 56 lks. dist., mkd. C N NE 1/64 S29 BT.
	A pinyon pine, 10 ins. diam., bears N. 77° W., 62 lks. dist., mkd. C N NE 1/64 S29 BT.



Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
31.64	Wash, 7 lks. wide, 2 ft. deep, drains S. 75° W.
42.04	The E 1/16 sec. cor. of secs. 20 and 29.
	From the N 1/16 sec. cor. of secs. 28 and 29.
	N. 86°18' W., on the E. and W. centerline of the NE¼ of sec. 29.
	Over mountainous land, through moderate timber.
7.20	Draw, drains N. 10° E.
11.50	Wash, 10 lks. wide, 2 ft. deep, drains S. 70° E., asc. steep E. slope.
18.86	The NE 1/16 sec. cor. of sec. 29.
20.70	Ridge, bears NE. and SW.
23.20	Wash, 5 lks. wide, 1 ft. deep, drains N. 10° E.
28.28	Point for the C-W-NE 1/64 sec. cor. of sec. 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.
	C-W-NE 1/64
	+
	S29
	1972
	from which
	A juniper, 6 ins. diam., bears S. 4° E., 10.5 lks. dist., mkd. C W NE 1/64 S29 BT.
	A juniper, 6 ins. diam., bears N. 86¼° W., 26.5 lks. dist., mkd. C W NE 1/64 S29 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.
37.60	Wash, 5 lks. wide, 6 ins. deep, drains N. 5° W.
37.70	The C-N 1/16 sec. cor. of sec. 29.
	Subdivision, NW¼ NE¼ S29
	From the C-W-NE 1/64 sec. cor. of sec. 29.
	N. 0°19'30" E., on the N. and S. centerline of the NW¼ NE¼ S29.
	Over rolling land, through moderate timber.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
8.60	Draw, drains N. 80° W.
10.48	Point for the NW-NE 1/64 sec. cor. of sec. 29 at the intersection with the E. and W. centerline of NW¼ NE¼ of sec. 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.
	NW-NE 1/64 + S29 1972
	from which
	An alligator juniper, 20 ins. diam., bears S. 18¼° E., 40 lks. dist., mkd. NW NE 1/64 S29 BT.
	An alligator juniper, 18 ins. diam., bears N. 73° W., 72.5 lks. dist., mkd. NW NE 1/64 S29 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
20.96	The W-E 1/64 sec. cor. of secs. 20 and 29.
	From the C-N-NE 1/64 sec. cor. of secs. 29.
	N. 86°41' W., on the E. and W. centerline of the NW¼ NE¼ of sec. 29.
	Over rolling land, through moderate timber.
3.00	Draw, drains S. 70° W.
9.38	The NW-NE 1/64 sec. cor. of sec. 29.
14.50	Draw, drains NW.
18.76	The C-N-N 1/64 sec. cor. of sec. 29.
	Subdivision, NW¼ Section 29
	From the C-W 1/16 sec. cor. of sec. 29.
	N. 1°02' E., on the N. and S. centerline of the NW¼ of sec. 29.
	Over rolling and broken land, through moderate timber.
11.70	Dry Canyon, 25 lks. wide, 2 ft. deep, drains N. 65° E.
16.70	Track road, bears N. 20° E. and S. 20° W.

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS	
20.68	<p>Point for the NW 1/16 sec. cor. of sec. 29, at the intervention with the E. and W. centerline of the NW<math>\frac{1}{4}</math> of sec. 29.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T8N R29E NW 1/16 + S29 1972</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 23 ins. diam., bears N. 49<math>\frac{1}{2}</math>° E., 74 lks. dist., mkd. NW 1/16 S29 BT.</p> <p style="padding-left: 40px;">A pinyon pine, 10 ins. diam., bears N. 13<math>\frac{1}{2}</math>° W., 49 lks. dist., mkd. NW 1/16 S29 BT.</p>
32.30	Draw, drains N. 80° E.
35.00	Wash, 10 lks. wide, 1 ft. deep drains E.
41.37	The W 1/16 sec. cor. of secs. 20 and 29.
<hr/>	
<p>From the C-N 1/16 sec. cor. of sec. 29.</p> <p>N. 86°20' W., on the E. and W. centerline of the NW<math>\frac{1}{4}</math> of sec. 29.</p> <p>Over rolling land, through moderate timber.</p>	
11.80	Wash, 10 lks. wide, 1 ft. deep, drains N. 25° E.
15.70	Dry Canyon, 30 lks. wide, 2 ft. deep, drains N. 35° E.
16.40	Track road, bears N. 30° E. and S. 30° W.
18.91	The NW 1/16 sec. cor. of sec. 29.
26.90	Spur, slopes NE.
31.00	Draw, drains N. 30° E.
37.82	The N 1/16 sec. cor. of secs. 29 and 30.
<hr/> <p>General Description</p> <hr/>	
<p>The area covered by this resurvey is rolling and mountainous, covered with juniper, pinyon pine, and ponderosa pine, Water Canyon drains northerly through sections 21 and 28. The water in this canyon is used for</p>	

Survey, Subdivision of Sections  
T. 8 N., R. 29 E.

CHAINS

irrigation in the northern part of the township. A graded road, F. S. N. 285 traverses the township along the east side of Water Canyon. Areas not covered by timber has fair to good grass. The elevation in the area resurveyed ranges from about 9,100 ft. above sea level in sections 31 to about 7,330 ft. above sea level in section 21. There is no evidence of mining. Other than a F. S. Ranger Station in the northern part of section 28, there is no habitation in the area resurveyed. A track road roughly parallels Dry Canyon through section 20 and midway through section 29.



CERTIFICATE OF SURVEY

(I) ~~We~~, Paul G. Bauer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 30th day and supplemental special instructions dated June 27, 1972. of August, 1971, (I) ~~We~~ have made a corrective dependent resurvey of a portion of the subdivisional lines, a dependent resurvey of a portion of the subdivisional lines and a survey of subdivision of sections 20, 21 and 29, Township 8 North, Range 29 East.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~us~~ and under (my) ~~our~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 30, 1973 (Date) Paul G. Bauer (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date APR 29 1974

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the corrective dependent resurvey of a portion of the subdivisional lines, the dependent resurvey of a portion of the subdivisional lines and the survey of subdivisions of sections 20, 21 and 29, Township 8 North, Range 29 East, Gila and Salt River Meridian, Arizona

executed by Paul G. Bauer

having been critically examined and found correct, are hereby approved.

MAR 19 1975 (Date) [Signature] (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626