

Form 9180-6
(April 1965)
(formerly 4-679)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

SURVEY of

a Portion of the

SUBDIVISIONAL LINES

TOWNSHIP 40 NORTH, RANGE 2 WEST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Under special instructions dated June 22, 19 71, which provided for the surveys
included under Group Number 536, approved June 22, 1971,
and assignment instructions dated July 19, 19 71.

Survey commenced August 31, 19 71

Survey completed September 10, 19 71

1A

BOOK 4 9/99

INDEX DIAGRAM

Township 40 North, Range 2 West

			28 (½)	18 (½)	9 (½)
6	5	4	27 8 26	17 2 16	7 1 7
7	8	9	25 10 24	15 11 14	6 12 5
18	17	16	23 15 23	13 14 13	4 13 3
19	20	21	22 22 21	12 23 11	3 24 2
30	29	28	20 27 19	11 26 10	1 25
31	32	33	18 34	9 35	36

Township 40 North, Range 2 West,
Gila and Salt River Meridian, Arizona

CHAINS

The north boundary (the Tenth Standard Parallel North,) was surveyed in 1911 by Andrew Nelson. The east, south and west boundaries and sections 32 and 36 were surveyed in 1954 by Donald E. Harding. The south boundary of section 31 was resurveyed in 1965 by Boyd S. Owens and Paul G. Bauer.

The following notes are those of a survey of a portion of the subdivisional lines of Township 40 North, Range 2 West.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated June 22, 1971.

The directions of all lines were determined by solar observations and all lines refer to the true meridian. Only the true line bearings and horizontal distances for the surveyed lines are given in these notes.

The geographic position at the corner of sections 25, 26, 35 and 36, as determined by traverse from USC&GS Triangulation Station Sandy, located in the northeast portion of section 21 of this township is: Latitude $36^{\circ}49'51''$ North and Longitude $112^{\circ}28'01''$ West.

The mean magnetic declination was found to be: 15° East.

Survey, Portion of the Subdivisional Lines,
Township 40 North, Range 2 West

Beginning at the cor. of secs. 25, 26, 35 and 36, monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 9 ins. above ground and with a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of the cor., brass cap mkd.

T40N R2W
S26 | S25
S35 | S36
1954

from which

A cor. of fences extending E. and S., bears S., 2 lks. dist.

N. $0^{\circ}01'$ W., bet. secs. 25 and 26.

Over rolling land, through moderate undergrowth.

6.00 Wash, 20 lks. wide, 2 ft. deep, drains W.

17.20 Wash, 8 lks. wide, 6 ins. deep, drains S. 80° W.

40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 19 ins. in the ground, and in a collar of stone, 2 ft. base to top, brass cap mkd.

Survey, Portion of the Subdivisional Lines, T. 40 N., R. 2 W.,

CHAINS	
	T40N R2W $\frac{1}{4}$ S26 S25 1971
50.30	Track road, bears S. 20° E. and N. 20° W.
80.00	Point for the cor. of secs. 23, 24, 25 and 26. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, brass cap mkd.
	T40N R2W S23 S24 S26 S25 1971
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner. Land, rolling. Soil, gravelly loam. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.
	From the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above ground, in a mound of stone, 2 ft. base to top, brass cap mkd.
	T40N R2W R1W S24 S19 S25 S30 1954
	N. 89°53' W., bet. secs. 24 and 25. Over rolling land, through moderate undergrowth.
22.10	Gully, 30 lks. wide, 5 ft. deep, drains N. 30° W.
40.00	Point for the ¼ sec. cor. of secs. 24 and 25. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 3½ ft. base to top, brass cap mkd.
	T40N R2W $\frac{1}{4}$ S24 S25 1971
61.90	Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W. from S. 80° E.
79.70	Wash, 15 lks. wide, 3 ft. deep, drains N. 50° W.
80.00	The cor. of secs. 23, 24, 25 and 26.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>Land, rolling. Soil, gravely loam and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p>
	<p>N. 0°01' W., bet. secs. 23 and 24.</p> <p>Over rolling land, through moderate undergrowth.</p>
0.30	Wash, 15 lks. wide, 3 ft. deep, drains N. 50° W.
24.00	Wash, 10 lks. wide, 1 ft. deep, drains N. 50° W.
40.00	Point for the ¼ sec. cor. of secs. 23 and 24.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground, and in a mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S23 S24 1971</p>
64.20	Wash, 10 lks. wide, 4 ins. deep, drains N. 80° W.
70.30	Gully, 25 lks. wide, 3 ft. deep, drains S. 70° W.
80.00	Point for the cor. of secs. 13, 14, 23 and 24.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W S14 S13 S23 S24 1971</p>
	<p>Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p>
	<p>From the cor. of secs. 13, 18, 19 and 24, on the E. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor., brass cap mkd.</p> <p style="text-align: center;">T40N R2W R1W S13 S18 S24 S19 1954</p>
	<p>N. 89°55' W., bet. secs. 13 and 24.</p> <p>Over rolling land, through moderate undergrowth.</p>

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
31.70	Wash, 15 lks. wide, 1½ ft. deep, drains N.
33.80	Power transmission line, bears S. 27°18' E. and N. 27°18' W.
39.99	Point for the ¼ sec. cor. of secs. 13 and 24. Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground and in a mound of stone, 2 ft. base to top, brass cap mkd.
T40N R2W ¼ S13 S24 1971	
79.98	The cor. of secs. 13, 14, 23 and 24. Land, rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.
<hr/> N. 0°01' W., bet. secs. 13 and 14.	
Over rolling land, through moderate undergrowth.	
6.00	Fenceline, bears N. 43° E. and S. 43° W.
9.10	Top of knoll, enter gently rolling land.
28.30	Wash, 5 lks. wide, 1 ft. deep, drains NW.
40.00	Point for the ¼ sec. cor. of secs. 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 2 ft. base to top, brass cap mkd.
T40N R2W ¼ S14 S13 1971	
60.90	Abandoned fenceline with a jeep trail paralleling it, bears S. 25° E. and N. 25° W.
67.20	Wash, 40 lks. wide, with 4 ft. banks, drains W., curving northerly.
79.45	Wash, 5 lks. wide, 6 ins. deep, drains W.
80.00	Point for the cor. of secs. 11, 12, 13 and 14. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, 1½ ft. base to top, brass cap mkd.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS

T40N R2W
S11 | S12
S14 | S13
1971

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.

Land, rolling to gently rolling.

Soil, shallow and rocky.

Timber, none.

Undergrowth, sagebrush and scattered cacti.

From the cor. of secs. 7, 12, 13 and 18, on the E. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 12 ins. above the ground, with a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor., brass cap mkd.

T40N
R2W R1W
S12 | S 7
S13 | S18
1954

S. 89°58' W., bet. secs. 12 and 13.

Over gently rolling land, through moderate undergrowth.

17.50 Track road, bears S. 20° E. and N. 20° W.

30.30 Track road, bears N. 50° E. and S. 50° W.

39.95 Point for the ¼ sec. cor. of secs. 12 and 13.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, 1½ ft. base to top, brass cap mkd.

T40N R2W
¼ S12
S13
1971

from which

U.S.G.S. bench mark, 3-16A, bears N. 9°28'30" W.,
11.59 chs. dist., monumented by a copper nail
and washer cemented in a large stone buried flush
with the ground, with the washer mkd. USGS BM.

41.75 Fenceline, bears N. and S.

44.00 Ryan Road, bears S. 30°54' E. and N. 30°54' W.

45.80 Wash, 10 lks. wide, 2 ft. deep, drains S. 30° W.

73.90 Track road, bears irregularly S. 27¼° E. and N. 27¼° W., paralleling a power transmission line.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
74.70	Power transmission line, bears S. 27°18' E. and N. 27°18' W.
79.90	<p>The cor. of secs. 11, 12, 13 and 14.</p> <p>Land, gently rolling. Soil, gravelly loam. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p>
	N. 0°01' W., bet. secs. 11 and 12.
	Over gently rolling land, through moderate undergrowth.
10.10	Power transmission line, bears S. 25° E. and N. 25° W.
25.60	Wash, 10 lks. wide, 1 ft. deep, drains W.
40.00	<p>Point for the ¼ sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, 1½ ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T40N R2W ¼ S11 S12 1971</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the corner.
47.40	Wash, 10 lks. wide, 6 ins. deep, drains N. 20° W., curving W.
57.50	Wash, 20 lks. wide, 1½ ft. deep, drains N. 75° W.
60.30	Ryan Road, bears S. 30°54' E. and N. 30°54' W.
76.30	Wash, 10 lks. wide, 6 ins. deep, drains irregularly W.
80.00	<p>Point for the cor. of secs. 1, 2, 11 and 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with a collar of stone, 2 ft. base to top, brass cap mkd.</p>
	<p style="text-align: center;">T40N R2W S 2 S 1 S11 S12 1971</p>
	<p>Land, gently rolling. Soil, shallow and rocky. Timber, none. Undergrowth, moderate sagebrush and scattered cacti.</p>

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS

From the cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with a mound of stone, 3 ft. diam., 2½ ft. high, W. of the cor., brass cap mkd.

T40N
R2W R1W
S 1 | S 6
S12 | S 7
1954

S. 89°58' W., bet. secs. 1 and 12.

Over rolling land, through moderate undergrowth.

14.90 Crest of spur, slopes W.

27.50 Wash, 50 lks. wide, 3½ ft. deep, drains N. 65° W., curving westerly.

32.00 Dim track road, bears N. 55° E. and S. 55° W.

35.80 Wash, 30 lks. wide, 3 ft. deep, drains S. 75° W.

39.93 Point for the ¼ sec. cor. of secs. 1 and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, in a collar of stone, 1½ ft. base to top, brass cap mkd.

T40N R2W
¼ S 1
S12
1971

Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the cor.

41.70 Fenceline, bears N. and S.

45.00 Track road, bears S. 20° E. and N. 20° W.

61.50 Wash, 25 lks. wide, 3 ft. deep, drains N. from S. 75° E.

64.60 Spur, slopes S.

73.60 Track road, bears S. 35° E. and N. 35° W.

79.86 The cor. of secs. 1, 2, 11 and 12.

Land, rolling.
Soil, gravely loam.
Timber, none.
Undergrowth, moderate sagebrush and scattered cacti.

N. 0°01' W., bet. secs. 1 and 2.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	Over gently rolling land, through scattered undergrowth.
11.50	Track road, bears S. 45° E., curving southerly and irregularly NW.
29.30	Wash, 70 lks. wide, 3 ft. deep, drains N. 15° W.
34.30	Crest of a small spur, slopes N. 80° W.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 1 and 2. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, brass cap mkd. T40N R2W $\frac{1}{4}$ S 2 S 1 1971
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
48.50	Low ridge, bears irregularly E. and W.
54.00	Wash, 20 lks. wide, 2 ft. deep, drains irregularly N. 60° W.
69.50	Fork of washes, 30 lks. wide, 1 ft. deep, drains N. 70° W., from S. 85° E. and S. 20° E.
81.21	Intersect the S. bdy. of T. 41 N., R. 2 W. (Tenth Standard Parallel North). Point for the closing cor. of secs. 1 and 2. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd. T41N S36 S 2 S 1 C C T40N R2W 1971
	from which The Standard cor. of secs. 35 and 36, T. 41 N., R. 2 W., bears West, 1.89 chs. dist., monumented by an iron post, 3 ins. diam., firmly set, projecting 16 ins. above the ground, brass cap mkd. T41N R2W S35 S36 1911
	The Standard cor. is located in a corner of fences extending N. and W. and E.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS

The closing cor. is located in a fenceline bearing E. and W.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the closing cor.

Land, gently rolling.

Soil, loam.

Timber, none.

Undergrowth, scattered sagebrush.

The true point for the $\frac{1}{4}$ sec. cor. on the N. bdy. of sec. 1, at midpoint between the closing cors., is located in a wash, 35 lks. wide, 1 ft. deep, draining N. 20° W., where a monument cannot be perpetuated.

Select a point 20 lks. East of the true point for a witness $\frac{1}{4}$ sec. cor. of sec. 1.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.

← $\frac{1}{4}$ S 1 WC
T40N R2W
1971

From the true point, the Standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 41 N., R. 2 W., bears West, 1.775 chs. dist., monumented by an iron post, 1 in. diam., firmly set, with 16 ins. projecting above ground and located $4\frac{1}{2}$ lks. S. 30° E. of a cor. of fences extending south and west, brass cap mkd.

$\frac{1}{4}$ S36
1911

Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the witness $\frac{1}{4}$ sec. cor.

From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set, and in a mound of stone, 2 ft. base, 18 ins. high to top, brass cap mkd.

T40N R2W
S34 | S35
S 3 | S 2
T39N
1954

N. $0^\circ 01'$ W., bet. secs. 34 and 35.

Over rolling land, through moderate undergrowth.

14.80

S. rim of Jacob Canyon, bears N. 75° E. and S. 75° W.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
21.20	Wash, in bottom of Jacob Canyon, 20 lks. wide, 2 ft. deep, drains S. 60° W.
23.70	N. rim of Jacob Canyon, bears E. curving SE. and W., curving NW.
26.30	Spur, slopes W.
37.70	Head of draw, drains N. 30° W., curving to S. 70° W.
40.00	Point for the ¼ sec. cor. of secs. 34 and 35. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 4 ft. base to top, brass cap mkd.
	T40N R2W ¼ S34 S35 1971
	The cor. is located near the head of a draw draining W.
48.40	Low ridge, bears E. and W.
74.10	Wash, 25 lks. wide, 1 ft. deep, drains N. 55° W.
80.00	Point for the cor. of secs. 26, 27, 34 and 35. Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 4 ft. base to top, brass cap mkd.
	T40N R2W S27 S26 S34 S35 1971
	Land, rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.
	From the cor. of secs. 25, 26, 35 and 36.
	N. 89°58' W., bet. secs. 26 and 35.
	Over rolling land, through moderate undergrowth.
11.70	Draw, drains N. 10° W.
40.08	Point for the ¼ sec. cor. of secs. 26 and 35. Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.
	T40N R2W ¼ S26 S35 1971

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
80.16	<p>The cor. of secs. 26, 27, 34 and 35.</p> <p>Land, rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p>
	<p>N. 0°01' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through moderate undergrowth.</p>
23.20	Wash, 10 lks. wide, 1 ft. deep, drains W.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W $\frac{1}{4}$ S27 S26 1971</p>
64.40	Wash, 15 lks. wide, 2 ft. deep, drains S. 60° W., curving NW. from E.
77.80	Fence, bears N. 45° E. and S. 45° W.
80.00	<p>Point for the cor. of secs. 22, 23, 26 and 27.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 2 ins. in the ground over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W S22 S23 S27 S26 1971</p> <p>Land, rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, dense sagebrush and scattered yellow top sage.</p>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°56' W., bet. secs. 23 and 26.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
4.80	Draw, drains NE.
17.80	Track road, bears irreg. SE. and NW.
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ $\frac{S23}{S26}$ 1971</p>
55.00	Wash, 10 lks. wide, 1 ft. deep, drains NW., curving W.
69.30	Same wash, 10 lks. wide, 2 ft. deep, drains S. 70° W., curving northwesterly.
76.90	Same wash, 15 lks. wide, 2 ft. deep, drains irreg. N. 80° W.
78.15	Fence, bears N. 45° E. and S. 45° W.
80.16	The cor. of secs. 22, 23, 26 and 27.
	<p>Land, gently rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p>
	<p>N. 0°01' W., bet. secs. 22 and 23.</p> <p>Over gently rolling land, through dense undergrowth.</p>
1.00	Wash, 15 lks. wide, 1 ft. deep, drains W.
29.10	Small draw, drains N. 60° W.
35.80	Wash, 15 lks. wide, 6 ins. deep, drains N. 30° E.
40.00	Point for the ¼ sec. cor. of secs. 22 and 23.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S22 S23 1971</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>
80.00	Point for the cor. of secs. 14, 15, 22 and 23.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W S15 S14 S22 S23 1971</p>
	<p>Land, gently rolling.</p>

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, dense to moderate sagebrush and scattered yellow top sage.</p>
	<p>From the cor. of secs. 13, 14, 23 and 24. N. 89°54' W., bet. secs. 14 and 23. Over rolling land, through moderate undergrowth.</p>
4.80	Track road, bears NE. and SW.
5.40	Fence, bears NE. and SW.
15.30	Spur, slopes S.
21.20	E. rim of canyon, bears Irreg. S. 60° E. and N. 30° W.
25.90	Wash in bottom of canyon, 20 lks. wide, 3 ft. deep, drains from SE. to N., curving NW.
27.60	W. rim of same canyon, bears S. 30° E. and N. 30° W.
40.07	Point for the ¼ sec. cor. of secs. 14 and 23. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	<p>T40N R2W ¼ $\frac{S14}{S23}$ 1971</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.
59.60	Draw, drains S. 35° W., curving W.
77.80	Wash, 7 lks. wide, 1 ft. deep, drains irreg. W. from S. 75° E.
80.14	The cor. of secs. 14, 15, 22 and 23. Land, rolling. Soil, sandy and gravelly loam. Timber, none. Undergrowth, moderate sagebrush, scattered yellow sage.
	<p>N. 0°01' W., bet. secs. 14 and 15. Over gently rolling land, through moderate undergrowth.</p>
0.55	Wash, 7 lks. wide, 1 ft. deep, drains W.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS		
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, $1\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W $\frac{1}{4}$ S15 S14 1971</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>	
59.90	<p>Wash, 5 lks. wide, 1 ft. deep, drains NW.</p>	
61.40	<p>Wash, 30 lks. wide, with 6 ft. banks, drains N. 70° W. for 1.50 dist., thence curves to NW.</p>	
62.20	<p>Wash, 20 lks. wide with 3 ft. banks, drains W.</p>	
73.20	<p>Wash, 10 lks. wide, 6 ins. deep, drains irreg. W.</p>	
80.00	<p>Point for the cor. of secs. 10, 11, 14 and 15.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, in a collar of stone, $1\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W <u>S10 S11</u> S15 S14 1971</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p>	
	<p>From the cor. of secs. 11, 12, 13 and 14.</p>	
	<p>N. $89^\circ 53'$ W., bet. secs. 11 and 14.</p>	
	<p>Over gently rolling land, through moderate undergrowth.</p>	
10.50	<p>Abandoned fenceline, bears S. 24° E. and N. 24° W.</p>	
16.80	<p>Gully, 40 lks. wide, with 7 ft. walls, drains N. 80° W. from SE.</p>	
28.80	<p>Wash, 15 lks. wide, 1 ft. deep, drains N. 45° W.</p>	
40.04	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p>	

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S11 S14 1971</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
46.90	Draw, drains N. 10° W.
55.20	Spur, slopes N.
63.10	Spur, slopes N.
80.08	The cor. of secs. 10, 11, 14 and 15.
	<p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p>
	<p>N. 0°01' W., bet. secs. 10 and 11.</p> <p>Over gently rolling land, through moderate undergrowth.</p>
21.50	Johnson Wash, south fork, 50 lks. wide, 1 ft. deep, drains N. 75° W., curving northerly.
40.00	Point for the ¼ sec. cor. of secs. 10 and 11.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S10 S11 1971</p>
42.50	Wash, 5 lks. wide, 1 ft. deep, drains irreg. NW.
53.20	Small draw, drains NW.
55.40	Spur, slopes N. 60° W., curving NW.
61.50	Wash, 10 lks. wide, 6 ins. deep, drains NW.
64.50	Spur, slopes NW.
78.20	Wash, 10 lks. wide, 6 ins. deep, drains S. 70° W., curving NW. to main wash.
80.00	Point for the cor. of secs. 2, 3, 10 and 11.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.</p>

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS		
	<p>T40N R2W $\frac{S\ 3}{S10} \frac{S\ 2}{S11}$ 1971</p> <p>Land, gently rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12. N. 89°52' W., bet. secs. 2 and 11. Over rolling land, through moderate undergrowth.</p> <p>0.90 Wash, 15 lks. wide, 1 ft. deep, drains S. 30° W.</p> <p>4.00 Bladed road, bears S. 30° E. and N. 30° W.</p> <p>6.20 Spur, slopes S. 10° W.</p> <p>13.20 Wash, 20 lks. wide, 2 ft. deep, drains NW., curving westerly.</p> <p>14.00 Ryan Road, bears S. 58° E., curving S. 34° E. and N. 58° W., curving N. 80° W.</p> <p>23.30 Draw, drains N., curving NW.</p> <p>36.10 Power transmission line, bears S. 27°18' E. and N. 27°18' W.</p> <p>40.04 Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 11. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;"> T40N R2W $\frac{1}{4} \frac{S\ 2}{S11}$ 1971</p> <p>41.40 Wash, 25 lks. wide, 1 ft. deep, drains irreg. N.</p> <p>58.00 Draw, drains N.</p> <p>76.60 Draw, drains south for 50 lks. thence westerly.</p> <p>80.08 The cor. of secs. 2, 3, 10 and 11. Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate sagebrush and yellow top sage.</p> <hr/>	

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	N. 0°01' W., bet. secs. 2 and 3.
	Over gently rolling land, through moderate undergrowth.
15.10	Wash, 5 lks. wide, 1 ft. deep, drains N. 20° W.
17.00	Wash, 8 lks. wide, 1 ft. deep, drains N. 70° W., curving northerly.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.
	T40N R2W $\frac{1}{4}$ S 3 S 2 1971
48.90	Low spur, slopes N. 55° W.
54.30	Track road, bears S. 60° E. and N. 60° W., curving S.
57.90	Wash, 40 lks. wide, with $3\frac{1}{2}$ ft. banks, drains N. 70° W., curving northerly.
61.20	Ryan Road, bears S. 29° E. and N. 29° W.
72.00	Spur, slopes N. 60° W.
80.97	Intersect the S. bdy. of T. 41 N., R. 2 W., (Tenth Standard Parallel North).
	Point for the closing cor. of secs. 2 and 3.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.
	T41N S35 S 3 S 2 C C T40N R2W 1971
	from which
	The Standard cor. of secs. 34 and 35, T. 41 N., R. 2 W., bears West, 1.93 chs. dist., monumented by an iron post, 3 ins. diam., firmly set, projecting 11 ins. above the ground, brass cap mkd.
	T41N R2W S34 S35 1911
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, S. of the closing cor.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS

Land, gently rolling.
Soil, sandy and gravelly clay loam.
Timber, none.
Undergrowth, moderate to sparse sagebrush.

The point for the $\frac{1}{4}$ sec. cor. of sec. 2 is on the N. bdy. at midpoint bet. the closing cors.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.

$\frac{1}{4}$ S 2
T40N R2W
1971

from which

The standard $\frac{1}{4}$ sec. cor. of sec. 35, T. 41 N., R. 2 W., bears West, 1.91 chs. dist., monumented by an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, brass cap mkd.

$\frac{1}{4}$ S 35
1911

From the cor. of secs. 3, 4, 33 and 34, on the S. bdy. of the Tp., monumented by an iron post, $2\frac{1}{2}$ ins. diam., set on solid rock, mound of stone, 4 ft. base to top, brass cap mkd.

T40N R2W
S33|S34
S 4|S 3
T39N
1954

N. $0^{\circ}02'$ W., bet. secs. 33 and 34.

Over rolling land, through moderate undergrowth.

- 4.90 Track road, bears S. 55° E. and N. 55° W.
- 23.90 Wash, 10 lks. wide, 2 ft. deep, drains N. 60° W. from SW.
- 25.80 Wash, 20 lks. wide, 1 ft. deep, drains N. 30° W., curving NE., from SE.
- 35.00 Same wash, 35 lks. wide, 1 ft. deep, drains NE., curving northerly.
- 40.00 Point for the $\frac{1}{4}$ sec. cor. of sec. 33 and 34.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 4 ins. in the ground over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.

Survey, Portion of the Subdivisional Lines
T. 40 N., R. 2 W.

CHAINS		
	T40N R2W $\frac{1}{4}$ S33 S34 1971	
44.90	Bladed road, bears S. 30° E., curving northerly and N. 30° W.	
47.66	Bladed road, bears N. 30° E. and S. 30° W.	
48.50	Bladed road, bears S. 30° E. curving S. 30° W. and N. 75° W., curving southerly.	
48.80	Spur, slopes N. 55° E.	
51.40	Track road, bears S. 60° E., curving south and N. 60° W., curving north.	
52.10	Wash in bottom of Jacob Canyon, 20 lks. wide, with 4 ft. banks, drains N. 80° W., curving northerly.	
61.50	Wash, 15 lks. wide, 6 ins. deep, drains west curving south.	
80.00	Point for the cor. of secs. 27, 28, 33 and 34.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, brass cap mkd.	
	T40N R2W S28 S27 S33 S34 1971	
	from which	
	A fence cor. bears N. 16°03' W., 6.19 chs. dist., fences extend N. 72°50' E. and West.	
	Land, rolling.	
	Soil, sandy and gravelly clay loam.	
	Timber, none.	
	Undergrowth, scattered sagebrush and grass.	
	From the cor. of secs. 26, 27, 34 and 35.	
	N. 89°56' W., bet. secs. 27 and 34.	
	Over gently rolling land, through dense undergrowth.	
8.40	Wash, 10 lks. wide, 1 ft. deep, drains irreg. NW. from S. 60° E.	
19.60	Small spur, slopes N.	
25.10	Draw, drains N. 30° E.	
35.70	Track road, bears irreg. SE and NW.	
40.04	Point for the ¼ sec. cor. of secs. 27 and 34.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.	

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	T40N R2W $\frac{1}{4}$ $\frac{S27}{S34}$ 1971
78.10	Track road, bears SE. curving southerly and irreg. N. 20° W.
80.08	The cor. of secs. 27, 28, 33 and 34. Land, gently rolling. Soil, sandy clay loam. Timber, none. Undergrowth, dense to scattered sagebrush and scattered grass.
	N. 0°02' W., bet. secs. 27 and 28. Over gently rolling land, through dense sagebrush.
3.20	Track road, bears S. 25° E. and N. 25° W.
6.45	Fence, bears N. 72°50' E. and S. 72°50' W.
20.10	Track road, bears N. 20° E. curving northerly and S. 20° W., curving southerly.
27.40	Wash, 20 lks. wide, 1 ft. deep, drains westerly.
30.80	Track road, bears S. 25° E. and N. 25° W. curving northerly.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 1½ ft. base to top, brass cap mkd.
	T40N R2W $\frac{1}{4}$ S28 S27 1971
	The cor. is located 35 lks. east of a track road bearing irreg. N. and S. and 171 lks. east of a N. and S. fence-line. Raise a mound of stone, 2½ ft. base, 2 ft. high, west of the cor.
41.90	Track road, bears N. 20° E. and S. 20° W.
51.90	Track road, bears NE. and S. 15° E.
63.30	Wash, 20 lks. wide, 1 ft. deep, drains N. 65° W.
65.70	Wash, 15 lks. wide, 1 ft. deep, drains S. 50° W.
74.40	Track road, bears S. 10° E. and N. 10° W.
80.00	Point for the cor. of secs. 21, 22, 27 and 28. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W S21 S22 S28 S27 1971</p> <p>The cor. is located 115 lks. east of a track road bearing irreg. N. and S. and 171 lks. east of a N. and S. fenceline.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°56' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through moderate undergrowth.</p>
15.40	A small canyon with wash 40 lks. wide, 2 ft. deep, drains S. 10° W., into north fork of Jacob Canyon.
20.90	East rim of north fork of Jacob Canyon, bears north curving NW. and south for 2.00 chs., thence easterly.
23.40	Wash in bottom of north fork of Jacob Canyon, 25 lks. wide, 2 ft. deep, drains north curving northwest from southwest.
24.50	West rim of north fork of Jacob Canyon, bears south curving S. 70° E. and north curving northwest.
38.30	Wash, 10 lks. wide, 1 ft. deep, drains N. 15° W.
40.06	Point for the ¼ sec. cor. of secs. 22 and 27.
	<p>Set an iron post, 12 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S22 S27 1971</p>
44.80	Draw, drains north.
67.90	Wash, 10 lks. wide, 2 ft. deep, drains NW. curving N. 15° W.
69.00	Wash, 20 lks. wide, 1 ft. deep, drains N. 15° W.
80.12	The cor. of secs. 21, 22, 27 and 28.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>Land, rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.</p>
	<p>N. 0°02' W., bet. secs. 21 and 22. Over gently rolling land, through moderate sagebrush.</p>
2.50	Track road, bears NE. and S. 30° W.
9.70	Wash, 15 lks. wide, 6 ins. deep, drains N. 60° E., curving north.
17.30	Track road, bears S. 20° E. and N. 30° W.
18.50	Wash, 20 lks. wide, 1 ft. deep, drains NW., curving northerly.
24.50	Same wash, 15 lks. wide, 6 ins. deep, drains N. 20° E. curving northerly.
25.90	Track road, bears N. 15° E., curving north and S. 15° W.
32.80	Wash in north fork of Jacob Canyon, 25 lks. wide, 1 ft. deep, drains NW., curving westerly.
40.00	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W $\frac{1}{4}$ S21 S22 1971</p> <p>from which</p> <p>U.S.C.&G.S. 2nd order Triangulation Station "Sandy" bears N. 55°23' W., 17.98 chs. dist., monumented by a standard disk set in bedrock flush with the surface of the ground, 9 ft. southeast of a white witness post. The disk is stamped SANDY 1953.</p> <p>The cor. is located 103 lks. east of a track road bearing irreg. N. and S. and 172 lks. east of a N. and S. fenceline.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>
57.50	Spur, slopes E.
78.20	Small draw, drains N. 30° W., curving northerly.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
80.00	<p>Point for the cor. of secs. 15, 16, 21 and 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground over an X chiseled in bedrock, mound of stone, 4 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W S16 S15 S21 S22 1971</p> <p>The cor. is located 139 lks. east of a track road bearing irreg. N. and S. and 173 lks. east of a N. and S. fenceline.</p> <p>Land, gently rolling. Soil, sandy and rocky clay loam. Timber, none. Undergrowth, scattered sagebrush and yellow top sage.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>N. 89°54' W., bet. secs. 15 and 22.</p>
	<p>Over gently rolling land, through scattered undergrowth</p>
35.80	<p>Spur, slopes N.</p>
38.40	<p>Draw, drains N.</p>
40.08	<p>Point for the ¼ sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S15 S22 1971</p>
42.00	<p>Spur, slopes N.</p>
50.30	<p>Draw, drains NW.</p>
54.50	<p>Spur, slopes N. 30° W.</p>
59.40	<p>Low spur, slopes north curving N. 60° W.</p>
68.80	<p>Draw, drains N. 15° W.</p>
80.16	<p>The cor. of secs. 15, 16, 21 and 22.</p> <p>Land, gently rolling. Soil, shallow and rocky clay loam. Timber, none. Undergrowth, scattered sagebrush and yellow top sage.</p>
	<p>N. 0°02' W., bet. secs. 15 and 16.</p>
	<p>Over gently rolling land, through moderate undergrowth.</p>

Survey, Portion of the Subdivisional Lines
T. 40 N., R. 2 W.

CHAINS		
1.40	Wash, 5 lks. wide, 1 ft. deep, drains N. 30° E.	
13.00	Wash, 25 lks. wide, 3 ft. deep, drains NW.	
40.00	Point for the ¼ sec. cor. of secs. 15 and 16. Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.	
	T40N R2W ¼ S16 S15 1971	
	The cor. is located 164 lks. east of a track road bearing irreg. N. and S. and 175 lks. east of a N. and S. fenceline.	
80.00	Point for the cor. of secs. 9, 10, 15 and 16. Set an iron post, 30 ins. long, 2½ ins. diam., 21 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.	
	T40N R2W S 9 S10 S16 S15 1971	
	The cor. is located 165 lks. east of a track road bearing irreg. N. and S. and 177 lks. east of a N. and S. fenceline. Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.	
	From the cor. of secs. 10, 11, 14 and 15.	
	N. 89°55' W., bet. secs. 10 and 15.	
	Over gently rolling land, through dense undergrowth.	
29.60	Gully in small canyon, 10 lks. wide, with 4 ft. walls, drains N. 50° W.	
34.20	Spur, slopes N. 30° W.	
35.90	Wash, 10 lks. wide, 1 ft. deep, drains N. 20° W.	
40.09	Point for the ¼ sec. cor. of secs. 10 and 15.	

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ $\frac{S10}{S15}$ 1971</p>
80.18	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, dense sagebrush and scattered yellow top sage.</p>
14.10	<p>N. 0°02' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land, through dense undergrowth.</p> <p>Track road, bears N. 40° E., curving easterly and S. 20° W., curving south.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T40N R2W ¼ S 9 S10 1971</p> <p>from which</p> <p style="padding-left: 40px;">A catch pond, 2½ chs. diam., bears S. 29°00' E., 25.09 chs. dist.</p> <p>The cor. is located 177 lks. east of a N. and S. fence-line.</p>
42.40	Wash, 5 lks. wide, 6 ins. deep, drains W. from SE.
62.70	Wash, 10 lks. wide, 1 ft. deep, drains W. from SE.
65.70	Spur, slopes W.
71.00	Wash, 10 lks. wide, 2 ft. deep, drains irreg. W.
80.00	<p>Point for the cor. of secs. 3, 4, 9 and 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.</p>

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
	T40N R2W $\frac{S\ 4}{S\ 9} \frac{S\ 3}{S10}$ 1971
	The cor. is located 180 lks. east of a N. and S. fence-line. Land, gently rolling to rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate sagebrush and scattered yellow top sage.
	From the cor. of secs. 2, 3, 10 and 11. N. 89°55' W., bet. secs. 3 and 10. Over rolling land, through moderate undergrowth.
7.20	Wash, 15 lks. wide, 1 ft. deep, drains S. 30° W.
16.30	Track road, bears N. 30° E. and S. 30° W.
16.50	Track road, bears N. and S.
25.00	Bladed road, bears S. 15° E. and N. 15° W.
26.40	Johnson Wash, south fork, 80 lks. wide, with 3 ft. banks, drains N. 20° W., curving westerly, from S.
37.10	Draw, drains N. 20° E.
40.10	Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 10. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.
	T40N R2W $\frac{1}{4} \frac{S\ 3}{S10}$ 1971
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.
44.70	Track road, bears S. 55° E. curving E. and N. 75° W., curving W.
49.90	Same road, bears irreg. N. and S.
58.90	Wash, 10 lks. wide, 2 ft. deep, drains NW. from S. 30° E.
64.10	Draw, drains N.
67.10	Spur, slopes N. 15° W.
69.10	Small draw, drains N.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
73.00	Small draw, drains N.
80.20	The cor. of secs. 3, 4, 9 and 10. Land, rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, moderate to scattered sagebrush.
	N. 0°02' W., bet. secs. 3 and 4. Over rolling land, through scattered undergrowth.
5.40	Wash, 25 lks. wide, with 3 ft. banks, drains N. 60° W., curving W.
11.20	Low ridge, bears S. 80° E. and N. 80° W.
24.90	Gully, 30 lks. wide, with 10 ft. walls, drains W. curving northerly.
30.70	Gully, 60 lks. wide, with 10 ft. walls, drains W., curving SW.
33.70	Gully, 150 lks. wide, with 12 ft. walls drains W-
35.60	Gully, 100 lks. wide, with 12 ft. walls, drains irreg. W.
38.70	Gully, 30 lks. wide, with 10 ft. walls, drains NW.
39.90	Point selected for the witness $\frac{1}{4}$ sec. cor. of secs. 3 and 4. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd. T40N R2W $\frac{1}{4}$ S 4 \uparrow S 3 W C 1971 Deposit glass alongside the iron post. The cor. is located 179 $\frac{1}{2}$ lks. east of a N. and S. fence-line.
40.00	True point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, falls in wash, 10 lks. wide, with 4 ft. banks, drains S. 80° W., and where a monument cannot be perpetuated.
40.84	Track road, bears SE. and NW.
41.80	S. edge of Johnson Wash, with 12 ft. walls, bears S. 80° E. and N. 80° W.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS	
43.50	Wash in bottom of Johnson Wash, 40 lks. wide, 4 ft. deep, drains S. 70° W.
44.00	N. edge of Johnson Wash, with 12 ft. wall, bears N. 80° E. and S. 80° W.
46.04	Fence, bears N. 45° E. and S. 45° W.
80.84	Intersect the S. bdy. of T. 41 N., R. 2 W., (the Tenth Standard Parallel North)
	Point for the closing cor. of secs. 3 and 4.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	<pre> T41N S34 S 4 S 3 T40N R2W C C 1971 </pre>
	from which
	The Standard cor. of secs. 33 and 34, T. 41 N., R. 2 W., bears West, 1.79 chs. dist., monumented by an iron post, 3 ins. diam., firmly set, projecting 6 ins. above ground and located 2 lks. north of a fence cor. with fences extending S. and W., brass cap mkd.
	<pre> T41N R2W S33 S34 1911 </pre>
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.
	Land, rolling to gently rolling. Soil, sandy and gravelly clay loam. Timber, none. Undergrowth, scattered sagebrush and tumbleweed in N. ½ and moderate sagebrush in S. ½ mile.
	The point for the ¼ sec. cor. on the N. bdy. of sec. 3 is at midpoint bet. the closing cors.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	<pre> ¼ S 3 T40N R2W 1971 </pre>
	from which
	The true point for the standard ¼ sec. cor. of sec. 34, T. 41 N., R. 2 W., bears West, 1.86 chs. dist., from which the remains of the rusted iron pipe, 1 in. diam., with upper portion and brass cap lying alongside, bears north, 20 lks. dist., brass cap mkd.

Survey, Portion of the Subdivisional Lines,
T. 40 N., R. 2 W.

CHAINS

T41N R2W
W C $\frac{1}{4}$ S 34
1911

Raise a mound of earth, 3 ft. base, 2 ft. high, S. of
the cor.

GENERAL DESCRIPTION

The elevation in the east one half of Township 40 North, Range 2 West, ranges from about 4,683 ft. near the northwest corner of section 3 to about 5,340 ft. above sea level near the southeast corner of section 36. The land is mostly gently rolling to rolling with several deep gulches in and near Johnson Wash. The drainage is generally to the west. The soil is a shallow and rocky clay loam in the southern portion and a sandy and gravelly clay loam in the northern portion of the surveyed area. The vegetation consists primarily of sagebrush with scattered yellow top sage and grass.

There is one main bladed road and several track roads throughout the area surveyed. A power line and graded road enters the north boundary of section 3 and leaves the township near the southwest corner of section 13. The primary use for the land is grazing. Water is limited to a catch pond in section 10 and in the Johnson Wash main drainage.

There are no settlers or mining in the surveyed area.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Harry K. Smith	Supervisory Surveying Technician
Michael Woods	Survey Aid
James W. Raleigh, Jr.	Survey Aid
Carter Clark, Jr.	Survey Aid
Carlos Ramirez	Survey Aid

31

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul G. Bauer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 day

of June, 1971, (I) ~~(We)~~ have surveyed a portion of the subdivisional lines in Township 40 North, Range 2 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 10, 1974
(Date)

Paul G. Bauer
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date MAY 30 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the survey of a portion of the subdivisional lines in Township 40 North, Range 2 West, Gila and Salt River Meridian, Arizona.

executed by Paul G. Bauer

having been critically examined and found correct, are hereby approved.

MAR 27 1975
(Date)

Bernard M. DeLoach
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 - 626