

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

RETRACEMENT,

Portion of the South Boundary,

Township 5 North, Range 28 East

and

DEPENDENT RESURVEY

of the

Boundaries

and

SURVEY

of

Subdivisions

of

Sections 3 and 10

Township 4 North, Range 28 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Boyd S. Owens

Cadastral Surveyor

Under special instructions dated September 7, 19 71, approved September 8, 1971,

_____ , which provided for the surveys included under U.S. Survey/Group
Number 539 , and assignment instructions dated September 13 , 19 71 .

October 12 , 1971

Survey commenced October 5 , 19 71

Survey completed July 10 , 19 72

1A

BOOK 5001

INDEX DIAGRAM

Township 4 North, Range 28 East
 3 2 1

6	5	4 12	3	10 2	1
7	8	9 7	9	4 11	12
18	17	16	6	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Sec. 3 - - - - - page 17
 Subdivision of Sec. 10 - - - - - page 15

Township 4 North, Range 28 East
Gila and Salt River Meridian, Arizona

CHAINS

The boundaries and subdivisional lines were surveyed in 1883 by W. R. Fitzgerald.

A portion of the north boundary and a portion of the subdivisional lines were resurveyed in 1914-16 by C. A. Long and R.P.A. Johnson.

The north boundary, (the First Standard Parallel North) through Range 28 East was resurveyed in 1940 by Ty White, Claude F. Warner and Frank Motosh.

H.E.S. No. 245 was surveyed in 1914 by C. A. Long and R.P.A. Johnson.

H.E.S. No. 603 was surveyed in 1921 by Thomas F. Myers. Both H.E.S. No. 245 and H.E.S. No. 603 were retraced and remonumented by the U.S. Forest Service in 1968.

The following notes are those of a retracement of a portion of the south boundary of Township 5 North, Range 28 East, (the First Standard Parallel North), and a dependent resurvey of the boundaries and the survey of subdivisions of Section 3 and 10, Township 4 North, Range 28 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the Specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated September 7, 1971.

The direction of all lines were determined by solar observation and all lines refer to the true meridian.

Only the true line bearings and horizontal distances for the surveyed lines are given in these notes.

The geographic position of the southeast corner of section 10, as determined by scaling from a 1958 advance copy of a U.S.G.S. Quadrangle "Nutrioso 3 NW., Arizona", scale 1:24,000 is: Latitude 33°44'56" North and Longitude 109°22'43" West.

The mean magnetic declination was found to be: 13° East.

Retracement, Portion of the South Boundary
Township 5 North, Range 28 East

Retracement of the survey executed by
Ty White, Claude F. Warner and Frank Motosh in 1940

Beginning at the Standard $\frac{1}{4}$ sec. cor. of sec. 34, Township 5 North, Range 28 East, monumented by an iron post 1 in. diam., firmly set, projecting 14 ins. above ground, brass cap mkd.

S C
 $\frac{1}{4}$ S 34
1940

from which

Retracement, Portion of the South Boundary
Township 5 North, Range 28 East

CHAINS	
	<p>An original bearing tree: A pine, 16 ins. diam., bears N. 12° W., 61 lks. dist., mkd. SC ¼ BT (Partially overgrown)</p> <p>A bearing tree established in 1940: A pine, 8 ins. diam., bears N. 35° E., 23 lks. dist., mkd. SC ¼ S34 BT.</p> <p>N. 89°54' W., along the S. bdy. of sec. 34.</p> <p>Over rolling land, asc. E. slope.</p> <p>2.70 E. edge of flat ridge, bears S. and NW.</p> <p>13.30 Leave ridge, bears S. and NW., desc. W. slope.</p> <p>14.13 Fence bears S. 25° E. and N. 25° W.</p> <p>14.62 The orig. closing cor. of secs. 2 and 3, T. 4 N., R. 28 E., bears N. 1°56' W., 44 lks. dist., hereinafter described.</p> <p>34.70 Home Creek, 25 lks. wide, with running water, flows irreg. S.</p> <p>39.90 The standard cor. of secs. 33 and 34; a pine 14 ins. diam., with partially overgrown blaze on N. face, mkd. T5N R28E S34 and with overgrown blaze on E. and W. faces, from which</p> <p>The original bearing trees:</p> <p>A pine, 19 ins. diam., bears N. 20° E., 54 lks. dist., mkd. T5N R28E S34 SC BT.</p> <p>A pine, 13 ins. diam., bears N. 16½° W., 33 lks. dist., mkd. T5N R28E S33 SC BT.</p> <p>Land, mountainous. Soil, dark, rocky clay loam. Timber, pine, fir and spruce. Undergrowth, small pine and some grass.</p>
0.10	<p>N. 89°57' W., along the S. bdy. of sec. 33.</p> <p>Over rolling land, through dense timber, asc. E. slope.</p> <p>The witness standard cor. of secs. 33 and 34, monumented by an iron post, 2 ins. diam., firmly set, projecting 10 ins. above ground, brass cap mkd.</p> <p style="text-align: center;">S C T5N R28E S33 S34 WC 1940</p> <p>From which bearing trees established in 1940:</p>

Retracement, Portion of the South Boundary,
Township 5 North, Range 28 East

CHAINS	
	<p>A pine, 13 ins. diam., bears N. $45\frac{1}{2}^{\circ}$ E., 119 lks. dist., mkd. WC T5N R28E S34 SC BT.</p> <p>A pine, 17 ins. diam., bears N. $42\frac{3}{4}^{\circ}$ W., 17 lks. dist., mkd. WC T5N R28E S33 SC BT.</p>
12.40	End of E. slope, bears irreg. NE. and SW., thence over gently rolling land.
24.50	Old logging road, bears irreg. N. and S.
35.40	Leave timber, enter seneca, bears irreg. N. and S.
37.50	Abandoned fenceline, bears irreg. N. and S.
38.70	Leave seneca, bears irreg. N. and S., enter timber.
39.90	<p>The standard $\frac{1}{4}$ sec. cor. of sec. 33, monumented by an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, and in a mound of stone, $1\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">S C $\frac{1}{4}$ S33 1940</p> <p>from which bearing trees altered in 1940:</p> <p>A pine, 13 ins. diam., bears N. $29\frac{3}{4}^{\circ}$ W., 141 lks. dist., mkd. $\frac{1}{4}$ S33 SC BT.</p> <p>A pine, 17 ins. diam., bears N. 56° W., 115 lks. dist., mkd. $\frac{1}{4}$ S33 SC BT.</p> <hr/> <p>N, $89^{\circ}45'$ W., beginning new measurement.</p>
8.70	Track road, bears S. 10° E. and N. 10° W.
14.47	The closing cor. of secs. 3 and 4, T. 4 N., R. 28 E., hereinafter described
40.14	<p>The standard cor. of secs. 32 and 33, monumented by an iron post, 2 ins. diam., firmly set, projecting 8 ins. above ground, brass cap mkd.</p> <p style="text-align: center;">S C T5N R28E S32 S33 1940</p> <p>from which the original bearing trees:</p> <p>A pine, 18 ins. diam., bears N. 48° E., 27 lks. dist., no marks visible.</p> <p>A pine, 24 ins. diam., bears N. $12\frac{1}{2}^{\circ}$ W., 10 lks. dist., no marks visible.</p> <p>Land, rolling. Soil, dark, rocky clay loam. Timber, yellow pine, fir and spruce. Undergrowth, grass in open areas.</p> <hr/>

Dependent Resurvey, Portion Subdivisional Lines,
Township 4 North, Range 28 East

CHAINS

Dependent Resurvey, Portion Subdivisional Lines,
Township 4 North, Range 28 East

Reestablishment of the survey executed by
W. R. Fitzgerald in 1883

Beginning at the cor. of secs. 10, 11, 14 and 15, monumented by a pine, 14 ins. diam., with partially healed blazes on N., E., S. and W. faces, from which the orig. bearing trees:

A pine, 11 ins. diam., with an open blaze, bears N. 45° W., 5 lks. dist., mkd. T4N R28E S10 BT.

A pine, 18 ins. diam., bears S. 45° E., 33 lks. dist., with an open blaze, no marks visible.

New reference monuments:

An iron post, 30 ins. long, 2½ ins. diam., set 16 ins. in the ground, for a reference monument, bears N. 45° E., 49 lks. dist., with brass cap mkd. T4N R28E S11 RM 32.4 ft. 1971 and an arrow pointing to the cor.

An iron post, 30 ins. long, 2½ ins. diam., set 16 ins. in the ground, for a reference monument, bears S. 45° E., 49 lks. dist., with brass cap mkd. T4N R28E S14 RM 32.4 ft. 1971 and an arrow pointing to the cor.

N. 0°03' E., bet. secs. 10 and 11.

Over rolling land, through moderate timber.

2.10 Enter seneca, bears E. and N. 75° W.

8.70 Leave seneca, enter timber, bears irreg. E. and W.

35.70 Rim, bears S. 80° E. and N. 80° W., desc. N. slope.

40.21 Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist., there is no remaining evidence of the orig. cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.

T4N R28E
¼
S10|S11
1971

from which

A pine, 8 ins. diam., bears N. 36 ¾° E., 101 lks. dist., mkd. T4N R28E ¼ S11 BT.

A pine, 11 ins. diam., bears N. 20° W., 64 lks. dist., mkd. T4N R28E ¼ S10 BT.

Raise a mound of stone 2½ ft. base, 2 ft. high, W. of the cor.

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
41.60	Leave timber, bears E. and N. 75° W., enter open grass-land.
42.60	Old bladed road, bears S. 75° E. and N. 75° W.
44.80	Abandoned F.S. telephone line, bears S. 75° E. and N. 75° W.
55.60	New graded road, bears N. 40° E., curving east and N. 60° W.
60.315	Point for the N 1/16 sec. cor. of secs. 10 and 11, at proportionate dist.
	Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, mound of stone to top, brass cap mkd.
	<p style="text-align: center;">T4N R28E N 1/16 S10 S11 1971</p>
	from which
	<p style="text-align: center;">A 2 in. iron post, firmly set, projecting 20 ins. above ground, bears S. 83°26' W., 3.035 chs. dist., metal cap mkd. JOHN H. PAGE LAND CO., PHOENIX.</p>
	<p style="text-align: center;">The iron post is located at a cor. of fences extending N. and W.</p>
68.50	Abandoned track road, bears S. 15° E. and N. 15° W.
68.60	South channel of West Fork of Black River, 25 lks. wide, 1 ft. deep, course E.
69.40	North channel of West Fork of Black River, 35 lks. wide, 1 ft. deep, course E., curving SE.
71.60	Fence, bears S. 54° E. and N. 54° W.
75.00	Old bladed road, bears E. and W.
80.42	<p>The cor. of secs. 2, 3, 10 and 11, monumented by a basalt stone, 18x12x4 ins. diam., marked with 5 notches on one edge, and 2 notches on opposite edge, found 6 ins. under the surface of the ground, from which the remains of an original bearing tree:</p>
	<p style="text-align: center;">A rotted pine stump, 18 ins. diam., with a re-bar in the center, bears N. 31°25' W., 28 lks. dist., (record N. 30° W.) There is no visible signs of the other orig. bearing tree.</p>
	At the cor. point
	<p>Set an iron post 30 ins. long, 2½ ins. diam., 13 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;">T4N R28E S 3 S 2 S10 S11 1971</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
	<p>from which</p> <p>An iron pipe, 2 ins. diam., projecting 12 ins. above ground, bears S. 77°24' W., 2.50 chs. dist., metal cap mkd. JOHN H PAGE LAND CO. NE. CORNER, PHOENIX. This iron pipe is located in a cor. of fences extending northerly and westerly.</p> <p>two bearing trees, origin unknown</p> <p>A pine, 18 ins. diam., bears N. 12°57' W., 411 lks. dist., with a partially healed blaze mkd. T4N R28E S2 BT.</p> <p>A pine, 16 ins. diam., bears N. 8°58' W., 405 lks. dist., with a partially healed blaze mkd. T4N R28E S2 BT.</p> <p>and new bearing trees</p> <p>A pine, 6 ins. diam., bears N. 53¼° E., 61 lks. dist., mkd. T4N R28E S2 BT.</p> <p>A pine, 8 ins. diam., bears S. 80 3/4° E., 38 lks. dist., mkd. T4N R28E S11 BT.</p> <p>The northeast corner of the old P. S. Cabin, 32 ft. square, oriented N-S-E-W, bears S. 66°02' W., 4.32 chs. dist.</p> <p>Land, rolling. Soil, dark, rocky clay loam. Timber, moderate to dense pine in S. ½ mile. Undergrowth, grass in N. ½ mile.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°47' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through moderate to dense timber.</p>
10.00	Old logging road, bears NE. and SW.
14.30	Leave timber, bears N. 30° E. and S. 10° W., enter seneca.
19.50	Leave seneca, bears S. 10° E. and N. 30° W., enter thick timber.
33.56	Fence, bears S. 40°10' E. and N. 40°10' W.
39.64	Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the orig. cor.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, mound of stone, 3½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E ¼ $\frac{S10}{S15}$ 1971</p>
	<p>from which</p> <p>A pine, 10 ins. diam., bears S. 64° W., 16 lks. dist., mkd. T4N R28E ¼ S15 BT.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
	<p>A pine, 8 ins. diam., bears N. 22¼° W., 25 lks. dist., mkd. T4N R28E ¼ S10 BT.</p> <p>The cor. is located 190 lks. S. of an old logging road bearing N. 80° E. and S. 80° W.</p>
55.00	Old logging road, bears N. 60° E., curving E. and S. 60° W., curving S.
60.90	Old logging road, bears N., curving NW. and S., curving SE.
76.63	Fence, bears N. 64°30' E. and S. 64°30' W.
79.28	<p>The cor. of secs. 9, 10, 15 and 16, monumented by a basalt stone, 11x11x8 ins. diam., (record size) found 6 ins. below the surface of the ground, no visible markings.</p> <p>from which the original bearing trees:</p> <p>A pine, 16 ins. diam., with partially healed blaze bears N. 1¼° E., 38 lks. dist., with visible markings of: R28E S10 (Record calls for N. 20° E., 38 lks. and mkd. T4N R28E S10 BT.)</p> <p>A pine, 20 ins. diam., with partially healed blaze, bears S. 20 3/4° E., 36 lks. dist., visible markings of: R28E S15 (Record calls for S. 15° E., 36 lks. and mkd. T4N R28E S15 BT.)</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;"> T4N R28E S 9 S10 S16 S15 1971 </p> <p>from which new bearing trees:</p> <p>A pine, 10 ins. diam., bears S. 44° W., 43½ lks. dist., mkd. T4N R28E S16 BT.</p> <p>A pine, 14 ins. diam., bears N. 27½° W., 45½ lks. dist., mkd. T4N R28E S9 BT.</p> <p>Bury the record size cor. stone alongside the iron post.</p> <p>Land, rolling. Soil, dark and rocky clay loam. Timber, pine and scattered fir. Undergrowth, grass.</p>
	<p>N. 0°12' E., bet. secs. 9 and 10.</p> <p>Over rolling land, through dense timber.</p>
15.80	Small rocky spur, slopes SE.
18.10	Fence, bears S. 55° E. and N. 55° W.
24.30	Draw, drains E.
32.20	Draw, drains E.

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

<p>CHAINS 39.88</p>	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R28E $\frac{1}{4}$ S 9 S10 1971</p> <p>from which</p> <p>A white fir, 5 ins. diam., bears N. $51\frac{1}{2}^\circ$ E., $10\frac{1}{2}$ lks. dist., mkd. T4N R28E $\frac{1}{4}$ S10 BT.</p> <p>A white fir, 4 ins. diam., bears S. $43\frac{3}{4}^\circ$ W., $34\frac{1}{2}$ lks. dist., mkd. T4N R28E $\frac{1}{4}$ S9 BT.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>
<p>42.10</p>	<p>Old logging road, bears E. and W.</p>
<p>59.82</p>	<p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 9 and 10, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R28E N $\frac{1}{16}$ S 9 S10 1971</p> <p>from which</p> <p>A pine, 12 ins. diam., bears N. $33\frac{3}{4}^\circ$ E., 43 lks. dist., mkd. T4N R28E N $\frac{1}{16}$ S10 BT.</p> <p>A pine, 8 ins. diam., bears S. 54° W., 30 lks. dist., mkd. T4N R28E N $\frac{1}{16}$ S9 BT.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>
<p>62.59</p>	<p>Fence, bears E. and W.</p>
<p>79.76</p>	<p>The cor. of secs. 3, 4, 9 and 10, (restored in 1916 by R.P.A. Johnson, U.S.F.S. Surveyor-Draftsman under Special Instructions dated June 23, 1916), monumented by lava stone, $28 \times 16 \times 5$ ins. diam., mkd. with 5 notches on S. edge and 3 notches on E. edge under which I find a lava stone, $6 \times 4 \times 3$ ins. diam., mkd. with an X.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, $1\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E S 4 S 3 S 9 S10 1971</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
	<p>from which</p> <p>A yellow pine, 29 ins. diam., bears S. $4\frac{1}{2}^{\circ}$ E., 28 lks. dist., with partially overgrown blaze mkd. N. 28E S10 (original BT as found in 1916 - yellow pine, 24 ins. diam., S. 2° E., 28 lks. dist.)</p> <p>A yellow pine, 15 ins. diam., bears S. 35° W., 110 lks. dist., with overgrown blaze (BT as established in 1916 - yellow pine, 4 ins. diam., S. $35\frac{1}{4}^{\circ}$ W., 111 lks. dist.)</p> <p>A yellow pine, 30 ins. diam., bears N. $49\frac{1}{4}^{\circ}$ W., 74 lks. dist., with partially overgrown blaze mkd. 4N R28E S4 BT.</p> <p>Bury both cor. stones alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Land, rolling. Soil, dark and rocky clay loam. Timber, pine, scattered fir. Undergrowth, grass.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. $89^{\circ}19'$ W., bet. secs. 3 and 10.</p> <p>Over nearly level open land.</p>
2.43	Fence, bears irreg. N. and S. 52 lks. to a cor. of fences extending irreg. N. and W.
6.20	East fork of Home Creek, 20 lks. wide, 1 ft. deep, flows S.
7.20	West fork of Home Creek, 10 lks. wide, 1 ft. deep, flows irreg. S.
9.885	Point for the E-E $1/64$ sec. cor. of secs. 3 and 10, at proportionate dist.; not monumented.
11.60	Fence bears S. $88^{\circ}05'$ E. and N. $88^{\circ}05'$ W.
19.77	Point for the E. $1/16$ sec. cor. of secs. 3 and 10, at proportionate dist.; not monumented.
22.80	Fence, bears S. $89^{\circ}33'$ E. and N. $89^{\circ}33'$ W.
39.54	Point for the $1/4$ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the orig. cor.
	<p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 17 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E $\frac{1}{4}$ $\frac{S 3}{S10}$ 1971</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
	<p>from which</p> <p>A section of steel fence post, projecting 20 ins. above ground, with an unmarked 2 in. square metal plate welded on top, bears S. 80°10' W., 124 lks. dist.</p>
39.80	Enter small willows, bears irreg. N. and S.
40.80	Leave small willows, bears irreg. N. and S.
41.70	West fork of Black River, 25 lks. wide, 2 ft. deep, course S. 10° E. for 90 lks., thence easterly.
63.50	Fence, bears N. and S.
76.60	Leave nearly level open grassland, bears S. 10° E. and N. 15° W.
77.40	Irrigation ditch, 10 lks. wide, 1½ ft. deep, drains S.
78.07	Graded road, bears S. curving southeasterly and N. curving northwesterly.
79.08	<p>The cor. of secs. 3, 4, 9 and 10.</p> <p>Land, nearly level. Soil, dark and gravelly clay loam. Timber, none. Undergrowth, grass and small willows in patches along West Fork of Black River.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 1°56' W., bet. secs. 2 and 3.</p> <p>Over rolling land, along W. edge of timber line, bears irreg. N. and S.</p>
4.80	Enter moderate to dense pine timber, bears SE. and W.
10.135	<p>Point for the S-S 1/64 sec. cor. of secs. 2 and 3, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E S S 1/64 S 3 S 2 1971</p>
	<p>from which</p> <p>A pine, 14 ins. diam., bears N. 17½° W., 42½ lks. dist., mkd. S-S 1/64 S3 BT.</p> <p>A pine, 12 ins. diam., bears N. 84° E., 38 lks. dist., mkd. S-S 1/64 S2 BT.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
20.27	<p>Point for the S 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R28E S 1/16 S 3 S 2 1971</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears N. 77½° W., 26 lks. dist., mkd. S 1/16 S3 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 16½° E., 21 lks. dist., mkd. S 1/16 S2 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
40.54	<p>Point for the ¼ sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R28E ¼ S 3 S 2 1971</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 29° E., 50 lks. dist., mkd. T4N R28E ¼ S2 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 19° W., 20½ lks. dist., mkd. T4N R28E ¼ S3 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>
50.675	<p>Point for the S-N 1/64 sec. cor. of secs. 2 and 3 at proportionate dist.; not monumented.</p>
60.81	<p>Point for the N 1/16 sec. cor. of secs. 2 and 3, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E N 1/16 S 3 S 2 1971</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 22° E., 69 lks. dist., mkd. T4N R28E N 1/16 S2 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 50° W., 14 lks. dist., mkd. T4N R28E N 1/16 S3 BT.</p>


Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	<p>80.81 Intersect the First Standard Parallel North.</p> <p>Point for the closing cor. of secs. 2 and 3.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.</p> <div style="text-align: center; border: 1px solid black; padding: 5px; margin: 10px auto; width: fit-content;"> <p>S 3 S 2 T4N R28E C C 1971</p> </div> <p>from which</p> <p>The standard ¼ sec. cor. of Sec. 34, T. 5 N., R. 28 E., bears S. 89°54' E., 14.62 chs. dist., hereinbefore described.</p> <p>A new bearing tree, a fir, 9 ins. diam., bears S. 55½° E., 80 lks. dist., mkd. T4N R28E S2 CC BT.</p> <p>A new bearing tree, a pine, 9 ins. diam., bears S. 26½° W., 114 lks. dist., mkd. T4N R28E S3 CC BT.</p> <p>The original closing cor. of Secs. 2 and 3, bears N. 1°56' W., 44 lks. dist., monumented by a basalt stone, 24 x 24 x 14 ins., firmly set in a mound of stone, projecting 16 ins. above ground, marked with 2 notches on E., CC on S. and 4 notches on W. faces. (I mark this stone A M and bury it in place.)</p> <p>From the original closing cor. (A M)</p> <p>An original bearing tree, a pine 18 ins. diam., bears S. 87° E., 15 lks. dist., mkd. with a partially healed blaze. (Record: S. 40° W., 55 lks. dist.).</p> <p>An original bearing tree, a pine 18 ins. diam., bears S. 15° E., 37.5 lks. dist., mkd. with an overgrown blaze (Record: S. 15° E., 25 lks. dist.).</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the iron post.</p> <p>The cor. is located on a N. slope and 49 lks. W. of a fence, bearing S. 25° E. and N. 25° W.</p> <p>Land, rolling. Soil, dark, shallow and rocky clay loam. Timber, moderate to dense pine, scattered fir. Undergrowth, grass.</p>
2.05	<p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 2°15' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land, through scattered timber.</p> <p>Graded road, bears S. 15° E. and N. 25° W.</p>
4.50	<p>Enter open grass-land, bears S. 70° E. and N. 50° W.</p>
8.10	<p>Track road, bears S. 15° E. and N. 10° W.</p>
8.50	<p>Irrigation ditch, 10 lks. wide, 1½ ft. deep, drains S. 15° E.</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
9.985	The NW. cor. of a wooden house, 26.4 ft. by 31 ft. in size, with the long sides bearing east and west, bears east, 6 lks. dist.
11.415	The NW. cor. of a wooden house, 26.4 ft. by 31 ft. in size, with the long sides bearing east and west, bears east, 5 lks. dist.
12.985	The NW. cor. of a wooden house, 26.4 ft. by 31 ft. in size with the long sides bearing east and west, bears east, 7 lks. dist.
16.285	Fence, bears S. 49°45' E. and N. 49°45' W.
20.37	Point for the S 1/16 sec. cor. of secs. 3 and 4, at proportionate dist.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.
	<p style="text-align: center;">T4N R28E S 1/16 S 4 S 3 1971</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
21.80	Enter scattered willows.
23.065	Corner No. 3 of H.E.S. 245, reestablished in 1968 by Gordon H. Long, U.S.F.S. Cadastral Surveyor, monumented by an iron post, 2½ ins. diam., projecting 4 ins. above ground, brass cap mkd.
	<p style="text-align: center;">HES 245 C C 3 ----- T4N R28E S4 S3 LS 6713 1968</p>
	The cor. is located in a fence bearing irreg. E. and W.
	Enter open grass-land, bears E. and W.
25.50	West Fork Black River, 30 lks. wide, water 2 ft. deep, and with 4 ft. banks, course S. 30° E., curving easterly.
25.90	Enter scattered willows, bears SE. and NW.
29.60	Enter open grass-land, bears E. and NW.
34.10	Base of slope, bears S. 60° E. and N. 60° W., asc. over SW. slope through timber.

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS	
34.385	<p>Corner No. 1 of H.E.S. 245, reestablished in 1968 by Gordon H. Long, U.S.F.S. Cadastral Surveyor, monumented by an iron post, 2½ ins. diam., firmly set in a collar of stone and projecting 6 ins. above ground, brass cap mkd.</p>
	<div style="text-align: center;"> <p>T4N R28E S 4 S 3</p>  <p>HES 245 LS6713 1968</p> </div> <p>A mound of stone, 3 ft. base, 2½ ft. high, is along the SW side of the iron post.</p>
40.74	<p>The ¼ sec. cor. of secs. 3 and 4, reestablished in 1914 by C. A. Long, U.S.F.S. Surveyor, monumented by a lava stone, 24x18x8 ins., mkd. ¼ on W. face, firmly set in a mound of stone, 3 ft. base, 1 ft. high.</p> <p>from which</p> <p>A yellow pine, 20 ins. diam., with an overgrown blaze, bears S. 17°41' E., 115 lks. dist.</p> <p>A yellow pine, 12 ins. diam., with an overgrown blaze, bears S. 25°50' W., 89 lks. dist.</p> <p>A yellow pine, 26 ins. diam., with a partially overgrown blaze, bears S. 89°30' W., 88 lks. dist., dim scribe mks. not legible.</p> <p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., over an X chiseled on solid rock, mound of stone, 4 ft. base to top, brass cap mkd.</p> <div style="text-align: center;"> <p>T4N R28E ¼ S 4 S 3 1971</p> </div> <p>Deposit the orig. cor. stone in the mound of stone surrounding the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 2°18' W., beginning new measurement.</p> <p>Over rolling land, through moderate to dense timber.</p>
8.65	<p>A cor. of fences bears East, 35 lks. dist., fences extend N., S. and W.</p>
41.16	<p>The closing cor. of secs. 3 and 4, on the First Standard Parallel North, reestablished in 1914 by C. A. Long, U.S. F.S. Surveyor, monumented by a lava stone, 24x11x10 ins., firmly set in a mound of stone, projecting 10 ins. above ground, mkd. with 3 notches on E., CC on S. and 3 notches on W. faces.</p> <p>At the cor. point</p>

Dependent Resurvey, Portion Subdivisional Lines,
T. 4 N., R. 28 E.

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, brass cap mkd.

S 4	S 3
T4N	R28E
C	C
1971	

from which the remains of the bearing trees established in 1914 by C. A. Long, U.S.F.S. Surveyor.

A pine, 34 ins. diam., with partially overgrown blaze, bears S. 43°10' E., 28½ lks. dist., mkd. T4N R28E S3 BT.

The stump hole of a pine, uprooted and dead, bears S. 69°22' W., 30 lks. dist., open blaze on tree mkd. T4N R28E S4 BT.

A new bearing tree, a pine, 11 ins. diam., bears S. 1½° W., 78 lks. dist., mkd. T4N R28E S4 CC BT.

The standard sec. cor. of sec. 32 and 33, T. 4 N., R. 28 E., bears N. 89°45' W., 25.67 chs. dist., previously described.

Bury the orig. cor. stone alongside the iron post in the mound of stone.

Land, rolling.

Soil, dark and rocky clay loam.

Timber, moderate to dense pine and scattered fir in northern portion.

Undergrowth, grass in open areas and patches of small willows along West Fork of Black River.

Subdivision of Sec. 10, T. 4 N., R. 28 E.

From the ¼ sec. cor. of secs. 10 and 15.

N. 0°08' E., along the N. and S. centerline of section 10.

Over gently rolling land, through moderate timber.

1.90 Old logging road, bears N. 80° E. and S. 80° W.

6.70 Fence, bears S. 40°10' E. and N. 40°10' W.

19.80 Old logging road, bears W. and E. curving SE.

22.30 Rim bears N. 35° E. and irreg. W., desc. N. slope.

30.40 Fence, bears irreg. E. and W.

31.40 Small creek, 10 lks. wide, 1 ft. deep, course N. 70° E.

31.70 Old logging road, parallels creek.

37.60 Spur, slopes E.

Survey, Subdivision of Section 10, T. 4 N., R. 28 E.

CHAINS	
40.08	<p>Point for the C $\frac{1}{4}$ sec. cor. of sec. 10 at intersection with the E. and W. centerline of sec. 10.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E C C $\frac{1}{4}$ S10 C 1971</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. $32\frac{3}{4}^{\circ}$ W., 48 lks. dist., mkd. T4N R28E C $\frac{1}{4}$ S10 BT.</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. $86\frac{1}{4}^{\circ}$ W., $97\frac{1}{2}$ lks. dist., mkd. C $\frac{1}{4}$ S10 BT.</p>
48.60	Graded road, bears S. 55° E. and N. 55° W.
53.10	Leave timber area, bears irreg. E. and W., enter open grass-land.
60.11	Fence, bears irreg. E. and W.
60.135	<p>Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, collar of stone, $2\frac{1}{2}$ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E C N $\frac{1}{16}$ S10 C 1971</p>
79.00	West Fork of Black River, 50 lks. wide, 3 ft. deep, course S. 80° E.
80.19	<p>The $\frac{1}{4}$ sec. cor. of secs. 3 and 10.</p> <p>Land, rolling to nearly level. Soil, shallow dark clay loam. Timber, moderate pine in south 53.00 chains. Undergrowth, scattered grass in timber area, open grass-land in north 27.00 chains.</p>
15.70	<p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>S. $89^{\circ}35'$ W., on the E. and W. centerline of sec. 10.</p> <p>Over rolling land, through dense timber.</p>
21.10	Fence, bears irreg. NE. and SW.
28.80	Leave timber, bears NE. and SW., enter seneca.
28.80	Wash, 15 lks. wide, 4 ft. banks, 1 ft. water, course N. 15° E.

Survey, Subdivision of Section 10, T. 4 N., R. 28 E.

CHAINS	
30.30	Leave seneca, bears N. and S., enter dense timber.
39.60	The C $\frac{1}{4}$ sec. cor. of sec. 10.
44.10	Ridge, bears SE. and NW.
79.20	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.
	<p>Land, rolling. Soil, shallow dark clay loam. Timber, dense pine. Undergrowth, scattered grass in timber area, moderate grass in seneca.</p>
Subdivision of Sec. 3, T. 4 N., R. 28 E.	
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	N. 2°08' W., along the N. and S. centerline of sec. 3.
	Over gently rolling land, through scattered small willows.
1.03	Fence, bears S. 89°05' E. and N. 89°05' W.
7.10	Leave willows, enter open grass lands, bears E. and W.
12.20	Junction of track roads extending S. 70° E., S. 80° W. curving S. and N. 35° W. curving NE.
19.90	Track road, bears NE. and SW.
20.31	Point for the C-S $\frac{1}{16}$ sec. cor. of sec. 3.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.
	<p>T4N R28E C S $\frac{1}{16}$ S 3 C 1971</p>
	from which
	<p>A ponderosa pine, 16 ins. diam., bears N. 69° W., 217 lks. dist., mkd. T4N R28E CS $\frac{1}{16}$ S3 BT.</p>
	<p>A ponderosa pine, 28 ins. diam., bears N. 10°25' W., 28.2 lks. dist., mkd. T4N R28E CS $\frac{1}{16}$ S3 BT.</p>
	<p>The SW. cor. of a cabin, 18½ x 16 ft. in size, bears N. 31° E., 194 lks. dist., with the long sides bearing N. 17° E. and S. 17° W.</p>

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS

The SW. cor. of a cabin, $33\frac{1}{2}$ x 43 ft. in size, bears N. $78^{\circ}07'$ E., 189 lks. dist., with the long sides bearing N. $8\frac{3}{4}^{\circ}$ E. and S. $8\frac{3}{4}^{\circ}$ W.

The NE. cor. of log barn, 31 x 26 ft. in size, bears S. $63^{\circ}05'$ W., 200 lks. dist., with the long sides bearing East and West.

- 23.66 Corral fence, bears E. and W.
- 24.67 Corral fence, bears E. and W., enter pine timber, bears NE. and SW.
- 25.387 Point for the C-S-N-S $1/256$ sec. cor. of sec. 3; not monumented.
- 26.00 Begin asc. over S. slope.
- 30.465 Point for the C-N-S $1/64$ sec. cor. of sec. 3; not monumented.
- 40.62 Point for the C $\frac{1}{4}$ sec. cor. of sec. 3, at the intersection with the E. and W. centerline of sec. 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, in a collar of stone, brass cap mkd.

T4N R28E

C

$\frac{1}{4}$ |S 3

C

1971

from which

A pine, 15 ins. diam., bears S. 84° E., 47 lks. dist., mkd. T4N R28E C $\frac{1}{4}$ S3 BT.

A pine, 6 ins. diam., bears S. 68° W., 79 lks. dist., mkd. T4N R28E C $\frac{1}{4}$ S3 BT.

- 43.70 Top of ascent, thence over gently rolling land.
- 60.82 Point for the C-N $1/16$ sec. cor. of sec. 3.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, brass cap mkd.

T4N R28E

C

N $1/16$ |S 3

C

1971

from which

A pine, 8 ins. diam., bears S. 51° W., 51 lks. dist., mkd. CN $1/16$ S3 BT.

A pine, 8 ins. diam., bears S. 84° W., 49 lks. dist., mkd. CN $1/16$ S3 BT.

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the cor.</p>
72.95	<p>Track road, bears E. and W.</p>
81.37	<p>Intersect the First Standard Parallel North.</p>
	<p>Point for the ¼ sec. cor. of sec. 3 only, on the north bdy. of the Tp., at midpoint between the closing cors.</p>
	<p>Set an iron post, 30 ins. long, 2½ in. diam., 20 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;"> $\frac{1}{4}$ S 3 T4N R28E 1971 </p>
	<p>from which</p>
	<p>A pine, 5 ins. diam., bears S. 56°20' E., 14 lks. dist., mkd. T4N R28E ¼ S3 BT.</p>
	<p>A pine, 5 ins. diam., bears S. 53¼° W., 40 lks. dist., mkd. T4N R28E ¼ S3 BT.</p>
	<p>The true standard cor. of secs. 33 and 34, a tree, (witnessed 10 lks. N. 89°57' W.), bears S. 89°57' E., 14.54 chs. dist.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.</p>
	<p>Land, gently rolling to rolling. Soil, dark rocky clay loam. Timber, ponderosa pine. Undergrowth, scattered willows along W. Fork of Black River and moderate grass.</p>
	<p>From the ¼ sec. cor. of secs. 2 and 3.</p>
	<p>S. 89°25'30" W., along the E. and W. centerline of sec. 3.</p>
	<p>Desc. W. slope through moderate pine timber.</p>
4.965	<p>Point for the C-E-E-E 1/256 sec. cor. of sec. 3.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.</p>
	<p style="text-align: center;"> T4N R28E <u>C E E E 1/256</u> S 3 1971 </p>
	<p>from which</p>
	<p>A pine, 9 ins. diam., bears N. 18° E., 51 lks. dist., mkd. C E E E 1/256 S3 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
9.10	Fence, bears S. 37°30' E. and N. 37°30' W., leave timber area, bears same as fence, thence over gently rolling grass land.
9.930	Point for the C-E-E 1/64 sec. cor. of sec. 3. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, brass cap mkd.
	<p>T4N R28E C E E 1/64 S 3 1971</p>
	from which A pine, 12 ins. diam., bears N. 1° W., 22 lks. dist., mkd. CEE 1/64 S3 BT. Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
13.40	Home Creek, (dry), 15 lks. wide, with 2½ ft. banks, drains irreg. S.
14.895	Point for the C-W-E-E 1/256 sec. cor. of sec. 3. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.
	<p>T4N R28E C W E E 1/256 C S 3 1971</p>
19.86	Point for the C-E 1/16 sec. cor. of sec. 3. Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.
	<p>T4N R28E C E 1/16 C S 3 1971</p>
24.825	Point for the C-E-W-E 1/256 sec. cor. of sec. 3. Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.
	<p>T4N R28E C E W E 1/256 S 3 1971</p>
	from which A pine, 10 ins. diam., bears N. 42°40' W., 223 lks. dist., mkd. CEWE 1/256 S3 BT. A pine, 5 ins. diam., bears N. 15° W., 158 lks. dist., mkd. CEWE 1/256 S3 BT. Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
27.20	Leave open grassland, enter pine timber, bears S. 80° E. and SW.
27.80	Track road, bears N. 30° E. and S. 30° W.
29.33	Fence, bears N. 10° E. and S. 10° W.
29.79	Point for the C-W-E 1/64 sec. cor. of sec. 3; not monumented.
39.72	The C ¼ sec. cor. of sec. 3.
76.95	Fence, bears S. 38° E. and N. 38° W.
79.37	The ¼ sec. cor. of secs. 3 and 4. Land, rolling. Soil, dark, rocky clay loam. Timber, ponderosa pine. Undergrowth, moderate grass.
From the point for the E 1/16 sec. cor. of secs. 3 and 10.	
N. 2°02' W., along the N. and S. centerline of the SE¼ of sec. 3.	
Asc. over gently rolling land.	
0.47	Fence, bears S. 88°35' E. and N. 88°35' W.
1.80	Abandoned track road, parallels fence.
8.17	Bladed road, bears S. 65° E. and N. 65° W.
10.15	Point for the C-S-SE 1/64 sec. cor. of sec. 3; not monumented.
20.30	Point for the SE 1/16 sec. cor. of sec. 3 at intersection with the E. and W. centerline of the SE¼ of sec. 3; not monumented.
26.28	Fence, bears irreg. E. and W.
30.445	Point for the C-N-SE 1/64 sec. cor. of sec. 3; not monumented.
40.59	The C-E 1/16 sec. cor. of sec. 3.
From the S 1/16 sec. cor. of secs. 2 and 3.	
S. 89°22' W., along the E. and W. centerline of the SE¼ of sec. 3.	
Over nearly level land, through moderate timber.	

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
4.950	<p>Point for the C-E-E-SE 1/256 sec. cor. of sec. 3.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R28E C E E SE 1/256 + S 3 1971</p> <p>from which</p> <p>A pine, 8 ins. diam., bears S. 84°10' E., 26½ lks. dist., mkd. C E E SE 1/256 S3 BT.</p> <p>A pine, 15 ins. diam., bears S. 22° W., 20 lks. dist., mkd. C E E SE 1/256 S3 BT.</p>
6.30	Fence, bears S. 17°30' E. and N. 17°30' W.
8.80	Home Creek, dry, 15 lks. wide, with 2 ft. banks, drains S. 10° W.
9.90	Point for the C-E-SE 1/64 sec. cor. of sec. 3; not monumented.
19.80	The point for the SE 1/16 sec. cor. of sec. 3.
29.70	Point for the C-W-SE 1/64 sec. cor. of sec. 3; not monumented.
34.65	<p>Point for the C-W-W-SE 1/256 sec. cor. of sec. 3.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2½ ft. base to top, brass cap mkd.</p> <p style="text-align: center;">T4N R28E C W W SE 1/256 S ————— S S 3 1972</p>
39.60	<p>The C-S 1/16 sec. cor. of sec. 3.</p> <hr/> <p>Subdivision of the SE¼ SE¼ Sec. 3, T. 4 N., R. 28 E.</p> <hr/> <p>From the point for the E-E 1/64 sec. cor. of secs. 3 and 10.</p> <p>N. 1°59' W., along the N. and S. centerline of the SE¼ SE¼ of sec. 3.</p> <p>Over nearly level land.</p>
3.87	Bladed road, bears S. 65° E. and N. 65° W.

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
5.90	Enter dense willows, bears S. 10° E. and N. 10° W.
10.145	Point for the SE-SE 1/64 sec. cor. of sec. 3, at intersection with the E. and W. centerline of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 3; not monumented.
16.00	Leave willows, bears irreg. E. and W.
18.76	Home Creek, dry, 15 lks. wide, with 1 $\frac{1}{2}$ ft. banks, drains S. 15° E. from N. 10° E.
20.29	The point for the C-E-SE 1/64 sec. cor. of sec. 3.
From the S-S 1/64 sec. cor. of secs. 2 and 3.	
S. 89°21' W., along the E. and W. centerline of the SE $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 3.	
Over gently rolling land, through moderate pine timber.	
2.75	Fence, bears S. 50° E. and N. 50° W.
4.945	Point for the C-E-SE-SE 1/256 sec. cor. of sec. 3.
Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 6 ins. in the ground, over an X chiseled on bedrock, mound of stone, 4 ft. base to top, brass cap mkd.	
<p style="text-align: center;">T4N R28E C E SE SE <u>1</u> 256 S 3 1972</p>	
from which	
<p style="text-align: center;">The NW. cor. of a cabin, 26x20 ft. in size, bears S. 50°30' E., 125 lks. dist., with the long sides bearing S. 85° E. and N. 85° W.</p>	
<p style="text-align: center;">The NW. cor. of a cabin, 28x20 ft. in size, bears S. 18°44' E., 662 lks. dist., with the long sides bearing S. 30° E. and N. 30° W.</p>	
<p style="text-align: center;">The NW. cor. of a cabin, 28x20 ft. in size, bears S. 16°13' E., 516 lks. dist., with the long sides bearing S. 25° E. and N. 25° W.</p>	

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS

The SW. cor. of a cabin, 28x20 ft. in size, bears S. 13°34' E., 484 lks. dist., with the long sides bearing S. 25° E. and N. 25° W.

The NW. cor. of a cabin, 60x32 ft. in size, bears S. 04°40' E., 304 lks. dist., with the long sides bearing S. 25° E. and N. 25° W.

The SE. cor. of a cabin, 24½x16 ft. in size bears S. 68°10' W., 36½ lks. dist., with the long sides bearing S. 15° E. and N. 15° W.

The SE. cor. of a cabin, 24½x16 ft. in size, bears N. 42°10' W., 82 lks. dist., with the long sides bearing N. 25° E. and S. 25° W.

6.00 Enter dense willows, bears irreg. N. and S.

8.55 Home Creek, dry, 15 lks. wide, with 1½ ft. banks, drains irreg. S.

9.89 The point for the SE-SE 1/64 sec. cor. of sec. 3.

12.00 Leave willows, bears irreg. N. and S., enter open grassland.

19.78 The point for the C-S-SE 1/64 sec. cor. of sec. 3.

Subdivision of the NW¼ SE¼ Sec. 3, T. 4 N., R. 28 E.

From the point for the C-W-SE 1/64 sec. cor. of sec. 3. N. 2°05' W., along the N. and S. centerline of the NW¼ SE¼ of sec. 3.

Over nearly level open grassland.

5.075 Point for the C-S-NW-SE 1/256 sec. cor. of sec. 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, brass cap mkd.

C S NW SE
1
 256
 S 3
 1972

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

5.28 Fence, bears N. 88°30' E. and S. 88°30' W.

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS

- 10.15 Point for the NW-SE 1/64 sec. cor. of sec. 3, at intersection with the E. and W. centerline of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of Sec. 3.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.
- NW SE 1/64
+
S 3
1972
- Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.
- 20.30 The point for the C-W-E 1/64 sec. cor. of sec. 3.
-
- From the point for the C-N-SE 1/64 sec. cor. of sec. 3.
- S. 89°23' W., along the E. and W. centerline of the NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 3.
- Over nearly level grassland.
- 4.955 Point for the C-E-NW-SE 1/256 sec. cor. of sec. 3.
- Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, brass cap mkd.
- T4N R28E
C E NW SE 1/256
S 3
1971
- 9.91 The NW-SE 1/64 sec. cor. of sec. 3.
- 14.78 Fence, bears N. 33°12' E. and S. 33°12' W., leave grassland, enter moderate pine timber.
- 14.865 Point for the C-W-NW-SE 1/256 sec. cor. of sec. 3; not monumented.
- 19.82 The point for the C-N-S 1/64 sec. cor. of sec. 3.
-
- Subdivision of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$ Sec. 3.
-
- From the C-W-W-SE 1/256 sec. cor. of sec. 3.
- N. 2°06'30" W., along the N. and S. centerline of the SW $\frac{1}{4}$ NW $\frac{1}{4}$ SE $\frac{1}{4}$ of sec. 3.
- Over nearly level grassland.

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS		
5.076	<p>Point for the SW-NW-SE 1/256 sec. cor. of sec. 3, at intersection with the E. and W. centerline of the SW$\frac{1}{4}$ NW$\frac{1}{4}$ SE$\frac{1}{4}$ of sec. 3.</p>	
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.</p>	
	<p>SW NW SE + 1 S-3 256 1972</p>	
	<p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>	
10.152	<p>The point for the C-W-NW-SE 1/256 sec. cor. of sec. 3.</p>	
	<p style="text-align: center;">_____</p> <p>From the C-S-NW-SE 1/256 sec. cor. of sec. 3.</p> <p>S. 89°23' W., along the E. and W. centerline of the SW$\frac{1}{4}$ NW$\frac{1}{4}$ SE$\frac{1}{4}$ of sec. 3.</p>	
	<p>Over nearly level grassland.</p>	
4.95	<p>The SW-NW-SE 1/256 sec. cor. of sec. 3.</p>	
8.11	<p>Fence, bears N. 33°12' E. and S. 33°12' W.</p>	
9.90	<p>The point for the C-S-N-S 1/256 sec. cor. of sec. 3.</p>	
	<p>Subdivision of the NE$\frac{1}{4}$ Sec. 3, T. 4 N., R. 28 E.</p>	
	<p>From the C-E 1/16 sec. cor. of sec. 3.</p> <p>N. 2°02' W., along the N. and S. centerline of the NE$\frac{1}{4}$ of sec. 3.</p>	
	<p>Over nearly level grassland.</p>	
5.055	<p>Point for the C-S-S-NE 1/256 sec. cor. of sec. 3; not monumented.</p>	
10.11	<p>Point for the C-S-NE 1/64 sec. cor. of sec. 3.</p>	
	<p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, brass cap mkd.</p>	
	<p>T4N R28E C S NE 1/64 S 3 1972</p>	
	<p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, W. of the cor.</p>	

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS

- 11.66 Home Creek, 15 lks. wide, 1 ft. deep, drains S. 15° E.
- 15.60 Wash, 10 lks. wide, 1 ft. deep, drains S. 40° E.
- 18.30 Center of small catch pond, 120 lks. diam.
- 20.22 Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E. and W. centerline of the NE¼ of sec. 3.
- Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, brass cap mkd.
- T4N R28E
E
N 1/16 | S 3
E
1972
- Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.
- 32.54 Fence, bears S. 70° E. and N. 70° W.
- 34.80 Home Creek, dry, 15 lks. wide, with 2 ft. banks, drains W., curving southerly.
- 36.00 Same Creek, 10 lks. wide, with 1½ ft. banks, drains SE, curving W.
- 36.07 Fence, bears S. 30° E. and N. 30° W.
- 38.70 Same Creek, 15 lks. wide, with 1 ft. banks, drains SW.
- 39.87 Same Creek, 15 lks. wide, with 1 ft. banks, drains SE.
- 40.48 Intersect the First Standard Parallel North.

True point for the E 1/16 sec. cor. on the N. bdy. of sec. 3, at midpoint between the NE¼ sec. cor. of sec. 3 and the closing cor. of secs. 2 and 3, falls on the E. bank of Home Creek, where a monument cannot be perpetuated; witnessed S. 89°54' E., 10 lks. dist.

At the witness cor. point.

Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.

← $\frac{W}{E \ 1/16 \ S \ 3 \ C}$
T4N R28E
1971

from this witness corner

The true standard cor. of secs. 33 and 34, a tree (witnessed 10 lks. N. 89°57' W.) bears N. 89°54' W., 5.47 chs. dist., previously described.

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS

A ponderosa pine, 4 ins. diam., bears S. 61°40' E., 44 lks. dist., mkd. with an X at breast height and BT at the base.

A pine, 10 ins. diam., bears S. 62°15' W., 67 lks. dist., mkd. with an X at breast height and BT at the base.

The closing corner of secs 2 and 3, bears S. 89°54' E., 19.81 chs. dist.

Raise a mound of stone, 2½ ft. base, 2 ft. high, S. of the cor.

From the N 1/16 sec. cor. of secs. 2 and 3.

S. 89°19' W., along the E. and W. centerline of the NE¼ of sec. 3.

Over rolling land, through moderate ponderosa pine timber.

- 9.94 Point for the C-E-NE 1/64 sec. cor. of sec. 3; not monumented.
- 19.22 Fence, bears irreg. N. and S., leave pine timber, bears irreg. N. and S., enter open grassland.
- 19.88 The NE 1/16 sec. cor. of sec. 3.
- 22.30 Home Creek, dry, 30 lks. wide, with 2 ft. banks, drains S. 25° E.
- 25.80 Leave open grassland, bears N. and S., enter moderate pine timber and asc. E. slope.
- 39.05 Fence, bears irreg. N. and S.
- 39.77 The C-N 1/16 sec. cor. of sec. 3.

Subdivision of the SE¼ NE¼ of sec. 3.

From the C-E-E 1/64 sec. cor. of sec. 3.

N. 1°59' W., along the N. and S. centerline of the SE¼ NE¼ of sec. 3.

Over rolling land.

- 1.10 Fence, bears S. 37°30' E. and N. 37°30' W., asc. S. slope through moderate pine timber.
- 5.06 Point for the C-S-SE-NE 1/256 sec. cor. of sec. 3.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2 ft. base to top, brass cap mkd.

T4N R28E
C S SE NE
1
256
+
S 3
1972

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
	<p>from which</p> <p>A pine, 4 ins. diam., bears N. 50° E., 12 lks. dist., mkd. with an X at breast height and with BT at the base of the tree.</p> <p>A pine, 16 ins. diam., bears S. 68° W., 29 lks. dist., mkd. C S SE NE 1/256 BT.</p>
10.12	Point for the SE-NE 1/64 sec. cor. of sec. 3, at intersection with the E. and W. centerline of the SE½ NE½ of sec. 3; not monumented.
20.25	The point for the C-E-NE 1/64 sec. cor. of sec. 3.
	<hr/> <p>From the point for the S-N 1/64 sec. cor. of secs. 2 and 3.</p> <p>S. 89°23' W., along the E. and W. centerline of the SE½ NE½ of sec. 3.</p> <p>Over rolling land, through moderate pine timber.</p>
8.30	Rocky rim, bears irreg. N. and SE., desc. steep W. slope.
9.93	The point for the SE-NE 1/64 sec. cor. of sec. 3.
14.895	Point for the C-W-SE-NE 1/256 sec. cor. of sec. 3.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, brass cap mkd.</p> <p style="text-align: center;">T4N R28E C-W-SE-NE 1/256 + S 3 1972</p>
	<p>from which</p> <p>A pine, 3 ins. diam., bears N. 35° E., 45 lks. dist., mkd. X at breast height and BT at the base.</p> <p>A pine, 4 ins. diam., bears S. 56° E., 22 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
17.12	Fence, bears S. 37°30' E. and N. 37°30' W., leave timber, bears same as fence, enter open grassland.
18.80	Home Creek, dry, 15 lks. wide, 2 ft. deep, drains irreg. S.
19.86	The C-S NE 1/64 sec. cor. of sec. 3.
	<hr/> <p style="text-align: center;">Subdivision of the SW½ SE½ NE½ of sec. 3.</p> <hr/> <p>From the C-W-E-E 1/256 sec. cor. of sec. 3.</p>

Survey, Subdivision of Section 3, T. 4 N., R. 28 E.

CHAINS	
	<p>N. 2°00'30" W., along the N. and S. centerline of the SW$\frac{1}{4}$ SE$\frac{1}{4}$ NE$\frac{1}{4}$ of sec. 3.</p> <p>Over gently rolling grassland.</p>
5.06	<p>Point for the SW-SE-NE 1/256 sec. cor. of sec. 3, at intersection with the E. and W. centerline of the SW$\frac{1}{4}$ SE$\frac{1}{4}$ NE$\frac{1}{4}$ of sec. 3.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, in a collar of stone, 2 ft. base to top, brass cap mkd.</p>
	<p>T4N R28E SW SE NE <u>1</u> 256 + S 3 1972</p>
6.60	<p>Home Creek, dry, 15 lks. wide, with 2$\frac{1}{2}$ ft. banks, drains S.</p>
7.60	<p>Fence, bears S. 50° E. and N. 50° W., leave open grassland, bears same as fence, enter moderate pine timber and asc. S. slope.</p>
10.12	<p>The C-W-SE-NE 1/256 sec. cor. of sec. 3.</p>
	<p>From the C-S-SE-NE 1/256 sec. cor. of sec. 3.</p> <p>S. 89°24'30" W., along the E. and W. centerline of the SW$\frac{1}{4}$ SE$\frac{1}{4}$ NE$\frac{1}{4}$ of sec. 3.</p> <p>Through moderate pine timber, desc. steep SW. slope.</p>
2.81	<p>Fence, bears S. 50° E. and N. 50° W.</p>
4.30	<p>Home Creek, dry, 15 lks. wide, with 2 ft. banks, drains irreg. S.</p>
4.965	<p>The SW-SE-NE 1/256 sec. cor. of sec. 3.</p>
9.93	<p>The point for the C-S-S-NE 1/256 sec. cor. of sec. 3.</p>
	<p>GENERAL DESCRIPTION</p>
	<p>The area resurveyed and surveyed in sections 3 and 10, T. 4 N., R. 28 E., varies from nearly level in the central portion to rolling in the north and south portions. The elevation ranges from about 7580 to 7880 ft. above sea level. The soil is dark, rocky clay loam. There is good grass in the open lands adjacent to the West Fork of Black River and moderate grass in the pine timber areas in the northern two thirds of section 3 and southern two thirds of section 10.</p> <p>The old P.S. Ranch Cabin is located in the northeast corner of section 10. There are several cabins in section 3, mostly near the southeast corner of the section and are primarily used in the summer and the fall season.</p>

General Description, T. 4 N., R. 28 E.

CHAINS

The West Fork of Black River traverses easterly through the southwest portion of section 3 and the northeast portion of section 10.

The area surveyed is located about 15 miles westerly by graded U.S.F.S. roads Nos. 285 and 82 from U.S. Highway 666 and about 8 airline miles southerly and 2 airline miles easterly from Big Lake.

The area surveyed is primarily volcanic in origin and no mineral formations were noted.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Harry K. Smith	Cadastral Surveyor
James W. Raleigh, Jr.	Surveying Aid
Carter Clark, Jr.	Surveying Aid
Michael Woods	Surveying Aid
Carlos Ramirez	Surveying Aid
Kurt Merkle	Surveying Aid
Ronald McCally	Surveying Aid
Ken Weir	Surveying Aid
Bruce Jackson	Surveying Aid

3
3

CERTIFICATE OF SURVEY

~~XX~~ (We), Paul G. Bauer and Boyd S. Owens, HEREBY
CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day
of September, 1971, ~~XX~~ (We) have retraced a portion of the south bound-
ary of Township 5 North, Range 28 East and have dependently resurveyed
the boundaries and surveyed subdivisions of Sections 3 and 10, Township
4 North, Range 28 East

of the Gila and Salt River Meridian, in the State of Arizona, which
are represented in the foregoing field notes as having been executed by ~~me~~, (us) and under ~~my~~
(our) direction; and that said survey has been made in strict conformity with said special instruc-
tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
specific manner described in the foregoing field notes.

October 12, 1973
(Date)

Paul G. Bauer
(Cadastral Surveyor)

October 12, 1973
(Date)

Boyd S. Owens
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
Date JUN 27 1974

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the retracement of a portion of the south boundary
of Township 5 North, Range 28 East and the dependent resurvey of the
boundaries and the survey of subdivision of Section 3 and 10, Township
4 North, Range 28 East, Gila and Salt River Meridian, Arizona.
executed by Paul G. Bauer and Boyd S. Owens
having been critically examined and found correct, are hereby approved.

MAY 13 1975
(Date)

Bernard M. [Signature]
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626