

Form 9180-6  
(April 1974)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE

NORTH BOUNDARY AND SUBDIVISIONAL LINES

WITH THE SUBDIVISION OF CERTAIN SECTIONS

TOWNSHIP 9 NORTH, RANGE 25 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

GILBERT V. OLSON

SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated May 3, 1973, approved May 8, 1973,

Supplemental Special Instructions dated June 14, 1973

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group

Number 558, and assignment instructions dated May 3, 1973.

Survey commenced May 14, 1973

Survey completed September 18, 1973

18

BOOK 5002

INDEX DIAGRAM

Township 9 North, Range 25 East

		6	4	3	2
6	5	18 4	15 8	10 2	1
		16	14		
7	8	9	13 10	8 11	12
			12		
18	17	16	10 15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subd. of Sec 3 pp 18-19  
 Subd. of Sec 4 pp 19-21  
 Subd. of Sec 10 pp 21-27

Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the dependent resurvey of portions of the north boundary and subdivisional lines with the subdivision of certain sections of Township 9 North, Range 25 East, Gila and Salt River Meridian, Arizona.

The survey of the north boundary and subdivisional lines of the part of the township resurveyed under this group was executed by Deputy Surveyor A. P. Johnson, in 1882. The east boundary was surveyed by the same A. P. Johnson, in 1882 and the north five miles thereof were resurveyed by Roger F. Wilson, U. S. Surveyor, under Group 192, in 1937.

The boundaries of section 20, and sections 26 through 36 were resurveyed by S. E. Blout, U. S. Surveyor, in 1915.

In the resurveys by Blout, in 1915, considerable distortion was found in the original survey. Numerous corners were missing, and the survey was superseded.

In connection with resurveys in Township 9 North, Range 26 East, Wilson, in 1937, discovered a gross error in the position of the survey of the west boundary thereof. At the corner of Townships 9 and 10 North, Ranges 25 and 26 East, a monument well set and marked for a closing corner of Townships 9 North, Ranges 25 and 26 East, was discovered. This corner was tied in and destroyed because it was not of record. It is to be noted that Wilson, in his resurvey of the line between Township 9 North, Ranges 25 and 26 East, southerly from the above described corner of Townships 9 and 10 North, Ranges 25 and 26 East, did accept the corners of an original survey which were harmoniously located in reference to the spurious corner of Townships 9 and 10 North, Ranges 25 and 26 East which was marked as a closing corner and destroyed by him.

In this dependent resurvey of the line between Townships 9 and 10 North, Range 25 East, evidence of closing corners of sections 1 and 2, 2 and 3, 3 and 4, and 4 and 5, was recovered. These corners were of approximately the same age, and bore markings characteristic of the Johnson corners in the subdivision of Township 9 North. They were not officially recorded, and in consonance with the procedure established by Wilson, in 1937, were destroyed or reduced to amended monuments.

Because of the distortions in the subdivisional lines of the Johnson surveys in the north tier of sections in Township 9 North, Range 25 East, a connecting line was surveyed between the Johnson corners and the resurvey corners of Blout in 1915 and Wilson in 1937. These connecting lines were not resurveyed.

The resurveys of the boundaries of sections 3, 4, and 10 were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947, and the provisions of the Special Instructions for Group 558, Arizona, dated May 3, 1973, and the Supplemental Special Instructions dated June 14, 1973.

Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS

Preliminary to the dependent resurvey all lines of the original survey were retraced and search made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. All retracement data are thoroughly verified and only the true line field notes are given herein.

The directions of the lines were obtained by direct observations on polaris and checked by direct observations on the sun. They refer to the true meridian.

The geographic position of the southeast corner of section 10, as scaled from U. S. Geological Survey Quadrangle "Boundary Butte", is:

Latitude 34° 11.1' N.  
Longitude 109° 40.4' W.

The mean magnetic declination is 13½° East.

Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

Reestablishment of the Survey Executed by  
A. P. Johnson, Deputy Surveyor, in 1882.

Beginning at the cor. of secs. 1, 2, 35, and 36, Tps. 9 and 10 N., R. 25 E., marked by rough lava stone, 28x18x6 ins., set in a mound of stone around corner post of fences bearing E., W., and N., mkd. with one notch on the E. edge and 5 notches on the W. edge, from which the remains of the original bearing trees:

A pine, 18 ins. diam., bears N. 42° E., 85 lks. dist., mkd. S36 BT. (record, N. 42° E., 60 lks.)

A pine stump, badly rotted, bears S. 45° W., 42 lks. dist. (record bearing and distance)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T10N R25E  
S 35 | S 36  
S 2 | S 1  
T9N

1973

Raise a mound of stone, 5 ft. base, 1½ ft. high around the corner and bury the old stone alongside the iron post.

Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this cor., the cor. of Tps. 9 and 10 N., Rs. 25 and 26 E., bears S. 89° 30' E., 79.09 chs. dist. This corner is marked by an iron post, 3 ins. diam., protruding 10 ins. above the ground, in a mound of stone, 4 ft. base, 1 ft. high, with brass cap mkd.</p>
	<p>T10N R25E R26E <u>S 36   S 31</u> S 1   S 6 T9N</p>
	<p>1937</p>
	<p>from which</p> <p>An unmarked stone, firmly set in a mound of stone, bears S. 89° 50' E., 4.08 chs. dist. (This is the stone recorded in the field notes of the Wilson resurvey in 1937.)</p> <p>From the cor. of secs. 1, 2, 35, and 36,</p> <p>A lava stone, 22x14x6 ins., mkd. with 1 groove on one edge, 5 grooves on opposite edge and CC on top face, lying on surface of ground near an irregular fence, bears N. 88° E., 5.26 chs. dist. This stone appears to have been marked for a corner established in harmony with the stone described above as found by Wilson in 1937 and destroyed at that time. The marked stone is mkd. AM and buried 24 ins. beneath the surface.</p> <p>From the cor. of secs. 1, 2, 35, and 36,</p> <p>N. 89° 48' W., between secs. 2 and 35.</p> <p>Along broken rocky southerly slopes, through scattered scrubby juniper and pinon timber, along N. edge of clearing for power line.</p>
15.00	Along broken southwesterly slopes, paralleling power line.
17.00	Truck trail bears NW. and SE.
35.10	Old mound of stone, on edge of clearing for power line bearing E. and W. Several rotted stakes are in center of mound.
40.00	No trace of the 1/4 sec. cor. was found. The cor. will probably fall in edge of clearing for power line. This missing cor. is not reestablished.
45.00	Ridge bears NW. and SE.
	Continue over broken, rocky W. to SW. slopes, through scattered timber, along N. edge of clearing for power line.
54.50	Forest Service road, bears NW. and SE.
75.84	A lava stone, 14x12x8 ins., loosely set in old mound of stone, bears North, 0.11 chs. dist., mkd. with 2 notches on the W., 4 notches on the E. edge, CC on the S. face. This stone appears to have been set in the subdivision of T. 9 N., R. 25 E. There is some evidence it has been used to determine the line between secs. 2 and 3.

Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>At the old stone</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 35 AM 1973</p> <p>Bury the old stone alongside the iron post.</p> <p>81.88 The cor. of secs. 2, 3, 34, and 35, mkd. by a porous lava rock, 9x8 ins., protruding 11 ins. above the ground in a mound of stone, mkd. with 2 notches on the E. and 4 notches on the W. edge. The cor. is set in fence line bearing N. and S., in S. edge of clearing for power line.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam, 24 ins. in the ground to solid rock, supported in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T10N R25E S 34   S 35 S 3   S 2 T9N 1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 22¼° W., 52 lks. dist., mkd. T10N R25E S34 BT.</p> <p style="padding-left: 40px;">No other trees available suitable for marking.</p> <p style="padding-left: 40px;">Bury the old stone at base of iron post.</p>	
	<p>S. 89° 34' W., between secs. 3 and 34.</p> <p>Descend gradual S. to SW. slopes, along N. edge of clearing for power line, through scattered scrubby junipers and pine timber in cut over area.</p> <p>31.00 Descend over rocky ledges, in heavy brush on SW. slopes.</p> <p>32.50 Old mound of stone, 3 ft. diam., 1 ft. high, with rotted post in center, bears North, 0.10 chs. dist.</p> <p>32.90 Foot of steep W. to SW. slope, enter creek bed.</p> <p>35.50 Center of Vernon Creek, dry, course N. 30° W.</p> <p>39.575 Point for the 1/4 sec. cor. of secs. 3 and 34, is determined at proportionate distance. There is no evidence of the original corner. Point for the corner falls on rocky N. slope in heavy brush.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>T10N R25E  <math>\frac{1}{4}</math> <math>\frac{S\ 34}{S\ 3}</math>  T9N  1973</p> <p>Raise a mound of stone, 4 ft. base, 2½ ft. high, N. of the corner.</p>	
41.00	Ascend gradual NE. slope, leave creek bottom, bears N. and SE., continue along irregular fence in N. edge of clearing for power line.	
44.00	Pulcifer Creek, dry, course N.	
48.00	Hillside drain, dry, course N., along gradual N. slopes, in cut over area along N. edge of clearing for power line.	
73.97	<p>A rough lava stone, 20x12x8 ins., set in a mound of stone, mkd. with 3 grooves on the E. and W. faces, CC on the S. face, bears North, 0.39 chs. dist. This stone appears to have been set in the survey of the subdivision of T. 9 N., R. 25 E. In order to perpetuate its location; in place of the old stone,</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>	
	<p>T10N R25E  A M  +  T9N  1973</p> <p>Bury the old stone alongside the iron post.</p>	
79.15	<p>The cor. of secs. 3, 4, 33, and 34, marked by a basalt stone, 8x4 ins., protruding 10 ins. above the ground, alongside an iron pipe, 1 in. diam., protruding 15 ins. above the ground, in center of a mound of stone, 2½ ft. diam., mkd. with 3 notches on the E. and W. edges.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
	<p>T10N R25E  <math>\frac{S\ 33\   S\ 34}{S\ 4\   S\ 3}</math>  T9N  1973</p> <p>Place the 1 in. iron pipe inside the 2½ in. iron post and bury the old stone at the base of the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 1 ft. high, around the iron post.</p> <p>Corner is set in N. edge of clearing for power line.</p>	

Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	S. 88° 50' W., between secs. 4 and 33.	
	Over nearly level land, through cut over timber, along N. edge of clearing for power line, and S. edge of abandoned field.	
13.75	Leave edge of clearing for power line, bears E. and SW.	
15.10	Center of graded road, bears N. 50° W. to Vernon and S. 50° E. to Carlock Ranch.	
15.60	Corner of fences bears S. and S. 88° 50' W., continue along fence through scrubby juniper timber, on gradual NE. to N. slopes.	
19.90	Point for the E 1/16 sec. cor. of secs. 4 and 33.  Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T10N R25E E 1/16 <math>\frac{S\ 33}{S\ 4}</math> T9N  1973</p>	
	from which	
	An angle iron, 1½x1 in., protruding 12 ins. above the ground, bears EAST, 9½ lks. dist.	
	A pine, 8 ins. diam., bears S. 39 ¾° E., 42 lks. dist., mkd. E 1/16 S4 BT.	
	A pine, 9 ins. diam., bears N. 7° W., 51 lks. dist., mkd. E 1/16 S33 BT.	
	Corner is set 44 lks. N. of wire fence which bears generally E. and W.	
	Continue along N. slopes, through scrubby pine and juniper timber, along meandering fence.	
39.80	The 1/4 sec. cor. of secs. 4 and 33, marked by a partly burned mound of stone, 3 ft. diam., with several rotted wooden stakes and rusted iron, in center, from which an original bearing tree:	
	A white oak, 24 ins. diam., bears EAST, 15 lks. dist. The blaze on the NW. face is overgrown and is not opened. (record, N. 70° E., 15 lks.)	
	At the corner point	
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T10N R25E ¼ <math>\frac{S\ 33}{S\ 4}</math> T9N  1973</p>	



Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS						
	<p>from which</p> <p>A pine, 14 ins. diam., bears S. 13 3/4° E., 31 lks. dist., mkd. 1/4 S4 BT.</p> <p>A pine, 10 ins. diam., bears S. 54 3/4° W., 19 lks. dist., mkd. 1/4 S4 BT.</p> <p>Bury the rotten wood and iron alongside the corner.</p> <p>Corner is set 66 lks. S. of fence bearing about E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 87° 51' W., beginning new measurement.</p> <p>Along northerly slopes, through cut over land in second growth pine and juniper.</p>					
6.00	Spur, slopes N., continue along northerly slopes.					
22.00	Improved Forest Service Road No. 224, bears NE. to Vernon and SW. to McNary.					
26.50	Drain, course N., over nearly level land, generally along fence bearing irregularly S. 87° E. and N. 88° W.					
34.10	Old mound of stone, 3 ft. diam., with rotted post in center, bears SOUTH, 11 lks. dist.					
40.20	<p>The cor. of secs. 4, 5, 32, and 33, mkd. by a rough basalt stone, 20x10x6 ins., loosely set in a mound of stone, mkd. with 4 grooves on the E. and 2 grooves on the W. faces, from which extant bearing trees:</p> <p>An oak, 32 ins. diam., bears S. 17° W., 79 lks. dist., mkd. T9N R25E S5 BT. (No record of this tree in original survey)</p> <p>An oak, 25 ins. diam., bears N. 54 3/4° W., 118 lks. dist., with partially overgrown blaze, some mks. are visible on trunk. The blaze is not re-opened. (No record of this tree in original survey)</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td>T10N R25E</td></tr> <tr><td>S 32   S 33</td></tr> <tr><td>S 5   S 4</td></tr> <tr><td>T9N</td></tr> <tr><td>1973</td></tr> </table> </div>	T10N R25E	S 32   S 33	S 5   S 4	T9N	1973
T10N R25E						
S 32   S 33						
S 5   S 4						
T9N						
1973						
	<p>from which</p> <p>A pine, 6 ins. diam., bears N. 24 3/4° E., 29 lks. dist., mkd. T10N R25E S33 BT.</p> <p>A pine, 5 ins. diam., bears S. 11 3/4° E., 17 lks. dist., mkd. T9N R25E S4 BT.</p> <p>A pine, 4 ins. diam., bears S. 6¼° W., 25 lks. dist., mkd. X BT.</p>					

Dependent Resurvey of a Portion  
of the North Boundary  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS

A pine, 5 ins. diam., bears N.  $28\frac{1}{2}^{\circ}$  W., 24 lks. dist., mkd. T10N R25E S32 BT.

The cor. post in fences bearing N. and S.  $88^{\circ}$  E., bears N.  $45^{\circ}$  W., 5 lks. dist.

Bury the old stone alongside the iron post.

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

From the cor. of secs. 10, 11, 14, and 15, marked by an old mound of stone, 3 ft. diam., with no trace of the original stone, from which the original bearing trees:

An oak, 15 ins. diam., bears N.  $14^{\circ}$  E., 44 lks. dist., with old closed blaze. (record, N.  $14^{\circ}$  E., 43 lks.)

A pine, 28 ins. diam., bears S.  $46^{\circ}$  E., 18 lks. dist., mkd. T9N R25E S14 BT. (record bearing and distance)

An oak, 12 ins. diam., bears S.  $15^{\circ}$  W., 15 lks. dist., blazes closed. (The record of the bearing and distance to this tree is S.  $15^{\circ}$  W., 75 lks. dist. The original field notes are probably in error in the distance.)

At the corner point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R25E  
S 10 | S 11  
S 15 | S 14

1973

from which a new bearing tree:

An oak, 10 ins. diam., bears N.  $59\frac{1}{2}^{\circ}$  E., 27 lks. dist., mkd. T9N R25E S11 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.

N.  $1^{\circ}$  18' E., between secs. 10 and 11.

Descend NW. slopes through cut over pine timber.

36.50

Dry drain, course NW., ascend gradual S. slope.

39.84

Point for the  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, determined at proportionate distance. There is no evidence of the original corner.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground to underlying rock, supported in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T9N R25E <math>\frac{1}{4}</math> S 10 S 11</p>
	<p style="text-align: center;">1973</p>
	<p>from which</p>
	<p>A pine, 8 ins. diam., bears N. <math>43\frac{1}{4}^{\circ}</math> E., 31 lks. dist., mkd. 1/4 S11 BT.</p>
	<p>A pine, 4 ins. diam., bears S. <math>27^{\circ}</math> E., 46 lks. dist., mkd. 1/4 S11 BT.</p>
	<p>Continue along SW. to W. slopes, through cut over pine timber.</p>
45.00	<p>Slope changes to very gradual W. to NW.</p>
59.76	<p>Point for the N 1/16 sec. cor. of secs. 10 and 11.</p>
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R25E N 1/16 S 10 S 11</p>
	<p style="text-align: center;">1973</p>
	<p>from which</p>
	<p>A pine, 8 ins. diam., bears S. <math>61\frac{1}{4}^{\circ}</math> W., 24 lks. dist., mkd. N 1/16 S10 BT.</p>
	<p>A pine, 10 ins. diam., bears N. <math>27\frac{3}{4}^{\circ}</math> W., 23 lks. dist., mkd. X BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.</p>
60.40	<p>Small drain, dry, course NW.</p>
79.68	<p>The cor. of secs. 2, 3, 10, and 11, marked by a basalt stone, 15x10x6 ins., set in a mound of stone, dimly mkd. with 3 grooves on the E. face. The stone is very rough and pitted.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 15 ins. in the ground to underlying rock, supported in mound of stones, <math>2\frac{1}{2}</math> ft. base, 1 ft. high, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R25E S 3 S 2 S 10 S 11</p>
	<p style="text-align: center;">1973</p>
	<p>from which</p>
	<p>A juniper, 8 ins. diam., bears N. <math>63\frac{3}{4}^{\circ}</math> E., 36 lks. dist., mkd. X BT.</p>
	<p>A pine, 5 ins. diam., bears S. <math>23^{\circ}</math> E., 44 lks. dist., mkd. T9N R25E S11 BT.</p>
	<p>A pine, 10 ins. diam., bears N. <math>39\frac{1}{4}^{\circ}</math> W., 56 lks. dist., mkd. T9N R25E S3 BT.</p>
	<p>No other accessories available.</p>

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	Bury the old stone alongside the iron post.
	<p>N. 0° 16' W., between secs. 2 and 3.</p> <p>Ascend along rocky S. slopes, through pine timber.</p> <p>4.00 Small spur slopes NW., descend gradual northerly slopes.</p> <p>30.00 Vernon Creek, dry, course N. 85° W. to S. 80° W. to dirt tank, about 10 chs. dist. Ascend SW. slope along a meandering wire fence.</p> <p>40.09 The 1/4 sec. cor. of secs. 2 and 3, marked by a rough basalt stone, 16x14x8 ins., set in a small mound of stones, in fence bearing S. 2° W. and N. There is no evidence of the original bearing trees.</p>
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E ¼ S 3 S 2</p> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner, and bury the old stone alongside the iron post.</p> <p>Corner is set in fence line bearing N. and S., in thicket of small pines, on heavily cut over area.</p>
	<p>N. 8° 50' W., beginning new measurement.</p> <p>Along westerly slopes, crossing numerous small drains course W. to NW., through scrubby timber.</p> <p>20.30 Point for the N 1/16 sec. cor. of secs. 2 and 3.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock, supported in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E N 1/16 S 3 S 2</p> <p style="text-align: center;">1973</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 7 ins. diam., bears S. 55½° E., 49 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 31½° W., 70 lks. dist., mkd. N 1/16 S3 BT.</p> <p>40.55 The cor. of secs. 2, 3, 34, and 35, on the N. boundary of the township, hereinbefore described.</p>
	<p>From the 1/4 sec. cor. of secs. 15 and 16, marked by a basalt stone, 23x10x5 ins., loosely set in a mound of stone, mkd. 1/4 on the W. face, from which original bearing trees:</p>

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

## CHAINS

A pine, 12 ins. diam., bears S. 23° E., 31 lks.  
dist., mkd. 1/4 S BT. (record, S. 20° E., 30 lks.)

A pine, 22 ins. diam., bears N. 32° W., 24 lks.  
dist., mkd. 1/4 S BT. (record bearing and distance)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins.  
in the ground to solid rock, supported in a mound of  
stone, 3 ft. diam. to top, with brass cap mkd.

T9N R25E  
    ¼  
S 16 | S 15

1973

Bury the old stone alongside the iron post.

From the 1/4 sec. cor. of secs. 15 and 16, the cor. of  
secs. 21, 22, 27, and 28, as set by Sidney Blout, U. S.  
Surveyor, in 1915, bears S. 0° 20' E., 118.43 chs. dist.  
This corner is marked by an iron post, 2 ins. diam., pro-  
truding 8 ins. above the ground, with brass cap mkd.

T9N R25E  
S 21 | S 22  
S 28 | S 27

1915

from which, the remains of the original bearing trees:

A pine stump, of indeterminate size, bears N. 24°  
E., 60 lks. dist.

A pine stump, 18 ins. diam., bears S. 9½° W., 43  
lks. dist., mkd. S28 BT.

A pine, 14 ins. diam., bears N. 65 3/4° W., 90  
lks. dist., mkd. S21 BT.

The SE. bearing tree is missing. This corner not  
disturbed.

This control line was fully retraced and careful search  
was made for evidence of intervening corners, none of  
which was recovered.

N. 0° 07' E., between secs. 15 and 16.

Descend over broken N. to NE. slopes, through pine timber  
along meandering fence.

19.00 Fence, bears N. and S. 20° W., continue generally along  
fence.

39.82 The cor. of secs. 9, 10, 15, and 16, marked by a basalt  
stone, 16x10x6 ins., firmly set in a mound of stone,  
3 ft. base, mkd. with 4 notches on the S. edge and 3  
grooves on the E. face, from which the remains of an  
original bearing tree:

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>A pine stump, 15 ins. diam., bears N. 37 3/4° E., 66 lks. dist., blazed and mkd. BT. Some illegible mks. are visible above the "BT". (Original record, N. 38° E., 65 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E S 9   S 10 S 16   S 15</p> <p style="text-align: center;">1973</p> <p>from which new bearing trees:</p> <p>A pine, 6 ins. diam., bears N. 34° E., 35 lks. dist., mkd. X BT.</p> <p>A pine, 8 ins. diam., bears S. 78½° E., 19 lks. dist., mkd. T9N R25E S15 BT.</p> <p>A pine, 10 ins. diam., bears S. 42° W., 30 lks. dist., mkd. T9N R25E S16 BT.</p> <p>A pine, 16 ins. diam., bears N. 49° W., 6 lks. dist., with blazes on N. and S. faces, overgrown and closed. The blazes are not opened.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner, alongside wire fence, and bury the old stone alongside the iron post.</p>	
<p>21.50</p> <p>30.00</p> <p>37.04</p>	<p>From the cor. of secs. 10, 11, 14, and 15, N. 88° 41' W., between secs. 10 and 15.</p> <p>Descend along NW. slope through cut over pine timber.</p> <p>Drain, course N., ascend E. slopes.</p> <p>Spur slopes N., descend NW. slope.</p> <p>The 1/4 sec. cor. of secs. 10 and 15, marked by a basalt stone, 16x12x8 ins., set in a mound of stone, mkd. 1/4 on the N. face, from which the remains of the original bearing trees:</p> <p>A pine stump, badly decayed, bears N. 30° W., 28 lks. dist. (record, N. 30° W., 36 lks.)</p> <p>A pine stump, badly decayed, bears S. 20° W., 60 lks. dist. (record, S. 17° W., 59 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E ¼ S 10 S 15</p> <p style="text-align: center;">1973</p>	

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which new bearing trees:</p> <p>A pine, 8 ins. diam., bears N. <math>42\frac{1}{2}^{\circ}</math> E., 45 lks. dist., mkd. 1/4 S10 BT.</p> <p>A pine, 10 ins. diam., bears S. <math>61\frac{1}{4}^{\circ}</math> E., 68 lks. dist., mkd. 1/4 S15 BT.</p> <p>Bury the old stone alongside the iron post.</p> <hr/> <p>S. <math>87^{\circ} 57'</math> W., beginning new measurement.</p> <p>Along northerly slopes through cut over pine timber.</p> <p>15.50 Drain, course N. to NE.</p> <p>27.50 Drain, course N. <math>10^{\circ}</math> E.</p> <p>29.50 Truck trail, bears N. and on curve to S. <math>15^{\circ}</math> W.</p> <p>39.91 The cor. of secs. 9, 10, 15, and 16.</p>
	<p>N. <math>0^{\circ} 57'</math> W., between secs. 9 and 10.</p> <p>Through cut over pine timber along fence.</p> <p>7.00 Small drain, course N. <math>25^{\circ}</math> E., along gradual NE. slopes.</p> <p>29.90 U. S. Forest Service Poncho Springs Fire Road, bears N. <math>60^{\circ}</math> W. and S. <math>60^{\circ}</math> E.</p> <p>39.92 The 1/4 sec. cor. of secs. 9 and 10, marked by a rough basalt rock, 14x10x7 ins., set in a mound of stone, mkd. 1/4 on the W. face, from which the remains of the original bearing trees:</p> <p>A pine, 28 ins. diam., bears N. <math>32\frac{1}{2}^{\circ}</math> E., 40 lks. dist., mkd. 1/4 S10 BT. (record, N. <math>38^{\circ}</math> E., 38 lks.)</p> <p>A pine stump, badly rotted, bears S. <math>62^{\circ}</math> W., 118 lks. dist., no mks. visible. (record, S. <math>62^{\circ}</math> W., 120 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E <math>\frac{1}{4}</math> S 9   S 10</p> <p style="text-align: center;">1973</p> <p>from which new bearing trees:</p> <p>A pine, 6 ins. diam., bears N. <math>83^{\circ}</math> E., 40 lks. dist., mkd. X BT.</p> <p>A pine, 6 ins. diam., bears N. <math>43\frac{1}{4}^{\circ}</math> W., 40 lks. dist., mkd. 1/4 S9 BT.</p> <p>Bury the old stone alongside the iron post.</p>

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Corner is set at E. side of wire fence, bearing N. 9° E. and S. 9° W.</p>
	<p>N. 0° 45' W., beginning new measurement.</p>
10.015	<p>Point for the S-N 1/64 sec. cor. of secs. 9 and 10.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R25E S N 1/64 S 9 S 10</p>
	<p style="text-align: center;">1973</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 21¼° E., 14 lks. dist., mkd. 1/64 S10 BT.</p>
	<p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 77 3/4° W., 68 lks. dist., mkd. 1/64 S9 BT.</p>
10.16	<p>Fence bears generally W. and E., 1.50 chs. to cor. fences bearing W. and S. 9° W. Enter Carlock Ranch.</p>
20.03	<p>Point for the N 1/16 sec. cor. of secs. 9 and 10, not monumented.</p>
39.90	<p>Graded road, bears S. 77° E., and N. 77° W., 70 lks. dist. to corner, whence roads bear S. 70° E., S. and on curve to N. 20° E.</p>
40.06	<p>The cor. of secs. 3, 4, 9, and 10, marked by an iron post, 1½ ins. diam., protruding 10 ins. above the ground, with brass cap 3 ins. diam., mkd.</p>
	<p style="text-align: center;">CARLOCK SECTIONS <u>4 3</u> 9 10 T9N R25E G&amp;SRBM</p>
	<p style="text-align: center;">Lic No 1476</p>
	<p>This corner is reported set at the locally accepted original corner. The corner was monumented for Carlock Brothers, and certified by Michael P. Weir, Registered Land Surveyor, in July, 1970, in Weir Engineering Company Job No. 2018 Certificate No. 7247. This point is accepted as the best available evidence of the original corner position.</p>
	<p>This corner is not disturbed.</p>
	<p>From the cor. of secs. 2, 3, 10, and 11, S. 89° 46' W., between secs. 3 and 10.</p>
	<p>Through pine timber, over nearly level land crossing Carlock Ranch.</p>
19.98	<p>Point for the E 1/16 sec. cor. of secs. 3 and 10, not monumented.</p>



Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
20.00	Small pond bears S., 150 lks. dist. Trail road bears W. from pond.
39.96	Point for the 1/4 sec. cor. of secs. 3 and 10, determined at proportionate distance. There is no evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T9N R25E $\frac{1}{4} \begin{array}{r} S 3 \\ S 10 \end{array}$ 1973
	from which
	A pine, 8 ins. diam., bears N. 4° E., 45 lks. dist., mkd. 1/4 S3 BT.
	A pine, 8 ins. diam., bears S. 79° E., 11 lks. dist., mkd. 1/4 S10 BT.
	Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the corner.
43.00	Pulcifer Creek, dry, course N. 12° W., over nearly level land in open park.
59.94	Point for the W 1/16 sec. cor. of secs. 3 and 10, not monumented.
78.00	Fence, bears N. 77° W. and S. 77° E.
79.92	The cor. of secs. 3, 4, 9, and 10.
	N. 0° 23' W., between secs. 3 and 4.
	Along E. side graded road, through open grassy area.
2.20	Graded road, bears S. 20° W. and N. 20° E.
10.00	Drain, dry, course N. 10° E. to NE.
10.75	Same road on curve from SE. to N. 50° W., continue over nearly level land through pine timber and cleared areas. Buildings at Carlock Ranch are about 10 chs. NW. of line.
34.80	Center of small dirt tank, about 50 ft. wide on W. side of line.
36.70	Center of small dirt tank, about 50 ft. wide on W. side of line.
38.00	Leave open park, enter pine timber, bears NW. and NE.
40.19	The 1/4 sec. cor. of secs. 3 and 4, marked by a rough basalt stone, 16x10x7 ins., set in a mound of stone, mkd. 1/4 on the W. face.

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid underlying rock, supported in a mound of stone, 3½ ft. base, 2 ft. high to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E ¼ S 4   S 3</p> <p style="text-align: center;">1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 38¼° E., 32 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A pine, 28 ins. diam., bears S. 35° W., 94 lks. dist. This tree has been blazed and mkd. 1/4 S4 BT. The blaze and marks indicate it has been marked for over 70 years. (It is not a bearing tree of record)</p> <p style="padding-left: 40px;">Bury the old stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 7° 40' W., beginning new measurement.</p> <p>Over nearly level land through pine timber.</p> <p>1.50 Abandoned track road, bears NE. and SW.</p> <p>39.60 Center of electric power transmission line, bears S. 89° 30' E. and N. 89° W.</p> <p>40.08 The cor. of secs. 3, 4, 33, and 34, on the N. boundary of the township, hereinbefore described.</p>
	<p>From the cor. of secs. 3, 4, 9, and 10,</p> <p>S. 89° 28' W., between secs. 4 and 9.</p> <p>0.36 Center of graded road, bears N. 17° E. and S. 17° W., 1.00 ch. to corner, whence roads bear N. 17° E., S. 73° E., and generally S.</p> <p>19.10 Fence, bears S. and N. 5° E., leave Carlock Ranch.</p> <p>19.17 An iron pipe, 1½ ins. diam., protruding 8 ins. above the ground.</p> <p>19.515 Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E E 1/16 <math>\frac{S\ 4}{S\ 9}</math></p> <p style="text-align: center;">1973</p>

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A pine, 9 ins. diam., bears N. 76° E., 21 lks. dist., mkd. 1/16 S4 BT.</p> <p>A pine, 14 ins. diam., bears S. 14¼° W., 37 lks. dist., mkd. 1/16 S9 BT.</p> <p>39.03 The 1/4 sec. cor. of secs. 4 and 9, marked by a basalt stone, 12x8x4 ins., in a mound of stone, mkd. 1/4 on the N. face, from which original bearing trees:</p> <p>An oak, 30 ins. diam., bears S. 31° W., 34 lks. dist., mkd. 1/4 S. BT. (record, S. 72° W., 33 lks.)</p> <p>A pine, 12 ins. diam., bears NORTH, 7 lks. dist., mkd. X BT. Tree scarred by old overgrown fence wires.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E S4 ¼S9</p> <p style="text-align: center;">1973</p> <p>Bury the old stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 26' W., beginning new measurement.</p> <p>Along broken northerly slopes, through timber.</p>	
<p>37.02</p>	<p>The cor. of secs. 4, 5, 8, and 9, marked by a rough basalt stone, 15x10x8 ins., set in a mound of stone, mkd. with 5 grooves on the S. face and 5 grooves on the E. edge, from which original bearing trees:</p> <p>A dead pine, 25 ins. diam., bears N. 14° E., 143 lks. dist., mkd. 9N 25E S4 BT. (record, N. 14° E., 42 lks.)</p> <p>A dead pine, 30 ins. diam., bears S. 11½° W., 100 lks. dist., with overgrown blaze. A new blaze is mkd. T9N R25E S8 BT. RCJ 565K 2-21-46. (record, S. 12° W., 100 lks.)</p> <p>A dead pine, 24 ins. diam., bears N. 16 ¾° W., 89 lks. dist., mkd. S5 BT. (record, N. 17° W., 87 lks.)</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E S 5   S 4 S 8   S 9</p> <p style="text-align: center;">1973</p>	

Dependent Resurvey of a Portion  
of the Subdivisional Lines  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which new bearing trees:</p> <p>A pine, 6 ins. diam., bears N. 35 3/4° E., 27 lks. dist., mkd. T9N R25E S4 BT.</p> <p>A pine, 8 ins. diam., bears S. 42 1/4° E., 31 lks. dist., mkd. T9N R25E S9 BT. -</p> <p>A pine, 5 ins. diam., bears S. 79 1/4° W., 19 lks. dist., mkd. T9N R25E S8 BT.</p> <p>A pine, 5 ins. diam., bears N. 28° W., 23 lks. dist., mkd. T9N R25E S5 BT.</p> <p>Bury the old stone alongside the iron post.</p>	
	<p>N. 6° 46' W., between secs. 4 and 5.</p>	
	<p>Descend northerly slopes, through pine timber.</p>	
<p>39.00</p>	<p>Sepulveda Creek, dry, course N. 70° E. to N. 30° E.</p>	
<p>40.37</p>	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, determined at proportionate distance. There is no evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to underlying rock, supported in a mound of stone, 3 ft. base, 1 1/2 ft. high to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E 1/4 S 5   S 4  1973</p>	
	<p>from which</p> <p>A pine, 10 ins. diam., bears S. 78° E., 39 lks. dist., mkd. 1/4 S4 BT.</p> <p>A pine, 18 ins. diam., bears N. 48 1/2° W., 80 lks. dist., mkd. 1/4 S5 BT.</p> <p>Continue bearing and distance.</p> <p>Along northerly slopes along W. side of dry creek.</p>	
<p>62.50</p>	<p>Graded road, bears N. 45° E. to Vernon and S. 50° W. to McNary.</p>	
<p>81.05</p>	<p>The cor. of secs. 4, 5, 32, and 33, on the N. boundary of the township, hereinbefore described.</p>	
	<p>Subdivision of Section 3</p>	
<p>40.25</p>	<p>From the 1/4 sec. cor. of secs. 3 and 10, N. 4° 18' W., along the N. and S. center line of sec. 3.</p> <p>Point for the center 1/4 sec. cor. of sec. 3, at the intersection with the E. and W. center line.</p>	

Subdivision of Section 3  
 Township 9 North, Range 25 East  
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to solid underlying rock, supported in a mound of stone, 4 ft. base, 2 ft. high to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E                      C ¼                      S 3</p> <p style="text-align: center;">1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 12½° E., 48 lks. dist., mkd. C ¼ S3 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 63¼° W., 22 lks. dist., mkd. C ¼ S3 BT.</p>
60.23	<p>Point for the C-N 1/16 sec. cor. of sec. 3.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E                      C                      N 1/16   S 3                      C</p> <p style="text-align: center;">1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 39¼° E., 20 lks. dist., mkd. C N 1/16 S3 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 63¼° E., 33 lks. dist., mkd. C N 1/16 S3 BT.</p>
80.26	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N. boundary of the township, hereinbefore described.</p>
42.80	<p>From the 1/4 sec. cor. of secs. 2 and 3,                      S. 89° 50' W., along the E. and W. center line of sec. 3.</p>
80.01	<p>The center 1/4 sec. cor. of sec. 3.</p>
80.01	<p>The 1/4 sec. cor. of secs. 3 and 4.</p>
41.18	<p>From the N 1/16 sec. cor. of secs. 2 and 3,                      S. 89° 38' W., along the E. and W. center line of the NE¼ of sec. 3.</p> <p>The C-N 1/16 sec. cor. of sec. 3.</p>
	<p style="text-align: center;">Subdivision of Section 4</p>
	<p>From the 1/4 sec. cor. of secs. 4 and 9,</p>

Subdivision of Section 4  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	N. 4° 36' W., along the N. and S. center line of sec. 4.	
40.69	Point for the center 1/4 sec. cor. of sec. 4, at the intersection with the E. and W. center line.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to solid underlying rock, supported in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.	
	T9N R25E	
	C ¼	
	S 4	
	1973	
	from which	
	A pine, 8 ins. diam., bears N. 37 3/4° E., 16 lks. dist., mkd. C ¼ S4 BT.	
	A pine, 12 ins. diam., bears N. 38½° W., 22 lks. dist., mkd. C ¼ S4 BT.	
79.71	The 1/4 sec. cor. of secs. 4 and 33, on the N. boundary of the township, hereinbefore described.	
	From the 1/4 sec. cor. of secs. 3 and 4,	
	N. 89° 59' W., along the E. and W. center line of sec. 4.	
21.01	Point for the C-E 1/16 sec. cor. of sec. 4.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base, 1 ft. high, with brass cap mkd.	
	T9N R25E	
	E 1/16	
	C ————— C	
	S 4	
	1973	
	from which	
	A pine, 5 ins. diam., bears S. 81° E., 12 lks. dist., mkd. X BT.	
	An oak, 12 ins. diam., bears S. 6° W., 15 lks. dist., mkd. C E 1/16 S4 BT.	
42.02	The center 1/4 sec. cor. of sec. 4.	
80.54	The 1/4 sec. cor. of secs. 4 and 5.	
	From the C-E 1/16 sec. cor. of sec. 4.	
	N. 6° 09' W., along the N. and S. center line of the NE¼ of sec. 4.	
39.54	The E 1/16 sec. cor. of secs. 4 and 33, on the N. boundary of the township, hereinbefore described.	

Subdivision of Section 4  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
40.41	<p>From the E 1/16 sec. cor. of secs. 4 and 9, N. 2° 30' W., along the N. and S. center line of the SE<math>\frac{1}{4}</math> of sec. 4.</p> <p>The C-E 1/16 sec. cor. of sec. 4.</p>
<p>Subdivision of Section 10</p>	
38.75	<p>From the 1/4 sec. cor. of secs. 10 and 15, N. 0° 48' W., along the N. and S. center line of sec. 10.</p> <p>Point for the center 1/4 sec. cor. of sec. 10, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E C <math>\frac{1}{4}</math> S 10  1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 56° W., 70 lks. dist., mkd. C <math>\frac{1}{4}</math> S10 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 78<math>\frac{1}{2}</math>° W., 94 lks. dist., mkd. C <math>\frac{1}{4}</math> S10 BT.</p>
58.73	<p>Point for the C-N 1/16 sec. cor. of sec. 10, not monu- mented.</p>
68.72	<p>Point for the C-N-N 1/64 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E C NN   S10 1/64   C</p> <p style="text-align: center;">1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 15<math>\frac{1}{4}</math>° W., 10 lks. dist., mkd. 1/64 S10 BT.</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears S. 70<math>\frac{1}{4}</math>° W., 75 lks. dist., mkd. 1/64 S10 BT.</p>
78.71	<p>The 1/4 sec. cor. of secs. 3 and 10.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 10 and 11, S. 89° 37' W., along the E. and W. center line of sec. 10.</p>

Subdivision of Section 10  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
19.25	Point for the C-E 1/16 sec. cor. of sec. 10, not monumented.
38.50	The center 1/4 sec. cor. of sec. 10.
58.50	Point for the C-W 1/16 sec. cor. of sec. 10, not monumented.
78.50	The 1/4 sec. cor. of secs. 9 and 10.
	From the point for the C-E 1/16 sec. cor. of sec. 10. N. 0° 15' E., along the N. and S. center line of the NE $\frac{1}{4}$ of sec. 10.
19.95	Point for the NE 1/16 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the NE $\frac{1}{4}$ , not monumented.
29.925	Point for the C-N-NE 1/64 sec. cor. of sec. 10, not monumented.
39.90	The point for the E 1/16 sec. cor. of secs. 3 and 10.
	From the N 1/16 sec. cor. of secs. 10 and 11. S. 89° 41' W., along the E. and W. center line of the NE $\frac{1}{4}$ of sec. 10.
9.81	Point for the C-E-NE 1/64 sec. cor. of sec. 10.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.  T9N R25E C E NE 1/64 S 10  1973  from which  A pine, 5 ins. diam., bears N. 67° E., 35 lks. dist., mkd. X BT.  A pine, 5 ins. diam., bears S. 29° W., 56 lks. dist., mkd. X BT.
19.62	The point for the NE 1/16 sec. cor. of sec. 10.
39.23	The point for the C-N 1/16 sec. cor. of sec. 10.
	From the C-E-NE 1/64 sec. cor. of sec. 10. N. 0° 47' E., along the N. and S. center line of the NE $\frac{1}{4}$ NE $\frac{1}{4}$ of sec. 10.
9.97	Point for the NE-NE 1/64 sec. cor. of sec. 10.  Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 ft. high, with brass cap mkd.



Subdivision of Section 10  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T9N R25E NE NE 1/64 S 10  1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 86° E., 20 lks. dist., mkd. 1/64 S10 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 2¼° W., 37 lks. dist., mkd. 1/64 S10 BT.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89° 43' W., along the E. and W. center line of the NE¼NE¼ of sec. 10.</p> <p>9.90 The point for the C-N-NE 1/64 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89° 43' W., along the E. and W. center line of the NW¼NE¼ of sec. 10.</p> <p>19.79 The C-N-N 1/64 sec. cor. of sec. 10.</p>	
	<p>From the point for the C-W 1/16 sec. cor. of sec. 10.</p> <p>N. 0° 46' W., along the N. and S. center line of the NW¼ of sec. 10.</p> <p>10.00 Point for the C-S-NW 1/64 sec. cor. of sec. 10.</p> <p>20.00 Point for the NW 1/16 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the NW¼, not monumented.</p> <p>40.01 The point for the W 1/16 sec. cor. of secs. 3 and 10.</p>	
	<p>From the point for the C-N 1/16 sec. cor. of sec. 10.</p> <p>S. 89° 41' W., along the E. and W. center line of the NW¼ of sec. 10.</p> <p>9.995 Point for the C-E-NW 1/64 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E C E NW 1/64 S 10  1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 5½° W., 38 lks. dist., mkd. 1/64 S10 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 78 ¾° W., 70 lks. dist., mkd. 1/64 S10 BT.</p>	

Subdivision of Section 10  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS	
<p>14.993</p>	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the corner.</p> <p>Point for the C-W-E-NW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E C W E NW 1/256 S 10 1973</p> <p>from which</p> <p>A pine, 10 ins. diam., bears N. 75½° E., 17 lks. dist., mkd. 1/256 S10 BT.</p> <p>A pine, 8 ins. diam., bears N. 48 ¾° W., 23 lks. dist., mkd. 1/256 S10 BT.</p>
<p>19.99</p>	<p>The point for the NW 1/16 sec. cor. of sec. 10.</p>
<p>39.98</p>	<p>The point for the N 1/16 sec. cor. of secs. 9 and 10.</p>
<p>9.99</p>	<p>Point for the NE-NW 1/64 sec. cor. of sec. 10.</p>
<p>10.00</p>	<p>The C-E-NW 1/64 sec. cor. of sec. 10.</p>
	<p>From the C-N-N 1/64 sec. cor. of sec. 10, S. 89° 43' W., along the E. and W. center line of the NE¼NW¼ of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E NE NW 1/64 S 10 1973</p> <p>from which</p> <p>A pine, 12 ins. diam., bears S. 87½° E., 56 lks. dist., mkd. 1/64 S10 BT.</p> <p>A pine, 16 ins. diam., bears S. 8° W., 58 lks. dist., mkd. 1/64 S10 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, NW. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0° 47' E., along the N. and S. center line of the NE¼NW¼ of sec. 10.</p>

Subdivision of Section 10  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
10.00	<p>S. 0° 47' E., along the N. and S. center line of the NW<math>\frac{1}{4}</math>SE<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>Point for the C-W-SE-NW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to solid rock, supported in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E C W SE NW 1/256 S 10  1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 51¼° E., 32 lks. dist., mkd. 1/256 S10 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 1¼° E., 37 lks. dist., mkd. 1/256 S10 BT.</p>	
5.00	<p>S. 89° 39' W., along the E. and W. center line of the SE<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>The point for the C-S-NW 1/64 sec. cor. of sec. 10.</p>	
5.00	<p>S. 89° 39' W., along the E. and W. center line of the SW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>Point for the C-E-SW-NW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E C E SW NW 1/256 S 10  1973</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 27¼° E., 84 lks. dist., mkd. 1/256 S10 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 89½° E., 59 lks. dist., mkd. 1/256 S10 BT.</p> <p>S. 0° 46' E., along the N. and S. center line of the SE<math>\frac{1}{4}</math>SW<math>\frac{1}{4}</math>NW<math>\frac{1}{4}</math> of sec. 10.</p> <p>Point for the SE-SW-NW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>	

Subdivision of Section 10  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>T9N R25E SE SW NW 1/256 S 10  1973</p>	
	<p>from which</p> <p>A pine, 8 ins. diam., bears N. 12° E., 34 lks. dist., mkd. 1/256 S10 BT.</p> <p>A pine, 6 ins. diam., bears S. 20 3/4° E., 24 lks. dist., mkd. 1/256 S10 BT.</p>	
	<p>S. 89° 38' W., along the E. and W. center lines of the SE<sup>1</sup>/<sub>4</sub>SW<sup>1</sup>/<sub>4</sub>NW<sup>1</sup>/<sub>4</sub> and the SW<sup>1</sup>/<sub>4</sub>SW<sup>1</sup>/<sub>4</sub>NW<sup>1</sup>/<sub>4</sub> of sec. 10.</p>	
<p>10.00</p>	<p>Point for the SW-SW-NW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
	<p>T9N R25E SW SW NW 1/256 S 10  1973</p>	
	<p>from which</p> <p>A pine, 8 ins. diam., bears S. 52½° E., 15 lks. dist., mkd. 1/256 S10 BT.</p> <p>A pine, 12 ins. diam., bears S. 34° W., 28 lks. dist., mkd. 1/256 S10 BT.</p>	
	<p>N. 0° 45' W., along the N. and S. center line of the SW<sup>1</sup>/<sub>4</sub>SW<sup>1</sup>/<sub>4</sub>NW<sup>1</sup>/<sub>4</sub> of sec. 10.</p>	
<p>5.01</p>	<p>Point for the C-W-SW-NW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p>T9N R25E C W SW NW 1/256 S 10  1973</p>	
	<p>from which</p> <p>A pine, 8 ins. diam., bears N. 32 3/4° E., 28 lks. dist., mkd. 1/256 S10 BT.</p> <p>A pine, 12 ins. diam., bears S. 38 3/4° E., 17 lks. dist., mkd. 1/256 S10 BT.</p>	
	<p>S. 89° 39' W., along the E. and W. center line of the SW<sup>1</sup>/<sub>4</sub>NW<sup>1</sup>/<sub>4</sub> of sec. 10.</p>	

Subdivision of Section 10  
Township 9 North, Range 25 East  
Gila and Salt River Meridian, Arizona

CHAINS

5.00

The S-N 1/64 sec. cor. of secs. 9 and 10.

## General Description

The terrain encompassed by this survey is nearly level with scattering pine and scrub juniper timber. Sepulveda Creek flows northerly through section 4 and Pulcifer Creek flows northerly through section 3.

The area is accessible by an improved road from U. S. Highway No. 60 and is approximately 24 miles westnorthwest of Springerville, Arizona.

8  
8

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Christopher N. Africa	Surveying Aid
David L. Foster	Surveying Aid
Daniel J. Warren	Surveying Aid

29

CERTIFICATE OF SURVEY

(I) ~~XXX~~ Gilbert V. Olson, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of May, 1973, Supplemental Special Instructions 14th June 1973, (I) ~~(We)~~ have dependently resurveyed portions of the north boundary and subdivisional lines and subdivided certain sections of Township 9 North, Range 25 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (us) and under (my) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 1, 1974  
(Date)

*Gilbert V. Olson*  
GILBERT V. OLSON (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date JUL 3 1974

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the north boundary and subdivisional lines with the subdivision of certain sections of Township 9 North, Range 25 East, Gila and Salt River Meridian, Arizona

executed by Gilbert V. Olson, Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JUN 5 1975  
(Date)

*Bernard W. Fisher*  
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626