

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# FIELD NOTES

of

REMONUMENTATION

in

Township 24 North, Range 3 East

Township 27 North, Range 5 East

Township 28 North, Range 5 East

Of the Gila and Salt River Meridian,

In the State of Arizona

### EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Under special instructions dated May 29, 19 73, approved May 29, 1973,

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 559, and assignment instructions dated May 29, 19 73.

Survey commenced June 4, 19 73

Survey completed June 14, 19 73

BOOK 5008

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

119

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

# INDEX TO SECTION CORNER MONUMENTS

Tp. 24 N R. 3E Mer. G&SRM., Ariz.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 27N R. 5E Mer. G&SRM., Ariz.

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 28N R. 5E Mer. G&SRM., Ariz.

6	24	17	4	16	14	1	
7	23	23	9	15	13	11	7
18	17	16	15	14	13		
19	20	17	21	22	23	24	
30	18	29	28	27	26	25	
31	32	33	34	35	36		

13

## Township 24 North; Range 3 East, G&amp;SRM., Arizona

## CHAINS

The following field notes are those of remonumentation of cadastral survey corners in Township 24 North, Range 3 East, Township 27 North, Range 5 East and Township 28 North, Range 5 East, G&SRM., Arizona. The remonumentation is by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The remonumentation was executed in accordance with the Manual of Surveying Instructions, 1947, and the Special Instructions for Group 559, Arizona, dated May 29, 1973. The approval of the Special Instructions on May 29, 1973, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination was  $14\frac{1}{2}^{\circ}$  East.

## Township 24 North, Range 3 East, G&amp;SRM., Arizona

The subdivisional lines were surveyed in 1883 by W. R. Fitzgerald.

Section 18 was resurveyed in 1915 by Charles D. Hodson, U.S.F.S. Surveyor-Draftsman.

Remonumentation, Subdivision, T. 24 N.,  
R. 3 E., G&SRM., Arizona

The cor. of secs. 11, 12, 13 and 14, monumented by a lava stone (record-sandstone), 14x8x6 ins., loosely set in an old mound of stone, 3 ft. base, 1 ft. high; the cor. stone is mkd. with 4 grooves on S. and 1 groove on E. faces, from which the remains of the orig. bearing trees

A pinyon pine, 16 ins. diam., bears S.  $85^{\circ}$  E., 69 lks. dist., mkd. with an overgrown blaze; (Note: record bearing and distance N.  $40^{\circ}$  E., 67 lks.)

A pinyon pine, 14 ins. diam., bears S.  $80^{\circ}$  W., 92 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 14 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T24N R3E  
S11 | S12  
S14 | S13  
1973

Remonumentation, T. 24 N., R. 3 E., G&SRM., Arizona

CHAINS

from which

A pinyon pine, 16 ins. diam., bears N.  $3\frac{1}{2}^{\circ}$  E., 149 lks. dist., mkd. T24N R3E S12 BT.

A pinyon pine, 6 ins. diam., bears N.  $61\frac{1}{2}^{\circ}$  W., 47 lks. dist., mkd. X BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 14 and 15, monumented by a red lava stone, (record-sandstone), 10x10x8 ins., mkd.  $\frac{1}{4}$  on N. face, loosely set in an old mound of stone  $2\frac{1}{2}$  ft. base, 8 ins. high, from which the orig. bearing tree

A pinyon pine, 14 ins. diam., dead and standing, bears N.  $68^{\circ}$  E., 33 lks. dist., mkd.  $\frac{1}{4}$  S BT (Note: record N.  $40^{\circ}$  E.)

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, in a collar of stone to top, 2 ft. base, brass cap mkd.

T24N R3E

$\frac{1}{4}$   
S15 | S14  
1973

from which

A ponderosa pine, 6 ins. diam., bears S.  $62^{\circ}$  W., 93 lks. dist., mkd. X BT.

A pinyon pine, 12 ins. diam., bears N.  $32^{\circ}$  W., 21 lks. dist., mkd. X BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, monumented by a juniper post, 3 ft. long, 6 ins. diam., mkd.  $\frac{1}{4}$  S on S. face, firmly set 21 ins. in the ground, from which the remains of the resurvey bearing trees

A juniper, stump, 10 ins. diam., mkd. with a portion of a blaze (mkd. portion has been cut off) bears N.  $70^{\circ}$  E., 53 lks. dist.

A pinyon pine, 8 ins. diam., bears S.  $14^{\circ}$  W., 59 lks. dist., mkd.  $\frac{1}{4}$  S BT (Note: Resurvey record S.  $9^{\circ}55'$  W.)

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, brass cap mkd.

Remonumentation, T. 24 N., R. 3 E., G&SRM., Arizona

## CHAINS

T24N R3E

$\frac{1}{2}$  S18

S19

1973

from which

A pinyon pine, 5 ins. diam., bears North, 32 lks. dist., mkd.  $\frac{1}{2}$  S 18 BT.

Set the inverted wooden post alongside the iron post.

The cor. is located in an E-W fence line.

The  $\frac{1}{2}$  sec. cor. of secs. 17 and 18, monumented by a malpais stone, 16x12x10 ins., firmly set, mkd.  $\frac{1}{2}$  on W. face, (an old mound of stone, 3 ft. base, 1 ft. high, bears W., 3 lks. dist.,) from which the remains of the resurvey bearing trees

Portions of a juniper stump and roots, bear N. 28° E., 81 lks. dist.; the railed over tree, 18 ins. diam., is alongside, with the scribed area on inaccessible underneath side.

The remains of a juniper stump, 20 ins. diam., bears N. 46° W., 34 lks. dist.; the railed over tree, 20 ins. diam., is alongside with the scribed area on inaccessible underneath side.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, brass cap mkd.

T24N R3E

$\frac{1}{2}$

S18 | S17

1973

from which

A juniper, 12 ins. diam., bears N. 25° E., 185 lks. dist., mkd.  $\frac{1}{2}$  S17 BT.

A pinyon pine, 10 ins. diam., bears N. 16° W., 167 lks. dist., mkd.  $\frac{1}{2}$  S18 BT.

Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$  ft. high, W. of the cor.

Bury the cor. stone alongside the iron post.

The cor. of secs. 7, 8, 17 and 18, monumented by a lava stone, 15x10x6 ins., (record-sandstone) set in center of an old mound of stone, 2 $\frac{1}{2}$  ft. diam., 8 ins. high, the cor. stone is mkd. with 5 notches on E. and 4 notches on S. edges, from which the remains of the orig. bearing trees

Remonumentation, T. 24 N., R. 3 E., G&SRM., Arizona

CHAINS

The root hole of a railed over pinyon pine, 12 ins. diam., bears S. 30° E., 207 lks. dist.; the tree is mkd. T24N R3E S17 BT. (Note: record S. 10° E., 56 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top, 3 ft. base, brass cap mkd.

T24N R3E  
S7|S8  
 S18|S17  
 1973

Bury the orig. cor. stone alongside the iron post.

Township 27 North, Range 5 East, G&SRM., Arizona

The north boundary and north tier of sections were surveyed in 1900 by L. Wolfly. The remainder of the boundaries and subdivisional lines were resurveyed in 1916 by Matthews and Wolff.

The mean magnetic declination is 14½° East.

Remonumentation, N. Bdy., T. 27 N., R. 5 E.,  
 G&SRM., Arizona

The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented by a limestone, 17x13x10 ins., firmly set, mkd. with 2 grooves on E. and 4 grooves on W. faces, from which the remains of the orig. bearing trees

A pinyon pine, 8 ins. diam., bears N. 78° E., 74 lks. dist., mkd. T28N R5E S35 BT.

The root hole of a dead and down pinyon pine, 6 ins. diam., bears S. 52° E., 79 lks. dist.; the tree is blazed and mkd., but not legible.

A pinyon pine, 8 ins. diam., bears S. 45° W., 69 lks. dist., mkd. T27N R5E S3 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 24 ins. in the ground, brass cap mkd.

T28N R5E  
S34|S35  
 S 3|S 2  
 T27N  
 1973

## Remonumentation, T. 27 N., R. 5 E., G&amp;SRM., Arizona

## CHAINS

from which

A pinyon pine, 14 ins. diam., bears S. 66° E., 75 lks. dist., mkd. T27N R5E S2 BT.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented by a pine post, 3 ft. long., 4 ins. diam., (loosely set in an old mound of stone,) squared on top end, mkd.  $\frac{1}{4}$  S. 34 on N. face (south face is rotted away), from which the remains of the orig. bearing tree

The root hole of a dead and down pinyon pine, 6 ins. diam., bears S. 32° E., 50 lks. dist.; the tree is mkd.  $\frac{1}{4}$  S 3 BT.

The root hole of a dead and down pinyon pine, 12 ins. diam., bears N. 21 $\frac{1}{2}$ ° W., 73 lks. dist.; the tree is mkd.  $\frac{1}{4}$  S 34 BT.

At the cor. point

Set an iron post 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 6 ins. in the ground over an X chiseled on solid limestone, mound of stone to top, 4 ft. base, brass cap mkd.

T28N R5E

$\frac{1}{4}$   $\frac{S34}{S 3}$

T27N

1973

from which

A pinyon pine, 6 ins. diam., bears S. 21° W., 36 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S 3 BT.

A pinyon pine, 9 ins. diam., bears N. 2° W., 57 lks. dist., mkd.  $\frac{1}{4}$  S 34 BT.

Set the inverted orig. post alongside the iron post.

The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by a limestone, 16x14x6 ins., firmly set along the N. side of an old mound of stone, 2 $\frac{1}{2}$  ft. diam., 1 ft. high, the stone is mkd. with 3 grooves on E. and W. faces and with 6 grooves on S. face; (record calls for a post and mkd. stone.)

At the cor. point



Remonumentation, T. 27 N., R. 5 E., G&SRM., Arizona

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to top, 10 ins. in the ground, mound of stone to top, 2½ ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4}$  S33 | S34  
 $\frac{1}{4}$  S 4 | S 3  
 T27N  
 1973

Bury the orig. cor. stone alongside the iron post.

Remonumentation, Subdivision, T. 27 N.,  
 R. 5 E., G&SRM., Arizona

The ¼ sec. cor. of secs. 2 and 3, monumented by a limestone, 18x16x4 ins.; loosely set, mkd. ¼ on W. face, from which the orig. bearing tree

A juniper, 10 ins. diam., bears S. 87° E., 94 lks. dist., mkd. ¼ S 2 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 24 ins. in the ground, brass cap mkd.

T27N R5E  
 $\frac{1}{4}$   
 S3 | S2  
 1973

Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 3 and 10, monumented by a pine post, 15 ins. long, 3 ins. square, loosely set in an old mound of stone, 3½ ft. base, 1 ft. high; the post is mkd. ¼ S3 on N. face and S10 on S. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, over an X chiseled on solid limestone, mound of stone to top 3½ ft. base, brass cap mkd.

T27N R5E  
 $\frac{1}{4}$  S 3  
 S10  
 1973

from which

A pinyon pine, 6 ins. diam., bears S. 74° W., 83 lks. dist., mkd. ¼ S 10 BT.

## Remonumentation, T. 27 N., R. 5 E., G&amp;SRM., Arizona

## CHAINS

Deposit the orig. pine post in the mound alongside the iron post.

The cor. is located 2 lks. N. of an E-W fenceline.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, monumented by a limestone, 16x12x4 ins. loosely set, mkd.  $\frac{1}{2}$  S on W. face from which the orig. bearing trees

A juniper, 14 ins. diam., bears N.  $53^{\circ}$  E., 175 lks. dist., partly overgrown blaze marks visible, but not legible.

A pinyon pine, 22 ins. diam., bears N.  $60\frac{1}{2}^{\circ}$  W., 176 lks. dist., partly overgrown blaze marks visible, but not legible.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 8 ins. in the ground, mound of stone to top,  $2\frac{1}{2}$  ft. base, brass cap mkd.

T27N R5E

$\frac{1}{4}$   
S 4 | S 3  
1973

Bury the orig. cor. stone alongside the iron post.

Township 28 North, Range 5 East, G&SRM., Arizona

The east, south and west boundaries and the subdivisional lines were surveyed in 1900 by L. Wolfly.

The mean magnetic declination is  $14\frac{1}{2}^{\circ}$  East.

Remonumentation, E. bdy., T. 28 N., R. 5 E.,  
G&SRM., Arizona

The cor. of secs. 1, 6, 7 and 12, on the E. bdy. of the Tp., monumented by a limestone, 24x20x6 ins., firmly set, mkd. with 5 grooves on S. and 1 groove on N. faces, from which the remains of the orig. bearing trees

A pinyon pine, 10 ins. diam., bears N.  $14\frac{3}{4}^{\circ}$  E., 49 lks. dist., mkd. T28N R6E S6 BT.

A pinyon pine, 24 ins. diam., bears S.  $34^{\circ}$  E., 56 lks. dist., mkd. T28N R6E S7 BT.

The root hole of a dead and down pinyon pine, 12 ins. diam., bears S.  $50^{\circ}$  W., 53 lks. dist.; the tree is mkd. T28N R5E S12 BT.

A pinyon pine, 30 ins. diam., bears N.  $27^{\circ}$  W., 37 lks. dist., mkd. T28N R5E S1 BT.

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 20 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N  
R5E R6E  
S 1 | S 6  
S12 | S 7  
1973

from which

A pinyon pine, 10 ins. diam.; bears S. 32° W., 75 lks. dist., mkd. T28N R5E S12 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The cor. is located 10 lks. SW. of a cor. of fences extending N. and E.

Remonumentation, W. Bdy., T. 28 N., R. 5 E.,  
G&SRM., Arizona

The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented by a limestone, 18x14x12 ins., firmly set, mkd. with 5 grooves on N. face and 1 groove on S. face, from which the remains of the orig. bearing trees

The root hole of a dead and down railed over juniper, 13 ins. diam., bears N. 55° E., 71 lks. dist.; the tree is mkd. T28N R5E S30 BT.

The root hole of a railed out bearing tree, (tree not found) bears S. 35° E., 110 lks. dist.

The root hole of a dead and down railed over pinyon pine, 12 ins. diam., bears S. 13° W., 65 lks. dist., the tree is mkd. T28N R4E S36 BT.

The root hole of a dead and down railed over pinyon pine, 8 ins. diam., bears N. 65° W., 62 lks. dist., the tree is mkd. T28N R4E S25 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 20 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.

T28N  
R4E R5E  
S25 | S30  
S36 | S31  
1973

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

Deposit the orig. cor. stone in the mound alongside the iron post.

The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp., monumented by a limestone, 14x12x6 ins., firmly set, mkd. with 2 notches on S. and 4 notches on N. edges, from which the orig. bearing trees

• A pinyon pine, 14 ins. diam., bears N. 62½° E., 265 lks. dist., mkd. T28N R5E S19 BT.

• A pinyon pine, 24 ins. diam., bears N. 4½° W., 253 lks. dist., mkd. T28N R4E S24 BT.

• A re-bar, 3/8 ins. diam., projecting 8 ins. above ground, bears N. 5° W.; 11.7 lks. dist., origin unknown.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 24 ins. in the ground, collar of stone to top, 1½ ft. base, brass cap mkd.

T28N  
R4E R5E  
S24 | S19  
S25 | S30  
1973

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by a limestone, 28x14x6 ins. firmly set in a mound of stone, 2½ ft. diam., 1 ft. high; the stone is mkd. with 3 grooves on N. and S. faces, from which the orig. bearing trees

A pinyon pine, 14 ins. diam., bears N. 32½° E., 41 lks. dist., mkd. T28N R5E S18 BT.

A pinyon pine, 14 ins. diam., bears S. 8° E., 33 lks. dist., mkd. T28N R5E S19 BT.

A pinyon pine, 10 ins. diam., bears S. 46° W., 52 lks. dist., partly overgrown marks visible, not legible.

A pinyon pine, 12 ins. diam., bears N. 74¾° W., 86 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 12 ins. in the ground, mound of stone to top, 3½ ft. base, brass cap mkd.

T28N  
R4E R5E  
S13 | S18  
S24 | S19  
1973

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

CHAINS

Deposit the orig. cor. stone in the mound alongside the iron post.

Remonumentation, Subdivision, T. 28 N.,  
R. 5 E., G&SRM., Arizona

The cor. of secs. 11, 12, 13 and 14, monumented by the remains of a pine post, 2 ft. long, 4 ins. diam., rotted and weathered, no visible marks, found lying on the ground; at same place find base of same post under the surface of the ground, from which the orig. bearing trees

A ponderosa pine, 30 ins. diam., bears N.  $7\frac{1}{2}^{\circ}$  E., 305 lks. dist., partly overgrown blaze, marks visible, not legible.

A pinyon pine, 14 ins. diam., bears S.  $21\frac{1}{2}^{\circ}$  E., 144 lks. dist., mkd. with an overgrown blaze.

A juniper, 10 ins. diam., bears S.  $19\frac{1}{2}^{\circ}$  W., 127 lks. dist., partly overgrown blaze, marks visible, not legible.

A pinyon pine, 36 ins. diam., bears N.  $34\frac{3}{4}^{\circ}$  W., 113 lks. dist., mkd. T28N R5E S11 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 12 ins. in the ground to bedrock, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E  
S11 | S12  
S14 | S13  
1973

from which

A ponderosa pine, 12 ins. diam., bears S.  $30\frac{3}{4}^{\circ}$  E., 96 lks. dist., mkd. T28N R5E S13 BT.

Deposit the remains of the orig. pine post in the mound alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 11 and 12, monumented by a weathered pine post, 3 ins. diam., projecting 18 ins. above the surface, no visible markings, remnants of the old post below the surface, from which the orig. bearing trees

A pinyon pine, 24 ins. diam., bears S.  $42\frac{1}{2}^{\circ}$  E., 30 lks. dist., mkd.  $\frac{1}{4}$  S 12 BT.

A pinyon pine, 14 ins. diam., bears N.  $30\frac{1}{2}^{\circ}$  W., 13 lks. dist., mkd.  $\frac{1}{4}$  S 11 BT.

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

## CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 24 ins. in the ground, collar of stone to top, 2 ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4}$   
 S11 | S12  
 1973

Bury the remains of the orig. pine post alongside the iron post.

The cor. of secs. 1, 2, 11 and 12 monumented by an old mound of stone, 2½ ft. diam., (no trace of the orig. pine post) from the center of which the remains of the orig. bearing trees

The root hole of a dead and down pinyon pine, 6 ins. diam., bears S. 68° E., 15 lks. dist., the tree is mkd. T28N R5E S12 BT.

A pinyon pine, 12 ins. diam., bears S. 65° W., 29 lks. dist., mkd. T28N R5E S11 BT.

At the cor. point

Set an iron post 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 6 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E  
 S 2 | S 1  
 S11 | S12  
 1973

from which

A juniper, 10 ins. diam., bears N. 30½° E., 95½ lks. dist., mkd. T28N R5E S1 BT.

A pinyon pine, 8 ins. diam., bears S. 38° E., 92½ lks. dist., mkd. T28N R5E S12 BT.

A juniper, 18 ins. diam., bears N. 25° W., 84 lks. dist., mkd. T28N R5E S2 BT.

The cor. of secs. 10, 11, 14 and 15, monumented by a limestone, 16x12x6 ins., loosely set in an old mound of stone, 3½ ft. diam., 1 ft. high; the cor. stone is mkd. with 2 grooves on E. face and 4 grooves on S. face, from which the remains of the orig. bearing trees

The stump of a pinyon pine, 16 ins. diam., dead and down, bears N. 77° E., 33 lks. dist., mkd. T28N R5E S11 BT.

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

A pinyon pine, 14 ins. diam., bears S.  $49\frac{1}{2}^{\circ}$  E., 72 lks. dist., mkd. T28N R5E S14 BT.

A pinyon pine, 12 ins. diam., bears S.  $50\frac{3}{4}^{\circ}$  W., 86 lks. dist., mkd. T28N R5E S15 BT.

A pinyon pine, 16 ins. diam., bears N.  $54\frac{1}{2}^{\circ}$  W., 65 lks. dist., mkd. T28N R5E S10 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 4 ins. in the ground to bedrock, mound of stone to top, 4 ft. base, brass cap mkd.

T28N R5E  
 $\frac{S10}{S15} | \frac{S11}{S14}$   
 1973

from which

A pinyon pine, 10 ins. diam., bears N.  $50\frac{1}{2}^{\circ}$  E., 85 lks. dist., mkd. T28N R5E S11 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 11 and 14, monumented by a pine post, 36 ins. long, 4 ins. diam., fallen over, mkd. S 14 on a face, from which the remains of the orig. bearing trees

A pinyon pine, 6 ins. diam., bears S.  $6\frac{1}{2}^{\circ}$  E., 23 lks. dist., mkd.  $\frac{1}{4}$  S 14 BT.

The root hole of a pinyon pine, 6 ins. diam., dead and down, bears N.  $26\frac{3}{4}^{\circ}$  W., 12 lks. dist.; the tree is mkd.  $\frac{1}{4}$  S 11 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 10 ins. in the ground to bedrock, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4} \frac{S11}{S14}$   
 1973

from which

A pinyon pine, 7 ins. diam., bears N.  $50^{\circ}$  E., 4 lks. dist., mkd.  $\frac{1}{4}$  S 11 BT.

Set the inverted orig. post alongside the iron post.

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

## CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, monumented by a limestone, 18x16x6 ins., loosely set, mkd.  $\frac{1}{4}$  S., from which the orig. bearing trees

A ponderosa pine, 18 ins. diam., bears N.  $82\frac{1}{2}^{\circ}$  E., 265 lks. dist., (Record 245 lks.) mkd. with an overgrown blaze.

A ponderosa pine, 24 ins. diam., dead and standing, bears S.  $85\frac{1}{2}^{\circ}$  W., 360 lks. dist., (Record 340 lks.) mkd.  $\frac{1}{4}$  S 10 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 22 ins. in the ground, brass cap mkd.

T28N R5E

$\frac{1}{4}$   
S10 | S11  
1972

from which

A ponderosa pine, 7 ins. diam., bears N.  $8^{\circ}$  W., 15 lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

Bury the orig. cor. stone alongside the iron post.

The cor. is located at a cor. of fences extending N., E. and W.

The cor. of secs. 2, 3, 10 and 11, monumented by a limestone, 16x12x12 ins., firmly set in an old mound of stone, 3 ft. base, 1' ft. high; the cor. stone is mkd. with 2 notches on E. and 5 notches on S. edges, from which the orig. bearing trees

A ponderosa pine, 20 ins. diam., bears N.  $28\frac{1}{2}^{\circ}$  E., 87 lks. dist., mkd. T28N R5E S2 BT.

A ponderosa pine, 20 ins. diam., bears S.  $76\frac{3}{4}^{\circ}$  E., 97 lks. dist., mkd. with an overgrown blaze.

A ponderosa pine, 22 ins. diam., bears S.  $24^{\circ}$  W., 50 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 14 ins. in the ground, mound of stone to top,  $3\frac{1}{2}$  ft. base, brass cap mkd.

T28N R5E

$\frac{S3}{S2}$   
S10 | S11  
1973

from which



Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

A ponderosa pine, 12 ins. diam.; bears S. 80° E.,  
97 lks. dist., mkd. T28N R5E S11 BT.

A ponderosa pine, 6 ins. diam., bears N. 46½° W.,  
45 lks. dist., mkd. X BT.

Deposit the orig. cor. stone in the mound alongside the  
iron post.

The ¼ sec. cor. of 2 and 11, monumented by a lime-  
stone, 20x12x8 ins., loosely set, mkd. ¼ on W. face, from  
which the remains of the orig. bearing trees

A pinyon pine, 8 ins. diam., bears N. 36¼° E.,  
15 lks. dist., mkd. ¼ S 2 BT.

The root hole of a pinyon pine, 10 ins. diam., dead  
and down, bears S. 6° W., 37 lks. dist.; the tree  
is mkd. ¼ S 11 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at  
the base, and with a brass cap riveted to the top, 8 ins.  
in the ground, mound of stone to top, 3 ft. base, brass  
cap mkd.

T28N R5E

¼  $\frac{S\ 2}{S11}$

1973

from which

A pinyon pine, 12 ins. diam., bears S. 21° W., 54  
lks. dist., mkd. ¼ S 11 BT.

Deposit the orig. cor. stone in the mound alongside the  
iron post.

The ¼ sec. cor. of secs. 2 and 3, reestablished by record  
course and distance from the remains of the orig. bearing  
trees

A ponderosa pine, 22 ins. diam., bears S. 65¼° E.,  
99 lks. dist., marks overgrown.

A ponderosa pine, 16 ins. diam., bears S. 30° W.,  
87 lks. dist., marks overgrown.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged  
at the base, and with a brass cap riveted to the top, 17  
ins. in the ground, mound of stone to top, 3 ft. base,  
brass cap mkd.

T28N R5E

¼  $\frac{S3}{S2}$

1973

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

## CHAINS

from which

A ponderosa pine, 18 ins. diam., bears S. 68° E.,  
101 lks. dist., mkd.  $\frac{1}{4}$  S 2 BT.

A ponderosa pine, 14 ins. diam., bears S. 48 $\frac{1}{2}$ ° W.,  
74 lks. dist., mkd.  $\frac{1}{4}$  S 3 BT.

No trace of the orig. pine post was found.

The  $\frac{1}{4}$  sec. cor. of secs. 10 and 15, monumented by a lime-  
stone, 20x12x12 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, from  
which the orig. bearing trees

A pinyon pine, 12 ins. diam., bears N. 53° E., 43  
lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

A pinyon pine, 10 ins. diam., bears S. 43° W., 37  
lks. dist., mkd.  $\frac{1}{4}$  S 15 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged  
at the base, and with a brass cap riveted to the top, 6  
ins. in the ground, mound of stone to top, 4 ft. base,  
brass cap mkd.

T28N R5E

$\frac{1}{4}$   $\frac{S10}{S15}$

1973

Deposit the orig. cor. stone in the mound alongside the  
iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 9 and 10, monumented by a lime-  
stone, 24x16x12 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, from  
which the remains of the orig. bearing trees

A pinyon pine, 9 ins. diam., dead and standing,  
bears N. 48° E., 37 lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

A juniper, 12 ins. diam., bears N. 61° W., 30 lks.  
dist., mkd.  $\frac{1}{4}$  S 9 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged  
at the base, and with a brass cap riveted to the top, 18  
ins. in the ground, mound of stone to top, 3 ft. base,  
brass cap mkd.

T28N R5E

$\frac{1}{4}$   $\frac{S9}{S10}$

1973

from which

A pinyon pine, 6 ins. diam., bears N. 70° E., 75  
lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

CHAINS

Deposit the orig. cor. stone in the mound alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 10, monumented by a limestone, 24x12x10 ins., loosely set, mkd.  $\frac{1}{4}$  S on N. face, from which the remains of the orig. bearing trees

A partly uprooted ponderosa pine, 10 ins. diam., lying on the ground but still living, bears N. 40° E., 59 lks. dist., mkd. with an overgrown blaze.

A partly uprooted juniper, 16 ins. diam., leaning at a 45° angle, but still living, bears S. 17° W., 50 lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 6 ins. in the ground to bedrock, mound of stone to top, 3 $\frac{1}{2}$  ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4}$   $\frac{S}{S10}$   
 1973

from which

A pinyon pine, 6 ins. diam., bears S. 31° W., 55 $\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S 10 BT.

A pinyon pine, 5 ins. diam., bears N. 70° W., 26 lks. dist., mkd.  $\frac{1}{4}$  S 3 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 3 and 4, monumented by a sandstone, 16x9x8 ins., firmly set, evidence of having been run over by a tractor, mkd.  $\frac{1}{4}$  S, other markings broken off, from which the remains of the orig. bearing trees

A ponderosa pine, 24 ins. diam., bears N. 20° E., 23 lks. dist., mkd. with an overgrown blaze.  
 (Note: record N. 80 $\frac{3}{4}$ ° W., 19 lks.)

A ponderosa pine, 16 ins. diam., bears S. 49 $\frac{1}{2}$ ° E., 23 lks. dist., marks visible, partly overgrown.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 22 ins. in the ground, brass cap mkd.

T28N R5E  
 $\frac{1}{4}$   
 S4|S3  
 1973

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

CHAINS

from which

A pinyon pine, 12 ins. diam., bears N. 64° W., 80 lks. dist., mkd.  $\frac{1}{4}$  S 4 BT.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the cor.

Deposit the orig. cor. stone in the mound W. of the cor.

The  $\frac{1}{4}$  sec. cor. of secs. 20 and 21, monumented by an old pine post, 30 ins. long, 3 ins. diam., squared on one end, fallen over, too badly rotted to read the scribe marks, from which the orig. bearing tree

A pinyon pine, 12 ins. diam., bears S. 24¼° E., 274 lks. dist., mkd.  $\frac{1}{4}$  S 21 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 20 ins. in the ground, brass cap mkd.

T28N R5E

$\frac{1}{4}$

S20|S21

1973

Set the orig. pine post alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 5, monumented by a limestone, 18x12x7 ins., loosely set, marks not legible, from which the remains of the orig. bearing trees

A ponderosa pine, 18 ins. diam., bears S. 83¼° E., 120 lks. dist.; (Record 30 lks.) mkd.  $\frac{1}{4}$  S 4 BT.

The stump of a dead and down ponderosa pine, 10 ins. diam., bears S. 44½° W., 19 lks. dist., the tree is mkd.  $\frac{1}{4}$  S 5 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 14 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E

$\frac{1}{4}$

S5|S4

1973

Deposit the orig. cor. stone in the mound alongside the iron post.

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 30 and 31, monumented by a limestone, 18x14x8 ins., firmly set, mkd.  $\frac{1}{4}$  on N. face, from which the remains of the orig. bearing trees

The root hole of a pinyon pine, 12 ins. diam., dead and down, bears S.  $76\frac{1}{2}^\circ$  W., 64 lks. dist.; the tree is mkd.  $\frac{1}{4}$  S 31 BT.

A pinyon pine, 14 ins. diam., bears N.  $39\frac{1}{2}^\circ$  W., 68 lks. dist., mkd.  $\frac{1}{4}$  S 30 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 22 ins. in the ground, brass cap mkd.

T28N R5E  
 $\frac{1}{4}$   $\frac{S30}{S31}$   
 1973

from which

A juniper, 10 ins. diam., bears S.  $37\frac{1}{2}^\circ$  E.,  $25\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S 31 BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 29 and 30, monumented by a limestone, 18x12x6 ins., loosely set in a mound of stone, 2 ft. diam., 8 ins. high, from which the orig. bearing trees

A pinyon pine, 14 ins. diam., bears S.  $41\frac{1}{4}^\circ$  E., 17 lks. dist., mkd.  $\frac{1}{4}$  S 29 BT.

A pinyon pine, 14 ins. diam., bears N.  $63\frac{1}{2}^\circ$  W., 54 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 18 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4}$   
 S30|S29  
 1973

from which

A pinyon pine, 8 ins. diam., bears S.  $78^\circ$  W., 68 lks. dist., mkd.  $\frac{1}{4}$  S 30 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

The cor. of secs. 19, 20, 29 and 30, monumented by a limestone, 20x10x10 ins., firmly set, mkd. with 5 grooves on E. and 2 grooves on S. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 24 ins. in the ground, brass cap mkd.

T28N R5E  
 $\frac{S19}{S30} | \frac{S20}{S29}$   
 1973

Bury the orig. cor. stone along the W. side of the iron post.

The ¼ sec. cor. of secs. 20 and 29, monumented by a limestone, 23x9x7 ins., loosely set, mkd. ¼ on N. face, from which the remains of the orig. bearing trees

A pinyon pine, 14 ins., diam., bears N. 35° E., (Record N. 38½° E.) 31 lks. dist., mkd. with an overgrown blaze.

The root hole of a pinyon pine, 12 ins. diam., dead and down, bears S. 9° E., 91 lks. dist.; the tree is mkd. ½ S 29 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 8 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4} \frac{S20}{S29}$   
 1973

from which

A pinyon pine, 8 ins. diam., bears S. 5° E., 76 lks. dist., mkd. ½ S 29 BT.

A pinyon pine, 18 ins. diam., bears N. 61° W., 30 lks. dist., mkd. ½ S 20 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 19 and 30, monumented by a limestone, 16x10x6 ins., loosely set, mkd. ¼ S on N. face.

At the cor. point

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 24 ins. in the ground, collar of stone to top, 1½ ft. base, brass cap mkd.

T28N R5E  
¼  
S19  
S20  
1973

Bury the orig. cor. stone alongside the iron post.

The cor. is located at a cor. of fences, extending northerly and westerly.

The ¼ sec. cor. of secs. 19 and 20, monumented by a limestone, 16x10x6 ins., loosely set, marks visible but not legible, from which the orig. bearing trees

A ponderosa pine, 22 ins. diam., bears N. 71½° E., 47 lks. dist., mkd. with an overgrown blaze.

A juniper, 10 ins. diam., bears N. 32¾° W., 33 lks. dist., mkd. ¼ S 19 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 20 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.

T28N R5E  
¼  
S19 | S20  
1973

from which

A pinyon pine, 7 ins. diam., bears S. 66½° E., 39 lks. dist., mkd. ¼ S 20 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 17 and 20, monumented by a pine post, 30 ins. long, 3 ins. diam., loosely set, mkd. ¼ S 17 on N. face, from which the orig. bearing trees

A pinyon pine, 8 ins. diam., bears S. 13¾° W., 36 lks. dist., mkd. ¼ S 20 BT.

A pinyon pine, 8 ins. diam., bears N. 50¾° W., 21 lks. dist., mkd. ¼ S 17 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 18 ins. in the ground, in a collar of stone 1½ ft. base, 8 ins. high, brass cap mkd.

## Remonumentation, T. 28.N., R. 5 E., G&amp;SRM., Arizona

CHAINS

T28N R5E

 $\frac{1}{4}$  S17  
S20

1973

Set the inverted orig. pine post alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 18 and 19, monumented by a pine post, 3 ft. long, 3 ins. diam., loosely set, flattened on top end, marks visible but not legible, from which the remains of the orig. bearing trees

The root hole of a pinyon pine, 14 ins. diam., dead and down, bears N.  $22\frac{1}{2}^{\circ}$  E., 125 lks. dist.; the tree is mkd.  $\frac{1}{4}$  S 18 BT.

A pinyon pine, 16 ins. diam., bears S.  $59\frac{3}{4}^{\circ}$  W., 36 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base, and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top,  $2\frac{1}{2}$  ft. base, brass cap mkd.

T28N R5E

 $\frac{1}{4}$  S18  
S19

1973

from which

A juniper, 9 ins. diam., bears N.  $20^{\circ}$  E.,  $42\frac{1}{2}$  lks. dist., mkd.  $\frac{1}{4}$  S 18 BT.

A pinyon pine, 18 ins. diam., bears S.  $31^{\circ}$  W., 44 lks. dist., mkd.  $\frac{1}{4}$  S 19 BT.

Set the inverted orig. pine post alongside the iron post.

The cor. of secs. 7, 8, 17 and 18, monumented by a limestone, 18x15x15 ins., firmly set, mkd. with 4 grooves on S. and 5 grooves on E. faces, from which the orig. bearing trees

A pinyon pine, 10 ins. diam., bears N.  $71^{\circ}$  E., 85 lks. dist., mkd. T28N R5E S8 BT.

A pinyon pine, 14 ins. diam., bears S.  $43\frac{1}{4}^{\circ}$  E., 93 lks. dist., mkd. with an overgrown blaze.

A pinyon pine, 9 ins. diam., bears S.  $69\frac{1}{2}^{\circ}$  W., 45 lks. dist., mkd. with an overgrown blaze.

A pinyon pine, 12 ins. diam., bears N.  $25^{\circ}$  W., 41 lks. dist., mkd. T28N R5E S7 BT.

At the cor. point



Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E  
 $\frac{S}{S18} \frac{7}{S17} \frac{S}{S8}$   
 1973

from which

A pinyon pine, 11 ins. diam., bears S. 31° E., 159 lks. dist., mkd. T28N R5E S17 BT.

A pinyon pine, 7 ins. diam., bears S. 79° W., 35½ lks. dist., mkd. T28N R5E S18 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 8 and 17, monumented by a limestone, 18x12x5 ins., firmly set, mkd. ¼ on W. face, from which the orig. bearing trees

A ponderosa pine, 18 ins. diam., bears N. 86° E., 56 lks. dist., mkd. with an overgrown blaze.

A ponderosa pine, 18 ins. diam., bears S. 69° E., 77 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, mound of stone to top, 2½ ft. base, brass cap mkd.

T28N R5E  
 $\frac{1}{4} \frac{S}{S17} \frac{8}{S8}$   
 1973

from which

A ponderosa pine, 16 ins. diam., bears N. 27° E., 125 lks. dist., mkd. ¼ S 8 BT.

A ponderosa pine, 10 ins. diam., bears S. 76° E., 96 lks. dist., mkd. ¼ S 17 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 7 and 8, monumented by a limestone, 24x16x5 ins., loosely set, no visible marks, from which the orig. bearing trees

A ponderosa pine, 24 ins. diam.; bears N. 52¾° W., 132 lks. dist., mkd. ¼ S 7 BT.

## Remonumentation, T. 28 N., R. 5 E., G&amp;SRM., Arizona

CHAINS

A ponderosa pine, 20 ins. diam., dead and standing, bears S. 88° E., 72 lks. dist., mkd.  $\frac{1}{2}$  S 8 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T28N R5E

$\frac{1}{2}$

S7|S8

1973

from which

A ponderosa pine, 15 ins. diam., bears S. 74½° E., 88 lks. dist., mkd.  $\frac{1}{2}$  S 8 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The cor. of secs. 5, 6, 7 and 8, monumented by a limestone, 19x14x10 ins., firmly set, mkd. with 5 notches on E. and S. edges, from which the orig. bearing trees

A ponderosa pine, 30 ins. diam., bears N. 66½° E., 104 lks. dist., mkd. T28N R5E S5 BT.

A ponderosa pine, 30 ins. diam., bears S. 1° E., 76 lks. dist., mkd. with an overgrown blaze.

A ponderosa pine, 30 ins. diam., bears S. 30¾° W., 138 lks. dist., mkd. T28N R5E S7 BT.

A ponderosa pine, 30 ins. diam., bears N. 74¾° W., 68 lks. dist., mkd. T28N R5E S6 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, brass cap mkd.

T28N R5E

S6|S5

S7|S8

1973

Partially bury the orig. cor. stone along the W. side of the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 5 and 8, monumented by a limestone, 3x2x1½ ft., in place, mkd.  $\frac{1}{2}$  X, from which the orig. bearing trees

A pinyon pine snag, 12 ft. high, 12 ins. diam., bears S. 31° E., 26 lks. dist., mkd.  $\frac{1}{2}$  S 8 BT.

Remonumentation, T. 28 N., R. 5 E., G&SRM., Arizona

CHAINS

A ponderosa pine, 24 ins. diam., bears N. 22½° W.,  
56 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged  
at the base, and with a brass cap riveted to the top,  
14 ins. in the ground, mound of stone to top, 3 ft. base,  
brass cap mkd.

T28N R5E

¼  $\frac{S5}{S8}$   
1973

from which

A ponderosa pine, 9 ins. diam., bears S. 30° E.,  
24 lks. dist., mkd. ¼ S 8 BT.

Partially bury the orig. cor. stone in the mound along-  
side the iron post.

The ¼ sec. cor. of secs. 5 and 6, monumented by a lime-  
stone, 18x12x6 ins., firmly set, mkd. ¼ on W. face, from  
which the remains of the orig. bearing trees

A ponderosa pine, 36 ins. diam., bears N. 5¾° E.,  
51 lks. dist., mkd. ¼ S 5 BT. (Record pinyon pine)

A pine stump, 18 ins. diam., bears N. 34° W., 165  
lks. dist., mkd. ¼ S 6 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged  
at the base and with a brass cap riveted to the top, 6  
ins. in the ground to bedrock, mound of stone to top,  
4 ft. base, brass cap mkd.

T28N R5E

¼  $\frac{S6}{S5}$   
1973

Deposit the orig. cor. stone in the mound alongside the  
iron post.



CERTIFICATE OF SURVEY

(I) ~~(We)~~ Paul G. Bauer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29 day

of May, 1973, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 24 North, Range 3 East and Townships 27 and 28 North, Range 5 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~(my)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 16, 1973  
(Date)

*Paul G. Bauer*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL  
Date AUG 27 1973

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 24 North, Range 3 East and Townships 27 and 28 North, Range 5 East, all of the Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

NOV 26 1975  
(Date)

*[Signature]*  
Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in

, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626