

Form 9180-6  
(April 1974)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of

REMONUMENTATION

in

Township 30 North, Range 2 East

Township 31 North, Range 1 East

Township 31 North, Range 1 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Under special instructions dated May 29, 1973, approved May 29, 1973,

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 559, and assignment instructions dated May 29, 1973.

Survey commenced June 4, 1973

Survey completed June 14, 1973

BOOK 5010

# INDEX DIAGRAM

Township \_\_\_\_\_, Range \_\_\_\_\_,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION  
CORNER MONUMENTS

Tp. 30N R. 2E Mer. G&SRM., Ariz.

	6	5	4	3	2	1
3	7 8	8	9	10	11	12
2	18	7 17	16	15	14	13
2	19	6 20	21	22	23	24
1	30	29	5 28	27	26	25
	31	32	4 33	4 34	35	36

Tp. 31N R. 1E Mer. G&SRM., Ariz.

	6	5	4	3	2	1
	7 10	8	9	10	11	12
	18	9 10 17	16	15	14	13
9	19	20	21	22	23	24
	30	29	28	27	26	25
	31	32	33	34	35	36

Tp. 31N R. 1W Mer. G&SRM., Ariz.

		11	11	12		
6	5	14	4	13	3	2
		13	13	12		1
7	8	9	10	11	12	15
18	17	16	15	14	15	13
						14
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

12/

## Township 30 North, Range 2 East, G&amp;SRM., Arizona

## CHAINS

The following field notes are those of remonumentation of cadastral survey corners in Township 30 North, Range 2 East, Township 31 North, Range 1 East and Township 31 North, Range 1 West, G&SRM., Arizona. The remonumentation is by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b) dated October 16, 1958.

The remonumentation was executed in accordance with the Manual of Surveying Instructions, 1947, and the Special Instructions for Group 559, Arizona, dated May 29, 1973. The approval of the Special Instructions on May 29, 1973, gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541 dated April 21, 1961.

The assistants furnished by the Forest Service remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

The mean magnetic declination was  $14\frac{1}{2}^{\circ}$  East.

## Township 30 North, Range 2 East, G&amp;SRM., Arizona

The south and west boundaries and subdivisional lines were surveyed in 1900 by F. B. Jacobs.

Remonumentation, W. Bdy., T. 30 N., R. 2 E.,  
G&SRM., Arizona

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp., monumented by a limestone, 20x12x5 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, from which the orig. bearing trees

A pinyon pine, 10 ins. diam., bears N.  $12\frac{1}{2}^{\circ}$  E.,  
20 lks. dist., mkd.  $\frac{1}{4}$  SXIX BT.

A pinyon pine, 14 ins. diam., bears S.  $63\frac{1}{2}^{\circ}$  W.,  
35 lks. dist., mkd. with an overgrown blaze.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top,  $3\frac{1}{2}$  ft. base, brass cap mkd.

T30N  
R1E R2E  
 $\frac{1}{4}$   
S24 | S19  
1973

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 30 N., R. 2 E., G&SRM., Arizona

CHAINS

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented by a limestone, 24x16x4 ins., firmly set, mkd. with 3 grooves on N. and S. faces, (a mound of stone 3 ft. base, bears N., 3 lks. dist.) from which the remains of the orig. bearing trees

A pinyon pine, 10 ins. diam., dead and standing, bears N.  $2\frac{1}{2}^{\circ}$  E., 45 lks. dist., mkd. T XXXN R11E SXVIII BT.

A pinyon pine, 12 ins. diam., bears S.  $18\frac{1}{2}^{\circ}$  E., 47 lks. dist., mkd. T XXX N R11E S XIX BT.

A pinyon pine, 12 ins. diam., bears S.  $30\frac{1}{2}^{\circ}$  W., 35 lks. dist., mkd. T XXXN R1E S XXIV BT.

The root hole of a pinyon pine, 14 ins. diam., dead and down, bears N.  $63^{\circ}$  W., 37 lks. dist., the tree is mkd. T XXX N R1E S XIII BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 6 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T30N  
R1E R2E  
S13|S18  
S24|S19  
1973

from which

A pinyon pine, 12 ins. diam., bears N.  $81\frac{1}{2}^{\circ}$  E., 31 lks. dist., mkd. T30N R2E S18 BT.

A pinyon pine, 12 ins. diam., bears N.  $88^{\circ}$  W., 53 lks. dist., mkd. T30N R1E S13 BT.

Bury the orig. cor. stone in the mound alongside the iron post.

The  $\frac{1}{2}$  sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented by a sandstone, 20x12x4 ins., firmly set, mkd.  $\frac{1}{2}$  on W. face, from which the orig. bearing trees

A pinyon pine, 14 ins. diam., bears N.  $56\frac{1}{2}^{\circ}$  E., 41 lks. dist., mkd.  $\frac{1}{2}$  S XVIII BT.

A pinyon pine, 12 ins. diam.; bears S.  $79^{\circ}$  W., 60 lks. dist., mkd.  $\frac{1}{2}$  S XIII BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, collar of stone to top, 3 ft. base, brass cap mkd.

## Remonumentation, T. 30 N., R. 2 E., G&amp;SRM., Arizona

## CHAINS

T30N  
R1E R2E  
 $\frac{1}{4}$   
S13|S18  
1973

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented by a limestone, 16x8x5 ins., loosely set in an old mound of stone, 4 ft. base, mkd. with 4 grooves on S. and 2 grooves on N. faces, from which the remains of the orig. bearing trees

The root hole of a ponderosa pine, 30 ins. diam., dead and down, bears N.  $3\frac{1}{2}^{\circ}$  E., 132 lks. dist., the tree is mkd. TXXXN R1E S7 BT.

A ponderosa pine, 30 ins. diam., bears S.  $54\frac{1}{2}^{\circ}$  E., 113 lks. dist., mkd. with an overgrown blaze.

A pinyon pine, 18 ins. diam., bears S.  $63\frac{1}{2}^{\circ}$  W., 65 lks. dist., mkd. TXXXN R1E SXIII BT.

A pinyon pine, 18 ins. diam., bears N.  $35^{\circ}$  W., 70 lks. dist., mkd. TXXXN R1E SXII BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 10 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T30N  
R1E R2E  
S12|S 7  
S13|S18  
1973

from which

A pinyon pine, bears N.  $16\frac{1}{2}^{\circ}$  E., 77 lks. dist., mkd. T30N R2E S7 BT.

Bury the orig. cor. stone alongside the iron post.

Remonumentation, S. Bdy., T. 30 N., R. 2 E.,  
G&SRM., Arizona

The  $\frac{1}{4}$  sec. cor. of secs. 4 and 33, on the S. bdy. of the Tp., monumented by a sandstone, 22x12x4 ins., firmly set, mkd.  $\frac{1}{4}$  on N. face, from which the remains of the orig. bearing trees

A pinyon pine, 14 ins. diam., bears S.  $85^{\circ}$  W., 25 lks. dist., mkd.  $\frac{1}{4}$  S4 BT.

Remonumentation T. 30 N., R. 2 E., G&SRM., Arizona

CHAINS

The root hole of a pinyon pine, 8 ins. diam., dead and down, bears North, 3 lks. dist., the tree is mkd.  $\frac{1}{4}$  S BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T30N R2E  
 $\frac{1}{4}$   $\frac{S33}{S4}$   
 T29N  
 1973

Bury the orig. cor. stone in the mound alongside the iron post.

Remonumentation, Subdivision, T. 30 N.,  
 R. 2 E., G&SRM., Arizona

The  $\frac{1}{4}$  sec. cor. of secs. 33 and 34, monumented by a sandstone, 16x10x6 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, from which the orig. bearing trees

A ponderosa pine, 22 ins. diam., bears S.  $36^\circ$  E., 4 lks. dist., mkd. with an overgrown blaze.

A juniper, 12 ins. diam., bears N.  $61\frac{1}{2}^\circ$  W., 77 lks. dist., mkd.  $\frac{1}{4}$  S33 BT.

At the cor. point

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 24 ins. in the ground, brass cap mkd.

T30N R2E  
 $\frac{1}{4}$   
 S33|S34  
 1973

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 32 and 33, monumented by a limestone, 24x8x8 ins., firmly set, mkd.  $\frac{1}{4}$  on W. face, from which the orig. bearing trees

A pinyon pine, 8 ins. diam., bears East, 14 lks. dist., mkd.  $\frac{1}{4}$  S33 BT. (partially overgrown)

A juniper, 24 ins. diam., bears N.  $73^\circ$  W., 23 lks. dist., mkd.  $\frac{1}{4}$  S32 BT.

## Remonumentation, T. 30 N., R. 2 E., G&amp;SRM., Arizona

## CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 10 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T30N R2E

½  
S32 | S33  
1973

Partially bury the inverted cor. stone along the NW side of the iron post.

The cor. of secs. 28, 29, 32 and 33, monumented by a limestone, 25x9x3 ins., (loosely set in an old mound of stone, 2½ ft. base) mkd. with 1 notch on S. and 4 notches on E. edges, from which the remains of the orig. bearing trees

A ponderosa pine, 24 ins. diam., bears N. 69° E., 47 lks. dist., mkd. T30N R2E S28 BT.

A pinyon pine, 16 ins. diam., bears S. 66° E., 142 lks. dist., mkd. T30N R2E S33 BT.

A ponderosa pine, 12 ins. diam., bears N. 8° W., 69 lks. dist., mkd. with a healed blaze (Record 71 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 10 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T30N R2E

S29 | S28  
S32 | S33  
1973

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 28 and 33, monumented by a sandstone, 20x10x6 ins., firmly set, mkd. ¼ on N. face, from which the orig. bearing trees

A ponderosa pine, 14 ins. diam., bears N. 41° E., 14 lks. dist., mkd. with an overgrown blaze.

A ponderosa pine, 36 ins. diam., bears S. 70° E., 98 lks. dist., mkd. ¼ S33 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top, 3 ft. base, brass cap mkd.



Remonumentation, T. 30 N., R. 2 E., G&SRM., Arizona

CHAINS

T30N R2E

$\frac{1}{4}$   $\frac{S28}{S33}$   
1973

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 19, 20, 29 and 30, monumented by a sandstone, 23x12x6 ins., firmly set, mkd. with 5 notches on E. and 2 notches on S. edges, from which the remains of the orig. bearing trees

A juniper, 14 ins. diam., bears N. 50 $\frac{1}{2}$ ° E., 17 lks. dist., mkd. T30N R2E S20 BT.

A pinyon pine, 10 ins. diam., bears S. 58° E., 63 lks. dist., mkd. T30N R2E S29 BT; (Record pine, 12 ins. diam., S. 6 $\frac{1}{4}$ ° E., 39 lks.)

A juniper, 20 ins. diam., bears N. 82° W., 63 lks. dist., mkd. T30N R2E S19 BT. (Record cedar, 21 ins. diam., N. 60° W., 12 lks. dist.)

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, mound of stone to top, 2 $\frac{1}{2}$  ft. base, brass cap mkd.

T30N R2E  
 $\frac{S19}{S30}$  |  $\frac{S20}{S29}$   
1973

from which

A juniper, 10 ins. diam., bears S. 72 $\frac{1}{2}$ ° W., 68 lks. dist., mkd. T30N R2E S30 BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 19 and 30, monumented by a limestone, 20x8x7 ins., firmly set, mkd.  $\frac{1}{4}$  on N. face, from which the orig. bearing trees

A juniper, 18 ins. diam., bears S. 81 $\frac{1}{2}$ ° E., 19 lks. dist., mkd.  $\frac{1}{4}$  S30 BT.

A pinyon pine, 18 ins. diam., bears N. 28 $\frac{1}{2}$ ° W., 47 lks. dist., mkd.  $\frac{1}{4}$  S19 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top, 3 ft. base, brass cap mkd.

## Remonumentation, T. 30 N., R. 2 E., G&amp;SRM., Arizona

## CHAINS

T30N R2E  
 $\frac{1}{4}$   $\frac{S19}{S30}$   
 1973

Bury the orig. cor. stone alongside the iron post.

The cor. of secs. 17, 18, 19 and 20, monumented by a limestone, 18x10x5 ins., firmly set, mkd. with 5 notches on E. and 3 notches on S. edges, from which the remains of the orig. bearing trees

A ponderosa pine, 24 ins. diam., bears N. 11½° E., 72 lks. dist., mkd. with an overgrown blaze.

A ponderosa pine, 40 ins. diam., bears S. 73½° W., 52 lks. dist., mkd. T30N R2E S19 BT.

A piece of partly rotted wood, 2½ ft. long, 3 ins. diam., lying on the ground, bears N. 2° W., 29 lks. dist., mkd. 30 NR., remaining marks illegible.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 12 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T30N R2E  
 $\frac{S18}{S19} | \frac{S17}{S20}$   
 1973

from which

A ponderosa pine, 18 ins. diam., bears S. 52° E., 42 lks. dist., mkd. T30N R2E S20 BT.

A pinyon pine, 8 ins. diam., bears N. 42° W., 98 lks. dist., mkd. T30N R2E S18 BT.

Bury the orig. cor. stone alongside the iron post.

The ¼ sec. cor. of secs. 17 and 18, monumented by a sandstone, 18x8x8 ins., firmly set, mkd. ¼ on W. face, from which the orig. bearing trees

A pinyon pine, 18 ins. diam., bears S. 38° E., 106 lks. dist., mkd. ¼ S17 BT.

A ponderosa pine snag, 25 ft. high, 30 ins. diam., bears S. 50° W., 198 lks. dist., mkd. ¼ S18 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, collar of stone to top, 1½ ft. base, brass cap mkd.

## Remonumentation, T. 30 N., R. 2 E., G&amp;SRM., Arizona

CHAINS

T30N R2E

$$\frac{1}{4}$$

$$\frac{S18}{S17}$$
 1973

from which

A ponderosa pine, 18 ins. diam., bears S. 76° W., 152 lks. dist., mkd.  $\frac{1}{4}$  S 18 BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, monumented by a limestone, 12x10x6 ins., firmly set, mkd.  $\frac{1}{4}$  on N. face, from which the remains of the orig. bearing trees

The root hole of a pinyon pine, 12 ins. diam., dead and down, bears S. 1° E., 47 lks. dist., the tree is mkd.  $\frac{1}{4}$  S18 BT.

The root hole of a pinyon pine, 10 ins. diam., dead and down, blaze marks only visible, bears N. 44° E., 8 lks. dist.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, brass cap mkd.

$$T30N R2E$$

$$\frac{1}{4} \frac{S7}{S18}$$
 1973

from which

A pinyon pine, 14 ins. diam., bears S.  $\frac{1}{2}$ ° W., 52 lks. dist., mkd.  $\frac{1}{4}$  S18 BT.

A pinyon pine, 10 ins. diam., bears N. 33° W., 24 lks. dist., mkd.  $\frac{1}{4}$  S7 BT.

Bury the orig. cor. stone alongside the iron post.

Township 31 North, Range 1 East, G&amp;SRM., Arizona

The W. bdy., the Gila and Salt River Meridian, was surveyed in 1899 by W. O. Secor.

The subdivisional lines south of the Grand Canyon were surveyed in 1900 by F. B. Jacobs.

Remonumentation, W. Bdy., T. 31 N., R. 1 E.  
G&SRM., Arizona

## Remonumentation, T. 31 N., R. 1 E., G&amp;SRM., Arizona

## CHAINS

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., reestablished at record course and distance from the orig. bearing tree

A pinyon pine, 14 ins. diam., bears N. 8° E., 52 lks. dist., mkd. T31N R1E S18 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, over an X, 4 ins. diam., chiseled on solid limestone, mound of stone to top, 4 ft. base, brass cap mkd.

T31N R1E  
R1W  
S13 | S18  
S24 | S19  
1973

from which

A juniper, 14 ins. diam., bears S. 62° W., 162 lks. dist., mkd. T31N R1W S24 BT.

A pinyon pine, .5 ins. diam., bears N. 32° W., 51 lks. dist., mkd. T31N R1W S13 BT.

Remonumentation, Subdivision, T. 31 N.,  
R. 1 E., G&SRM., Arizona

The ¼ sec. cor. of secs. 18 and 19, monumented by a limestone, 25x12x6 ins., firmly set, marks not legible, from which the remains of the orig. bearing trees

A pinyon pine, 14 ins. diam., bears S. 10½° E., 47 lks. dist., mkd. ¼ SXIX BT (Record 20 lks.)

The root hole of a pinyon pine, 16 ins. diam., dead and down, bears N. 65½° W., 20 lks. dist., the tree is mkd. ¼ SXVIII BT (Record 47 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, mound of stone to top, 2 ft. base, brass cap mkd.

T31N R1E  
¼ S18  
S19  
1973

from which

A pinyon pine, 10 ins. diam., bears N. 54° E., 34 lks. dist., mkd. ¼ S 18 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

Remonumentation, T. 31 N., R. 1 E., G&SRM., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 17 and 18, monumented by a limestone, 30x12x6 ins., firmly set, (in an old mound of stone, 2 $\frac{1}{2}$  ft. base) mkd.  $\frac{1}{4}$  on W. face, from which the remains of the orig. bearing trees

The root hole of a pinyon pine, 13 ins. diam., dead and down, bears N. 83° E., 42 lks. dist., the tree is mkd.  $\frac{1}{4}$  S XVII BT.

A juniper, 24 ins. diam., bears N. 86° W., 54 lks. dist., mkd.  $\frac{1}{4}$  S XVIII BT. (Record 36 lks.)

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., 8 ins. in the ground, mound of stone to top, 3 $\frac{1}{2}$  ft. base, brass cap mkd.

T31N R1E

$\frac{1}{4}$   
S18|S17  
1973

from which

A juniper, 6 ins. diam., bears N. 76° E., 38 lks. dist., mkd.  $\frac{1}{4}$  S 17 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 7 and 18, monumented by a limestone, 22x12x4 ins., loosely set (in an old mound of stone, 3 ft. base) mkd.  $\frac{1}{4}$  on N. face, from which the remains of the orig. bearing trees

A juniper, 18 ins. diam., bears S. 10 $\frac{1}{2}$ ° E., 55 lks. dist., mkd.  $\frac{1}{4}$  S XVIII BT.

The root hole of a pinyon pine, 12 ins. diam., dead and down, bears N. 3° W., 270 lks. dist., the tree is mkd.  $\frac{1}{4}$  S VII BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T31N R1E

$\frac{1}{4}$   $\frac{S 7}{S18}$   
1973

from which

A pinyon pine, 6 ins. diam., bears N. 50 $\frac{1}{2}$ ° W., 48 lks. dist., mkd.  $\frac{1}{4}$  S 7 BT.

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 31 N., R. 1 W., G&SRM., Arizona

CHAINS

Township 31 North, Range 1 West, G&SRM., Arizona

The north boundary and subdivisional lines were surveyed in 1900 by W. O. Secor.

Remonumentation, N. Bdy., T. 31 N., R. 1 W., G&SRM., Arizona

The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., monumented by a limestone, 20x13x6 ins., firmly set, (in an old mound of stone, 4 ft. base, 1 ft. high) mkd. with 4 grooves on E. and 2 grooves on W. faces, from which the remains of the orig. bearing trees

A pinyon pine, 6 ins. diam., bears N. 62° E., 69 lks. dist., mkd. T32N R1W S33 BT.

A pinyon pine, 10 ins. diam., bears S. 34° W., 152 lks. dist., mkd. T31N R1W S5 BT.

A pinyon pine, 12 ins. diam., bears N. 32° W., 76 lks. dist., mkd. T32N R1W S32 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base, and with a brass cap riveted to the top, 6 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T32N R1W  
S32 | S33  
S 5 | S 4  
T31N  
1973

from which

A pinyon pine, 14 ins. diam., bears S. 46° E., 86 lks. dist., mkd. T31N R1W S4 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 4 and 33; on the N. bdy. of the Tp., monumented by a limestone, 26x16x8 ins.; firmly set, (in an old mound of stone 4 ft. base, 1 ft. high) mkd. ¼ on N. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 7 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T32N R1W  
¼ S33  
S 4  
T31N  
1973

from which

A juniper, 8 ins. diam., bears N. 62° W., 103 lks. dist., mkd. ¼ S33 BT.

Remonumentation, T. 31 N., R. 1 W., G&SRM., Arizona

CHAINS

Deposit the orig. cor. stone in the mound alongside the iron post.

The cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., monumented by a limestone, 32x18x6 ins., firmly set, (in a mound of stone 4 ft. base, 1 ft. high) mkd. with 3 notches on E. and W. edges, from which the orig. bearing trees

A juniper, 10 ins. diam., bears N. 23° E., 236 lks. dist., mkd. T32N R1W S34 BT.

A pinyon pine, 14 ins. diam., bears S. 22½° E., 175 lks. dist., mkd. T31N R1W S3 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 8 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T32N	R1W
S33	S34
S 4	S 3
T31N	
1973	

from which

A juniper, 5 ins. diam., bears S. 62½° W., 206 lks. dist., mkd. S4 BT.

A juniper, 10 ins. diam., bears N. 27° W., 97 lks. dist., mkd. S33 BT.

Deposit the orig. cor. stone in the mound alongside the iron post.

Remonumentation, Subdivision, T. 31 N.,  
R. 1 W., G&SRM., Arizona

The cor. of secs. 3, 4, 9 and 10, monumented by a limestone, 36x24x10 ins., loosely set (in an old mound of stone, 4½ ft. base, 1 ft. high) mkd. with 5 grooves on S. and 3 grooves on E. faces.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 6 ins. in the ground, mound of stone to top, 4½ ft. base, brass cap mkd.

T31N	R1W
S 4	S 3
S 9	S10
1973	

## Remonumentation, T. 31 N., R. 1 W., G&amp;SRM., Arizona

## CHAINS

Deposit the orig. cor. stone in the mound alongside the iron post.

The  $\frac{1}{2}$  sec. cor. of secs. 3 and 4, monumented by a limestone, 18x13x6 ins., loosely set, (in an old mound of stone, 2 $\frac{1}{2}$  ft. base, 1 ft. high), mkd.  $\frac{1}{2}$  on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 12 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T31N R1W

$\frac{1}{2}$   
S4|S3  
1973

Deposit the orig. cor. stone in the mound alongside the iron post.

The cor. of secs. 4, 5, 8 and 9, monumented by a limestone, 19x10x10 ins., firmly set, (in an old mound of stone, 3 ft. base, 1 ft. high) mkd. with 5 grooves on S. and 4 grooves on E. faces, from which the remains of the orig. bearing trees

The root hole of a pinyon pine, 24 ins. diam., dead and down, bears N. 80° E., 272 lks. dist., the tree is mkd. T31N R1W S9 BT. (Record S. 80°50' W., 272 lks., mkd. T31N R1W S8 BT.)

A pinyon pine, 14 ins. diam., bears N. 3° W., 57 lks. dist., mkd. T31N R1W S5 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 22 ins. in the ground, collar of stone to top, 2 $\frac{1}{2}$  ft. base, brass cap mkd.

T31N R1W

S5|S4  
S8|S9  
1973

from which

A pinyon pine, 12 ins. diam., bears N. 81° E., 273 lks. dist., mkd. T31N R1W S4 BT.

Bury the orig. cor. stone alongside the iron post.

The  $\frac{1}{2}$  sec. cor. of secs. 4 and 9, monumented by a limestone, 31x18x6 ins., firmly set, (in a mound of stone, 3 ft. base, 1 ft. high) mkd.  $\frac{1}{2}$  on N. face.



Remonumentation, T: 31 N.; R. 1 W., G&SRM., Arizona

CHAINS

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 20 ins. in the ground, mound of stone to top, 4 ft. base, brass cap mkd.

T31N R1W  
 $\frac{1}{4}$   $\frac{S4}{S9}$   
 1973

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 4 and 5, monumented by a limestone, 16x14x8 ins., firmly set, (in an old mound of stone, 3½ ft. base, 1 ft. high) mkd. ¼ on W. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 10 ins. in the ground, mound of stone to top, 3½ ft. base, brass cap mkd.

T31N R1W  
 $\frac{1}{4}$   
 S5 | S4  
 1973

Deposit the orig. cor. stone in the mound alongside the iron post.

The ¼ sec. cor. of secs. 13 and 24, monumented by a sandstone, 20x12x9 ins., firmly set, mkd. ¼ on N. face, from which the remains of the orig. bearing trees

A pinyon pine, 18 ins. diam., bears N. 21° W., 92 lks. dist., mkd. ¼ S13 BT.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., flanged at the base and with a brass cap riveted to the top, 24 ins. in the ground, in a collar of stone to top, 2½ ft. base, brass cap mkd.

T31N R1W  
 $\frac{1}{4}$   $\frac{S13}{S24}$   
 1973

Bury the orig. cor. stone alongside the iron post.

Remonumentation, T. 31 N., R. 1 W., G&SRM., Arizona

CHAINS

The  $\frac{1}{4}$  sec. cor. of secs. 13 and 14, monumented by a limestone in place, 24x16x4 ins., mkd.  $\frac{1}{4}$  on W. face, surrounded by an old mound of stone, from which the remains of the orig. bearing trees

The root hole of a pinyon pine, 6 ins. diam., dead and down, bears N. 59° E., 42 lks. dist., the tree is mkd.  $\frac{1}{4}$  S13 BT.

A juniper, 24 ins. diam., bears S. 59° W., 58 lks. dist., mkd.  $\frac{1}{4}$  S14 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 24 ins. in the ground, mound of stone to top, 3 ft. base, brass cap mkd.

T31N R1W  
 $\frac{1}{4}$   
 S14 | S13  
 1973

from which

A pinyon pine, 14 ins. diam., bears N. 29° E., 60 lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

Deposit the orig. cor. stone in the mound surrounding the iron post.

The  $\frac{1}{4}$  sec. cor. of secs. 12 and 13, monumented by a limestone, 18x12x6 ins., loosely set in an old mound of stone, 3 ft. diam., the stone is mkd.  $\frac{1}{4}$  on N. face, from which the original bearing trees

A juniper, 18 ins. diam., bears N. 10° E., 41 lks. dist., mkd.  $\frac{1}{4}$  S12 BT.

A juniper, 18 ins. diam., bears S. 31° E., 12 lks. dist., mkd.  $\frac{1}{4}$  S13 BT.

At the cor. point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$  ins. diam., flanged at the base and with a brass cap riveted to the top, 18 ins. in the ground, mound of stone to top, 2 $\frac{1}{2}$  ft. base, brass cap mkd.

T31N R1W  
 $\frac{1}{4}$   $\frac{S12}{S13}$   
 1973

Deposit the orig. cor. stone in the mound surrounding the iron post.

Remonumentation; T. 31 N.; R. 1 W., G&SRM., Arizona

CHAINS



CERTIFICATE OF SURVEY

(I) ~~(We)~~ Paul G. Bauer, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29 day of May, 1973, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 30 North, Range 2 East and Township 31 North, Ranges 1 East and 1 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 16, 1973 (Date) Paul G. Bauer (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date AUG 27 1973

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 30 North, Range 2 East and Township 31 North, Ranges 1 East and 1 West, all of the Gila and Salt River Meridian, Arizona,

executed by Paul G. Bauer, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

NOV 20 1975 (Date) Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626