

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS

OF THE EAST AND WEST BOUNDARIES

A PORTION OF THE SUBDIVISIONAL LINES

AND THE

SUBDIVISION OF CERTAIN SECTIONS IN

TOWNSHIP 1 SOUTH, RANGE 3 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

RICHARD L. OAKES

SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated JANUARY 23, 19 68, approved JANUARY 30, 1968,

_____ , which provided for the surveys included under U.S. Survey/Group
Number 498 , and assignment instructions dated JANUARY 26, 19 68.

Survey commenced FEBRUARY 23, 19 68

Survey completed JUNE 21, 19 68

159

INDEX DIAGRAM

Township 1 South, Range 3 West

6	5	4	3 17	2 13	1 8
7 22	8 22	9	16 10 15	12 11 11	6 12 2
4 18 20	21 17 19	18 16	15 15 14	10 14 9	5 13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

- Subdivision of section 10 pp 23-25
- Subdivision of section 11 pp 25-27
- Subdivision of section 12 pp 27-29
- Subdivision of section 14 pp 29-31
- Subdivision of section 15 pp 31-34
- Subdivision of section 17 pp 34-36
- Subdivision of section 18 pp 37-39

Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of a dependent resurvey of portions of the east and west boundaries, a portion of the subdivisional lines, and the subdivision of certain sections in Township 1 South, Range 3 West of the Gila and Salt River Meridian, Arizona.

Earlier pertinent surveys are tabulated as follows:

<u>Lines Surveyed</u>	<u>By Whom</u>	<u>Date</u>
Base Line (N. bdy.) & E., S. and W. bdrs.	R. C. Powers	1882
Subdivisional Lines	R. C. Powers	1883
Portion of S. bdy. (Res.)	W. H. Thorn	1916
Portion of S. & E. bdrs. (Res.)	K. L. Siebecker	1931
Portion of the E., & W., bdrs., & sub- divisional lines (Res.)	Donald E. Harding	1958

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 23, 1968.

The directions of all lines of this survey were determined by direct altitude observation on the sun for azimuth, and verified by a line of known azimuth at a U. S. Coast and Geodetic Survey triangulation station "Buckeye" and its azimuth mark. This station is located in section 21. All lines were adjusted for difference in longitude and refer to the true meridian. The adjusted horizontal distances, only, are entered in this field note record.

Preliminary to the resurvey, the lines of the original surveys and the resurveys were retraced and a diligent search made for any evidence of the corner positions. Many of the corners of the original survey in this township have been remonumented with various kinds of durable materials, in the years previous, by County Surveyors and the Arizona Public Service Company. In some instances where physical evidence of a corner monument could not be found, the intersection of section line roads and property boundary fence lines, constructed before corners were destroyed, were used to determine the corner positions. Missing corners were reestablished according to the rules of proportionate measurement. Accessory material was not available for many of the corners established in this survey.

The geographic position of the SE. corner of sec. 12, as scaled from the U. S. Geological Survey "Buckeye", quadrangle is:

Latitude: 33° 20.9' N.
Longitude: 112° 30.2' W.

The observed mean magnetic declination is 14° E.

Dependent Resurvey of a Portion of the East Boundary
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

Reestablishment of the Survey Executed by
R. C. Powers, U. S. Deputy Surveyor, in 1882
and Resurvey Executed by K. L. Siebecker,
U. S. Deputy Surveyor, in 1931

Beginning at the cor. of secs. 7, 12, 13 and 18, on the
E. boundary of the township, monumented with an iron
post, 2 ins. diam., set 4 ins. below the surface of a
graded road, with brass cap mkd.

T1S
R3W R2W
S 12 | S 7
S 13 | S 18

1931

substantiated by an original bearing tree:

A mesquite, 14 ins. diam., bears S. $72\frac{1}{4}^{\circ}$ E.,
297 lks. dist., mkd. T1S R2W S18 BT.

And new reference monuments,

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set
25 ins. in the ground, for a reference monument,
bears S. $39\frac{1}{2}^{\circ}$ W., 43.5 ft. dist., with brass cap
mkd. T1S R3W RM S13 43.5 FT 1968, and an arrow
pointing to the corner.

An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set
25 ins. in the ground, for a reference monument,
bears N. $49\frac{1}{4}^{\circ}$ W., 34.5 ft. dist., with brass cap
mkd. T1S R3W RM S12 34.5 FT 1968, and an arrow
pointing to the corner.

A Corps of Engineers survey mark, a standard
bronze disk set in concrete, mkd. TL ZJ 11
A.M.S. 1960, bears N. $35\frac{1}{2}^{\circ}$ W., 47 lks. dist.

N. $1^{\circ} 26'$ E., between secs. 7 and 12.

Over nearly level land, along graded road.

30.00 Enter Gila River bottom.

40.09 Point for the 1/4 sec. cor. of secs. 7 and 12, at
proportionate distance. There is no evidence of the
1931 resurvey corner.

Set a copper-coated steel stake, 30 ins. long, $\frac{1}{2}$ in.
diam., 8 ins. below the surface of a graded road, with
brass cap, $1\frac{1}{2}$ ins. diam., mkd.

T1S
R3W R2W
 $\frac{1}{4}$
S 12 | S 7

1968

from which

Dependent Resurvey of a Portion of the East Boundary
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 41 3/4° E., 54.3 ft. dist., with brass cap mkd. T1S R2W RM ¼ S7 54.3 FT 1968, and an arrow pointing to the corner.</p>
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 14 3/4° W., 81.4 ft. dist., with brass cap mkd. T1S R3W RM ¼ S12 81.4 FT 1968, and an arrow pointing to the corner.</p>
41.00	<p>Leave Gila River bottom, continue down graded road.</p>
60.135	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 12.</p>
	<p>Set a copper-coated steel stake, 30 ins. long, ½ in. diam., 8 ins. below the surface of a graded road, with brass cap, 1½ ins. diam., mkd.</p>
	<p style="text-align: center;">T1S R3W R2W N 1/16 S 12 S 7</p>
	<p style="text-align: center;">1968</p>
	<p>from which</p>
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 19¼° W., 54.1 ft. dist., with brass cap mkd. T1S R3W RM N. 1/16 S12 54.1 FT 1968, and an arrow pointing to the corner.</p>
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 87¼° W., 16.4 ft. dist., with brass cap mkd. T1S R3W RM N. 1/16 S12 16.4 FT 1968, and an arrow pointing to the corner.</p>
80.18	<p>The cor. of secs. 1, 6, 7 and 12, as determined at record bearing and distance from the only remaining witness cor. established in 1931:</p>
	<p>An iron post, 1 in. diam., firmly set with 8 ins. projecting above ground, bears N. 45° W., 93 lks. dist., with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W R2W S 1 S 6 S 12 S 7 W C</p>
	<p style="text-align: center;">1931</p>
	<p>The 1931 resurvey established four witness corners for this point and the above corner is now treated as a reference monument.</p>
	<p>At the corner point</p>
	<p>Set a copper-coated steel stake, 30 ins. long, ½ in. diam., flush with the surface of the road, at the intersection of Airport Road bearing N. and S. and Beloat Road bearing E. and W., with brass cap, 1½ ins. diam., mkd.</p>

Dependent Resurvey of a Portion of the East Boundary
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	<p style="text-align: center;">T1S R3W R2W <u>S 1 S 6</u> S 12 S 7</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 28° E., 120.3 ft. dist., with brass cap mkd. T1S R2W RM S6 120.3 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 61¼° E., 61.1 ft. dist., with brass cap mkd. T1S R2W RM S7 61.1 FT 1968, and an arrow pointing to the corner.</p>
	<p>Dependent Resurvey of a Portion of the West Boundary Township 1 South, Range 3 West Gila and Salt River Meridian, Arizona</p>
	<p>Reestablishment of the Survey Executed by R. C. Powers U. S. Deputy Surveyor, in 1882, and Resurvey executed by Donald E. Harding, Cadastral Surveyor, in 1958</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 18, 19 and 24, on the W. boundary of the township, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W R3W <u>S 13 S 18</u> S 24 S 19</p> <p style="text-align: center;">1958</p> <p>N. 0° 15' E., between secs. 13 and 18.</p> <p>Over level bottom land, through dense brush.</p>
20.00	<p>Point for the S. 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
37.20	<p style="text-align: center;">T1S R4W R3W S 1/16 S 13 S 18</p> <p style="text-align: center;">1968</p> <p>Gila River, 30 lks. wide, 1 ft. deep, drains W.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate position. There is no evidence of the 1958 resurvey corner.</p>

Dependent Resurvey of a Portion of the West Boundary
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W R3W ¼ S 13 S 18 1968</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 09' E., beginning new measurement.</p> <p>Over level bottom land, through dense brush.</p> <p>35.80 Channel of Gila River, 20 lks. wide, 1 ft. deep, course SW.</p> <p>40.00 The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W R3W S 12 S 7 S 13 S 18 1958</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines Township 1 South, Range 3 West Gila and Salt River Meridian, Arizona</p>
<p>40.24</p>	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883 and Resurvey Executed by Donald E. Harding, Cadastral Surveyor in 1958</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S 14 S 13 S 23 S 24 1958</p> <p>Corner is located on projection of a graded road to the N.</p> <p>N. 0° 53' E., between secs. 13 and 14.</p> <p>Over level land.</p> <p>The 1/4 sec. cor. of secs. 13 and 14, determined at record position from the 1958 reference monuments as follows:</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An iron post, 2½ ins. diam., projecting 6 ins. above ground, bears N. 51° E., 54 lks. dist., with brass cap mkd. T1S R3W RM ¼ S13 1958, and an arrow pointing to the corner.</p>
	<p>An iron post, 2½ ins. diam., projecting 6 ins. above ground, bears S. 51° W., 54 lks. dist., with brass cap mkd. T1S R3W RM ¼ S14 1958, and an arrow pointing to the corner.</p>
	<p>At the corner point</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. below the surface of a graded road, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W ¼ S 14 S 13 1968</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 54' E., beginning new measurement.</p>
	<p>Over gently rolling land, along old fenced lane.</p>
39.81	<p>The cor. of secs. 11, 12, 13 and 14, monumented with an iron post, 2½ ins. diam., firmly set with ¾ ins. projecting above ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W S 11 S 12 S 14 S 13 1958</p>
	<p>Set a cedar post, 7 ft. long, 8 ins. diam., 2½ ft. in the ground, 1½ ft. N. of the corner.</p>
	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 0° 03' W., between secs. 11 and 12.</p>
	<p>Over bottom land, through dense brush.</p>
19.825	<p>Point for the S. 1/16 sec. cor. of secs. 11 and 12.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W S 1/16 S 11 S 12 1968</p>
39.65	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate distance. There is no evidence of the original corner monument.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R3W ¼ S 11 S 12 1968</p>
59.475	<p>Corner is situated 34 lks. W. of power line bearing N. and S.</p> <p>Point for the N. 1/16 sec. cor. of secs. 11 and 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
62.00	<p style="text-align: center;">T1S R3W N 1/16 S 11 S 12 1968</p> <p>Corner is situated 18 lks. W. of power line bearing N. and S.</p>
65.40	Gila River, 1 ch. wide, 2 ft. deep, course SW.
79.30	<p>Enter onto and continue down graded road.</p> <p>The cor. of secs. 1, 2, 11 and 12, determined at the intersection of the center lines of Beloat Road bearing E. and W. and a graded road bearing N. and S. This point agrees with the position of this corner as determined from ties obtained from the Maricopa County Engineering Dept. and the Arizona Public Service Co. and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 18 ins. long, ½ in. diam., flush with the surface of the road, with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">T1S R3W S 2 S 1 S 11 S 12 1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 64¼° W., 75.9 ft. dist., with brass cap mkd. T1S R3W RM S2 75.9 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 22° W., 65.1 ft. dist., with brass cap mkd. T1S R3W RM S2 65.1 FT 1968, and an arrow pointing to the corner.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E. boundary of the township, hereinbefore described.</p> <p>S. 89° 50' W., between secs. 1 and 12.</p> <p>Over level land, along oil surfaced road.</p>	
20.02	<p>Point for the E. 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set a copper-coated steel stake, 18 ins. long, ½ in. diam., flush with the surface of the road, on center line of Beloat Road bearing E. and W., with brass cap, 1½ ins. diam., mkd.</p> $\begin{array}{r} \text{T1S R3W} \\ \text{E } 1/16 \frac{\text{S } 1}{\text{S } 12} \\ 1968 \end{array}$ <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 50 ¾° E., 48.6 ft. dist., with brass cap mkd. T1S R3W RM E. 1/16 S1 48.6 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 54 ¾° W., 53.6 ft. dist., with brass cap mkd. T1S R3W RM E. 1/16 S1 53.6 FT 1968, and an arrow pointing to the corner.</p>	
40.04	<p>The 1/4 sec. cor. of secs. 1 and 12, determined by ties received from Maricopa County Engineering Dept. and Arizona Public Service Co:</p> <p>A fence corner post, bears N., 33 ft. dist.</p> <p>A cross (+) chiseled in a concrete headwall, bears NE., 57.1 ft. dist.</p> <p>A cross (+) chiseled on the W. end of a headwall, bears SE., 44.25 ft. dist.</p> <p>A power line pole, bears SW., 44.1 ft. dist.</p> <p>This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 18 ins. long, ½ in. diam., flush with the surface of the road, on center line of Beloat Road bearing E. and W., with brass cap, 1½ ins. diam., mkd.</p> $\begin{array}{r} \text{T1S R3W} \\ \frac{1}{4} \frac{\text{S } 1}{\text{S } 12} \\ 1968 \end{array}$	

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 42 3/4° W., 41.4 ft. dist., with brass cap mkd. T1S R3W RM ¼ S12 41.4 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 12° W., 33.6 ft. dist., with brass cap mkd. T1S R3W RM ¼ S1 33.6 FT 1968, and an arrow pointing to the corner.</p>
20.04	<p>S. 89° 46' W., beginning new measurement.</p> <p>Over level land, along oil surfaced road.</p> <p>Point for the W. 1/16 sec. cor. of secs. 1 and 12.</p> <p>Set a copper-coated steel stake, 18 ins. long, ½ in. diam., flush with the surface of the road, on center line of Beloit Road bearing E. and W., with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">T1S R3W W 1/16 $\frac{S 1}{S 12}$ 1968</p>
40.08	<p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 4¼° E., 36.6 ft. dist., with brass cap mkd. T1S R3W RM W 1/16 S1 36.6 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 49½° E., 50.4 ft. dist., with brass cap mkd. T1S R3W RM W. 1/16 S1 50.4 FT 1968, and an arrow pointing to the corner.</p> <p>The cor. of secs. 1, 2, 11 and 12.</p>
24.70 34.00	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883 and Resurvey Executed by Donald E. Harding, Cadastral Surveyor in 1958</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89° 48' W., between secs. 14 and 23.</p> <p>Over rolling land, through undergrowth of mesquite and greasewood.</p> <p>Wash, 40 lks. wide, 2 ft. deep, drains NW.</p> <p>Wash, 30 lks. wide, 2 ft. deep, drains NNE.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
39.67	The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2½ ins. diam., firmly set with 5 ins. projecting above ground, with brass cap mkd.
	$\begin{array}{c} \text{T1S R3W} \\ \frac{1}{4} \frac{\text{S } 14}{\text{S } 23} \\ 1958 \end{array}$
	<hr/> N. 89° 48' W., beginning new measurement.
	Ascending gradual E. slope.
32.00	Top of low ascent, spur, slopes NE., descend NW. slope.
38.00	Wash, 20 lks. wide, 2 ft. deep, drains N.
39.67	The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set with 12 ins. projecting above ground, with brass cap mkd.
	$\begin{array}{c} \text{T1S R3W} \\ \frac{\text{S } 15 \text{S } 14}{\text{S } 22 \text{S } 23} \\ 1958 \end{array}$
	<hr/> N. 0° 40' E., between secs. 14 and 15.
	Descend over N. slope, through undergrowth of mesquite, cactus and greasewood.
14.60	Trail road, bears E. and W.
20.045	Point for the S. 1/16 sec. cor. of secs. 14 and 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{T1S R3W} \\ \text{S } 1/16 \\ \text{S } 15 \text{S } 14 \\ 1968 \end{array}$
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.
20.80	Wash, 30 lks. wide, 2 ft. deep, drains NE., ascend SE. slope.
26.30	Spur, slopes SE., descend N. slope.
32.70	Road, bears ENE. and WSW.
33.50	Road, bears E. and W.
40.09	The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set with 5 ins. projecting above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R3W $\frac{1}{4}$ S 15 S 14 1958</p>
<p>16.00 19.865</p>	<p style="text-align: center;">N. 0° 04' W., beginning new measurement.</p> <p>Over nearly level land, through dense brush.</p> <p>Gila River, 80 lks. wide, 3 ft. deep, course SW.</p> <p>Point for the N. 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
<p>39.73</p>	<p style="text-align: center;">T1S R3W N 1/16 S 15 S 14 1968</p> <p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate distance based on the 1958 resurvey corners E., S. and W. There is no evidence of the 1958 resurvey corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W $\frac{S 10 S 11}{S 15 S 14}$ 1968</p>
<p>20.03</p>	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>N. 89° 58' W., between secs. 11 and 14.</p> <p>Point for the E. 1/16 sec. cor. of secs. 11 and 14.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
<p>40.06</p>	<p style="text-align: center;">T1S R3W $\frac{S 11}{S 14}$ E 1/16 1968</p> <p>The 1/4 sec. cor. of secs. 11 and 14, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W $\frac{1}{4} \frac{S 11}{S 14}$ 1958</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	WEST, beginning new measurement
	Over level land, through dense brush.
12.50	Gila River, 80 lks. wide, 2 ft. deep, course SW.
20.03	Point for the W. 1/16 sec. cor. of secs. 11 and 14.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R3W S 11 W 1/16 — S 14</p>
	<p style="text-align: center;">1968</p>
40.06	The cor. of secs. 10, 11, 14 and 15.
	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883</p> <hr style="width: 20%; margin: auto;"/>
	N. 0° 02' E., between secs. 10 and 11.
	Over level land, through dense brush.
19.845	Point for the S. 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R3W S 1/16 S 10 S 11</p>
	<p style="text-align: center;">1968</p>
29.90	Leave dense brush, continue over sparse grass land.
39.69	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate distance. There is no evidence of the original corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R3W ¼</p>
	<p style="text-align: center;">S 10 S 11</p>
	<p style="text-align: center;">1968</p>
	Corner is situated 8 lks. E. of fence bearing N., from the WSW.
45.20	Canal ditch, 4 ft. wide, 2½ ft. deep, course WSW.
50.90	Enter onto and continue down graded road.
79.38	The cor. of secs. 2, 3, 10 and 11, determined by ties received from Maricopa County Engineering Dept:

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The extension of power line to W. bears S., 23.22 ft. dist.</p> <p>A cross (+) chiseled in headwall, bears SW., 58.0 ft. dist.</p> <p>This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 18 ins. long, ½ in. diam., flush with the surface of the road, at the intersection of Beloat Road bearing E. and W., and Rainbow Road bearing N. and S., with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;"> T1S R3W S 3 S 2 S 10 S 11 </p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 50¼° W., 41.4 ft. dist., with brass cap mkd. T1S R3W RM S10 41.4 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 46 ¾° W., 43.0 ft. dist., with brass cap mkd. T1S R3W RM S3 43.0 FT 1968, and an arrow pointing to the corner.</p>
<p>39.97</p>	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89° 52' W., between secs. 2 and 11.</p> <p>Over level land, along oil surfaced road.</p> <p>The ¼ sec. cor. of secs. 2 and 11, determined longitudinally by crop division to the N., and latitudinally on center line of oil surfaced Beloat Road bearing E. and W. This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 18 ins. long, ½ in. diam., flush with the surface of the road, with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;"> T1S R3W ¼ S 2 S 11 </p> <p style="text-align: center;">1968</p> <p>from which</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 64 3/4° E., 72.5 ft. dist., with brass cap mkd. T1S R3W RM ¼ S2 72.5 FT 1968, and an arrow pointing to the corner.</p>
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 76 3/4° E., 127.2 ft. dist., with brass cap mkd. T1S R3W RM ¼ S11 127.2 FT 1968, and an arrow pointing to the corner.</p>
	<p>S. 89° 58' W., beginning new measurement.</p>
	<p>Over level land, along oil surfaced road.</p>
37.50	<p>Canal ditch, 4 ft. wide, 2½ ft. deep, course S.</p>
39.99	<p>The cor. of secs. 2, 3, 10 and 11.</p>
	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883 and Resurvey Executed by Donald E. Harding, Cadastral Surveyor in 1958</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>N. 89° 49' W., between secs. 15 and 22.</p>
	<p>Over rolling land, through scattered undergrowth of mesquite and greasewood.</p>
20.02	<p>Point for the E. 1/16 sec. cor. of secs. 15 and 22.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W E 1/16 $\frac{S\ 15}{S\ 22}$</p>
	<p style="text-align: center;">1968</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the corner.</p>
25.50	<p>Road, bears N. and S.</p>
39.40	<p>Wash, 40 lks. wide, 3 ft. deep, drains NE.</p>
40.04	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set with 12 ins. projecting above ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W ¼ $\frac{S\ 15}{S\ 22}$</p>
	<p style="text-align: center;">1958</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S 16 S 15 S 21 S 22</p> <p style="text-align: center;">1958</p> <p>N. 0° 32' E., between secs. 15 and 16.</p> <p>Over rolling land, through scattered undergrowth, descending N. slope.</p>
37.80	Trail road, bears ENE. and WSW.
39.84	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set with 5 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W ¼ S 16 S 15</p> <p style="text-align: center;">1958</p> <hr/> <p>N. 0° 23' E., beginning new measurement.</p>
16.80	Gila River, 50 lks. wide, 4 ft. deep, course generally NW., continue through dense brush.
19.985	<p>Point for the N. 1/16 sec. cor. of secs. 15 and 16.</p> <p>Set an iron post, 30 ins long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W N 1/16 S 16 S 15</p> <p style="text-align: center;">1968</p>
39.97	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set with 10 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S 9 S 10 S 16 S 15</p> <p style="text-align: center;">1958</p> <hr/> <p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 89° 58' W., between secs. 10 and 15.</p>
20.035	Point for the E. 1/16 sec. cor. of secs. 10 and 15, not monumented.
40.07	The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., firmly set with 12 ins. projecting above ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T1S R3W $\frac{1}{4} \frac{S 10}{S 15}$ 1958</p> <hr/> <p>N. 89° 45' W., beginning new measurement. Over bottom land, through dense brush.</p>	
20.075	<p>Point for the W. 1/16 sec. cor. of secs. 10 and 15.</p>	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>	
40.15	<p style="text-align: center;">T1S R3W W 1/16 $\frac{S 10}{S 15}$ 1968</p> <p>The cor. of secs. 9, 10, 15 and 16.</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883</p> <hr/> <p>N. 0° 03' W., between secs. 9 and 10. Over bottom land, through dense brush.</p>	
0.40	<p>Channel of the Gila River, 50 lks. wide, 3 ft. deep, course SW.</p>	
5.20	<p>Leave river bottom, continue over level farm land, along E. side of canal ditch.</p>	
19.86	<p>Point for the S. 1/16 sec. cor. of secs. 9 and 10.</p>	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>	
39.72	<p style="text-align: center;">T1S R3W S 1/16 S 9 S 10 1968</p> <p>Set a wooden guard post, 6 ft. long, 4 ins. diam., alongside the corner, which is situated in farm yard. Thence, over cultivated land.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate distance, falls in cultivated field. There is no evidence of the original corner.</p> <p>Set a copper-coated steel stake, 30 ins. long, ½ in. diam., 12 ins. below the surface of the ground, with brass cap, 1½ ins. diam., mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R3W $\frac{1}{4}$</p> <p style="text-align: center;">S 9 S 10</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 61° W., 115.3 Ft. dist., with brass cap mkd. T1S R3W RM $\frac{1}{4}$ S9 115.3 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. $62\frac{1}{4}^\circ$ W., 113.5 ft. dist., with brass cap mkd. T1S R3W RM $\frac{1}{4}$ S9 113.5 FT 1968, and an arrow pointing to the corner.</p> <p>The reference monuments are set in a N. S. fence line on E. bank of canal ditch.</p> <p>79.44 The cor. of secs. 3, 4, 9 and 10, determined longitudinally on projection of center line of graded road extending N., and latitudinally on center line of oil surfaced Beloat Road extending E. and W. This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 18 ins. long, $\frac{1}{2}$ in. diam., flush with the surface of the road, with brass cap, $1\frac{1}{2}$ ins. diam., mkd.</p> <p style="text-align: center;">T1S R3W $\frac{S\ 4 S\ 3}{S\ 9 S\ 10}$</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. $56\frac{1}{2}^\circ$ W., 54.5 ft. dist., with brass cap mkd. T1S R3W RM S9 54.5 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set 25 ins. in the ground, for a reference monument bears N. 46° W., 54.5 ft. dist., with brass cap mkd. T1S R3W RM S4 54.5 FT 1968, and an arrow pointing to the corner.</p> <hr/> <p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. $89^\circ 49'$ W., between secs. 3 and 10.</p> <p>Over level land, along oil surfaced road.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
40.13	<p>The 1/4 sec. cor. of secs. 3 and 10, determined longitudinally on projection of fence lines N. and S. and latitudinally on center line of oil surfaced Beloat Road bearing E. and W. This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 18 ins. long, 1/2 in. diam., flush with surface of the road, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T1S R3W 1/4 $\frac{S\ 3}{S\ 10}$</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 35° E., 41.6 ft. dist., with brass cap mkd. T1S R3W RM 1/4 S3 41.6 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2 1/2 ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 57 3/4° W., 66.2 ft. dist., with brass cap mkd. T1S R3W RM 1/4 S3 66.2 FT 1968, and an arrow pointing to the corner.</p> <hr/> <p>N. 89° 49' W., beginning new measurement.</p> <p>Over level land, along oil surface road.</p>	
40.17	<p>The cor. of secs. 3, 4, 9 and 10.</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883 and Resurvey Executed by Donald E. Harding, Cadastral Surveyor in 1958</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 1/2 ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S 17 S 16 S 20 S 21</p> <p style="text-align: center;">1958</p> <p>from which</p> <p>U.S.C. & G.S. triangulation station "Buckeye" bears S. 44° 16' E., 51.19 chs. dist. Said station is in latitude 33° 19' 39.127" N. and longitude 112° 33' 54.676" W.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	Thence, N. 0° 27' E., between secs. 16 and 17.
	Over nearly level land, through dense salt cedar.
20.06	Point for the S. 1/16 sec. cor. of secs. 16 and 17.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W
	S 1/16
	S 17 S 16
	1968
40.12	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate distance. There is no evidence of the 1958 resurvey corner.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W
	¼
	S 17 S 16
	1968
50.20	Gila River, 30 lks. wide, 2 ft. deep, course W.
60.18	Point for the N. 1/16 sec. cor. of secs. 16 and 17.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W
	N 1/16
	S 17 S 16
	1968
61.80	Channel of Gila River, 140 lks. wide, 3 ft. deep, course W.
64.40	Canal ditch, 50 lks. wide, 1 ft. deep, course WSW.
65.00	Enter onto and continue down trail road.
80.24	The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2½ ins. diam., firmly set with 12 ins. projecting above ground, with brass cap mkd.
	T1S R3W
	S 8 S 9
	S 17 S 16
	1958
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89° 33' W., between secs. 17 and 20.
	Over rolling land, through scattered salt cedar and undergrowth.

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS		
39.82	The 1/4 sec. cor. of secs. 17 and 20, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.	
	$\begin{array}{r} \text{T1S R3W} \\ \frac{1}{4} \frac{\text{S } 17}{\text{S } 20} \\ 1958 \end{array}$	
	<hr/>	
	S. 89° 58' W., beginning new measurement.	
	Over rolling hills, through scattered undergrowth.	
19.91	Point for the W. 1/16 sec. cor. of secs. 17 and 20.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 11 ins. in the ground to bedrock, in a collar of stone, 3 ft. base to top of brass cap, mkd.	
	$\begin{array}{r} \text{T1S R3W} \\ \text{W } 1/16 \frac{\text{S } 17}{\text{S } 20} \\ 1968 \end{array}$	
39.82	The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.	
	$\begin{array}{r} \text{T1S R3W} \\ \frac{\text{S } 18 \text{S } 17}{\text{S } 19 \text{S } 20} \\ 1958 \end{array}$	
	<hr/>	
	S. 89° 11' W., between secs. 18 and 19.	
	Over nearly level land, through scattered undergrowth.	
20.605	Point for the E. 1/16 sec. cor. of secs. 18 and 19.	
	Set an iron post, 30 ins long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.	
	$\begin{array}{r} \text{T1S R3W} \\ \text{E } 1/16 \frac{\text{S } 18}{\text{S } 19} \\ 1968 \end{array}$	
	Set a wooden guard post alongside the iron post.	
41.21	The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.	
	$\begin{array}{r} \text{T1S R3W} \\ \frac{1}{4} \frac{\text{S } 18}{\text{S } 19} \\ 1958 \end{array}$	

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 1 South, Range 3 West
Gila and Salt River meridian, Arizona

CHAINS	
	<p>S. 89° 11' W., beginning new measurement.</p> <p>Over level bottom land, through thick salt cedar and willows.</p> <p>38.39 Power line, bears N. and S.</p> <p>38.99 The cor. of secs. 13, 18, 19 and 24, on the W. boundary of the township, hereinbefore described.</p>
	<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0° 02' E., between secs. 17 and 18.</p> <p>Over level bottom land, through dense undergrowth.</p> <p>19.93 Point for the S. 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W S 1/16</p> <p style="text-align: center;">S 18 S 17</p> <p style="text-align: center;">1968</p>
	<p>29.70 Enter along W. edge of graded road, on curve from SE. to N.</p>
	<p>39.86 Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate distance. There is no evidence of the 1958 resurvey corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, with collar of broken concrete, 3 ft. base to top of brass cap, mkd.</p> <p style="text-align: center;">T1S R3W ¼</p> <p style="text-align: center;">S 18 S 17</p> <p style="text-align: center;">1968</p>
	<p>59.79 Point for the N. 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set a copper-coated steel stake, 30 ins. long, ½ in. diam., 8 ins. below the surface of a road, with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">T1S R3W N 1/16</p> <p style="text-align: center;">S 18 S 17</p> <p style="text-align: center;">1968</p> <p>from which</p> <p style="text-align: center;">An "X" chiseled in the NE. cor. of headwall of culvert, bears S. 21½° E., 61.5 ft. dist.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An "X" chiseled in the NW. cor. of headwall of culvert, bears S. 8 3/4° W., 73.0 ft. dist.</p>
60.30	<p>Gila River, 80 lks. wide, 2 ft. deep, course SW.</p>
79.72	<p>The cor. of secs. 7, 8, 17 and 18, determined at record bearing and distance from the only remaining reference monument:</p> <p>An iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, bears S. 61° 56' E., 41 lks. dist., with brass cap mkd. T1S R3W S17 RM 1958, and an arrow pointing to the corner. The marks 27.1 FT are added to the brass cap.</p> <p>This point falls on 10 in. steel lid of water main valve which is flush with the surface of the road.</p>
20.06	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89° 49' W., between secs. 8 and 17.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>Point for the E. 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W E 1/16 $\frac{S 8}{S 17}$ 1968</p>
30.30	<p>Irrigation ditch, flows generally W.</p>
40.12	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron post, 2½ ins. diam., firmly set with 10 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W $\frac{1}{4} \frac{S 8}{S 17}$ 1958</p>
40.08	<p>S. 89° 48' W., beginning new measurement.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>The cor. of secs. 7, 8, 17 and 18.</p>
20.605	<p>S. 89° 24' W., between secs. 7 and 18.</p> <p>Over nearly level land, through dense undergrowth.</p> <p>Point for the E. 1/16 sec. cor. of secs. 7 and 18.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W E 1/16 $\frac{S 7}{S 18}$ 1968</p>
41.21	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate distance. There is no evidence of the 1958 resurvey corner.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W $\frac{1}{4} \frac{S 7}{S 18}$ 1968</p>
79.98	<p>The cor. of secs. 7, 12, 13 and 18, on the W. boundary of the township, hereinbefore described.</p>
<p>Subdivision of Section 10 Township 1 South, Range 3 West Gila and Salt River Meridian, Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 10 and 15.</p>
	<p>N. 0° 01' W., along the N. and S. center line of sec. 10.</p>
	<p>Over bottom land, through dense undergrowth.</p>
16.15	<p>Irrigation ditch, 10 lks. wide, 2 ft. deep, flows SW.</p>
19.895	<p>Point for the C-S. 1/16 sec. cor. of sec. 10.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W C S 1/16 S 10 1968</p>
	<p>Set a wooden guard post, alongside the iron post.</p>
21.05	<p>Trail road on top of dike, bears ENE. and WSW., thence over cultivated land.</p>
39.79	<p>Point for the center 1/4 sec. cor. of sec. 10, at the intersection with the E. and W. center line, not monumented, falls in cultivated field.</p>
79.49	<p>The 1/4 sec. cor. of secs. 3 and 10.</p>

Subdivision of Section 10
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 10 and 11.</p> <p>N. 89° 52' W., along the E. and W. center line of sec. 10.</p> <p>Over nearly level land.</p> <p>6.85 Irrigation ditch, 10 lks. wide, 3 ft. deep, flows SW.</p> <p>20.05 Point for the C-E. 1/16 sec. cor. of sec. 10, not monumented, falls in hay meadow.</p> <p>40.10 The point for the center 1/4 sec. cor. of sec. 10.</p> <p>60.185 Point for the C-W. 1/16 sec. cor. of sec. 10, not monumented, falls in hay meadow.</p> <p>80.27 The 1/4 sec. cor. of secs. 9 and 10.</p>
	<p>From the point for the E. 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 00.5' E., along the N. and S. center line of the SE$\frac{1}{4}$ of sec. 10.</p> <p>19.87 Point for the SE. 1/16 sec. cor. of sec. 10, at the intersection with E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W SE 1/16 S 10 1968</p> <p>39.74 The point for the C-E. 1/16 sec. cor. of sec. 10.</p>
	<p>From the S. 1/16 sec. cor. of secs. 10 and 11.</p> <p>N. 89° 55' W., along the E. and W. center line of the SE$\frac{1}{4}$ of sec. 10.</p> <p>20.045 The SE. 1/16 sec. cor. of sec. 10.</p> <p>40.09 The C-S. 1/16 sec. cor. of sec. 10.</p>
	<p>From the W. 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0° 02' W., along the N. and S. center line of the SW$\frac{1}{4}$ of sec. 10.</p> <p>19.88 Point for the SW. 1/16 sec. cor. of sec. 10, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 10
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.76	<p>T1S R3W SW 1/16 S 10</p> <p>1968</p> <p>The point for the C-W. 1/16 sec. cor. of sec. 10.</p>
20.08 40.16	<p>From the C-S. 1/16 sec. cor. of sec. 10.</p> <p>N. 89° 48' W., along the E. and W. center line of the SW$\frac{1}{4}$ of sec. 10.</p> <p>The SW. 1/16 sec. cor. of sec. 10.</p> <p>The S. 1/16 sec. cor. of secs. 9 and 10.</p>
	<p>Subdivision of Section 11 Township 1 South, Range 3 West Gila and Salt River Meridian, Arizona</p>
19.84	<p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0° 01' W., along the N. and S. center line of sec. 11.</p> <p>Over bottom land, through dense undergrowth.</p> <p>Point for the C-S. 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
29.90 39.68	<p>T1S R3W C S 1/16 S 11</p> <p>1968</p> <p>Gila River, 1.00 chn. wide, 3 ft. deep, course SW.</p> <p>Point for the center 1/4 sec. cor. of sec. 11, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, to bedrock, in a collar of stone, 3 ft. base to top of brass cap, mkd.</p>
79.39	<p>T1S R3W C 1/4 S 11</p> <p>1968</p> <p>Thence, continue over level pasture land.</p> <p>The 1/4 sec. cor. of secs. 2 and 11.</p>

Subdivision of Section 11
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 11 and 12. WEST, along the E. and W. center line of sec. 11. Over bottom land, through dense undergrowth.</p>
19.99	<p>Point for the C-E. 1/16 sec. cor. of sec. 11. Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. T1S R3W C E 1/16 S 11 1968</p>
24.25	Gila River, 1.00 chn. wide, 3 ft. deep, course SW.
39.98	The center 1/4 sec. cor. of sec. 11.
60.00	<p>Point for the C-W. 1/16 sec. cor. of sec. 11. Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. T1S R3W C W 1/16 S 11 1968</p>
	Thence, over cultivated field.
80.02	The 1/4 sec. cor. of secs. 10 and 11.
19.83	<p>From the E. 1/16 sec. cor. of secs. 11 and 14. N. 0° 02' W., along the N. and S. center line of the SE¼ of sec. 11. Point for the SE. 1/16 sec. cor. of sec. 11, at the intersection with the E. and W. center line of the SE¼. Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd. T1S R3W SE 1/16 S 11 1968</p>
39.66	The C-E. 1/16 sec. cor. of sec. 11.
20.01	<p>From the S. 1/16 sec. cor. of secs. 11 and 12. N. 89° 59' W., along the E. and W. center line of the SE¼ of sec. 11. The SE. 1/16 sec. cor. of sec. 11.</p>
40.02	The C-S 1/16 sec. cor. of sec. 11.

Subdivision of Section 11
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	From the W. 1/16 sec. cor. of secs. 11 and 14. N. 0° 00.5' E., along the N. and S. center line of the SW $\frac{1}{4}$ of sec. 11.
19.84	Point for the SW. 1/16 sec. cor. of sec. 11, at the intersection with the E. and W. center line of the SW $\frac{1}{4}$. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd. T1S R3W SW 1/16 S 11 1968
39.68	The C-W. 1/16 sec. cor. of sec. 11. <hr/> From the C-S. 1/16 sec. cor. of sec. 11. WEST, along the E. and W. center line of the SW $\frac{1}{4}$ of sec. 11.
5.00	Gila River, 1.00 chn. wide, 3 ft. deep, course SW.
20.03	The SW. 1/16 sec. cor. of sec. 11.
40.06	The S. 1/16 sec. cor. of secs. 10 and 11. <hr/>
<p>Subdivision of Section 12 Township 1 South, Range 3 West Gila and Salt River Meridian, Arizona</p> <hr/>	
	From the 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 $\frac{1}{2}$ ins diam., firmly set with 4 ins. projecting above ground, with brass cap mkd. T1S R3W $\frac{1}{4}$ $\frac{S 12}{S 13}$ 1958
39.84	N. 0° 25' E., along the N. and S. center line of sec. 12. Over bottom land, through dense undergrowth. Point for the center 1/4 sec. cor. of sec. 12, at the intersection with the E. and W. center line. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd. T1S R3W C $\frac{1}{4}$ S 12 1968
59.805	Point for the C-N. 1/16 sec. cor. of sec. 12. Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.

Subdivision of Section 12
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>T1S R3W C N 1/16 S 12</p> <p>1968</p>	
79.77	The 1/4 sec. cor. of secs. 1 and 12.	
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. boundary of the township, hereinbefore described.</p> <p>N. 89° 54' W., along the E. and W. center line of sec. 12.</p> <p>Over bottom land, through dense undergrowth.</p>	
19.685	<p>Point for the C-E. 1/16 sec. cor. of sec. 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>	
	<p>T1S R3W C E 1/16 S 12</p> <p>1968</p>	
39.37	The center 1/4 sec. cor. of sec. 12.	
59.23	<p>Point for the C-W. 1/16 sec. cor. of sec. 12.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>	
	<p>T1S R3W C W 1/16 S 12</p> <p>1968</p>	
79.09	The 1/4 sec. cor. of secs. 11 and 12.	
	<hr/> <p>From the C-E. 1/16 sec. cor. of sec. 12.</p> <p>N. 0° 56' E., along the N. and S. center line of the NE¼ of sec. 12.</p>	
20.00	<p>Point for the NE. 1/16 sec. cor. of sec. 12, at the intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>	
	<p>T1S R3W NE 1/16 S 12</p> <p>1968</p>	
40.00	The E. 1/16 sec. cor. of secs. 1 and 12.	

Subdivision of Section 12
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	From the N. 1/16 sec. cor. of secs. 7 and 12.
	S. 89° 58' W., along the E. and W. center line of the NE $\frac{1}{4}$ of sec. 12.
19.85	The NE 1/16 sec. cor. of sec. 12.
39.70	The C-N. 1/16 sec. cor. of sec. 12.
	From the C-W. 1/16 sec. cor. of sec. 12.
	N. 0° 11' E., along the N. and S. center line of the NW $\frac{1}{4}$ of sec. 12.
19.895	Point for the NW. 1/16 sec. cor. of sec. 12, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W
	NW 1/16
	S 12
	1968
39.79	The W. 1/16 sec. cor. of secs. 1 and 12.
	From the C-N. 1/16 sec. cor. of sec. 12.
	S. 89° 56' W., along the E. and W. center line of the NW $\frac{1}{4}$ of sec. 12.
19.95	The NW. 1/16 sec. cor. of sec. 12.
39.90	The N. 1/16 sec. cor. of secs. 11 and 12.
	Subdivision of Section 14
	Township 1 South, Range 3 West
	Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 14 and 23.
	N. 0° 36' E., along the N. and S. center line of sec. 14.
	Over nearly level land, through scattered undergrowth.
40.17	Point for the center 1/4 sec. cor. of sec. 14, at the intersection with the E. and W. center line.
	Set a copper-coated steel stake, 30 ins. long, $\frac{1}{2}$ in. diam., 10 ins. below the surface of the road, with brass cap, 1 $\frac{1}{2}$ ins. diam., mkd.
	T1S R3W
	C 1/4
	S 14
	1968

Subdivision of Section 14
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears N. 61 3/4° E., 47.4 ft. dist., with brass cap mkd. T1S R3W RM C¼ S14 47.4 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground, for a reference monument, bears S. 68 3/4° E., 45.0 ft. dist., with brass cap mkd. T1S R3W RM C¼ S14 45.0 FT 1968, and an arrow pointing to the corner.</p>	
60.05	Point for the C-N, 1/16 sec. cor. of sec. 14, not monumented, falls in hay meadow.	
79.93	The 1/4 sec. cor. of secs. 11 and 14.	
<hr/>		
	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89° 55' W., along the E. and W. center line of sec. 14.</p> <p>Over nearly level land, along meandering graded road.</p>	
39.85	The center 1/4 sec. cor. of sec. 14.	
59.66	Point for the C-W. 1/16 sec. cor. of sec. 14.	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, in a right-of-way fence bearing E. and W., on the N. side of a graded road, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C W 1/16 S 14 1968</p>	
75.40	Leave right-of-way on curve from E. to WSW.	
79.47	The 1/4 sec. cor. of secs. 14 and 15.	
<hr/>		
	<p>From the C-W. 1/16 sec. cor. of sec. 14.</p> <p>N. 0° 16' E., along the N. and S. center line of the NW¼ of sec. 14.</p>	
19.87	Point for the NW. 1/16 sec. cor. of sec. 14, at the intersection with the E. and W. center line of the NW¼.	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W NW 1/16 S 14 1968</p>	

Subdivision of Section 14
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
31.50	Gila River, 1.00 chn. wide, 4 ft. deep, course SW.
39.74	The W. 1/16 sec. cor. of secs. 11 and 14.
	From the point for the C-N. 1/16 sec. cor. of sec. 14.
	N. 89° 58' W., along the E. and W. center line of the NW¼ of sec. 14.
19.92	The NW. 1/16 sec. cor. of sec. 14.
39.84	The N. 1/16 sec. cor. of secs. 14 and 15.
Subdivision of Section 15 Township 1 South, Range 3 West Gila and Salt River Meridian, Arizona	
	From the 1/4 sec. cor. of secs. 15 and 22.
	N. 0° 17' E., along the N. and S. center line of sec. 15.
	Over gently rolling land.
19.96	Point for the C-S. 1/16 sec. cor. of sec. 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground to bedrock, in a collar of stone, 4 ft. base to top of brass cap mkd.
	T1S R3W C S 1/16 S 15
	1968
39.92	Point for the center 1/4 sec. cor. of sec. 15, at the intersection with the E. and W. center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W C 1/4 S 15
	1968
	Thence enter bottom land, through dense undergrowth.
49.90	Gila River, 50 lks. wide, 4½ ft. deep, course W.
59.80	Point for the C-N. 1/16 sec. cor. of sec. 15.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W C N 1/16 S 15
	1968

Subdivision of Section 15
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
79.68	<p>The 1/4 sec. cor. of secs. 10 and 15.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S. 89° 58' W., along the E. and W. center line of sec. 15.</p> <p>Over gently rolling land.</p>
20.16	Point for the C-E. 1/16 sec. cor. of sec. 15, not monumented, falls in cultivated field.
40.32	The center 1/4 sec. cor. of sec. 15.
50.37	<p>Point for the C-E-W. 1/64 sec. cor. of sec. 15.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C E W 1/64 S 15 1968</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.</p>
60.42	<p>Point for the C-W. 1/16 sec. cor. of sec. 15.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 2 ft. base to top of brass cap mkd.</p> <p style="text-align: center;">T1S R3W C W 1/16 S 15 1968</p>
80.52	<p>The 1/4 sec. cor. of secs. 15 and 16.</p> <hr/> <p>From the point for the C-E. 1/16 sec. cor. of sec. 15.</p> <p>N. 0° 07' E., along the N. and S. center line of the NE¼ of sec. 15.</p>
10.00	Leave cultivated field, enter dense undergrowth.
19.87	<p>Point for the NE. 1/16 sec. cor. of sec. 15, at the intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W NE 1/16 S 15 1968</p>

Subdivision of Section 15
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.74	The point for the E. 1/16 sec. cor. of secs. 10 and 15.
	From the N. 1/16 sec. cor. of secs. 14 and 15.
	WEST, along the E. and W. center line of the NE $\frac{1}{4}$ of sec. 15.
20.10	The NE. 1/16 sec. cor. of sec. 15.
40.20	The C-N. 1/16 sec. cor. of sec. 15.
	From the E. 1/16 sec. cor. of secs. 15 and 22.
	N. 0° 28' E., along the N. and S. center line of the SE $\frac{1}{4}$ of sec. 15.
20.00	Point for the SE. 1/16 sec. cor. of sec. 15, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to bedrock, in a collar of stone, 4 ft. base to top of brass cap mkd.
	T1S R3W
	SE 1/16
	S 15
	1968
40.00	The point for the C-E. 1/16 sec. cor. of sec. 15.
	From the S. 1/16 sec. cor. of secs. 14 and 15.
	N. 89° 55' W., along the E. and W. center line of the SE $\frac{1}{4}$ of sec. 15.
20.09	The SE. 1/16 sec. cor. of sec. 15.
40.18	The C-S. 1/16 sec. cor. of sec. 15.
	From the C-W. 1/16 sec. cor. of sec. 15.
	N. 0° 21' E., along the N. and S. center line of the NW $\frac{1}{4}$ of sec. 15.
19.93	Point for the NW. 1/16 sec. cor. of sec. 15, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.
	T1S R3W
	NW 1/16
	S 15
	1968
39.86	The W. 1/16 sec. cor. of secs. 10 and 15.

Subdivision of Section 15
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
	From the C-N. 1/16 sec. cor. of sec. 15.	
	N. 89° 53' W., along the E. and W. center line of the NW $\frac{1}{4}$ of sec. 15.	
10.04	Point for the C-E-NW. 1/64 sec. cor. of sec. 15.	
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.	
	T1S R3W	
	C E NW 1/64	
	S 15	
	1968	
20.08	The NW. 1/16 sec. cor. of sec. 15.	
40.17	The N. 1/16 sec. cor. of secs. 15 and 16.	
	From the C-E-W. 1/64 sec. cor. of sec. 15.	
	N. 0° 19' E., along the N. and S. center line of the SE $\frac{1}{4}$ NW $\frac{1}{4}$ of sec. 15.	
19.905	The C-E-NW. 1/64 sec. cor. of sec. 15.	
	Subdivision of Section 17	
	Township 1 South, Range 3 West	
	Gila and Salt River Meridian, Arizona	
	From the 1/4 sec. cor. of secs. 17 and 20.	
	N. 0° 12' E., along the N. and S. center line of sec. 17.	
	Over rolling land, through scattered undergrowth.	
5.20	Trail road, bears E. and SW.	
19.91	Point for the C-S. 1/16 sec. cor. of sec. 17.	
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.	
	T1S R3W	
	C S 1/16	
	S 17	
	1968	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.	
21.30	Leave rolling hills, enter bottom land, continue through dense undergrowth.	
37.44	Channel of Gila River, 40 lks. wide, 2 ft. deep, course SW.	
39.82	Point for the center 1/4 sec. cor. of sec. 17, at the intersection with the E. and W. center line.	

Subdivision of Section 17
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C 1/4 S 17</p> <p style="text-align: center;">1968</p>
59.81	<p>Point for the C-N. 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C N 1/16 S 17</p> <p style="text-align: center;">1968</p>
67.30	Gila River, 1.00 chn. wide, 3 ft. deep, course W.
79.80	The 1/4 sec. cor. of secs. 8 and 17.
19.975	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p> <p>WEST, along the E. and W. center line of sec. 17.</p> <p>Over bottom land, through dense undergrowth.</p> <p>Point for the C-E. 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C E 1/16 S 17</p> <p style="text-align: center;">1968</p>
39.95	The center 1/4 sec. cor. of sec. 17.
59.94	<p>Point for the C-W. 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C W 1/16 S 17</p> <p style="text-align: center;">1968</p>
79.93	The 1/4 sec. cor. of secs. 17 and 18.
13.20	<p>From the C-E. 1/16 sec. cor. of sec. 17.</p> <p>N. 0° 19' E., along the N. and S. center line of the NE¼ of sec. 17.</p> <p>Gila River, 1.00 chn. wide, 3 ft. deep, course WNW.</p>

Subdivision of Section 17
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
20.025	<p>Point for the NE. 1/16 sec. cor. of sec. 17, at the intersection with the E. and W. center line of the NE$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W NE 1/16 S 17 1968</p>
22.50	Gila River, 1.00 chn. wide, 3 ft. deep, course WNW.
40.05	The E. 1/16 sec. cor. of secs. 8 and 17.
20.02	<p>From the N. 1/16 sec. cor. of secs. 16 and 17.</p> <p>S. 89° 55' W., along the E. and W. center line of the NE$\frac{1}{4}$ of sec. 17.</p>
36.74	The NE. 1/16 sec. cor. of sec. 17.
39.84	Gila River, 70 lks. wide, 2 ft. deep, course WNW.
40.04	The C-N. 1/16 sec. cor. of sec. 17.
19.92	<p>From the W. 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 0° 07' E., along the N. and S. center line of the SW$\frac{1}{4}$ of sec. 17.</p> <p>Point for the SW. 1/16 sec. cor. of sec. 17, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W SW 1/16 S 17 1968</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high W. of the corner.</p>
39.84	The C-W. 1/16 sec. cor. of sec. 17.
19.95	<p>From the C-S. 1/16 sec. cor. of sec. 17.</p> <p>S. 89° 59' W., along the E. and W. center line of the SW$\frac{1}{4}$ of sec. 17.</p>
39.90	The SW. 1/16 sec. cor. of sec. 17.
39.90	The S. 1/16 sec. cor. of secs. 17 and 18.

Subdivision of Section 18
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 03' E., along the N. and S. center line of sec. 18.</p> <p>Over bottom land, through dense undergrowth.</p>
19.96	<p>Point for the C-S. 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C S 1/16 S 18</p> <p style="text-align: center;">1968</p>
36.60	<p>Gila River, 40 lks. wide, 3 ft. deep, course W.</p>
39.92	<p>Point for the center 1/4 sec. cor. of sec. 18, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C 1/4 S 18</p> <p style="text-align: center;">1968</p>
59.89	<p>Point for the C-N. 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R3W C N 1/16 S 18</p> <p style="text-align: center;">1968</p>
	<p>from which</p> <p style="padding-left: 40px;">A well casing, 20 ins. diam., projecting 3 ft. above ground, bears S. 82° 33' E., 1.46 chs. dist.</p>
79.86	<p>The 1/4 sec. cor. of secs. 7 and 18.</p>
	<p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>S. 89° 18' W., along the E. and W. center line of sec. 18.</p> <p>Over bottom land, through dense undergrowth.</p>
20.62	<p>Point for the C-E. 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 18
 Township 1 South, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R3W C E 1/16 S 18</p> <p style="text-align: center;">1968</p> <p>38.70 Gila River, 60 lks. wide, 2 ft. deep, course SW.</p> <p>41.24 The center 1/4 sec. cor. of sec. 18.</p> <p>61.78 Point for the C-W. 1/16 sec. cor. of sec. 18, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W C W 1/16 S 18</p> <p style="text-align: center;">1968</p> <p>80.08 The 1/4 sec. cor. of secs. 13 and 18, on the W. boundary of the township, hereinbefore described.</p> <hr/> <p>From the C-E. 1/16 sec. cor. of sec. 18.</p> <p>N. 0° 02.5' E., along the N. and S. center line of the NE¼ of sec. 18.</p> <p>10.30 Gila River, 60 lks. wide, 2 ft. deep, course SW.</p> <p>19.95 Point for the NE. 1/16 sec. cor. of sec. 18, at the intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T1S R3W NE 1/16 S 18</p> <p style="text-align: center;">1968</p> <p>39.90 The E. 1/16 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the N. 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 89° 20.5' W., along the E. and W. center line of the NE¼ of sec. 18.</p> <p>20.61 The NE. 1/16 sec. cor. of sec. 18.</p> <p>41.22 The C-N. 1/16 sec. cor. of sec. 18.</p>
	<p>From the E. 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 0° 02.5' E., along the N. and S. center line of the SE¼ of sec. 18.</p>

Subdivision of Section 18
Township 1 South, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
19.94	Point for the SE. 1/16 sec. cor. of sec. 18, at the intersection with the E. and W. center line of the SE $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R3W SE 1/16 S 18 1968</p>
39.88	The C-E. 1/16 sec. cor. of sec. 18.
	<p>From the S. 1/16 sec. cor. of secs. 17 and 18.</p> <p>S. 89° 14' W., along the E. and W. center line of the SE$\frac{1}{4}$ of sec. 18.</p>
20.61	The SE. 1/16 sec. cor. of sec. 18.
41.22	The C-S. 1/16 sec. cor. of sec. 18.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area resurveyed in this township, for the most part, is low bottom land, with some medium foothills in the southern portion, covered with greasewood, ocotillo, palo verde, cacti and sparse grass.</p> <p>The Gila River cuts through the township from east to west with an overflow bottom of approximately one mile in width, covered mostly with dense salt cedar, willows, scattered mesquite and sparse grass.</p> <p>The city of Buckeye is located in section 5, which is out of the area surveyed.</p>

CHAINS

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Leo J. Woster	Surveying Technician
Darwin E. Johnston	Surveying Aid
R. Wayne Wilson	Surveying Aid
William L. McDorman	Surveying Aid
Victor E. Templeton	Surveying Aid
Ned E. Carnahan	Surveying Aid
James S. Pritchard	Surveying Aid

CERTIFICATE OF SURVEY

I, Richard L. Oakes, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23 day of January, 1968, I have dependently resurveyed portions of the east and west boundaries, a portion of the subdivisional lines, and subdivided certain sections in T. 1 S., R. 3 W., Gila and Salt River Meridian, Arizona.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by me and under my direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 9, 1974 (Date)

Richard L. Oakes (Cadastral Surveyor)

Richard L. Oakes

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date AUG 26 1974

BUREAU OF LAND MANAGEMENT, Washington, D. C.

The foregoing field notes of the dependent resurvey of portions of the east and west boundaries, a portion of the subdivisional lines, and the subdivision of certain sections in T. 1 S., R. 3 W., Gila and Salt River Meridian, Arizona.

executed by Richard L. Oakes Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

FEB 4 1976 (Date)

Bernard W. Fisher Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)