

1A

BOOK 5013

INDEX DIAGRAM

Township 1 South, Range 4 West

6	5	4	3	2	1
7	8	9	10	11 11	12 6
18 25	17 25	16 19	15 15	10 14 9	5 13 5
2 19 23	23 20 22	18 21 17	14 22 13	8 23 8	3 24
2 30 20	21 29	16 28 16	13 27 12	7 26	25
31	32	33	34	35	36

- Subdivision of section 13 pp 26-28
- Subdivision of section 14 pp 28-30
- Subdivision of section 19 pp 30-31
- Subdivision of section 20 pp 31-33
- Subdivision of section 21 pp 33-36
- Subdivision of section 22 pp 36-39
- Subdivision of section 23 pp 39-40
- Subdivision of section 27 pp 40-41
- Subdivision of section 28 pp 41-42
- Subdivision of section 29 pp 42-44
- Subdivision of section 30 pp 44-45

Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of a dependent resurvey of a portion of the west boundary, a portion of the subdivisional lines, and the subdivision of certain sections in Township 1 South, Range 4 West of the Gila and Salt River Meridian, Arizona.

Earlier pertinent surveys are tabulated as follows:

<u>Lines Surveyed</u>	<u>By Whom</u>	<u>Date</u>
Base Line (N. Bdy.) and E. and S. Bdrs.	R. C. Powers	1882
W. Boundary	R. C. Powers	1882-83
Subdivisional Lines	R. C. Powers	1883
South Boundary (Res.)	K. L. Siebecker	1931
Portions of the E. and W. Bdrs. and Subdivisional Lines (Res.)	Donald E. Harding	1958
Portion of the E. Boundary (Res.)	Concurrently	

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated January 23, 1968.

The directions of all lines of this survey were determined by direct altitude observation on the sun for azimuth, and verified by a line of known azimuth at U. S. Coast and Geodetic Survey triangulation station "Power Butte" and its azimuth mark. This station is located in section 26 of Township 1 South, Range 5 West. All lines were adjusted for difference in longitude and refer to the true meridian. The adjusted horizontal distances, only, are entered in this field note record.

Preliminary to the resurvey, the lines of the original surveys and the resurveys were retraced and a diligent search made for any evidence of the corner positions. Many of the corners of the original survey in this township have been remonumented with various kinds of durable materials, in the years previous, by County Surveyors and the Arizona Public Service Company. In some instances where physical evidence of a corner monument could not be found, the intersection of section line roads and property boundary fence lines, constructed before corners were destroyed, were used to determine the corner positions. Missing corners were reestablished according to the rules of proportionate measurement. Accessory material was not available for many of the corners established in this survey.

The geographic position of the SE. corner of section 13, as scaled from U. S. G. S. sheet, "Buckeye", Arizona, is:

Latitude: 33° 20.0' N.
Longitude: 112° 36.4' W.

The observed mean magnetic declination is 14° E.

Dependent Resurvey of a Portion
of the West Boundary
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U.S. Deputy Surveyor, in 1882-83 and the Resurvey Executed by Donald E. Harding, Cadastral Surveyor, in 1958</p> <hr/> <p>Beginning at the 1/4 sec. cor. of secs. 25 and 30, on the W. boundary of the township, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R5W R4W ¼ S 25 S 30</p> <p style="text-align: center;">1958</p> <p>Set a salt cedar post, 6 ins. diam., projecting 3 ft. above the ground, W. of the corner.</p> <p>N. 0° 06' E., between secs. 25 and 30.</p> <p>Over bottom land, through dense brush.</p> <p>39.71 Point for the cor. of secs. 19, 24, 25, and 30, at pro- portionate distance. There is no remaining evidence of the 1958 resurvey monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R5W R4W S 24 S 19 S 25 S 30</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., W. of the corner.</p>	
	<p>N. 0° 06' E., between secs. 19 and 24.</p> <p>Over bottom land, through dense brush.</p> <p>30.00 SE. bank of Hassayampa River, bears SW. to NNE., thence along dry river bed.</p> <p>39.71 True point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance. There is no remaining evidence of the 1958 resurvey monument. This point falls in the center of the dry Hassayampa River bed, impractical for monumentation.</p> <p>49.21 E. bank of the Hassayampa River, bears S. to NW.</p> <p>49.31 Selected point for the witness 1/4 sec. cor. of secs. 19 and 24.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, in a collar of stone, 3 ft. base to top, with brass cap mkd.</p>	

Dependent Resurvey of a Portion
of the West Boundary
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

<p>CHAINS</p>	<p>W C T1S R5W R4W $\frac{1}{4}$ S 24 S 19 ↓ 1968</p>
<p>79.42</p>	<p>Set a wood post, 4 ins. square, W. of the corner.</p> <p>The cor. of secs. 13, 18, 19, and 24, monumented with an iron pipe, 1½ ins. diam., set 12 ins. below the surface of intersection of graded roads bearing N., E., and W. There is no evidence of the resurvey sandstone.</p> <p>from which</p> <p>An iron post, 2½ ins. diam., projecting 20 ins. above the ground, bears N. 51 3/4° W., 35.4 ft. dist., with brass cap mkd. RM T1S R5W S13 1958 and an arrow pointing to the corner. Reset the iron post, 26 ins. in the ground, and add the markings 35.4 FT.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 1/2 in. diam., 30 ins. long, 10 ins. below surface of the road, with brass cap mkd.</p>
	<p>T1S R5W R4W <u>S 13 S 18</u> <u>S 24 S 19</u> 1968</p>
	<p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 25 ins. in the ground for a reference monument, bears S. 51 3/4° E., 35.4 ft. dist., with brass cap mkd. RM T1S R4W S19 35.4 FT 1968, with an arrow pointing to the corner.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>
	<p>Reestablishment of the Survey Executed by R. C. Powers, U.S. Deputy Surveyor, in 1883 and the Resurvey Executed by Donald E. Harding, Cadastral Surveyor, in 1958</p> <hr/> <p>From the cor. of secs. 23, 24, 25, and 26, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	T1S R4W S 23 S 24 S 26 S 25
	1958
	N. 0° 07' E., between secs. 23 and 24.
	Over level land, through thick mesquite brush.
4.60	Concrete irrigation ditch, flows W.
23.90	Fence, bears E. and W.
24.76	Road, bears E. and W.
39.81	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance. The 1958 iron post was torn out by a bulldozer and lying loose on the ground.
	Reset the 1958 monument, an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T1S R4W ¼ S 23 S 24
	1958
58.92	Fence, bears E. and W.
59.715	Point for the N 1/16 sec. cor. of secs. 23 and 24.
	Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.
	T1S R4W N 1/16 S 23 S 24
	1968
	Deposit broken glass in ground around corner.
61.32	Woven wire fence, bears NE. and SW., leave mesquite brush and enter salt cedar.
69.31	S. bank of river canal, bears SW. and NE.
69.60	River canal, 3 ft. deep, course SW.
69.90	N. bank of river canal, bears SW. and NE.
79.62	The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2½ ins. diam., firmly set with 16 ins. projecting above ground, supported by a collar of stone, 3 ft. base to top, with brass cap mkd.
	T1S R4W S 14 S 13 S 23 S 24
	1958

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. boundary of the township, monumented with an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the field note record of the W. boundary of T. 1 S., R. 3 W., resurveyed concurrently with this Group.</p> <p>N. 89° 57' W., between secs. 13 and 24. Over bottom land, through dense salt cedar.</p>
19.99	<p>Point for the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W E 1/16 $\frac{S\ 13}{S\ 24}$ 1968</p>
39.98	<p>The 1/4 sec. cor. of secs. 13 and 24, monumented with an iron post, 2½ ins. diam., firmly set with 2 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W 1/4 $\frac{S\ 13}{S\ 24}$ 1958</p> <p style="text-align: center;">_____</p>
19.97	<p>N. 89° 49' W., beginning new measurement.</p> <p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W W 1/16 $\frac{S\ 13}{S\ 24}$ 1968</p>
30.39	<p>Center line of U. S. Highway No. 80, bears N. 1° 33' W., and S. 1° 33' E. From this point, the PC of a curve left on the highway center line, bears N. 1° 33' W., 32.31 chs. dist. The long chord of the curve is N. 4° 32' 30" W., 36.245 chs. (2392.25 ft.), and the radius is 22,918.32 ft.</p>
39.94	<p>The cor. of secs. 13, 14, 23, and 24.</p>
19.855	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883</p> <p style="text-align: center;">_____</p> <p>N. 0° 26' E., between secs. 13 and 14.</p> <p>Point for the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 1/16 S 14 S 13 1968</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.71	<p>Set a steel guard post E. of the corner.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance. There is no remaining evidence of the original monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 14 S 13</p> <p style="text-align: center;">1968</p>
66.80	<p>Center line of Arlington Canal, 3 ft. deep, course S. 68° 35' W. From this point, the intersection of the center line of this canal with the center line of U. S. Highway No. 80, bears N. 68° 35' E., 5.63 chs. dist.</p>
79.42	<p>The corner of secs. 11, 12, 13, and 14, determined latitudinally in line with an old fence to the W. and longitudinally by center line of old right-of-way to the S. This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., flush with the surface of trail road, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 11 S 12 S 14 S 13</p> <p style="text-align: center;">1968</p> <p>from which</p> <p style="padding-left: 40px;">An iron pin, 1/2 in. diam., set firmly in the ground, bears S. 86° 00' E., 26 lks. dist.</p>
	<p>From the cor. of secs. 7, 12, 13, and 18, on the E. boundary of the township, monumented with an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the field note record of the W. boundary of T. 1 S., R. 3 W., resurveyed concurrently with this Group.</p> <p>S. 89° 43' W., between secs. 12 and 13.</p> <p>Over rolling land, through sagebrush.</p>
39.81	<p>Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate distance. There is no remaining evidence of the original monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 12 S 13</p> <p style="text-align: center;">1968</p>
47.12	<p>Center line of Arlington Canal, course S. 68° 35' W. From this point, the intersection of the center line of this canal with the center line of U. S. Highway No. 80, bears S. 68° 35' W., 29.38 chs. dist.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS				
75.87	Center line of U. S. Highway No. 80, bears N. 7° 32' W., and S. 7° 32' E. From this point, the PT of a curve on the highway center line, bears S. 7° 32' E., 11.15 chs. dist. and the intersection of the highway center line with the center line of the Arlington Canal, bears S. 7° 32' E., 10.68 chs. dist.			
79.62	The cor. of secs. 11, 12, 13, and 14.			
	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883 and the Resurvey Executed by Donald E. Harding, Cadastral Surveyor, in 1958</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 26, 27, 34, and 35, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T1S R4W</td></tr> <tr><td>S 27 S 26</td></tr> <tr><td>S 34 S 35</td></tr> </table> <p>1958</p> </div> <p>A mound of stone, 3 ft. base, 2½ ft. high, is W. of the corner.</p> <p>N. 0° 25' W., between secs. 26 and 27.</p> <p>Over rolling land, through scattered undergrowth.</p>	T1S R4W	S 27 S 26	S 34 S 35
T1S R4W				
S 27 S 26				
S 34 S 35				
39.95	The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above the ground, with brass cap mkd.			
	<div style="text-align: center;"> <table style="margin: auto;"> <tr><td>T1S R4W</td></tr> <tr><td>¼</td></tr> <tr><td>S 27 S 26</td></tr> </table> <p>1958</p> </div> <p>A mound of stone, 3 ft. base, 2 ft. high is W. of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 25' W., beginning new measurement.</p>	T1S R4W	¼	S 27 S 26
T1S R4W				
¼				
S 27 S 26				
19.40	Irrigation ditch, bears E. and W., along E. edge of road, bears E. to N.			
39.93	The cor. of secs. 22, 23, 26, and 27, reestablished by record bearing and distance from the only remaining 1958 resurvey reference monument:			
	<p style="padding-left: 40px;">An iron post, 2½ ins. diam., firmly set with 8 ins. projecting above the ground, bears N. 74° 58' W., 40 lks. dist., mkd. RM T1S R4W S22 1958 and an arrow pointing to the corner.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2 in. diam., 6 ins. below the surface of the road, with brass cap, 1½ ins. diam., mkd.</p>			

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R4W S 22 S 23 <u> </u> S 27 S 26</p> <p style="text-align: center;">1968</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 44¼° E., 42.2 ft. dist., with brass cap mkd. T1S R4W S26 RM 42.2 FT 1968, and an arrow pointing to the corner.</p>
39.95	<p>From the cor. of secs. 23, 24, 25, and 26.</p> <p>N. 89° 48' W., between secs. 23 and 26.</p> <p>Over nearly level land, through scattered undergrowth.</p> <p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.</p>
40.47	<p style="text-align: center;">T1S R4W ¼ S 23 <u> </u> S 26</p> <p style="text-align: center;">1958</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 58' W., beginning new measurement.</p> <p>The cor. of secs. 22, 23, 26, and 27.</p>
19.75	<p>N. 0° 35' E., between secs. 22 and 23.</p> <p>Over level bottom land, through scattered mesquite brush.</p> <p>Point for the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
22.00 34.50 38.10 39.50	<p style="text-align: center;">T1S R4W S 1/16 S 22 S 23</p> <p style="text-align: center;">1968</p> <p>Set a wood guard post, 8 ins. square, W. of the corner.</p> <p>Fence, bears E. and W.</p> <p>Leave mesquite, enter salt cedar.</p> <p>Fence, bears NE. and SW.</p> <p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T1S R4W $\frac{1}{4}$ S 22 S 23</p> <p style="text-align: center;">1958</p> <p>A mound of stone, 2 ft. base, 1½ ft. high, is W. of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 36' E., beginning new measurement.</p> <p>2.58 S. bank of Gila River, in a man-made channel, bears NW. and SE.</p> <p>2.82 Gila River, 2 ft. deep, course NW.</p> <p>3.07 N. bank of river, bears NW. and SE.</p> <p>39.45 The cor. of secs. 14, 15, 22, and 23, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T1S R4W S 15 S 14 <hr style="width: 50%; margin: auto;"/>S 22 S 23</p> <p style="text-align: center;">1958</p>	
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 89° 36' W., between secs. 14 and 23.</p> <p>19.93 Point for the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T1S R4W E 1/16 $\frac{S 14}{S 23}$</p> <p style="text-align: center;">1968</p>	
	<p>37.87 Leave salt cedar, enter mesquite.</p> <p>39.86 The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2½ ins. diam., firmly set with 2 ins. projecting above ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T1S R4W $\frac{1}{4}$ $\frac{S 14}{S 23}$</p> <p style="text-align: center;">1958</p> <p>A mound of stone, 2 ft. base, 1½ ft. high, is N. of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 35' W., beginning new measurement.</p> <p>15.15 Leave mesquite, enter dense salt cedar.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

<p>CHAINS 19.95</p>	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W W 1/16 $\frac{S\ 14}{S\ 23}$ 1968</p>
<p>39.90</p>	<p>The cor. of secs. 14, 15, 22, and 23.</p> <hr/> <p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883</p> <hr/> <p>N. 0° 29' E., between secs. 14 and 15.</p> <p>Over river bottom land, through salt cedar.</p>
<p>13.00</p>	<p>Gila River overflow channel, course SW.</p>
<p>26.80</p>	<p>Trail road, bears E. and W.</p>
<p>28.79</p>	<p>Arlington Canal, 3 ft. deep, course S. 59° 05' W.</p>
<p>39.77</p>	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate distance. There is no remaining evidence of the original monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W $\frac{1}{4}$ S 15 S 14 1968</p> <p>from which</p> <p style="padding-left: 40px;">An iron pipe, 1 in. diam., set firmly in the ground, painted red, bears S. 0° 15' W., 66.4 lks. dist.</p> <p style="padding-left: 40px;">An iron pipe, 1½ ins. diam., set firmly in the ground, with 4 ins. brass cap mkd. Maricopa County Eng. Dept., bears N. 74½° W., 37.8 ft. dist.</p>
<p>40.60</p>	<p>Irrigation canal, course SW., thence along fence.</p>
<p>77.15</p>	<p>Cor. of fences, bears E., W., and S., on the S. right-of-way line of old Highway No. 80.</p>
<p>77.89</p>	<p>Center line of old U. S. Highway No. 80, bears E. and W.</p>
<p>79.13</p>	<p>Irrigation Canal, course W.</p>
<p>79.54</p>	<p>Point for the cor. of secs. 10, 11, 14, and 15, determined latitudinally at proportionate distance and longitudinally on projection of fence to the S. and center line of lane to the N. This point is accepted as the best available evidence of the original corner position.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 10 S 11 S 15 S 14</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 60 ¾° W., 51.1 ft. dist., with brass cap mkd. RM T1S R4W S10 51.1 FT 1968, and an arrow pointing to the corner.</p> <p>An iron pipe, 1¼ ins. diam., set firmly in the ground, with brass cap 4 ins. diam., mkd. Maricopa County Eng. Dept., bears N. 76° 00' W., 77.3 lks. dist.</p>
	<p>From the cor. of secs. 11, 12, 13, and 14.</p> <p>S. 89° 42' W., between secs. 11 and 14.</p> <p>Over nearly level land.</p> <p>13.40 Center line of old U. S. Highway No. 80, on curve NE. and SW.</p> <p>19.10 Irrigation canal, course W.</p> <p>21.60 Road, parallel to canal ENE. to W., thence along road.</p> <p>39.60 Point for the 1/4 sec. cor. of secs. 11 and 14, determined longitudinally in line with fence to the N. and latitudinally on line between adjacent section corners. This point is accepted as the best available evidence of the original corner position.</p>
<p>40.11</p>	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 11 S 14</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 58¼° E., 41.3 ft. dist., with brass cap mkd. RM T1S R4W S11 41.3 FT 1968, and an arrow pointing to the corner.</p> <p style="text-align: center;">_____</p> <p>S. 89° 42' W., beginning new measurement.</p> <p>The cor. of secs. 10, 11, 14, and 15.</p> <hr/> <p>N. 0° 32' E., between secs. 10 and 11.</p> <p>Along center line of dirt road.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	<p>39.77 The 1/4 sec. cor. of secs. 10 and 11, determined at the intersection of the center lines of Hazen Road, bearing E. and W., and Turner Road bearing N. and S. This point is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2 in. diam., flush with the surface of the road, with brass cap, 1 1/2 ins. diam., mkd.</p> <p style="text-align: center;">T1S R4W 1/4 S 10 S 11</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An "X" chiseled in a concrete headwall, bears N. 63 3/4° E., 29.5 ft. dist.</p> <p>An "X" chiseled in a concrete headwall, bears S. 56 3/4° E., 30.3 ft. dist.</p> <p>An "X" chiseled in a concrete headwall, bears S. 67 1/4° W., 43.0 ft. dist.</p> <p>An "X" chiseled in a concrete headwall, bears N. 67 1/2° W., 42.5 ft. dist.</p>
9.10	<p style="text-align: center;">Reestablishment of the Survey Executed by R. C. Powers, U. S. Deputy Surveyor, in 1883, and the Resurvey Executed by Donald E. Harding, Cadastral Surveyor, in 1958</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 26, 27, 34, and 35.</p> <p>N. 89° 51' W., between secs. 27 and 34.</p> <p>Over rolling land, through scattered undergrowth.</p> <p>Fence, bears N. and S.</p>
39.98	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W 1/4 S 27 S 34</p> <p style="text-align: center;">1958</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is N. of the corner.</p>
14.30	<p>Road, bears NNE. and SSW.</p>
39.98	<p>The cor. of secs. 27, 28, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., firmly set with 10 ins. projecting above ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T1S R4W S 28 S 27 S 33 S 34</p> <p style="text-align: center;">1958</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W. of the corner.</p>	
	<p>N. 0° 18' E., between secs. 27 and 28.</p> <p>Over rolling land, through scattered undergrowth.</p>	
0.76	Trail road, bears NE. and SW.	
3.06	Trail road, bears NW. and SE.	
39.53	Trail road, bears E. and W.	
39.97	The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.	
	<p style="text-align: center;">T1S R4W 1/4 S 28 S 27</p> <p style="text-align: center;">1958</p>	
	<p>N. 0° 23' E., beginning new measurement.</p>	
19.52	Dike, bears E. and W.	
23.11	Fence, bears E. and W.	
35.51	Concrete ditch, bears SSE. and NNW., thence along lane alongside ditch.	
40.00	The cor. of secs. 21, 22, 27, and 28, monumented with an iron post, 2½ ins. diam., set flush with the surface of the ground, with brass cap mkd.	
	<p style="text-align: center;">T1S R4W S 21 S 22 S 28 S 27</p> <p style="text-align: center;">1958</p>	
	<p>This corner is located in a fence line bearing N. and S.</p>	
	<p>From the cor. of secs. 22, 23, 26, and 27.</p> <p>N. 89° 42' W., between secs. 22 and 27.</p> <p>Over nearly level land, through mesquite brush, along fence and irrigation canal.</p>	
18.85	Road, bears N.	
19.72	Point for the E 1/16 sec. cor. of secs. 22 and 27. Did not monument this point, falls in private land.	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.44	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 22 S 27</p> <p style="text-align: center;">1958</p> <p>This corner falls on edge of trail road.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 42' W., beginning new measurement.</p>
19.72	<p>Point for the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W W 1/16 S 22 S 27</p> <p style="text-align: center;">1958</p> <p>Set a steel fence post, 6 ft. long, N. of the cor. Corner falls 2 lks. S. of fence, bears E. and W.</p>
39.44	<p>The cor. of secs. 21, 22, 27, and 28.</p>
5.06	<p>N. 0° 13' W., between secs. 21 and 22.</p> <p>Along fence bearing N. and S. on E. side of road.</p> <p>Corner of fences bearing E., W., and S., through dense salt cedar over river bottom land.</p>
19.54	<p>Point for the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 1/16 S 21 S 22</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., W. of the corner.</p>
39.08	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 21 S 22</p> <p style="text-align: center;">1958</p> <hr style="width: 20%; margin: auto;"/>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0° 08' W., beginning new measurement.
19.52	Point for the N 1/16 sec. cor. of secs. 21 and 22.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W N 1/16 S 21 S 22</p>
	<p style="text-align: center;">1968</p>
	Set a salt cedar post, 4 ins. diam., W. of the corner.
31.53	Gila River, 5 ft. deep, 16 ft. wide, course W.
35.12	Canal road, bears E. and W. Leave salt cedar.
35.50	Arlington Canal, course W., enter cultivated land, along fence, bears N.
39.04	The cor. of secs. 15, 16, 21, and 22, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W S 16 S 15 S 21 S 22</p>
	<p style="text-align: center;">1958</p>
	From the cor. of secs. 14, 15, 22, and 23.
	S. 89° 42' W., between secs. 15 and 22.
	Over river bottom land, through dense salt cedar.
19.97	Point for the E 1/16 sec. cor. of secs. 15 and 22.
	Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W E 1/16 S 15 S 22</p>
	<p style="text-align: center;">1968</p>
	Set a guard post, N. of the corner.
21.45	Leave bottom land, and salt cedar, along bench through dense undergrowth.
39.94	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set with 5 ins. projecting above ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W ¼ S 15 S 22</p>
	<p style="text-align: center;">1958</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 89° 41' W., beginning new measurement.</p> <p>19.98 Point for the W 1/16 sec. cor. of secs. 15 and 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T1S R4W</p> <p>W 1/16 $\frac{S\ 15}{S\ 22}$</p> <p>1968</p> </div> <p>37.66 Dirt road, bears NE. and SW.</p> <p>38.10 Arlington Canal, 2 ft. deep, 45 ft. wide, course SW.</p> <p>39.66 Ditch, 10 lks. wide, course S.</p> <p>39.96 The corner of secs. 15, 16, 21, and 22.</p>
40.01	<p>From the cor. of secs. 27, 28, 33, and 34.</p> <p>S. 89° 40' W., between secs. 28 and 33.</p> <p>Over rolling land, through scattered underbrush.</p> <p>The 1/4 sec. cor. of secs. 28 and 33, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T1S R4W</p> <p>¼ $\frac{S\ 28}{S\ 33}$</p> <p>1958</p> </div> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 41' W., beginning new measurement.</p> <p>5.00 Trail road, bears N. and S.</p> <p>39.93 The cor. of secs. 28, 29, 32, and 33, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T1S R4W</p> <p>$\frac{S\ 29}{S\ 32} \frac{S\ 28}{S\ 33}$</p> <p>1958</p> </div> <p>A mound of stone, 3 ft. base, 2 ft. high, is W. of the corner.</p>
	<p>N. 0° 17' E., between secs. 28 and 29.</p> <p>Over rolling land, through scattered undergrowth.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
39.66	<p>The 1/4 sec. cor. of secs. 28 and 29, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 29 S 28</p> <p style="text-align: center;">1958</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 15' E., beginning new measurement.</p>	
19.82	<p>Point for the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W N 1/16 S 29 S 28</p> <p style="text-align: center;">1968</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the corner.</p>	
39.24	<p>Bank 20 ft. high, descend to river bottom land, enter dense salt cedar.</p>	
39.64	<p>The cor. of secs. 20, 21, 28, and 29, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 20 S 21 S 29 S 28</p> <p style="text-align: center;">1958</p> <p>A wood post, 2 ins. diam., projecting 3 ft. above the ground, is W. of the corner.</p>	
20.02	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>S. 89° 11' W., between secs. 21 and 28.</p> <p>Over nearly level land, through bird feed area.</p> <p>Point for the E 1/16 sec. cor. of secs. 21 and 28. This point falls in swamp type of land, made by the State Game and Fish Service to grow bird feed, therefore did not monument this point.</p>	
39.18	<p>Trail road on top of dike, bears N. and S.</p>	
39.53	<p>Point selected for the witness 1/4 sec. cor. of secs. 21 and 28.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T1S R4W $\frac{1}{4} \leftarrow \frac{S\ 21}{S\ 28} WC$</p> <p style="text-align: center;">1968</p> <p>Set a steel fence post, 1 lk. N. of the corner.</p>
40.04	True point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate distance. There is no remaining evidence of the 1958 resurvey corner. Corner falls in bottom of wash, impractical for monumentation.
45.00	Ascend NE. slope of Robins Butte.
56.60	Top of ascent, descend NW. slope.
70.00	End of descent, over nearly level land, through desert undergrowth.
78.60	Descend bank, bears NE. and SW., 20 ft. high to river bottom land, enter dense salt cedar.
80.08	The cor. of secs. 20, 21, 28, and 29.
	<p>N. 0° 12' E., between secs. 20 and 21.</p> <p>Over river bottom land, through dense salt cedar.</p>
6.90	Gila River, course W.
19.87	Point for the S 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W S 1/16 S 20 S 21</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 6 ins. diam., projecting 3 ft. above the ground, W. of the corner.</p>
39.74	The 1/4 sec. cor. of secs. 20 and 21, monumented with an iron post, 2½ ins. diam., firmly set with 4 ins. projecting above ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W $\frac{1}{4}$ S 20 S 21</p> <p style="text-align: center;">1958</p> <p>A mound of stone, 2 ft. base, 1 ft. high, is W. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 16' E., beginning new measurement.</p>
19.77	Point for the N 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.54	<p style="text-align: center;">T1S R4W N 1/16 S 20 S 21</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 6 ins. diam., W. of the corner.</p> <p>The cor. of secs. 16, 17, 20, and 21, reestablished longitudinally on projection of center line of road to the N. and latitudinally on projection of center line of road to the W. There was no evidence of an E. and W. fence or the 1958 corner monument mentioned in the 1958 resurvey notes. This point is accepted as the best available evidence of the position of the 1958 resurvey corner.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 17 S 16 S 20 S 21</p> <p style="text-align: center;">1968</p> <p>Set a wood post, 4 ins. square, W. of the corner.</p>
19.88 39.76 59.64	<p>From the cor. of secs. 15, 16, 21, and 22.</p> <p>WEST, between secs. 16 and 21.</p> <p>Through cotton field.</p> <p>Point for the E 1/16 sec. cor. of secs. 16 and 21. Did not monument this point as falls in cotton field.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate distance. No evidence of the 1958 witness corner or stone buried in the field could be found. Did not monument this point as fell in cotton field.</p> <p>Point for the W 1/16 sec. cor. of secs. 16 and 21. Corner falls in center of trail road.</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2 in. diam., 8 ins. below the surface of the road, with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">T1S R4W W 1/16 $\frac{S 16}{S 21}$</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 26 ins. in the ground, for a reference monument, bears S. 32½° W., 35.5 ft. dist., with brass cap mkd. RM T1S R4W W 1/16 S21 35.5 FT 1968 and an arrow pointing to the corner.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>An iron post, 30 ins. long, 2½ ins. diam., set 26 ins. in the ground for a reference monument, bears N. 27¼° W., 28.0 ft. dist., with brass cap mkd. RM T1S R4W W 1/16 S16 28.0 FT 1968, and an arrow pointing to the corner.</p>
59.80	<p>Leave cultivated land, over nearly level land, through undergrowth.</p>
79.52	<p>The cor. of secs. 16, 17, 20, and 21.</p>
	<p>From the cor. of secs. 29, 30, 31, and 32, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;"> T1S R4W <u>S 30 S 29</u> S 31 S 32 </p> <p style="text-align: center;">1958</p> <p>A mound of stone, 3 ft. base, 1½ ft. high, is W. of the corner.</p> <p>S. 88° 56' W., between secs. 30 and 31.</p> <p>Over rolling land, through desert undergrowth.</p>
4.60	<p>Wash, course NNE.</p>
20.06	<p>Point for the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T1S R4W <u>S 30</u> E 1/16 S 31 </p> <p style="text-align: center;">1968</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of the corner.</p>
40.12	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;"> T1S R4W ¼ <u>S 30</u> S 31 </p> <p style="text-align: center;">1958</p> <p>A mound of stone, 3 ft. base, 2½ ft. high, N. of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 52' W., beginning new measurement.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
39.66	<p>The cor. of secs. 25, 30, 31, and 36, on the W. boundary of the township monumented with an iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R5W R4W S 25 S 30 S 36 S 31</p> <p style="text-align: center;">1958</p> <p>This corner is located 1 lk. SE. of corner of fences bearing N. and W.</p>
8.20	<p>From the cor. of secs. 29, 30, 31, and 32. N. 0° 12' E., between secs. 29 and 30. Over rolling land, through desert undergrowth.</p> <p>Wash, course NW.</p>
19.59	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 1/16 S 30 S 29</p> <p style="text-align: center;">1968</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of the corner.</p>
26.30	<p>Wash, course NNW.</p>
32.50	<p>Trail road, bears E. and W., enter thick mesquite brush.</p>
39.18	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 30 S 29</p> <p style="text-align: center;">1958</p> <p>A wood post, 6 ins. square, projecting 8 ft. above the ground, is set W. of the corner.</p>
	<p style="text-align: center;">_____</p> <p>N. 0° 11' E., beginning new measurement.</p>
4.39	<p>Top of bank, 20 ft. high, descend to river bottom land.</p>
4.60	<p>Over river bottom land, through salt cedar.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>19.57</p>	<p>Point for the N 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W N 1/16 S 30 S 29</p> <p style="text-align: center;">1968</p>
<p>39.14</p>	<p>Point for the cor. of secs. 19, 20, 29, and 30, at proportionate distance. There is no remaining evidence of the 1958 resurvey monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 19 S 20 S 30 S 29</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 6 ins. diam., W. of the corner.</p> <hr/> <p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89° 59' W., between secs. 20 and 29.</p> <p>Over river bottom land, through dense salt cedar.</p> <p>20.01 Point for the E 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W E 1/16 S 20 S 29</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., N. of the corner.</p> <p>22.00 Gila River, 6 ft. wide, 3 ft. deep, course S.</p> <p>40.02 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance. There is no remaining evidence of the 1958 resurvey monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 20 S 29</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 6 ins. diam., N. of the corner.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
60.03	<p>Point for the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W W 1/16 $\frac{S\ 20}{S\ 29}$</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., N. of the corner.</p>
80.04	<p>The cor. of secs. 19, 20, 29, and 30.</p>
	<p>N. 89° 38' W., between secs. 19 and 30.</p>
	<p>Over river bottom land, through dense salt cedar.</p>
0.50	<p>Gila River, course S.</p>
20.03	<p>Point for the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W E 1/16 $\frac{S\ 19}{S\ 30}$</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 8 ins. diam., N. of the corner.</p>
34.66	<p>Ditch, course S.</p>
40.06	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate distance. There is no remaining evidence of the 1958 resurvey monument.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ $\frac{S\ 19}{S\ 30}$</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 8 ins. diam., N. of the corner.</p>
79.91	<p>The cor. of secs. 19, 24, 25, and 30, on the W. boundary of the township, hereinbefore described.</p> <hr/> <p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0° 30' E., between secs. 19 and 20.</p> <p>Over river bottom land, through dense salt cedar.</p>
0.50	<p>Gila River, course SW.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
15.00	Leave dense salt cedar.	
19.57	Point for the S 1/16 sec. cor. of secs. 19 and 20.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.	
	T1S R4W S 1/16 S 19 S 20	
	1968	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.	
39.14	Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate position. There is no remaining evidence of the 1958 resurvey monument. This corner falls in an abandoned lane, but the fences of the 1958 survey had been removed.	
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.	
	T1S R4W ¼ S 19 S 20	
	1968	
	Set a mesquite post, 4 ins. diam., W. of the corner.	
	N. 0° 20' W., beginning new measurement.	
	Along abandoned lane.	
11.90	Trail road on S. bank of Arlington Canal, bears E. and W.	
12.22	Arlington Canal, course W.	
12.50	N. bank of Arlington Canal, along fenced land to graded road.	
39.93	The cor. of secs. 17, 18, 19, and 20, monumented with an iron pipe, 1½ ins. diam., set 12 ins. under the surface of the intersection of graded roads bearing N., S., E., and W.	
	from which 1958 reference monument	
	An iron post, 2½ ins. diam., firmly set with 8 ins. projecting above ground, bears S. 54¼° E., 52.6 ft. dist., (record: 52.8 ft.), mkd. RM T1S R4W S20 1958, and an arrow pointing to the corner. Added 52.6 FT to the markings.	
	At the corner point	
	Set a copper-coated steel stake, 30 ins. long, 1/2 in. diam., 12 ins. under surface of the road, with brass cap, 1½ ins. diam., mkd.	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T1S R4W S 18 S 17 S 19 S 20</p> <p style="text-align: center;">1968</p> <p>from which</p> <p>An iron post, 30 ins. long, 2½ ins. diam., set 26 ins. in the ground, for a reference monument, bears N. 54¼° W., 52.6 ft. dist., with brass cap mkd. RM T1S R4W S18 52.6 FT 1968 and an arrow pointing to the corner.</p> <p>Bury the iron pipe alongside the new monument.</p>	
<p>40.36</p>	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 89° 54' W., between secs. 17 and 20.</p> <p>Along graded road.</p> <p>The 1/4 sec. cor. of secs. 17 and 20, determined at record bearing and distance from a 1958 reference monument.</p> <p>An iron post, 2½ ins. diam., firmly set with 6 ins. projecting above ground, bears S. 39° W., 49.5 ft. dist. (record), mkd. RM T1S R4W S20 and an arrow pointing to the corner. Added 49.5 FT to the markings.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2 in. diam., 12 ins. under surface of road, with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 17 S 20</p> <p style="text-align: center;">1968</p> <p>from which another 1958 reference monument</p> <p>An iron post, 2½ ins. diam., bears N. 39° E., 34.3 ft. dist., (record: 49.5 ft. dist.) mkd. RM T1S R4W 1/4 S17 and an arrow pointing to the corner. This reference monument was loosely set in the ground, and is determined to have been moved from the original position. Reset the monument 26 ins. in the ground, and added 34.3 FT to the markings.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 54' W., beginning new measurement.</p>	
<p>39.87</p>	<p>The cor. of secs. 17, 18, 19, and 20.</p> <p>N. 89° 21' W., between secs. 18 and 19.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
<p>40.01</p>	<p>Along graded road.</p> <p>The 1/4 sec. cor. of secs. 18 and 19, monumented with an iron pipe 1½ ins. diam., set 12 ins. under surface of road.</p> <p>from which</p> <p>An iron post, 2½ ins. diam., loosely set with 10 ins. projecting above ground, with brass cap broken off, bears S. 19¼° E., 25.1 ft. dist. Replaced this reference monument with an iron post, 30 ins. long, 2½ ins. diam., set 20 ins. in the ground, in a collar of stone, with brass cap mkd. RM T1S R4W S19 25.1 FT 1968, and an arrow pointing to the corner.</p> <p>An iron post, 2½ ins. diam., set 2 ins. under surface of the ground, bears N. 19¼° W., 25.1 ft. dist., with brass cap mkd. RM T1S R4W S18 and an arrow pointing to the corner. Reset this corner 20 ins. in the ground, and add 25.1 FT to markings.</p> <p>At the corner point</p> <p>Set a copper-coated steel stake, 30 ins. long, 1/2 in. diam., 12 ins. below the surface of the road, with brass cap, 1½ ins. diam., mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 18 S 19</p> <p style="text-align: center;">1968</p> <p>Bury the iron pipe alongside the new monument.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 89° 27' W., beginning new measurement.</p>	
<p>39.88</p>	<p>The cor. of secs. 13, 18, 19, and 24, on the W. boundary of the township, hereinbefore described.</p>	
<p>Subdivision of Section 13 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>		
<p>19.96</p>	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0° 20' E., along the N. and S. center line of sec. 13.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 13.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 13 C S 1/16</p> <p style="text-align: center;">1968</p>	
<p>39.92</p>	<p>Point for the center 1/4 sec. cor. of sec. 13, at the intersection with the E. and W. center line.</p>	

Subdivision of Section 13
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
79.74	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C ¼ S 13</p> <p style="text-align: center;">1968</p> <p>The 1/4 sec. cor. of secs. 12 and 13.</p>
19.965	<p>From the 1/4 sec. cor. of secs. 13 and 18, on the E. boundary of the township, monumented with an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the field note record of the W. boundary of T. 1 S., R. 3 W., resurveyed concurrently with this Group.</p> <p>S. 89° 54' W., along the E. and W. center line of sec. 13.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 13.</p>
39.93	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 13 C E 1/16</p> <p style="text-align: center;">1968</p> <p>The center 1/4 sec. cor. of sec. 13.</p>
59.865	<p>Point for the C-W 1/16 sec. cor. of sec. 13.</p>
71.71	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 13 C W 1/16</p> <p style="text-align: center;">1968</p> <p>Center line of U. S. Highway No. 80 on a curve left. From this point, the PC bears S. 2° 10' E., 7.47 chs. dist.</p>
79.80	<p>The 1/4 sec. cor. of secs. 13 and 14.</p>
19.98	<p>From the E 1/16 sec. cor. of secs. 13 and 24.</p> <p>N. 0° 18' E., along the N. and S. center line of the SE¼ of sec. 13.</p> <p>Point for the SE 1/16 sec. cor. of sec. 13, at the intersection with the E. and W. center line of the SE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
39.96	<p style="text-align: center;">T1S R4W S 13 SE 1/16</p> <p style="text-align: center;">1968</p> <p>The C-E 1/16 sec. cor. of sec. 13.</p>

Subdivision of Section 13
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	<p>From the S 1/16 sec. cor. of secs. 13 and 18, on the E. boundary of the township, monumented with an iron post, 2½ ins. diam., set, mkd., and witnessed as described in the field note record of the W. boundary of T. 1 S., R. 3 W., resurveyed concurrently with this Group.</p>
	<p>S. 89° 58' W., along the E. and W. center line of the SE¼ of sec. 13.</p>
19.98	<p>The SE 1/16 sec. cor. of sec. 13.</p>
39.96	<p>The C-S 1/16 sec. cor. of sec. 13.</p>
	<p>From the W 1/16 sec. cor. of secs. 13 and 24.</p>
	<p>N. 0° 23' E., along the N. and S. center line of the SW¼ of sec. 13.</p>
19.905	<p>Point for the SW 1/16 sec. cor. of sec. 13, at the intersection with the E. and W. center line of the SW¼.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T1S R4W S 13 SW 1/16</p>
	<p>1968</p>
39.81	<p>The C-W 1/16 sec. cor. of sec. 13.</p>
	<p>From the C-S 1/16 sec. cor. of sec. 13.</p>
	<p>N. 89° 58' W., along the E. and W. center line of the SW¼ of sec. 13.</p>
19.95	<p>The SW 1/16 sec. cor. of sec. 13.</p>
31.04	<p>Center line of U. S. Highway No. 80, bears N. 1° 33' W., and S. 1° 33' E. From this point, the PC of a curve left on the highway center line, bears N. 1° 33' W., 12.42 chs. dist.</p>
39.90	<p>The S 1/16 sec. cor. of secs. 13 and 14.</p>
	<p>Subdivision of Section 14 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 14 and 23.</p>
	<p>N. 0° 36' E., along the N. and S. center line of sec. 14.</p>
19.86	<p>Point for the C-S 1/16 sec. cor. of sec. 14.</p>
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T1S R4W S 14 C S 1/16</p>
	<p>1968</p>
39.72	<p>Point for the center 1/4 sec. cor. of sec. 14, at the intersection with the E. and W. center line.</p>

Subdivision of Section 14
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C ¼ S 14</p> <p style="text-align: center;">1968</p>
51.46	Center line of Arlington Canal, course S. 68° 35' W. From this point, the intersection of the center line of the canal with the line between secs. 13 and 14, bears N. 68° 35' E., 42.75 chs. dist., and an angle point (change of direction only) on the canal center line, bears S. 68° 35' W., 5.79 chs. dist.
79.46	The 1/4 sec. cor. of secs. 11 and 14.
	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>S. 89° 38' W., along the E. and W. center line of sec. 14.</p>
19.87	Point for the C-E 1/16 sec. cor. of sec. 14.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 14 C E 1/16</p> <p style="text-align: center;">1968</p>
39.74	The center 1/4 sec. cor. of sec. 14.
61.31	Center line of Arlington Canal, course S. 59° 05' W. From this point, an angle point (change of direction only) on the canal center line, bears N. 59° 05' E., 19.00 chs. dist.
79.75	The 1/4 sec. cor. of secs. 14 and 15.
	<p>From the E 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0° 31' E., along the N. and S. center line of the SE¼ of sec. 14.</p>
19.86	Point for the SE 1/16 sec. cor. of sec. 14, at the intersection with the E. and W. center line of the SE¼.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W S 14 SE 1/16</p> <p style="text-align: center;">1968</p>
39.72	The C-E 1/16 sec. cor. of sec. 14.
	<p>From the S 1/16 sec. cor. of secs. 13 and 14.</p> <p>S. 89° 37' W., along the E. and W. center line of the SE¼ of sec. 14.</p>
19.90	The SE 1/16 sec. cor. of sec. 14.

Subdivision of Section 14
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS 39.80	The C-S 1/16 sec. cor. of sec. 14.
	Subdivision of Section 19 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona
19.71	From the 1/4 sec. cor. of secs. 19 and 30. N. 0° 06' E., along the N. and S. center line of sec. 19. Point for the C-S 1/16 sec. cor. of sec. 19. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T1S R4W C S 1/16 S 19 C 1968 </div>
39.42	Set a salt cedar post, 3 ins. diam., W. of the corner. Point for the center 1/4 sec. cor. of sec. 19, at the intersection with the E. and W. center line. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T1S R4W C ¼ S 19 1968 </div> Corner falls on N. bank of Arlington Canal.
79.26	The 1/4 sec. cor. of secs. 18 and 19.
20.16	From the 1/4 sec. cor. of secs. 19 and 20. N. 89° 14' W., along the E. and W. center line of sec. 19. Point for the C-E 1/16 sec. cor. of sec. 19. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T1S R4W C $\frac{E\ 1/16}{S\ 19}$ C 1968 </div>
40.32	The center 1/4 sec. cor. of sec. 19.
80.18	The true point for the 1/4 sec. cor. of secs. 19 and 24, on the W. boundary of the township, hereinbefore described.

Subdivision of Section 19
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
19.64	<p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 0° 18' E., along the N. and S. center line of the SE$\frac{1}{4}$ of sec. 19.</p> <p>Point for the SE 1/16 sec. cor. of sec. 19, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W SE 1/16 S 19</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., W. of the corner.</p>
39.28	<p>The C-E 1/16 sec. cor. of sec. 19.</p>
20.10	<p>From the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>N. 89° 26' W., along the E. and W. center line of the SE$\frac{1}{4}$ of sec. 19.</p> <p>The SE 1/16 sec. cor. of sec. 19.</p>
40.20	<p>The C-S 1/16 sec. cor. of sec. 19.</p>
<p>Subdivision of Section 20 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>	
19.72	<p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0° 01' W. along the N. and S. center line of sec. 20.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 20.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C S 1/16 S 20 C</p> <p style="text-align: center;">1968</p> <p>Set a mesquite post, 3 ins. diam., W. of the corner.</p>
39.44	<p>Point for the center 1/4 sec. cor. of sec. 20, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C $\frac{1}{4}$ S 20</p> <p style="text-align: center;">1968</p>

Subdivision of Section 20
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
79.16	Set a mesquite post, 4 ins. diam., W. of the corner. The 1/4 sec. cor. of secs. 17 and 20.
20.08	From the 1/4 sec. cor. of secs. 20 and 21. S. 89° 36' W., along the E. and W. center line of sec. 20. Point for the C-E 1/16 sec. cor. of sec. 20. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
40.16	<div style="text-align: center;"> T1S R4W E 1/16 C ————— C S 20 </div> 1968 Set a salt cedar post, 3 ins. diam., N. of the corner. The center 1/4 sec. cor. of sec. 20.
59.99	Point for the C-W 1/16 sec. cor. of sec. 20. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
79.82	<div style="text-align: center;"> T1S R4W C — W 1/16 — C S 20 </div> 1968 Set a salt cedar post, 3 ins. diam., N. of the corner. The 1/4 sec. cor. of secs. 19 and 20.
19.80	From the E 1/16 sec. cor. of secs. 20 and 29. N. 0° 05' E., along the N. and S. center line of the SE¼ of sec. 20. Point for the SE 1/16 sec. cor. of sec. 20, at the intersection with the E. and W. center line of the SE¼. Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
39.60	<div style="text-align: center;"> T1S R4W SE 1/16 S 20 </div> 1968 Set a salt cedar post, 3 ins. diam., N. of the corner. The C-E 1/16 sec. cor. of sec. 20.
	From the S 1/16 sec. cor. of secs. 20 and 21.

Subdivision of Section 20
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89° 48' W., along the E. and W. center line of the SE ¹ / ₄ of sec. 20.
20.04	The SE 1/16 sec. cor. of sec. 20.
40.08	The C-S 1/16 sec. cor. of sec. 20.
	From the W 1/16 sec. cor. of secs. 20 and 29.
	N. 0° 15' E., along the N. and S. center line of the SW ¹ / ₄ of sec. 20.
19.645	Point for the SW 1/16 sec. cor. of sec. 20, at the intersection with the E. and W. center line of the SW ¹ / ₄ .
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W SW 1/16 S 20</p>
	1968
	Set a salt cedar post, 4 ins. diam., W. of the corner.
39.29	The C-W 1/16 sec. cor. of sec. 20.
	From the C-S 1/16 sec. cor. of sec. 20.
	S. 89° 48' W., along the E. and W. center line of the SW ¹ / ₄ of sec. 20.
19.92	The SW 1/16 sec. cor. of sec. 20.
39.84	The S 1/16 sec. cor. of secs. 19 and 20.
Subdivision of Section 21 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona	
	From the true point for the 1/4 sec. cor. of secs. 21 and 28, hereinbefore described.
	N. 0° 01' E., along the N. and S. center line of sec. 21.
19.71	Point for the C-S 1/16 sec. cor. of sec. 21.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W C S 1/16 S 21 C</p>
	1968
	Set a salt cedar post, 4 ins. diam., W. of the corner.
39.42	Point for the center 1/4 sec. cor. of sec. 21, at the intersection with the E. and W. center line.

Subdivision of Section 21
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C ¼ S 21</p> <p style="text-align: center;">1968</p>	
59.06	<p>Point for the C-N 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C N 1/16 S 21 C</p> <p style="text-align: center;">1968</p>	
78.70	<p>Set a salt cedar post, 3 ins. diam., W. of the corner.</p> <p>The point for the 1/4 sec. cor. of secs. 16 and 21, hereinbefore described.</p>	
19.94	<p>From the 1/4 sec. cor. of secs. 21 and 22.</p> <p>S. 89° 42' W., along the E. and W. center line of sec. 21.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W E 1/16 C ——— C S 21</p> <p style="text-align: center;">1968</p>	
39.88	<p>Set a salt cedar post, 3 ins. diam., N. of the corner.</p> <p>The center 1/4 sec. cor. of sec. 21.</p>	
59.85	<p>Point for the C-W 1/16 sec. cor. of sec. 21.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W W 1/16 C ——— C S 21</p> <p style="text-align: center;">1968</p>	
79.82	<p>Set a salt cedar post, 5 ins. diam., N. of the corner.</p> <p>The 1/4 sec. cor. of secs. 20 and 21.</p>	

Subdivision of Section 21
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
19.58	<p>From the C-E 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 04' W., along the N. and S. center line of the NE$\frac{1}{4}$ of sec. 21.</p> <p>Point for the NE 1/16 sec. cor. of sec. 21, at the intersection with the E. and W. center line of the NE$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W NE 1/16 S 21 1968</p> <p>Set a cedar post, 3 ins. diam., W. of the corner.</p>
39.16	<p>The point for the E 1/16 sec. cor. of secs. 16 and 21, hereinbefore described.</p>
19.91	<p>From the N 1/16 sec. cor. of secs. 21 and 22.</p> <p>S. 89° 51' W., along the E. and W. center line of the NE$\frac{1}{4}$ of sec. 21.</p> <p>The NE 1/16 sec. cor. of sec. 21.</p>
39.82	<p>The C-N 1/16 sec. cor. of sec. 21.</p>
19.625	<p>From the point for the E 1/16 sec. cor. of secs. 21 and 28, hereinbefore described.</p> <p>N. 0° 06' W., along the N. and S. center line of the SE$\frac{1}{4}$ of sec. 21.</p> <p>Point for the SE 1/16 sec. cor. of sec. 21, at the intersection with the E. and W. center line of the SE$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W SE 1/16 S 21 1968</p> <p>Set a salt cedar post, 3 ins. diam., W. of the corner.</p>
39.25	<p>The C-E 1/16 sec. cor. of sec. 21.</p>
19.98	<p>From the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>S. 89° 27' W., along the E. and W. center line of the SE$\frac{1}{4}$ of sec. 21.</p> <p>The SE 1/16 sec. cor. of sec. 21.</p>
39.96	<p>The C-S 1/16 sec. cor. of sec. 21.</p>

Subdivision of Section 21
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	<p>From the C-W 1/16 sec. cor. of sec. 21.</p> <p>N. 0° 08' E., along the N. and S. center line of the NW$\frac{1}{4}$ of sec. 21.</p> <p>19.705 Point for the NW 1/16 sec. cor. of sec. 21, at the intersection with the E. and W. center line of the NW$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W NW 1/16 S 21 1968</p> <p>Set a salt cedar post, 4 ins. diam., W. of the corner.</p> <p>39.41 The W 1/16 sec. cor. of secs. 16 and 21.</p>	
	<p>From the C-N 1/16 sec. cor. of sec. 21.</p> <p>S. 89° 51' W., along the E. and W. center line of the NW$\frac{1}{4}$ of sec. 21.</p> <p>19.92 The NW 1/16 sec. cor. of sec. 21.</p> <p>39.84 The N 1/16 sec. cor. of secs. 20 and 21.</p>	
	<p>Subdivision of Section 22 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 0° 12' E., along the N. and S. center line of sec. 22.</p> <p>19.64 Point for the C-S 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C S 1/16 S 22 1968</p> <p>Set a guard post W. of the corner.</p> <p>39.28 Point for the center 1/4 sec. cor. of sec. 22, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C $\frac{1}{4}$ S 22 1968</p>	

Subdivision of Section 22
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
58.905	<p>Point for the C-N 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C N 1/16 S 22</p> <p style="text-align: center;">1968</p> <p>Set a guard post W. of the corner.</p>
78.53	<p>The 1/4 sec. cor. of secs. 15 and 22.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>WEST, along the E. and W. center line of sec. 22.</p>
19.845	<p>Point for the C-E 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C E 1/16 S 22</p> <p style="text-align: center;">1968</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of the corner.</p>
39.69	<p>The center 1/4 sec. cor. of sec. 22.</p>
59.55	<p>Point for the C-W 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C W 1/16 S 22</p> <p style="text-align: center;">1968</p>
79.41	<p>The 1/4 sec. cor. of secs. 21 and 22.</p> <hr/> <p>From the point for the E 1/16 sec. cor. of secs. 22 and 27, hereinbefore described.</p> <p>N. 0° 23' E., along the N. and S. center line of the SE¼ of sec. 22.</p>
19.695	<p>Point for the SE 1/16 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 22
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS		
39.39	<p style="text-align: center;">T1S R4W SE 1/16 S 22</p> <p style="text-align: center;">1968</p> <p>Set a guard post alongside the corner.</p> <p>The C-E 1/16 sec. cor. of sec. 22.</p>	
19.785 39.57	<p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>N. 89° 51' W., along the E. and W. center line of the SE$\frac{1}{4}$ of sec. 22.</p> <p>The SE 1/16 sec. cor. of sec. 22.</p> <p>The C-S 1/16 sec. cor. of sec. 22.</p>	
19.59 39.18	<p>From the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>N. 0° 01' W., along the N. and S. center line of the SW$\frac{1}{4}$ of sec. 22.</p> <p>Point for the SW 1/16 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the SW$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W SW 1/16 S 22</p> <p style="text-align: center;">1968</p> <p>Set a guard post W. of the corner.</p> <p>The C-W 1/16 sec. cor. of sec. 22.</p>	
19.80 39.60	<p>From the C-S 1/16 sec. cor. of sec. 22.</p> <p>N. 89° 51' W., along the E. and W. center line of the SW$\frac{1}{4}$ of sec. 22.</p> <p>The SW 1/16 sec. cor. of sec. 22.</p> <p>The S 1/16 sec. cor. of secs. 21 and 22.</p>	
19.57	<p>From the C-W 1/16 sec. cor. of sec. 22.</p> <p>N. 0° 02' E., along the N. and S. center line of the NW$\frac{1}{4}$ of sec. 22.</p> <p>Point for the NW 1/16 sec. cor. of sec. 22, at the intersection with the E. and W. center line of the NW$\frac{1}{4}$.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 25 ins. in the ground, with brass cap mkd.</p>	

Subdivision of Section 22
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
39.14	<p style="text-align: center;">T1S R4W NW 1/16 S 22</p> <p style="text-align: center;">1968</p> <p>Set a guard post W. of the corner.</p> <p>The W 1/16 sec. cor. of secs. 15 and 22.</p>
19.92	<p>From the C-N 1/16 sec. cor. of sec. 22.</p> <p>S. 89° 51' W., along the E. and W. center line of the NW¹/₄ of sec. 22.</p> <p>The NW 1/16 sec. cor. of sec. 22.</p>
39.84	<p>The N 1/16 sec. cor. of secs. 21 and 22.</p>
<p>Subdivision of Section 23 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>	
39.57	<p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0° 09' E., along the N. and S. center line of sec. 23.</p> <p>Point for the center 1/4 sec. cor. of sec. 23, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
59.385	<p style="text-align: center;">T1S R4W C ¼ S 23</p> <p style="text-align: center;">1968</p> <p>Point for the C-N 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
79.20	<p style="text-align: center;">T1S R4W C N 1/16 S 23</p> <p style="text-align: center;">1968</p> <p>The 1/4 sec. cor. of secs. 14 and 23.</p>
19.965	<p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 51' W., along the E. and W. center line of sec. 23.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 23
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>T1S R4W C E 1/16 S 23 1968</p>
39.93	The center 1/4 sec. cor. of sec. 23.
60.02	<p>Point for the C-W 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T1S R4W C W 1/16 S 23 1968</p>
80.11	The 1/4 sec. cor. of secs. 22 and 23.
19.86	<p>From the C-E 1/16 sec. cor. of sec. 23.</p> <p>N. 0° 08' E., along the N. and S. center line of the NE¼ of sec. 23.</p> <p>Point for the NE 1/16 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the NE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
39.72	<p>T1S R4W NE 1/16 S 23 1968</p> <p>The E 1/16 sec. cor. of secs. 14 and 23.</p>
19.95	<p>From the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 43' W., along the E. and W. center line of the NE¼ of sec. 23.</p> <p>The NE 1/16 sec. cor. of sec. 23.</p>
39.90	The C-N 1/16 sec. cor. of sec. 23.
<p>Subdivision of Section 27 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>	
20.01	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0° 03' W., along the N. and S. center line of sec. 27.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 27
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>T1S R4W C S 1/16 S 27 1968</p>	
40.02	<p>Point for the center 1/4 sec. cor. of sec. 27, at the intersection with the E. and W. center line.</p>	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
	<p>T1S R4W C ¼ S 27 1968</p>	
	<p>Corner falls approximately 4 lks. S. of fence, bears E. and W.</p>	
79.98	<p>The 1/4 sec. cor. of secs. 22 and 27.</p>	
	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p>	
	<p>N. 89° 45' W., along the E. and W. center line of sec. 27.</p>	
39.70	<p>The center 1/4 sec. cor. of sec. 27.</p>	
59.56	<p>Point for the C-W 1/16 sec. cor. of sec. 27.</p>	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	
	<p>T1S R4W C W 1/16 S 27 1968</p>	
	<p>Corner falls approximately 2 lks. S. of fence, bears E. and W.</p>	
79.42	<p>The 1/4 sec. cor. of secs. 27 and 28.</p>	
	<p>Subdivision of Section 28 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 28 and 33.</p>	
	<p>N. 0° 19' E., along the N. and S. center line of sec. 28.</p>	
39.81	<p>Point for the center 1/4 sec. cor. of sec. 28, at the intersection with the E. and W. center line.</p>	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>	
	<p>T1S R4W C ¼ S 28 1968</p>	

Subdivision of Section 28
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p>
79.63	<p>The true point for the 1/4 sec. cor. of secs. 21 and 28, hereinbefore described.</p>
40.00	<p>From the 1/4 sec. cor. of secs. 27 and 28. S. 89° 26' W., along the E. and W. center line of sec. 28. The center 1/4 sec. cor. of sec. 28.</p>
79.98	<p>The 1/4 sec. cor. of secs. 28 and 29.</p>
<p>Subdivision of Section 29 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona</p>	
38.82	<p>From the 1/4 sec. cor. of secs. 29 and 32, monumented with an iron post, 2½ ins. diam., firmly set with 12 ins. projecting above ground, in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W ¼ S 29 S 32</p> <p style="text-align: center;">1958</p> <p>N. 0° 16' E., along the N. and S. center line of sec. 29.</p> <p>Point for the center 1/4 sec. cor. of sec. 29, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C ¼ S 29</p> <p style="text-align: center;">1968</p> <p>from which</p> <p style="text-align: center;">The SE. cor. of a rock house bears N. 84½° E., 55 lks. dist.</p>
58.51	<p>Point for the C-N 1/16 sec. cor. of sec. 29.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T1S R4W C N 1/16 S 29 C</p> <p style="text-align: center;">1968</p> <p>Set a wood post, 8 ins. diam., W. of the corner.</p>
78.20	<p>The 1/4 sec. cor. of secs. 20 and 29.</p>

Subdivision of Section 29
Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS	
	From the 1/4 sec. cor. of secs. 28 and 29.
	N. 89° 35' W., along the E. and W. center line of sec. 29.
20.01	Point for the C-E 1/16 sec. cor. of sec. 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground, supported by a collar of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T1S R4W E 1/16 C-----C S 29 1968</p>
40.02	The center 1/4 sec. cor. of sec. 29.
60.00	Point for the C-W 1/16 sec. cor. of sec. 29.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W W 1/16 C-----C S 29 1968</p>
	Corner falls on fence line, bears E. and W.
79.98	The 1/4 sec. cor. of secs. 29 and 30.
	From the C-E 1/16 sec. cor. of sec. 29.
	N. 0° 15' E., along the N. and S. center line of the NE¼ of sec. 29.
19.75	Point for the NE 1/16 sec. cor. of sec. 29, at the intersection with the E. and W. center line of the NE¼.
	Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T1S R4W NE 1/16 S 29 1968</p>
	Set a salt cedar post, 4 ins. diam., N. of the corner.
39.50	The E 1/16 sec. cor. of secs. 20 and 29.
	From the N 1/16 sec. cor. of secs. 28 and 29.
	N. 89° 47' W., along the E. and W. center line of the NE¼ of sec. 29.
20.01	The NE 1/16 sec. cor. of sec. 29.

Subdivision of Section 29
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
40.02	The C-N 1/16 sec. cor. of sec. 29.
	From the C-W 1/16 sec. cor. of sec. 29.
	N. 0° 13' E., along the N. and S. center line of the NW $\frac{1}{4}$ of sec. 29.
19.62	Point for the NW 1/16 sec. cor. of sec. 29, at the intersection with the E. and W. center line of the NW $\frac{1}{4}$.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T1S R4W NW 1/16 S 29 1968
	Raise a mound of stone, 2 ft. base, 1 $\frac{1}{2}$ ft. high, W. of the corner.
39.24	The W 1/16 sec. cor. of secs. 20 and 29.
	From the C-N 1/16 sec. cor. of sec. 29.
	N. 89° 47' W., along the E. and W. center line of the NW $\frac{1}{4}$ of sec. 29.
20.00	The NW 1/16 sec. cor. of sec. 29.
40.00	The N 1/16 sec. cor. of secs. 29 and 30.
	Subdivision of Section 30 Township 1 South, Range 4 West Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 30 and 31.
	N. 0° 15' E., along the N. and S. center line of sec. 30.
19.96	Point for the C-S 1/16 sec. cor. of sec. 30.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.
	T1S R4W C S 1/16 S 30 C 1968
	Set a mesquite post, 3 ins. diam., W. of the corner.
39.92	Point for the center 1/4 sec. cor. of sec. 30, at the intersection with the E. and W. center line.
	Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.

Subdivision of Section 30
 Township 1 South, Range 4 West
 Gila and Salt River Meridian, Arizona

CHAINS	
79.34	<p style="text-align: center;">T1S R4W C ¼ S 30</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., W. of the corner.</p> <p>The 1/4 sec. cor. of secs. 19 and 30.</p>
20.04	<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>S. 89° 57' W., along the E. and W. center line of sec. 30.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 30.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
40.08 79.85	<p style="text-align: center;">T1S R4W E 1/16 C ————— C S 30</p> <p style="text-align: center;">1968</p> <p>Set a salt cedar post, 4 ins. diam., N. of the corner.</p> <p>The center 1/4 sec. cor. of sec. 30.</p> <p>The 1/4 sec. cor. of secs. 25 and 30.</p>
19.77	<p>From the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0° 14' E., along the N. and S. center line of the SE¼ of sec. 30.</p> <p>Point for the SE 1/16 sec. cor. of sec. 30, at the intersection with the E. and W. center line of the SE¼.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
39.54	<p style="text-align: center;">T1S R4W SE 1/16 S 30</p> <p style="text-align: center;">1968</p> <p>Set a mesquite post, 4 ins. diam., W. of the corner.</p> <p>The C-E 1/16 sec. cor. of sec. 30.</p>
20.05 40.10	<p>From the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>S. 89° 27' W., along the E. and W. center line of the SE¼ of sec. 30.</p> <p>The SE 1/16 sec. cor. of sec. 30.</p> <p>The C-S 1/16 sec. cor. of sec. 30.</p>

Township 1 South, Range 4 West
Gila and Salt River Meridian, Arizona

CHAINS

General Description

The area embraced in this survey lies approximately 5 miles southwest of Buckeye, Arizona. The land in the southern portion of the survey is rolling. Vegetation consists of desert type undergrowth. The northern portion of the survey lies in the Gila River bottom, with dense salt cedar throughout. The Gila River flows generally in a westerly direction through the survey. The biggest portion of the land is used for a state game refuge.

Form 4-680
(June 1963)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Selmer O. Olson	Cadastral Surveyor
Santiago T. Chavez	Surveying Aid
Alex L. Chavez	Surveying Aid
Robert W. Savidge	Surveying Aid
Scott L. Robinson	Surveying Aid
William L. McDorman	Surveying Aid
Darwin E. Johnston	Surveying Aid
Ned E. Carnahan	Surveying Aid
Victor E. Templeton	Surveying Aid
Colin R. Kelly	Surveying Aid

CERTIFICATE OF SURVEY

We, Richard L. Oakes &
 X Marlin G. Livermore II, HEREBY CERTIFY upon honor that,
 in pursuance of special instructions bearing date of the 23 day of January, 1968,
~~have~~ We have dependently resurveyed a portion of the west boundary, a
 portion of the subdivisional lines, and subdivided certain sections in
 T. 1 S. R. 4 W., Gila & Salt River Meridian, Arizona

of the Gila & Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by ~~me~~^{US} and under ~~my~~^{OUR} direction;
 and that said survey has been made in strict conformity with said special instructions, the Manual
 of Instructions for the Survey of the Public Lands of the United States, and in specific manner
 described in the foregoing field notes.

August 16, 1974
 (Date)

Richard L. Oakes
 (Cadastral Surveyor)

Richard L. Oakes

August 23, 1974
 (Date)

Marlin G. Livermore II
 (Cadastral Surveyor)

Marlin G. Livermore II

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL
 Date AUG 26 1974

BUREAU OF LAND MANAGEMENT,
 Washington, D. C.

The foregoing field notes of the dependent resurvey of a portion of the west
 boundary, a portion of the subdivisional lines, and the subdivision of
 certain sections in T. 1 S. R 4 W., Gila & Salt River Meridian, Arizona

executed by Richard L. Oakes & Marlin G. Livermore II Supervisory Cadastral
 Surveyors
 having been critically examined and found correct, are hereby approved.

FEB 4 1976
 (Date)

Bernard W. Fisher
 Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 , is a true copy of the original field notes.

(Date)

(Chief, Division of Engineering)