

Form 9180-6
(April 1974)

RECEIVED
B. L. M. AZ STATE OFFICE

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

AUG 11 1976

10:00 A.M.
PHOENIX, ARIZONA

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF

THE NORTH BOUNDARY AND SUBDIVISIONAL LINES

WITH THE SUBDIVISION OF CERTAIN SECTIONS IN

TOWNSHIP 15 NORTH, RANGE 3 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

GILBERT V. OLSON

SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated March 23, 1973, approved April 3, 1973,

Supplemental Special Instructions dated April 13, 1973

_____, which provided for the surveys included under U.S. Survey/Group
Number 530, and assignment instructions dated March 14, 1973.

Survey commenced March 19, 1973

Survey completed January 29, 1976

1A

INDEX DIAGRAM

Township 15 North, Range 3 West,

6	5	2		8	2	1
		4	15			
7	8	14	14	11	11	12
		13		10		
18	17	12	9	10	11	13
19	20	21	22	18	14	4
				18	6	
30	29	28	27	26	25	24
31	32	33	34	35	36	3

- NE $\frac{1}{4}$ of sec. 4.....pp. 15 - 16
- SE $\frac{1}{4}$ of sec. 4.....p. 16
- NW $\frac{1}{4}$ of sec. 14.....pp. 17 - 18
- SW $\frac{1}{4}$ of sec. 14.....p. 18
- SE $\frac{1}{4}$ of sec. 23.....p. 20

Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of portions of the north boundary and subdivisional lines, with the subdivision of certain sections in Township 15 North, Range 3 West, Gila and Salt River Meridian, Arizona.

Earlier pertinent surveys are tabulated as follows:

<u>Lines Surveyed</u>	<u>By Whom</u>	<u>Date</u>
North, East Boundaries and portions of the West and South Boundaries	S. W. Foreman	1871
Portion of the Subdivisional Lines	S. W. Foreman	1872
West Boundary (Survey and Resurvey)	Sidney E. Blout	1924
Portions of the South Boundary and Subdivisional Lines (Survey); North and East Boundaries and portions of the South Boundary and Subdivisional Lines (Resurvey)	Sidney E. Blout & Charles E. Hunter	1927

John Witmer, Cadastral Surveyor, remonumented the corner of sections 2, 3, 10, and 11, in 1969.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, the Special Instructions dated March 23, 1973, and the Supplemental Special Instructions dated April 13, 1973.

Before restoring the corners the lines of the original surveys were retraced and a diligent search made for any evidence of the original corners, bearing trees, and calls of the original field notes. When duly identified, the corner positions were remonumented and new accessories obtained. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner. For simplification of the record, only the true line notes are furnished.

The directions of all lines were determined by use of the solar transit and refer to the true meridian. The lines were carried by transit method and confirmed by altitude observations of the sun.

The geographic position of the corner of sections 23, 24, 25, and 26, as determined from United States Geological Survey "Iron Springs", Quadrangle, is:

Latitude 34° 39.4' N.
Longitude 112° 32.1' W.

The observed mean magnetic declination is 15½° East.

Dependent Resurvey of a Portion
of the North Boundary
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

Reestablishment of the Resurvey Executed by
Sidney E. Blout, U. S. Cadastral Engineer
and Charles E. Hunter, U. S. Transitman,
in 1927.

Beginning at the cor. of secs. 3, 4, 33, and 34, Tps. 15
and 16 N., R. 3 W., the N. boundary of the township,
monumented with an iron post, 2 ins. diam., firmly set,
projecting 32 ins. above the ground, in a mound of stone,
with brass cap mkd.

$$\begin{array}{r} \text{T16N R3W} \\ \text{S 33 | S 34} \\ \hline \text{S 4 | S 3} \\ \text{T15N} \end{array}$$

1927

substantiated by:

A pinon, 4 ins. diam., bears N. $34\frac{1}{2}^\circ$ E., 158 lks.
dist., mkd. T16N R3W S34 BT.

A pinon, 8 ins. diam., bears S. $87\frac{1}{4}^\circ$ E., 236 lks.
dist., mkd. T15N R3W S3 BT.

N. $89^\circ 44'$ W., between secs. 4 and 33.

Over broken land with sagebrush.

20.50 Point for the E 1/16 sec. cor. of secs. 4 and 33, on the
N. boundary of the township, not monumented.

41.00 The 1/4 sec. cor. of secs. 4 and 33, on the N. boundary
of the township, monumented with an iron post, 1 in.
diam., firmly set, projecting 9 ins. above the ground,
with brass cap mkd.

$$1/4 \frac{\text{S 33}}{\text{S 4}}$$

1927

Corner is located in fence line bearing E. and W., 40
lks. W. of a wash draining S.

N. $89^\circ 39'$ W., beginning new measurement.

Over broken land with scattered pinon and juniper timber.

19.50 Mint Wash, 50 ft. wide, 2 lks. deep, course NW.

24.60 Mint Wash, course SW.

30.00 Mint Wash, course NW.

41.07 The cor. of secs. 4, 5, 32, and 33, on the N. boundary
of the township, monumented with an iron post, 2 ins.
diam., firmly set, projecting 20 ins. above the ground,
in a mound of stone. The marks T15N and 1973 are added
to the brass cap so it now reads:

Dependent Resurvey of a Portion
of the North Boundary
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

T16N R3W
S 32 | S 33
S 5 | S 4

T15N
1973

1927

Corner is located in a fence bearing E. and W.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

From the cor. of secs. 23, 24, 25, and 26, monumented
with an iron post, 2 ins. diam., firmly set, projecting
8 ins. above the ground, with brass cap mkd.

T15N R3W
S 23 | S 24
S 26 | S 25

1927

substantiated by:

A pinon, 12 ins. diam., bears S. $87\frac{3}{4}^{\circ}$ W., 190
lks. dist., mkd. T15N R3W S26 BT.

A cedar, 8 ins. diam., bears N. 56° W., 253 lks.
dist., mkd. T15N R3W S23 BT.

N. $4^{\circ} 24'$ W., between secs. 23 and 24.

Over nearly level land, through moderate juniper.

19.83 Point for the S $\frac{1}{16}$ sec. cor. of secs. 23 and 24.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins.
in the ground, with brass cap mkd.

T15N R3W
S 1/16
S 23 | S 24

1973

Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W. of
the corner.

Corner is located in fence bearing E. and W.

39.66 The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with an
iron post, 1 in. diam., firmly set, projecting 4 ins.
above the ground, with brass cap mkd.

$\frac{1}{4}$
S 23 | S 24

1927

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS					
39.66	<p>Corner is located in fence line bearing N. and S.</p> <hr style="width: 20%; margin: 0 auto;"/> <p>N. 4° 24' W., beginning new measurement.</p> <p>Over level land along a fence, through scattered timber.</p> <p>The cor. of secs. 13, 14, 23, and 24, monumented with an iron post, 2 ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T15N R3W</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> </table> <p>1927</p> </div> <p>Corner is located at intersection of fences extending N., E., and S.</p>	S 14	S 13	S 23	S 24
S 14	S 13				
S 23	S 24				
13.50 40.13	<p>N. 0° 39' W., between secs. 13 and 14.</p> <p>Over level land along a fence, through scattered juniper.</p> <p>Paved road, bears NW. and SE.</p> <p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron post, 1 in. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p style="margin: 0 0 0 40px;">1/4</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> </table> <p>1927</p> </div> <p>substantiated by:</p> <p style="margin-left: 40px;">A stump, 10 ins. diam., bears west, 98 lks. dist., no marks visible.</p> <p>Corner is located in fence line bearing N. and S.</p>	S 14	S 13		
S 14	S 13				
17.20 19.95 39.90	<p>From the cor. of secs, 23, 24, 25, and 26.</p> <p>S. 89° 41' W., between secs. 23 and 26.</p> <p>Descend through scattered pinon and juniper timber.</p> <p>Mint Wash, 20 ft. wide, 2 lks. deep, course N.; begin ascent over broken land.</p> <p>Point for the E 1/16 sec. cor. of secs. 23 and 26, not monumented.</p> <p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p>				

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">1/4 $\frac{S\ 23}{S\ 26}$</p> <p style="text-align: center;">1927</p> <p>substantiated by:</p> <p style="text-align: center;">A pinon, 7 ins. diam., bears N. 70½° E., 49 lks. dist., with blaze grown over.</p>	
	<p>From the cor. of secs. 13, 14, 23, and 24.</p> <p>S. 86° 54' W., between secs. 14 and 23.</p>	
44.00	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 $\frac{S\ 14}{S\ 23}$</p> <p style="text-align: center;">1927</p> <p>Corner is located 1 lk. E. of intersection of fences extending S. and W.</p> <p style="text-align: center;">_____</p> <p>N. 86° 25' W., beginning new measurement.</p>	
18.08	<p>Point for the W 1/16 sec. cor. of sec. 14 only.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground to bedrock, in a collar of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W <u>W 1/16 S 14</u></p> <p style="text-align: center;">1973</p> <p>Corner is located at intersection of fences extending N. and E.</p>	
26.89	<p>The closing cor. of secs. 22 and 23, monumented with an iron post, 2 ins. diam., firmly set, projecting 30 ins. above the ground, in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W <u>S 14</u> S 22 S 23 T15N R3W C C</p> <p style="text-align: center;">1927</p> <p>substantiated by:</p> <p style="text-align: center;">A pinon, 10 ins. diam., bears S. 31° E., 73 lks. dist., mkd. T15N R3W S23 CC BT.</p> <p style="text-align: center;">A pinon, 12 ins. diam., bears S. 89¼° W., 36 lks. dist., blazed, scribing illegible.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS																						
	<p>Thence between secs. 14 and 22.</p> <p>36.16 The SW. cor. of sec. 14, monumented with an iron post, 2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap erroneously mkd. showing S23 instead of S22. The marks are changed so they now read:</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td></td> <td>T15N</td> </tr> <tr> <td>T15N</td> <td> </td> <td>R3W</td> </tr> <tr> <td></td> <td></td> <td><u>S 14</u></td> </tr> <tr> <td>S 22</td> <td></td> <td></td> </tr> <tr> <td>R3W</td> <td></td> <td></td> </tr> </table> <p>1975 1927</p> <p>substantiated by:</p> <p>A pinon, 8 ins. diam., bears N. 8° E., 42 lks. dist., with blaze grown over.</p> <p>A pinon, 14 ins. diam., bears N. 59¼° E., 74 lks. dist., mkd. T15N R3W S14 BT.</p> </div>			T15N	T15N		R3W			<u>S 14</u>	S 22			R3W								
		T15N																				
T15N		R3W																				
		<u>S 14</u>																				
S 22																						
R3W																						
	<p>N. 1° 07' W., along the W. boundary of sec. 14.</p> <p>Over broken land, through pinon and juniper timber.</p> <p>2.33 The witness closing cor. of secs. 15 and 22, monumented with an iron post, 2 ins. diam., firmly set in a mound of stone, with brass cap mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td></td> <td></td> <td>W C</td> </tr> <tr> <td></td> <td></td> <td>T15N</td> </tr> <tr> <td>C</td> <td> </td> <td>T15N</td> </tr> <tr> <td>C</td> <td> </td> <td>S 15</td> </tr> <tr> <td></td> <td></td> <td><u>S 14</u></td> </tr> <tr> <td>C</td> <td> </td> <td>S 22</td> </tr> <tr> <td></td> <td></td> <td>R3W</td> </tr> </table> <p>1927</p> <p>substantiated by:</p> <p>A pinon, 8 ins. diam., bears S. 13° W., 53 lks. dist., mkd. T15N R3W S22 BT. WC.</p> <p>A pinon, 14 ins. diam., bears N. 57 3/4° W., 67 lks. dist., mkd. T15N R3W S22 WC BT CC.</p> <p>The 1927 survey record failed to show this monument as a witness corner; however, the physical evidence of the boulder at record distance for the corner (true point, hereinafter described) and the WC's mkd. on the brass cap and bearing trees is significant enough to determine the monument is in fact a witness corner.</p> <p>2.38 Record distance for the true point for the closing cor. of secs. 15 and 22, falls on large boulder, impractical for monumentation.</p> <p>23.50 Enter nearly level land.</p> </div>			W C			T15N	C		T15N	C		S 15			<u>S 14</u>	C		S 22			R3W
		W C																				
		T15N																				
C		T15N																				
C		S 15																				
		<u>S 14</u>																				
C		S 22																				
		R3W																				

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
40.92	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ S 15 S 14 1927 </p> <p>substantiated by:</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears S. 83$\frac{1}{4}$° E., 63 lks. dist., mkd. 1/4 S14 BT.</p> <p>Corner is located in fence line, bearing E. and W.</p> <p style="text-align: center;">_____</p> <p>N. 1° 15' W., beginning new measurement.</p> <p>Over nearly level land, through scattered timber.</p>	
20.47	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T15N R3W N 1/16 S 15 S 14 1973 </p> <p>Corner is located 40 lks. W. of Mint Wash.</p>	
40.94	<p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> T15N R3W S 10 S 11 S 15 S 14 T15N R3W 1927 </p> <p>substantiated by:</p> <p style="padding-left: 40px;">A root hole, bears N. 19$\frac{1}{2}$° E., 33 lks. dist., with an oak, 5 ins. diam., lying alongside, blazed, scribing illegible.</p> <p style="padding-left: 40px;">An oak, 5 ins. diam., bears S. 84$\frac{1}{2}$° E., 40 lks. dist., with decayed area facing corner.</p> <p style="padding-left: 40px;">An oak, 5 ins. diam., bears S. 10° W., 76 lks. dist., with blaze grown over.</p> <p style="padding-left: 40px;">An oak, 5 ins. diam., bears N. 44° W., 49 lks. dist., blazed, scribing illegible.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

From the point for the 1/4 sec. cor. of secs. 11 and 14, determined latitudinally in line with the remains of an old fence line to the E., and longitudinally at proportionate distance between the cor. of secs. 7, 12, 13, and 18 on the E. boundary of the township, and the cor. of secs. 10, 11, 14, and 15. A diligent search was made for this corner and all intermediate corners, no evidence of the original monuments could be found. This point is accepted as the best available evidence of the original corner position.

Set an iron post, 30 ins. long, 2½ ins. diam., over an X chiseled on bedrock, encircled in a mound of stone, 4 ft. base to top, with brass cap mkd.

T15N R3W
1/4 $\frac{S 11}{S 14}$

1976

Corner is located 7 ft. S. of a fence bearing E. and W.

From this corner the cor. of secs. 7, 12, 13, and 18, on the E. boundary of the township, bears N. 89° 06' E., 123.34 chs. dist., monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, in fence line bearing N. and S., with brass cap mkd.

T15N
R3W R2W
 $\frac{S 12 | S 7}{S 13 | S 18}$

1927

substantiated by:

A pinon, 14 ins. diam., bears N. 72½° W., 195 lks. dist., with the mks. S12 BT visible (record 196 lks.)

N. 89° 10' W., between secs. 11 and 14.

Over rolling land, through scrub oak.

20.54 Point for the W 1/16 sec. cor. of secs. 11 and 14.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground to bedrock, encircled in a collar of stone, with brass cap mkd.

T15N R3W
W 1/16 $\frac{S 11}{S 14}$

1973

Corner is located 45 lks. S. of corner of new fences, bearing S. 85° E., and S. 15° W.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
30.50	Mint Wash, 20 ft. wide, 2 lks. deep, course N.
41.08	The cor. of secs. 10, 11, 14, and 15.
	<p>From the south 1/4 sec. cor. of sec. 15 only, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"><u>1/4 S 15</u></p> <p style="text-align: center;">1927</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A pinon, 12 ins. diam., bears N. 67$\frac{1}{4}$° W., 16 lks. dist., blazed, scribing illegible.</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 48$\frac{1}{2}$° W., 57 lks. dist., blazed, scribing illegible.</p> <p>N. 89° 46' E., between secs. 15 and 22.</p> <p>Over broken land, through pinon and juniper timber, with large rounded granite boulders.</p>
40.04	<p>The closing cor. of secs. 15 and 22, on the W. boundary of sec. 14, hereinbefore described.</p> <p>From this closing cor. the SW. cor. of sec. 14, bears S. 1° 07' E., 2.38 chs. dist., hereinbefore described.</p>
	<p>From the cor. of secs. 10, 11, 14, and 15.</p> <p>N. 85° 32' W., between secs. 10 and 15.</p> <p>Over broken land, through pinon and juniper timber.</p>
41.34	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 1 in. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 $\frac{S\ 10}{S\ 15}$</p> <p style="text-align: center;">1927</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears S. 11° E., 54 lks. dist., mkd. 1/4 S15 BT. (record, S. 10$\frac{1}{4}$° E.)</p> <p style="padding-left: 40px;">A pinon, 6 ins. diam., bears N. 12° W., 20 lks. dist., mkd. 1/4 S10 BT. (record, N. 10$\frac{1}{4}$° W.)</p>
	<p>From the cor. of secs. 9 and 10 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, with brass cap mkd.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

T15N R3W
S 9 | S 10

1927

substantiated by:

A pinon, 10 ins. diam., bears N. 12 3/4° E., 52 lks. dist., with blaze grown over.

A pinon, 8 ins. diam., bears N. 22° W., 19 lks. dist., with blaze grown over.

Corner is located at intersection of fences extending north, S. 85 1/4° E., and west.

N. 2° 07' W., between secs. 9 and 10.

Over rolling land, through pinon and juniper timber.

40.05

Point for the 1/4 sec. cor. of secs. 9 and 10, determined at proportionate distance. There is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.

T15N R3W
^{1/4}
S 9 | S 10

1973

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the corner.

Corner is located 2.50 chs. SE. of ridge, bearing NE. and SW.

80.10

The cor. of secs. 3, 4, 9, and 10, determined at single proportionate distance between the cor. of secs. 9 and 10, to the S., and the cor. of secs. 3, 4, 33, and 34, on the N. boundary of the township, hereinbefore described. There is no remaining evidence of the original corner. The single proportion method was used for this corner to position it in harmony with other found corners in the nearby area. This position is acceptable to all adjacent landowners.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

T15N R3W
S 4 | S 3
S 9 | S 10

1973

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the corner.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point the cor. of secs. 2, 3, 10, and 11, bears S. 83° 34' E., 87.05 chs. dist., monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 3 S 2 ----- S 10 S 11</p> <p style="text-align: center;">1969</p>
	<p>N. 2° 07' W., between secs. 3 and 4.</p> <p>Over broken land, through pinon and juniper timber.</p> <p>20.025 Point for the S 1/16 sec. cor. of secs. 3 and 4, not monumented.</p> <p>28.20 Mint Wash, 20 ft. wide, 3 lks. deep, course NW.</p> <p>40.05 Point for the 1/4 sec. cor. of secs. 3 and 4, determined at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a collar of stone, 2 ft. base, 1½ ft. high, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W ¼ S 4 S 3</p> <p style="text-align: center;">1973</p> <p>Corner is located 1 ch. SE. of ridge, bearing NE. and SW.</p> <p>54.50 Deep wash, drains SW.</p> <p>60.075 Point for the N 1/16 sec. cor. of secs. 3 and 4, not monumented.</p> <p>80.40 The cor. of secs. 3, 4, 33, and 34, on the N. boundary of the township, hereinbefore described.</p>
	<p>From the cor. of secs. 9 and 10 only.</p> <p>N. 89° 33' W., along the S. boundary of sec. 9.</p> <p>Ascend broken land, through pinon and juniper timber.</p> <p>26.59 Fall 4 lks. S. of the 1/4 sec. cor. of sec. 16 only, monumented with an iron post, 1 in. diam., firmly set, projecting 24 ins. above the ground, in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">----- 1/4 S 16</p> <p style="text-align: center;">1927</p> <p>Corner is located in a fence, bearing E. and W.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	<p>41.24 The 1/4 sec. cor. of sec. 9 only, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above the ground, in a mound of stone, with brass cap mkd.</p>
	<p style="text-align: center;"><u>1/4 S 9</u> 1927</p>
	<p>substantiated by:</p> <p style="padding-left: 40px;">A pinon, 8 ins. diam., bears N. 57½° E., 95 lks. dist., mkd. 1/4 S9 BT.</p> <p>Corner is located in a fence, bearing E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 33' W., beginning new measurement.</p>
25.36	<p>Fall 2 lks. N. of the closing cor. of secs. 16 and 17, monumented with an iron post, 2 ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R3W S 9 <u>S 17 S 16</u> C C 1927</p>
	<p>Corner is located 1 lk. S. of fence, bearing E. and W.</p>
41.21	<p>The cor. of secs. 8 and 9 only, monumented with an iron post, 2 ins. diam., firmly set, projecting 16 ins. above the ground, in a mound of stone, 2½ ft. base, 1 ft. high, N., with brass cap mkd.</p>
	<p style="text-align: center;">T15N R3W S 8 S 9 <u>S 17</u> 1927</p>
	<p>substantiated by:</p> <p style="padding-left: 40px;">A juniper, 18 ins. diam., bears N. 14½° E., 48 lks. dist., with blaze grown over.</p>
	<p>N. 1° 52' W., between secs. 8 and 9.</p> <p>Over broken land, through pinon and juniper timber.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, determined at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
79.94	<p style="text-align: center;">T15N R3W $\frac{1}{4}$ S 8 S 9</p> <p style="text-align: center;">1973</p> <p>The cor. of secs. 4, 5, 8, and 9, monumented with a mica schist, 22x15x6 ins., mkd. with 4 notches on the E. edge, firmly set in a small mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, in a small collar of stone, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R3W S 5 S 4 <hr style="width: 50%; margin: auto;"/>S 8 S 9</p> <p style="text-align: center;">1973</p> <p>Deposit the stone monument alongside the corner.</p>
20.52	<p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>N. 89° 39' W., between secs. 4 and 9.</p> <p>Over broken land, through scrub oak and juniper timber.</p> <p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.</p>
41.04	<p style="text-align: center;">T15N R3W E 1/16 $\frac{S 4}{S 9}$</p> <p style="text-align: center;">1973</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, determined at proportionate distance. There is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p>
44.60	<p style="text-align: center;">T15N R3W 1/4 $\frac{S 4}{S 9}$</p> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of the corner.</p> <p>Jerome Canyon with small stream, drains N.</p>
82.08	<p>The cor. of secs. 4, 5, 8, and 9.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
40.16	<p>N. 2° 18' W., between secs. 4 and 5.</p> <p>Over broken land, through scrub oak and juniper timber.</p> <p>The 1/4 sec. cor. of secs. 4 and 5, monumented with a mica schist, 18x15x6 ins., no mks. visible, firmly set in a mound of stone, 2 ft. base, 1½ ft. high.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 3 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 5 S 4 ¼</p> <p style="text-align: center;">1973</p> <p>Deposit the stone monument alongside the corner.</p> <p>Corner is located on ridge, bearing NW. and SE.</p>	
40.17	<p>N. 1° 56' W., beginning new measurement.</p> <p>The cor. of secs. 4, 5, 32, and 33, on the N. boundary of the township, hereinbefore described.</p>	
<p>Subdivision of Certain Sections Township 15 North, Range 3 West Gila and Salt River Meridian, Arizona</p>		
20.04	<p style="text-align: center;">In Section 4</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 2° 06' W., along the N. and S. center line of sec. 4.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, 16 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W C S 1/16 S 4 C</p> <p style="text-align: center;">1973</p>	
40.08	<p>Point for the center 1/4 sec. cor. of sec. 4, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 28 ins. in the ground, with brass cap mkd.</p>	

Subdivision of Certain Sections
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T15N R3W S 4 C ¼</p> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <p>Corner is located 20 lks. E. of bottom of draw, draining N.</p> <p>60.05 Point for the C-N 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam. 8 ins. in the ground to bedrock, in a mound of stone, 2 ft. base, 1½ ft. high, with brass cap mkd.</p>	
	<p style="text-align: center;">T15N R3W C N 1/16 S 4 C</p> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <p>80.30 The 1/4 sec. cor. of secs. 4 and 33, on the N. boundary of the township, hereinbefore described.</p>	
	<p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>N. 89° 35' W., along the E. and W. center line of sec. 4.</p> <p>20.51 Point for the C-E 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, in a collar of stone, with brass cap mkd.</p>	
	<p style="text-align: center;">T15N R3W C ——— S 4 ——— C E 1/16</p> <p style="text-align: center;">1973</p> <p>Corner is located 10 lks. SE. of bottom of draw, draining SW.</p> <p>41.02 The center 1/4 sec. cor. of sec. 4.</p>	
	<p>82.21 The 1/4 sec. cor. of secs. 4 and 5.</p>	
	<p>From the C-E 1/16 sec. cor. of sec. 4.</p> <p>N. 2° 06' W., along the N. and S. center line of the NE 1/4 of sec. 4.</p> <p>20.00 Point for the NE 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the NE 1/4.</p>	

Subdivision of Certain Sections
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, encircled in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 4 NE 1/16 1973</p>
40.29	The point for the E 1/16 sec. cor. of secs. 4 and 33, on the N. boundary of the township, hereinbefore described.
	<p>From the point for the N 1/16 sec. cor. of secs. 3 and 4. N. 89° 40' W., along the E. and W. center line of the NE 1/4 of sec. 4.</p>
20.51	The NE 1/16 sec. cor. of sec. 4.
41.02	The C-N 1/16 sec. cor. of sec. 4.
	<p>From the E 1/16 sec. cor. of secs. 4 and 9. N. 2° 06' W., along the N. and S. center line of the SE 1/4 of sec. 4.</p>
20.03	Point for the SE 1/16 sec. cor. of sec. 4, at the intersection with the E. and W. center line of the SE 1/4.
	<p>Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 4 SE 1/16 1973</p>
40.06	The C-E 1/16 sec. cor. of sec. 4.
	<p>From the point for the S 1/16 sec. cor. of secs. 3 and 4. N. 89° 37' W., along the E. and W. center line of the SE 1/4 of sec. 4.</p>
20.51	The SE 1/16 sec. cor. of sec. 4.
41.02	The C-S 1/16 sec. cor. of sec. 4.
	<p>In Section 14</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the 1/4 sec. cor. of secs. 14 and 23. N. 2° 15' E., along the N. and S. center line of sec. 14.</p>

Subdivision of Certain Sections
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
42.89	<p>Point for the center 1/4 sec. cor. of sec. 14, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 14 C ¼</p> <p style="text-align: center;">1973</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p>
63.25	Point for the C-N 1/16 sec. cor. of sec. 14, not monumented.
83.61	The 1/4 sec. cor. of secs. 11 and 14.
	<p>From the 1/4 sec. cor. of secs. 13 and 14.</p> <p>N. 89° 32' W., along the E. and W. center line of sec. 14.</p> <p>Over gently rolling land across pasture.</p>
34.50	Enter rolling land with juniper timber.
41.79	The center 1/4 sec. cor. of sec. 14.
61.05	<p>Point for the C-W 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 14 C ——— C W 1/16</p> <p style="text-align: center;">1973</p>
80.31	The 1/4 sec. cor. of secs. 14 and 15.
	<p>From the C-W 1/16 sec. cor. of sec. 14.</p> <p>N. 0° 29' E., along the N. and S. center line of the NW 1/4 of sec. 14.</p>
20.41	<p>Point for the NW 1/16 sec. cor. of sec. 14, at the intersection with the E. and W. center line of the NW 1/4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 14 NW 1/16</p> <p style="text-align: center;">1973</p>

Subdivision of Certain Sections
 Township 15 North, Range 3 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.
40.82	The W 1/16 sec. cor. of secs. 11 and 14.
	From the point for the C-N 1/16 sec. cor. of sec. 14.
	N. 89° 20' W., along the E. and W. center line of the NW 1/4 of sec. 14.
19.90	The NW 1/16 sec. cor. of sec. 14.
39.80	The N 1/16 sec. cor. of secs. 14 and 15.
	From the W 1/16 sec. cor. of sec. 14 only.
	N. 0° 37' E., along the N. and S. center line of the SW 1/4 of sec. 14.
41.89	Over gently rolling land, through juniper timber. The C-W 1/16 sec. cor. of sec. 14.
	In Section 15
	From the S 1/4 sec. cor. of sec. 15 only.
	N. 1° 56' W., along the N. and S. center line of sec. 15.
42.45	Point for the center 1/4 sec. cor. of sec. 15, at the intersection with the E. and W. center line.
	Set an iron post, 30 ins. long, 2½ ins. diam., 4 ins. in the ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.
	T15N R3W S 15 C ¼
	1973
	Corner is located 20 chs. S. of small ENE. drain.
82.88	The 1/4 sec. cor. of secs. 10 and 15.
	From the 1/4 sec. cor. of secs. 14 and 15.
	N. 84° 45' W., along the E. and W. center line of sec. 15.
40.91	The center 1/4 sec. cor. of sec. 15.
70.11	The west 1/4 sec. cor. of sec. 15 only, monumented with an iron post, 1 in. diam., firmly set, projecting 20 ins. above the ground, in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.

Subdivision of Certain Sections
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;"> 1/4 S 15</p> <p style="text-align: center;">1927</p> <p>substantiated by:</p> <p>A pinon, 8 ins. diam., bears N. 63$\frac{1}{4}$° E., 95 lks. dist., mkd. 1/4 S15 BT in partially grown over blaze.</p> <p>A pinon, 12 ins. diam., bears S. 88° E., 6 lks. dist., blazed, scribing illegible.</p>
<p>19.91</p> <p>39.82</p> <p>77.58</p>	<p style="text-align: center;">In Section 23</p> <hr style="width: 20%; margin: auto;"/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 7° 30' W., along the N. and S. center line of sec. 23.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 23, not monumented.</p> <p>Over gently rolling land with large rounded granite boulders and juniper timber.</p> <p>Point for the center 1/4 sec. cor. of sec. 23, at the intersection with the E. and W. center line.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., over an X in large granite boulder, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 23 C 1/4</p> <p style="text-align: center;">1973</p> <p>The 1/4 sec. cor. of secs. 14 and 23.</p>
<p>21.02</p>	<p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 37' W., along the E. and W. center line of sec. 23.</p> <p>Over gently rolling land, through scattered pinon and juniper timber.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 28 ins. in the ground, in a collar of stone, with brass cap mkd.</p> <p style="text-align: center;">T15N R3W S 23 C — E 1/16 — C</p> <p style="text-align: center;">1973</p>

Subdivision of Certain Sections
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Corner is located 6 lks. W. of fence, bearing N. and S., at S. end of cattle guard.</p>
34.20	Mint Wash, 20 ft. wide, 3 lks. deep, course N.
42.04	The center 1/4 sec. cor. of sec. 23.
73.60	<p>The west 1/4 sec. cor. of sec. 23 only, monumented with an iron post, 1 in. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> $\frac{1}{4}$ S 23 1927 </div> <p>substantiated by:</p> <p style="padding-left: 40px;">A pinon, 10 ins. diam., bears N. 70½° E., 88 lks. dist., blazed, scribing illegible.</p> <p style="padding-left: 40px;">A pinon, 14 ins. diam., bears S. 68 3/4° E., 81 lks. dist., with blaze partially grown over, scribing illegible.</p>
19.87	<p>From the point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>N. 5° 57' W., along the N. and S. center line of the SE 1/4 of sec. 23.</p> <p>Point for the SE 1/16 sec. cor. of sec. 23, at the intersection with the E. and W. center line of the SE 1/4.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T15N R3W S 23 SE 1/16 1973 </div>
39.74	<p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W. of the corner.</p> <p>The C-E 1/16 sec. cor. of sec. 23.</p>
20.48	<p>From the S 1/16 sec. cor. of secs. 23 and 24.</p> <p>S. 89° 39' W., along the E. and W. center line of the SE 1/4 of sec. 23.</p> <p>The SE 1/16 sec. cor. of sec. 23.</p>
40.97	The point for the C-S 1/16 sec. cor. of sec. 23.

General Description
Township 15 North, Range 3 West
Gila and Salt River Meridian, Arizona

CHAINS

The area encompassed by this survey varies from rough, broken land with large, rounded granite boulders to nearly level pasture land. The vegetation consists of scrub oak on the broken ridges, juniper and pinon on the higher elevations and cottonwood and willows along the drainages. The open areas on the lower elevations are covered with native grasses. Mint Wash drains the area from the southeast corner of section 23 to the northwest corner of section 4, with numerous draws and small canyons draining into it.

There are several houses in sections 3 and 11, and extensive subdivision developments in the northeast quarter of section 23 and the west half of section 24. A paved county road runs generally north and south along the east edge of the area surveyed.

	CHAINS		
--	--------	--	--

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Gilbert V. Olson, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day Supplemental Special Instructions 13th of March, 19 73, ~~(XXXXXX)~~ April 1973 (I) have dependently resurveyed portions of the north boundary and subdivisional lines, and subdivided certain sections in Township 15 North, Range 3 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 18, 1976 (Date) [Signature] (Cadastral Surveyor) Gilbert V. Olson

CERTIFICATE OF APPROVAL

SUBMITTED FOR APPROVAL Date FEB 01 1974 MAY 20 1976

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the north boundary and subdivisional lines, with the subdivision of certain sections in Township 15 North, Range 3 West, Gila and Salt River Meridian, Arizona.

executed by Gilbert V. Olson Supervisory Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JUL 30 1976 (Date) [Signature] (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626