

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF

REMONUMENTATION

IN

TOWNSHIP 15 NORTH, RANGE 13 EAST

TOWNSHIP 15 NORTH, RANGE 14 EAST

TOWNSHIP 14 NORTH, RANGE 14 EAST

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul L. Reeves, Cadastral Surveyor

Under special instructions dated July 29, 19 75, approved July 31, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
Number 577, and assignment instructions dated July 29, 19 75.

Survey commenced August 12, 19 75

Survey completed September 5, 19 75

BOOK 5024

INDEX DIAGRAM

Township _____, Range _____,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

INDEX TO SECTION
CORNER MONUMENTS

Tp. 15 N. R. 13 E. Mer. 4 G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 15 N. R. 14 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Tp. 14 N. R. 14 E. Mer. G&SR

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Township 15 North, Range 13 East
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of remonumentation of cadastral survey corners in Township 15 North, Range 13 East, Township 15 North, Range 14 East, and Township 14 North, Range 14 East, G&SRM, Arizona. The remonumentation is by agreement with the U.S. Forest Service. The detailed cooperative agreement was approved by the Director, Bureau of Land Management, by memorandum (5.04b), dated October 16, 1958.

The remonumentation was executed in accordance with the Manual of Surveying Instructions, 1973 and the Special Instructions for Group 577, Arizona, dated July 29, 1975. The approval of the Special Instructions on July 31, 1975 gave authority to proceed with the remonumentation in accordance with the Director's Order No. 541, dated April 21, 1961.

The assistants, furnished by the Forest Service, remonumented the original corner positions after verification. An open sight compass was used to obtain the bearings and a standard steel tape was used to measure the distances to corner accessories.

Township 15 North, Range 13 East, G&SRM, Arizona

The East boundary was surveyed in 1893 by Philip Contzen.

The North boundary and subdivisional lines were surveyed in 1893 by Daniel Drummond.

Re monumentation, E. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

The mean magnetic declination is $13 \frac{3}{4}^{\circ}$ E.

The $\frac{1}{4}$ sec. cor. of secs. 7 and 12, Tps. 15 N., Rs. 13 and 14 E., monumented by a sandstone, 21 x 12 x 6 ins., projecting 14 ins. above ground, mkd. $\frac{1}{4}$ on W face.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound of stone to top, with brass cap mkd.

T 15 N
R 13 E R 14 E
 $\frac{1}{4}$
S 12 | S 7
1975

Deposit the mkd. stone alongside the iron post.

The cor. is located in a burned over area, 3 lks. E of a N-S fence, 105 lks. E of a track road bearing N and S and 300 lks. S of a track road bearing E and W.

Remonumentation, E. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

The cor. of secs. 1, 6, 7 and 12, Tps. 15 N., Rs. 13 and 14 E., monumented by a limestone, 15 x 12 x 10 ins., firmly set, projecting 10 ins. above ground, mkd. with 1 groove on the N face and 5 grooves on the S face from which the remains of the original bearing trees

A stump hole, bears N. 70° E., 248 lks. dist.

A limb on a cedar tree, 24 ins. diam., bears S. 25½° E., 42.5 lks. dist., mkd. T15N R14 S7 BT. (Record, S. 20° E., 40 lks.)

A limb on a pinon pine tree, 9 ins. diam., bears S. 75° W., 68 lks. dist., mkd. T15N R13E S12 BT.

A stump hole, bears N. 54° W., 225 lks. dist., a down pine alongside, 15 ins. diam., mkd. with illegible scribe marks on a limb. (Record, N. 53° W., 231 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 15 N
R 13 E R 14 E
S 1 | S 6
S 12 | S 7

1975

Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.

Deposit the mkd. stone alongside the iron post.

The cor. is located 3 lks. E of a N-S fence.

The ¼ sec. cor. of secs. 1 and 6, Tps. 15 N., Rs. 13 and 14 E., monumented by a limestone, 12 x 12 x 4 ins., loosely set, no visible marks, from which the remains of the original bearing trees

A stump hole, bears S. 61½° E., 82 lks. dist., illegible scribe marks on a small piece of wood lying alongside.

A stump hole, bears N. 53° W., 207 lks. dist., a down pine alongside, 10 ins. diam., mkd. ¼ S BT. (Record, N. 57° W., 206 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, mound of stone, 2½ ft. base to top, with brass cap mkd.

Remonumentation, E. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

T 15 N
R 13 E R 14 E
 $\frac{1}{4}$
S 1 | S 6
1975

from which a new bearing tree

A pinon, 8 ins. diam., bears S. 85° W., 68.5 lks.
dist., mkd. $\frac{1}{4}$ S1 BT.

Deposit the unmarked stone alongside the iron post.

The cor. is located 4 lks. E of a N-S fence.

Remonumentation, N. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, Tps. 15 and 16 N.,
Rs. 13 E., monumented by a limestone, 13 x 10 x 5 ins.,
firmly set, mkd. $\frac{1}{4}$ on N face, from which the remaining
bearing tree

A pine, 7 ins. diam., bears S. 86 $\frac{1}{4}$ ° E., 14 lks.
dist., mkd. $\frac{1}{4}$ S BT. (Record, S. 89° E., 14 lks.)

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 14 ins. in
the ground, mound of stone, 3 ft. base to top, with brass
cap mkd.

T 16 N R 13 E
 $\frac{1}{4}$ $\frac{S 36}{S 1}$
T 15 N
1975

Deposit the mkd. stone alongside the iron post.

The cor. is located 3 lks. N of an E-W fence.

The cor. of secs. 1, 2, 35 and 36, Tps. 15 and 16 N.,
Rs. 13 E., monumented by a sandstone, 22 x 9 x 8 ins.,
loosely set, mkd. with 1 groove on the E face and 5
grooves on the W face, from which the remains of the
original bearing trees

A stump hole, bears S. 30° W., 60 lks. dist., a
down pine alongside is badly deteriorated with
no marks visible.

There is no remaining evidence of the other bearing
trees.

At the cor. point

Remonumentation, N. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2 ft. base to top, with brass cap mkd.

T 16 N R 13 E
S 35 | S 36
S 2 | S 1
T 15 N
1975

from which new bearing trees

A cedar, 8 ins. diam., bears S. 62° E., 109 lks. dist., mkd. T15N R13E S1 BT.

A cedar, 16 ins. diam., bears S. 50½° W., 136 lks. dist., mkd. T15N R13E S2 BT.

Deposit the mkd. stone alongside the iron post.

The cor. is located 2 lks. N of an E-W fence.

The ¼ sec. cor. of secs. 2 and 35, Tps. 15 and 16 N., Rs. 13 E., monumented by a malpais stone, 17 x 12 x 6 ins., firmly set, projecting 11 ins. above ground, mkd. ¼ on S face, from which the remains of the original bearing trees

A stump hole, bears N. 48½° W., 78 lks. dist., pine snag alongside, mkd. ¼ S BT.

A cedar, 8 ins. diam., bears S. 16° W., 35 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 16 N R 13 E
¼ S 35
S 2
T 15 N
1975

Deposit the mkd. stone alongside the iron post.

The cor. is located 7.5 lks. S of an E-W fence.

The cor. of secs. 2, 3, 34 and 35, Tps. 15 and 16 N., Rs. 13 E., reestablished by record course and dist. from the remains of the original bearing trees

A stump hole, bears N. 37° E., 175 lks. dist., down pine, badly deteriorated alongside, no marks visible.

Remonumentation, N. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

A stump hole, bears S. 5° E., 71 lks. dist., a down pine alongside, 9 ins. diam., mkd. with illegible scribe marks.

A stump hole, bears S. 72° W., 54 lks. dist., a down pine alongside, 8 ins. diam., mkd. with illegible scribe marks.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 16 N R 13 E
S 34 | S 35
S 3 | S 2
T 15 N
1975

The cor. is located 3 lks. S of an E-W fence.

The ¼ sec. cor. of secs. 3 and 34, Tps. 15 and 16 N., Rs. 13 E., monumented by a malpais stone, 16 x 10 x 6 ins., loosely set, mkd. ¼ on N face, from which the remains of the original bearing trees

A dead pine, 15 ins. diam., bears S. 70° E., 5 lks. dist., mkd. ¼ S BT.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 16 N R 13 E
¼ S 34
S 3
T 15 N
1975

from which a new bearing tree

A pine, 5 ins. diam., bears S. 45° E., 70 lks. dist., mkd. ¼ S3 BT.

Deposit the mkd. stone alongside the iron post.

From the cor., a fence cor. bears N. 61° W., 90.5 lks. dist., fences extend E, S and W.

The cor. of secs. 3, 4, 33 and 34, Tps. 15 and 16 N., Rs. 13 E., monumented by a malpais stone, 16 x 10 x 4 ins., firmly set, projecting 8 ins. above ground, no visible marks, from which the remains of the original bearing trees

Remonumentation, N. Bdy.,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

A stump hole, bears N. $78\frac{1}{2}^\circ$ E., 111 lks. dist., a down pine alongside, 10 ins. diam., mkd. with illegible scribe marks.

A stump hole, bears S. $25\frac{1}{2}^\circ$ E., 125 lks. dist., a down pine alongside, 12 ins. diam., mkd. T15N R13E S3 BT.

A stump hole, bears S. 14° W., 176 lks. dist., a down pine snag alongside, 6 ins. diam., with no scribe marks visible.

A stump hole, bears N. 20° W., 292 lks. dist., a down cedar alongside, 12 ins. diam., mkd. with a healed blaze.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 4 ft. base to top, with brass cap mkd.

T 16 N R 13 E

S 33	S 34
S 4	S 3

T 15 N
1975

Deposit the unmarked stone alongside the iron post.

The cor. is located 88 lks. N of an E-W fence.

Remonumentation, Subdivision,
T. 15 N., R. 13 E., G&SRM, Arizona

The cor. of secs. 2, 3, 10 and 11, reestablished by record course and distance from the original bearing trees

A pine, 13 ins. diam., bears N. $71\frac{1}{4}^\circ$ E., 248 lks. dist., mkd. T15N R13E, with other marks grown over.

A cedar, 12 ins. diam., bears S. $52\frac{1}{4}^\circ$ E., 219 lks. dist., mkd. T15N R13E S11 BT.

A stump hole, bears S. $49\frac{1}{4}^\circ$ W., 256 lks. dist., a down pine alongside, 8 ins. diam., mkd. T15N R13E S3 BT.

A pine, 8 ins. diam., bears N. $55\frac{1}{2}^\circ$ W., 182 lks. dist., mkd. T15N R13, no other marks visible.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

Remonumentation, Subdivision,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

T 15 N R 13 E

$$\begin{array}{c|c} \text{S } 3 & \text{S } 2 \\ \hline \text{S } 10 & \text{S } 11 \end{array}$$
 1975

from which a new bearing tree

A juniper, 5 ins. diam., bears S. 30° W., 164.5
lks. dist., mkd. T15N R13E S10 BT.

The cor. is located 56 lks. S of a track road bearing NE
and SW.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 10, monumented by a
malpais stone, 14 x 10 x 8 ins., firmly set, projecting
8 ins. above ground, mkd. $\frac{1}{4}$ on N face, from which the
remains of the original bearing trees

A stump hole, bears N. 84° E., 18 lks. dist., a
down pine alongside, 8 ins. diam., mkd. with
an open blaze - scribe marks illegible.

A stump hole, bears S. 2° E., 35 lks. dist., a
down pine alongside, 8 ins. diam., mkd. $\frac{1}{4}$ S BT.

At the cor. point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins.
in the ground, mound of stone, 2 ft. base to top, with
brass cap mkd.

T 15 N R 13 E

$$\frac{1}{4} \begin{array}{c} \text{S } 3 \\ \hline \text{S } 10 \end{array}$$
 1975

from which new bearing trees

A pinon, 8 ins. diam., bears N. 49 $\frac{1}{4}$ ° E., 112 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.

A juniper, 6 ins. diam., bears S. 84 $\frac{3}{4}$ ° W.,
36.5 lks. dist., mkd. $\frac{1}{4}$ S10 BT.

Deposit the mkd. stone alongside the iron post.

The $\frac{1}{4}$ sec. cor. of secs. 3 and 4, monumented by a sand-
stone in place, 4 x 2 x 2 ft. above ground, mkd. with
a + at the cor. point and $\frac{1}{4}$ on the SW face, from which
the remains of the original bearing trees

A stump hole, bears S. 40° E., 27 lks. dist., a
down pine alongside, 9 ins. diam., mkd. with
a faint 4 in an open blaze.

Remonumentation, Subdivision,
T. 15 N., R. 13 E., G&SRM, Arizona

CHAINS

A stump hole, bears N. 78° W., 37 lks. dist.,
a down pine alongside, 6 ins. diam., mkd.
¼ S BT.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., over the
+ chiseled in solid sandstone, mound of stone, 5 ft.
base to top, with brass cap mkd.

T 15 N R 13 E
 ½
 S 4 | S 3
 1975

from which new accessories

A sandstone outcrop, 12 x 4 x 3 ft. above ground,
bears N. 82½° E., 42 lks. dist., mkd. X BO.

A sandstone outcrop, 6 x 3 x 2 ft., above ground,
bears N. 87½° W., 139 lks. dist., mkd. X BO.

Township 15 North, Range 14 East, G&SRM, Arizona

The subdivisional lines were surveyed in 1893 by Philip
Contzen.

Remonumentation, Subdivision,
T. 15 N., R. 14 E., G&SRM, Arizona

The mean magnetic declination is 13 ¾° E.

The cor. of secs. 26, 27, 34 and 35, monumented by a
limestone, 15 x 8 x 6 ins., loosely set, mkd. with 1
notch on S edge and 2 notches on E edge, from which the
original bearing tree

A pine, 14 ins. diam., bears S. 88° E., 107 lks.
dist., mkd. with a partially healed blaze -
scribe marks illegible.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins.
in the ground, mound of stone, 2½ ft. base to top, with
brass cap mkd.

T 15 N R 14 E
 S 27 | S 26
 S 34 | S 35
 1975

Remonumentation, Subdivision,
T. 15 N., R. 14 E., G&SRM, Arizona

CHAINS

from which a new bearing tree

A pine, 12 ins. diam., bears N. $32\frac{1}{2}^\circ$ W., 146.5
lks. dist., mkd. T15N R14E S27 BT.

Deposit the mkd. stone alongside the iron post.

The cor. is located in a N-S fence, 37 lks. South of a
fence cor. with fence extending N, S and E.

The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented by a
limestone, 15 x 8 x 6 ins., firmly set, projecting 8 ins.
above ground, mkd. $\frac{1}{4}$ on W face, mound of stone, 2 ft.
base, 1 ft. high, W from which the original bearing
trees

A cedar, 12 ins. diam., bears S. 23° E., 102
lks. dist., mkd. with a healed blaze.

A limb on a cedar, 12 ins. diam., bears N. 38° W.,
116 lks. dist., mkd. with illegible scribe
marks. (Record, N. $36\frac{1}{2}^\circ$ W., 116 lks.)

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins.
in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with
brass cap mkd.

T 15 N R 14 E
 $\frac{1}{4}$
 S 27 | S 26
 1975

Deposit the mkd. stone alongside the iron post.

The cor. is located 7.5 lks. W of a N-S fence.

The $\frac{1}{4}$ sec. cor. of secs. 22 and 23, monumented by a
sandstone, 20 x 7 x 6 ins., firmly set, projecting 14
ins. above ground, mkd. $\frac{1}{4}$ on W face, from which the re-
mains of the original bearing trees

A pine, 5 ins. diam., bears N. 58° W., 62 lks.
dist., mkd. with a partially healed blaze.
(Record, N. $62\frac{1}{2}^\circ$ W., 62 lks.)

A stump hole, bears S. $14\frac{1}{2}^\circ$ E., 10 lks. dist.
(Record, S. 10° E., 10 lks.)

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins.
in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with
brass cap mkd.

Remonumentation, Subdivision,
T. 15 N., R. 14 E., G&SRM, Arizona

CHAINS

T 15 N R 14 E

$\frac{1}{4}$
 S 22 | S 23

1975

Deposit the mkd. stone alongside the iron post.

The cor. is located in a N-S fence.

The $\frac{1}{4}$ sec. cor. of secs. 15 and 22, monumented by a limestone, 18 x 8 x 6 ins., loosely set, scattered mound of stone N, mkd. 4 on N face, from which the remains of the original bearing trees

A stump hole, bears N. $47\frac{1}{2}^\circ$ E., 29 lks. dist.,
a down cedar alongside, 14 ins. diam., no
marks visible.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 15 N R 14 E

$\frac{1}{4}$ $\frac{S 15}{S 22}$

1975

from which a new bearing tree

A cedar, 16 ins. diam., bears S. 54° E., 70 lks.
dist., mkd. $\frac{1}{4}$ S22 BT.

Deposit the mkd. stone alongside the iron post.

The cor. is located 1 lk. S of an E-W fence and 50 lks. E of the junction of washes draining southerly from NE and NW.

The cor. of secs. 17, 18, 19 and 20, monumented by a limestone, loosely set in a mound of stone, no marks visible, from which the remains of the original bearing trees

A cedar, 12 ins. diam., bears S. 62° E., 27 lks.
dist., mkd. T15N R14E S20 BT.

A stump hole, bears N. $35\frac{1}{2}^\circ$ W., 76 lks. dist.,
a down pinon alongside, 9 ins. diam., mkd.
T15N R14E S18 BT.

At the cor. point

Remonumentation, Subdivision,
T. 15 N., R. 14 E., G&SRM, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2 ft. base to top, with brass cap mkd.

T 15 N R 14 E
S 18 | S 17
S 19 | S 20
1975

from which a new bearing tree

A cedar, 12 ins. diam., bears N. 75° W., 91 lks. dist., mkd. T15N R14E S18 BT.

Deposit the unmarked stone alongside the iron post.

The cor. is located 3 lks. E of a fence cor. with fences extending N, E and S and 68 lks. N of a dirt road bearing E and W.

The ¼ sec. cor. of secs. 17 and 18, reestablished by record course and distance from the remains of the original bearing trees

A stump hole, bears N. 30½° E., 76 lks. dist., a down pinon alongside, 8 ins. diam., mkd. ¼ S BT.

A stump hole, bears S. 11¼° W., 227 lks. dist., a down pinon alongside, 10 ins. diam., mkd. with illegible scribe marks.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground to bedrock, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 15 N R 14 E
¼
S 18 | S 17
1975

from which a new bearing tree

A cedar, 5 ins. diam., bears S. 30 3/4° W., 112 lks. dist., mkd. ¼ S18 BT.

The cor. is located in a N-S fence.

The cor. of secs. 7, 8, 17 and 18, reestablished by record course and distance from the remains of one of the original bearing trees

A stump hole, bears S. 46° W., 64 lks. dist., a down pinon alongside, 12 ins. diam., mkd. 5N R14E S18 BT - no other marks legible.

Remonumentation, Subdivision,
T. 15 N., R. 14 E., G&SRM, Arizona

CHAINS

The other original bearing trees have been bulldozed out or destroyed by fire.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

T 15 N		R 14 E	
S 7		S 8	
S 18		S 17	
1975			

from which new bearing trees

A pine, 9 ins. diam., bears S. 53½° W., 205 lks. dist., mkd. T15N R14E S18 BT.

A cedar, 4 ins. diam., bears S. 21¼° W., 80 lks. dist., mkd. X at breast height and BT at the base.

The cor. is located 2 lks. NE of a fence cor. with fences extending S and W.

Township 14 North, Range 14 East, G&SRM, Arizona

The subdivisional lines were surveyed in 1893 by Philip Contzen.

Remonumentation, Subdivision,
T. 14 N., R. 14 E., G&SRM, Arizona

The mean magnetic declination is 13 3/4° E.

The cor. of secs. 2, 3, 10 and 11, monumented by a limestone, 18 x 12 x 6 ins., firmly set, projecting 12 ins. above ground, mkd. with 2 grooves on the E face and 5 grooves on the S face, with a mound of stone N, from which the remains of the original bearing trees

A pinon, 12 ins. diam., bears S. 18¼° E., 89 lks. dist., mkd. with a partially healed blaze - scribe marks visible but illegible. (Record, S. 15 3/4° E., 89 lks.)

A stump hole, bears N. 63½° W., 74 lks. dist., a down pinon alongside, 8 ins. diam., mkd. T14N R14E S3 BT. (Record, N. 63½° W., 14 lks.)

At the cor. point

Remonumentation, Subdivision,
T. 14 N., R. 14 E., G&SRM, Arizona

CHAINS

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 14 N R 14 E

S 3	S 2
S 10	S 11

 1975

from which a new bearing tree

A cedar, 10 ins. diam., bears N. $64\frac{3}{4}^{\circ}$ W.,
87 lks. dist., mkd. T14N R14E S3 BT.

Deposit the mkd. stone alongside the iron post.

The cor. is located 3 lks. SW of the cor. of fences extending N and E.

The $\frac{1}{4}$ sec. cor. of secs. 2 and 3, monumented by a limestone, 18 x 14 x 6 ins. loosely set in a scattered mound of stone, no marks visible, from which the remains of the original bearing trees

A stump hole, bears S. $37\frac{1}{2}^{\circ}$ W., 35 lks. dist.,
a down pinon alongside, 8 ins. diam., mkd.
 $\frac{1}{4}$ S BT.

A stump hole, bears N. $19\frac{1}{2}^{\circ}$ E., 22 lks. dist.,
a down pinon alongside, 10 ins. diam., mkd.
 $\frac{1}{4}$ S BT. (Record, N. $49\frac{1}{2}^{\circ}$ E., 92 lks.)

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.

T 14 N R 14 E
 $\frac{1}{4}$

S 3	S 2
-----	-----

 1975

from which new bearing trees

A cedar, 5 ins. diam., bears N. 60° E., 31 lks.
dist., mkd. $\frac{1}{4}$ S2 BT.

A cedar, 5 ins. diam., bears S. $89\frac{1}{2}^{\circ}$ W., 26 lks.
dist., mkd. $\frac{1}{4}$ S3 BT.

Deposit the unmarked stone alongside the iron post.

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Paul L. Reeves, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of July, 1975, (I) ~~(We)~~ have remonumented a portion of the cadastral survey corners in Township 15 North, Range 13 East, Township 15 North, Range 14 East and Township 14 North, Range 14 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 15, 1976

(Date)

Paul L. Reeves

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the remonumentation of a portion of the cadastral survey corners in Township 15 North, Range 13 East, Township 15 North, Range 14 East and Township 14 North, Range 14 East, all of the Gila and Salt River Meridian, Arizona,

executed by Paul L. Reeves, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

APR 27 1977

(Date)

Bernard W. Foster
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626