



1A

RECEIVED  
STATE OF INDIANA  
JUL 1 1911  
M.A. COLE  
INDIANA, INDIANA

BOOK 5036

# INDEX DIAGRAM

Township 21 North, Range 6 East,

6	5	4	3	2	1
			7		
7	8	9	6 10	1 11	12
			4		
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of Sec. 10 - Pages 8 thru 24.

Township 21 North, Range 6 East  
Gila and Salt River Meridian, Arizona

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and the subdivisional survey of section 10, Township 21 North, Range 6 East, Gila and Salt River Meridian, Arizona.

The township boundaries and subdivisional lines, except the line bet. secs. 2 and 3, were surveyed by John L. Harris, Deputy Surveyor, in 1878. The line between sections 2 and 3 was surveyed by James A. Lampert, Deputy Surveyor, in 1903. Horace M. Muscott and Claude F. Warner, Assistant Cadastral Engineer, resurveyed the west boundary of the township in 1941. Certain corners were remonumented by Howard H. Thomas, Cadastral Surveyor, in 1968, and Louis D. Gilbert, Cadastral Surveyor, in 1970.

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 579, Arizona, dated August 29, 1975.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations, and refer to the true meridian.

The geographic position of the southeast cor. of section 10, as scaled from the Geological Survey quadrangle map, FLAGSTAFF WEST, ARIZ., prepared in 1962, is as follows:

Latitude 35°12.6' N.      Longitude 111°44.1' W.

The mean magnetic declination is 14°30' E.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona  
(Restoring the 1878 survey by John L. Harris)

Beginning at the cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2½ ins. diam., projecting 2 ins. above a collar of stone, 2 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1968 remonumentation in T. 21 N., R. 6 E., from which the remains of the original bearing trees

A pine stump, 30 ins. diam., bears S. 72½° E.,  
50 lks. dist. (Record bearing S. 85° E.)

A ponderosa pine, 33 ins. diam., bears S. 61° W.,  
68 lks. dist., mkd. with a partially over-  
grown blaze. (Record bearing S. 71° W.)

A ponderosa pine, 33 ins. diam., bears N. 46° W.,  
90 lks. dist.; mkd. with a partially over-  
grown blaze. (Record bearing and dist.  
N. 43° W., 91 lks.)

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

CHAINS	
	The cor. is located 26 lks. W of a N and S power line and 3 lks. NW of a fence cor.; fences extend N and S. 15° E.
	N. 0°08' W., bet. secs. 10 and 11.
	Over gently rolling land, through dense timber.
	Along the W side of a N and S fence.
17.80	Fence, bears E and W.
19.82	Pt. for the S 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T21N R6E S 1/16 S10 S11 1975</p>
	from which
	<p style="text-align: center;">A ponderosa pine, 13 ins. diam., bears N. 45° W., 33 lks. dist., mkd. S 1/16 S10 BT.</p>
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.
	The cor. is located 30 lks. W of a N and S power line and 65 lks. W of a N and S fence.
22.60	Power line, bears E and W.
24.775	Pt. for the S-N-S 1/256 sec. cor. of secs. 10 and 11; not monumented.
29.73	Pt. for the N-S 1/64 sec. cor. of secs. 10 and 11.
	Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">N-S 1/64 S10 S11 1975</p>
	from which
	<p style="text-align: center;">A ponderosa pine, 6 ins. diam., bears S. 47° W., 54 lks. dist., mkd. N-S 1/64 S10 BT.</p>
32.50	Abandoned track road, bears N. 65° E. and S. 65° W.
32.70	Fence, bears N. 65° E. and S. 65° W.
37.40	Fence, bears N. 60° E. and S. 60° W.
38.80	Fence, bears irregularly N and S.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

## CHAINS

- 39.64 The  $\frac{1}{4}$  sec. cor. of secs. 10 and 11, monumented with an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., projecting 4 ins. above a collar of stone,  $2\frac{1}{2}$  ft. base, 4 ins. high, with brass cap mkd. as described in the official record of the 1968 remonumentation in T. 21 N., R. 6 E., from which the remains of the original bearing trees
- A pine stump, 20 ins. diam., bears S.  $20^\circ$  E.,  
9 lks. dist.
- A pine stump, 22 ins. diam., bears S.  $73\frac{1}{2}^\circ$  W.,  
21 lks. dist. (Record bearing West)
- The 1968 bearing trees
- A ponderosa pine, 7 ins. diam., bears N.  $29^\circ$  E.,  
14 lks. dist., mkd. X BT.
- A ponderosa pine, 14 ins. diam., bears S.  $79^\circ$  E.,  
81 lks. dist., mkd.  $\frac{1}{4}$  S11 BT.
- The cor. is located 35 lks. W of a N and S power line.
- \_\_\_\_\_
- N.  $0^\circ 08'$  E., beginning new measurement.
- Along the E side of a N and S fence.
- 5.06 Pt. for the S-S-N  $1/256$  sec. cor. of secs. 10 and 11; not monumented.
- 10.12 Pt. for the S-N  $1/64$  sec. cor. of secs. 10 and 11; not monumented.
- 20.24 Pt. for the N  $1/16$  sec. cor. of secs. 10 and 11.
- Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 14 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.
- T21N R6E  
N  $1/16$   
S10 | S11  
1975
- from which
- A ponderosa pine, 11 ins. diam., bears S.  $44^\circ$  W.,  
24 lks. dist., mkd. N  $1/16$  S10 BT.
- The cor. is located 33 lks. W of a N and S power line.
- 27.40 Fence, bears N.  $70^\circ$  E. and S.  $70^\circ$  W.
- 28.30 Draw, drains S.  $60^\circ$  W.
- 40.48 The cor. of secs. 2, 3, 10 and 11, monumented with an iron post,  $2\frac{1}{2}$  ins. diam., projecting 2 ins. above a collar of stone, 2 ft. base, 4 ins. high, with brass cap mkd. as described in the official record of the 1968 remonumentation in T. 21 N., R. 6 E., from which the remains of the original bearing trees

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine stump, 24 ins. diam., bears N. 30 3/4° E., 65 lks. dist., mkd. with a healed blaze. (Record bearing and dist. N. 35° E., 63 lks. dist.)</p>
	<p>A pine stump, 25 ins. diam., bears S. 34° E., 79 lks. dist., no marks visible.</p>
	<p>A pine stump, 28 ins. diam., bears S. 7° W., 25 lks. dist., mkd. with a healed blaze.</p>
	<p>A pine stump, 28 ins. diam., bears N. 59° W., 7 lks. dist., mkd. with a healed blaze.</p>
	<p>The 1968 bearing tree</p>
	<p>A ponderosa pine, 16 ins. diam., bears S. 67° W., 46 lks. dist., mkd. T21N R6E S10 BT.</p>
	<p>The cor. is located S. 47° W., 44.5 lks. dist., from power pole No. 1; power lines extend northeasterly and southerly.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, clay loam and rocky.</p>
	<p>Timber, ponderosa pine.</p>
	<p>Undergrowth, young pine and native grasses.</p>
	<p>From the cor. of secs. 10, 11, 14 and 15.</p>
	<p>S. 89°38' W., bet. secs. 10 and 15.</p>
	<p>Over gently rolling land, through dense timber.</p>
	<p>3.60 Graded gravel road, bears S. 25° E. and N. 25° W.</p>
	<p>15.50 Dim trail road, bears N and S.</p>
	<p>15.80 Wash, 10 lks. wide, 1 ft. deep, drains southerly.</p>
	<p>19.94 Pt. for the E 1/16 sec. cor. of secs. 10 and 15.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T21N R6E E 1/16 <math>\frac{S10}{S15}</math> 1975</p>
	<p>from which</p>
	<p>A ponderosa pine, 9 ins. diam., bears N. 2° W., 25 lks. dist., mkd. E 1/16 S10 BT.</p>
	<p>39.88 The ¼ sec. cor. of secs. 10 and 15, monumented with a nail set in the center of a mound of stone, 2 ft. base, 6 ins. high, from which the remains of the original bearing trees</p>
	<p>A pine stump, 32 ins. diam., bears N. 19° E., 61 lks. dist.; down tree alongside mkd. ¼ S.</p>

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

## CHAINS

A decayed pine stump, bears S. 10° E., 139 lks.  
dist.

At the cor. pt.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in  
the ground, with brass cap mkd.

T21N R6E

¼  $\frac{S10}{S15}$

1975

from which a new bearing tree

A ponderosa pine, 12 ins. diam., bears N. 40½° E.,  
84 lks. dist., mkd. ¼ S10 BT.

Raise a mound of stone, 2½ ft. base, 2 ft. high, N of the  
cor.

Deposit the nail alongside the iron post.

S. 89°18' W., beginning new measurement.

3.00 Fence, bears S. 35° E. and N. 35° W.

25.50 Power line, bears S. 55° E. and N. 55° W., approximately  
100 lks. dist., thence N. 88° W.

28.30 Track road, bears N. 30° E. and S. 30° W.

41.11 The cor. of secs. 9, 10, 15 and 16, monumented with a  
volcanic stone, 15 x 12 x 13 ins., firmly set in a mound  
of stone, 2 ft. base, 6 ins. high, mkd. with an X on top,  
from which the original bearing trees

A pine stump, 30 ins. diam., bears N. 56° E.,  
58 lks. dist.; a down tree alongside mkd.  
TXXIN RVIEEX.

A ponderosa pine, 35 ins. diam., bears S. 74° E.,  
148 lks. dist., mkd. with a healed blaze.  
(Record bearing S. 72° E.)

The stump hole of an uprooted pine tree, bears  
S. 82½° W., 113 lks. dist.; the uprooted  
tree, 28 ins. diam., lying alongside, is  
mkd. with a healed blaze. (Record bearing  
S. 85° W.)

A decayed pine stump, bears N. 30½° W., 54  
lks. dist. (Record bearing N. 20° W.)

At the cor. pt.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in  
the ground, with brass cap mkd.

T21N R6E

S 9 | S10  
S16 | S15

1975

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which new bearing trees</p> <p>A ponderosa pine, 10 ins. diam., bears N. 70° E., 65 lks. dist., mkd. T21N R6E S10 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 13¼° W., 11.5 lks. dist., mkd. T21N R6E S9 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Land, gently rolling. Soil, clay loam and rocky. Timber, pine. Undergrowth, young pine and native grasses.</p>
<p>1.20</p> <p>40.52</p>	<p>N. 1°04' E., bet. secs. 9 and 10.</p> <p>Over gently rolling land, through dense timber.</p> <p>Power line, bears S. 88° E. and N. 88° W.</p> <p>The ¼ sec. cor. of secs. 9 and 10, monumented with a re- bar, 3/8 in. diam., set in a mound of stone, 2 ft. base, 6 ins. high; a tag attached to the re-bar is mkd. L.S. 2473, from which the remains of the original bearing trees</p> <p>A partially decayed pine stump, bears S. 85 3/4° E., 91 lks. dist. (Record bearing S. 87° E.)</p> <p>A partially decayed pine stump, bears S. 84° W., 88 lks. dist. (Record bearing West)</p> <p>At the cor. pt.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, 2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T21N R6E</p> <p>¼</p> <p>S 9   S10</p> <p>1975</p> </div> <p>from which a new bearing tree</p> <p>A ponderosa pine, 8 ins. diam., bears N. 10½° E., 35 lks. dist., mkd. ¼ S10 BT.</p> <p>Reset the re-bar alongside the iron post.</p>
<p>40.15</p>	<p>N. 0°05' W., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with a mound of stone, 2 ft. base, 1 ft. high, from which the remains of the original bearing trees</p>



Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

## CHAINS

A ponderosa pine, 38 ins. diam., bears N. 71° E.,  
114 lks. dist., mkd. TXXIN R.

A partially burned pine stump, 24 ins. diam.,  
bears S. 47° E., 83 lks. dist.

A pine stump, 28 ins. diam., bears S. 10° W.,  
44 lks. dist.

A pine stump, 24 ins. diam., bears N. 45½° W.,  
133 lks. dist. (Record bearing N. 43° W.)

At the cor. pt.

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in  
the ground, mound of stone, 3 ft. base to top, with brass  
cap mkd.

T21N R6E

S 4 | S 3

S 9 | S10

1975

from which new bearing trees

A ponderosa pine, 7 ins. diam., bears N. 51¼° E.,  
161 lks. dist.; mkd. T21N R6E S3 BT.

A ponderosa pine, 8 ins. diam., bears S. 63½° E.,  
106 lks. dist., mkd. T21N R6E S10 BT.

A ponderosa pine, 7 ins. diam., bears S. 7 3/4° W.,  
193 lks. dist., mkd. T21N R6E S9 BT.

A ponderosa pine, 4 ins. diam., bears N. 33° W.,  
45 lks. dist., mkd. T21N R6E S4 BT.

Land, gently rolling.

Soil, clay loam and rocky.

Timber, pine

Undergrowth, young pine and native grasses.

From the cor. of secs. 2, 3, 10 and 11.

N. 89°58' W., bet. secs. 3 and 10.

Over gently rolling land, through medium to dense timber.

4.80 Fence, bears S. 25° E. and N. 25° W.

20.04 Pt. for the E 1/16 sec. cor. of secs. 3 and 10.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in  
the ground, with brass cap mkd.

T21N R6E

E 1/16 — S 3

S10

1975

from which

Dependent Resurvey of a Portion of the Subdivisional  
Lines, Township 21 North, Range 6 East,  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>A ponderosa pine, 8 ins. diam., bears S. 17½° E., 40 lks. dist., mkd. E 1/16 S10 BT.</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>	
23.30	<p>Track road, bears N. 60° E. and S. 60° W.</p>	
40.08	<p>The ¼ sec. cor. of secs. 3 and 10, monumented with a re- bar, 3/8 in. diam., set in a mound of stone, 2½ ft. base, 6 ins. high; a tag attached to the re-bar is mkd. L.S. 2473, from which the original bearing trees</p>	
	<p>A ponderosa pine, 40 ins. diam., bears S. 67° E., 49 lks. dist., mkd. ¼ S. (Record dist. 50 lks.)</p>	
	<p>A pine stump, 24 ins. diam., bears N. 72° W., 71 lks. dist. (Record dist. 67 lks.)</p>	
	<p>At the cor. pt.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T21N R6E ¼ <math>\frac{S\ 3}{S10}</math> 1975</p>	
	<p>from which new bearing trees</p>	
	<p>A ponderosa pine, 6 ins. diam., bears S. 17° E., 44 lks. dist., mkd. ¼ S10 BT.</p>	
	<p>A ponderosa pine, 10 ins. diam., bears N. 33° W., 30 lks. dist., mkd. T21N R6E S3 ¼ BT.</p>	
	<p>Reset the re-bar alongside the iron post.</p>	
	<p style="text-align: center;">_____</p> <p>S. 89°39' W., beginning new measurement.</p>	
9.30	<p>Track road, bears N. 15° E. and S. 15° W.</p>	
40.23	<p>The cor. of secs. 3, 4, 9 and 10.</p>	
	<p>Land, gently rolling. Soil, clay loam and rocky. Timber, pine. Undergrowth, young pine and native grasses.</p>	
	<p style="text-align: center;">Subdivision of Section 10, T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona</p>	
	<p style="text-align: center;">_____</p> <p>From the ¼ sec. cor. of secs. 10 and 15.</p>	
	<p>N. 0°06'30" W., on the N and S center line of sec. 10.</p>	
	<p>Over gently rolling land, through dense timber.</p>	

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

- 13.00 Track road, bears N. 75° E. and S. 75° W.
- 19.98 Pt. for the center S 1/16 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
- C  
S 1/16 | S10  
C  
1975
- from which
- A ponderosa pine, 9 ins. diam., bears N. 73½° E.,  
13.5 lks. dist., mkd. C-S 1/16 S10 BT.
- A ponderosa pine, 9 ins. diam., bears N. 10° W.,  
20.5 lks. dist., mkd. C-S 1/16 S10 BT.
- 22.90 Fence, bears N. 35° E. and S. 35° W.
- 29.97 Pt. for the center N-S 1/64 sec. cor. of sec. 10, not monumented.
- 34.965 Pt. for the center N-N-S 1/256 sec. cor. of sec. 10, not monumented.
- 39.96 Pt. for the center ¼ sec. cor. of sec. 10, at intersection with the E and W center line of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T21N R6E  
C¼ S10  
1975
- from which
- A ponderosa pine, 5 ins. diam., bears S. 41° E.,  
16 lks. dist., mkd. C¼ S10 BT.
- A ponderosa pine, 8 ins. diam., bears N. 50° W.,  
33.5 lks. dist., mkd. C¼ S10 BT.
- Raise a mound of stone, 4½ ft. base, 1½ ft. high, W of the cor.
- 45.015 Pt. for the center S-S-N 1/256 sec. cor. of sec. 10, not monumented.
- 50.07 Pt. for the center S-N 1/64 sec. cor. of sec. 10, not monumented.
- 60.18 Pt. for the center N 1/16 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
- C  
N 1/16 | S10  
C  
1975

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 29½° E., 22 lks. dist., mkd. C-N 1/16 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N. 52° W., 32 lks. dist., mkd. C-N 1/16 S10 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
65.25	Track road, bears N. 55° E. and S. 55° W.
80.40	The ¼ sec. cor. of secs. 3 and 10.
	<p>From the ¼ sec. cor. of secs. 10 and 11.</p> <p>N. 89°55' W., on the E and W center line of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
.15	Fence, bears irregularly N and S.
4.985	Pt. for the center E-E-E 1/256 sec. cor. of sec. 10.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-E-E-E 1/256 1975</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 19½° E., 36 lks. dist., mkd. C-E-E-E 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 1° W., 32 lks. dist., mkd. C-E-E-E 1/256 S10 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p>
7.00	Fence, bears S. 60° E. and N. 60° W.; enter open grass land, edge bears S. 60° E. and N. 60° W.
9.97	Pt. for the center E-E 1/64 sec. cor. of sec. 10; not monumented.
14.955	Pt. for the center W-E-E 1/256 sec. cor. of sec. 10; not monumented.
19.94	Pt. for the center E 1/16 sec. cor. of sec. 10; not monumented.
24.925	Pt. for the center E-W-E 1/256 sec. cor. of sec. 10; not monumented.
29.70	Fence, bears N. 50° E. and S. 50° W.; enter dense timber, edge bears N. 50° E. and S. 50° W.
29.91	Pt. for the center W-E 1/64 sec. cor. of sec. 10, not monumented.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

- 34.895 Pt. for the center W-W-E 1/256 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
- S10  
C-W-W-E  
1/256  
1975
- from which
- A ponderosa pine, 10 ins. diam., bears N. 58° E.,  
35.5 lks. dist., mkd. C-W-W-E 1/256 S10 BT.
- A ponderosa pine, 8 ins. diam., bears S. 47° W.,  
13 lks. dist., mkd. C-W-W-E 1/256 S10 BT.
- Raise a mound of stone, 3½ ft. base, 1 ft. high, N of the cor.
- 39.88 The center ¼ sec. cor. of sec. 10.
- 55.70 Track road, bears N. 25° E. and S. 25° W.
- 80.13 The ¼ sec. cor. of secs. 9 and 10.

NE¼, Section 10

---

- From the pt. for the center E 1/16 sec. cor. of sec. 10.  
North, on the N and S center line of the NE¼ of sec. 10.  
Over gently rolling open grass land.
- 5.06 Pt. for the center S-S-NE 1/256 sec. cor. of sec. 10;  
not monumented.
- 10.12 Pt. for the center S-NE 1/64 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
- S10  
C-S-NE  
1/64  
1975
- from which
- A ponderosa pine, 15 ins. diam., bears S. 87½° W.,  
125 lks. dist., mkd. C-S-NE 1/64 S10 BT.
- Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.
- 18.50 Enter dense timber, edge bears S. 80° E. and N. 80° W.
- 19.70 Fence, bears S. 60° E. and N. 60° W.
- 20.24 Pt. for the NE 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the NE¼ of sec. 10.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S10 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 8½° E., 18 lks. dist., mkd. NE 1/16 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 60½° W., 24 lks. dist., mkd. NE 1/16 S10 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of the cor.</p>	
40.48	<p>The E 1/16 sec. cor. of secs. 3 and 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>N. 89°56'30" W., on the E and W center line of the NE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>	
.60	Fence, bears N and S 50 lks. dist. to a fence cor.; fences extend N, S and N. 80° W.	
1.70	Fence, bears S. 80° E. and N. 80° W.	
5.00	Fence, bears N. 55° E. and S. 55° W.	
10.00	Pt. for the center E-NE 1/64 sec. cor. of sec. 10; not monumented.	
20.00	The NE 1/16 sec. cor. of sec. 10.	
24.995	<p>Pt. for the center E-W-NE 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-E-W-NE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 50½° E., 65 lks. dist., mkd. C-E-W-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 12° W., 6 lks. dist., mkd. C-E-W-NE 1/256 S10 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>	
29.99	Pt. for the center W-NE 1/64 sec. cor. of sec. 10, not monumented.	

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.98	<p>The center N 1/16 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the pt. for the center E-E 1/64 sec. cor. of sec. 10.</p> <p>N. 0°04' E., on the N and S center line of the SE¼ of the NE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
2.60	Fence, bears SE and NW.
5.06	<p>Pt. for the center S-SE-NE 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-S-SE-NE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 34° E., 35 lks. dist., mkd. C-S-SE-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 4 ins. diam., bears S. 75° W., 17.5 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of the cor.</p>
10.12	Pt. for the SE-NE 1/64 sec. cor. of sec. 10, at intersection with the E and W center line of the SE¼ of the NE¼ of sec. 10; not monumented.
18.00	Fence, bears E and W.
20.24	<p>The pt. for the center E-NE 1/64 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the pt. for the S-N 1/64 sec. cor. of secs. 10 and 11.</p> <p>N. 89°55' W., on the E and W center line of the SE¼ of the NE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
4.995	Pt. for the center E-SE-NE 1/256 sec. cor. of sec. 10; not monumented.
9.99	The pt. for the SE-NE 1/64 sec. cor. of sec. 10.
14.63	Fence, bears S. 30° E. and N. 30° W.; enter open grass land, edge bears S. 30° E. and N. 30° W.
14.985	<p>Pt. for the center W-SE-NE 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">S10 C-W-SE-NE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 55° E., 21 lks. dist., mkd. C-W-SE-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 22° E., 38.5 lks. dist., mkd. C-W-SE-NE 1/256 S10 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N of the cor.</p> <p>The cor. is at the N edge of a pine stump, projecting 3 ft. above ground.</p>
19.98	<p>The center S-NE 1/64 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-E-E 1/256 sec. cor. of sec. 10.</p> <p>N. 0°05'30" E., on the N and S center line of the SE¼ of the SE¼ of the NE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
5.06	<p>Pt. for the SE-SE-NE 1/256 sec. cor. of sec. 10, at intersection with the E and W center line of the SE¼ of the SE¼ of the NE¼ of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground and in a collar of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S10 SE-SE-NE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 55° E., 60 lks. dist., mkd. SE-SE-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 53° W., 45.5 lks. dist., mkd. SE-SE-NE 1/256 S10 BT.</p>
10.12	<p>The pt. for the center E-SE-NE 1/256 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the pt. for the S-S-N 1/256 sec. cor. of secs. 10 and 11.</p> <p>N. 89°55' W., on the E and W center line of the SE¼ of the SE¼ of the NE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
.95	<p>Fence, bears N and S.</p>



Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

- 4.99 The SE-SE-NE 1/256 sec. cor. of sec. 10.
- 9.98 The center S-SE-NE 1/256 sec. cor. of sec. 10.
- 
- From the pt. for the center W-E-E 1/256 sec. cor. of sec. 10.
- N. 0°02' E., on the N and S center line of the SW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.
- Over gently rolling open grass land.
- 5.06 Pt. for the SW-SE-NE 1/256 sec. cor. of sec. 10, at intersection with the E and W center line of the SW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 16 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
- S10  
SW-SE-NE  
1/256  
1975
- from which
- A ponderosa pine, 8 ins. diam., bears N. 15° E.,  
82 lks. dist., mkd. SW-SE-NE 1/256 S10 BT.
- A ponderosa pine, 12 ins. diam., bears S. 69° E.,  
154 lks. dist., mkd. SW-SE-NE 1/256 S10 BT.
- 10.12 The center W-SE-NE 1/256 sec. cor. of sec. 10.
- 
- From the center S-SE-NE 1/256 sec. cor. of sec. 10.
- N. 89°55' W., on the E and W center line of the SW $\frac{1}{4}$  of the SE $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.
- Over gently rolling land, through dense timber.
- 2.00 Fence, bears S. 30° E. and N. 30° W.; enter open grass land, edge bears S. 30° E. and N. 30° W.
- 4.99 The SW-SE-NE 1/256 sec. cor. of sec. 10.
- 9.98 The pt. for the center S-S-NE 1/256 sec. cor. of sec. 10.
- 
- From the pt. for the center W-E 1/64 sec. cor. of sec. 10.
- N. 0°03'30" W., on the N and S center line of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.
- Over gently rolling land, through dense timber.
- 5.06 Pt. for the center S-SW-NE 1/256 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">S10 C-S-SW-NE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 70½° E., 9.5 lks. dist., mkd. C-S-SW-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 27° W., 13 lks. dist., mkd. C-S-SW-NE 1/256 S10 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.</p>
10.12	Pt. for the SW-NE 1/64 sec. cor. of sec. 10, at intersection with the E and W center line of the SW¼ of the NE¼ of sec. 10; not monumented.
20.23	<p>The pt. for the center W-NE 1/64 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S-NE 1/64 sec. cor. of sec. 10.</p> <p>N. 89°55' W., on the E and W center line of the SW¼ of the NE¼ of sec. 10.</p> <p>Over rolling land, through medium timber.</p>
3.20	Fence, bears S. 25° E. and N. 25° W.; enter dense timber, edge bears S. 25° E. and N. 25° W.
4.99	<p>Pt. for the center E-SW-NE 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-E-SW-NE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 9° E., 18 lks. dist., mkd. C-E-SW-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 76° E., 17.5 lks. dist., mkd. C-E-SW-NE 1/256 S10 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N of the cor.</p>
9.98	The pt. for the SW-NE 1/64 sec. cor. of sec. 10.
14.97	Pt. for the center W-SW-NE 1/256 sec. cor. of sec. 10; not monumented.
19.96	<p>The pt. for the center S-N 1/64 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the pt. for the center E-W-E 1/256 sec. cor. of sec. 10.</p>

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

N.  $0^{\circ}02'$  W., on the N and S center line of the SE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.

Over gently rolling open grass land.

4.30 Fence, bears N.  $50^{\circ}$  E. and S.  $50^{\circ}$  W.; enter dense timber, edge bears N.  $50^{\circ}$  E. and S.  $50^{\circ}$  W.

5.06 Pt. for the SE-SW-NE 1/256 sec. cor. of sec. 10, at intersection with the E and W center line of the SE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, mound of stone,  $2\frac{1}{2}$  ft. base to top, with brass cap mkd.

S10  
SE-SW-NE  
1/256  
1975

from which

A ponderosa pine, 9 ins. diam., bears S.  $49^{\circ}$  E.,  
29.5 lks. dist., mkd. SE-SW-NE 1/256 S10 BT.

A ponderosa pine, 9 ins. diam., bears S.  $60^{\circ}$  W.,  
26.5 lks. dist., mkd. SE-SW-NE 1/256 S10 BT.

10.12 The center E-SW-NE 1/256 sec. cor. of sec. 10.

From the pt. for the center S-S-NE 1/256 sec. cor. of sec. 10.

N.  $89^{\circ}55'$  W., on the E and W center line of the SE $\frac{1}{4}$  of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.

Over gently rolling open grass land.

4.30 Fence, bears N.  $15^{\circ}$  E. and S.  $15^{\circ}$  W.; enter dense timber, edge bears N.  $15^{\circ}$  E. and S.  $15^{\circ}$  W.

4.985 The SE-SW-NE 1/256 sec. cor. of sec. 10.

9.975 The center S-SW-NE 1/256 sec. cor. of sec. 10.

From the center W-W-E 1/256 sec. cor. of sec. 10.

N.  $0^{\circ}05'$  W., on the N and S center line of the SW $\frac{1}{4}$  of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.

Over gently rolling land, through dense timber.

5.06 Pt. for the SW-SW-NE 1/256 sec. cor. of sec. 10, at intersection with the E and W center line of the SW $\frac{1}{4}$  of the SW $\frac{1}{4}$  of the NE $\frac{1}{4}$  of sec. 10.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 19 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>S10 SW-SW-NE 1/256 1975</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 35° E., 37 lks. dist., mkd. SW-SW-NE 1/256 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 5° W., 44 lks. dist., mkd. SW-SW-NE 1/256 S10 BT.</p>
10.12	<p>The pt. for the center W-SW-NE 1/256 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center S-SW-NE 1/256 sec. cor. of sec. 10.</p> <p>N. 89°55' W., on the E and W center line of the SW¼ of the SW¼ of the NE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
4.985	The SW-SW-NE 1/256 sec. cor. of sec. 10.
9.97	The pt. for the center S-S-N 1/256 sec. cor. of sec. 10.
	<p>SE¼, Section 10</p> <hr style="width: 20%; margin: 10px auto;"/>
	<p>From the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>N. 0°08' W., on the N and S center line of the SE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
19.91	<p>Pt. for the SE 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the SE¼ of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over an X chiseled in solid rock, mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p>SE 1/16 S10 1975</p>
	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 58° E., 12 lks. dist., mkd. SE 1/16 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears N. 42½° W., 36 lks. dist., mkd. SE 1/16 S10 BT.</p>
23.20	Track road, bears S. 55° E. and N. 55° W.
23.80	Fence, bears E and W.
28.20	Enter open grass land, edge bears S. 55° E. and N. 55° W.
29.86	Pt. for the center N-SE 1/64 sec. cor. of sec. 10.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

S10  
C-N-SE  
1/64  
1975

from which

A ponderosa pine, 12 ins. diam., bears S. 14½° E., 183 lks. dist., mkd. C-N-SE 1/64 S10 BT.

A ponderosa pine, 8 ins. diam., bears S. 81° W., 197 lks. dist., mkd. C-N-SE 1/64 S10 BT.

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.

39.81 The pt. for the center E 1/16 sec. cor. of sec. 10.

From the S 1/16 sec. cor. of secs. 10 and 11.

S. 89°52' W., on the E and W center line of the SE¼ of sec. 10.

Over gently rolling land, through dense timber.

4.99 Pt. for the center E-E-SE 1/256 sec. cor. of sec. 10, not monumented.

7.00 Track road, bears N. 5° E. and S. 5° W.

7.40 Fence, bears S. 50° E. and N. 50° W.

9.98 Pt. for the center E-SE 1/64 sec. cor. of sec. 10.

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.

S10  
C-E-SE  
1/64  
1975

from which

A ponderosa pine, 10 ins. diam., bears S. 30° E., 29 lks. dist., mkd. C-E-SE 1/64 S10 BT.

A ponderosa pine, 6 ins. diam., bears N. 4° W., 10 lks. dist., mkd. C-E-SE 1/64 S10 BT.

12.60 Abandoned track road, bears N. 30° E. and S. 30° W.

13.00 Draw, drains S. 25° W.

14.97 Pt. for the center W-E-SE 1/256 sec. cor. of sec. 10.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 1½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S10 C-W-E-SE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 16° E., 9 lks. dist., mkd. C-W-E-SE 1/256 S 10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 55° W., 13.5 lks. dist., mkd. C-W-E-SE 1/256 S10 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of the cor.</p>
19.96	The SE 1/16 sec. cor. of sec. 10.
26.50	Track road, bears NE and SW.
29.935	Pt. for the center W-SE 1/64 sec. cor. of sec. 10, not monumented.
39.91	The center S 1/16 sec. cor. of sec. 10.
	_____
	<p>From the center E-SE 1/64 sec. cor. of sec. 10.</p> <p>N. 0°08' W., on the N and S center line of the NE¼ of the SE¼ of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
1.60	Fence, bears SE and NW; enter open grass land, edge bears SE and NW.
2.00	Track road, bears S. 80° W. and N. 80° E. curving North-erly.
3.90	Fence, bears N. 55° E. and S. 55° W.
4.965	Pt. for the center S-NE-SE 1/256 sec. cor. of sec. 10.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-S-NE-SE 1/256 1975</p> <p>from which</p> <p style="padding-left: 40px;">The NW cor. of a burned block house, 50 x 38 ft., bears S. 77 ¾° E., 81 lks. dist., long side bears N. 40° E. and S. 40° W.</p> <p style="padding-left: 40px;">A propane tank, 500 gallon capacity, bears S. 48 ¾° E., 325 lks. dist.</p> <p style="padding-left: 40px;">The NW cor. of a water pump house, 11 ft. square, bears S. 36½° E., 427 lks. dist., one side bears S. 35° E.</p>

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

## CHAINS

- Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.
- 5.50 Fence, bears S. 60° E. and N. 60° W.
- 9.70 Fence, bears S. 75° E. and N. 75° W.
- 9.93 Pt. for the NE-SE 1/64 sec. cor. of sec. 10, at intersection with the E and W center line of the NE¼ of the SE¼ of sec. 10; not monumented.
- 19.865 The pt. for the center E-E 1/64 sec. cor. of sec. 10.
- From the N-S 1/64 sec. cor. of secs. 10 and 11.
- West, on the E and W center line of the NE¼ of the SE¼ of sec. 10.
- Over gently rolling land, through dense timber.
- 4.70 Track road, bears N. 70° E. and S. 70° W.; enter open grass land, edge bears NE and SW.
- 4.99 Pt. for the center E-NE-SE 1/256 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- S10  
C-E-NE-SE  
1/256  
1975
- from which
- A ponderosa pine, 12 ins. diam., bears N. 51° E.,  
63 lks. dist., mkd. C-E-NE-SE 1/256 S10 BT.
- A ponderosa pine, 8 ins. diam., bears S. 3° E.,  
121.5 lks. dist., mkd. C-E-NE-SE 1/256 S10 BT.
- Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.
- 9.98 The pt. for the NE-SE 1/64 sec. cor. of sec. 10.
- 14.965 Pt. for the center W-NE-SE 1/256 sec. cor. of sec. 10.
- Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, 3 ft. base to top, with brass cap mkd.
- S10  
C-W-NE-SE  
1/256  
1975
- from which
- A ponderosa pine, 11 ins. diam., bears S. 8° E.,  
202 lks. dist., mkd. C-W-NE-SE 1/256 S10 BT.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A ponderosa pine, 12 ins. diam., bears S. 40° W., 236 lks. dist., mkd. C-W-NE-SE 1/256 S10 BT.</p>
19.95	<p>The center N-SE 1/64 sec. cor. of sec. 10.</p> <hr/> <p>From the pt. for the center E-E-SE 1/256 sec. cor. of sec. 10.</p> <p>N. 0°08' W., on the N and S center line of the SE<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
4.96	<p>Pt. for the SE-NE-SE 1/256 sec. cor. of sec. 10, at in- tersection with the E and W center line of the SE<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 16 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S10 SE-NE-SE 1/256 1975</p> <p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears N. 46° E., 30.5 lks. dist., mkd. SE-NE-SE 1/256 S10 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 43° E., 42.5 lks. dist., mkd. SE-NE-SE 1/256 S10 BT.</p>
9.80	<p>Track road, bears N. 70° E. and S. 70° W.</p>
9.92	<p>The center E-NE-SE 1/256 sec. cor. of sec. 10.</p> <hr/> <p>From the pt. for the S-N-S 1/256 sec. cor. of secs. 10 and 11.</p> <p>S. 89°56' W., on the E and W center line of the SE<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>
4.99	<p>The SE-NE-SE 1/256 sec. cor. of sec. 10.</p>
5.70	<p>Track road, bears N and S.</p>
7.40	<p>Graded gravel road, bears S. 5° E. and N. 5° W.</p>
9.98	<p>The center S-NE-SE 1/256 sec. cor. of sec. 10.</p> <hr/> <p>From the pt. for the center W-SE 1/64 sec. cor. of sec. 10.</p> <p>N. 0°07'30" W., on the N and S center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of sec. 10.</p> <p>Over gently rolling land, through dense timber.</p>



Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
3.90	Fence, bears S. 30° E. and N. 30° W.
9.20	Fence, bears N. 25° E. and S. 25° W.
9.98	Pt. for the NW-SE 1/64 sec. cor. of sec. 10, at intersection with the E and W center line of the NW $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 10.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.
	S10 NW-SE 1/64 1975
	from which
	A ponderosa pine, 7 ins. diam., bears N. 85° E., 60 lks. dist., mkd. NW-SE 1/64 S10 BT.
	A ponderosa pine, 10 ins. diam., bears S. 17° W., 24 lks. dist., mkd. NW-SE 1/64 S10 BT.
14.965	Pt. for the center N-NW-SE 1/256 sec. cor. of sec. 10.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S10 C-N-NW-SE 1/256 1975
	from which
	A ponderosa pine, 13 ins. diam., bears S. 72° E., 43 lks. dist., mkd. C-N-NW-SE 1/256 S10 BT.
	A ponderosa pine, 14 ins. diam., bears S. 52° W., 111.5 lks. dist., mkd. C-N-NW-SE 1/256 S10 BT.
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 ft. high, W of the cor.
16.50	Fence, bears S. 30° E. and N. 30° W.; enter open grass land, edge bears S. 30° E. and N. 30° W.
19.70	Fence, bears N. 50° E. and S. 50° W.
19.95	The pt. for the center W-E 1/64 sec. cor. of sec. 10.
	From the center N-SE 1/64 sec. cor. of sec. 10.
	S. 89°59' W., on the E and W center line of the NW $\frac{1}{4}$ of the SE $\frac{1}{4}$ of sec. 10.
	Over gently rolling open grass land.
5.00	Enter dense timber, edge bears S. 60° E. and N. 60° W.

Subdivision of Section 10,  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
9.50	Fence, bears N. 25° E. and S. 25° W.
9.975	The NW-SE 1/64 sec. cor. of sec. 10.
14.96	Pt. for the center W-NW-SE 1/256 sec. cor. of sec. 10; not monumented.
15.10	Fence, bears N. 30° E. and S. 30° W.
19.945	The pt. for the center N-S 1/64 sec. cor. of sec. 10.
	_____
	From the pt. for the center W-NW-SE 1/256 sec. cor. of sec. 10.
	N. 0°07' W., on the N and S center line of the NW¼ of the NW¼ of the SE¼ of sec. 10.
	Over gently rolling land, through dense timber.
.30	Fence, bears N. 30° E. and S. 30° W.
4.995	Pt. for the NW-NW-SE 1/256 sec. cor. of sec. 10, at intersection with the E and W center line of the NW¼ of the NW¼ of the SE¼ of sec. 10.
	Set an iron post, 28 ins. long, 2½ ins. diam., over an X chiseled in solid rock, mound of stone, 4½ ft. base to top, with brass cap mkd.
	S10 NW-NW-SE 1/256 1975
	from which
	A ponderosa pine, 4 ins. diam., bears N. 58° E., 35.5 lks. dist., mkd. X at breast height and BT at the base.
	A ponderosa pine, 8 ins. diam., bears S. 38° W., 41.5 lks. dist., mkd. NW-NW-SE 1/256 S10 BT.
9.99	The center W-W-E 1/256 sec. cor. of sec. 10.
	_____
	From the center N-NW-SE 1/256 sec. cor. of sec. 10.
	N. 89°58' W., on the E and W center line of the NW¼ of the NW¼ of the SE¼ of sec. 10.
	Over gently rolling land, through dense timber.
2.60	Fence, bears N. 25° E. and S. 25° W.
4.99	The NW-NW-SE 1/256 sec. cor. of sec. 10.
9.98	The pt. for the center N-N-S 1/256 sec. cor. of sec. 10.

General Description  
T. 21 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS

## GENERAL DESCRIPTION

The land encompassed in this survey is located about 4.5 miles west of Flagstaff, Arizona. The terrain is gently rolling, covered with dense ponderosa pine, except for an open meadow located in the center of the E $\frac{1}{2}$  of Section 10; this meadow abounds with native grasses for grazing. The soil is clay loam and rocky. Elevation ranges from 7,500 feet above sea level in the northeast  $\frac{1}{4}$  to 7,340 feet above sea level in the southeast  $\frac{1}{4}$ , with southerly drainage.

The only residents in the area surveyed are located in the southeast  $\frac{1}{4}$  of Section 10, which is furnished access by a graded gravel road. Track roads in the area furnish further access.

An average number of readings throughout Section 10 gives a mean magnetic declination of 14°30' E., with no noticeable difference due to local attraction.

CHAINS		



CERTIFICATE OF SURVEY

(I) ~~(We)~~, Harry K. Smith, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 29th day of August, 1975, (I) ~~(We)~~ have dependently resurveyed a portion of the subdivisional lines and subdivided Section 10, Township 21 North, Range 6 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(We)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 16, 1976  
(Date)

Harry K. Smith  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and the subdivision of Section 10, Township 21 North, Range 6 East, of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUL 27 1977  
(Date)

Bernard W. Johnson  
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626



