

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the  
 \_\_\_\_\_  
 Dependent Resurvey  
 \_\_\_\_\_  
 of a  
 \_\_\_\_\_  
 Portion of the First Standard Parallel South  
 \_\_\_\_\_  
 through Ranges 24 and 25 East  
 \_\_\_\_\_  
 Retracement of a Portion of the South Boundary  
 \_\_\_\_\_  
 and Dependent Resurvey of a  
 \_\_\_\_\_  
 Portion of the East Boundary  
 \_\_\_\_\_  
 and  
 \_\_\_\_\_  
 Subdivisional Lines  
 \_\_\_\_\_  
 and  
 \_\_\_\_\_  
 Survey of Subdivisions in Sections  
 \_\_\_\_\_  
 6, 8, 9, 15, 23, 25 and 26  
 \_\_\_\_\_  
 Township 6 South, Range 25 East  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Of the Gila and Salt River Meridian,  
 In the State of Arizona

EXECUTED BY

Paul L. Reeves Cadastral Surveyor  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

Under special instructions dated November 22, 1976, approved November 23, 1976,

\_\_\_\_\_, which provided for the surveys included under ~~U.S. Survey~~/Group  
 Number 592, and assignment instructions dated November 23, 1976.

Survey commenced November 30, 1976

Survey completed February 1, 1977

1A

BOOK 5040

INDEX DIAGRAM

Township 6 South, Range 25 East

3		1			
6 25 24	5 23	4 21	8	2	1
7 22	8 20 22	9 18 19	10 17	11	12
18	17 20	16 16	15 14 15	14 13 9	13 9
19	20	21	22 13	23 8 11	24 7
30	29	28	27 11	26 6 10	25 5 4
31	32	33	34	35 6 4	36 4

Subdivision	Section 6	Pages	27-33
"	"	8	" 33-36
"	"	9	" 37-38
"	"	15	" 38-42
"	"	23	" 42-44
"	"	25	" 44-48
"	"	26	" 48-51

Township 6 South, Range 25 East  
Gila and Salt River Meridian, Arizona

## CHAINS

The exterior boundaries and subdivisional lines were surveyed in 1875 by Theodore F. White. The north boundary was resurveyed in 1920 - 21 by William H. Thorn and Benjamin J. Kinsey. The east boundary was resurveyed in 1895 - 96 by Philip Contzen. The west boundary and a portion of the south boundary was resurveyed in 1916 by Albert B. Rich. The east boundary was resurveyed in 1960 by Dell Cazier, Glen B. Hatch and Eldon W. Sibley. A portion of the south boundary was resurveyed in 1964 - 70 by Paul G. Bauer and Leonard Murphy. A portion of the south boundary was retraced and a portion resurveyed in 1966 by Paul G. Bauer and Robert F. Johnson. A portion of the subdivisional lines were resurveyed and sections 21 and 22 were subdivided in 1964 - 70 by Leonard Murphy and Paul G. Bauer. A portion of the west boundary was resurveyed in 1964 - 72 by Leonard Murphy, Frank Rogers and Paul G. Bauer.

The following field notes are those of a dependent resurvey of a portion of the First Standard Parallel South through ranges 24 and 25 East; a retracement of a portion of the south boundary; a dependent resurvey of a portion of the east boundary and subdivisional lines and survey of subdivisions in sections 6, 8, 9, 15, 23, 25 and 26, Township 6 South, Range 25 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions 1973, and the special instructions for Group No. 592, Arizona dated November 22, 1976.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions; lost corners were reestablished at proportionate positions but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of section 25, as scaled from the U. S. Geological Survey Quadrangle Map, "Safford, Arizona", prepared in 1960, is as follows:

Latitude  $32^{\circ}52.5'$  N. Longitude  $109^{\circ}43.9'$  W.

The mean magnetic declination is  $13^{\circ}30'$  E.

Dependent Resurvey of a Portion of the First Standard Parallel South, through Range 25 East, Gila and Salt River Meridian, Arizona.  
(Restoring the 1920-21 resurvey by William H. Thorn and Benjamin J. Kinsey)

Beginning at the standard corner of secs. 31 and 32, monumented with an iron post 2 ins. diam., firmly set projecting 12 ins. above the ground, in a mound of

Dependent Resurvey of a Portion of the First Standard  
Parallel South, through Range 25 East,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">SC T5S R25E   S31 S32 ----- 1920</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, N. of cor. N. 89°54' W., on the S. bdy. of sec. 31.</p> <p>Across washed area, through medium undergrowth and scattered timber.</p>
10.00	Peck Wash, 2 chs. wide, 3 ft. deep, drains S. 15° E.
20.00	West rim of canyon, bears S. 30° E. and N. 30° W.
22.90	East rim of canyon, bears NE and SW.
29.34	Point for the closing cor. of secs. 5 and 6, hereinafter described.
31.80	Bottom of canyon, drains S. 15° W.
39.21	The original standard ¼ sec. cor. of sec. 31, (now an angle point) monumented with an iron post, 1 inch in diam., firmly set projecting 12 ins. above the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.
	<p>A P 1920</p> <hr style="width: 10%; margin: auto;"/>
	S. 89°47' W., beginning new measurement.
0.10	West rim of canyon, bears N. 15° E. and S. 15° W.
0.70	The standard ¼ sec. cor. of sec. 31, monumented with an iron post, 1 inch in diam., firmly set in a mound of stone, 3 ft. base, 2½ ft. high, with brass cap mkd.
	<p>SC ¼ S31 ----- 1920</p>
12.30	Track road, bears N. 25° E. and S. 25° W.
15.70	East rim of canyon, bears N. 30° E. and S. 30° W.
29.10	Bottom of canyon, drains southerly.
30.08	Point for the ¼ sec. cor. of sec. 6, at proportionate dist.
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p>T5S R25E  ----- ¼ S6 T6S R25E 1977</p>

Dependent Resurvey of a Portion of the First Standard  
Parallel South, through Range 25 East,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, S. of cor.</p>
	<p>Cor. is located at the base of canyon wall.</p>
38.80	<p>West rim of canyon, bears N. 30° E. and S. 30° W.</p>
40.00	<p>The Standard township corner of secs. 31 and 36, Tps. 5 S., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set, projecting 18 ins. above ground, in a mound of stone, 3½ ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">SC T 5 S R24E R25E <u>S36 S31</u> 1916</p>
	<p>Cor. is located 2 lks. E. of N. and S. fence line.</p>
<p>Dependent Resurvey of a Portion of the First Standard Parallel South, through Range 24 East, Gila and Salt River Meridian, Arizona. (Restoring the 1916 resurvey by A. B. Rich)</p>	
	<p>N. 89°46' W., on the S bdy. of sec. 36.</p>
	<p>Over rolling land, through medium undergrowth.</p>
19.89	<p>Point for the standard E 1/16 sec. cor. of sec. 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">SC T5S R24E <u>E 1/16 S36</u> 1977</p>
	<p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of cor.</p>
27.54	<p>The closing cor. of secs. 1 and 6, Tps. 6 S., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, 2½ ft. base, 1½ ft. high, with brass cap mkd.</p>
	<p style="text-align: center;">T5S R24E <u>S36</u> <u>S1 S6</u> R24E R25E T6S CC 1916</p>
39.79	<p>The standard ¼ sec. cor. of sec. 36, monumented with an iron post, 1 inch diam., firmly set, projecting 12 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SC <u>¼ S36</u> 1916</p>
	<p>Mound of stone, 2½ ft. base, 1 ft. high N of cor.</p>

Retracement of a Portion of the South Boundary,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	<p>Retracement of a Portion of the South Boundary T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona Retracing the 1966 resurvey and retracement by Paul G. Bauer and Robert F. Johnson</p>
	<p>From the E 1/16 sec. cor. of secs. 1 and 36 on the S. bdy. of the Tp., monumented by an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E E 1/16 <math>\frac{S36}{S 1}</math> T7S 1966</p> <p>Topography is essentially the same as recorded in the 1966 resurvey.</p> <p>N. 89°53' W., bet. secs. 1 and 36.</p> <p>Over gently rolling land.</p> <p>19.90 Point for the ¼ sec. cor. of secs. 1 and 36 at proportionate dist.; there is no evidence of the cor. set in 1966; not monumented.</p> <p>20.58 Point for the meander cor. set in 1966; no monument found.</p> <p>59.70 Point for the cor. of secs. 1, 2, 35 and 36 at proportionate dist.; not monumented now or in 1966.</p>
	<p>N. 89°53' W., bet. secs. 2 and 35.</p> <p>Over rolling land.</p> <p>39.80 Point for the ¼ sec. cor. of secs. 2 and 35 at proportionate dist.; not monumented now or in 1966.</p> <p>79.60 The cor. of secs. 2, 3, 34 and 35, monumented by a local iron post, 2½ ins. diam., 3 ins. below surface of N and S paved road, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E <math>\frac{34 35}{3 2}</math> T7S R25E</p>
	<p>Dependent Resurvey of a Portion of the E. bdy. T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona. (Restoring the 1960 resurvey by Dell Cazier, Glen B. Hatch, and Eldon W. Sibley.)</p>
	<p>From the cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2½ ins. diam., firmly set, projecting 14 ins. above the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E R26E <math>\frac{S25 S30}{S36 S31}</math> 1960</p>

Dependent Resurvey of a Portion of the E. bdy. T. 6 S.,  
R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	North, bet. secs. 25 and 30.
	Over rolling land, through medium creosote.
9.955	Point for the S-S 1/64 sec. cor. of secs. 25 and 30; not monumented.
19.91	Point for the S 1/16 sec. cor. of secs. 25 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.
	T6S
	R25E R26E
	S 1/16
	S25 S30
	1976
39.82	The ¼ sec. cor. of secs. 25 and 30, monumented with an iron post, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.
	T6S
	R25E R26E
	¼
	S25 S30
	1960
	Land, rolling.
	Soil, stoney, sandy loam.
	Timber, none.
	Undergrowth, creosote and cacti.
Dependent Resurvey of a Portion of the Subdivisional	
Lines, T. 6 S., R. 25 E., Gila and Salt River Meridian,	
Arizona.	
(Restoring the 1875 survey by Theodore F. White)	
From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., heretofore described.	
N. 89°50' W., bet. secs. 25 and 36.	
Over level land, through medium creosote,	
3.10	Descend W. slope.
6.00	Enter nearly level land.
9.93	Point for the E-E 1/64 sec. cor. of secs. 25 and 36; not monumented.
11.67	From this point on line, fence cor. bears N, 3 lks, dist., fences extend S and W.
19.86	Point for the E 1/16 sec. cor. of secs. 25 and 36.
	Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	T6S R25E
	S25
	E 1/16 S36
	1976

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS		
	Fence cor. bears N. 79° W., 31 lks. dist., fences extend N., E. and W.	
24.60	Power line, bears S. 30° E. and N. 30° W.	
25.40	Fence cor., fences extend E., S. 30° E. and N. 30° W.	
26.00	Paved road, bears S. 30° E. and N. 30° W.	
26.50	Telephone line, bears S. 30° E. and N. 30° W.	
29.30	Power line, bears N. 60° E. and W.	
32.80	Graham Canal, 15 lks. wide, flows Northerly.	
39.72	Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.	
79.44	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.  From this point, the point for the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp. bears S. 0°16' W., 79.38 chs. dist. heretofore described.	
	N. 0°20' W., bet. secs. 25 and 26.  Along a graded road bet. cultivated fields.	
39.69	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.  Set an iron post, 28 ins. long, 2½ ins. diam., 7 ins. below surface of graded road, bears N. and S., with brass cap mkd.  T6S R25E ¼ S26 S25 1976	
	from which  An iron post, 28 ins. long, 2½ ins. diam. set 21 ins. in the ground, for a reference monument, bears N. 55° E., 71.2 lks. dist., with brass cap mkd. T6S R25E ¼ S25 RM 47 ft. 1976 and an arrow pointing to the cor.  A power pole bears S. 27°40' E., 36.2 lks. dist. (Has 3 transformers attached.)	
40.20	Graham canal, 15 lks. wide, flows SW, from E.	
43.30	Telephone line, bears S. 60° E. and N. 60° W.	
44.00	Paved road, bears S. 60° E. and N. 60° W.	
44.90	Power and fence lines, bear S. 60° E. and N. 60° W., thence over rolling land.	
59.535	Point for the N 1/16 sec. cor. of secs. 25 and 26,  Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.  T6S R25E N 1/16 S26 S25 1976	



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
63.60	Talley Wash, 1 ch. wide, 2 ft. deep, drains SW.
79.38	<p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below surface of a graded gravel road, bears N. 39° E. and S. 42° W., with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R25E  <math>\frac{S23}{S26}   \frac{S24}{S25}</math>                      1976</p> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 85° E., 83.3 lks. dist., with brass cap mkd. T6S R25E S24 RM 55 ft. 1976 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 85° W., 83.3 lks. dist., with brass cap mkd. T6S R25E S26 RM 55 ft. 1976 and an arrow pointing to the cor.</p> <p>Land, level to rolling.                      Soil, sandy loam.                      Timber, mesquite.                      Undergrowth, creosote, catclaw and cacti.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S                      R25E R26E  <math>\frac{S24}{S25}   \frac{S19}{S30}</math>                      1964</p> </div> <p>Mound of stone, 2½ ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 2 lks. E. of fence line, bears NE and SW, S. 89°59' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through medium creosote.</p>
1.00	Wash, 25 lks. wide, 3 ft. deep drains SW.
39.87	<p>The ¼ sec. cor. of secs. 24 and 25, monumented with a volcanic stone, 14x14x10 ins., firmly set, projecting 6 ins. above the ground, mkd. ¼ on NE face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R25E  <math>\frac{S24}{\frac{1}{4} S25}</math>                      1976</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
<p>29.70</p> <p>31.40</p> <p>37.10</p> <p>40.15</p>	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°49' W., beginning new measurement.</p> <p>Descend steep W slope.</p> <p>Enter dense mesquite, edge bears N. 30° E. and S. 30° W., thence over washed area.</p> <p>Talley Wash, 60 lks. wide, 2 ft. deep, drains southerly.</p> <p>The cor. of secs. 23, 24, 25 and 26.</p> <p>Land, rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, creosote, catclaw and cacti.</p>
<p>39.69</p> <p>35.30</p> <p>36.00</p> <p>40.09</p>	<p>N. 0°47' E., bet. secs. 23 and 24.</p> <p>Over rolling land, through medium creosote and mesquite.</p> <p>The ¼ sec. cor. of secs. 23 and 24, monumented with a volcanic stone 12x10x8 ins., firmly set, projecting 6 ins. above ground, mkd. ¼ on S face; a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6S R25E</p> <p>¼</p> <p>S23   S24</p> <p>1976</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°05' E., beginning new measurement.</p> <p>Track road, bears N. 25° E. and S. 25° W.</p> <p>Wash, 75 lks. wide, 4 ft. deep, drains S. 60° W., thence across washed area.</p> <p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T6S R25E</p> <p>S14   S13</p> <p>S23   S24</p> <p>1976</p> </div> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high W. of cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS

From this point the  $\frac{1}{4}$  sec. cor. of secs. 13 and 14 bears N.  $0^{\circ}06'$  E., 40.09 chs. dist., monumented with a volcanic stone, 16x10x8 ins. firmly set, projecting 8 ins. above ground, mkd.  $\frac{1}{4}$  on S face, in a mound of stone,  $2\frac{1}{2}$  ft. base, 1 ft. high.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T6S R25E  
 $\frac{1}{4}$   
S14 | S13  
1976

Rebuild the mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

Deposit the mkd. stone alongside the iron post.

Land, gently rolling.  
Soil, rocky, sandy loam.  
Timber, scattered mesquite.  
Undergrowth, creosote.

From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented with an iron post,  $2\frac{1}{2}$  ins. diam., firmly set, projecting 9 ins. above the ground, with brass cap mkd.

T6S  
T25E R26E  
S13 | S18  
S24 | S19  
1960

Mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of cor.

N.  $89^{\circ}59'$  W., bet. secs. 13 and 24.

Over gently rolling land, through medium creosote and mesquite.

39.77

Point for the  $\frac{1}{4}$  sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 18 ins. in the ground, with brass cap mkd.

T6S R25E  
 $\frac{1}{4}$  S13  
S24  
1976

Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
69.90	Watson Wash, 50 lks. wide, 4 ft. deep, drains S. 85° E., from NE, thence across washed area.
79.54	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, gently rolling. Soil, rocky sandy loam. Timber, mesquite. Undergrowth, creosote, catclaw and cacti.</p>
	<p>From the point for the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°52' W., bet. secs. 26 and 35.</p> <p>Over cultivated land.</p>
24.00	Enter dense salt cedar and river bottom weeds, edge bears N. and S.
39.84	Point for the ¼ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
42.54	Point for the record meander cor. of secs. 26 and 35 on the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
44.21	Point for the record meander cor. of secs. 26 and 35 on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
56.80	Gila River, 2 chs. wide, course N. 35° W., as scaled from U.S. Geological Quadrangle Map, Thatcher, Arizona, dated 1960.
79.68	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a railroad spike, 4 lks. W. of center of paved road, bears N. and S.</p> <p>from which</p> <p>An iron post, 2½ ins. diam., firmly set, projecting 8 ins. above ground for a reference monument, bears S. 37°45' W., 50 lks. dist., with brass cap mkd. S34 RM 33 ft. 1964, and an arrow pointing to the cor.</p> <p>The top of a water pump, bears N. 41°45' W., 108 lks. dist.</p> <p>A soil conservation service brass cap set in concrete, bears N. 33°40' W., 87.5 lks. dist., mkd. S27 RM 57.7 ft. 1960. (record 84.4 lks., sec. 34)</p> <p>Land, nearly level. Soil, sandy loam. Timber, salt cedar, mesquite and scattered cotton wood. Undergrowth, weeds.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Restoring the 1964-70 Resurvey by Leonard W. Murphy and Paul G. Bauer</p> <hr/>
	<p>N. 0°12' E., bet. secs. 26 and 27.</p> <p>Along paved road.</p>
0.45	Graded gravel road, bears W.
7.20	Leave paved road, bears S. 2° E. and N. 2° W.
25.00	Gila River, 2 chs. wide, course N. 65° W.
39.67	Point for the ¼ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
44.50	Enter cultivated field, bears SE and NW.
59.11	Point for the record meander cor. of secs. 26 and 27, on the left bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
61.56	Point for the record meander cor. of secs. 26 and 27 on the right bank of the Gila River, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
78.50	Leave cultivated field, bears E and W.
79.35	The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2½ ins. diam., flush with surface of ground, with brass cap mkd.
	<p>T6S R25E S22 S23 S27 S26 1964</p>
	<p>from which</p> <p>A bolt <math>\frac{3}{4}</math> ins. diam., imbedded in the concrete foundation of an open machinery shed, bears N. 64°45' E., 13 lks. dist.</p> <p>A spike nail in a support post of the shed, bears N. 70°45' W., 21 lks. dist.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, arrow weed and salt cedar along the river banks.</p>
	<p>Restoring the 1875 Survey by Theodore F. White</p> <hr/>
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 88°24' W., bet. secs. 23 and 26.</p> <p>Over rolling land, through medium creosote and scattered mesquite.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
13.40	Track road, bears S. 10° E. and N. 10° W.
20.08	Point for the E 1/16 sec. cor. of secs. 23 and 26.  Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.
	T6S R25E E 1/16 $\frac{S23}{S26}$ 1976
30.12	Point for the W-E 1/64 sec. cor. of secs. 23 and 26; not monumented.
35.10	Fence line, bears N . and S.
40.16	The ¼ sec. cor. of secs. 23 and 26, monumented with a mound of stone, 2 ft. base, 6 ins. high, with the remains of a charred stake in mound, from which an original bearing tree
	A mesquite, 16 ins. diam., bears S. 2°30' E., 61 lks. dist., open blaze, no marks visible.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T6S R25E ¼ $\frac{S23}{S26}$ 1976
	Deposit the remains of charred stake alongside the cor.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.
	Cor. is located 10 lks. W. of a small draw, drains southerly.
	<hr style="width: 20%; margin: 0 auto;"/> S. 88°33' W., beginning new measurement.
5.60	Power line, bears S. 55° E. and N. 55° W.
6.40	Paved road, bears S. 55° E. and N. 55° W,
7.10	Telephone line, bears S, 55° E, and N, 55° W,
8.20	Graham Canal, 15 lks. wide, flows N. 55° W,
8.30	Enter cultivated land, edge bears S, 55° E, and N, 55° W,
19.39	Point for the W 1/16 sec. cor. of secs. 23 and 26; not monumented.
38.78	The cor. of secs. 22, 23, 26 and 27,

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Land, rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, creosote, catclaw and cacti.</p> <hr/> <p>Restoring the 1964-70 Resurvey by Leonard W. Murphy and Paul G. Bauer</p> <hr/> <p>N. 0°40' E., bet. secs. 22 and 23. Over nearly level land.</p> <p>0.06 South edge of open machinery shed.</p> <p>0.45 North edge of same shed, thence over cultivated land.</p> <p>19.82 Point for the S 1/16 sec. cor. of secs. 22 and 23; not monumented.</p> <p>20.00 Leave cultivated land, edge bears E and W.</p> <p>27.40 Graham Canal, 15 lks. wide, flows N. 35° W.</p> <p>28.70 Telephone line, bears S. 40° E. and N. 40° W.</p> <p>29.40 Paved road, bears S. 40° E. and N. 40° W.</p> <p>36.60 Power line, bears S. 40° E. and N. 40° W.</p> <p>39.64 The ¼ sec. cor. of secs. 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E ¼ S22 S23 1964</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, W of cor. A private survey cor. bears West 0.9 lk. dist., monu- mented with an iron pipe, 1 inch diam., firmly set, projecting 12 ins. above ground, mkd. ¼ S22/23.</p> <hr/> <p style="text-align: center;">Restoring the 1875 Survey by Theodore F. White</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. S. 89°58' W., bet. secs. 14 and 23. Over rolling land, through medium creosote.</p> <p>22.80 Enter wash area, bears NE and SW, thence through medium creosote and mesquite.</p> <p>37.70 Fence line, bears N and S.</p> <p>39.77 The ¼ sec. cor. of secs. 14 and 23, monumented with a scattered mound of stone, from which the original bear- ing trees</p> <p style="padding-left: 40px;">A decayed mesquite stump, bears S. 87° E., 100 lks, dist., no marks visible.</p> <p style="padding-left: 40px;">A decayed mesquite snag, bears N. 85°30' W., 102 lks, dist., no marks visible.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E  <math>\frac{1}{4} \frac{S14}{S23}</math>                      1976</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.</p>
1.50	<p style="text-align: center;">_____</p> <p>N. 89°59' W., beginning new measurement.</p> <p>Continue over wash area.</p> <p>Leave wash area, bears NE and SW, thence over rolling land, through medium creosote.</p>
39.49	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E  <math>\frac{S15 S14}{S22 S23}</math>                      1964</p> <p>Mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Land, rolling.                      Soil, sandy loam.                      Timber, mesquite.                      Undergrowth, creosote, catclaw and cacti.</p>
4.10	<p>N. 0°24' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through medium creosote.</p> <p>Track road, bears N. 60° E. and S. 60° W.</p>
36.90	<p>Enter large draw, edge bears N. 30° W. and S. 30° W.</p>
39.89	<p>The ¼ sec. cor. of secs. 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E  <math>\frac{1}{4} \frac{S15 S14}{S22 S23}</math>                      1964</p> <p>Mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p> <p>Rebuild the mound of stone, to the W. of cor.</p> <p>Add the date 1977 to the brass cap.</p> <p>(Note: There is no official record of this cor.)</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	N. 0°22' W., beginning new measurement.
2.00	Butler Wash, 50 lks. wide, 3 ft. deep, drains S. 65° W.
6.10	Leave wash area, edge bears N. 30° E. and S. 30° W.
39.95	The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.
	T6S R25E S10 S11 S15 S14 1964
	Mound of stone, 3½ ft. base, 2 ft. high, S. of cor.
	Rebuild the mound of stone to the W. of cor.
	Found the original mkd. stone, 12x9x5 ins., buried alongside the iron post.
	Add the date 1977 to the brass cap.
	(Note: There is no official record of this cor.)
	Land, rolling. Soil, rocky, sandy loam. Timber, mesquite. Undergrowth, creosote, catclaw and cacti.
	Restoring the 1964-70 Resurvey by Leonard W. Murphy and Paul G. Bauer
	From the ¼ sec. cor. of secs. 15 and 22, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.
	T6S R25E ¼ <u>    </u> S15 S22 1964
	Mound of stone, 2½ ft. base, 1 ft. high, N. of cor.
	N. 89°28' W., bet. secs. 15 and 22.
	Over gently rolling land through medium creosote and mesquite.
0.50	Track road, bears NE and SW.
16.10	Wash, 100 lks. wide, 5 ft. deep, drains S. 20° W.
17.60	Graded gravel road, bears N. 20° E. and SW.
17.90	Graham Canal, 15 lks. wide, flows N. 55° W.
19.95	Point for the W 1/16 sec. cor. of secs. 15 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.
	T6S R25E W 1/16 <u>    </u> S15 S22 1977

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.
22.90	Enter SE cor. of cultivated field, edge bears W. and N. 25° W.
31.70	Concrete irrigation ditch, 5 lks. wide, flows North.
39.90	The cor. of secs. 15, 16, 21 and 22, in the S. edge of a cultivated field, has been destroyed. Determined the cor. point from two accessories
	An X on a concrete irrigation ditch abutment, bears S. 70°15' E., 43.9 lks. dist.
	An iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, bears S. 57°30' W., 43.9 lks. dist., with brass cap mkd. S21 RM 28.9 ft. 1964, and an arrow pointing to the cor. point.
	The reference monument is located in E. and W. fence line.
	Land, gently rolling.
	Soil, rocky, sandy loam.
	Timber, mesquite.
	Undergrowth, creosote and cacti.
	N. 0°03' W., bet. secs. 15 and 16.
	Over cultivated land.
10.00	Concrete irrigation ditch, 5 lks. wide, flows NW.
11.60	Graham Canal, 15 lks. wide, flows NW, thence over rolling land, through medium creosote.
19.88	Point for the S 1/16 sec. cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6S R25E S 1/16 S16 S15 1977</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high W. of cor.
	Cor. is located 15 lks. E. of a draw, drains southerly.
39.76	The ¼ sec. cor. of secs. 15 and 16, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.
	<p style="text-align: center;">T6S R25E ¼ S16 S15 1964</p>
	A 4x4 wood post, projecting 2½ ft. above ground, is set alongside the cor.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS					
39.73	<p>Mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Fence cor. bears N. 46° E., 40 lks. dist., fences extend N. 1° W. and W.</p> <hr/> <p style="text-align: center;">Restoring the 1875 Survey by Theodore F. White</p> <p>N. 1°06' W., beginning new measurement.</p> <p>The cor. of secs. 9, 10, 15 and 16, monumented with a volcanic stone 15x9x8 ins. firmly set, projecting 10 ins. above ground, mkd. with 3 notches on E. and 4 notches on S. edges, in a mound of stone, 2½ ft. base to top.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R25E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S9</td> <td style="padding: 0 5px;">S10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S16</td> <td style="padding: 0 5px;">S15</td> </tr> </table> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the cor.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Fence cor. bears S. 86° W., 39.5 lks. dist., fences extend S. 1° E. and N. 89° W.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, scattered mesquite. Undergrowth, creosote and cacti.</p>	S9	S10	S16	S15
S9	S10				
S16	S15				
13.70 40.01	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°43' W., bet. secs. 10 and 15.</p> <p>Over gently rolling land, through dense creosote.</p> <p>Track road, bears N. 25° E. and S. 25° W.</p> <p>Point for the ¼ sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6S R25E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">¼</td> <td style="padding: 0 5px;">S10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">S15</td> </tr> </table> <p>1977</p> </div> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.</p> <p>Cor. is located 15 lks. E. of a wash, 20 lks. wide, 3 ft. deep, drains south, curves southwesterly.</p>	¼	S10		S15
¼	S10				
	S15				

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
80.02	<p>A claim cor. bears S. 8°55' W., 84 lks. dist., monumented with a 2x2 inch wooden post, projecting 3 ft. above a mound of stone, 3 ft. base, 1½ ft. high, with tag attached and mkd. NWLY COM COR NET 6 NET 7.</p> <p>The cor. of secs. 9, 10, 15 and 16.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, scattered mesquite. Undergrowth, creosote and cacti.</p>
2.50	<p>N. 0°18' W., bet. secs. 9 and 10.</p> <p>Over gently rolling land, through medium creosote.</p> <p>Draw, drains SW.</p>
16.00	<p>Enter large draw, edge bears NE and SW.</p>
31.50	<p>Leave large draw, edge bears N. 25° E. and S. 25° W.</p>
39.96	<p>The ¼ sec. cor. of secs. 9 and 10, monumented with a volcanic stone, 13x11x9 ins., firmly set, projecting 7 ins. above the ground, mkd. ¼ on SE face, mound of stone 2½ ft. base, 2 ft. high, W. of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E ¼ S 9 S10 1977</p> <p>Deposit the mkd. stone alongside the cor.</p> <p>Rebuild the mound of stone, 3½ ft. base, 2½ ft. high, W. of cor.</p>
40.02	<p>N. 0°06' E., beginning new measurement.</p> <p>The cor. of secs. 3, 4, 9 and 10, monumented with a volcanic stone, 18x16x10 ins. firmly set, projecting 8 ins. above the ground, in a mound of stone, 2 ft. base, 1 ft. high mkd. with 5 grooves on S face and 1 groove visible on E face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E S4 S3 S9 S10 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Deposit the mkd. stone, alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>Cor. is located 12 lks. S of a track road, bears S. 70° E. and N. 70° W.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, scattered palo verde and mesquite. Undergrowth, creosote and cacti.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°37' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through medium creosote.</p>
17.00	<p>Chesley Wash, 100 lks. wide, 15 ft. deep, drains SSW, as scaled from U.S. Geological Quadrangle Map, Thatcher, Arizona, dated 1960.</p>
39.73	<p>Point for the ¼ sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E       S9 ¼    S16       1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>Fence cor., bears N. 70° E., 75 lks. dist.; fences extend E, S and W.</p>
44.00	<p>Draw, drains SW.</p>
49.70	<p>Graham Canal, 15 lks. wide, flows N. 35° W.</p>
50.00	<p>Track road on canal bank, bears S. 35° E. and N. 35° W.</p>
57.00	<p>Enter NE cor. of cultivated field, edge bears S and W.</p>
59.59	<p>Point for the W 1/16 sec. cor. of secs. 9 and 16.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. below surface of N edge of cultivated field, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E       S9 W 1/16 S16       1977</p> <p>from which</p> <p>A mesquite, 4 ins. diam., bears N. 12° E., 124 lks. dist., mkd. X BT at base due to structure of the tree.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 77° E., 252 lks. dist., with brass cap mkd. T6S R25E W1/16 S9 RM 166.4 ft. 1977, and an arrow pointing to the cor.</p>	
78.80	<p>Paved road, bears N and S.</p>	
79.45	<p>Point for the cor. of secs. 8, 9, 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p>	
	<p>From this point the cor. of secs. 16, 17, 20 and 21, bears S. 0°27' E., 79.43 chs. dist., monumented with an iron post, 2½ ins. diam., set 4 ins. below surface of shoulder of paved road, with brass cap mkd.</p>	
	<p style="text-align: center;">T6S R25E S17 S16 S20 S21 1964</p>	
	<p>Cor. is located 37 lks. S. of center of curve in paved road, bears SE curving E and NW curving N.</p>	
	<p>from which</p>	
	<p>An iron post, 2½ ins. diam., projecting 4 ins. above the ground for a reference monument bears S. 66°13' E., 40.8 lks. dist., with brass cap mkd. T6S R25E S21 RM 27 ft. 1964, and an arrow pointing to the cor.</p>	
	<p>An iron post, 2½ ins. diam., projecting 6 ins. above the ground for a reference monument, bears S. 64°08' W., 35.5 lks. dist., with brass cap mkd. T6S R25E S20 RM 23.4 ft. 1964 and an arrow pointing to the cor.</p>	
	<p>The reference monuments are located in an E and W fence line.</p>	
	<p>Land, rolling. Soil, rocky, sandy loam. Timber, mesquite. Undergrowth, creosote, catclaw and cacti.</p>	
	<p>N. 1°07' E., bet. secs. 8 and 9.</p>	
	<p>Over gently rolling land, through medium mesquite.</p>	
7.00	<p>Holyoke Wash, 75 lks. wide, 3 ft. deep drains SW.</p>	
12.70	<p>Paved road, bears S and NW.</p>	
14.10	<p>Track road, on canal bank, bears S. 75° E. and N. 75° W.</p>	
14.40	<p>Graham Canal, 15 lks. wide, flows N. 55° W., thence over rolling land, through medium creosote and scattered mesquite</p>	
19.86	<p>Point for the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

## CHAINS

T6S R25E  
S 1/16  
S8|S9  
1977

Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.

Fence cor. bears N. 65° E., 73 lks. dist., fences extend E, S and W.

37.30 Wash, 20 lks. wide, 2 ft. deep in a draw, drains SW.

39.72 The ¼ sec. cor. of secs. 8 and 9, monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.

T6S R25E  
¼  
S8|S9  
1964

Mound of stone, 3 ft. base, 2 ft. high W. of cor.

N. 0°05' E., beginning new measurement.

3.50 Enter large draw, edge bears N. 65° E. and S. 65° W.

10.20 Leave large draw, edge bears N. 65° E. and S. 65° W.

26.30 Large draw, drains S. 35° W.

39.64 The cor. of secs. 4, 5, 8 and 9, monumented with a volcanic stone, 12x8x4 ins. firmly set, projecting 8 ins. above the ground, mkd. with 5 grooves on S and 4 grooves on E faces, in a mound of stone, 2½ ft. base to top.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.

T6S R25E  
S5|S4  
S8|S9  
1977

Deposit the mkd. stone alongside the iron post.

Land, rolling.

Soil, rocky sandy loam.

Timber, mesquite.

Undergrowth, creosote, catclaw and cacti.

From the cor. of secs. 3, 4, 9 and 10.

N. 89°54' W., bet. secs. 4 and 9.

Over gently rolling land, through medium creosote, scattered mesquite and palo verde.

27.00 Holyoke Wash, 100 lks. wide, 15 ft. deep drains S., curving SW.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
39.96	<p>The ¼ sec. cor. of secs. 4 and 9, monumented with a volcanic stone, 15x12x9 ins. firmly set, projecting 6 ins. above the ground, in a mound of stone, 2½ ft. base to top, mkd. ¼ on E face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E     S4 ¼ — S9     1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.</p> <p>Cor. is located 7 lks. W of a fence line, bears S. 10° E. and N. 10° W.</p>
6.00	<p>S. 89°45' W., beginning new measurement.</p>
38.47	<p>Wash, 100 lks. wide, 25 ft. deep, drains SW.</p> <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling. Soil, rocky, sandy loam. Timber, mesquite and palo verde. Undergrowth, creosote, catclaw and cacti.</p>
19.89	<p>From the point for the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°54' W., bet. secs. 8 and 17.</p> <p>Over level land, along abandoned fence line, bet. cultivated fields.</p>
39.78	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17; not monumented.</p>
79.56	<p>Point for the ¼ sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> <p>The cor. of secs. 7, 8, 17 and 18, monumented with a reinforcement rod ½ inch diam., projecting 1 inch above the ground. This cor. was established by L.S. 9090 and is accepted as the best evidence of the original cor. position; not remonumented.</p> <p>Land, level. Soil, sandy loam. Timber, none. Undergrowth, weeds.</p>
39.63	<p>N. 0°07' E., bet. secs. 7 and 8.</p> <p>Over cultivated land.</p> <p>Point for the ¼ sec. cor. of secs. 7 and 8 at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p>
39.70	<p>Power line, bears E and W.</p>
39.90	<p>Paved road, bears E and W.</p>



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS					
40.20	Fence line, bears E and W, thence along W side of cultivated land.				
59.445	Point for the N 1/16 sec. cor. of secs. 7 and 8; not monumented.				
61.20	Leave cultivated land, edge bears S. 78° E. and South, thence through dense mesquite.				
62.40	Track road on canal bank, bears S. 55° E. and N. 55° W.				
62.70	Graham Canal, 15 lks. wide, flows N. 55° W., thence over rolling land, through medium creosote and scattered mesquite.				
70.30	Spur slopes S. 60° W.				
71.70	Descend vertical cliff, 75 ft. high, bears N. 60° E. and S. 60° W.				
72.70	Peck Wash, 50 lks. wide, 2 ft. deep, drains S. 60° W., thence across wash area.				
79.26	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a volcanic stone, 14x10x8 ins. loosely set, mkd. with 5 notches on S and 5 notches on E edges, from which an original bearing tree</p> <p style="padding-left: 40px;">A mesquite snag bears S. 30°30' E., 175 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>T6S R25E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S6</td> <td style="padding: 0 5px;">S5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S7</td> <td style="padding: 0 5px;">S8</td> </tr> </table> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of the cor.</p> <p>Land, level to rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, creosote and cacti.</p>	S6	S5	S7	S8
S6	S5				
S7	S8				
	<p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>N. 89°57' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through medium creosote and scattered mesquite.</p>				
37.90	Enter large draw, edge bears N and S.				
39.90	<p>Point selected for the witness ¼ sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; padding: 10px 0;"> <p>WC</p> <p>T6S R25E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">←</td> <td style="border-right: 1px solid black; padding: 0 5px;">S5</td> </tr> <tr> <td style="padding: 0 5px;">←</td> <td style="border-right: 1px solid black; padding: 0 5px;">S8</td> </tr> </table> <p>¼</p> <p>1977</p> </div>	←	S5	←	S8
←	S5				
←	S8				

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.
40.10	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate dist., falls in the E. edge of Big Spring Wash, 50 lks. wide, 3 ft. deep, drains southerly, impracticable to monument; there is no remaining evidence of the original cor.
44.40	West edge of large draw, bears N and S.
46.00	Fence line, bears N. 25° E. and S. 25° W.
60.15	Point for the W 1/16 sec. cor. of secs. 5 and 8.  Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6S R25E  <math display="block">W \frac{1}{16} \frac{S5}{S8}</math>                     1977</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
76.70	Peck Wash, 50 lks. wide, 2 ft. deep, drains S. 35° W., thence over wash area.
79.68	Fence line, bears S. 65° E. and N. 65° W., 30 lks. dist., thence N. 70° W.
80.20	The cor. of secs. 5, 6, 7 and 8.  Land, rolling. Soil, rocky, sandy loam. Timber, mesquite. Undergrowth, creosote, catclaw and cacti.
	N. 89°28' W., bet. secs. 6 and 7.
	Over rolling land, through medium creosote and scattered mesquite.
7.00	Graded gravel road, bears SE and NW.
9.935	Point for the E-E 1/64 sec. cor. of secs. 6 and 7; not monumented.
19.87	Point for the E 1/16 sec. cor. of secs. 6 and 7.  Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6S R25E  <math display="block">E \frac{1}{16} \frac{S6}{S7}</math>                     1977</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of cor.
20.40	Graham Canal, 15 lks. wide, flows NW.
28.20	Concrete irrigation ditch, 5 lks. wide, flows N., thence over cultivated land.
38.90	Leave cultivated land, bears N and S.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6. S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
39.10	Power line, bears N and S.
39.60	Paved road, bears N and S.
39.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 6 and 7 at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
40.05	Fence line, bears N and S.
40.20	Concrete ditch, 5 lks. wide, flows S, thence over cultivated land.
77.00	Leave cultivated land, edge bears N and S.
77.20	Fence and power line, bears N and S.
77.55	The cor. of secs. 1, 6, 7, and 12 on the W. bdy. of the Tp. monumented with an iron post, $2\frac{1}{2}$ ins. diam., 10 ins. below surface of graded gravel road, bears N and S, with brass cap mkd.
	T6S R24E R25E S1 S6 S12 S7 1965
	from which
	An iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above the ground, for a reference monument, bears N. $83^\circ$ E., 30.3 lks. dist., with brass cap mkd. T6S R25E S7 RM 20 ft. 1965, and an arrow pointing to the cor.
	Remark the brass cap to read S6 and add the date 1977.
	An iron post, $2\frac{1}{2}$ ins. diam., firmly set, projecting 6 ins. above the ground, for a reference monument, bears N. $35^\circ$ W., 45.5 lks. dist., with brass cap mkd. T6S R24E S1 RM 30 ft. 1965, and an arrow pointing to the cor.
	Land, E. 20 chs. rolling, remainder nearly level. Soil, sandy loam. Timber, mesquite. Undergrowth, creosote, and cacti.
	From the cor. of secs. 5, 6, 7 and 8.
	N. $0^\circ 06'$ E., bet. secs. 5 and 6.
	Over rolling land, through medium creosote and scattered mesquite.
0.21	Fence line, bears N. $70^\circ$ W. and S. $70^\circ$ E., 28 lks. dist., thence S. $65^\circ$ E.
3.70	Graded gravel road, bears N. $55^\circ$ E. and S. $55^\circ$ W.
9.895	Point for the S-S $1/64$ sec. cor. of secs. 5 and 6, not monumented.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS		
19.79	<p>Point for the S 1/16 sec. cor. of secs. 5 and 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E S 1/16 S6 S5 1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.</p>	
25.00	<p>Graded road, bears N. 70° W. and N. 70° E. curving Northerly.</p>	
29.685	<p>Point for the S-N 1/64 sec. cor. of secs. 5 and 6, not monumented.</p>	
39.58	<p>The ¼ sec. cor. of secs. 5 and 6, monumented with a volcanic stone, 15x11x6 ins., firmly set, projecting 8 ins. above the ground in a mound of stone, 2 ft. base to top, mkd. ¼ on S face, with a ¼ inch reinforcement rod projecting 10 ins. above ground alongside the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E ¼ S6 S5 1977</p> <p>Deposit the mkd. stone and reinforcement rod alongside the cor.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of cor.</p> <p>From this point the SE cor. of a block building 31.5 x 10.5 ft., bears N. 47°34' W., 90.7 lks. dist., long side, bears N. 83° W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°15' E., beginning new measurement.</p>	
3.00	<p>Graded road, bears S. 25° E. and N. 25° W. approximately 2 chs. to the end.</p>	
16.00	<p>SE rim of canyon, bears NE and SW.</p>	
40.19	<p>The closing cor. of secs. 5 and 6, monumented with an iron post, 2 ins. diam., set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap improperly mkd.</p> <p style="text-align: center;">T25S R T6S ——— R25E                       S6   S5           CC           1920</p> <p>Remark the cap to read</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.

CHAINS	
40.38	<p style="text-align: center;">AM T5S R25E S31 ----- S6   S5 T6S   R25E CC 1977 1920</p> <p>Point for the closing cor. of secs. 5 and 6, at intersection with the First Standard Parallel South.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R25E S31 ----- S6   S5 T6S   R25E CC 1977</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, S. of cor.</p> <p>From this point the standard cor. of secs. 31 and 32, T. 5 S., R. 25 E., bears S. 89°54' E., 29.34 chs. dist., heretofore described.</p> <p>Land, rolling. Soil, rocky, sandy loam. Timber, mesquite. Undergrowth, creosote and cacti.</p>
	<p style="text-align: center;">Subdivision of Section 6, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.</p>
7.00 11.50 13.00 19.87	<p>From the point for the ¼ sec. cor. of secs. 6 and 7. N. 0°01' E., along the N and S center line of sec. 6, along paved road.</p> <p>Paved road, bears S and N. 20° W., curving NW, thence through medium creosote and mesquite.</p> <p>Graded gravel road, bears N. 60° E. and S. 60° W.</p> <p>Graham Canal, 15 lks. wide, flows N. 70° W., thence over rolling land, through medium creosote and scattered mesquite.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E C S 1/16   S6 C 1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.</p>

Subdivision of Section 6, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS		
29.805	Point for the C-N-S 1/64 sec. cor. of sec. 6; not monumented.	
39.74	Point for the C <sup>1</sup> / <sub>4</sub> sec. cor. at intersection with the E and W center line of sec. 6.  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	
	T6S R25E C <sup>1</sup> / <sub>4</sub> S6 1977	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of cor.	
68.50	Rim of canyon, bears N. 65° E. and S. 65° W.	
79.50	The ¼ sec. cor. of sec. 6 on the N bdy. of the Tp., heretofore described.  From this point the standard township cor. of Tps. 5 S., Rs. 24 and 25 E., bears S. 89°47' W., 9.92 chs. dist., heretofore described.	
	From the ¼ sec. cor. of secs. 5 and 6.  N. 89°15' W., along the E and W center line of sec. 6.  Over rolling land, through medium creosote.	
9.95	Point for the C-E-E 1/64 sec. cor. of sec. 6; not monumented.	
18.80	Draw, drains SW.	
19.90	Point for the C-E 1/16 sec. cor. of sec. 6; not monumented.	
29.85	Point for the C-W-E 1/64 sec. cor. of sec. 6; not monumented.	
31.00	Track road, bears N and S.	
39.80	The C <sup>1</sup> / <sub>4</sub> sec. cor. of sec. 6.	
77.46	The ¼ sec. cor. of secs. 1 and 6 on the W bdy. of Tp., monumented with an iron post, 1 inch in diam., firmly set projecting 12 ins. above the ground, with brass cap mkd.	
	¼ S1 S6 1916	
	Remark the brass cap to read	
	T6S R24E R25E ¼ S1 S6 1977 1916	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.	

Subdivision of Section 6, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

## CHAINS

Cor. is located 3 lks. SW of cor. of fences extending  
N.  $30^{\circ}$ E and S.  $10^{\circ}$  W.

SE $\frac{1}{4}$  Section 6

From the E 1/16 sec. cor. of secs. 6 and 7.

N.  $0^{\circ}04'$  E., along the N and S center line of the SE $\frac{1}{4}$ ,  
sec. 6.

Over rolling land, through medium creosote.

9.915 Point for the C-S-SE 1/64 sec. cor. of sec. 6; not  
monumented.

14.872 Point for the C-N-S-SE 1/256 sec. cor. of sec. 6.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 20 ins.  
in the ground, with brass cap mkd.

S6  
C-N-S-SE  
1/256  
1977

Raise a mound of stone, 2 $\frac{1}{2}$  ft. base, 1 $\frac{1}{2}$  ft. high, W. of  
cor.

From this point a reinforcement rod  $\frac{1}{2}$  inch in diam.,  
projecting 12 ins. above the ground, bears S.  $50^{\circ}$  W.,  
64.5 lks. dist.

From this same point the SE cor. of fence around Bryce  
Cemetery, bears N.  $18^{\circ}36'$  W., 231.5 lks. dist.

19.83 Point for the SE 1/16 sec. cor. at intersection with  
the E and W center line of the SE $\frac{1}{4}$  of sec. 6; not  
monumented.

24.79 Point for the C-S-N-SE 1/256 sec. cor. of sec. 6; not  
monumented.

29.40 Power line, bears N.  $55^{\circ}$  E. and S.  $55^{\circ}$  W., graded gravel  
road, bears N.  $65^{\circ}$  E. curving NE and S.  $65^{\circ}$  W. curving  
SW.

29.75 Point for the C-N-SE 1/64 sec. cor. of sec. 6; not  
monumented.

39.00 Draw, drains SW.

39.67 The point for the C-E 1/16 sec. cor. of sec. 6.

From the S 1/16 sec. cor. of secs. 5 and 6.

N.  $89^{\circ}21'30''$  W., along the E and W center line of the  
SE $\frac{1}{4}$ , of sec. 6.

Over rolling land, through medium creosote.

9.94 Point for the C-E-SE 1/64 sec. cor. of sec. 6; not  
monumented.

14.91 Point for the C-W-E-SE 1/256 sec. cor. of sec. 6; not  
monumented.

Subdivision of Sec. 6, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona

CHAINS		
19.88	The point for the SE 1/16 sec. cor. of sec. 6.	
24.855	<p>Point for the C-E-W-SE 1/256 sec. cor. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S6 C-E-W-SE 1/256 1977</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of cor.</p> <p>From this point the SW cor. of fence around Bryce Cemetery, bears S. 29° E., 289.7 lks. dist.</p>	
27.50	Graded gravel road, bears N. 35° E. and S. 35° W.	
29.83	Point for the C-W-SE 1/64 sec. cor. of sec. 6; not monumented.	
38.05	Power line, bears N and S.	
39.78	The C-S 1/16 sec. cor. of sec. 6.	
4.955	<p style="text-align: center;">—————</p> <p>From the point for the C-E-SE 1/64 sec. cor. of sec. 6.</p> <p>N. 0°05' E., along the N and S center line of the NE¼ of the SE¼, sec. 6.</p>	
9.91	Point for the NE-SE 1/64 sec. cor. at intersection with the E and W center line of the NE¼ of the SE¼ of sec. 6; not monumented.	
19.82	<p>The point for the C-E-E 1/64 sec. cor. of sec. 6.</p> <p style="text-align: center;">—————</p> <p>From the point for the N-S 1/64 sec. cor. of secs. 5 and 6.</p> <p>N. 89°18'30" W., along the E and W center line of the NE¼ of the SE¼, sec. 6.</p>	
9.945	The point for the NE-SE 1/64 sec. cor. of sec. 6.	
14.92	Point for the C-W-NE-SE 1/256 sec. cor. of sec. 6; not monumented.	
19.40	Power line, bears N. 55° E. and S. 55° W.	
19.895	<p>The point for the C-N-SE 1/64 sec. cor. of sec. 6.</p> <p style="text-align: center;">—————</p> <p>From the point for the C-W-E-SE 1/256 sec. cor. of sec. 6.</p> <p>N. 0°04'30" E., along the N and S center line of the SW¼ of the NE¼ of the SE¼, sec. 6.</p>	
4.955	Point for the SW-NE-SE 1/256 sec. cor. at intersection with the E and W center line of the SW¼ of the NE¼ of SE¼, sec. 6.	



Subdivision of Sec. 6, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S6 SW-NE-SE 1/256 1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located in small draw, drains S. 65° W., from N. 65° W.</p> <p>From this point the NE cor. of Bryce Cemetery bears N. 68°31'30" W., 309 lks. dist.</p>
9.91	<p>The point for the C-W-NE-SE 1/256 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-S-NE-SE 1/256 sec. cor. of sec. 6.</p> <p>N. 89°20' W., along the E and W center line of the SW¼ of the NE¼ of the SE¼, sec. 6.</p>
4.97	The SW-NE-SE 1/256 sec. cor. of sec. 6.
9.94	The point for the C-S-N-SE 1/256 sec. cor. of sec. 6.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the E-E 1/64 sec. cor. of secs. 6 and 7.</p> <p>N. 0°05' E., along the N and S center line of the SE¼ of the SE¼, sec. 6.</p>
9.905	Point for the SE-SE 1/64 sec. cor. at intersection with the E and W center line of the SE¼ of the SE¼ sec. 6; not monumented.
14.858	Point for the C-N-SE-SE 1/256 sec. cor. of sec. 6; not monumented.
19.81	The point for the C-E-SE 1/64 sec. cor. of sec. 6.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the S-S 1/64 sec. cor. of secs. 5 and 6.</p> <p>N. 89°24'45" W., along the E and W center line of the SE¼ of the SE¼, sec. 6.</p>
9.94	The point for the SE-SE 1/64 sec. cor. of sec. 6.
14.91	Point for the C-W-SE-SE 1/256 sec. cor. of sec. 6; not monumented.
19.88	The point for the C-S-SE 1/64 sec. cor. of sec. 6.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-W-SE-SE 1/256 sec. cor. of sec. 6.</p>

Subdivision of Sec. 6, T. 6 S., R. 25 E.  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>N. 0°04'30" E., along the N and S center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p>	
4.955	<p>Point for the NW-SE-SE 1/256 sec. cor. at intersection with the E and W center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S6 NW-SE-SE 1/256 1977</p> <p>Raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1<math>\frac{1}{2}</math> ft. high W. of cor.</p> <p>Cor. is located in a small draw, drains West, from SE.</p>	
9.91	<p>The point for the C-W-E-SE 1/256 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-N-SE-SE 1/256 sec. cor. of sec. 6.</p> <p>N. 89°23' W., along the E and W center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p>	
4.97	<p>The NW-SE-SE 1/256 sec. cor. of sec. 6.</p>	
9.94	<p>The C-N-S-SE 1/256 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-W-SE 1/64 sec. cor. of sec. 6.</p> <p>N. 0°02'30" E., along the N and S center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p>	
4.962	<p>Point for the C-S-NW-SE 1/256 sec. cor. of sec. 6; not monumented.</p>	
9.925	<p>Point for the NW-SE 1/64 sec. cor. at intersection with the E and W center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6; not monumented.</p>	
19.85	<p>The point for the C-W-E 1/64 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-N-SE 1/64 sec. cor. of sec. 6.</p> <p>N. 89°18'30" W., along the E and W center line of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p>	
4.962	<p>The point for the C-E-NW-SE 1/256 sec. cor. of sec. 6; not monumented.</p>	
9.925	<p>The point for the NW-SE 1/64 sec. cor. of sec. 6.</p>	
19.85	<p>The point for the C-N-S 1/64 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the C-E-W-SE 1/256 sec. cor. of sec. 6.</p> <p>N. 0°03'15" E., along the N and S center line of the SE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p>	
4.96	<p>Point for the SE-NW-SE 1/256 sec. cor. at intersection with the E and W center line of the SE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math></p>	

Subdivision of Sec. 6, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>of the SE<math>\frac{1}{4}</math>, sec. 6.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S6 SE-NW-SE 1/256 1977</p> <p>Raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1<math>\frac{1}{2}</math> ft. high, W of cor.</p> <p>Cor. is located 15 lks. W of a graded gravel road, bears N. 30° E. and S. 30° W.</p> <p style="text-align: right;">Bryce</p> <p>From this point the NW cor. of fence around/cemetery, bears N. 69°35' E., 378 lks. dist.</p>
9.92	<p>The point for the C-E-NW-SE 1/256 sec. cor. of sec. 6.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-S-N-SE 1/256 sec. cor. of sec. 6.</p> <p>N. 89°20' W., along the E and W center line of the SE<math>\frac{1}{4}</math> of the NW<math>\frac{1}{4}</math> of the SE<math>\frac{1}{4}</math>, sec. 6.</p>
4.97	<p>The SE-NW-SE 1/256 sec. cor. of sec. 6.</p>
9.94	<p>The point for the C-S-NW-SE 1/256 sec. cor. of sec. 6.</p>
<p>Subdivision of Sec. 8, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.</p>	
	<p>From the point for the <math>\frac{1}{4}</math> sec. cor. of secs. 8 and 17.</p> <p>N. 0°21' E., along the N and S center line of Sec. 8.</p> <p>Over cultivated land.</p>
0.10	<p>Abandoned fence line, bears E and W.</p>
19.835	<p>Point for the C-S 1/16 sec. cor. of sec. 8; not monumented.</p>
19.90	<p>Irrigation ditch, 5 lks. wide, flows W from E; leave cultivated land, bears E and W.</p>
20.30	<p>Curve in graded gravel road, bears N and E.</p>
20.60	<p>Power line, bears E. and W 50 lks., thence N.</p>
39.67	<p>Point for the C<math>\frac{1}{4}</math> sec. cor. of sec. 8, at intersection with the E and W center line of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., flush with surface of shoulder of a road, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E C<math>\frac{1}{4}</math> S8 1977</p>

Subdivision of Sec. 8, T. 6 S., R. 25 E.  
Gila and Salt River Meridian, Arizona.

CHAINS		
	<p>from which</p> <p>A power pole bears S. 86° W., 68.4 lks. dist., which is the cor. of a power line; extending S and W.</p> <p>Cor. is located 21.5 lks. N. of fence cor.; fences extend S and E curving SE.</p>	
39.92	Paved road, bears W and E, curving S. 55° E., thence through medium creosote and scattered mesquite.	
43.00	Track road on canal bank, bears S. 50° E. and N. 50° W.	
43.20	Graham Canal, 15 lks. wide, flows N. 50° W.	
59.49	Point for the C-N 1/16 sec. cor. of sec. 8.	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E C N 1/16   S8 C 1977</p>	
	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W of cor.</p> <p>Fence cor., bears N. 14° W., 93 lks. dist., fences extend S. 2° W., and N. 57° W.</p>	
62.50	Big Spring Wash, 50 lks. wide, 3 ft. deep, drains S. 10° E., as scaled from U.S. Geological Quadrangle Map, Thatcher, Arizona, dated 1960.	
79.31	The true point for the ¼ sec. cor. of secs. 5 and 8.	
	<p>From the ¼ sec. cor. of secs. 8 and 9.</p> <p>N. 89°57' W., along the E and W center line of sec. 8.</p> <p>Over rolling land, through medium creosote and scattered mesquite.</p>	
20.155	Point for the C-E 1/16 sec. cor. of sec. 8.	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E E 1/16 C ——— C S8 1977</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>	
28.30	Graham Canal, 15 lks. wide, flows N. 55° W.	
28.50	Track road on canal bank, bears S. 55° E. and N. 55° W.	
38.90	Paved road, bears S. 55° E. and N. 55° W., curving W.	

Subdivision of Sec. 8, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
40.31	The $C\frac{1}{4}$ sec. cor. of sec. 8.
	Continue along S edge of paved road.
60.275	Point for the C-W 1/16 sec. cor. of sec. 8; not monumented.
80.24	The point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
<u>SE<math>\frac{1}{4}</math>, Section 8</u>	
	From the point for the E 1/16 sec. cor. of secs. 8 and 17 N. $0^{\circ}44'$ E., along the N and S center line of the SE $\frac{1}{4}$ , sec. 8.
	Over cultivated land.
0.08	Abandoned fence line, bears E and W.
19.70	Leave cultivated land, edge bears E and W.
19.845	Point for the SE 1/16 sec. cor. at intersection with the E and W center line of the SE $\frac{1}{4}$ , sec. 8.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T6S R25E SE 1/16 S8 1977
	Set a steel fence post, alongside the cor.
20.00	Graded gravel road, bears E and W.
20.30	Fence line, bears E and W, thence through dense mesquite.
20.60	Power line, bears E and W.
27.70	Paved road, bears S. $55^{\circ}$ E. and N. $55^{\circ}$ W.
34.00	Track road on canal bank, bears SE and NW.
34.20	Graham Canal, 15 lks. wide, flows NW.
39.69	The C-E 1/16 sec. cor. of sec. 8.
	From the S 1/16 sec. cor. of secs. 8 and 9.
	N. $89^{\circ}54'30''$ W., along the E and W center line of the SE $\frac{1}{4}$ , sec. 8.
	Over rolling land, through medium creosote and scattered mesquite.
4.40	Graham Canal, 15 lks. wide, flows NW.
4.70	Track road on canal bank, bears SE and NW.
8.80	Paved road, bears S. $55^{\circ}$ E. and N. $55^{\circ}$ W.

Subdivision of Sec. 8, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
10.20	Graded gravel road, bears S. 65° E. to paved road and W, thence over level land bet. road and cultivated land.
12.10	Power line, bears S. 60° E. and N. 60° W.
20.015	The SE 1/16 sec. cor. of sec. 8.
40.03	The point for the C-S 1/16 sec. cor. of sec. 8.
<u>NW<math>\frac{1}{4}</math>, Section 8</u>	
From the point for the C-W 1/16 sec. cor. of sec. 8.	
N. 0°15'30" E., along the N and S center line of the NW $\frac{1}{4}$ , sec. 8.	
Over farm lot.	
0.25	Paved road, bears E and W.
14.00	Track road on canal bank, bears S, 75° E. and N, 75° W,
14.30	Graham Canal, 15 lks. wide, flows N. 75° W., thence over rolling land, through medium creosote.
19.81	Point for the NW 1/16 sec. cor. at intersection with the E and W center line of the NW $\frac{1}{4}$ , sec. 8.
Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.	
T6S R25E NW 1/16 S8 1977	
Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.	
30.20	Fence line, bears S. 60° E. and N, 60° W., 65 lks. dist., to the cor. of fences extending S. 60° E., N. 60° W. and S. 30° W.
39.62	The W 1/16 sec. cor. of secs. 5 and 8.
_____	
From the C-N 1/16 sec. cor. of sec. 8.	
N89°57'30" W., along the E and W center line of the NW $\frac{1}{4}$ , sec. 8.	
Over rolling land, through medium creosote and scattered mesquite.	
20.01	The NW 1/16 sec. cor. of sec. 8.
28.70	Graham Canal, 15 lks. wide, flows NW.
29.00	Track road on canal bank, bears SE and NW.
31.60	Enter cultivated land, edge bears S. 40° E. and N. 80° W.
40.03	The point for the N 1/16 sec. cor. of secs. 7 and 8.

Subdivision of Sec. 9, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	<p>Subdivision of Sec. 9, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.</p>
19.915	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 16. N. <math>0^{\circ}16'30''</math> W., along the N and S center line of sec. 9. Over rolling land, through medium creosote and scattered mesquite. Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 9. Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E C S <math>\frac{1}{16}</math>   S9 C 1977</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, <math>1\frac{1}{2}</math> ft. high, W of cor.</p>
20.43	Fence line, bears E and W.
39.83	<p>Point for the <math>C\frac{1}{4}</math> sec. cor. at intersection with the E and W center line of sec. 9. Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E <math>C\frac{1}{4}</math> S9 1977</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, <math>1\frac{1}{2}</math> ft. high, W of cor.</p>
79.78	The $\frac{1}{4}$ sec. cor. of secs. 4 and 9.
35.70	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 9 and 10. N. <math>89^{\circ}47'30''</math> W., along the E and W center line of sec. 9. Over rolling land, through medium creosote. Fence line, bears S. <math>5^{\circ}</math> E. and N. <math>5^{\circ}</math> W.</p>
39.71	The $C\frac{1}{4}$ sec. cor. of sec. 9.
55.90	Holyoke Wash, 250 lks. wide, drains SW.
59.07	<p>Point for the C-W <math>\frac{1}{16}</math> sec. cor. of sec. 9. Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E W <math>\frac{1}{16}</math> C ————— C S9 1977</p>

Subdivision of Sec. 9, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
75.90	Wash, 20 lks. wide, 2 ft. deep, drains SW.
78.43	The ¼ sec. cor. of secs. 8 and 9.
SW¼, Section 9	
	From the W 1/16 sec. cor. of secs. 9 and 16.
	N. 0°24'30" W., along the N and S center line of the SW¼, sec. 9.
	Over gently rolling land, through medium mesquite and undergrowth.
8.90	Track road on canal bank, bears S. 60° E. and N. 60° W.
9.10	Graham Canal, 15 lks. wide, flows N. 60° W., thence over rolling land, through medium creosote and scattered mesquite.
19.885	Point for the SW 1/16 sec. cor. at intersection with the E and W center line of the SW¼, sec. 9.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T6S R25E SW 1/16 S9 1977
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
20.30	Fence line, bears E and W.
37.50	Holyoke Wash, 2 chs. wide, 3 ft. deep, drains SW.
39.77	The C-W 1/16 sec. cor. of sec. 9.
From the C-S 1/16 sec. cor. of sec. 9.	
	N. 89°43' W., along the E and W center line of the SW¼, sec. 9.
	Over rolling land, through medium creosote.
6.50	Wash in a draw, 10 lks. wide, 1 ft. deep, drains irregularly South.
19.605	The SW 1/16 sec. cor. of sec. 9.
30.00	Holyoke Wash, 100 lks. wide, 3 ft. deep, drains SW.
39.21	The S 1/16 sec. cor. of secs. 8 and 9.
Subdivision of Sec. 15, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.	



Subdivision of Sec. 15, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
<p>0.20 2.70 9.80 17.00 19.915</p>	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 15 and 22. N. <math>0^{\circ}29'30''</math> W., along the N and S center line of sec. 15. Over rolling land, through medium creosote. Track road, bears NE and SW. South edge of large draw, bears N. <math>50^{\circ}</math> E. and S. <math>50^{\circ}</math> W. Butler Wash, 200 lks. wide, 3 ft. deep, drains S. <math>50^{\circ}</math> W. North edge of large draw, bears N. <math>50^{\circ}</math> E. and S. <math>50^{\circ}</math> W. Point for the C-S <math>\frac{1}{16}</math> sec. cor. of sec. 15.</p>
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E C S <math>\frac{1}{16}</math>   S15 C 1977</p>
<p>29.87 38.00 39.50 39.825</p>	<p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, <math>1\frac{1}{2}</math> ft. high, W of cor. Cor. is located 20 lks. W of a small draw, drains S. Point for the C-N-S <math>\frac{1}{64}</math> sec. cor. of sec. 15; not monumented. Track road, bears NE and SW. Track road, bears N. <math>80^{\circ}</math> E. and S. <math>80^{\circ}</math> W. Point for the C<math>\frac{1}{4}</math> sec. cor., at intersection with the E and W center line of sec. 15.</p>
<p>79.655</p>	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E C<math>\frac{1}{4}</math> S15 1977</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, <math>1\frac{1}{2}</math> ft. high, W of cor. The <math>\frac{1}{4}</math> sec. cor. of secs. 10 and 15.</p>
<p>4.80 15.90</p>	<p>From the <math>\frac{1}{4}</math> sec. cor. of secs. 14 and 15. N. <math>89^{\circ}34'06''</math> W., along the E and W center line of sec. 15. Over washed area, through medium creosote and mesquite. Butler Wash, 75 lks. wide, 3 ft. deep, drains S. <math>60^{\circ}</math> W. North edge of large draw, bears N and S, thence over gently rolling land, through medium creosote.</p>

Subdivision of Sec. 15, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
36.10	Track road, bears NE and SW.
39.10	Track road, bears S. 80° W. and N. 80° E. curving NE.
39.955	The C <sup>1</sup> / <sub>4</sub> sec. cor. of sec. 15.
44.903	Point for the C-E-E-W 1/256 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.
	S15 C-E-E-W 1/256 1977
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
49.85	Point for the C-E-W 1/64 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.
	S15 C-E-W 1/64 1977
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
59.747	Point for the C-W 1/16 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T6S R25E W 1/16 C ————— C
	S15 1977
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N of cor.
79.54	The ¼ sec. cor. of secs. 15 and 16.
	SW¼, Section 15
	From the W 1/16 sec. cor. of secs. 15 and 22.
	N. 0°16' W., along the N and S center line of the SW¼, sec. 15.
	Over rolling land, through medium creosote.
1.20	Graham Canal, 15 lks. wide, flows N. 55°W.
18.30	Draw, drains SW.
19.90	Point for the SW 1/16 sec. cor. at intersection with the E and W center line of the SW¼, sec. 15.

Subdivision of Sec. 15, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E SW 1/16 S15 1977</p>	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p>	
27.80	Track road, bears N. 70° E. and S. 70° W.	
29.85	Point for the C-N-SW 1/64 sec. cor. of sec. 15; not monumented.	
39.80	The C-W 1/16 sec. cor. of sec. 15.	
	—————	
	From the C-S 1/16 sec. cor. of sec. 15.	
	N. 89°31'30" W., along the E and W center line of the SW¼, sec. 15.	
	Over rolling land, through medium creosote.	
8.70	Graded gravel road, bears N and S.	
9.94	Point for the C-E-SW 1/64 sec. cor. of sec. 15; not monumented.	
17.40	Draw, drains SW.	
19.88	The SW 1/16 sec. cor. of sec. 15.	
39.75	The S 1/16 sec. cor. of secs. 15 and 16.	
	—————	
	From the point for the C-E-SW 1/64 sec. cor. of sec. 15.	
	N. 0°25' W., along the N and S center line of the NE¼ of the SW¼, sec. 15.	
	Over rolling land, through medium creosote.	
9.00	Point selected for the witness NE-SW 1/64 sec. cor. of sec. 15.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	
	WC ↑ S15 NE-SW 1/64 1977	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.	
	Cor. is located in a E and W fence line around cemetery.	
9.95	True point for the NE-SW 1/64 sec. cor. at intersection with the E and W center line of the NE¼ of the SW¼ sec. 15 falls between two graves.	

Subdivision of Sec. 15, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS		
	<p>Set a railroad spike flush with ground at true cor. point.</p> <p>From which</p> <p>The NE cor. of fence around cemetery, bears N. 44°31' E., 421 lks. dist.</p> <p>The SE cor. of fence around cemetery, bears S. 75°45' E., 296.5 lks. dist.</p> <p>The SW cor. of fence around cemetery, bears S. 35°56' W., 133 lks. dist.</p> <p>The NW cor. of fence around cemetery, bears N. 16°14' W., 284 lks. dist.</p>	
19.90	<p>The C-E-W 1/64 sec. cor. of sec. 15.</p> <hr/> <p>From the point for the C-N-S 1/64 sec. cor. of sec. 15.</p> <p>N. 89°31'30" W., along the E and W center line of the NE¼ of the SW¼, sec. 15.</p> <p>Over rolling land, through medium creosote.</p>	
2.60	<p>Graded gravel road, bears N. 30° E. curving NW and S. 30° W. curving SW.</p>	
4.955	<p>Point for the C-E-NE-SW 1/256 sec. cor. of sec. 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S15 C-E-NE-SW 1/256 1977</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.</p>	
9.91	<p>The true point for the NE-SW 1/64 sec. cor. of sec. 15.</p>	
19.835	<p>The point for the C-N-SW 1/64 sec. cor. of sec. 15.</p> <hr/> <p style="text-align: center;">Subdivision of Sec. 23, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.</p> <hr/> <p>From the ¼ sec. cor. of secs. 23 and 26.</p> <p>N. 0°43' E., along the N and S center line of sec. 23.</p> <p>Over rolling land through medium creosote and scattered mesquite.</p>	
19.31	<p>Point for the C-S 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>	

Subdivision of Sec. 23, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
38.62	<p style="text-align: center;">T6S R25E C S 1/16   S23 C 1977</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor. for support.</p> <p>Cor. is located on a steep N slope.</p> <p>Point for the C¼ sec. cor. at intersection with the E and W center line of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
66.90	<p style="text-align: center;">T6S R25E C¼ S23 1976</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p> <p>Watson Wash, 75 lks. wide, 4 ft. deep, drains W, as scaled from U. S. Geological Survey Quadrangle Map, Thatcher, Arizona, dated 1960.</p>
70.60	Track road on spur, bears E and W, spur slopes W.
74.60	Wash, 40 lks. wide, 2 ft. deep, drains W, thence across washed area.
79.64	The ¼ sec. cor. of secs. 14 and 23.
36.70	<p>From the ¼ sec. cor. of secs. 23 and 24.</p> <p>N. 89°56' W., along the E and W center line of sec. 23.</p> <p>Over rolling land, through medium creosote.</p> <p>Fence line, bears N and S.</p>
40.19	The C¼ sec. cor. of sec. 23.
59.59	<p>Point for the C-W 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
78.99	<p style="text-align: center;">T6S R25E W 1/16 C ————— C S23 1976</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>The ¼ sec. cor. of secs. 22 and 23.</p>
	<p>SW¼, Section 23</p> <hr style="width: 20%; margin: auto;"/>

Subdivision of Sec. 23, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	From the point for the W 1/16 sec. cor. of secs. 23 and 26.
	N. 0°42' E., along the N and S center line of the SW $\frac{1}{4}$ , sec. 23.
	Over cultivated land.
3.00	Leave cultivated land, edge bears S. 80° E. and N. 80° W.
6.80	Graham Canal, 15 lks. wide, flows NW.
7.10	Telephone line, bears S. 55° E. and N. 55° W.
7.60	Paved road, bears S. 55° E. and N. 55° W., thence over broken land, through medium creosote.
9.30	Power line, bears S. 55° E. and N. 55° W.
19.565	Point for the SW 1/16 sec. cor. at intersection with the E and W center line of the SW $\frac{1}{4}$ , sec. 23.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T6S R25E SW 1/16 S23 1976
	Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.
39.13	The C-W 1/16 sec. cor. of sec. 23.
	_____
	From the C-S 1/16 sec. cor. of sec. 23.
	S. 89°17'30" W., along the E and W center line of the SW $\frac{1}{4}$ , sec. 23.
	Over rolling land, through medium creosote.
19.39	The SW 1/16 sec. cor. of sec. 23.
24.90	Flood control dike, bears N and S.
29.95	Power line, bears S. 40° E. and N. 40° W.
31.10	Paved road, bears S. 40° E. and N. 40° W.
31.80	Telephone line, bears S. 40° E. and N. 40° W.
36.80	Graham Canal, 15 lks. wide, flows N. 5° W.
38.785	The point for the S 1/16 sec. cor. of secs. 22 and 23.
	Subdivision of Sec. 25, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.
	From the point for the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.
	North, along the N and S center line of sec. 25.
	Over cultivated land.

Subdivision of Sec. 25, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
11.00	Leave cultivated land, edge bears S. 30° E. and N. 30° W.
11.30	Graham Canal, 15 lks. wide, flows N. 30° W.
16.70	Telephone line, bears S. 35° E. and N. 35° W.
17.50	Paved road, bears S. 35° E. and N. 35° W., thence over rolling land, through medium creosote.
18.80	Power line, bears N. 35° W. and S. 35° E.
19.88	Point for the C-S 1/16 sec. cor. of sec. 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T6S R25E C S 1/16   S25 C 1976</p>
	Fence cor. bears S. 48° W., 16 lks. dist.; fences extend N and W.
36.90	Fence line, bears S. 75° E. and N. 75° W.
39.76	Point for the C¼ sec. cor. at intersection with the E and W center line of sec. 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T6S R25E C¼ S25 1976</p>
77.30	Draw, drains SW.
79.36	The ¼ sec. cor. of secs. 24 and 25.
	<p>From the ¼ sec. cor. of secs. 25 and 30, on the E boundary of the Tp.</p> <p>N. 89°55' W., along the E and W center line of sec. 25.</p> <p>Over rolling land, through medium creosote.</p>
18.40	Fence line, bears N and S.
19.855	Point for the C-E 1/16 sec. cor. of sec. 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6S R25E E 1/16 C ————— C S25 1976</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.

Subdivision of Sec. 25, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
39.71	The C $\frac{1}{4}$ sec. cor. of sec. 25.
48.40	Fence line, bears S. 75° E. and N. 75° W.
60.40	Spur, slopes S.
61.70	Fence line, bears N and S.
70.40	Power line, bears S. 60° E. and N. 60° W.
71.60	Paved road, bears S. 60° E. and N. 60° W.
72.40	Telephone line, bears S. 60° E. and N. 60° W.
73.50	Graham Canal, 15 lks. wide, flows N. 60° W. curving to N. 80° W., thence bet. cultivated land and canal.
79.26	Concrete ditch, 5 lks. wide, flows S.
79.65	The $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
SE $\frac{1}{4}$ , Section 25	
	From the E 1/16 sec. cor. of secs. 25 and 36.
	N. 0°01' E., along the N and S center line of the SE $\frac{1}{4}$ , sec. 25.
	Over rolling land, through medium creosote along E side of fence line.
9.945	Point for the C-S-SE 1/64 sec. cor. of sec. 25.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	S25 C-S-SE 1/64 1976
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.
	From this point the SW cor. of fence around Graham Cemetery, bears N. 42°13' E., 2.98 chs. dist.
10.60	Fence line, bears N. 60° E. and S. 60° W., 18.5 lks. dist., thence South.
19.89	Point for the SE 1/16 sec. cor. at intersection with the E and W center line of the SE $\frac{1}{4}$ , sec. 25.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T6S R25E SE 1/16 S25 1976
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.
	From this point a bench mark, bears S. 41°48' W., 7.137 chs. dist., monumented with a brass cap in a concrete base 12x12 ins. projecting 4 ins. above the ground, with



Subdivision of Sec. 25, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
	brass cap mkd. Thatcher U. S. Soil Erosion Service Triangulation 1935.
	From this same point the NW cor. of fence around Graham Cemetery, bears S. 34°07' E., 3.487 chs. dist.
39.78	The C-E 1/16 sec. cor. of sec. 25.
	From the S 1/16 sec. cor. of secs. 25 and 30, on the E boundary of the Tp.
	N. 89°53' W., along the E and W center line of the SE $\frac{1}{4}$ , sec. 25.
	Over rolling land, through medium creosote.
9.93	Point for the C-E-SE 1/64 sec. cor. of sec. 25; not monumented.
12.412	Point for the 1/1024 sec. cor. of sec. 25.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	1/1024 1976
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N of cor.
	From this point the NE cor. of fence around Graham Cemetery, bears S. 6°37' E., 2.95 chs. dist.
19.86	The SE 1/16 sec. cor. of sec. 25.
39.71	The C-S 1/16 sec. cor. of sec. 25.
	From the point for the E-E 1/64 sec. cor. of secs. 25 and 36.
	North, along the N and S center line of the SE $\frac{1}{4}$ of the SE $\frac{1}{4}$ , sec. 25.
	Over broken land, through medium creosote.
9.95	Point for the SE-SE 1/64 sec. cor. at intersection with the E and W center line of the SE $\frac{1}{4}$ of the SE $\frac{1}{4}$ , sec. 25; not monumented.
19.90	The point for the C-E-SE 1/64 sec. cor. of sec. 25.
	From the point for the S-S 1/64 sec. cor. of secs. 25 and 30, on the E boundary of Tp.
	N. 89°50' W., along the E and W center line of the SE $\frac{1}{4}$ of the SE $\frac{1}{4}$ , sec. 25.
	Over broken land, through medium creosote.
9.93	The point for the SE-SE 1/64 sec. cor. of sec. 25.

Subdivision of Sec. 25, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
12.415	<p>Point for the 1/1024 sec. cor. of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/1024 1976</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> <p>From this point the SE cor. of fence around Graham Cemetery, bears N. 13°33' E., 2.355 chs. dist.</p>
19.87	<p>The C-S-SE 1/64 sec. cor. of sec. 25.</p>
	<p style="text-align: center;">Subdivision of Sec. 26, T. 6 S., R. 25 E., Gila and Salt River Meridian, Arizona.</p>
	<p>From the point for the ¼ sec. cor. of secs. 26 and 35. N. 0°34' W., along the N and S center line of sec. 26. Over level land, through dense salt cedar and weeds.</p>
18.10	<p>Enter cultivated land, edge bears E and W.</p>
39.68	<p>Point for the C¼ sec. cor. at intersection with the E and W center line of sec. 26; not monumented.</p>
47.40	<p>Graded road, bears E and W.</p>
60.05	<p>Point for the C-N 1/16 sec. cor. of sec. 26; not monumented.</p>
70.235	<p>Point for the C-N-N 1/64 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S26 C-N-N 1/64 1976</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located, 10 lks. E of concrete irrigation ditch, 5 lks. wide, flows N and 40 lks. W of Graham Canal, 15 lks. wide, flows N curving NW.</p>
73.50	<p>Leave cultivated land, bears SE and NW.</p>
73.70	<p>Graham Canal, 15 lks. wide, flows NW.</p>
73.90	<p>Telephone line, bears SE and NW.</p>
74.50	<p>Paved road, bears SE and NW.</p>
75.30	<p>Power line, bears SE and NW, thence over broken land, through medium creosote and mesquite.</p>

Subdivision of Sec. 26, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
80.42	The $\frac{1}{4}$ sec. cor. of secs. 23 and 26.
	From the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.
	N. $89^{\circ}54'$ W., along the E and W center line of sec. 26.
	Over nearly level land, through dense creosote and mesquite.
0.70	Graham Canal, 15 lks. wide, flows SW.
16.50	Talley Wash, 100 lks. wide, 4 ft. deep, drains S. $25^{\circ}$ W.
20.00	Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 26; not monumented.
27.80	Graham Canal, 15 lks. wide, flows N. $50^{\circ}$ W., thence over cultivated land.
40.00	The point for the C $\frac{1}{4}$ sec. cor. of sec. 26.
40.25	Enter dense mesquite, edge bears N and S.
42.50	Power line bears N. $20^{\circ}$ E. and S. $20^{\circ}$ W.
45.80	Leave dense mesquite, edge bears S. $25^{\circ}$ E. and N. $25^{\circ}$ W., thence over cultivated land.
77.00	Leave cultivated land, edge bears SE and NW, thence through dense weeds, salt cedar and willows.
79.31	The point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
	NE $\frac{1}{4}$ , Section 26
	From the point for the C-E $\frac{1}{16}$ sec. cor. of sec. 26.
	N. $0^{\circ}26'30''$ W., along the N and S center line of the NE $\frac{1}{4}$ , sec. 26.
	Over nearly level land, through medium creosote and mesquite.
16.50	Telephone line, bears S. $55^{\circ}$ E. and N. $55^{\circ}$ W.
17.10	Paved road, bears S. $55^{\circ}$ E. and N. $55^{\circ}$ W.
18.50	Power line, bears S. $55^{\circ}$ E. and N. $55^{\circ}$ W.
20.10	Point for the NE $\frac{1}{16}$ sec. cor. at intersection with the E and W center line of NE $\frac{1}{4}$ , sec. 26.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T6S R25E NE $\frac{1}{16}$ S26 1976
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.

Subdivision of Sec. 26, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
30.155	Point for the C-N-NE 1/64 sec. cor. of sec. 26; not monumented.
40.21	<p>The E 1/16 sec. cor. of secs. 23 and 26.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 89°08'30" W., along the E and W center line of the NE<math>\frac{1}{4}</math>, sec. 26.</p> <p>Over nearly level land, through medium creosote and scattered mesquite.</p>
3.90	Talley Wash, 100 lks. wide, 4 ft. deep, drains S. 25° W.
9.90	Graded gravel road, bears N. 10° E. and S. 10° W.
20.04	The NE 1/16 sec. cor. of sec. 26.
22.30	Power line, bears S. 55° E. and N. 55° W.
24.10	Paved road, bears S. 55° E. and N. 55° W.
25.20	Telephone line, bears S. 55° E. and N. 55° W.
30.065	Point for the C-W-NE 1/64 sec. cor. of sec. 26; not monumented.
32.30	Power line, bears N. 30° E. and S. 30° W.
35.078	<p>Point for the C-W-W-NE 1/256 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S26 C-W-W-NE 1/256 1976</p>
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, N of cor.
36.50	Graded gravel road, bears S. 15° E. and N. 15° W.
38.00	Graham Canal, 15 lks. wide, flows N. 15° W.
40.09	<p>The point for the C-N 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the point for the C-W-NE 1/64 sec. cor. of sec. 26.</p> <p>N. 0°31'30" W., along the N and S center line of the NW<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math>, sec. 26.</p> <p>Over nearly level land, through medium creosote and mesquite.</p>
1.90	Graded gravel road, bears E and W.
3.90	Telephone line, bears SE and NW. Power line, bears N. 30° E. and S. 30° W.
4.90	Paved road, bears SE and NW.

Subdivision of Sec. 26, T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS	
6.30	Power line, bears SE and NW.
10.12	Point for the NW-NE 1/64 sec. cor. at intersection with the E and W center line of the NW $\frac{1}{4}$ of the NE $\frac{1}{4}$ , sec. 26; not monumented.
20.24	The point for the W-E 1/64 sec. cor. of secs. 23 and 26.
	<p style="text-align: center;">—————</p> <p>From the point for the C-N-NE 1/64 sec. cor. of sec. 26. N. 88°47' W., along the E and W center line of the NW<math>\frac{1}{4}</math> of the NE<math>\frac{1}{4}</math>, sec. 26.</p>
	Over nearly level land, through medium creosote and mesquite.
10.035	The point for the NW-NE 1/64 sec. cor. of sec. 26.
14.20	Power line, bears SE and NW.
15.055	Point for the C-W-NW-NE 1/256 sec. cor. of sec. 26.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p>S26 C-W-NW-NE 1/256 1976</p>
	Set a steel fence post alongside the cor.
15.50	Paved road, bears SE and NW.
16.20	Telephone line, bears SE and NW.
17.20	Power line, bears S. 5° E. and N. 5° W.
18.70	Graded gravel road, bears N and S.
20.075	The C-N-N 1/64 sec. cor. of sec. 26.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Section 25 of this survey is located 4 miles Northwest of Safford, Arizona. The general elevation of this township ranges from about 2800 to 3300 feet above sea level. The soil is a rocky, sandy loam.</p> <p>The Gila River flows in a Northwesterly direction through the center of the township; bottom land is a rich, silty clay loam, of which most is under cultivation.</p> <p>Access is by way of a paved road which crosses the center of the township in a SE and NW direction. There are several unimproved or lightly gravelled roads throughout the township.</p> <p>The vegetation consist of willows, salt cedar and scattering cotton wood trees along the Gila River and irrigation canals. The remainder of the township consist of creosote, mesquite and cactus.</p>

General Description  
T. 6 S., R. 25 E.,  
Gila and Salt River Meridian, Arizona.

CHAINS

There is no evidence of mining activity or minerals.

The mean of a considerable number of observations of the magnetic declination throughout the township is  $13^{\circ}30'$  E., with a range of  $1^{\circ}$  in local attraction.



CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY  
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22nd day  
 of November, 1976, (I) ~~(We)~~ have dependently resurveyed a portion of  
 the First Standard Parallel South, through Ranges 24 and 25 East; retraced  
 a portion of the south boundary; dependently resurveyed a portion of the  
 East boundary and subdivisional lines, and surveyed subdivisions in  
 Sections 6, 8, 9, 15, 23, 25 and 26, Township 6 South, Range 25 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
 are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my)  
~~(Our)~~ direction; and that said survey has been made in strict conformity with said special instruc-  
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in  
 specific manner described in the foregoing field notes.

September 20, 1977  
 (Date)

*Paul L. Reeves*  
 (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the First  
 Standard Parallel South through Ranges 24 and 25 East, the retracement  
 of a portion of the South boundary, the dependent resurvey of a portion  
 of the East boundary and subdivisional lines and the survey of subdivi-  
 sions in sections 6, 8, 9, 15, 23, 25 and 26, Township 6 South, Range 25  
 East, Gila and Salt River Meridian, Arizona,

executed by Paul L. Reeves, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

NOV 8 1977  
 (Date)

*Bernard W. Fisher*  
 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
 , is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626