

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey of a Portion of the E., Bdy.

and

Subdivisional Lines

and the

Survey of Subdivisions in Sections

25, 26 and 27

Township 7 South, Range 26 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul L. Reeves

Cadastral Surveyor

Under special instructions dated November 22, 19 76, approved November 23, 1976,

_____, which provided for the surveys included under U.S. Survey/Group
Number 592, and assignment instructions dated November 23, 1976.

Survey commenced February 24, 19 77

Survey completed March 14, 19 77

1A

BOOK 5045

INDEX DIAGRAM

Township 7 South, Range 26 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
			12	9	5
30	29	28	11 27	8 26	4 25
			11	7	4
31	32	33	10 34	6 35	3 36

Subdivision, Sec. 25 ----- Page 13
 " " " 26 ----- " 15
 " " " 27 ----- " 17

Township 7 South, Range 26 East,
Gila and Salt River Meridian, Arizona.

CHAINS

The boundaries and subdivisional lines were surveyed in 1875 by Theodore F. White. The North boundary was resurveyed in 1895 by Philip Contzen and resurveyed again in 1960 by Dell Cazier, Glen B. Hatch and Eldon W. Sibley. The east and south boundaries were resurveyed in 1957 by Donald E. Harding, and the north $\frac{1}{2}$ mile bet. secs. 13 and 18 was resurveyed in 1965-66 by Paul G. Bauer and Robert Johnson. The west boundary of sec. 6 was resurveyed in 1966 by Paul G. Bauer and Robert Johnson. A portion of the subdivisional lines were resurveyed and sec. 9 was subdivided in 1966 by Paul G. Bauer and Robert Johnson. The east four miles of the south boundary was retraced in 1969 by Louis D. Gilbert.

The following field notes are those of a dependent resurvey of a portion of the east boundary and subdivisional lines and the survey of subdivisions in sections 25, 26 and 27, Township 7 South, Range 26 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the manual of Surveying Instructions 1973, and the special instructions for Group No. 592, Arizona dated November 22, 1976.

The direction of the lines of this survey were determined by altitude observations on the sun and refer to the true meridian. Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original position; lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The Woodruff Engineering Corners (L.S. 9090) tied to in this survey are harmoniously related to existing original corners, have been recognized by adjacent land owners, and are accepted as the best available evidence of the original corner positions.

The geographic position of the southeast corner of sec. 35, as scaled from the U.S. Geological Survey Quadrangle Map, "Safford, Arizona", prepared in 1960, is as follows:

Latitude $32^{\circ}46.4'$ N. Longitude $109^{\circ}38.8'$ W.

The mean magnetic declination is $13^{\circ}00'$ E.

Dependent Resurvey of a Portion of the East Boundary,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.
(Restoring the 1957 resurvey by Donald E. Harding)

Beginning at the cor. of secs. 25, 30, 31 and 36, monumented with an iron post, $2\frac{1}{2}$ ins. diam., firmly set projecting 5 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the East Boundary,
T. 7 S., R. 26 E., Gila and Salt River Meridian, Arizona.

CHAINS	
	<p style="text-align: center;">T7S R26E R27E S25 S30 S36 S31 1957</p> <p>Mound of stone, 2½ ft. base, 1 ft. high W. of cor. N. 0°11' E., bet. secs. 25 and 30. Over rolling land, through medium creosote and mesquite.</p>
29.10	Telephone line, bears S. 83° E. and N. 83° W.
33.30	Fence line, bears SE and NW.
34.20	Southern Pacific Railroad, bears SE and NW.
35.20	Fence line, bears SE and NW.
39.96	Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. below the surface of a track road on S. bank of canal, bears S. 75° E. and N. 75° W., with brass cap mkd.
	<p style="text-align: center;">T7S R26E R27E ¼ S25 S30 1977</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 2½ ins. diam., 28 ins. long, set 21 ins. in the ground, for a reference monument, bears S. 10° W., 136.4 lks. dist., with brass cap mkd. T7S R26E ¼ S25 RM 90 ft. 1977, and an arrow pointing to the cor.</p> <p>Set a mesquite post, along side the reference monument.</p> <p style="padding-left: 40px;">A steel post, 4 ins. diam., projecting 4 ft. above concrete in gate on S bank of canal, bears N. 54°20' W., 58 lks. dist., mkd. XB0.</p>
40.40	Highline Canal, 25 lks. wide, flows N. 70° W.
47.70	San Simon River, course N. 70° W.
49.00	Leave undergrowth, edge bears S. 70° E. and N. 70° W., thence across cultivated land.
79.92	The cor. of secs. 19, 24, 25 and 30, monumented with a ¼ inch reinforcement rod, projecting 1 inch above a concrete cylinder 6 ins. diam., 6 ins. below surface of S edge of graded road extending E and E edge of paved road which, bears N and S curving West. This position

Dependent Resurvey of a Portion of the East Boundary,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS

is harmoniously related to existing original cors.,
has long been recognized as the cor. by adjacent land
owners, and is accepted as the best available evidence
of the original cor. position; not monumented.

from which

A power pole bears N. 48° E., 65 lks. dist.

A power pole, bears N. 39° W., 92.5 lks. dist.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 7 S., R. 26 E., Gila & Salt River Meridian,
Arizona.

(Restoring the 1875 survey by Theodore F. White)

From the cor. of secs. 1, 2, 35 and 36 on the S bdy.
of the Tp., monumented with an iron post, 2½ ins.
diam., firmly set projecting 4 ins. above the ground,
with brass cap mkd.

T7S R26E
S35|S36
S2|S1
T8S
1957

Cor. is located under E and W power line.

N. 0°07' E., bet. secs. 35 and 36.

Over nearly level land, through dense creosote.

37.20 Track road, bears S. 75° E. and N. 75° W.

39.82 Point for the ¼ sec. cor. of secs. 35 and 36, at pro-
portionate dist.; there is no remaining evidence of
the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins.
in the ground, with brass cap mkd.

T7S R26E
¼
S35|S36
1977

Set a mesquite post, along side the cor.

79.64 The cor. of secs. 25, 26, 35 and 36, monumented with
a local iron pipe, 2½ ins. diam., firmly set project-
ing 14 ins. above the ground, in a mound of stone
2½ ft. base to top, with brass cap mkd.

Woodruff Engineering

26|25
35|36
1973
LS - 9090

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the township.</p>
	<p>N. 89°49' W., bet. secs. 25 and 36.</p>
	<p>Over rolling land, through dense creosote and scattered mesquite.</p>
15.50	<p>Track road, bears S. 35° E. and N. 35° W.</p>
17.50	<p>Graded gravel road, bears S and N curving NW.</p>
29.50	<p>Track road, bears NW and SW.</p>
29.70	<p>Fence line, bears N. 2° W. and S. 2° E. 14 lks. to cor. of fences extending W and N. 2° W., approx. 160 lks., thence NW.</p>
39.74	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 36, monumented with a local brass tablet, concreted in a 3 in. diam. PVC pipe, flush with ground, in a mound of stone, 2½ ft. base, 1 ft. high, with a 14x8x6 inch granite stone in mound mkd. $\frac{1}{4}$, brass cap mkd.</p> <p style="text-align: center;">Woodruff Engineering T7S R26E $\frac{1}{4}$ $\frac{25}{36}$ 1975 LS - 9090</p> <p>Deposit the mkd. stone along side the cor.</p> <p>Set a steel fence post along side the cor.</p> <p>Cor. is located 6 lks. S of fence line, bears S. 88° E. and N. 88° W.</p> <p style="text-align: center;">_____</p> <p>N. 89°49' W., beginning new measurement.</p>
33.20	<p>From this point on line a fence cor. bears North, 17 lks. dist., fences extend S. 88° E. and NW.</p>
39.73	<p>The cor. of secs. 25, 26, 35 and 36.</p>
	<p>N. 0°10' E., bet. secs. 25 and 26.</p>
	<p>Over rolling land through medium creosote and mesquite.</p>
12.60	<p>Fence line, bears SE and NW.</p>
38.10	<p>Telephone line, bears S. 83° E. and N. 83° W.</p>
39.80	<p>The $\frac{1}{4}$ sec. cor. of secs. 25 and 26, monumented with a local iron pipe, 2½ ins. diam., firmly set projecting 10 ins. above the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
	<p style="text-align: center;">Woodruff Engineering T7S R26E $\frac{1}{4}$ 26 25 1973 LS - 9090</p> <p>from which</p> <p style="padding-left: 40px;">A telephone pole, bears S. 0°23' E., 169 lks. dist. Mound of stone, 2 ft. base, 1 ft. high W of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°10' E., beginning new measurement.</p>
19.90	<p>Point for the N 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E N 1/16 S26 S25 1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.</p>
20.20	Fence line, bears S. 85° E. and N. 85° W.
27.00	Highline Canal, 20 lks. wide, flows N. 80° W.
27.20	Track road on canal bank, bears S. 80° E. and N. 80° W., thence across cultivated land.
39.80	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a brass cap, 2½ ins. diam., in a base of concrete 8 ins. in diam., flush with surface of paved road, mkd.</p> <p style="text-align: center;">Woodruff Engineering T7S R26E $\frac{23}{26}$ $\frac{24}{25}$ 1973 LS - 9090</p> <p>Cor. is located 2 lks. N of center of paved road, bears E and W.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E bdy. of township.</p> <p>S. 89°58' W., bet. secs. 24 and 25.</p>
.25	Center of paved road, bears N and S curving to the W, thence along irrigation ditch, bet. cultivated land and paved road.
35.70	Paved road curves to SW, continue along irrigation ditch and cultivated land.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
39.74	Point for the $\frac{1}{4}$ sec. cor. of secs. 24 and 25, falls in a irrigation ditch which flows N from E.
39.863	The witness $\frac{1}{4}$ sec. cor. of secs. 24 and 25, monumented with a brass tablet $2\frac{1}{2}$ ins. in diam., concreted in a PVC pipe 3 ins. diam., projecting 3 ins. above the ground, with brass tablet mkd.
	<p style="text-align: center;">Woodruff Engineering $\frac{1}{4}$ $\frac{24}{25}$ W.C. WC 8.09 → 1975 LS - 9090</p>
	From this point a bench mark bears S. $3^{\circ}34'$ E., 308.5 lks. dist., monumented with a brass tablet $3\frac{1}{2}$ ins. diam., set in a concrete bridge abutment, mkd. U.S. Geological Survey Gaging Station.
	Cor. is located in a N and S fence line.
	S. $89^{\circ}58'$ W., beginning new measurement.
1.90	Enter dense mesquite and salt cedar, edge bears S. 65° E. and N. 65° W.
4.10	San Simon River, 50 lks. wide, course N. 65° W.
19.30	Leave dense undergrowth, edge bears N and S.
19.747	Point for the W $1/16$ sec. cor. of secs. 24 and 25; not monumented.
27.70	Southern Pacific Railroad, bears S. 60° E. and N. 60° W.
29.10	Curve in paved road, bears S. 85° E. and W.
39.617	The cor. of secs. 23, 24, 25 and 26.
	From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of township, monumented with an iron post, $2\frac{1}{2}$ ins. diam., 6 ins. below surface of N and S graded gravel road, with brass cap mkd.
	<p style="text-align: center;">T7S R26E $\frac{S34 S35}{S3 S2}$ T8S 1957</p>
	from which
	A power pole, bears S. $84^{\circ}07'$ E., 181.5 lks. dist.
	An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45° W., 83.3 lks. dist., with brass cap mkd. T7S R26E S34 RM 55 ft. 1977, and an arrow pointing to the cor.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS		
39.79	<p>Deposit broken glass at base of reference monument.</p> <p>Add the mks. 1977 to the sec. cor.</p> <p>Sec. cor. is located 18 lks. N of E and W power line.</p> <p>N. 0°12' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land, along graded gravel road.</p> <p>Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. below the surface of a N and S graded gravel road, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E ¼ S34 S35 1977</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45° E., 60.6 lks. dist., with brass cap mkd. T7S R26E ¼S 35 RM 40 ft. 1977, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground for a reference monument, bears S. 45° W., 60.6 lks. dist., with brass cap mkd. T7S R26E ¼ S34 RM 40 ft. 1977, and an arrow pointing to the cor.</p>	
79.58	<p>The cor. of secs. 26, 27, 34 and 35, monumented with a local iron pipe 2½ ins. diam., firmly set, projecting 8 ins. above the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">Woodruff Engineering T7S R26E 27 26 34 35 1973 LS - 9090</p>	
39.88	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°49' W., bet. secs. 26 and 35.</p> <p>Over gently rolling land, through dense creosote and scattered mesquite.</p> <p>The ¼ sec. cor. of secs. 26 and 35, monumented with a local iron pipe, 2½ ins. diam., firmly set, projecting 6 ins. above the ground in a mound of stone, 2 ft. base to top, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
	Woodruff Engineering T7S R26E $\frac{1}{4} \frac{26}{35}$ 1973 LS - 9090
	<hr/> N. 89°49' W., beginning new measurement.
19.94	Point for the W 1/16 sec. cor. of secs. 26 and 35. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T7S R26E W 1/16 $\frac{S26}{S35}$ 1977
	Raise a mound of stone, 2 ft. base, 1 ft. high N of cor.
38.60	Graded gravel road, bears N. 25° E. and S. 25° W. curving S.
39.60	Graded gravel road, bears N and S.
39.88	The cor. of secs. 26, 27, 34 and 35.
	<hr/> N. 0°15' E., bet. secs. 26 and 27. Over rolling land, through medium creosote and mesquite.
39.40	Fence line, bears E and W.
39.80	The ¼ sec. cor. of secs. 26 and 27, monumented with a local iron pipe, 2½ ins. diam., firmly set projecting 10 ins. above the ground, in a mound of stone, with brass cap mkd.
	Woodruff Engineering T7S R26E $\frac{1}{4} \frac{27}{26}$ 1973 LS - 9090
	<hr/> N. 0°15' E., beginning new measurement.
7.60	Telephone line, bears S. 83° E. and N. 83° W.
18.85	Dirt flood control dike, bears S. 80° E., 50 lks. and N. 80° W.
19.905	Point for the N 1/16 sec. cor. of secs. 26 and 27. Set a brass tablet, 3¼ ins. diam., 3½ ins. stem, in drill hole in concrete abutment for a cattle guard, 12 ins. below surface of graded gravel road, bears S. 25° E. and N. 25° W., mkd.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS

T7S R26E
N 1/16
S27|S26
1977

from which

An iron post 28 ins. long, 2½ ins. diam., set 12 ins. in the ground, in a mound of stone 2½ ft. base to top, for a reference monument, bears S. 78°37' E., 91.6 lks. dist., with brass cap mkd. T7S R26E N 1/16 S26 RM 60.5 ft. 1977, and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, for a reference monument, bears S. 43°33' W., 36.4 lks. dist., with brass cap mkd. T7S R26E N 1/16 S27 RM 24 ft. 1977, and an arrow pointing to the cor.

- 27.70 Highline Canal, 20 lks. wide, flows N. 85° W.
- 27.90 Track road on canal bank, bears S. 85° E. and N. 85° W.
- 39.20 Power and telephone lines, bear E and W.
- 39.25 Paved road, bears E and W.
- 39.81 The cor. of secs. 22, 23, 26 and 27, monumented with a local iron pipe 2¼ ins. diam., set flush with surface of road shoulder, with brass cap mkd.

Woodruff Engineering
T7S R26E
S22|S23
S27|S26
1973
LS - 9090

Cor. is located 80 lks. N. 65° E. of intersection of paved road, bears N, S, E, and W, and 10 lks. S of concrete irrigation ditch, 5 lks. wide, flows E from W.

- From the cor. of secs. 23, 24, 25 and 26.
- N. 89°48' W., bet. secs. 23 and 26.
- Along N side of paved road.
- 39.81 The ¼ sec. cor. of secs. 23 and 26, monumented with a local iron pipe, 2½ ins. diam., firmly set projecting 8 ins. above the ground, with brass cap mkd.

Woodruff Engineering
T7S R26E
¼ 23
26
1973
LS - 9090

Cor. is located at S edge of a concrete irrigation ditch, 10 lks. wide, flows W, and 27 lks. N of center of E and W paved road.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
	<p>N. 89°48' W., beginning new measurement.</p> <p>.90 Concrete irrigation ditch, 5 lks. wide, flows N.</p> <p>19.905 Point for the W 1/16 sec. cor. of secs. 23 and 26; not monumented.</p> <p>39.81 The cor. of secs. 22, 23, 26 and 27.</p>
	<p>From the cor. of secs. 3, 4, 33 and 34, on the S bdy. of Township, monumented with an iron post, 2½ ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E S33 S34 S4 S3 T8S 1957</p> <p>Cor. is located at the cor. fences extending E, S, and W, and 20 lks. N of E and W powerline.</p> <p>N. 0°03' E., bet. secs. 33 and 34.</p> <p>Over rolling land, through dense creosote and scattered mesquite.</p> <p>39.84 Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E ¼ S33 S34 1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.</p> <p>Cor. is located 1 link E of N and S fence line, and 21 lks. N of fence cor., fences extend N, E and W.</p> <p>79.68 The cor. of secs. 27, 28, 33 and 34, monumented with a local iron pipe, 2½ ins. diam., firmly set, projecting 4 ins. above ground, in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">Woodruff Engineering T7S R26E 28 27 33 34 1974 LS - 9090</p> <p>Cor. is located 1 link W of N and S fence line.</p> <p>From this point a local iron pipe, 2½ ins. diam., firmly set projecting 15 ins. above the ground, bears</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
39.70	<p>S. 3°58' W., 76.6 lks. dist., with cap mkd.</p> <p style="text-align: center;">T7S R26E S28 S27 S33 S34 GBS 61</p> <hr/> <p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°51' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through dense creosote and scattered mesquite.</p> <p>Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E ¼ S27 S34 1977</p>
79.40	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high N of cor.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°09' E., bet. secs. 27 and 28.</p> <p>Over rolling land, through medium creosote and scattered mesquite.</p>
18.80 39.84	<p>E end of a dirt flood control dike, extends W.</p> <p>The ¼ sec. cor. of secs. 27 and 28, monumented with a local iron pipe, 2½ ins. diam., firmly set, projecting 10 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">Woodruff Engineering T7S R26E ¼ S28 S27 1973 LS - 9090</p> <p>Cor. is located 47 lks. W of a fence line, bears S. 1° E. and N. 1° W.</p> <hr/> <p>N. 0°09' E., beginning new measurement.</p>
16.90	<p>Telephone line, bears S. 83° E. and N. 83° W.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
19.92	<p>The N 1/16 sec. cor. of secs. 27 and 28, monumented with a reinforcement rod ½ inch in diam., projecting 4 ins. above the ground, with metal tag attached and mkd. LS-9090.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E N 1/16 S28 S27 1977</p> <p>Deposit the reinforcement rod inside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.</p> <p>Cor. is located in a N and S fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' E., beginning new measurement.</p>
1.20	<p>Fence cor., fences extend N. 1° W., E and S. 1° E.</p>
11.30	<p>Highline Canal, 15 lks. wide, flows N. 83° W.</p>
11.60	<p>Track road on canal bank, bears S. 80° E. and N. 80° W.</p>
11.90	<p>Graded gravel road, bears N and SW.</p>
19.00	<p>Road intersection, paved roads extend N, E and W, graded gravel road extends S.</p>
19.92	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a local iron pipe, 2½ ins. diam., set flush with surface of paved road, with brass cap mkd.</p> <p style="text-align: center;">Woodruff Engineering T7S R26E <u>21 22</u> <u>28 27</u> 1973 LS - 9090</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>
	<p>N. 89°48' W., bet. secs. 22 and 27.</p>
	<p>Over level land along N side of paved road and S edge of cultivated land.</p>
39.76	<p>Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p>
79.30	<p>Concrete irrigation ditch, 5 lks. wide, flows N.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.

CHAINS	
79.35	Telephone line, bears N and S.
79.51	The cor. of secs. 21, 22, 27 and 28.
Subdivision of Sec. 25, T. 7 S., R. 26 E. Gila & Salt River Meridian, Arizona.	
From the $\frac{1}{4}$ sec. cor. of secs. 25 and 36.	
N. $0^{\circ}10'30''$ E., along the N and S center line of sec. 25.	
Over gently rolling land, through medium creosote and cacti.	
17.80	Fence line, bears S. 30° E. and N. 30° W.
33.40	Telephone line, bears S. 83° E. and N. 83° W.
38.50	Graded gravel road, bears E, curving SE, and W, curving NW.
39.88	Point for the $C\frac{1}{4}$ sec. cor. at intersection with the E and W center line of sec. 25.
Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. below surface of a N and S track road, with brass cap mkd.	
T7S R26E $C\frac{1}{4}$ S25 1977	
from which	
An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, for a reference monument, bears S. 50° E., 33.3 lks. dist., with brass cap mkd., T7S R26E $C\frac{1}{4}$ S25 RM 22 ft. 1977, and an arrow pointing to the cor.	
An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 21 ins. in the ground, for a reference monument, bears S. 50° W., 33.3 lks. dist., with brass cap mkd. T7S R26E $C\frac{1}{4}$ S25 RM 22 ft. 1977, and an arrow pointing to the cor.	
The section cor. is located 5 lks. N of a gate in fence line, bears E and W.	
56.30	Highline Canal, 15 lks. wide, flows N. 80° W.
56.50	Track road on canal bank, bears S. 80° E. and N. 80° W., thence over cultivated land.
59.815	Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 25; not monumented.
59.90	Leave cultivated land, edge bears S. 35° E. and N. 35° W.
63.10	Southern Pacific railroad, bears S. 60° E. and N. 60° W.

Subdivision of Sec. 25, T. 7 S., R. 26 E.
Gila & Salt River Meridian, Arizona.

CHAINS	
64.00	Curve in graded gravel road, bears N and S. 60° E.
76.00	Paved road bears N. 85° W., curving W and N. 70° E., curving E.
77.40	San Simon River, course N. 65° W.
79.75	The true point for the ¼ sec. cor. of secs. 24 and 25.
	From the ¼ sec. cor. of secs. 25 and 30 on the E bdy. of the township.
	N. 89°56' W., along the E and W center line of sec. 25.
	Over gently rolling land, through dense mesquite.
5.40	Fence line, bears S. 50° E. and N. 50° W.
6.60	Southern Pacific railroad, bears S. 50° E. and N. 50° W.
7.40	Fence line, bears S. 50° E. and N. 50° W., thence over rolling land, through medium creosote and scattered mesquite.
34.80	Fence cor., fences extend N. 2° E. and W.
39.74	The C¼ sec. cor. of sec. 25.
46.50	Fence cor.: fences extend E and NW 1 chain, thence N.
46.80	Graded gravel road, bears S. 55° E., curving E and N. 55° W., curving N.
53.30	Fence line, bears S. 30° E. and N. 30° W.
59.61	Point for the C-W 1/16 sec. cor. of sec. 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T7S R26E C $\frac{W 1/16}{S25}$ C 1977</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high N of cor.
79.48	The ¼ sec. cor. of secs. 25 and 26.
	<p style="text-align: center;"><u>NW ¼, Section 25</u></p>
	From the C-W 1/16 sec. cor. of sec. 25.
	N. 0°10' E., along the N and S center line of the NW¼, sec. 25.
	Over rolling land, through medium creosote and cacti.


Subdivision of Sec. 25, T. 7 S., R. 26 E.
Gila & Salt River Meridian, Arizona.

CHAINS	
19.10	Fence line, bears S. 85° E. and N. 85° W.
19.92	Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW¼, sec. 25.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	T7S R26E NW 1/16 S25 1977
	Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.
	Cor. is located in a thicket.
21.10	Highline Canal, 20 lks. wide, flows N. 70° W.
21.30	Track road on canal bank, bears S. 70° E. and N. 70° W., thence across cultivated land.
35.10	Southern Pacific railroad, bears S. 60° E. and N. 60° W.
39.30	Paved road, bears E and W.
39.84	The point for the W 1/16 sec. cor. of secs. 24 and 25.
	<p style="text-align: center;">_____</p> From the point for the C-N 1/16 sec. cor. of sec. 25. West, along the E and W center line of the NW¼, sec. 25. Over cultivated land.
6.00	Graded gravel road, bears N and S.
15.00	Leave cultivated land, bears S. 70° E. and N. 70° W.
16.20	Track road on canal bank, bears S. 70° E. and N. 70° W.
16.70	Highline Canal, 20 lks. wide, flows N. 70° W., thence over rolling land, through medium creosote and mesquite.
19.87	The NW 1/16 sec. cor. of sec. 25.
39.74	The N 1/16 sec. cor. of secs. 25 and 26.
	Subdivision of Sec. 26, T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.
	From the ¼ sec. cor. of secs. 26 and 35. N. 0°12' E. along the N and S center line of sec. 26. Over rolling land, through medium creosote, cacti and scattered mesquite.
39.79	The C¼ sec. cor. of sec. 26, monumented with a local iron pipe 2½ ins. diam., firmly set projecting 10 ins. above the ground, with brass cap mkd.

Subdivision of Sec. 26, T. 7 S., R. 26 E.,
Gila & Salt River Meridian, Arizona.

CHAINS

Woodruff Engr.
S-26



Mound of stone, 3 ft. base, 1½ ft. high W of cor.

Fence cor. bears S. 5° E., 44.5 lks. dist., fences extend S and W.

N. 0°12' E., beginning new measurement.

- 2.00 Track road, bears E and W.
- 4.20 Telephone line, bears S. 85° E. and N. 85° W.
- 19.90 Point for the C-N 1/16 sec. cor. of sec. 26, not monumented.
- 28.20 Highline Canal, 20 lks. wide, flows W.
- 28.40 Track road on canal bank, bears E and W, thence across cultivated land.
- 39.20 Power line, bears E and W.
- 39.50 Paved road, bears E and W.
- 39.80 The ¼ sec. cor. of secs. 23 and 26.

From the ¼ sec. cor. of secs. 25 and 26.

N. 89°49' W., along the E and W center line of sec. 26.

Over rolling land, through medium creosote and cacti.

- 14.70 Telephone line, bears S. 83° E. and N. 83° W.
- 39.84 The C¼ sec. cor. of sec. 26.
- 59.765 Point for the C-W 1/16 sec. cor. of sec. 26.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

T7S R26E
C $\frac{W \ 1/16}{S26}$ C
1977

Raise a mound of stone, 3 ft. base, 1½ ft. high N of cor.

Cor. is located 39 lks. N of a E and W fence line.

- 69.10 Graded gravel road, bears S. 30° E. and N. 30° W.

Subdivision of Sec. 26, T. 7 S., R. 26 E.,
Gila & Salt River Meridian, Arizona.

CHAINS	
79.69	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
<p>NW $\frac{1}{4}$, Section 26</p> <hr/>	
<p>From the C-W 1/16 sec. cor. of sec. 26.</p>	
<p>N. 0°13' E., along the N and S center line of the NW$\frac{1}{4}$, sec. 26.</p>	
<p>Over gently rolling land, through medium creosote and cacti.</p>	
5.30	Telephone line, bears S. 83° E. and N. 83° W.
19.90	Point for the NW 1/16 sec. cor. at intersection with the E and W center line of the NW $\frac{1}{4}$, sec. 26.
<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
<p>T7S R26E NW 1/16 S26 1977</p>	
<p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high W of cor.</p>	
26.00	Highline Canal, 20 lks. wide, flows W.
26.30	Track road on canal bank, bears E and W, thence across cultivated land.
39.00	Power line, bears E and W.
39.50	Paved road, bears E and W.
39.80	The point for the W 1/16 sec. cor. of secs. 23 and 26.
<hr/>	
<p>From the point for the C-N 1/16 sec. cor. of sec. 26.</p>	
<p>N. 89°48'30" W., along the E and W center line of the NW$\frac{1}{4}$, sec. 26.</p>	
<p>Over rolling land, through medium creosote and cacti.</p>	
19.91	The NW 1/16 sec. cor. of sec. 26.
39.83	The N 1/16 sec. cor. of secs. 26 and 27.
<p>Subdivision of Sec. 27, T. 7 S., R. 26 E., Gila & Salt River Meridian, Arizona.</p>	
<p>From the $\frac{1}{4}$ sec. cor. of secs. 27 and 34.</p>	
<p>N. 0°12' E., along the N and S center line of sec. 27.</p>	
<p>Over rolling land, through dense creosote and scattered mesquite and cacti.</p>	

Subdivision of Sec. 27, T. 7 S., R. 26 E.,
Gila & Salt River Meridian, Arizona.

CHAINS	
39.82	<p>Point for the $C\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 27.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E $C\frac{1}{4}$ S27 1977</p>
48.70	<p>Fence line, bears E and W.</p>
52.10	<p>Telephone line, bears S. 83° E. and N. 83° W.</p>
59.735	<p>Point for the C-N $1/16$ sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R26E C N $1/16$ S27 C 1977</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W of cor.</p>
64.00	<p>Highline Canal, 20 lks. wide, flows W.</p>
64.30	<p>Track road on canal bank, bears E and W, thence across cultivated land.</p>
78.60	<p>Power line, bears E and W.</p>
79.00	<p>Paved road, bears E and W.</p>
79.65	<p>The point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 26 and 27.</p> <p>N. $89^\circ 50'$ W., along the E and W center line of sec. 27.</p> <p>Over rolling land, through medium creosote and cacti.</p>
20.45	<p>Fence line, bears NW and SE, 55 lks. to fence cor.; fences extend E, S, and NW.</p>
39.73	<p>The $C\frac{1}{4}$ sec. cor. of sec. 27.</p>
79.46	<p>The $\frac{1}{4}$ sec. cor. of secs. 27 and 28.</p>
<p>GENERAL DESCRIPTION</p> <p>Section 27 of this survey is located 3 miles Southeast of Safford, Arizona. The general elevation of the area surveyed within this Township ranges from about 2978 to 3080 feet above sea level. The soil is a rocky, sandy loam, over the higher elevations.</p>	

Subdivision of Sec. 27, T. 7 S., R. 26 E.,
Gila & Salt River Meridian, Arizona.

CHAINS

The San Simon River flows in a Northwesterly direction through the NE corner of Section 25; bottom land is a rich, silty clay loam, of which most is under cultivation.

Access is by way of a number of unimproved and graded gravel roads.

The vegetation consist of willows, salt cedar and scattering cottonwood trees along the San Simon River and canal banks. Vegetation on the remainder of the area surveyed consists of creosote, mesquite and cactus.

There is no evidence of mining activity or minerals.

The mean of a considerable number of observations of the magnetic declination through out the Township is 13°00' E., with a range of 1° in local attraction.

CHAINS		

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Survey Aid
John J. Bulinski	Survey Aid
Dirk L. Peterson	Survey Aid
Duane R. Ferneau	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 22 nd day of November, 1976, (I) ~~(We)~~ have dependently resurveyed a portion of the east boundary and subdivisional lines, and surveyed subdivisions in sections 25, 26, and 27, Township 7 South, Range 26 East,

of the Gila & Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my) ~~(US)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 24, 1977 (Date) Paul L. Reeves (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the east boundary and subdivisional lines and the survey of subdivisions in sections 25, 26, and 27, Township 7 South, Range 26 East, Gila & Salt River Meridian, Arizona,

executed by Paul L. Reeves, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

JAN 20 1978 (Date) Roger T. Barron Acting (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626