

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

 Dependent Resurvey

 of a

 Portion of the East Boundary of the

 San Carlos Indian Reservation, T. 4 S., R. 22 E.

 the South Boundary of the (abandoned)

 Fort Thomas Military Reservation

 and a Portion of

 the East Boundary and Subdivisional Lines

 with a

 Survey of Subdivisions in Sections

 4, 9, 10, 11, 13, 14, 23 and 29

 of

 Township 5 South, Range 23 East

Of the Gila and Salt River Meridian,
 In the State of Arizona

EXECUTED BY

Paul L. Reeves Cadastral Surveyor

 Under the Supervision of

Boyd S. Owens, Chief, Branch of Cadastral Survey

Under special instructions dated December 1, 1975, approved December 4, 1975,

_____, which provided for the surveys included under U.S. Survey/Group
 Number 581, and assignment instructions dated December 1, 1975.

Survey commenced February 9, 1976

Survey completed December 14, 1976

BOOK 5 055

INDEX DIAGRAM

Township 5 South, Range 23 East

| | | | | | |
|-------------|-------------|----------------------|-------------|-------------|-----------|
| 6 | 5 28 27 | 3 4 4 22 27 | 8 17 21 | 2 18 | 1 |
| 7 | 8 26 | 9 20 25 | 10 16 19 | 11 10 15 | 12 10 |
| 18 | 17 | 16 | 15 14 13 | 14 9 13 | 13 6 8 |
| 19 32 32 | 20 33 | 21 | 22 12 | 23 7 11 | 24 5 6 |
| 30 32 30 | 29 24 31 | 28 | 27 | 26 | 25 5 |
| 31 30 | 32 23 | 33 | 34 | 35 | 36 4 |

| | | | | |
|-------------|---------|----|-------|-------|
| Subdivision | Section | 4 | Pages | 33-37 |
| " | " | 9 | " | 37-41 |
| " | " | 10 | " | 41-42 |
| " | " | 11 | " | 42-44 |
| " | " | 13 | " | 44-48 |
| " | " | 14 | " | 48-50 |
| " | " | 23 | " | 50-51 |
| " | " | 29 | " | 51-53 |

T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of a dependent resurvey of a portion of the East boundary of the San Carlos Indian Reservation, T. 4 S., R. 22 E.; the resurvey of the South boundary of the (abandoned) Fort Thomas Military Reservation, and the resurvey of a portion of the East boundary and subdivisional lines and a survey of subdivisions in secs. 4, 9, 10, 11, 13, 14, 23 and 29, T. 5 S., R. 23 E., G&SR Meridian, Arizona, sufficiently to establish the boundaries of the Federal lands therein.

The exterior boundaries and subdivisional lines were surveyed in 1875 by Theodore F. White, The Camp Goodwin Military Reservation (abandoned) through the Tp. was surveyed in 1888 by Clarence H. Wallace. The Fort Thomas Military Reservation (abandoned) was surveyed by Earl D. Thomas, an Army Lieutenant, in 1876. Lorenzo D. Chillson surveyed a portion of the subdivisional lines, resurveyed a portion of the North boundary and the boundaries of the Fort Thomas Military Reservation (abandoned) within the Tp., in 1894. The South boundary and South four and one half miles of the West boundary were resurveyed by Phillip Contzen in 1900. The East half mile of the South boundary was resurveyed in 1916 by Albert B. Rich. The North one mile of the East boundary and a portion of the subdivisional lines were resurveyed and section 1 subdivided in 1965 by Leonard Murphy. The East four miles of the North boundary was resurveyed in 1965-67 by Leonard Murphy and Paul G. Bauer. The South boundary was resurveyed in 1967 by Kenneth D. Herman and Gary Oviatt. The East boundary of the San Carlos Indian Reservation was surveyed by Paul Riecker in 1883; resurveyed by Charles E. Walker in 1887, a portion by H. L. Baldwin in 1915, and a portion by Ray Harpin in 1974.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions 1973, and the special instructions for Group No. 581, Arizona dated December 1, 1975.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the $\frac{1}{4}$ sec. cor. of Secs. 31 and 36 on the east boundary of the township, as scaled from the U.S. Geological Survey Quadrangle Map, "Thatcher, Arizona", prepared in 1960 is as follows:

Latitude $32^{\circ}57.3'$ N. Longitude $109^{\circ}55.9'$ W.

The mean magnetic declination is $13^{\circ}30'$ E.

Dependent Resurvey of a Portion of E. bdy.,
San Carlos Indian Reservation, T. 4 S., R. 22 E.,
Gila and Salt River Meridian, Arizona.

CHAINS

Dependent Resurvey of a Portion of E. bdy., San Carlos Indian Reservation, T. 4 S., R. 22 E., G&SR Meridian, Arizona.

(Restoring the 1974 Resurvey by Ray Harpin)

Beginning at the 2 mile cor., monumented with an iron post 3 ins. diam., firmly set projecting 10 ins. above ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

SCIR | T4S
2 M | R22E
 | S23

74
1915

Cor. is located in N-S fence line.

S. 0°11' E., on line 2-2½.


Over rolling land, through medium undergrowth, along a fence line.

7.13 From this pt. on line, a granite stone, 24x18 ins. firmly set projecting 10 ins. above the ground, bears East, 0.6 lks. dist., mkd. CTMR CC on the East face, cor. is located at the intersection of fences extending N, S and E.

8.07 From this pt. on line, a brass tablet 3 ins. diam., bears West, 5.4 lks. dist., mkd. U.S. Public Health Service ACO Operative Project 38+29.5.

30.89 Point for the initial cor. of the (abandoned) Fort Thomas and Camp Goodwin Military Reservations, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.



Cor. is located 1 link E of N and S fence line and 20 lks. E of graded road, bears N and S.

40.01 The 2½ mile cor., monumented with an iron post, 2½ ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

SCIR | T4N
2½ M | R22E

1974

Remark the cap to read

Dependent Resurvey of a Portion of E. bdy.,
San Carlos Indian Reservation, T. 4 S., R. 22 E.,
Gila and Salt River Meridian, Arizona.

CHAINS

| | |
|------|------|
| SCIR | T4S |
| 2½ M | R22E |
| | 1976 |
| | 1974 |

Cor. is located in a fence line, bears N and S.

Dependent Resurvey of the South boundary of the
(abandoned) Fort Thomas Military Reservation.
(Restoring the 1894 Resurvey by Lorenzo Dow Chillson)

From the initial cor. on the E bdy. of San Carlos
Indian Reservation, heretofore described.

S. 59°08' E., on the S bdy. of the (abandoned) Fort
Thomas Military Reservation.

Over cultivated land.

- 26.00 Track road bears N. 30° E., and S. 30° W., thence
through dense mesquite.
- 29.50 Goodwin Wash, 100 lks. wide, drains N. 30° E.
- 32.00 Leave dense mesquite, bears N. 30° E. and S. 30° W.,
thence over rolling land through medium creosote and
scattered mesquite.
- 102.00 Graded dirt road, bears NE and SW.
- 104.40 Power line, bears NE and SW.
- 108.70 Fence line, bears E and W.
- 115.70 Fence line, bears N and S.
- 208.01 From this point on line, the closing cor. for secs. 31
and 32, of T. 4 S., R. 23 E., on the S bdy. of the
(abandoned) Fort Thomas Military Reservation, bears
South 1 link dist., mon. with a granite stone, 12x10 ins.
firmly set, projecting 10 ins. above ground, mkd. CTMR CC
on N face, with mound of stone, 3 ft. base, 1 ft. high S.
- 210.00 Fence line, bears N and S.
- 258.36 From this pt. on line, cor. no. 2 of the (abandoned)
Camp Goodwin Military Reservation bears S, 45° W.,
2.01 chs. dist., monumented with a granite stone,
16x10x8 ins. loosely set in a mound of stone, 2 ft.
base, 6 ins. high, stone mkd. CGMR on south face,
- 266.00 Fence line, bears N. 35° E. and S. 35° W.
- 302.06 Point for the closing cor., of secs. 4 and 5, T. 5 S.,
R. 23 E.; hereinafter described.
- From this point the cor. of secs. 4, 5, 32 and 33,
Tps. 4 and 5 S., R. 23 E., bears N, 0°32' W., 19.42 chs.,
dist., hereinafter described.

Dependent Resurvey of the South boundary of the
(abandoned) Fort Thomas Military Reservation

| CHAINS | | |
|--|--|--|
| 394.48 | Point for the closing cor. of secs. 3 and 4; not monumented. | |
| | From this point the cor. of secs. 3, 4, 9 and 10, bears S. 0°32' W., 12.925 chs. dist.; hereinafter described. | |
| 402.10 | Paved road, bears N. 40° E. and S. 40° W. | |
| 408.30 | Power line, bears N. 25° E. and S. 25° W. | |
| 408.35 | Fence line, bears N. 25° E. and S. 25° W. | |
| 419.57 | Point for the closing cor. of secs. 3 and 10; not monumented. | |
| | From this point the cor. of secs. 3, 4, 9 and 10, bears S. 89°53' W., 21.66 chs. dist., hereinafter described. | |
| 460.90 | Track road, bears NE and SW. | |
| 486.20 | Fence line, bears N and S. | |
| 486.30 | Track road, bears N and S. | |
| 486.43 | Point for the closing cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor. Also the SE corner of the (abandoned) Fort Thomas Military Reservation; not monumented. | |
| | From this point the ¼ sec. cor. of secs. 10 and 11, bears S. 0°12' W., 5.91 chs. dist.; hereinafter described. | |
| <p>Dependent Resurvey of a Portion of East boundary Township 5 South, Range 23 East, Gila and Salt River Meridian, Arizona. (Restoring the 1875 survey by Theodore F. White)</p> | | |
| <p>From the ¼ sec. cor. of secs. 31 and 36, monumented with an angle iron, 2 ft. long, projecting 6 ins. above the ground, from which the remains of original bearing tree</p> | | |
| <p>A mesquite stump, 9 ins. diam., bears N. 27° W., 60 lks. dist., no marks visible. (Record N. 30¾° W.)</p> | | |
| At the cor. point | | |
| Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd. | | |
| <p>T5S R23E R24E ¼ S36 S31 1976</p> | | |
| Deposit the angle iron alongside the iron post. | | |

Dependent Resurvey of a Portion of East boundary
Township 5 South, Range 23 East, Gila and
Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | <p>Fence cor. bears S. 45° E., 1 lk. dist., fences extend N, E and S.</p> |
| | <p>N. 0°13' W., bet. secs. 31 and 36.</p> |
| | <p>Over nearly level land, through medium undergrowth.</p> |
| 16.00 | <p>Dodge - Nevada Canal, 10 lks. wide, flows N. 30° W. from S. 80° E., thence along track road and cultivated field.</p> |
| 40.01 | <p>Point for the cor. of secs. 25, 30, 31 and 36. At proportionate dist.; there is no remaining evidence of the original cor.; not monumented. Cor. point is in graded road, bears E and W.</p> |
| | <p>Land, nearly level. Soil, sand loam. Timber, none. Undergrowth, creosote, mesquite, salt cedar and cacti.</p> |
| | <p>N. 0°13' W., bet. secs. 25 and 30.</p> |
| | <p>Over level cultivated fields.</p> |
| 40.01 | <p>Point for the ¼ sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> |
| 80.02 | <p>Point for the cor. of secs. 19, 24, 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> |
| | <p>Land, level farm land. Soil, sandy loam. Timber, none. Undergrowth, none.</p> |
| | <p>N. 0°13' W., bet. secs. 19 and 24.</p> |
| | <p>Over level cultivated field.</p> |
| 0.10 | <p>Graded road bears E and W.</p> |
| 22.60 | <p>Fence and cultivated field, bears S. 25° E. and N. 25° W.</p> |
| 23.00 | <p>Southern Pacific Railroad, bears S. 25° E. and N. 25° W., as scaled from U.S. Geological Quadrangle, Thatcher, Arizona, 1960.</p> |
| 27.00 | <p>Highway No. 70, bears S. 25° E. and N. 25° W., as scaled from U.S. Geological Quadrangle, Thatcher, Arizona, 1960.</p> |
| 34.50 | <p>Fort Thomas Canal, 10 lks. wide, flows NW, as scaled from U.S. Geological Quadrangle, Thatcher, Arizona, 1960.</p> |
| 40.01 | <p>Point for the ¼ sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> |

Dependent Resurvey of a Portion of East boundary
Township 5 South, Range 23 East, Gila and
Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| 40.30 | Graded road, bears E and W, thence through dense timber and undergrowth, along fence line. |
| 80.02 | <p>Point for the cor. of secs. 13, 18, 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> <p>Land, level. Soil, sandy loam. Timber, N½ mesquite and scattering cotton wood. Undergrowth, mesquite.</p> |
| | N. 0°13' W., bet. secs. 13 and 18. |
| | Over nearly level land, through dense timber and undergrowth. |
| 0.20 | Track road, bears E and W. |
| 20.40 | Enter open cultivated field, bears E and W. |
| 39.60 | Enter dense undergrowth, bears E and W. |
| 40.01 | Point for the ¼ sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 73.50 | Left bank of Gila River, bears SE and NW. |
| 78.50 | Right bank of Gila River. |
| 80.02 | <p>Point for the cor. of secs. 7, 12, 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> <p>From this point the ¼ sec. cor. of secs. 1 and 6, bears N. 0°13' W., 120.03 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E R24E ¼ S1 S6 1965</p> |
| | Mound of stone, 2½ ft. base, 2 ft. high W of cor. |
| | This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered. |
| | <p>Land, nearly level. Soil, sandy loam. Timber, scattering cotton wood. Undergrowth, salt cedar, willows and mesquite.</p> |
| | <p>Dependent Resurvey of a Portion of subdivisional lines, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona. (Restoring the 1875 survey by Theodore F. White)</p> |
| | <p>From the point for the cor. of secs. 19, 24, 25 and 30 on the E bdy. of the Tp,</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | N. 89°51' W., bet. secs. 24 and 25. Over level land along track road and fence line. |
| 39.00 | Canal, 10 lks. wide, flows N. |
| 39.82 | Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 42.00 | Enter dense timber and undergrowth. |
| 77.50 | Dodge - Nevada Canal, 15 lks. wide, flows N. 30° W., thence through medium undergrowth. |
| 79.63 | Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. From this point the standard cor. of secs. 35 and 36, bears S. 0°10' E., 160.04 chs. dist.; monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd. SC T5S R23E S35 S36 1967 This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered. Land, level. Soil, sandy loam. Timber, mesquite. Undergrowth, mesquite and creosote. |
| | From the point for the cor. of secs. 23, 24, 25 and 26. N. 0°24' W., bet. secs. 23 and 24. Over gently rolling land, through scattering timber and medium undergrowth. |
| 0.80 | Fence, bears E and W. |
| 1.60 | Track road, bears E and W. |
| 8.00 | Dodge - Nevada Canal, 15 lks. wide, flows N. 30° W. |
| 22.10 | Irrigation ditch, 10 lks. wide, flows N. 65° E. |
| 23.70 | Concrete lined ditch, 5 lks. wide, flows N. 65° E., thence across cultivated field. |
| 40.01 | Point for the ¼ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 41.20 | Leave cultivated field, bears E and W. |
| 41.30 | Fence, bears E and W, 24 lks. to cor. of fences extending N, E and W. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | | | | | | | | | | | | | | | | | | | | | | | |
|--------|--|-------|---|-------|---|-------|--|-------|--|-------|--|-------|--|-------|---|--------|--|-------|--|-------|-----------------------|-------|---|
| 60.50 | Fence, bears W and E, 21 lks. to cor. of fences extending S and W. | | | | | | | | | | | | | | | | | | | | | | |
| 65.70 | Graded road, bears S. 25° E. and N. 25° W. | | | | | | | | | | | | | | | | | | | | | | |
| 78.40 | Track road, bears S. 50° E. and N. 50° W. | | | | | | | | | | | | | | | | | | | | | | |
| 80.02 | <p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E <u>S14 S13</u> <u>S23 S24</u> 1976</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, mesquite, creosote and cacti.</p> | | | | | | | | | | | | | | | | | | | | | | |
| | <p>From the point for the cor. of secs. 13, 18, 19 and 24, on the E bdy. of Tp.</p> <p>N. 89°51' W., bet. secs. 13 and 24.</p> <p>Over nearly level land, along track road.</p> <tr> <td data-bbox="305 1462 451 1489">24.90</td> <td data-bbox="451 1462 1385 1489">Power line, bears S. 25° E. and N. 25° W.</td> </tr> <tr> <td data-bbox="305 1524 451 1550">25.90</td> <td data-bbox="451 1524 1385 1550">Highway No. 70, bears S. 25° E. and N. 25° W.</td> </tr> <tr> <td data-bbox="305 1585 451 1612">26.50</td> <td data-bbox="451 1585 1385 1650">Southern Pacific Railroad, bears S. 25° E. and N. 25° W.</td> </tr> <tr> <td data-bbox="305 1685 451 1712">26.90</td> <td data-bbox="451 1685 1385 1712">Irrigation ditch, 10 lks. wide, flows N.</td> </tr> <tr> <td data-bbox="305 1747 451 1774">28.90</td> <td data-bbox="451 1747 1385 1774">Fort Thomas Canal, 15 lks. wide, flows N. 30° W.</td> </tr> <tr> <td data-bbox="305 1809 451 1835">36.50</td> <td data-bbox="451 1809 1385 1835">Graded road, bears S. 75° E. and N. 75° W.</td> </tr> <tr> <td data-bbox="305 1870 451 1897">39.80</td> <td data-bbox="451 1870 1385 1897">Dodge - Nevada Canal, 10 lks. wide flows N.</td> </tr> <tr> <td data-bbox="305 1932 451 1959">39.945</td> <td data-bbox="451 1932 1385 1997">Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</td> </tr> <tr> <td data-bbox="305 2032 451 2059">46.50</td> <td data-bbox="451 2032 1385 2059">Fence, bears N and S, thence over gently rolling land.</td> </tr> <tr> <td data-bbox="305 2093 451 2120">49.30</td> <td data-bbox="451 2093 1385 2120">Fence, bears N and S.</td> </tr> <tr> <td data-bbox="305 2155 451 2182">59.92</td> <td data-bbox="451 2155 1385 2575"> <p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> </td> </tr> | 24.90 | Power line, bears S. 25° E. and N. 25° W. | 25.90 | Highway No. 70, bears S. 25° E. and N. 25° W. | 26.50 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. | 26.90 | Irrigation ditch, 10 lks. wide, flows N. | 28.90 | Fort Thomas Canal, 15 lks. wide, flows N. 30° W. | 36.50 | Graded road, bears S. 75° E. and N. 75° W. | 39.80 | Dodge - Nevada Canal, 10 lks. wide flows N. | 39.945 | Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. | 46.50 | Fence, bears N and S, thence over gently rolling land. | 49.30 | Fence, bears N and S. | 59.92 | <p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> |
| 24.90 | Power line, bears S. 25° E. and N. 25° W. | | | | | | | | | | | | | | | | | | | | | | |
| 25.90 | Highway No. 70, bears S. 25° E. and N. 25° W. | | | | | | | | | | | | | | | | | | | | | | |
| 26.50 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. | | | | | | | | | | | | | | | | | | | | | | |
| 26.90 | Irrigation ditch, 10 lks. wide, flows N. | | | | | | | | | | | | | | | | | | | | | | |
| 28.90 | Fort Thomas Canal, 15 lks. wide, flows N. 30° W. | | | | | | | | | | | | | | | | | | | | | | |
| 36.50 | Graded road, bears S. 75° E. and N. 75° W. | | | | | | | | | | | | | | | | | | | | | | |
| 39.80 | Dodge - Nevada Canal, 10 lks. wide flows N. | | | | | | | | | | | | | | | | | | | | | | |
| 39.945 | Point for the ¼ sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. | | | | | | | | | | | | | | | | | | | | | | |
| 46.50 | Fence, bears N and S, thence over gently rolling land. | | | | | | | | | | | | | | | | | | | | | | |
| 49.30 | Fence, bears N and S. | | | | | | | | | | | | | | | | | | | | | | |
| 59.92 | <p>Point for the W 1/16 sec. cor. of secs. 13 and 24.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> | | | | | | | | | | | | | | | | | | | | | | |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | T5S R23E W 1/16 $\frac{S13}{S24}$ 1976 |
| 69.905 | Point for the W-W 1/64 sec. cor. of secs. 13 and 24; not monumented. |
| 79.40 | Telephone line, bears SE and NW. |
| 79.89 | The cor. of secs. 13, 14, 23 and 24. Land, nearly level to gently rolling. Soil, sandy loam. Timber, none. Undergrowth, mesquite, creosote, salt cedar and cacti. |
| | N. 0°13' W., bet. secs. 13 and 14. Over gently rolling land, through sparse undergrowth. |
| 0.80 | Fence, bears E and W. |
| 1.60 | Graded road, bears N. 85° E. and S. 85° W. |
| 9.90 | Graded road, bears S. 60° E. and N. 60° W. |
| 10.005 | Point for the S-S 1/64 sec. cor. of secs. 13 and 14; not monumented. |
| 20.01 | Point for the S 1/16 sec. cor. of secs. 13 and 14. Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | T5S R23E S 1/16 S14 S13 1976 |
| 35.70 | Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Graded road, bears N. 12° E. and S. 12° W. |
| 40.01 | Point for the ¼ sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 55.70 | Track road, bears SE and NW, thence through dense undergrowth. |
| 59.50 | Fence, bears E and W. |
| 60.30 | Fort Thomas Canal, 20 lks. wide, flows NW. |
| 79.50 | Irrigation ditch, 5 lks. wide, flows E. |
| 79.90 | Track road, bears E and W. |
| 80.02 | Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | <p>Land, gently rolling. Soil, sandy loam. Timber, cotton wood and mesquite. Undergrowth, mesquite, creosote and cacti.</p> |
| | <p>From the point for the cor. of secs. 7, 12, 13 and 18 on the E bdy. of the Tp.</p> <p>N. 89°51' W., bet. secs. 12 and 13.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 1.50 | Right bank of Gila River, bears NE and SE. |
| 10.90 | Left bank of Gila River, thence along a track road. |
| 20.10 | Graded road, bears N and W, track road bears E. |
| 20.20 | Powerline, bears N and S. |
| 39.975 | Point for the ¼ sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 40.00 | Canal, 10 lks. wide, flows N. |
| 63.70 | Power line, bears S. 25° E. and N. 25° W. |
| 64.80 | Highway No. 70, bears S. 25° E. and N. 25° W. |
| 66.00 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. |
| 79.95 | The point for the cor. of secs. 11, 12, 13 and 14. |
| | <p>Land, gently rolling. Soil, sandy loam. Timber, cotton wood. Undergrowth, mesquite and salt cedar.</p> |
| | <p>N. 0°04' W., bet. secs. 11 and 12.</p> <p>Over nearly level land, through dense undergrowth.</p> |
| 0.20 | Irrigation ditch, 5 lks. wide, flows E, thence across cultivated field. |
| 19.90 | Fence, bears E and W, leave cultivated field. |
| 20.30 | Irrigation ditch, flows W. |
| 25.00 | Fence, bears S. 25° E. and N. 25° W. |
| 28.40 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. |
| 30.40 | Highway No. 70, bears S. 25° E. and N. 25° W. |
| 39.80 | Fence, bears E and W. |
| 39.95 | Track road, bears E and W. |
| 40.01 | Point for the ¼ sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |

Dependent Resurvey of a Portion of Subdivisional Lines
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 40.20 | Concrete lined irrigation ditch, 5 lks. wide, flows E, thence across cultivated field. |
| 60.20 | Track road, bears E and W. |
| 60.40 | Irrigation ditch, 5 lks. wide, flows E. |
| 79.80 | Fence, bears E and W. |
| 80.02 | The cor. of secs. 1, 2, 11 and 12, monumented with an iron post, 2½ ins. diam., 6 ins. below surface of graded road, bears E and W, with brass cap mkd. |
| | T5S R23E $\frac{S2 S1}{S11 S12}$ 1965 |
| | From which An iron post, 2½ ins. diam., projecting 6 ins. above the ground, for a reference monument, bears S. 59° W. 40.9 lks. dist., with brass cap mkd., T5S R23E S11 RM 27 ft. 1965 and an arrow pointing to the cor. |
| | There is no remaining evidence of the reference monument set NW in 1965. |
| | Land, nearly level. Soil, sandy loam. Timber, scattering mesquite, cotton wood and tamarisk. Undergrowth, mesquite. |
| | From the point for the cor. of secs. 23, 24, 25 and 26. S. 89°46' W., bet. secs. 23 and 26. |
| | Over nearly level land, through sparse undergrowth. |
| 0.20 | Fence bears N and S. |
| 20.075 | Point for the E 1/16 sec. cor. of secs. 23 and 26. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. |
| | T5S R23E E 1/16 $\frac{S23}{S26}$ 1976 |
| | Raise a mound of stone, 2½ ft. base, 1½ ft. high N of cor. |
| 20.80 | Fence, bears N and S. |
| 40.15 | Point for the ¼ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | <p style="text-align: center;">T5S R23E $\frac{1}{4}$ $\frac{S23}{S26}$ 1976</p> |
| | <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> |
| 59.70 | <p>Track road, bears N and S.</p> |
| 60.23 | <p>Point for the W 1/16 sec. cor. of secs. 23 and 26.</p> |
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E W 1/16 $\frac{S23}{S26}$ 1975</p> |
| | <p>Raise a mound of stone, 1½ ft. base, 1 ft. high, N of cor.</p> |
| 60.50 | <p>Fence, bears N and S.</p> |
| 62.30 | <p>Wash, 40 lks. wide, drains easterly from S.</p> |
| 80.31 | <p>The cor. of secs. 22, 23, 26 and 27, monumented with a flint stone 12x8x5 ins., projecting 5 ins. above the ground, mkd. with 2 notches on E edge and 2 notches on S edge.</p> |
| | <p>At the cor. point</p> |
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E $\frac{S22 S23}{S27 S26}$ 1976</p> |
| | <p>Deposit the mkd. stone along side the iron post.</p> |
| | <p>Set a mesquite post, 4 ins. diam., 5 ft. long, along side the iron post.</p> |
| | <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, mesquite, creosote and cacti.</p> |
| | <p>N. 0°08' W., bet. secs. 22 and 23.</p> |
| | <p>Over nearly level land, through medium undergrowth.</p> |
| 23.80 | <p>Track road, bears NE and SW.</p> |
| 38.30 | <p>Track road, bears S. 55° W. and N. 55° E. curving E.</p> |
| 38.40 | <p>Cor. of fences, extending Northerly and S. 55° W.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 40.03 | <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E $\frac{1}{4}$ S22 S23 1976</p> <p>Raise a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high W of cor.</p> <p>Cor. is located 5 lks. E of N and S fence.</p> |
| 42.70 | <p>Fence, bears E and W, 6 lks. to cor. of fences extending N, E and S.</p> |
| 44.60 | <p>Wash, 20 lks. wide, drains Easterly.</p> |
| 80.06 | <p>Point for the cor. of secs. 14, 15, 22 and 23. At proportionate dist.; there is no remaining evidence of the original cor.; not monumented.</p> <p>From this point the cor. of secs. 15, 16, 21 and 22, bears N. $89^{\circ}55'$ W., 79.73 chs. dist.; determined from remains of original bearing trees.</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S. $74\frac{1}{2}^{\circ}$ E., 72 lks. dist., no marks visible. (Record S. $77\frac{1}{2}^{\circ}$ E.)</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears S. 45° E., 65 lks. dist., no marks visible. (Record S. 50° E.)</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. $42\frac{1}{2}^{\circ}$ W., 88 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S16 S15 S21 S22 1976</p> <p>Raise a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high W of cor.</p> <p>This control line was fully retraced and careful search was made for evidence of the intervening corner, none of which was recovered.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | <p>From the cor. of secs. 13, 14, 23 and 24.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | <p>S. 89°47' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through sparse undergrowth.</p> |
| 3.10 | Track road, bears S. 60° E. and N. 60° W. |
| 5.80 | Track road, bears S. 25° E. and N. 25° W. |
| 6.60 | Track road, bears N. 40° E. and S. 40° W. |
| 9.50 | El Paso natural gas pipeline, bears S. 35° E. and N. 35° W. |
| 19.80 | Fence, bears N and S. |
| 20.00 | Track road, bears N and S, thence over cultivated field. |
| 32.30 | Leave cultivated field, bears N and S. |
| 39.10 | Track road, bears N and S. |
| 39.20 | Fence, bears N and S. |
| 39.97 | Point for the ¼ sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 42.00 | Fence, bears N and S. |
| 56.20 | Irrigation ditch, 15 lks. wide, flows N. 25° W. |
| 59.96 | Point for the W 1/16 sec. cor. of secs. 14 and 23; not monumented. |
| 79.95 | <p>The point for the cor. of secs. 14, 15, 22 and 23.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | <p>N. 0°03' W., bet. secs. 14 and 15.</p> <p>Over medium rolling land through sparse undergrowth.</p> |
| 1.30 | Fence line, bears E and W. |
| 16.80 | Fence, bears N. 80° E. and S. 80° W. |
| 20.015 | <p>Point for the S 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S 1/16 S15 S14 1976</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located on steep E slope.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 40.03 | <p>The $\frac{1}{4}$ sec. cor. of secs. 14 and 15, monumented with a granite stone, 12x10x7 ins. projecting 6 ins. above the ground, mkd. $\frac{1}{4}$ on S face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E $\frac{1}{4}$ S15 S14 1976</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p> <p>Cor. is located 75 lks. E of N and S fence.</p> |
| 18.50 | <p>N. $0^{\circ}24'$ W., beginning new measurement.</p> <p>Fence, bears N. 65° E. and S. 65° W.</p> |
| 19.96 | <p>Point for the N $1/16$ sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E N $1/16$ S15 S14 1976</p> <p>Set a cedar post, 6 ins. diam., 6 ft. long, alongside the cor.</p> |
| 20.20 | <p>Fence, bears E and W.</p> |
| 39.92 | <p>Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S10 S11 S15 S14 1976</p> <p>Raise a mound of stone, $1\frac{1}{2}$ ft. base, 1 ft. high, W of cor.</p> <p>Land, medium rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | <p>From the point for the cor. of secs. 11, 12, 13 and 14.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | S. 89°42' W., bet. secs. 11 and 14. Over gently rolling land along a track road. |
| 9.00 | Enter dense undergrowth along a canal. |
| 17.00 | Fence, bears irregularly N. 65° E. and S. 65° W. |
| 17.40 | Fort Thomas Canal, 10 lks. wide, flows N. 70° W. curving Northerly. |
| 27.20 | Telephone line, bears S. 20° E. and N. 20° W. |
| 34.90 | Wash, 40 lks. wide, drains N. 80° E. |
| 39.97 | Point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 40.10 | Abandoned fence, bears N and S. |
| 48.50 | Fence, bears N. 89° E. and S. 89° W. |
| 59.70 | Abandoned fence, bears N and S. |
| 59.95 | Point for the W 1/16 sec. cor. of secs. 11 and 14; not monumented. |
| 64.80 | El Paso natural gas pipeline and track road, bears S. 35° E. and N. 35° W. |
| 79.93 | The cor. of secs. 10, 11, 14 and 15. Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, mesquite, salt cedar, creosote and cacti. |
| | N. 0°12' E., bet. secs. 10 and 11. Over medium rolling land, through medium undergrowth. |
| 19.96 | Point for the S 1/16 sec. cor. of secs. 10 and 11. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T5S R23E S 1/16 S10 S11 1976 |
| | Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor. |
| 22.30 | El Paso natural gas pipeline and track road, bears S. 35° E. and N. 35° W. |
| 39.92 | Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T5S R23E

¼

S10|S11

1976

Raise a mound of stone, 1½ ft. base, 1 ft. high, W of cor.

Cor. is located in E and W fence, on E edge of track road, bears N and S. 10° W.

45.83

Point for the closing cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor. Also the SE cor. of the (abandoned) Fort Thomas Military Reservation; not monumented.

Restoring the 1894 resurvey by Lorenzo D. Chillson.

N. 0°12' E., continuing measurement bet. secs. 10 and 11, common with the E bdy. of the (abandoned) Fort Thomas Military Reservation.

58.90

Graded roads, extend N, S and W.

59.10

Power line, bears S. 65° W. and N. 65° E., 40 lks. to lines extending N. 3° W., SE and S. 65° W.

66.60

Power lines, extend N and S. 3° E.

72.00

Graded road, bears Northeasterly and S.

73.30

Wash, 30 lks. wide, drains N. 10° E.

77.30

Telephone line, bears SE and NW.

80.27

Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.

From this point, the point for the cor. of secs. 2, 3, 34 and 35, bears N. 0°31' E., 79.91 chs. dist.; not monumented.

From the point for the cor. of secs. 2, 3, 34 and 35,

The ¼ sec. cor. of secs. 1 and 36, bears N. 89°58' E., 118.72 chs. dist., monumented with an iron post, 2½ ins. diam., projecting 8 ins. above the ground, with brass cap mkd.

T4S R23E

¼ $\frac{S36}{S1}$

T5S

1965

Mound of stone, 3 ft. base, 2 ft. high, N of cor.

From the point for the cor. of secs. 2, 3, 34 and 35, the cor. of secs. 3, 4, 33 and 34, bears S. 89°58' W., 79.14 chs. dist., hereinafter described.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | <p>These control lines were fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.</p> <p>Land, medium rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> <hr/> <p>Restoring the 1875 survey by Theodore F. White.</p> <hr/> <p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°55' W., bet. secs. 2 and 11.</p> <p>Along a graded road.</p> |
| 23.20 | Power line, bears S. 20° E. and N. 20° W. |
| 24.30 | Highway No. 70, bears S. 30° E. and N. 30° W., graded road bears E and track road bears W. |
| 25.40 | Southern Pacific Railroad, bears S. 30° E. and N. 30° W. |
| 32.10 | Fort Thomas Canal, 15 lks. wide, flows N. 20° W., curving N. |
| 38.70 | Track road ends, thence over medium rolling land, through medium undergrowth. |
| 39.77 | <p>Point for the ¼ sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E ¼ S 2 S11 1976</p> <p>Cor. is located 10 lks. W of irrigation ditch, 5 lks. wide, 3 ft. deep, flows SE.</p> |
| 59.10 | Fence, bears N. 35° E. and S. 35° W. |
| 59.66 | <p>Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E W 1/16 S 2 S11 1976</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high N of cor.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 78.50 | Fence, bears S and N. 20° W. |
| 78.80 | Graded road, bears S. 5° E. and N. 15° W. |
| 79.40 | Wash, 30 lks. wide, 5 ft. deep, flows Northerly. |
| 79.55 | The point for the cor. of secs. 2, 3, 10 and 11. |
| | <p>Land, nearly level to medium rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | <p>From the cor. of secs. 10, 11, 14 and 15.</p> |
| | <p>N. 89°52' W., bet. secs. 10 and 15.</p> |
| | <p>Over gently rolling land, through medium undergrowth.</p> |
| 1.30 | Fence, bears N and S. |
| 37.70 | Track road, bears N. 35° E. and S. 35° W., curving W. |
| 39.92 | <p>The ¼ sec. cor. of secs. 10 and 15, monumented with a mound of stone, 2½ ft. base, 1 ft. high, from which the remains of an original bearing tree</p> |
| | <p>A mesquite stump, 12 ins. diam., bears S. 8° W., 145 lks. dist.; no marks visible. (Record 142 lks.)</p> |
| | <p>At the cor. point</p> |
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E ¼ $\frac{S10}{S15}$ 1976</p> |
| | <p>N. 89°58' W., beginning new measurement.</p> |
| | <p>Over medium rolling land, through medium undergrowth.</p> |
| 19.855 | Point for the W 1/16 sec. cor. of secs. 10 and 15. |
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E W 1/16 $\frac{S10}{S15}$ 1976</p> |
| | <p>Raise a mound of stone, 1½ ft. base, 6 ins. high, N of cor.</p> |
| 21.30 | <p>Fence cor., bears North, 35 lks. dist., fences extend N. 5° E. and W.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 35.80 | Black Rock Wash, 350 lks. wide, 3 ft. deep, drains N. 50° E. |
| 39.71 | <p>Point for the cor. of secs. 9, 10, 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>From this point the $\frac{1}{4}$ sec. cor. of secs. 15 and 16, bears S. 0°15' E., 39.99 chs. dist., determined from the remains of an original bearing tree.</p> <p>A mesquite stump, 13 ins. diam., bears S. 3½° E., 52 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½' base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E ¼ S16 S15 1976</p> <p>Land, gently rolling to medium rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | <p>N. 0°30' E., bet. secs. 9 and 10.</p> <p>Over nearly level land, through medium undergrowth.</p> |
| 11.50 | Graded road, bears SE and NW curving North, thence along E side of road. |
| 19.995 | Point for the S 1/16 sec. cor. of secs. 9 and 10; not monumented. |
| 39.99 | Point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 59.985 | <p>Point for the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E N 1/16 S9 S10 1976</p> |
| 79.98 | Point for the cor. of secs. 3, 4, 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor. |
| | <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | <p>Set a cut off iron post, 16 ins. long, 2½ ins. diam., 9 ins. below surface of graded E and W road, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E $\frac{S4 S3}{S9 S10}$ 1976</p> <p>From which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45° W., 50 lks. dist., with brass cap mkd., T5S R23E S9 RM 33 ft. 1976, and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° W., 50 lks. dist., with brass cap mkd., T5S R23E S4 RM 33 ft. 1976, and an arrow pointing to the cor.</p> <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, mesquite, creosote and cacti.</p> |
| | <p>Restoring the 1894 resurvey by Lorenzo D. Chillson.</p> <hr style="width: 20%; margin: auto;"/> <p>From the point for the cor. secs. 2, 3, 10 and 11.</p> <p>S. 89°53' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land, through medium undergrowth along S side of graded road.</p> |
| 3.10 | Telephone line, bears SE and NW. |
| 5.40 | Fence, bears N and S. |
| 10.30 | Fence, bears N and S. |
| 19.20 | Graded road, bears E and S. |
| 20.30 | Fence, bears N and S. |
| 21.80 | Black Rock Wash, 100 lks. wide, 2 ft. deep, drains N. 35° E. |
| 39.41 | Point for the ¼ sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 40.10 | Fence, bears S and N, 33 lks. dist., to cor. of fence's extending E, S and W. |
| 40.50 | El Paso natural gas pipeline, bears S. 35° E. and N. 35° W. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| 44.60 | Begin along track road. |
| 53.90 | Wash, 30 lks. wide, drains N. 30° E. |
| 54.70 | Track road, bears E and SW. |
| 57.52 | Point for the closing cor. of secs. 3 and 10, at intersection with the S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented. |
| | From this point the point for the closing cor. of secs. 10 and 11, bears S. 59°08' E., 66.86 chs. dist. This is also the SE cor. of the (abandoned) Fort Thomas Military Reservation; not monumented. |
| | Restoring the 1875 survey by Theodore F. White. |
| | S. 89°53' W., continuing measurement. |
| 63.60 | Graded road, bears SE and W. |
| 79.18 | The cor. of secs. 3, 4, 9 and 10. |
| | Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti. |
| | N. 0°32' E., bet. secs. 3 and 4. |
| | Over gently rolling land, through medium undergrowth. |
| 0.50 | Powerline and fence, bears S. 85° E. and N. 85° W. |
| 1.90 | Paved road, bears N. 55° E. and S. 55° W. |
| 12.925 | Point for the closing cor. of secs. 3 and 4 at intersection with the S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented. |
| | From this point the initial cor. on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 394.48 chs. dist.; heretofore described. |
| | Restoring the 1894 resurvey by Lorenzo D. Chillson. |
| | N. 0°32' E., continuing measurement. |
| 14.50 | Fence, bears E and W. |
| 19.995 | Point for the S 1/16 sec. cor. of secs. 3 and 4; not monumented. |
| 20.04 | Fence, bears S. 85° E. and N. 85° W. |
| 20.30 | Graded road, bears S. 85° E. and N. 85° W. |
| 20.40 | Powerline, bears S. 85° E. and N. 85° W. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| 33.40 | Track road, bears N. 80° E. and S. 80° W. |
| 39.99 | Point for the ¼ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented. |
| 40.40 | Fence, bears S. 85° E. and N. 85° W. |
| 50.40 | Fence, bears S. 85° E. and N. 85° W. |
| 54.80 | El Paso natural gas pipeline, bears S. 30° E. and N. 30° W. |
| 70.10 | Fence, bears E and W. |
| 76.10 | Fence, bears E and W. |
| 77.20 | Telephone line, bears SE and NW. |
| 79.80 | Fence cor., fence extend E and S. 5° W. |
| 79.90 | Graded road, bears E and W, curving South. |
| 80.07 | The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, with brass cap mkd. |
| | <p style="text-align: center;">T4S R23E <u>S33 S34</u> <u>S4 S3</u> T5S 1965</p> |
| | Cor. is located in E and W fence line. |
| | <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | Restoring the 1875 survey by Theodore F. White. |
| | <p style="text-align: center;">-----</p> <p>From the standard cor. of secs. 32 and 33, on the S bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set, projecting 8 ins. above the ground, with brass cap mkd.</p> |
| | <p style="text-align: center;">SC T5S R23E <u>S32 S33</u> 1967</p> |
| | Mound of stone, 2 ft. base, 1½ ft. high W of cor. |
| | N. 0°22' W., bet. secs. 32 and 33. |
| | Over gently rolling land, through medium creosote and scattered mesquite. |
| 39.98 | Point for the ¼ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | | |
|--------|---|--|
| 69.40 | Fence line, bears N. 20° E. and S. 20° W. | |
| 79.96 | Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the orig. cor. | |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. | |
| | T5S R23E S29 S28 S32 S33 1976 | |
| | Set a mesquite post, 5 ins. diam., 5 ft. long, beside the cor. | |
| | From this point the point for the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., bears S. 89°58' E., 318.75 chs. dist.; heretofore described. | |
| | This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered. | |
| | Land, gently rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, creosote and cacti. | |
| 39.98 | N. 0°08' W., bet. secs. 28 and 29. | |
| | Over gently rolling land, through medium creosote and scattered mesquite. | |
| | Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor. | |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. | |
| | T5S R23E ¼ S29 S28 1976 | |
| | Set a mesquite post, 4 ins. diam., 5 ft. long, beside the cor. | |
| 79.96 | The cor. of secs. 20, 21, 28 and 29, monumented with the remains of a wooden post, at a mound of earth, 2 ft. base, 6 ins. high, from which the original bearing tree | |
| | A mesquite stump, 8 ins. diam., bears S. 59° E., 191 lks. dist.; no marks visible. (Record 181 lks. dist.) | |
| | At the cor. point | |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. | |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridina, Arizona.

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">T5S R23E S20 S21 S29 S28 1976</p> <p>Raise a mound of stone, 1½ ft. base, 1½ ft. high, W of cor.</p> <p>Deposit the remains of the wooden post alongside the iron post.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, scattered mesquite. Undergrowth, creosote and cacti.</p> |
| | <p>From the point for the cor. of secs. 9, 10, 15 and 16. West, bet. secs. 9 and 16. Over medium rolling land, through medium undergrowth.</p> |
| 7.60 | Track road, bears N and S curving Westerly. |
| 13.30 | Corral fence, bears N and S. |
| 14.30 | Corral fence, bears N and S. |
| 19.81 | Point for the E 1/16 sec. cor. of secs. 9 and 16; not monumented. |
| 24.40 | Wash, 100 lks. wide, drains N. 30° E. |
| 32.50 | Ridge, bears N. 10° E. and S. 10° W. |
| 39.62 | The ¼ sec. cor. of secs. 9 and 16, monumented with a decayed wooden post 3 ins. diam., in mound of stone, 2½ ft. base, 1 ft. high; not remonumented. |
| | <p>_____</p> <p>S. 89°50' W. beginning new measurement.</p> |
| | Over medium rolling land, through scattering undergrowth. |
| 19.00 | Fence, bears N. 65° E. and S. 65° E. and S. 65° W. |
| 19.60 | Fence cor., fences extend N, N. 65° E. and S. 65° W. |
| 39.70 | The cor. of secs. 8, 9, 16 and 17, monumented with the remains of a mesquite post and mound of earth 1½ ft. base, 6 ins. high. |
| | At the cor. point |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | <p>T5S R23E S8 S9 S17 S16 1976</p> |
| | Deposit the remains of the mesquite post along side the iron post. |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 19.995 | <p>Raise a mound of stone, 1½ ft. base, 1 ft. high, W of cor.</p> <p>Land, medium rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> <hr/> <p>N. 0°09' W., bet. secs. 8 and 9.</p> <p>Over nearly level land, through medium undergrowth.</p> <p>Point for the S 1/16 sec. cor. of secs. 8 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E S 1/16 S8 S9 1976</p> |
| 22.40 | <p>Raise a mound of stone, 1½ ft. base, 1 ft. high, W of cor.</p> <p>Wash, 20 lks. wide, drains N. 25° E.</p> |
| 39.99 | <p>The ¼ sec. cor. of secs. 8 and 9, determined from the remains of the original bearing trees</p> <p>A mesquite stump, 10 ins. diam., bears N. 10½° E., 102 lks. dist., no marks visible.</p> <p>A mesquite stump, 8 ins. diam., bears N. 79° W., 173 lks. dist., no marks visible (Record N. 81° W.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. below the surface of a graded road, bears N. 35° E. and S. 35° W., with brass cap mkd.</p> <p style="text-align: center;">T5S R23E ¼ S8 S9 1976</p> <p>From which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 10 ins. in the ground, for a reference monument, encircled by a mound of stone, 4 ft. base to top, bears S. 45° E., 36.4 lks. dist., with brass cap mkd. T5S R23E ¼ S9 RM 24 ft. 1976, and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 45° W., 36.4 lks. dist., with brass cap mkd. T5S R23E ¼ S8 RM 24 ft. 1976, and an arrow pointing to the cor.</p> |


Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> |
| | <p>N. 0°45' E., beginning new measurement.</p> |
| | <p>Over nearly level land, through medium undergrowth.</p> |
| 19.00 | <p>Graded road, bears N. 30° E. curving Easterly and S. 30° W. curving Westerly.</p> |
| 40.01 | <p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> |
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E $\frac{S5 S4}{S8 S9}$ 1976</p> |
| | <p>From this point the cor. of secs. 5, 6, 7 and 8, bears S. 89°49' W., 79.21 chs. dist., monumented with the remains of a mesquite post, 3 ins. diam., 4 ft. long, scribe marks illegible, along side a mound of stone, 2 ft. base, 1 ft. high.</p> |
| | <p>At the cor. point</p> |
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 11 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> |
| | <p style="text-align: center;">T5S R23E $\frac{S6 S5}{S7 S8}$ 1976</p> |
| | <p>Bury the wooden post along side the iron post in the mound of stone.</p> |
| | <p>This control line was fully retraced and careful search was made for evidence of the intervening corner, of which none was found.</p> |
| | <p>Land, nearly level. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| | <p>From the cor. of secs. 3, 4, 9 and 10.</p> |
| | <p>S. 89°57' W., bet. secs. 4 and 9.</p> |
| | <p>Over gently rolling land, through medium undergrowth.</p> |
| 0.40 | <p>Fence, bears S and N, 20 lks. to cor. of fences extending S and W. Power line bears N and S.</p> |

Dependent Resurvey of a Portion of Subdiviisonal Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 0.80 | Intersection of roads, bears N curving NE, E, S and SW curving Westerly. |
| 19.895 | <p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E E 1/16 $\frac{S4}{S9}$ 1976</p> <p>Raise a mound of stone, 1½ ft. base, 1 ft. high, N of cor.</p> <p>Cor. is located 9 lks. S of E and W fence.</p> |
| 39.79 | <p>Point for the ¼ sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E ¼ $\frac{S4}{S9}$ 1976</p> <p>Raise a mound of stone, 1½ ft. base, 1 ft. high, N of cor.</p> <p>Cor. is located 1 lk. N of E and W fence.</p> |
| 49.90 | Wash, 20 lks. wide, drains N. 55° E. |
| 50.40 | Fence cor., bears S. 10 lks., fences extend E, S. 10° E. and W. |
| 60.60 | Fence cor., bears South 10 lks. dist., fences extend E and S. |
| 61.40 | Track road, bears N. 30° E. and S. 30° W. |
| 73.70 | Track road, bears N. 20° E. and S. 20° W. |
| 79.59 | <p>The cor. of secs. 4, 5, 8 and 9.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> |
| 11.00 | <p>N. 0°06' E., bet. secs. 4 and 5.</p> <p>Over gently rolling land, through sparse undergrowth.</p> <p>Track road, bears S. 50° E. and N. 50° W.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| 40.01 | <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E $\frac{1}{4}$ S5 S4 1976</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ}44'$ E., beginning new measurement.</p> |
| 13.50 | <p>Fence bears S. 65° W. and N. 65° E., 4 lks. to cor. of fences extending S. 40° E. and S. 65° W.</p> |
| 17.60 | <p>Track road, bears N. 65° E. and S. 65° W.</p> |
| 19.97 | <p>Point for the N $1/16$ sec. cor. of secs. 4 and 5.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E N $1/16$ S5 S4 1976</p> <p>Raise a mound of stone, $1\frac{1}{2}$ ft. base, 8 ins. high, W of cor.</p> |
| 20.28 | <p>The orig. closing cor. of secs. 4 and 5, on the S bdy. of the (abandoned) Fort Thomas Military Reservation, monumented with a granite stone, 10x7x5 ins. in a mound of stone, 2 ft. base to top, mkd. CC on N face. Add the mks. AM on top of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>Restoring the 1894 resurvey by Lorenzo D. Chillson.</p> <hr style="width: 20%; margin: auto;"/> <p>N. $0^{\circ}32'$ W., beginning new measurement.</p> |
| 0.15 | <p>Point for the closing cor. of secs. 4 and 5 on S bdy. of (abandoned) Fort Thomas Military Reservation.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, in a mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E CT MR CC S5 S4 S5 S4 CC 1976</p>  |

Dependent Resurvey of a Portion of Subdivision Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | | |
|--------|--|--|
| 19.57 | <p>From this pt., the initial cor. on the E bdy. of San Carlos Indian Reservation, bears N. 59°08' W., 302.06 chs. dist.; heretofore described.</p> <p>From this same pt., the closing cor. for secs. 10 and 11 bears S. 59°08' E., 184.37 chs. dist.; heretofore described.</p> <p>The cor. of secs. 4, 5, 32 and 33, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R23E <u>S32 S33</u> S5 S4 T5S 1965</p> </div> <p>Land, gently rolling. Soil, sandy loam. Timber, none. Undergrowth, creosote, mesquite and cacti.</p> | |
| 39.89 | <p>From the standard cor. of secs. 31 and 32 on the S bdy. of the Tp., monumented with an iron post, 2½ ins. diam., firmly set projecting 7 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T5S R23E <u>S31 S32</u> 1967</p> </div> <p>Mound of stone, 2 ft. base, 1½ ft. high, N of cor. N. 0°36' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through medium creosote and scattered mesquite.</p> | |
| 79.78 | <p>Point for the ¼ sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p> | |
| 79.78 | <p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R23E <u>S30 S29</u> S31 S32 1976</p> </div> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>From this point the cor. of secs. 30 and 31 only, on the W bdy. of the Tp., bears S. 89°18' W., 80.04 chs. dist.,</p> | |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

CHAINS

monumented with a granite stone, 14x8x6 ins., firmly set 4 ins. below surface of ground, mkd. with 5 notches on N and 1 notch on S, from which an original 1875 bearing tree

A mesquite, 16 ins. diam., bears S. 49½° E., 202 lks. dist.; partly healed blaze, marks visible TVSR.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

| | | |
|------|--|------|
| T5S | | T5S |
| | | S30 |
| R22E | | S31 |
| S36 | | R23E |
| | | 1976 |

Deposit the mkd. stone along side the iron post.

Set a mesquite post, 4 ins. diam., 4 ft. long, beside the iron post.

This control line was fully retraced and careful search was made for evidence of the intervening corner, none of which was recovered.

Land, gently rolling.
Soil, sandy loam.
Timber, scattered mesquite.
Undergrowth, creosote and cacti.

From the cor. of secs. 28, 29, 32 and 33.

S. 89°56' W., bet. secs. 29 and 32.

Over broken land, through medium creosote and scattered mesquite.

39.89

Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate dist; there is no remaining evidence of the orig. cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

| | |
|-----|------|
| T5S | R23E |
| ¼ | S29 |
| | S32 |
| | 1976 |

Raise a mound of stone, 2 ft. base, 1½ ft. high N of cor.

51.20

Leave broken land, thence over gently rolling land.

79.77

The cor. of secs. 29, 30, 31 and 32.

Land, broken to gently rolling.
Soil, sandy loam.
Timber, scattered mesquite.
Undergrowth, creosote and cacti.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | <p>N. 0°05' W., bet. secs. 29 and 30.</p> <p>Over gently rolling land, through medium creosote and scattered mesquite.</p> |
| 39.89 | <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E $\frac{1}{4}$ S30 S29 1976</p> <p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p> |
| 59.835 | <p>Point for the N $\frac{1}{16}$ sec. cor. of secs. 29 and 30; not monumented.</p> |
| 66.30 | <p>Enter washed area, bears NE and SW, thence through medium creosote and cat claw.</p> |
| 79.78 | <p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the orig. cor.; not monumented.</p> <p>From this point the cor. of secs. 19 and 30 only on the W bdy. of the Tp. bears S. 89°17' W., 79.93 chs. dist., monumented with a granite stone, 14x12x10 ins., firmly set 6 ins. below surface of ground, with 4 grooves on N face, no other marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S T5S R22E S19 S30 S25 R23E 1976</p> <p>Deposit the mkd. stone, along side the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, E of cor.</p> <p>From this same point, the cor. of secs. 17, 18, 19 and 20, bears N. 0°29' E., 79.78 chs. dist. monumented with a wooden post 4x4 ins., firmly set, projecting 3 ft. above a mound of stone, 3 ft. base, 1 ft. high, mkd. 19 on SW and 20 on SE, from which an orig. bearing tree</p> <p style="padding-left: 40px;">A mesquite, 8 ins. diam., bears N. $54\frac{1}{2}^\circ$ W., 184 lks. dist., marks visible TVS RXX (Record 180 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> |

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| 39.85 | <p style="text-align: center;">T5S R23E S18 S17 S19 S20 1976</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor.</p> <p>Bury the mkd. post, horizontally in base of mound of stone.</p> <p>These control lines were fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, creosote, cat claw and cacti.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°48' W., bet secs. 20 and 29.</p> <p>Over broken land, through medium creosote and mesquite.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the orig. cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E ¼ S20 S29 1976</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p> |
| 59.77 | <p>Point for the W 1/16 sec. cor. of secs. 20 and 29; not monumented.</p> |
| 79.69 | <p>The point for the cor. of secs. 19, 20, 29 and 30.</p> <p>Land, gently rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, creosote, cat claw and cacti.</p> <hr/> <p style="text-align: center;">Subdivision of Section 4, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.</p> <hr/> <p>From the ¼ sec. cor. of secs. 4 and 9.</p> <p>N. 0°20' E., along the N and S center line of sec. 4.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 20.00 | <p>Point for the C-S 1/16 sec. cor. of sec. 4.</p> |

Subdivision of Section 4, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | | |
|--------|---|--|
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C S 1/16 S4 C 1976</p> | |
| | <p>Raise a mound of stone, 1½ ft. base, 6 ins. high, W of cor.</p> | |
| 20.10 | <p>Fence, bears E and W, 80 lks. to cor. of fences extending N and E.</p> | |
| 36.705 | <p>Intersect the S bdy. of the (abandoned) Fort Thomas Military Reservation.</p> <p>Point for the closing cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">C CC S4 CC S4 C 1976</p> | |
| | <p>From this point, the initial cor. on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 348.23 chs. dist., heretofore described.</p> | |
| 40.00 | <p>Point for the C¼ sec. cor. at intersection with the E and W center line of sec. 4; not monumented.</p> | |
| 40.20 | <p>Fence, bears E and W.</p> | |
| 60.00 | <p>Point for the C-N 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C N 1/16 S4 C 1976</p> | |
| | <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W of cor.</p> <p>Fence cor., bears N. 50° W., 14 lks. dist., fences extend N and W.</p> | |
| 79.97 | <p>The ¼ sec. cor. of secs. 4 and 33, monumented with an iron post, 2½ ins. diam., 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R23E ¼ S33 S4 T5S 1976</p> | |

Subdivision of Section 4, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | Mound of stone, 2 ft. base, 1½ ft. high, N of cor. |
| | From the point for the ¼ sec. cor. of secs. 3 and 4. S. 89°56'30" W., along the E and W center line of sec. 4. Over gently rolling land, through medium undergrowth. |
| 0.95 | Graded road, bears N and S. |
| 1.15 | Fence bears N and S. |
| 19.97 | Point for the C-E 1/16 sec. cor. of sec. 4; not monumented. |
| 20.90 | Fence, bears S and N, 23 lks. to cor. of fences extending E, S and W. |
| 39.94 | The point for the C¼ sec. cor. of sec. 4. |
| 40.80 | Fence, bears S and N, 10 lks. to cor. of fences extending E, S and NW. |
| 45.465 | Point for the closing cor. at intersection with S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented. |
| | From this point the initial cor. on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 341.82 chs. dist.; heretofore described. |
| 55.90 | Fence, bears N. 80° E. and S. 80° W. |
| 59.91 | Point for the C-W 1/16 sec. cor. of sec. 4; not monumented. |
| 64.00 | Fence, bears N. 10° E. and S. 10° W. |
| 66.40 | Fence, bears SE and NW. |
| 79.88 | The ¼ sec. cor. of secs. 4 and 5. |
| | SE¼ Section 4 |
| | From the E 1/16 sec. cor. of secs. 4 and 9. N. 0°26'30" E., along the N and S center line of the SE¼ sec. 4. Over nearly level land, through medium undergrowth. |
| 19.995 | Point for the SE 1/16 sec. cor. at intersection with the E and W center line of the SE¼ sec. 4. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. |
| | T5S R23E SE 1/16 S4 1976 |
| | Raise a mound of stone, 1½ ft. base, 1 ft. high, W of cor. |
| 20.30 | Fence, bears E and W. |
| 22.80 | Fence, bears S. 85° E. and N. 85° W. |

Subdivision of Section 4, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|----------------------------|--|
| 24.80 | <p>Point for the closing cor. at intersection with the S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented.</p> <p>From this point the initial cor. on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 371.38 chs. dist., heretofore described.</p> |
| 25.30 | <p>Fence, bears S. 85° E. and N. 85° W.</p> |
| 39.99 | <p>The point for the C-E 1/16 sec. cor. of sec. 4.</p> <hr/> <p>From the point for the S 1/16 sec. cor. of secs. 3 and 4. S. 89°56' W., along the E and W centerline of the SE¼ of sec. 4.</p> <p>Over nearly level land, through medium undergrowth.</p> |
| 11.87 | <p>Point for the closing cor. at intersection with the S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented.</p> <p>From this point the initial point on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 380.73 chs. dist., heretofore described.</p> |
| 19.93 | <p>The SE 1/16 sec. cor. of sec. 4.</p> |
| 20.60 | <p>Fence, bears S and N, 7 lks. to cor. of fences extending N, S and W.</p> |
| 39.86 | <p>The C-S 1/16 sec. cor. of sec. 4.</p> |
| <p>NW¼ Section 4</p> <hr/> | |
| 8.63 | <p>From the point for the C-W 1/16 sec. cor. of sec. 4. N. 0°13'30" E., along the N and S center line of the NW¼ of sec. 4.</p> <p>Over medium rolling land, through sparse undergrowth, Intersect the S bdy. of the (abandoned) Fort Thomas Military Reservation.</p> <p>Point for the closing cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>CTMR W CC S4 CC S4 W 1976</p> </div> <p>From this point the initial cor. on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 325.03 chs. dist.; heretofore described.</p> |

Subdivision of Section 4, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|---|---|
| 19.99 | <p>Point for the NW 1/16 sec. cor. at intersection with the E and W center line of the NW$\frac{1}{4}$ of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E NW 1/16 S4 1976</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1 ft. high, W of cor.</p> |
| 20.01 | Fence, bears E and W. |
| 39.30 | Wash, 20 lks. wide, drains NE. |
| 39.93 | <p>The W 1/16 sec. cor. of secs. 4 and 33, monumented with an iron post, 2$\frac{1}{2}$ ins. diam., in a mound of stone, 3$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high, with brass cap mkd.</p> <p style="text-align: center;">T4S R23E W 1/16 $\frac{S33}{S 4}$ T5S 1976</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 4.</p> <p>S. 89°56' W., along the E and W center line of the NW$\frac{1}{4}$ of sec. 4.</p> <p>Over rolling land through medium undergrowth.</p> |
| 19.99 | The NW 1/16 sec. cor. of sec. 4. |
| 39.01 | <p>Point for the closing cor. at intersection with the S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented.</p> <p>From this point the initial point on the E bdy. of the San Carlos Indian Reservation, bears N. 59°08' W., 302.96 chs. dist., heretofore described.</p> |
| 39.79 | The N 1/16 sec. cor. of secs. 4 and 5. |
| <p>Subdivision of Section 9, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.</p> | |
| <p>From the $\frac{1}{4}$ sec. cor. of secs. 9 and 16.</p> <p>N. 0°23' E., along the N and S center line of sec. 9.</p> <p>Over gently rolling land, through medium undergrowth.</p> | |
| 9.80 | Fence, bears N. 75° E. and S. 75° W. |
| 19.955 | <p>Point for the C-S 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C S 1/16 S 9 C 1976</p> |

Subdivision of Section 9, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| | <p>Set a mesquite post, 3 ins. diam., 5 ft. long, alongside the cor.</p> <p>From this point a local cor., monumented with a wooden post, 3x4 ins., projecting 9 ins. above the ground, bears N. 84° W., 113.5 lks. dist.</p> |
| 39.91 | <p>Point for the $\frac{1}{4}$ sec. cor. at intersection with the E and W center line of sec. 9.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E $\frac{1}{4}$ S9 1976</p> |
| | <p>Set a mesquite post, 3 ins. diam., $5\frac{1}{2}$ ft. long, alongside the cor.</p> <p>From this point a local cor., monumented with a wooden post, 4x4 ins. projecting 5 ins. above the ground, bears N. 83°39' W., 105 lks. dist.</p> |
| 59.905 | <p>Point for the C-N $\frac{1}{16}$ sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C N $\frac{1}{16}$ S 9 C 1976</p> |
| | <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>From this point a local cor., monumented with a $\frac{1}{2}$ inch open end pipe, projecting 2 ft. above ground and a 2x4 inch wooden post alongside, bears S. 89°54' W., 108 lks. dist.</p> |
| 69.70 | <p>Graded road, bears N. 80° E. and S. 80° W.</p> |
| 79.90 | <p>The $\frac{1}{4}$ sec. cor. of secs. 4 and 9.</p> |
| | <p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 9 and 10.</p> |
| | <p>S. 89°54'30" W., along the E and W center line of sec. 9.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 0.20 | <p>Powerline and fence, bears N and S.</p> |
| 0.45 | <p>Graded road, bears N and S.</p> |
| 0.70 | <p>Fence, bears S and N, 24 lks. to cor. of fences extending N, S, and W.</p> |

Subdivision of Section 9, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--|--|
| 19.85 | <p>Point for the C-E 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. below surface of cultivated field, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C $\frac{E\ 1/16}{S9}$ C 1976</p> <p>From which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, for a reference monument, bears S. 45° W., 30.3 lks. dist., with brass cap mkd., T5S R23E C-E 1/16 S9 RM 20 ft. 1976, and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 21 ins. in the ground, for a reference monument, bears N. 45° W., 30.3 lks. dist., with brass cap mkd., T5S R23E C-E 1/16 S9 RM 20 ft. 1976, and an arrow pointing to the cor.</p> <p>Reference monuments are located 3 lks. W of N and S fence.</p> |
| 39.70 | The C¼ sec. cor. of sec. 9. |
| 59.90 | Fence, bears N and S. |
| 79.74 | The ¼ sec. cor. of secs. 8 and 9. |
| <p>NE¼ Section 9</p> <hr style="width: 20%; margin: auto;"/> | |
| 0.35 | <p>From the C-E 1/16 sec. cor. of sec. 9.</p> <p>N. 0°26' E., along the N and S center line of the NE¼ of sec. 9.</p> <p>Over nearly level land, through medium undergrowth.</p> <p>Fence, bears E and W, 20 lks. to cor. of fences extending E, S and W.</p> |
| 6.10 | Fence, bears E and W. |
| 19.99 | <p>Point for the NE 1/16 sec. cor., at intersection with the E and W center line of the NE¼ of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E NE 1/16 S9 1976</p> |
| 20.20 | Raise a mound of stone, 2 ft. base, 1 ft. high W of cor. |
| 20.20 | Fence, bears E and W. |
| 34.00 | Graded road, bears N. 85° E. and S. 85° W. |

Subdivision of Section 9, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 39.99 | <p>The E 1/16 sec. cor. of secs. 4 and 9.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89°54'30" W., along the E and W center line of the NE¹/₄ of sec. 9.</p> <p>Over nearly level land, through medium undergrowth.</p> |
| 0.25 | Fence and powerline, bears N and S. |
| 0.50 | Graded road, bears N and S. |
| 19.87 | The NE 1/16 sec. cor. of sec. 9. |
| 20.50 | Fence, bears N and S. |
| 39.74 | The C-N 1/16 sec. cor. of sec. 9. |
| | <p>SE¹/₄ Section 9</p> <hr/> |
| | <p>From the point for the E 1/16 sec. cor. of secs. 9 and 16.</p> <p>N. 0°27'30" E., along the N and S center line of the SE¹/₄ of sec. 9.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 11.50 | Wash, 25 lks. wide, 5 ft. deep, drains N. 15° E., from S. 25° W. |
| 17.70 | Fence cor., fences extend Northerly, N. 75° E. and S. 75° W. |
| 19.985 | <p>Point for the SE 1/16 sec. cor. at intersection with the E and W centerline of the SE¹/₄ of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> |
| | <p>T5S R23E SE 1/16 S9 1976</p> |
| | <p>Raise a mound of stone, 1½ ft. base, 6 ins. high, W of cor.</p> <p>Cor. is located 1 lk. W of N and S fence.</p> |
| 39.97 | <p>The C-E 1/16 sec. cor. of sec. 9.</p> <hr/> <p>From the point for the S 1/16 sec. cor. of secs. 9 and 10.</p> <p>S. 89°57' W., along the E and W center line of the SE¹/₄ of sec. 9.</p> <p>Over nearly level land, through medium undergrowth.</p> |
| 14.00 | Wash, 25 lks. wide, 5 ft. deep, drains Northerly. |
| 19.83 | The SE 1/16 sec. cor. of sec. 9. |

Subdivision of Section 9, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--|--|
| 39.66 | The C-S 1/16 sec. cor. of sec. 9. |
| Subdivision of Section 10, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona. | |
| From the 1/4 sec. cor. of secs. 10 and 15. | |
| N. 0°33' E., along the N and S center line of sec. 10. | |
| Over gently rolling land, through medium undergrowth. | |
| 19.96 | Point for the C-S 1/16 sec. cor. of sec. 10. |
| Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. | |
| T5S R23E C S 1/16 S10 C 1976 | |
| Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of cor. | |
| 24.10 | Track road, bears E curving NE and W curving NW. |
| 37.70 | Track road, bears SW and NE, curving N. |
| 39.92 | Point for the C 1/4 sec. cor., at intersection with the E and W center line of sec. 10. |
| Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. | |
| T5S R23E C 1/4 S10 1976 | |
| Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor. | |
| Fence cor., bears N. 55° E., 29 lks. dist., fences extend N, E and W. | |
| 47.50 | Black Rock Wash, 80 lks. wide, 2 ft. deep, drains N. 35° E. |
| 69.28 | Point for the closing cor. of sec. 10 at intersection with the S bdy. of the (abandoned) Fort Thomas Military Reservation; not monumented. |
| From this point the point for the closing cor. of secs. 10 and 11, bears S. 59°08' E., 45.88 chs. dist. This is also the SE cor. of the (abandoned) Fort Thomas Military Reservation; not monumented. | |
| 79.33 | El Paso natural gas pipeline, bears N. 35° W. and S. 35° E. |
| 80.09 | The point for the 1/4 sec. cor. of secs. 3 and 10. |

Subdivision of Section 10, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|---|--|
| | <p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>N. $89^{\circ}52'$ W., along the E and W center line of sec. 10.</p> <p>Over gently rolling land, through medium undergrowth, along S side of fence line.</p> |
| 2.30 | Fence cor., fences extend N. 50° E., E, S and W. |
| 12.30 | El Paso natural gas pipeline, bears S. 35° E. and N. 35° W. |
| 19.83 | <p>Point for the C-E $1/16$ sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \text{T5S R23E} \\ \text{C } \frac{\text{E } 1/16}{\text{S10}} \text{ C} \\ 1976 \end{array}$ <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of cor.</p> <p>Fence cor., bears N. 60° W., 21 lks. dist., fences extend N, E and W.</p> |
| 38.80 | Track road, bears N curving NE and S, curving SW. |
| 39.66 | The $C\frac{1}{4}$ sec. cor. of sec. 10. |
| 45.60 | Black Rock Wash, 80 lks. wide, 2 ft. deep, drains N. 40° E. |
| 59.53 | <p>Point for the C-W $1/16$ sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} \text{T5S R23E} \\ \text{C } \frac{\text{W } 1/16}{\text{S10}} \text{ C} \\ 1976 \end{array}$ <p>Raise a mound of stone, 2 ft. base, 6 ins. high, N of cor.</p> |
| 59.56 | Fence, bears S and N, 15 lks., dist. to cor. of fences extending E, S and W. |
| 79.40 | The $\frac{1}{4}$ sec. cor. of secs. 9 and 10. |
| <p>Subdivision of Section 11, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.</p> | |
| | <p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.</p> <p>N. $0^{\circ}03'30''$ E., along the N and S center line of sec. 11.</p> <p>Over gently rolling land, through medium undergrowth.</p> |

Subdivision of Section 11, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| 19.99 | Point for the C-S 1/16 sec. cor. of sec. 11; not monumented. |
| 33.70 | Telephone line, bears SE and NW. |
| 39.98 | Point for the C $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 11. |
| | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 12 ins. in the ground, in a mound of stone, 2 $\frac{1}{2}$ ft. base to top, with brass cap mkd. |
| | T5S R23E C $\frac{1}{4}$ S11 1976 |
| | Cor. is located 10 lks. E. of fence cor., fences extend N, E, S and W. |
| 60.09 | Point for the C-N 1/16 sec. cor. of sec. 11. |
| | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | T5S R23E C N 1/16 S11 C 1976 |
| | Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 $\frac{1}{2}$ ft. high, W of cor. |
| 60.90 | Fence, bears E and W, 20 lks. to cor. of fences extending E and S. |
| 69.70 | Corral fence, bears S. 40° E. and N. 40° W. |
| 76.70 | Corral fence, bears N. 30° E. and S. 30° W. |
| 80.20 | The $\frac{1}{4}$ sec. cor. of secs. 2 and 11. |
| | From the point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 12. S. 89°39'30" W., along the E and W center line of sec. 11. Over gently rolling land, through medium undergrowth. |
| 3.30 | Powerline, bears S. 25° E. and N. 25° W. |
| 4.40 | Highway No. 70, bears S. 25° E. and N. 25° W. |
| 5.30 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. |
| 32.70 | Fort Thomas Canal, 20 lks. wide, flows N. 25° W. |
| 39.88 | The C $\frac{1}{4}$ sec. cor. of sec. 11. |
| 59.825 | Point for the C-W 1/16 sec. cor. of sec. 11. |

Subdivision of Sec. 11, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|---|---|
| | <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C $\frac{W\ 1/16}{S11}$ C 1976</p> |
| 59.90 | Fence, bears N and S, 23 lks. to cor. of fences extending N, E and W. |
| 74.50 | Fence cor., fences extend N, E and W. |
| 79.77 | The ¼ sec. cor. of secs. 10 and 11. |
| <p>SW¼ Section 11</p> <hr/> | |
| | <p>From the point for the W 1/16 sec. cor. of secs. 11 and 14.</p> <p>N. 0°09' E., along the N and S center line of the SW¼ of sec. 11.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 19.97 | <p>Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW¼ of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E SW 1/16 S11 1976</p> |
| | <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> |
| 39.93 | The C-W 1/16 sec. cor. of sec. 11. |
| <hr/> | |
| | <p>From the point for the C-S 1/16 sec. cor. of sec. 11.</p> <p>S. 89°41' W., along the E and W center line of the SW¼ of sec. 11.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 19.955 | The SW 1/16 sec. cor. of sec. 11. |
| 38.40 | El Paso natural gas pipe line and track road, bears S. 35° E. and N. 35° W. |
| 39.91 | The S 1/16 sec. cor. of secs. 10 and 11. |
| <p>Subdivision of Section 13, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.</p> | |

Subdivision of Section 13, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|---|
| | <p>From the point for the ¼ sec. cor. of secs. 13 and 24. N. 0°12' W., along the N and S center line of sec. 13. Over nearly level land through dense undergrowth along irrigation ditch.</p> |
| 0.50 | Graded road, bears irregularly E and W. |
| 20.00 | Point for the C-S 1/16 sec. cor. of sec. 13; not monu- mented. |
| 23.00 | Dodge-Nevada Canal, 10 lks. wide, flow N. 35° W., from S. |
| 24.80 | Fence, bears S. 25° E. and N. 25° W. |
| 27.30 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. |
| 29.60 | Highway No. 70, bears S. 25° E. and N. 25° W. |
| 31.80 | Dodge-Nevada Canal, 10 lks. wide, flow N., from S. 35° W. |
| 31.90 | Powerline and fence, bears S. 25° E. and N. 25° W. |
| 40.00 | Point for the C¼ sec. cor., at intersection with the E and W center line of sec. 13; not monumented. |
| 80.03 | The point for the ¼ sec., cor. of secs. 12 and 13. |
| | <p>From the point for the ¼ sec. cor. of secs. 13 and 18 on the E bdy. of the Tp. N. 89°50'30" W., along the E and W centerline of sec. 13. Over nearly level land, through dense undergrowth along irrigation ditch.</p> |
| 39.80 | Irrigation ditch flows N and E, from S. |
| 39.96 | The point for the C¼ sec. cor. of sec. 13. |
| 40.50 | Graded road, bears Northeasterly and W. |
| 44.00 | Powerline, bears S. 25° E. and N. 25° W. |
| 45.00 | Highway No. 70, bears S. 25° E. and N. 25° W. |
| 46.10 | Southern Pacific Railroad, bears S. 25° E. and N. 25° W. |
| 59.935 | Point for the C-W 1/16 sec. cor. of sec. 13; not monu- mented. |
| 68.20 | Fort Thomas Canal, 15 lks. wide, flows N. 10° W., thence over gently rolling land. |
| 69.70 | Graded road, bears E and N. 50° W. |
| 77.60 | Graded road, bears NE curving E and SW curving S. |

Subdivision of Section 13, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--|---|
| 79.91 | The point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14. |
| <p>$SW\frac{1}{4}$ Section 13</p> <hr/> | |
| <p>From the W $\frac{1}{16}$ sec. cor. of secs. 13 and 24.</p> | |
| <p>N. $0^{\circ}13'$ W., along the N and S center line of the $SW\frac{1}{4}$ of sec. 13.</p> | |
| <p>Over rolling land, through medium undergrowth.</p> | |
| 0.70 | Fence line, bears E and W. |
| 1.20 | Graded gravel road, bears E and W. |
| 10.00 | Point for the C-S-SW $\frac{1}{64}$ sec. cor. of sec. 13. |
| <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. in diam., 21 ins. in the ground, with brass cap mkd.</p> | |
| <p>C-S-SW $\frac{1}{64}$ S13 1976</p> | |
| <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p> | |
| 16.00 | Track road, bears SE and NW. |
| 20.00 | Point for the SW $\frac{1}{16}$ sec. cor. at intersection with the E and W center line of the $SW\frac{1}{4}$ of sec. 13; not monumented. |
| 22.30 | Power line, bears S. 30° E. and N. 30° W. |
| 23.70 | Track road, bears S. 30° E. and N. 30° W. |
| 25.00 | Fort Thomas Canal, 15 lks. wide, flows N. 30° W. |
| 25.50 | Enter cultivated field, bears S. 30° E. and N. 30° W. |
| 39.75 | Leave cultivated field, bears E and W, telephone and fence line, bears E and W. |
| 39.90 | Graded gravel road, bears E and W. |
| 40.00 | The point for the C-W $\frac{1}{16}$ sec. cor. of sec. 13. |
| <hr/> | |
| <p>From the point for the C-S $\frac{1}{16}$ sec. cor. of sec. 13.</p> | |
| <p>N. $89^{\circ}50'30''$ W., along the E and W center line of the $SW\frac{1}{4}$ of sec. 13.</p> | |
| <p>Over cultivated land.</p> | |
| 15.00 | Leave cultivated land, bears S. 30° E. and N. 30° W. |

Subdivision of Section 13, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 15.20 | Fort Thomas Canal, 15 lks. wide, flows N. 30° W., thence through medium undergrowth. |
| 16.80 | Track road, bears S. 30° E. and N. 30° W. |
| 18.70 | Power line, bears S. 30° E. and N. 30° W., thence over gently rolling land. |
| 19.955 | The point for the SW 1/16 sec. cor. of sec. 13. |
| 29.945 | Point for the C-W-SW 1/64 sec. cor. of sec. 13. Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | C-W-SW 1/64 S13 1976 |
| | Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor. |
| 39.935 | The S 1/16 sec. cor. of secs. 13 and 14. |
| | SW¼, of the SW¼, of Section 13 |
| | From the point for the W-W 1/64 sec. cor. of secs. 13 and 24. |
| | N. 0°13' W., along the N and S center line of the SW¼, of the SW¼, sec. 13. |
| | Over gently rolling land, through medium undergrowth. |
| 0.80 | Fence line, bears E and W. |
| 1.60 | Graded gravel road, bears E and W. |
| 7.70 | Track road, bears E and W. |
| 10.00 | Point for the SW-SW 1/64 sec. cor., at intersection with the E and W center line of the SW¼, of the SW¼, sec. 13. Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | SW-SW 1/64 S13 1976 |
| | Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. |
| | From this point the SW cor. of fence around cemetery, bears S. 82°51' E., 276 lks. dist.; cemetery 568x212 ft., long side bears N and S. |
| 20.01 | The C-W-SW 1/64 sec. cor. of sec. 13. |

Subdivision of Section 13, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|---|--|
| | <p>From the C-S-SW 1/64 sec. cor. of sec. 13.</p> <p>N. 89°52' W., along the E and W center line of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$, of sec. 13.</p> <p>Over gently rolling land, through medium undergrowth.</p> |
| 9.99 | The SW-SW 1/64 sec. cor. of sec. 13. |
| 19.99 | The point for the S-S 1/64 sec. cor. of secs. 13 and 14. |
| <p>Subdivision of Section 14, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.</p> | |
| | <p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.</p> <p>N. 0°13'30" W., along the N and S center line of sec. 14.</p> <p>Over nearly level open land.</p> |
| 1.20 | Fence, bears E and W. |
| 1.50 | Graded road, bears E and W, thence across cultivated field. |
| 20.005 | Point for the C-S 1/16 sec. cor. of sec. 14; not monumented. |
| 20.90 | Fence and cultivated field, bears E and W, thence over gently rolling land, through sparse undergrowth. |
| 40.01 | Point for the C $\frac{1}{4}$ sec. cor., at intersection with the E and W center line of sec. 14. |
| | <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C$\frac{1}{4}$ S14 1976</p> |
| | <p>Raise a mound of stone, 1$\frac{1}{2}$ ft. base, 1 ft. high, W of cor.</p> |
| 44.00 | El Paso natural gas pipeline, bears S. 35° E. and N. 35° W. |
| 59.985 | Point for the C-N 1/16 sec. cor. of sec. 14; not monumented. |
| 78.90 | Wash, 15 lks. wide, drains N. 65° E. |
| 79.96 | The point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14. |
| | <p>From the point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 14.</p> <p>S. 89°49' W., along the E and W center line of sec. 14.</p> <p>Over gently rolling land, through sparse undergrowth.</p> |

Subdivision of Section 14, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|--------|--|
| 13.60 | Telephone line, bears S. 15° E. and N. 17° W. |
| 19.40 | Fence, bears N and S. |
| 37.30 | El Paso natural gas pipeline, bears S. 35° E. and N. 35° W. |
| 39.97 | The C ¹ / ₄ sec. cor. of sec. 14. |
| 59.905 | Point for the C-W 1/16 sec. cor. of sec. 14. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, in a mound of stone, 2½ ft. base to top, with brass cap mkd. |
| | <p>T5S R23E C $\frac{W \ 1/16}{S14}$ C 1976</p> |
| 79.84 | The ¼ sec. cor. of secs. 14 and 15. |
| | <p>SW¼ Section 14</p> <hr style="width: 20%; margin: auto;"/> |
| | From the point for the W 1/16 sec. cor. of secs. 14 and 23. |
| | N. 0°10' W., along the N and S center line of the SW¼ of sec. 14. |
| | Over gently rolling land, through sparse undergrowth. |
| 20.01 | Point for the SW 1/16 sec. cor., at intersection with the E and W center line of the SW¼ of sec. 14. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | <p>T5S R23E SW 1/16 S14 1976</p> |
| | Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor. |
| 21.00 | Fence bears W and E, 13 lks. to cor. of fences extending N, E, S and W. |
| 40.02 | The C-W 1/16 sec. cor. of sec. 14. |
| | From the point for the C-S 1/16 sec. cor. of sec. 14. |
| | S. 89°47'30" W., along the E and W center line of the SW¼ of sec. 14. |
| | Over cultivated field. |
| 16.60 | Leave cultivated field, bears N and S, thence over gently rolling land, through sparse undergrowth. |
| 19.80 | Fence, bears N and S. |

Subdivision of Section 14, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|---|---|
| 19.97 | The SW 1/16 sec. cor. of sec. 14. |
| 24.80 | Fence, bears N. 85° E. and S. 85° W. |
| 39.93 | The S 1/16 sec. cor. of secs. 14 and 15. |
| <p>NW$\frac{1}{4}$ Section 14</p> <hr/> | |
| | From the C-W 1/16 sec. cor. of sec. 14. |
| | N. 0°18' W., along the N and S center line of the NW $\frac{1}{4}$ of sec. 14. |
| | Over medium rolling land, through sparse undergrowth. |
| 19.965 | Point for the NW 1/16 sec. cor., at intersection with the E and W center line of the NW $\frac{1}{4}$ of sec. 14. |
| | Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd. |
| | <p>T5S R23E NW 1/16 S14 1976</p> |
| | Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor. |
| 20.50 | Fence, bears E and W. |
| 33.10 | El Paso natural gas pipeline, bears S. 30° E. and N. 30° W. |
| 39.93 | The point for the W 1/16 sec. cor. of secs. 11 and 14. |
| <hr/> | |
| | From the point for the C-N 1/16 sec. cor. of sec. 14. |
| | S. 89°45'30" W., along the E and W center line of NW $\frac{1}{4}$ of sec. 14. |
| | Over medium rolling land, through sparse undergrowth. |
| 10.90 | El Paso natural gas pipeline, bears S. 30° E. and N. 30° W. |
| 19.96 | The NW 1/16 sec. cor. of sec. 14. |
| 39.92 | The N 1/16 sec. cor. of secs. 14 and 15. |
| <p>Subdivision of Section 23, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona.</p> <hr/> | |
| | From the $\frac{1}{4}$ sec. cor. of secs. 23 and 26. |
| | N. 0°15'30" W., along the N and S center line of sec. 23. |
| | Over nearly level land, through sparse undergrowth. |

Subdivision of Section 23, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | |
|---|--|
| 8.80 | Wash, 20 lks. wide, 3 ft. deep, drains N. 80° E. |
| 40.03 | Point for the C¼ sec. cor., at intersection with the E and W center line of sec. 23. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd. |
| | T5S R23E C¼ S23 1976 |
| | Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor. |
| 42.10 | Fence line, bears E and W, 15 lks. to cor. of fences extending N. 2° E., E and W. |
| 49.20 | Fence line, bears N. 2° E. and S. 2° W. |
| 60.60 | Irrigation ditch, 15 lks. wide, flows NW. |
| 80.05 | The point for the ¼ sec. cor. of secs. 14 and 23. |
| | From the point for the ¼ sec. cor. of secs. 23 and 24. S. 89°47' W., along the E and W center line of sec. 23. Over cultivated land. |
| 9.00 | Leave cultivated land, bears N and S. |
| 9.10 | Fence line, bears N and S. thence across nearly level land, through medium undergrowth and scattered mesquite. |
| 20.035 | Point for the C-E 1/16 sec. cor. of sec. 23. |
| | Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. |
| | T5S R23E C <u>E 1/16</u> C S23 1976 |
| | Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor. |
| | Cor. is located 167 lks. S of E and W fence line. |
| 25.70 | Irrigation ditch, 15 lks. wide, flow NW. |
| 26.60 | Fence line, bears SE and NW. |
| 40.07 | The C¼ sec. cor. of sec. 23. |
| 60.40 | Track road, bears N and S. |
| 60.50 | Fence line, bears N and S. |
| 80.15 | The ¼ sec. cor. of secs. 22 and 23. |
| Subdivision of Section 29, T. 5 S., R. 23 E., Gila and Salt River Meridian, Arizona. | |

Subdivision of Section 29, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona.

| CHAINS | | |
|--------|---|--|
| 39.94 | <p>From the $\frac{1}{4}$ sec. cor. of secs. 29 and 32.</p> <p>N. $0^{\circ}07'$ W., along the N and S center line of sec. 29.</p> <p>Over rolling land, through medium creosote and mesquite.</p> <p>Point for the $C\frac{1}{4}$ sec. cor. at intersection with the E and W center line of sec. 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C$\frac{1}{4}$ S29 1976</p> | |
| 59.905 | <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p> <p>Point for the C-N $1/16$ sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C N $1/16$ S29 C 1976</p> | |
| 79.87 | <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 29.</p> | |
| 39.86 | <p>From the $\frac{1}{4}$ sec. cor. of secs. 28 and 29.</p> <p>S. $89^{\circ}51'$ W., along the E and W center line of sec. 29.</p> <p>Over rolling land, through medium creosote and mesquite.</p> <p>The $C\frac{1}{4}$ sec. cor. of sec. 29.</p> | |
| 59.79 | <p>Point for the C-W $1/16$ sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground in a mound of stone, $1\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E C $\frac{W\ 1/16}{S29}$ C 1976</p> | |
| 79.72 | <p>Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 30.</p> | |
| | <p>NW$\frac{1}{4}$ Section 29</p> <hr style="width: 20%; margin: auto;"/> | |

Subdivision of Section 29, T. 5 S., R. 23 E.,
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 19.955 | <p>From the C-W 1/16 sec. cor. of sec. 29.</p> <p>N. 0°05'30" W., along the N and S center line of the NW$\frac{1}{4}$, of sec. 29.</p> <p>Over rolling land, through medium creosote and mesquite.</p> <p>Point for the NW 1/16 sec. cor. at intersection with the E and W center line of the NW$\frac{1}{4}$, of sec. 29.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R23E NW 1/16 S29 1976</p> |
| 39.91 | <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>The point for the W 1/16 sec. cor. of secs. 20 and 29.</p> <p style="text-align: center;">_____</p> <p>From the C-N 1/16 sec. cor. of sec. 29.</p> <p>S. 89°50'30" W., along the E and W center line of the NW$\frac{1}{4}$, of sec. 29.</p> <p>Over rolling land, through medium creosote and mesquite.</p> |
| 19.92 | <p>The NW 1/16 sec. cor. of sec. 29.</p> |
| 39.85 | <p>The point for the N 1/16 sec. cor. of secs. 29 and 30.</p> |
| | <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Section 4 of this survey is located 1$\frac{1}{2}$ miles Southwest of Fort Thomas, Arizona. The general elevation ranges from 2,700 to 3,100 feet above sea level. The soil is a stoney, sandy loam.</p> <p>The Gila River flows in a Northwesterly direction through the Northeast portion of the township; bottom land is rich, silty clay loam of which most is under cultivation.</p> <p>Access is by way of Highway No. 70, which crosses the Northeastern portion of the township in a North Northwesterly direction, paralleled by the Southern Pacific Railroad. There are several unimproved or lightly gravelled roads throughout the township.</p> <p>The vegetation consist of willows, salt cedar and scattering cotton wood trees along the Gila River and irrigation canals. The remainder of the township consist of creosote, mesquite and cactus.</p> <p>There is no evidence of mining activity or minerals.</p> <p>The mean of a considerable number of observations of the magnetic declination throughout the township is 13°30' E., with a range of 1° in local attraction.</p> |

CHAINS

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

| NAMES | CAPACITY |
|---------------------|------------|
| Rex D. Krusell | Survey Aid |
| John P. Bennett III | Survey Aid |
| David M. Conrad | Survey Aid |
| Tim L. Tietjen | Survey Aid |
| Wilfred J. Brusich | Survey Aid |
| John J. Bulinski | Survey Aid |
| Jay D. Lytle | Survey Aid |
| Duane R. Ferneau | Survey Aid |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 1st day of December, 1975, (I) ~~(We)~~ have dependently resurveyed a portion of the East boundary of the San Carlos Indian Reservation, T. 4 S., R. 22 E., the South boundary of the (abandoned) Fort Thomas Military Reservation and a portion of the East boundary and subdivisional lines and surveyed subdivisions in Sections 4, 9, 10, 11, 13, 14, 23 and 29, Township 5 South, Range 23 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 24, 1978
(Date)

Paul L. Reeves
(Cadastral Surveyor)

under the supervision of

April 24, 1978
(Date)

Boyd S. Owens
(Cadastral Surveyor)

Chief, Branch of Cadastral Survey

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the East boundary of the San Carlos Indian Reservation, T. 4 S., R. 22 E., the South boundary of the (abandoned) Fort Thomas Military Reservation and a portion of the East boundary and subdivisional lines and survey of subdivisions in sections 4, 9, 10, 11, 13, 14, 23 and 29, Township 5 South, Range 23 East, G&SRM., Arizona,

executed by Paul L. Reeves, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

MAY 08 1978
(Date)

Bernard W. Foster
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626