

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

Dependent Resurvey of a Portion of

The Fifth Standard Parallel North

Along the South Boundary of Township 21 North, Ranges 18 and 19 West,

Portions of the West Boundary (Fifth Guide Meridian West)

Between Ranges 18 and 19 West,

and Portions of

The South Boundary and Subdivisional Lines of

Township 20 North, Range 18 West

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Harry K. Smith,

Cadastral Surveyor

Under special instructions dated April 21, 19 77, approved April 21, 1977,

, which provided for the surveys included under U.S. Survey/Group
Number 595, and assignment instructions dated April 21, 1977.

Survey commenced May 10, 19 77

Survey completed May 20, 19 77

1A

BOOK 5057

INDEX DIAGRAM

Township 20 North, Range 18 West

8	32					
7	6 30	31 5 30	4	3	2	1
		29	19			
	7 28	8 28	9 18	10	11	12
6						
5	18 26	17 26	16	15	14	13
	19 23	20 24	17 23	21 16	22	23
4				12		
3	30 21	22 20	15 14	28 11	27	26 25
	31	19 32 13	33	34	35	36
		10 9				

Township 20 North, Range 18 West,
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes describe the dependent resurvey of a portion of the Fifth Standard Parallel North along the south boundaries of Township 21 North, Ranges 18 and 19 West, the dependent resurvey of a portion of the west boundary (Fifth Guide Meridian West) between Range 18 and 19 West, a portion of the south boundary, and a portion of the subdivisional lines of Township 20 North, Range 18 West, Gila and Salt River Meridian, Arizona.

The south boundaries of Townships 21 North, Ranges 18 and 19 West, were surveyed by Omar H. Case in 1872. John J. Fisher resurveyed the south boundary of Township 21 North, Range 18 West in 1905 and Fred W. Rodolf resurveyed the south boundary of Township 21 North, Range 19 West in 1911. The west boundary was surveyed by John J. Fisher in 1905. Portions of the west boundary were resurveyed by Fred W. Rodolf in 1910 and William B. Alexander in 1910 and 1911. Fred W. Rodolf surveyed the south and east boundaries in 1909 and the subdivisional lines in 1910. Several plats of private surveys within the township are on file at the Mohave County Courthouse in Kingman, Arizona.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 595, Arizona, dated April 21, 1977.

Preliminary to the resurvey the lines of the original survey and resurveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record, or from ties to lot corners as shown on recorded private survey plats. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations, verified by azimuth from Fig Springs Triangulation Station, and refer to the true meridian. Electronic measuring instruments were used making it impractical to record all topographical items.

The geographic position of the southeast corner of section 32, as scaled from U.S. Geological Quadrangle Map, "Kingman SW, Arizona," prepared in 1967, is as follows:

Latitude 35°04.1' N. Longitude 114°12.6' W.

The mean magnetic declination is 15°00' E.

Dependent Resurvey of a Portion of the
Fifth Standard Parallel North, along the
South Boundary of Township 21 North, Range 18 West,
Gila and Salt River Meridian, Arizona.

(Restoring the 1905 resurvey by John J. Fisher)

Beginning at the stan. $\frac{1}{4}$ sec. cor. of sec. 32, monumented with a granite stone, 20x6x5 ins., firmly set 13 ins. in the ground, mkd. SC $\frac{1}{4}$ on the N. face.

Dependent Resurvey, Fifth Stan. Par. N.,
S. Bdy., T. 21 N., R. 18 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T21N R18W <u>¼ S32</u> 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the cor.</p> <p>Cor. is near the N. edge of a graded road, bears E. and W.</p> <p>S. 89°55' W., on the S. bdy. of sec. 32.</p> <p>Along the N. edge of a graded road, bears E. and W.</p> <p>4.22 Point for the closing cor. of secs. 5 and 6, Tp. 20 N., R. 18 W., at proportionate dist.; there is no remaining evidence of the original cor., hereinafter described.</p>
40.02	<p>The stan. cor. of secs. 31 and 32, monumented with a volcanic stone, 16x10x9 ins., firmly set 12 ins. in the ground, mkd. with 5 notches on the E. edge and 1 notch on the W. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SC T21N R18W <u>S31 S32</u> 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 90.9 lks. dist., mkd. T21N R18W S32 RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° W., 90.9 lks. dist., mkd. RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is at the N. edge of a graded road, bears E. and W.</p>
4.21	<p>S. 89°57' W., on the S. bdy. of sec. 31.</p> <p>Along the N. edge of a graded road, bears E. and W.</p> <p>Point for the ¼ sec. cor. of sec. 6, only, Tp. 20 N., R. 18 W., at proportionate dist.; hereinafter described.</p>

Dependent Resurvey, Fifth Stan. Par. N.,
S. Bdy., T. 21 N., R. 18 W.,
Gila and Salt River Meridian, Arizona

CHAINS

40.04

The stan. $\frac{1}{4}$ sec. cor. of sec. 31, monumented with a granite stone, 16x12x8 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on the N. face.

At the cor. point

Set an iron post, 28 ins. long $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

S C
T21N R18W
 $\frac{1}{4}$ S31
1977

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

Cor. is located 20 lks. N. of a graded road, bears E. and W.

S. $89^{\circ}55'$ W., beginning new measurement.

3.31

The closing cor. of secs. 1 and 6, Tps. 20 N., Rs. 18 and 19 W., hereinafter described.

39.99

Point for the stan. cor. of Tps. 21 N., Rs. 18 and 19 W., at proportionate dist., using the broken boundary method is at the N. edge of a bladed road, bears E. and W. The original monument, a granite stone, 16x10x3 ins., mkd. SC XXI N and 6 grooves on one face, and XIX W with 6 grooves on the opposite face, was found lying loose on the ground.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 38 ins. in the ground, with brass cap mkd.

S C
T21N
R19W | R18W
S36 | S31
1977

Deposit the mkd. stone alongside the iron post.

from the cor.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 75.8 lks. dist., mkd. SC T21N R18W S31 RM 50 FT. 1977 and an arrow pointing to the cor.

An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° W., 75.8 lks. dist., mkd. RM 50 FT. 1977 and an arrow pointing to the cor.

Cor. is at the N. edge of a graded, bears E. and W.

Dependent Resurvey, Fifth Stan. Par. N.,
S. Bdy., T. 21 N., R. 18 W.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Dependent Resurvey of a Portion of the Fifth Standard Parallel North, on the South Boundary of Township 21 North, Range 19 West, Gila and Salt River Meridian, Arizona</p>
	<p>(Restoring the 1911 resurvey by Fred W. Rodolf)</p> <hr style="width: 20%; margin: auto;"/>
40.01	<p>From the stan. cor. of Tps. 21 N., Rs. 18 and 19 W. S. 89°57' W., on the S. bdy. of sec. 36.</p> <p>Along the N. side of a graded road, bears E. and W.</p> <p>The stan. $\frac{1}{4}$ sec. cor. of sec. 36, monumented with a granite stone, 21x12x10 ins., firmly set 10 ins. in the ground, mkd. $\frac{1}{4}$ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S C T21N R19W $\frac{1}{4}$ S36 <hr style="width: 50%; margin: auto;"/>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, $4\frac{1}{2}$ ft. base, 3 ft. high, N. of the cor.</p> <p>Cor. is located 26 lks. N. of the center of a graded road, bears E. and W.</p>
	<p>Dependent Resurvey of a Portion of the Fifth Guide Meridian West, Through Township 20 North, Between Ranges 18 and 19 West, Gila and Salt River Meridian, Arizona</p>
	<p>(Restoring the resurveys by William B. Alexander in 1910 and 1911.)</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the cor. of secs. 25, 30, 31 and 36, Tps. 20 N., Rs. 18 and 19 W., monumented with a lava stone, 17x14x10 ins., firmly set 11 ins. in the ground, mkd. with 1 groove on the W. face and 5 grooves on the E. face.</p> <p>At the cor. point</p> <p>set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 34 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey, Fifth Guide Mer. W.,
T. 20 N., bet. Rs. 18 and 19 W.,
Gila and Salt River Mer., Arizona

CHAINS

T20N
R19W | R18W
S25 | S30
S36 | S31
1977

Deposit the mkd. stone alongside the iron post.
from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears N. 45° E., 90.9 lks. dist.,
mkd. T20N R18W S30 RM 60 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° W., 90.9 lks. dist.
mkd. T20N R19W S36 RM 60 FT. 1977 and an
arrow pointing to the cor.

Cor. is located at the E. edge of a road extending N.,
the N. edge of a road extending E., the W. edge of a
road extending S., and the S. edge of a road extending
W.

N. 0°04' E., bet. secs. 25 and 30.

Over gently rolling land, through medium undergrowth,
along the E. edge of a bladed road, bears E. and W.

40.13

The ¼ sec. cor. of secs. 25 and 30, monumented with a
lava stone 17x8x8 ins., firmly set 12 ins. in the
ground, mkd. ¼ on the W. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins.
in the ground, with brass cap mkd.

T20N
¼
R19W | R18W
S25 | S30
1977

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 3 ft. high, W.
of the cor.

Cor. is located 25 lks. E. of the center of a bladed
road, bears N. and S.

N. 0°01' E., beginning new measurement.

39.58

The cor. of secs. 19, 24, 25, and 30, determined at a
calculated bearing and dist. from the NE cor. of lot
1, Golden Valley Ranches, Unit 20, in sec. 25, T. 20 N.,
R. 19 W., as recorded on the private survey plat on
file at the Mohave County Court House in Kingman,
Arizona. This position is accepted as the best availa-
ble evidence of the original corner position.

from which

Dependent Resurvey, Fifth Guide Mer. W.,
T. 20 N., bet. Rs. 18 and 19 W.,
Gila and Salt River Mer., Arizona

CHAINS

The NE cor. of said lot 1, bears S. 45° W.,
85.7 lks. dist., monumented with a re-bar,
½ in. diam., projecting 6 ins. above ground.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins.
in the ground, with brass cap mkd.

T20N	
R19W	R18W
S24	S19
S25	S30
1977	

from which

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° E., 75.8 lks. dist.,
mkd. T20N R18W S30 RM 50 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears N. 45° W., 75.8 lks. dist.,
mkd. T20N R19W S24 RM 50 FT. 1977 and an
arrow pointing to the cor.

Cor. is located in a fence bearing E. and W., at the
W. edge of a road extending N., the S. edge of a road
extending E., the E. edge of a road extending S., and
the N. edge of a road extending W.

From the cor. of secs. 13, 18, 19, and 24, determined
at a calculated bearing and dist. from the SE cor. of
lot 8, Golden Valley Ranches, Unit 4, in sec. 13,
T. 20 N., R. 19 W., as recorded on the private survey
plat on file at the Mohave County Court House in
Kingman, Arizona. This position is accepted as the best
available evidence of the original corner position.

from which

The SE cor. of said lot 8, bears N. 45° W.,
85.7 lks. dist., monumented with a re-bar,
½ in. diam., projecting 6 ins. above ground.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 38 ins.
in the ground, with brass cap mkd.

T20N	
R19W	R18W
S13	S18
S24	S19
1977	

Dependent Resurvey, Fifth Guide Mer. W.,
T. 20 N., bet. Rs. 18 and 19 W.,
Gila and Salt River Mer., Arizona

CHAINS

A volcanic stone, 20x12x12 ins., mkd. with 3 notches on opposite edges, found lying loose on the ground, is deposited alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 45° E., 60.6 lks. dist., mkd. T20N R18W S18 RM 40 FT. 1977 and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° W., 60.6 lks. dist., mkd. T20N R19W S24 RM 40 FT. 1977 and an arrow pointing to the cor.

Cor. is located 20 lks. N. of the N. edge of a bladed road extending E., at the E. edge of a road extending N., the W. edge of a road going S., and the S. edge of a road going W.

N. 0°03' E., bet. secs. 13 and 18.

Along the E. edge of a bladed road, bears N. and S.

40.00

The ¼ sec. cor. of secs. 13 and 18, monumented with a volcanic stone, 18x12x5 ins., firmly set 12 ins. in the ground, mkd. ¼ on the W. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T20N
¼
R19W | R18W
S13 | S18
1977

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.

Cor. is at the E. edge of a bladed road, bears N. and S.

N. 0°07' E., beginning new measurement.

40.02

The cor. of secs. 7, 12, 13, and 18, determined at midpoint between the SW cor. of lot 8, Golden Valley Ranches Unit 3 in sec. 7, T. 20 N., R. 18 W., and the NE cor. of lot 1, Golden Valley Ranches Unit 4, in sec. 13, T. 20 N., R. 19 W., as recorded on private survey plats and on file at the Mohave County Court House in Kingman, Arizona. This position is accepted as the best available evidence of the original corner position.

Dependent Resurvey, Fifth Guide Mer. W.,
T. 20 N., bet. Rs. 18 and 19 W.,
Gila and Salt River Mer., Arizona

CHAINS

from which

The SW cor. of said lot 8, bears N. 45° E.,
85.7 lks. dist., monumented with a re-bar,
½ in. diam., projecting 6 ins. above ground.

The NE cor. of said lot 1, bears S. 45° W.,
85.7 lks. dist., monumented with a re-bar,
½ in. diam., projecting 6 ins. above ground.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins.
in the ground, with brass cap mkd.

T20N	
R19W	R18W
S12	S7
S13	S18
1977	

A granite stone, 20x13x9 ins., mkd. with 4 notches
on one edge and 2 notches on the opposite edge, found
lying loose on the ground is deposited alongside the
cor.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam., set
22 ins. in the ground for a reference monument,
bears S. 45° E., 53 lks. dist., mkd.
T20N R18W S18 RM 35 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set
22 ins. in the ground for a reference monument,
bears N. 45° W., 98.5 lks. dist., mkd.
T20N R19W S12 RM 65 FT. 1977 and an
arrow pointing to the cor.

Cor. is located at the W. edge of a road extending N.,
the S. edge of a road extending E., the E. edge of a
road extending S., and in the center of two roads
extending W.

From the cor. of secs. 1, 6, 7, and 12, monumented
with a granite stone 19x13x7 ins., firmly set 12 ins.
in the ground, mkd. with 1 notch on the N. edge and
5 notches on the S. edge.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 38 ins.
in the ground, with brass cap mkd.

T20N	
R19W	R18W
S 1	S 6
S12	S 7
1977	

Dependent Resurvey, Fifth Guide Mer. W.,
T. 20 N., bet. Rs. 18 and 19 W.,
Gila and Salt River Mer., Arizona

CHAINS

Deposit the mkd. stone alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 24 ins. in the ground, for a reference
monument, bears N. 45° E., 75.8 lks. dist.,
mkd. T20N R18W S6 RM 50 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 20 ins. in the ground for a reference
monument, bears S. 45° W., 75.8 lks. dist.,
mkd. T20N R19W S12 RM 50 FT. 1977 and an
arrow pointing to the cor.

Cor. is located at the E. edge of a road extending N.,
the N. edge of a road extending E., the W. edge of a
road extending S., and the S. edge of a road extending
W.

N. 0°09' W., bet. secs. 1 and 6.

Over gently rolling land, along E. edge of road,
through medium undergrowth.

40.05 Point for the ¼ sec. cor. of secs. 1 and 6, at propor-
tionate dist.; there is no remaining evidence of the
original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins.
in the ground, with brass cap mkd.

T20N
¼
R19W R18W
S 1 | S 6
1977

Raise a mound of stone, 3 ft. base, 2 ft. high, W.
of the cor.

80.84 Graded road, bears E. and W.

81.01 The closing cor. of secs. 1 and 6, on the Fifth
Standard Parallel North, monumented with a granite
stone, 23x10x9 ins., firmly set 18 ins. in the ground,
mkd. CC XX N and 6 grooves on the S. face, XIX W and
6 grooves on the W. face, and XVIII W with 6 grooves
on the E. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 26 ins.
in the ground, with brass cap mkd.

T21N R18W
S31
S 1 | S 6
R19W R18W
T20N
CC
1977

Dependent Resurvey, Fifth Guide Mer. W.,
T. 20 N., bet. Rs. 18 and 19 W.,
Gila and Salt River Mer., Arizona

CHAINS

Deposit the mkd. stone alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° E., 83.3 lks. dist.,
mkd. T20N R18W CC S6 RM 55 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears N. 45° W., 83.3 lks. dist.,
mkd. RM 55 FT. 1977 and an arrow pointing
to the cor.

From this closing cor., the stan. ¼ sec. cor. of sec.
31, T. 21 N., R. 18 W., baars N. 89°55' E., 3.31 chs.
dist., heretofore described.

Dependent Resurvey of a Portion of the South Boundary,
T. 20 N., R. 18 W., Gila and Salt River Meridian,
Arizona.

(Restoring the 1909 survey by Fred W. Rodolf)

From the cor. of secs. 4, 5, 32, and 33, on the S.
bdy. of the Tp., monumented with a volcanic stone,
17x10x7 ins., firmly set 3 ins. below surface of the
ground, mkd. with 4 notches on the E. edge and 2
notches on the W. edge.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 38 ins.
in the ground, with brass cap mkd.

T20N R18W
S32|S33
S 5|S 4
T19N
1977

Deposit the mkd. stone alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. in diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° E., 68.2 lks. dist.,
mkd. T19N R18W S4 RM 45 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. in diam.,
set 20 ins. in the ground for a reference
monument, bears N. 45° W., 68.2 lks. dist.,
mkd. T20N R18W S32 RM 45 FT. 1977 and an
arrow pointing to the cor.

Dependent Resurvey of a Portion of the South Boundary,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in the center of a bladed road, bears E. and W., the W. edge of a road extending N., and at the E. edge of a road extending S.</p> <p>N. 89°53' W., bet. secs. 5 and 32.</p> <p>Over gently rolling land, through medium undergrowth, along bladed road, bears E. and W.</p>
30.30	Telephone line, bears N. 53° E. and S. 53° W.
33.35	Asphalt road, bears N. 53° E. and S. 53° W.
39.99	<p>The ¼ sec. cor. of secs. 5 and 32, monumented with an iron pipe, 35 ins. long, 1 inch in diam., firmly set 6 ins. below ground, with a granite stone, 19x13x9 ins., mkd. ¼ on the N. face, set alongside the iron pipe.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S32 S 5 T19N 1977</p> <p>Deposit the mkd. stone and reset the iron pipe alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p>
3.60	Power line, bears N. 53° E. and S. 53° W.
39.99	<p>The cor. of secs. 5, 6, 31, and 32, monumented with a granite stone, 14x11x7 ins., firmly set 10 ins. in the ground, mkd. with 5 notches on the E. edge and 1 notch on the W. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S31 S32 S 6 S 5 T19N 1977</p> <p>Deposit the mkd. stone alongside the iron post. from the cor.</p>

Dependent Resurvey of a Portion of the South Boundary,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	<p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 75.8 lks. dist., mkd. T20N R18W S32 RM 50 FT. 1977 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 45° W., 121.2 lks. dist., mkd. T20N R18W S31 RM 80 FT. 1977 and an arrow pointing to the cor.</p> <p>From this point a U.S. Coast and Geodetic Survey monument, bears S. 9°22' W., 39.093 chs. dist., a bronze disk, set in concrete, mkd. "AZIMUTH MARK FIG SPRING 1948."</p>				
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona.</p>				
	<p>(Restoring the 1910 Survey by Fred W. Rodolf)</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the cor. of secs. 27, 28, 33, and 34, monumented with a volcanic stone, 17x14x10 ins., firmly set 11 ins. in the ground, mkd. with 3 notches on the E. edge and 1 notch on the S. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R18W</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S33</td> <td style="padding: 0 5px;">S34</td> </tr> </table> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located 1 link E. of a fence bearing N. and S., at the E. edge of a road extending N., the S. edge of a road extending E., in the center of a road extending S., and at the N. edge of a road extending W.</p> <p>N. 0°08' E., bet. secs. 27 and 28.</p> <p>Along the E. edge of a bladed road and fence line bearing N. and S.</p> <p>2.85 Fence cor.; fences extend N. 50° E. and S.</p> <p>3.10 Telephone line, bears N. 50° E. and S. 50° W.</p>	S28	S27	S33	S34
S28	S27				
S33	S34				

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
5.60	Asphalt road, bears N. 50° E. and S. 50° W.
18.40	Power line, bears N. 47° E. and S. 47° W.
39.93	<p>The ¼ sec. cor. of secs. 27 and 28, monumented with a granite stone, 20x16x6 ins., firmly set 10 ins. below the surface of the ground, mkd. ¼ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S28 S27 1977</p> <p>Deposit the mkd. stone alongside the iron post. from the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° W., 90.9 lks. dist., mkd. T20N R18W S28 ¼ RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° W., 90.5 lks. dist., mkd. T20N R18W S28 ¼ RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is located in the center of a bladed road, bears N. and S., and 68 lks. E. of a fence line bearing N. and S.</p> <p style="text-align: center;">_____</p> <p>N. 0°07' W., beginning new measurement.</p> <p>Along the center of a bladed road, bears N. and S.</p>
40.05	<p>The cor. of secs. 21, 22, 27, and 28, determined at midpoint bet. the SE cor. of lot 1046, Paradise Acres Unit 5, in sec. 21, and the NW cor. of lot 1, Paradise Acres Unit 2, in sec. 27, as recorded on private survey plats and on file at the Mohave County Court House in Kingman, Arizona. This position is accepted as the best available evidence of the original corner position.</p> <p>from which</p> <p>The SE cor. of said lot 1046, bears N. 45° W., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 6 ins. above ground.</p> <p>The NW cor. of said lot 1, bears S. 45° W., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 6 ins. above ground.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S21 S22 S28 S27 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 113.6 lks. dist., mkd. T20N R18W S22 RM 75 FT. 1977 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° W., 90.9 lks. dist., mkd. T20N R18W S28 RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p>A fence cor., bears S. 56°23' W., 80.3 lks. dist.; fences extend S. and W.</p> <p>Cor. is located at the E. edge of a road extending N., the N. edge of a road extending E., the S. edge of a road extending W. and in the center of a road extending S.</p>
<p>23.20</p> <p>25.50</p> <p>35.20</p> <p>40.02</p>	<p>From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp.</p> <p>N. 0°03' W., bet. secs. 32 and 33.</p> <p>Along the W. edge of a bladed road, bears N. and S.</p> <p>Telephone line, bears N. 53° E. and S. 53° W.</p> <p>Asphalt road, bears N. 53° E. and S. 53° W.</p> <p>Power line, bears N. 53° E. and S. 53° W.</p> <p>The ¼ sec. cor. of secs. 32 and 33, monumented with a volcanic stone, 12x10x5 ins., firmly set 10 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S32 S33 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 1½ ft. high, W. of the cor.</p> <p>Cor. is located 18 lks. W. of the center of a bladed road, bears N. and S.</p> <p>From this point a U.S. Geological Survey Bench Mark, published elevation 2302 ft. above mean sea level, bears S. 3°03' E., 15.52 chs. dist., an aluminum disk, set in a concrete base, 6 ins. square, projecting 4 ins. above ground, dated 1965.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 28, 29, 32, and 33, monumented with a volcanic stone, 21x12x12 ins., firmly set 15 ins. in the ground, mkd. with 4 grooves on the E. face and 1 groove on the S. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 38 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S29 S28 S32 S33 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>from the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 75.8 lks. dist., mkd. T20N R18W S28 RM 50 FT. 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears S. 45° W., 75.8 lks. dist., mkd. T20N R18W S32 RM 50 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is located at the E. edge of a road extending N., the N. edge of a road extending E., the S. edge of a road extending W., and the W. edge of a road extending S.</p>
.20 4.20 7.40 23.30 40.02	<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 89°51' W., bet. secs. 28 and 33.</p> <p>Over gently rolling land, through medium creosote, along the N. edge of a bladed road, bears E. and W.</p> <p>Bladed road, bears N. and S.</p> <p>Telephone line, bears N. 50° E. and S. 50° W.</p> <p>Asphalt road, bears N. 50° E. and S. 50° W.</p> <p>Power line, bears N. 47° E. and S. 47° W.</p> <p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S28 S33 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located 25 lks. N. of the center of a bladed road, bears E. and W.</p> <p>80.04 The cor. of secs. 28, 29, 32, and 33.</p> <hr/> <p>N. 0°01' E., bet. secs. 28 and 29.</p> <p>Along the E. edge of a bladed road, bears N. and S.</p> <p>40.00 The ¼ sec. cor. of secs. 28 and 29, monumented with a volcanic stone 13x10x9 ins., firmly set 10 ins. in the ground, mkd. ¼ on the W. face, with a mound of stone, 3 ft. base, 6 ins. high, N. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R18W</p> <p> ½</p> <p>S29 S28</p> <p> </p> <p> 1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 25 lks. E. of the center of a bladed road, bears N. and S.</p> <hr/> <p>N. 0°01' W., beginning new measurement.</p>
<p>40.01</p>	<p>The cor. of secs. 20, 21, 28, and 29, determined at midpoint bet. the SE cor. of lot 1061, sec. 21, and the NE cor. of lot 309, sec. 29, as recorded on private survey plats Paradise Acres Unit 5 and Paradise Acres Unit 3, respectively, on file at the Mohave County Court House in Kingman, Arizona.</p> <p>The SE cor. of lot 1061, sec. 21, bears N. 45° E., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 6 ins. above ground.</p> <p>The NE cor. of lot 309, sec. 29, bears S. 45° W., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 8 ins. above ground.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. below the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R18W</p> <p>S20 S21</p> <p>S29 S28</p> <p> 1977</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The original monument, a volcanic stone, 20x12x10 ins., mkd. with 4 grooves on the E. face and 2 grooves on the S. face, found lying loose on the ground, is deposited alongside the iron post.</p> <p>from the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45° E., 75.8 lks. dist., mkd. T20N R18W S28 RM 50 FT. 1977 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground for a reference monument, bears N. 45° W., 75.8 lks. dist., mkd. T20N R18W S20 RM 50 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is located in the center of a gate in an E. and W. fence, at the W. edge of a road extending N., the S. edge of a road extending E., the E. edge of a road extending S. and the N. edge of a road extending W.</p>
<p>40.07</p>	<p>From the cor. of secs. 21, 22, 27, and 28.</p> <p>N. 89°49' W., bet. secs. 21 and 28.</p> <p>Over gently rolling land, through medium undergrowth, along the S. edge of a bladed road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 21 and 28, monumented with a volcanic stone, 17x11x7 ins., firmly set 13 ins. in the ground, mkd. ¼ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S21 S28 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located in an E. and W. fence, 20 lks. S. of the center of a bladed road, bears E. and W.</p> <p style="text-align: center;">_____</p> <p>N. 89°49' W., beginning new measurement.</p> <p>Along a fence, bears S. 89°49' E. and N. 89°49' W.</p>
<p>39.97</p>	<p>The cor. of secs. 20, 21, 28 and 29.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
39.95	<p>N. 0°02' W., bet. secs. 20 and 21.</p> <p>Over gently rolling land, through medium undergrowth, along the W. edge of a bladed road, bears N. and S.</p> <p>The ¼ sec. cor. of secs. 20 and 21, monumented with a volcanic stone, 16x13x10 ins., firmly set 12 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S20 S21 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 24 lks. W. of the center of a bladed road, bears N. and S.</p>
39.99	<p>N. 0°01' W., beginning new measurement.</p> <p>The cor. of secs. 16, 17, 20, and 21, determined at calculated distances to and on line bet. the NW cor. of lot 806, Paradise Acres Unit 5, in sec. 21, and the SE cor. of lot 8, block P, Golden Valley Ranches Unit 2, in sec. 17, as recorded on private survey plats on file at the Mohave County Court House in Kingman, Arizona. This position is accepted as the best available evidence of the original corner position.</p> <p>from which</p> <p style="padding-left: 40px;">The NW cor. of said lot 806, bears S. 45° E., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 3 ins. above ground.</p> <p style="padding-left: 40px;">The SE cor. of said lot 8, block P, bears N. 45° W., 85.7 lks. dist., monumented with a re-bar, ½ in. diam., projecting 6 ins. above ground.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S17 S16 S20 S21 1977</p> <p>The original monument, a granite stone, 24x12x6 ins., mkd. with 4 grooves on the E. face and 3 grooves on the S. face, found lying loose on the ground, is deposited alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS

from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears N. 45° E., 98.5 lks. dist.,
mkd. T20N R18W S16 RM 65 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° W., 98.5 lks. dist.,
mkd. T20N R18W S20 RM 65 FT. 1977 and an
arrow pointing to the cor.

Cor. is located at the W. edge of a road extending N.,
the center of a road extending E., the W. edge of a
road extending S., and the S. edge of a road extending
W.

From the cor. of secs. 8, 9, 16, and 17, monumented
with a volcanic stone, 18x11x7 ins., firmly set 17 ins.
in the ground, mkd. with 4 grooves on the E. face and
4 grooves on the S. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 38 ins.
in the ground, with brass cap mkd.

T20N R18W
S 8 | S 9
S17 | S16
1977

Deposit the mkd. stone alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 20 ins. in the ground for a reference
monument, bears S. 45° E., 106.1 lks. dist.,
mkd. T20N R18W S16 RM 70 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 20 ins. in the ground for a reference
monument, bears N. 45° W., 106.1 lks. dist.,
mkd. T20N R18W S8 RM 70 FT. 1977 and an
arrow pointing to the cor.

Cor. is located in the center of a road extending S.
and at the S. edge of a road extending W.

N. 0°04' W., bet. secs. 8 and 9.

Over gently rolling land, through medium undergrowth.

40.00

The ¼ sec. cor. of secs. 8 and 9, monumented with a
malpais stone, 16x11x10 ins., firmly set 11 ins. in
the ground, mkd. ¼ on the W. face.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S 8 S 9 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>North, beginning new measurement.</p> <p>The cor. of secs. 4, 5, 8, and 9, monumented with a malpais stone, 20x13x10 ins., firmly set 15 ins. in the ground, mkd. with 4 grooves on the E. face and 5 grooves on the S. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S 5 S 4 S 8 S 9 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located at the E. edge of a dim road extending N., and at the S. edge of a road extending W.</p>
40.00	<p>From the cor. of secs. 5, 6, 31, and 32, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°04' W., bet. secs. 31 and 32.</p> <p>Through medium undergrowth, along the E. edge of a bladed road, bears N. and S.</p> <p>The ¼ sec. cor. of secs. 31 and 32, monumented with a volcanic stone, 18x10x8 ins., firmly set 10 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 13 ins. in the ground to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S31 S32 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS

40.00

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the cor.

Cor. is located 28 lks. E. of a bladed road, bears N. and S.

N. 0°02' W., beginning new measurement.

The cor. of secs. 29, 30, 31, and 32, determined at midpoint bet. the SW cor. of lot 549, Paradise Acres Unit 3, in sec. 29 and the NE cor. of lot 1077, Paradise Acres Unit 6, in sec. 31, as recorded on private survey plats on file at the Mohave County Court House in Kingman, Arizona. This position is accepted as the best available evidence of the original corner position.

from which

The SW cor. of said lot 549, bears N. 45° E., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 4 ins. above ground.

The NE cor. of said lot 1077, bears S. 45° W., 64.3 lks. dist., monumented with a re-bar, ½ in. diam., projecting 6 ins. above ground.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, with brass cap mkd.

T20N R18W
S30|S29
S31|S32
1977

The original monument, a volcanic stone, 19x13x9 ins., mkd. with 5 notches on one edge and 1 notch on an adjacent edge, found lying loose on the ground, is deposited alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° E., 75.8 lks. dist., mkd. T20N R18W S32 RM 50 FT. 1977 and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° W., 75.8 lks. dist., mkd. T20N R18W S30 RM 50 FT. 1977 and an arrow pointing to the cor.

Cor. is located at the W. edge of a road extending N., the S. edge of a road extending E., the E. edge of a road extending S., and the N. edge of a road extending W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS		
39.98	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>N. 89°53' W., bet. secs. 29 and 32.</p> <p>Over gently rolling land, through medium undergrowth, along the S. edge of a bladed road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 29 and 32, monumented with a volcanic stone, 12x12x8 ins., firmly set 6 ins. in the ground, mkd. ¼ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ $\frac{S29}{S32}$ 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the cor.</p> <p>Cor. is located 27 lks. S. of the center of a bladed road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°55' W., beginning new measurement.</p>	
39.99	<p>The cor. of secs. 29, 30, 31, and 32.</p> <hr style="width: 100%;"/> <p>N. 89°41' W., bet. secs. 30 and 31.</p> <p>Along the N. edge of a bladed road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 30 and 31, monumented with a volcanic stone, 20x8x8 ins. firmly set 12 ins. in the ground, mkd. ¼ on the N. face, with a mound of stone 2 ft. base, 1 ft. high, N. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ $\frac{S30}{S31}$ 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Rebuild the mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located 25 lks. N. of the center of a bladed road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
39.47	<p>N. 89°42' W., beginning new measurement.</p> <p>Intersect the W. bdy. of the Tp., at the cor. of secs. 25, 30, 31, and 36, heretofore described.</p>
39.99	<p>From the cor. of secs. 29, 30, 31, and 32.</p> <p>N. 0°03' W., bet. secs. 29 and 30.</p> <p>Along the W. edge of a bladed road, bears N. and S.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 29 and 30, monumented with a volcanic stone, 18x16x12 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on the W. face.</p> <p>At the cor. point.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W $\frac{1}{4}$ S30 S29 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W. of the cor.</p> <p>Cor. is located 24 lks. W. of the center of a bladed road, bears N. and S.</p>
40.01	<p>N. 0°01' E., beginning new measurement.</p> <p>Point for the cor. of secs. 19, 20, 29, and 30, at proportionate dist. The original monument, a granite stone, 19x12x10 ins., mkd. with 5 grooves on the E. face and 2 grooves on the S. face, was found lying loose on the ground. There is no remaining evidence of lot cors. in secs. 19 and 29, as recorded on private survey plats at the Mohave County Court House in Kingman, Arizona.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S19 S20 S30 S29 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 1 link S. of a fence, bears E. and W., at the E. edge of a road extending N., the N. edge of a road extending E., the W. edge of a road extending S., and the S. edge of a road extending W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>From the cor. of secs. 20, 21, 28, and 29.</p> <p>N. 89°53' W., bet. secs. 20 and 29.</p> <p>Over gently rolling land, through medium undergrowth, along a fence, bears E. and W., on the N. edge of a road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 20 and 29, monumented with a volcanic stone 20x12x10 ins., firmly set 16 ins. in the ground, mkd. ¼ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R18W</p> <p>¼ <u>S20</u></p> <p> S29</p> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located in a fence, bears E. and W.</p>
40.00	<p>N. 89°55' W., beginning new measurement.</p> <p>The cor. of secs. 19, 20, 29, and 30.</p>
40.01	<p>N. 89°52' W., bet. secs. 19 and 30.</p> <p>Over gently rolling land, through medium undergrowth, along a fence, bears E. and W., on the S. side of a bladed road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 19 and 30, monumented with a volcanic stone, 18x15x12 ins., firmly set 12 ins. in the ground, mkd. ¼ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R18W</p> <p>¼ <u>S19</u></p> <p> S30</p> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 3 ft. high, N. of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located in a fence, bears E. and W., 20 lks. S. of the center of a bladed road, bears E. and W.</p> <hr/> <p>N. 89°57' W., beginning new measurement.</p> <p>39.36 Intersect the W. bdy. of the Tp., at the cor. of secs. 19, 24, 25, and 30, heretofore described.</p>
	<p>From the cor. of secs. 19, 20, 29, and 30.</p> <p>N. 0°07' W., bet. secs. 19 and 20.</p> <p>Over gently rolling land, through medium undergrowth, along the E. edge of a bladed road, bears N. and S.</p> <p>40.02 The ¼ sec. cor. of secs. 19 and 20, monumented with a volcanic stone, 14x12x9 ins., firmly set 12 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S19 S20 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Deposit broken green glass at base of the iron post.</p> <p>Cor. is located 24 lks. E. of the center of a bladed road, bears N. and S.</p>
	<hr/> <p>N. 0°03' W., beginning new measurement.</p> <p>39.92 The cor. of secs. 17, 18, 19 and 20, monumented with a volcanic stone, 17x14x9 ins., firmly set 11 ins. in the ground, mkd. with 5 grooves on the E. face and 2 grooves on the S. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S18 S17 S19 S20 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS

from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° E., 60.6 lks. dist.,
mkd. T20N R18W S20 RM 40 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears N. 45° W., 60.6 lks. dist.,
mkd. T20N R18W S18 RM 40 FT. 1977 and an
arrow pointing to the cor.

Cor. is located in the center of a bladed road, bears
N. and S., at the S. edge of a road extending E., and
the N. edge of a road extending W.

From the cor. of secs. 16, 17, 20, and 21.

N. 89°51' W., bet. secs. 17 and 20.

Over gently rolling land, through medium undergrowth,
along the S. edge of a bladed road, bears E. and W.

40.03

The ¼ sec. cor. of secs. 17 and 20, monumented with a
volcanic stone, 15x12x8 ins., firmly set 12 ins. in
the ground, mkd. ¼ on the N. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 34 ins.
in the ground, with brass cap mkd.

T20N R18W

¼ $\frac{S17}{S20}$

1977

Deposit the mkd. stone alongside the iron post.

from the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° E., 60.6 lks. dist.,
mkd. T20N R18W S20 ¼ RM 40 FT. 1977 and an
arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam.,
set 22 ins. in the ground for a reference
monument, bears S. 45° W., 60.6 lks. dist.,
mkd. T20N R18W S20 ¼ RM 40 FT. 1977 and an
arrow pointing to the cor.

Cor. is located at the S. edge of a bladed road, bears
E. and W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.04	<p>N. 89°57' W., beginning new measurement.</p> <p>The cor. of secs. 17, 18, 19, and 20.</p>
39.98	<p>N. 89°51' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land, through medium undergrowth, along the N. edge of a bladed road, bears E. and W.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 18 and 19, monumented with a volcanic stone, 14x10x6 ins., firmly set 12 ins. in the ground, mkd. $\frac{1}{4}$ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W $\frac{1}{4}$ $\frac{S18}{S19}$ 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located 20 lks. N. of the center of a bladed road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°40' W., beginning new measurement.</p> <p>Intersect the W. bdy. of the Tp., at the cor. of secs. 13, 18, 19, and 24, heretofore described.</p>
40.05	<p>From the cor. of Secs. 17, 18, 19, and 20.</p> <p>North, bet. secs. 17 and 18.</p> <p>Along a bladed road, bears N. and S.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W $\frac{1}{4}$ S18 S17 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS								
80.10	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 45° E., 295.5 lks. dist., mkd. T20N R18W ¼ S17 RM 195 FT. 1977 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears S. 45° W., 204.5 lks. dist., mkd. T20N R18W ¼ S18 RM 135 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is located near the W. edge of a bladed road, bears N. and S., and in a wash area.</p> <p>The cor. of secs. 7, 8, 17, and 18, monumented with malpais stone, 19x16x12 ins., firmly set 16 ins. in the ground, mkd. with 5 grooves on the E. face, no other marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T20N R18W</p> <table border="0"> <tr> <td>S 7</td> <td> </td> <td>S 8</td> </tr> <tr> <td>S18</td> <td> </td> <td>S17</td> </tr> </table> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>from the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 45° E., 90.9 lks. dist., mkd. T20N R18W S8 RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears S. 45° W., 90.9 lks. dist., mkd. T20N R18W S18 RM 60 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is at the W. edge of a bladed road, bears N. and S. and at the S. edge of a road extending E. and W.</p>	S 7		S 8	S18		S17	
S 7		S 8						
S18		S17						
40.03	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>N. 89°54' W., bet. secs. 8 and 17.</p> <p>Over gently rolling land, through medium undergrowth, along the S. edge of a bladed road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 8 and 17, monumented with a volcanic stone, 18x10x6 ins., firmly set 12 ins. in the ground, mkd. ¼ on the N. face.</p>							

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.03	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ $\frac{S\ 8}{S17}$ 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N. of the cor.</p> <p>Cor. is located 30 lks. S. of the center of a bladed road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°53' W., beginning new measurement.</p> <p>The cor. of secs. 7, 8, 17, and 18.</p>
39.99	<p>N. 89°59' W., bet. secs. 7 and 18.</p> <p>Over gently rolling land, through medium undergrowth, along the S. edge of a bladed road, bears E. and W.</p> <p>The ¼ sec. cor. of secs. 7 and 18, monumented with a volcanic stone, 16x14x6 ins., firmly set 10 ins. in the ground, mkd. ¼ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ $\frac{S\ 7}{S18}$ 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.</p> <p>Cor. is located 35 lks. S. of the center of a bladed road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°38' W., beginning new measurement.</p> <p>Intersect the W. bdy. of the Tp., at the cor. of secs. 7, 12, 13, and 18, heretofore described.</p>
38.94	<p>From the cor. of secs. 7, 8, 17, and 18.</p> <p>N. 0°01' W., bet. secs. 7 and 8.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>Over gently rolling land, through medium undergrowth, along the W. edge of a bladed road, bears N. and S.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 36 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W $\frac{1}{4}$ S 7 S 8 1977</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 10° E., 204.5 lks. dist., mkd. T20N R18W $\frac{1}{4}$ S8 RM 135 FT. 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 10° W., 204.5 lks. dist., mkd. T20N R18W $\frac{1}{4}$ S7 RM 135 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is located in a bladed road, bears N. and S., and in a wash area.</p>
80.02	<p>The cor. of secs. 5, 6, 7, and 8, monumented with a volcanic stone, 17x11x8 ins., firmly set 14 ins. in the ground, mkd. with 5 grooves on the E. face and 5 grooves on the S. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 40 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W S 6 S 5 S 7 S 8 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>from the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. in diam., set 20 ins. in the ground, for a reference monument, bears S. 45° E., 60.6 lks. dist., mkd. T20N R18W S8 RM 40 FT. 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. in diam., set 20 ins. in the ground, for a reference monument, bears N. 45° W., 60.6 lks. dist., mkd. T20N R18W S6 RM 40 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. is located in the center of a bladed road bears N. and S., the N. edge of a road extending W., and the S. edge of a road extending E.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 4, 5, 8, and 9.</p> <p>N. 89°53' W., bet. secs. 5 and 8.</p> <p>Over gently rolling land, through medium undergrowth, along the S. edge of a bladed road, bears E. and W.</p> <p>40.00 Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W $\frac{1}{4}$ $\frac{S\ 5}{S\ 8}$ 1977</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N. of the cor.</p> <p>Cor. is located 20 lks. S. of the center of a bladed road, bears E. and W.</p> <p>80.00 The cor. of secs. 5, 6, 7, and 8.</p>
	<p>N. 89°59' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land, through medium undergrowth, along the N. edge of a bladed road, bears E. and W.</p> <p>40.00 The $\frac{1}{4}$ sec. cor. of secs. 6 and 7, monumented with a basalt stone, 16x11x8 ins., firmly set 14 ins. in the ground, mkd. $\frac{1}{4}$ on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W $\frac{1}{4}$ $\frac{S\ 6}{S\ 7}$ 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N. of the cor.</p> <p>Cor. is located 20 lks. N. of a bladed road, bears E. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°35' W., beginning new measurement.</p> <p>38.99 Intersect the W. bdy. of the Tp., at the cor. of secs. 1, 6, 7, and 12, heretofore described.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the cor. of secs. 5, 6, 7, and 8.</p> <p>N. 0°02' W., bet. secs. 5 and 6.</p> <p>Along a bladed road, bears N. and S.</p> <p>40.01 The ¼ sec. cor. of secs. 5 and 6, monumented with a granite stone, 18x7x10 ins., firmly set 15 ins. in the ground, mkd. ¼ on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T20N R18W ¼ S 6 S 5 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of the cor.</p> <p>from which</p> <p style="padding-left: 40px;">A re-bar, ½ in. diam., projecting 6 ins. above the ground, bears N. 63° E., 68.2 lks. dist.</p> <p style="padding-left: 40px;">A re-bar, ½ in. diam., projecting 6 ins. above the ground, bears S. 63° E., 68.2 lks. dist.</p> <p>Cor. is located 23 lks. W. of the center of a bladed road, bears N. and S.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0°01' E., beginning new measurement.</p>
41.20	Graded road, bears E. and W.
41.41	<p>Point for the closing cor. of secs. 5 and 6, on the Fifth Standard Parallel North, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21N R18W S32 S 6 S 5 T20N R18W CC 1977</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 45° E., 83.3 lks. dist., mkd. RM 55 FT. 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam.,</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 20 N., R. 18 W., Gila and Salt River Meridian, Arizona

CHAINS

set 24 ins. in the ground for a reference monument, bears S. 45° W., 83.3 lks. dist., mkd. T20N R18W S6 CC RM 55 FT. 1977 and an arrow pointing to the cor.

Cor. is located at the W. edge of a bladed road, bears N. and S., and at the N. edge of a graded road, bears E. and W.

From the closing cor., the $\frac{1}{4}$ sec. cor. of sec. 32, T. 21 N., R. 18 W., bears N. 89°55' E., 4.22 chs. dist., heretofore described.

The point for the $\frac{1}{4}$ sec. cor. of sec. 6 only, T. 20 N., R. 18 W., is at proportionate dist. on the N. bdy. of sec. 6.

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T21N R18W
<u> </u>
$\frac{1}{4}$ S 6
T20N R18W
1977

Raise a mound of stone, 3 ft. base, 2 ft. high, S. of the cor.

Cor. is 24 lks. N. of the center of a graded road, bears E. and W.

From this point, the stan. cor. of secs. 31 and 32, T. 21 N., R. 18 W., bears N. 89°57' E., 4.21 chs. dist., heretofore described.

GENERAL DESCRIPTION

The land encompassed in this resurvey is located about 12 miles southwest of Kingman, Arizona. An asphalt road crosses the southeast portion of the township from which dirt roads extend, providing access. Drainage is generally south via the Sacramento Wash, which enters on the north boundary of sec. 6 and crosses the township departing at the south boundary of sec. 32. Elevations range from about 2,540 feet above sea level in section 32.

The terrain is gently rolling and has a cover of creosote, native grasses, cacti, and in the southern portion, yucca.

There is no evidence of minerals in the area. Several sections have been subdivided into lots and staked, with roads bladed along certain lot lines. At the present time, none of the lots are occupied and the only obvious use of the land is for grazing.

The mean of a considerable number of observations of the magnetic declination throughout the resurvey is 15°00' E., with a range of 2°00' in local attraction.

CHAINS

CERTIFICATE OF SURVEY

(I ~~We~~), Harry K. Smith, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of April, 19 77, (I ~~We~~) have dependently resurveyed a portion of the Fifth Standard Parallel North on the south boundaries of Townships 21 North, Ranges 18 and 19 West, a portion of the west boundary (Fifth Guide Meridian West) and the south boundary and subdivisional lines of Township 20 North, Range 18 West.

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 1, 1978
(Date)

Harry K. Smith
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the Fifth Standard Parallel North on the south boundaries of Townships 21 North, Ranges 18 and 19 West, a portion of the west boundary (Fifth Guide Meridian West and the south boundary and subdivisional lines of Township 20 North, Range 18 West, of the Gila and Salt River Meridian, Arizona.

executed by Harry K. Smith, Cadastral Surveyor
having been critically examined and found correct, are hereby approved.

MAY 8 1978
(Date)

Bernard W. Halper
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 20 N., R. 18 W., G&SRM., Arizona, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 - 626