

ORIGINAL

BOOK 5061

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the Dependent Resurvey of

A Portion of the South and North Boundaries,

A Portion of the Subdivisional Lines

and

Subdivision of Sections 26 and 27

Township 6 North, Range 27 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Harry K. Smith, Cadastral Surveyor

Under special instructions dated September 19, 19 75, approved September 19, 1975,

, which provided for the surveys included under U.S. Survey/Group
Number 580, and assignment instructions dated September 19, 19 75.

Survey commenced October 7, 19 75

Survey completed November 26, 19 75

BOOK 5061

INDEX DIAGRAM

Township 6 North, Range 27 E.
3

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
Fort Apache 19 20		21	22	23	24
Indian Reservation		17	16	11	7
30	29	28	15 27	10 26	6 25
		15	14	9	5
31	32	33	34	35	36
			12	8	3
				1	

Subdivision, sec. 26-----page 18
 Subdivision, sec. 27-----page 20

T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south and north boundaries, a portion of the subdivisional lines, and the subdivision of sections 26 and 27.

That portion of the east boundary of the White Mountain Indian Reservation within this township, and the township boundaries and subdivisional lines outside of the White Mountain Indian Reservation, were surveyed by W. R. Fitzgerald, Deputy Surveyor, in 1883. The north boundary of the White Mountain Indian Reservation, within this township, was surveyed by Jesse B. Wright, U. S. Deputy Surveyor, in 1906. William B. Kimmel, U. S. Surveyor, resurveyed that portion of the east boundary of the White Mountain Indian Reservation within this township, in 1913, and resurveyed a portion of the south boundary of the township in 1916. The east and north boundaries of the township were resurveyed in 1940 by Frank Motech, Public Land Surveyor, Ty White, Assistant Cadastral Engineer, and Claude F. Warner, Assistant Cadastral Engineer. Certain cadastral survey corners on the boundary of the White Mountain Indian Reservation were remonumented by John H. Witmer, Cadastral Surveyor, in 1969, and Marlin G. Livermore II, Cadastral Surveyor, in 1970.

This survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 580, Arizona, dated September 19, 1975.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations, and refer to the true meridian.

The geographic positions of the corner of sections 1, 2, 35 and 36, on the south boundary of the township, as scaled from the advance sheet of the Geological Survey quadrangle map, NUTRIOS0 2 SW., ARIZ., prepared in 1958, is as follows:

Latitude 33° 51.8' N. Longitude 109° 27.3' W.

The mean magnetic declination is 13° E.

Dependent Resurvey of a Portion of the S. Bdy. of T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona
(Restoring a portion of the 1883 survey by W. R. Fitzgerald)

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 2 and 35, on the S. bdy. of the Tp., monumented with a mound of stone, 3 ft. base, 1 ft. high, from which the original bearing tree

A pine, 24 ins. diam., bears N. 40° W., 22 lks.
dist., mkd. $\frac{1}{4}$ S BT.

At the cor. pt.

Dependent Resurvey of a Portion of the S Bdy.
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground and in a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E $\frac{S35}{\frac{1}{4} S 2}$ T5N 1975</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 42° W., 27½ lks. dist., mkd. ¼ S2 BT.</p> <p style="padding-left: 40px;">A white fir, 9 ins. diam., bears N. 51 3/4° W., 81 lks. dist., mkd. ¼ S. 35 BT.</p> <p>N. 89°44' W., bet. secs. 2 and 35.</p> <p>Ascent steep NE slope, through medium timber and undergrowth.</p> <p>2.20 Top of steep ascent, thence over rolling land, edge bears S. 60° E. and N. 60° W.</p> <p>14.10 Track road, bears N. 50° E. and S. 50° W.</p> <p>33.00 Same track road, bears S. 20° E. and N. 20° W.</p> <p>40.04 The pt. for cor. of secs. 2, 3, 34 and 35, determined at record bearing and dist. from the remains of an original bearing tree.</p> <p style="padding-left: 40px;">A fir stump, 17 ins. diam., sawed off 2 ft. above the ground, bears N. 10° W., 7 lks. dist.; a fir tree lying alongside is mkd. T6N R27E S34 BT.</p> <p>At the cor. pt.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E $\frac{S34 S35}{S 3 S 2}$ T5N 1975</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A douglas fir, 16 ins. diam., bears N. 51¼° E., 18.5 lks. dist., mkd. T6N R27E S35BT.</p> <p style="padding-left: 40px;">A douglas fir, 12 ins. diam., bears S. 83¼° E., 123.5 lks. dist., mkd. T5N R27E S2BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears S. 72° W., 78 lks. dist., mkd. T5N R27E S3 BT.</p> <p style="padding-left: 40px;">A douglas fir, 8 ins. diam., bears N. 50¼° W., 51 lks. dist., mkd. T6N R27E S34 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of the cor.</p>

Dependent Resurvey of a Portion of the N Bdy.
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	(Restoring a portion of the 1940 resurvey by Frank Motoh, Ty White and Claude F. Warner)
	<p>From the cor. of secs. 2, 3, 34 and 35, on the N bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 6 ins. above a mound of stone, 2½ ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1940 dependent resurvey of the S bdy. of T. 7 N., R. 27 E., from which the only remaining original bearing tree</p>
	<p>A pine, 21 ins. diam., bears S. 75½° W., 30 lks. dist., mkd. with a healed blaze. This tree is used as a fence cor.; fences extend southerly and westerly.</p>
	<p>And the 1940 bearing trees</p>
	<p>A pine, 32 ins. diam., bears N. 8 3/4° E., 122 lks. dist., mkd. T7N R27E S35 BT.</p>
	<p>A pine, 23 ins. diam., bears S. 46 3/4° E., 75 lks. dist., mkd. T6N R27E S2 BT.</p>
	<p>A pine, 38 ins. diam., bears N. 38½° W., 53 lks. dist., mkd. T7N R27E S34BT. (Record bearing N. 40° W.)</p>
	<p>N. 89°58' W., bet. secs. 3 and 34.</p>
	<p>Over rolling land, through scattering stands of timber.</p>
40.27	<p>The ¼ sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey of the S bdy. of T. 7 N., R. 27 E.</p>
	<p>A mound of stone, 3 ft. base, 1 ft. high, is N of the cor.</p>
	<p>West, beginning new measurement.</p>
	<p>Over gently rolling open grassland.</p>
3.90	<p>Fence, bears N. 65° E. and S. 65° W.</p>
40.31	<p>The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey of the S bdy. of T. 7 N., R. 27 E.</p>
	<p>A mound of stone, 3 ft. base, 2 ft. high, is W of the cor.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona (Restoring the Survey by W. R. Fitzgerald in 1883)</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the Tp., determined at record bearing and dist., from the remains of the original bearing tree,</p>
	<p>A dead fir, 13 ins. diam., bears S. 30° E., 13 lks. dist., mkd. T5N R27E S1 BT, underneath a healed blaze.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

At the cor. pt.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T6N R27E
S35|S36
S 2|S 1

T5N
1975

from which new bearing trees

A fir, 6 ins. diam., bears N. 16½° E., 44 lks. dist., mkd. T6N R27E S36 BT.

A fir, 20 ins. diam., bears S. 4½° E., 176 lks. dist., mkd. T5N R27E S1 BT.

A ponderosa pine, 11 ins. diam., bears S. 67 ¾° W., 47 lks. dist., mkd. T5N R27E S2 BT.

A fir, 9 ins. diam., bears N. 64° W., 25 lks. dist., mkd. T6N R27E S35 BT.

The cor. is located on a S slope.

N. 0°36' E., bet. secs. 35 and 36.

Over rolling land, through medium to dense timber and medium undergrowth.

32.30 Enter open grass land, edge bears S. 50° E. and N. 50° W.

33.70 Abandoned railroad bed, bears S. 55° E. and N. 50° W.

39.19 Pt. for the ¼ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T6N R27E
¼
S35|S36
1975

from which

A ponderosa pine, 12 ins. diam., bears N. 72 ¾° E., 132 lks. dist., mkd. ¼ S 36 BT.

A ponderosa pine, 10 ins. diam., bears N. 39 ¾° W., 116 lks. dist., mkd. ¼ S35 BT.

Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.

39.30 Fence, bears N. 63 ¾° E. and S. 63 ¾° W.; enter medium to dense timber, edge bears N. 65° E. and S. 65° W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS									
78.38	<p>The pt. for the cor. of secs. 25, 26, 35 and 36, determined from the remains of the original bearing tree</p> <p>A pine stump, 22 ins. diam., sawed off 2 ft. above the ground, bears S. 10° W., 21 lks. dist., mkd. S 36 BT (Record markings S35).</p> <p>At the cor. pt.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <table border="0" style="margin-left: auto; margin-right: auto;"> <tr> <td colspan="2">T6N R27E</td> </tr> <tr> <td>S26</td> <td>S25</td> </tr> <tr> <td>S35</td> <td>S36</td> </tr> <tr> <td colspan="2">1975</td> </tr> </table> <p>from which new bearing trees</p> <p>A ponderosa pine, 26 ins. diam., bears N. 51° E., 89½ lks. dist., mkd. T6N R27E S25 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 67° W., 119½ lks. dist., mkd. T6N R27E S35 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N. 23¼° W., 143 lks. dist., mkd. T6N R27E S26 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.</p>	T6N R27E		S26	S25	S35	S36	1975	
T6N R27E									
S26	S25								
S35	S36								
1975									
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 3 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey of the W bdy. of T. 6 N., R. 28 E., from which the remains of the original bearing tree</p> <p>A stump hole, bears S. 77½° W., 58 lks. dist.; a dead pine, 30 ins. diam., lying alongside the stump hole is mkd. T6N R27E S36 BT.</p> <p>The 1940 bearing trees</p> <p>A dead ponderosa pine, 44 ins. diam., bears N. 10° E., 95 lks. dist., mkd. T6N R28E S30 BT.</p> <p>A fir, 23 ins. diam., bears N. 59½° W., 185 lks. dist., mkd. T6N R27E S25 BT.</p> <p>A mound of stone, 2 ft. base, 6 ins. high, is W of the cor.</p> <p>S. 88°27' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through dense timber and undergrowth.</p>								
39.78	<p>Pt. for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>								

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E ¼ $\frac{S25}{S36}$ 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 35° W., 136 lks. dist., mkd. ¼ S36 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 26° W., 106 lks. dist., mkd. ¼ S 25 BT.</p>
59.30	Enter open grass land, edge bears N and S.
79.56	The cor. of secs. 25, 26, 35 and 36.
	<hr/> <p>N. 0°45' E., bet. secs. 25 and 26.</p> <p>Over medium rolling land, through dense timber.</p>
10.50	Leave dense timber, edge bears E and W.
28.00	Logging trail, bears E and W.
28.10	Enter dense timber, edge bears S. 40° E. and N. 40° W.
41.13	Point for the ¼ sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E ¼ $\frac{S26}{S25}$ 1975</p> <p>from which</p> <p style="padding-left: 40px;">A spruce, 14 ins. diam., bears East, 49 lks. dist., mkd. ¼ S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 60° W., 39 lks. dist., mkd. ¼ S26 BT.</p>
45.60	Leave dense timber, edge bears S. 80° E., and N. 80° W.
57.00	Graded road, bears S. 75° E. and N. 75° W.
62.80	Spur, slopes N. 80° W.
64.40	Creek, 20 lks. wide, 2 ft. deep, course SW.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
76.70	Abandoned railroad bed, bears S. 60° W. and N. 65° E.; curving easterly.
82.26	Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R27E $\frac{S23}{S26} \frac{S24}{S25}$ 1975</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.
	<p>From the cor. of secs. 19, 24, 25 and 30, on the E bdy. of the tp., monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, mound of stone, 2½ ft. base, 2 ft. high W of cor., with brass cap mkd. as described in the official records of the 1940 dependent resurvey of the W bdy. of T. 6 N., R. 28 E.</p>
	N. 89°55' W., bet. secs. 24 and 25.
	Over medium rolling grass land.
4.20	Track road, bears S. 50° E. and N. 50° W.
8.00	Fence, bears S. 60° E. and N. 60° W.
16.40	Fence, bears N and S.
16.80	Track road, bears N and S.
27.50	Small wash, drains N. 15° W.
38.90	Ridge, bears N and S.
39.27	Point for the ¼ sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T6N R27E $\frac{1}{4} \frac{S24}{S25}$ 1975</p>
57.80	Creek, 5 lks. wide, course S. 60° W.
78.54	The cor. of secs. 23, 24, 25 and 26.
	N. 2°29' W., bet. secs. 23 and 24.
	Over medium rolling grass land.
14.90	Fence, bears S. 85° E. and N. 85° W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
41.17	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long; $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R27E $\frac{1}{4}$ S23 S24 1975</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p>
43.30	<p>Draw, drains easterly.</p>
68.70	<p>Enter scattering timber.</p>
77.00	<p>Graded road, bears E and SW.</p>
81.70	<p>Fence, bears N. 65° E. and S. 65° W.</p>
82.34	<p>The point for the cor. of secs. 13, 14, 23 and 24, determined at record bearing and dist. from the original bearing tree.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 35 ins. diam., bears S. 25° W., 40 lks. dist., mkd. T6N R27E S23 BT.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R27E S14 S13 S23 S24 1975</p>
	<p>from which new bearing trees</p>
	<p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 64° E., 55 lks. dist., mkd. T6N R27E S13 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears S. $72\frac{1}{4}^\circ$ E., 49 lks. dist., mkd. T6N R27E S24 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 19 ins. diam., bears N. $28\frac{3}{4}^\circ$ W., 83.5 lks. dist., mkd. T6N R27E S14 BT.</p>
	<p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W of cor.</p>
	<hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the tp.</p>
	<p>N. $1^\circ 33'$ E., bet. secs. 34 and 35.</p>
	<p>Over medium rolling land, through dense timber.</p>
13.20	<p>Logging trail, bears S. 25° E. and N. 25° W.</p>
18.20	<p>Logging trail, bears N. 75° E. and S. 75° W.</p>
40.16	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E $\frac{1}{4}$ S34 S35 .1975</p> <p>from which</p> <p style="padding-left: 40px;">A spruce, 12 ins. diam., bears S. 40° E., 66 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p style="padding-left: 40px;">A fir, 12 ins. diam., bears S. 65° W., 40.5 lks. dist., mkd. $\frac{1}{4}$ S34 BT.</p>
80.32	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E <u>S27 S26</u> S34 S35 1975</p> <p>from which</p> <p style="padding-left: 40px;">A spruce, 10 ins. diam.; bears N. 11° E., 47 lks. dist., mkd. T6N R27E S26 BT.</p> <p style="padding-left: 40px;">A spruce, 10 ins. diam., bears S. 73½° E., 89.5 lks. dist., mkd. T6N R27E S35 BT .</p> <p style="padding-left: 40px;">A spruce, 10 ins. diam., bears S. 45° W., 68 lks. dist., mkd. T6N R27E S34 BT.</p> <p style="padding-left: 40px;">A spruce, 8 ins. diam., bears N. 47° W., 26 lks. dist., mkd. T6N R27E S27 BT.</p>
23.70 29.30 39.34	<p>From the cor. of secs. 25, 26, 35 and 36. N. 88°33' W., bet. secs. 26 and 35. Over medium rolling land, through dense timber.</p> <p>Logging trail, bears S. 40° E. and N. 40° W.</p> <p>Begin descent of steep SW slope.</p> <p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
 T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T6N R27E $\frac{1}{4}$ $\frac{S26}{S35}$ 1975</p> <p>from which</p> <p style="margin-left: 40px;">A spruce, 15 ins. diam., bears S. 2° E., 61 lks. dist., mkd. $\frac{1}{4}$ S35 BT.</p> <p style="margin-left: 40px;">A spruce, 9 ins. diam., bears N. 20$\frac{1}{2}$° W., 43.5 lks. dist., mkd. $\frac{1}{4}$ S26 BT.</p>
46.30	West fork of Black River, 20 lks. wide, course SE, begin steep ascent.
48.70	Abandoned railroad bed, bears SE and NW.
78.67	The cor. of secs. 26, 27, 34 and 35.
	<p>N. 0°29' E., bet. secs. 26 and 27. Over rolling land, through dense timber.</p>
28.60	Graded road, bears N. 50° E. and S. 50° W.
31.00	Abandoned fence, bears S. 40° E. and N. 40° W., thence over open grass land.
39.90	Fence, bears N. 88° E. and S. 88° W.
40.15	Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E $\frac{1}{4}$ $\frac{S27}{S26}$ 1975</p>
	<p>Raise a mound of stone, 3$\frac{1}{2}$ ft. base, 2$\frac{1}{4}$ ft. high W of cor.</p> <p>From this cor. a local monument, a 1-inch open end pipe, projecting 7 ins. above the ground in a mound of stone, 2 ft. base, 6 ins. high, bears N. 65°58' W., 318 lks. dist.</p> <p>From this same cor. a local monument, a $\frac{1}{2}$ inch reinforcement rod, projecting 3 ins. above the ground, bears N. 74°42' W., 535.5 lks. dist.</p>
57.50	West Fork of Black River, 10 lks. wide, course NE.
59.80	Fence, bears E and W.
60.225	Point for the N 1/16 sec. cor. of secs. 26 and 27.
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T6N R27E N 1/16 S27 S26 1975</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high W of cor.</p> <p>From this cor. a local monument, ½ inch reinforcement rod, bears N. 54°44' W., 247 lks. dist.</p> <p>From this same cor. the NE cor. of a log cabin, 20 x 16 ft, bears S. 76° W., 294 lks. dist., long sides bear N. 18° E and S. 18° W.</p>	
60.70	Track road, bears E and W curving SW.	
80.30	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E S22 S23 S27 S26 1975</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 23 3/4° E., 63 lks. dist., mkd. T6N R27E S23 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 82¼° W., 187 lks. dist., mkd. T6N R27E S27 BT.</p> <p style="padding-left: 40px;">A spruce, 8 ins. diam., bears N. 42° W., 75.5 lks. dist., mkd. T6N R27E S22 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high W of cor.</p> <p>Cor. is located on S edge of timberline, bears E and W.</p> <p>From this cor. a private surveyors cor., bears N. 45°10' W., 165 lks. dist., monumented with a 1-inch iron pipe, projecting 4 ins. above the ground, in mound of stone, 2 ft. base, with aluminum cap attached mkd. T6N R27E 33 23 27 26 SSE Co. 4/28.</p> <p>From the same cor. the cor. of secs. 2, 3, 34 and 35, on the N bdy. of the tp., bears N. 0°45' W., 320.76 chs. dist. heretofore described.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.</p>	
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>N. 89°59' W., bet. secs. 23 and 26.</p> <p>Over medium rolling grass land.</p>	
6.90	Graded road, bears N. 20° E. and S. 20° W.	
10.80	Creek, 4 lks. wide, course S. 30° E.	

BOOK 5061

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
25.40	Ridge, bears N and S.
39.53	Point for the $\frac{1}{4}$ sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd. T6N R27E $\frac{1}{4}$ $\frac{S23}{S26}$ 1975
	Raise a mound of stone, $2\frac{1}{2}$ ft. base $1\frac{1}{2}$ ft. high N of cor.
43.80	Enter dense timber, edge bears S. 35° E. and N. 35° W.
50.50	Leave timber, edge bears N and S.
55.90	Enter dense timber, edge bears N and S.
59.29	Point for the W $\frac{1}{16}$ sec. cor. of secs. 23 and 26. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. T6N R27E W $\frac{1}{16}$ $\frac{S23}{S26}$ 1975
	from which
	A ponderosa pine, 8 ins. diam., bears S. 58° E., 63.5 lks. dist., mkd. W $\frac{1}{16}$ S26 BT.
	A ponderosa pine, 18 ins. diam., bears N. 34° W., 71.5 lks. dist., mkd. W $\frac{1}{16}$ S23 BT.
	Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N of cor.
	Cor. is located on steep SW slope.
63.10	Creek, 5 lks. wide, flows southerly.
79.05	The cor. of secs. 22, 23, 26 and 27.
	From the cor. of secs. 3, 4, 33 and 34, on the S bdy. of the tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, encircled by a mound of stone 2 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1916 dependent resurvey of the N bdy. of fractional T. 5 N., R. 27 E., from which the original bearing trees
	A fir stump, 10 ins. diam., bears N. $50\frac{3}{4}^\circ$ E., 18.5 lks. dist., mkd. T6N R27E S34 BT. (Record N. $53\frac{1}{4}$ E., 17 lks. dist.)
	A ponderosa pine, 22 ins. diam., bears S. $79\frac{1}{4}^\circ$ E., 22 lks. dist., mkd. T5N R27E BT (Record S. 77° E.)

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A white fir stump, 12 ins. diam., bears S $8\frac{1}{4}^{\circ}$ W., 15.5 lks. dist., mkd. T6N R27E S4 BT (Record S. 13° W., 17 lks. dist.)</p> <p>A fallen fir, 11 ins. diam., bears N. $26\frac{1}{4}^{\circ}$ W., 39 lks. dist., mkd. T6N R27E S33 BT (Record N. 25° W.)</p> <p>from which new bearing trees</p> <p>A white fir, 12 ins. diam., bears N. 26° E., 78 lks. dist., mkd. T6N R27E S34 BT.</p> <p>A pine, 14 ins. diam., bears S. 9° W., 85.5 lks. dist., mkd. T5N R27E S4 BT.</p> <p>A ponderosa pine, 16 ins. diam., bears N. $57\frac{1}{4}^{\circ}$ W., 34 lks. dist., mkd. T6N R27E S33 BT.</p> <p>Raise a mound of stone $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W of cor.</p> <p>Add the mks. 1975 to the brass cap.</p> <p>Note: The topography for the following mile is scaled from U.S. Geological Quadrangle Map Nutrioso 2 SW and Nutrioso 2 NW, Apache County, Arizona 1958.</p> <p>N. $1^{\circ}55'$ E., bet. secs. 33 and 34.</p> <p>Over medium rolling land, through dense timber.</p>
13.80	Draw, drains easterly.
27.40	Graded road, bears S. 40° E. and N. 40° W.
34.40	Creek, 5 lks. wide course S. 70° E.
40.13	Point for the $\frac{1}{4}$ sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R27E</p> <p>$\frac{1}{4}$</p> <p>S33 S34</p> <p>1975</p> </div> <p>from which</p> <p>A pine, 5 ins. diam., bears N. 66° E., 29.5 lks. dist., mkd. $\frac{1}{4}$ S34 BT.</p> <p>A pine, 13 ins. diam., bears S. 30° W., 43.5 lks. dist., mkd. $\frac{1}{4}$ S33 BT.</p>
40.75	Graded road, bears S. 50° E. and N. 50° W.
52.30	Graded road, bears S. 40° E. and N. 40° W.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
64.20	Graded road, bears N. 70° E. and S. 70° W.
80.26	Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T6N R27E <u>S28 S27</u> <u>S33 S34</u> 1975 </div> from which A pine, 10 ins. diam., bears N. 61° E., 104.5 lks. dist., mkd. T6N R27E S27 BT. A white fir, 5 ins. diam., bears S. 9° E., 39 lks. dist., mkd. T6N R27E S34 BT. A spruce, 6 ins. diam., bears S. 46° W., 25 lks. dist., mkd. T6N R27E S33 BT. A white fir, 7 ins. diam., bears N. 59° W., 20.5 lks. dist., mkd. T6N R27E S28 BT. Raise a mound of stone, 3 ft. base, 1½ ft. high W of cor.
	From the cor. of secs. 26, 27, 34 and 35. West, bet. secs. 27 and 34. Over rolling land, through dense timber.
32.50	Logging trail, bears SE and NW.
39.16	Point for the ¼ sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, mound of stone, 3½ ft. base to top, with brass cap mkd. <div style="text-align: center;"> T6N R27E ¼ <u>S27</u> S34 1975 </div> from which A yellow pine, 18 ins. diam., bears S. 7½° W., 121 lks. dist. mkd. ¼ S34 BT. A pine, 15 ins. diam., bears N. 60° W., 7 lks. dist., mkd. ¼ S27 BT.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

	<p>CHAINS 72.00</p>	<p>Graded road, bears N. 35° E. and S. 35° W., as scaled from U. S. Geological Quadrangle Map Nutrioso 2 NW, Apache County, Arizona 1958.</p>
	78.31	<p>The cor. of secs. 27, 28, 33 and 34.</p>
		<p>S. 89°00' W., bet. secs. 28 and 33.</p> <p>Over rolling land, through dense timber.</p>
	26.525	<p>The closing cor. of secs. 28 and 33, on the E bdy. of the Fort Apache Indian Reservation, monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1913 resurvey of the E bdy. of the Fort Apache Indian Reservation, from which the original bearing trees</p> <p>An aspen, 17 ins. diam., bears N. 52 3/4° E., 33 lks. dist., mkd. with a healed blaze. (Record 32 lks. dist.)</p> <p>A pine, 13 ins. diam., bears S. 47 1/2° E., 15 lks. dist., mkd. T6N R27E S33 CC BT.</p> <p>From this cor. the 2 1/2 mile cor., on the E bdy. of the Fort Apache Indian Reservation, bears north, 199 lks. dist., monumented with an iron post, 1 inch diam., projecting 10 ins. above the ground, with brass cap mkd. as described in the official record of the 1913 resurvey of the E bdy. of the Fort Apache Indian Reservation, from which the original bearing trees</p> <p>A pine, 14 ins. diam., bears N. 15 1/2° E., 40 lks. dist., mkd. WMIR 2 1/2 M BT.</p> <p>A pine, 22 ins. diam., bears N. 76 1/4° W., 30 lks. dist., mkd. WMIR 2 1/2 M BT.</p> <p>Note: During the 1913 resurvey of the East bdy. of the Fort Apache Indian Reservation, the original closing cor. of secs. 28 and 33 was found 81 lks. West of line. The position of the original closing cor. was used in proportioning bet. secs. 26 and 35, 27 and 34 and 28 and 33.</p> <p>Both cors. are located in N and S fence.</p>
		<p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>N. 0°14' E., bet. secs. 27 and 28.</p> <p>Over medium rolling land, through dense timber.</p>
	40.11	<p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E 1/4 S28 S27 1975</p> <p>from which</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>60.10</p> <p>80.22</p>	<p>A fir, 7 ins. diam., bears S. 89° E., 42 lks. dist., mkd. $\frac{1}{4}$ S27 BT.</p> <p>A fir, 12 ins. diam., bears N. 50° W., 88.5 lks. dist., mkd. $\frac{1}{4}$ S28 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high W of cor.</p> <p>Creek, 8 lks. wide, course N. 80° E.</p> <p>Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R27E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S21</td> <td style="padding: 0 5px;">S22</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S28</td> <td style="padding: 0 5px;">S27</td> </tr> </table> <p>1975</p> </div> <p>from which</p> <p>A spruce, 12 ins. diam., bears N. 5° E., 76 lks. dist., mkd. T6N R27E S 22 BT.</p> <p>A spruce, 12 ins. diam., bears S. 76¼° E., 20.5 lks. dist., mkd. T6N R27E S27 BT.</p> <p>A spruce, 16 ins. diam., bears S. 62¼° W., 8 lks. dist., mkd. T6N R27E S28 BT.</p> <p>A spruce, 9 ins. diam., bears N. 31½° W., 76.5 lks. dist., mkd. T6N R27E S21 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high W of cor.</p> <p>Cor. is located 20 lks. S of a draw, drains N. 60° E.</p> <p>From this cor. the cor. of secs. 3, 4, 33 and 34, on the N bdy. of the tp. bears N. 1°02' W., 320.85 chs. dist., heretofore described.</p> <p>This control line was fully retraced and careful search was made for evidence of intervening corners, none of which were recovered.</p>	S21	S22	S28	S27
S21	S22				
S28	S27				
<p>19.655</p>	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°56' W., bet. secs. 22 and 27.</p> <p>Over medium rolling land, through dense timber.</p> <p>Point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T6N R27E</p> <table style="margin: auto;"> <tr> <td style="padding: 0 5px;">E 1/16</td> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S27</td> </tr> </table> <p>1975</p> </div> <p>from which</p> <p>A ponderosa pine, 18 ins. diam., bears S. 11° E., 99 lks. dist., mkd. E 1/16 S27 BT.</p>	E 1/16	S22	S27	
E 1/16	S22	S27			

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>A spruce, 8 ins. diam., bears N. $4\frac{3}{4}^{\circ}$ W., 51.5 lks. dist., mkd. E $1/16$ S22 BT.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high N of cor.</p> <p>24.10 Fence, bears N and S, thence over grass land.</p> <p>33.20 Wash, 10 lks. wide, drains SW.</p> <p>39.31 Point for the $\frac{1}{4}$ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E $\frac{1}{4}$ $\frac{S22}{S27}$ 1975</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, N of cor.</p> <p>39.70 Track road, bears N and S.</p> <p>44.80 West fork of Black River, 15 lks. wide, flows southerly.</p> <p>78.62 The cor. of secs. 21, 22, 27 and 28.</p>	
26.91	<p>S. $87^{\circ}34'$ W., bet. secs. 21 and 28.</p> <p>Over rolling land, through dense timber.</p> <p>The closing cor. of secs. 21 and 28, on the E bdy, of the Fort Apache Indian Reservation, monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd. as described in the official record of the 1913 resurvey of the E bdy. of the Fort Apache Indian Reservation, from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 30 ins. diam., bears N. $22\frac{1}{4}^{\circ}$ E., 80 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A fir stump, 33 ins. diam., bears S. 33° E., 94 lks. dist., mkd. T6N R27E S28 BT.</p> <p>From this cor. the $1\frac{1}{2}$ mile cor., on the E bdy. of the Fort Apache Indian Reservation, bears north, 237.5 lks. dist., monumented with an iron post, 1 inch diam., projecting 10 ins. above the ground, with brass cap mkd. as described in the official record of the 1913 resurvey of the E bdy. of the Fort Apache Indian Reservation, from which the original bearing trees</p> <p style="padding-left: 40px;">A fir, 17 ins. diam., bears N. $32\frac{3}{4}^{\circ}$ E., 17 lks. dist., mkd. with a healed blaze. (Record 16 lks.)</p> <p style="padding-left: 40px;">A dead spruce, 10 ins. diam., bears N. $67\frac{1}{2}^{\circ}$ W., 30 lks. dist., mkd. WMIR $1\frac{1}{2}$ M BT (Record 31 lks.)</p> <p>Note: During the 1913 resurvey of the East bdy. of the Fort Apache Indian Reservation, the original closing cor. of secs. 21 and 28 was found 24 lks. west. This position was used for proportioning the line bet. secs. 24 and 25, 23 and 26, 22 and 27 and 21 and 28.</p> <p>Both cors. are located in N and S fence.</p>	

Subdivision of Section 26
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 26 and 35.</p> <p>N. $0^{\circ}36'30''$ E., along the N and S center line of sec. 26.</p> <p>Over rolling land, through dense timber.</p>
40.64	<p>Point for the $C\frac{1}{4}$ sec. cor. of sec. 26, at intersection with the E and W center line of sec. 26.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E C$\frac{1}{4}$ S26 1975</p> <p>from which</p> <p style="padding-left: 40px;">A douglas fir, 10 ins. diam., bears N. 75° W., 9 lks. dist., mkd. C$\frac{1}{4}$ S26 BT.</p> <p style="padding-left: 40px;">A douglas fir, 15 ins. diam., bears N. 33° W., 47 lks. dist., mkd. C$\frac{1}{4}$ S26 BT.</p>
51.80	<p>Leave timber, thence over grass land, edge bears S. 80° E. and N. 80° W.</p>
57.80	<p>Graded road, bears E and W.</p>
60.955	<p>Point for the C-N $1/16$ sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6N R27E C N $1/16$ S26 C 1975</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high W of cor.</p>
61.30	<p>Creek, 10 lks. wide, course westerly.</p>
62.40	<p>Abandoned railroad bed, bears S. 80° E. and N. 80° W.</p>
81.27	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 26.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 25 and 26.</p> <p>N. $89^{\circ}16'$ W., along the E and W center line of sec. 26.</p> <p>Over rolling land, through dense timber.</p>
39.44	<p>The $C\frac{1}{4}$ sec. cor. of sec. 26.</p>
59.14	<p>Point for the C-W $1/16$ sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., on rocky surface, mound of stone, 4 ft. base to top, with brass cap mkd.</p>

Subdivision of Section 26,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T6N R27E C $\frac{W}{S} \frac{1/16}{26}$ C 1975</p>
	<p>from which</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears S. 85° E., 100.5 lks. dist., mkd. C W 1/16 S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 14° W., 49.5 lks. dist., mkd. C W 1/16 S26 BT.</p>
62.00	Graded road, bears S. 15° E. and N. 15° W. (Scaled from U.S.F.S. map).
67.00	Abandoned railroad bed, bears S. 17° E. and N. 17° W.
69.20	West Fork of Black River, 10 lks. wide, course southerly.
73.70	Fence, bears N. 88° E. and S. 88° W.
78.84	The $\frac{1}{4}$ sec. cor. of secs. 26 and 27.
Subdivision of the NW $\frac{1}{4}$, Section 26	
	<p>From the C-W 1/16 sec. cor. of sec. 26.</p> <p>N. 0°32' E., along the N and S center line of the NW$\frac{1}{4}$ of sec. 26.</p> <p>Over rolling land, through dense timber.</p>
18.40	Leave timber, thence over grass land, edge bears NE and SW.
20.205	<p>Point for the NW 1/16 sec. cor. of sec. 26 at intersection with the E and W center line of the NW$\frac{1}{4}$ sec. 26.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6N R27E NW 1/16 S26 1975</p>
	<p>from which</p> <p style="padding-left: 40px;">A spruce, 9 ins. diam., bears S. 15° E., 119 lks. dist., mkd. NW 1/16 S26 BT.</p> <p style="padding-left: 40px;">A spruce, 13 ins. diam., bears S. 49° W., 51 lks. dist., mkd. NW 1/16 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1$\frac{1}{2}$ ft. high W of cor.</p>
25.70	Graded road, bears E and W.
28.10	Creek, 10 lks. wide, course SW.
29.50	Abandoned railroad bed, bears E and W.
40.41	The W 1/16 sec. cor. of secs. 23 and 26.

Subdivision of Section 26,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	From the C-N 1/16 sec. cor. of sec. 26.
	N. 89°38' W., along the E and W center line of the NW ¹ / ₄ of sec. 26.
	Over open rolling grass land.
13.00	Graded road, bears S. 70° E. and N. 70° W. (Scaled from U.S.F.S. map).
19.73	The NW 1/16 sec. cor. of sec. 26.
22.50	Enter timber, edge bears SE and NW.
24.50	Spur, slopes N.
28.00	Graded road, bears N. 30° E. and S. 30° W. (Scaled from U.S.F.S. map).
31.70	Leave timber, edge bears NE and SW.
35.30	Fence, bears SE and NW.
35.60	Abandoned railroad bed, bears S. 20° W. and N. 20° E.
36.30	Fence, bears NE and SW.
38.90	Creek, 10 lks. wide, course southerly.
39.46	The N 1/16 sec. cor. of secs. 26 and 27.

Subdivision of Section 27, T. 6 N., R. 27 E.

	From the ¹ / ₄ sec. cor. of secs. 27 and 34.
	N. 0°23'30" E., along the N and S center line of sec. 27.
	Over rolling land, through dense timber.
15.00	Logging trail, bears SE and NW.
22.60	Graded road, bears S. 75° E. and N. 75° W., curving NNW.
38.70	Abandoned fence, bears E and W.
40.15	Point for the C ¹ / ₄ sec. cor. of sec. 27, at intersection with the E and W center line of sec. 27.
	Set an iron post, 28 ins. long, 2 ¹ / ₂ ins. diam., on surface of solid rock, mound of stone, 4 ft. base to top, with brass cap mkd.
	T6N R27E C ¹ / ₄ S27 1975
	from which
	A spruce, 6 ins. diam., bears N. 54 ¹ / ₂ ° E., 31.5 lks. dist., mkd. C ¹ / ₄ S27 BT.
	A douglas fir, 10 ins. diam., bears N. 51° W., 18 lks. dist., mkd. C ¹ / ₄ S27 BT.

Subdivision of Section 27,
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located on moderate N slope.
53.70	Leave timber, thence over grass land, edge bears E and W.
59.70	Track road, bears E and W.
60.215	Point for the C-N 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T6N R27E C N 1/16 S27 C 1975</p>
	Raise a mound of stone, 2 ft. base, 1 ft. high W of cor.
61.80	Creek, 10 lks. wide, course easterly.
67.30	West fork of Black River, 10 lks. wide, course SE.
78.80	Track road, bears SE and NW.
79.79	Fence, bears E and W.
80.28	The ¼ sec. cor. of secs. 22 and 27.
	From the ¼ sec. cor. of secs. 26 and 27.
	S.89°56'30" W., along the E and W center line of sec. 27.
	Over open rolling grass land.
5.20	Fence, bears N and S.
10.70	Enter dense timber, edge bears S. 50° E. and N. 50° W.
19.605	Point for the C-E 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">E 1/16 C ——— C S27 1975</p>
	from which
	A spruce, 7 ins. diam., bears N. 84° E., 36 lks. dist., mkd. CE 1/16 S27 BT.
	A douglas fir, 7 ins. diam., bears S. 12¼° E., 48 lks. dist., mkd. CE 1/16 S27 BT.
	Raise a mound of stone, 2 ft. base, 1 ft. high N of cor.
39.21	The C¼ sec. cor. of sec. 27.
42.90	Fence, bears N and S.
78.44	The ¼ sec. cor. of secs. 27 and 28.

Subdivision of Section 27
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	Subdivision of the NE $\frac{1}{4}$ of Section 27.
	<p>From the C-E 1/16 sec. cor. of sec. 27.</p> <p>N. 0°27' E., along the N and S center line of the NE$\frac{1}{4}$ of sec. 27.</p> <p>Over rolling land, through dense timber.</p>
8.10	Leave timber, thence over open grass land, edge bears E and W.
13.50	West fork of Black River, 10 lks. wide, course easterly.
14.60	Track road, bears S. 65° E. and N. 65° W.
19.40	Fence, bears E and W.
20.07	Point for the NE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the NE $\frac{1}{4}$ of sec. 27.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p>T6N R27E NE 1/16 S27 1975</p>
40.14	<p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 1$\frac{1}{2}$ ft. high W of cor. The E 1/16 sec. cor. of secs. 22 and 27.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 26 and 27.</p> <p>S. 89°56'30" W., along the E and W center line of the NE$\frac{1}{4}$ of sec. 27.</p>
1.50	Track road, bears SW and NE, curving easterly.
19.64	The NE 1/16 sec. cor. of sec. 27.
23.60	Fence, bears N and S.
29.70	Track road, bears S. 60° E. and N. 60° W.
35.60	West fork of Black River, 10 lks. wide, course SE.
39.28	The C-N 1/16 sec. cor. of sec. 27.
	<p>GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 20 miles SSW of the town of Springerville, Ariz. The township is drained by the West Fork of the Black River and its tributaries, the drainage being generally to the east and southeast. Elevation ranges from about 8,600 feet to 9,850 feet above sea level.</p> <p>Access is by way of county asphalt Route No. 70 and numerous unimproved or lightly gravelled Forest Service roads. There is an abandoned railroad bed that meanders through the SE cor. of the Tp.</p>

General Description
T. 6 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS

A large portion of the township is covered with timber, including pine, spruce, fir and aspen. The undergrowth consists of young timber. There is a good cover of native grasses in the open areas.

The principal use of the area is logging and live-stock grazing. Public land areas are used for recreation by hunters, fishermen, hikers, campers, etc.

The only improvement noted was a log cabin in section 27, near the N 1/16 sec. cor. of secs. 26 and 27.

There is no evidence of mining activity or minerals.

The mean of a considerable number of observations of the magnetic declination throughout the township is 13° E., with a range of 1° in local attraction.

CHAINS

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Harry K. Smith, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of September, 1975, (I) ~~(We)~~ have dependently resurveyed a portion of the south and north boundaries, a portion of the subdivisional lines, and subdivided sections 26 and 27 of Township 6 North, Range 27 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

July 19, 1976

(Date)

Harry K. Smith

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south and north boundaries, a portion of the subdivisional lines, and the subdivision of sections 26 and 27, of Township 6 North, Range 27 East, of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

JUN 2 1978

(Date)

Roger T. Barron
Acting Chief, Division of Cadastral Survey

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 - 626