

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the Dependent Resurvey of a

Portion of the West Boundary and Subdivisional Lines

and the

Survey of a Portion of the

Subdivisional Lines completing the Subdivision

and an

Informational Traverse of the Present Right and

Left Banks of the Salt River

and the

Survey of the Medial Line

(South Boundary of the Salt River Indian Reservation)

Township 2 North, Range 6 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Paul G. Bauer

Cadastral Surveyor

Harry K. Smith

Cadastral Surveyor

supplemental
Under/special instructions dated January 15, 19 74, approved January 16, 1974
and supplemental special instructions dated and approved December 12, 1977,

_____, which provided for the surveys included under U.S. Survey/Group
Number 372, Arizona, and assignment instructions dated January 15, 19 74.
and December 12, 1977.

Survey commenced January 17, 19 74

Survey completed January 13, 19 78

1A

BOOK 5062

INDEX DIAGRAM

Township 2 North, Range 6 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14 15	7 13 31
19 30	20 29	21	22 21	11 23 10	6 24 4
30 26	26 29 25	23 28 22	19 27 17	9 26	25
31	32	33	34	35	36

Traverse of the Present Right Bank of the Salt River - Page 32
 Traverse of the Present Left Bank of the Salt River - Page 41
 Survey, South Boundary, Salt River Indian Reservation

Pages

- 52 In Sec. 30
- 56 In Sec. 29
- 60 In Sec. 28
- 64 In Sec. 27
- 65 In Sec. 22
- 69 In Sec. 23
- 72 In Sec. 14
- 73 In Sec. 13

Dependent Resurvey and Survey of
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

The history of surveys of Township 2 North, Range 6 East, Gila and Salt River Meridian, Arizona, is as follows:

The south and west boundaries and that portion of the east boundary south of the Salt River along with a portion of the subdivisional lines were surveyed in 1868 by George P. Ingalls.

That portion of the west boundary north of the Salt River, the west 3 miles of the north boundary and the right bank of the Salt River through the township was surveyed in 1888 by L. D. Chillson.

The west boundary, the west 3 miles of the north boundary and the right bank of the Salt River was resurveyed in 1910-11 by Robert A. Farmer, who in the same period, surveyed that portion of the east boundary north of the Salt River, the east 3 miles of the north boundary, the subdivisional lines north of the Salt River, the right and left banks of the Right-of-Way of the Arizona Canal and subdivided all the sections north of the Salt River with the exception of section 12.

The south boundary and the south 3 miles of the east boundary was resurveyed in 1900 by Homer Santee. The south 4 miles of the east boundary was resurveyed in 1930 by Theodore Vander Meer.

A portion of the east boundary was concurrently resurveyed under this same group.

The following field notes are those of the dependent resurvey of a portion of the west boundary and subdivisional lines; a completion survey of the subdivisional lines and an informational traverse of the present right and left banks of the Salt River and a survey of the medial lines (south boundary of the Salt River Indian Reservation) through the township.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1947 and the Supplemental Special Instructions for Group No. 372, Arizona, dated January 15, 1974, and Supplemental Special Instructions dated December 12, 1977.

Preliminary to the resurvey executed under these supplemental instructions, the original surveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. Ties to many corners of local origin were provided by the Arizona State Highway Dept. and those corners were accepted as the best remaining evidence of the original cor. positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by solar instrument methods and by means of fore- and backsights and angular deflections from azimuths obtained by direct solar observations.

The geographic position of the corner of sections 19, 24, 25 and 30 on the east boundary of the township, as calculated by traverse from U.S.C. & G.S. triangulation station Granite Reef, in sec. 13 is as follows:

Dependent Resurvey and Survey of
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Latitude 33°29'43" N. Longitude 111°41'01" W.</p> <p>The mean magnetic declination is 14° E.</p> <hr/> <p>Dependent Resurvey of a Portion of the West Boundary of T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>(Restoring the resurvey executed by Robert A. Farmer in 1910-1911)</p> <hr/> <p>Beginning at the cor. of secs. 25 and 36, T. 2 N., R. 5 E., on the Salt River Indian Reservation Bdy., monumented with an unmarked brass cap, 2 ins. diam., set in a receptacle, 12 ins. diam., 4 ins. deep, in the center of Gilbert Road and the E. end of Thomas Road, as recorded with the Arizona State Highway Department by Merle Brock on 11-4-42. This position has long been recognized by private surveyors as the cor., is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position; this cor. functions as the cor. of secs. 25, 30, 31 and 36, Tp. 2 N., Rs. 5 and 6 E., on the Salt River Indian Reservation Bdy.; not remonumented.</p> <p>N. 0°02' E., bet. secs. 25 and 30.</p> <p>Along the Salt River Indian Reservation Bdy. and along the center of Gilbert Road, asphalt surface, bearing N and S.</p>
6.695	Point for the meander cor. of sec. 25, T. 2 N., R. 5 E., at proportionate dist.; there is no remaining evidence of the cor. set during the 1910 resurvey on the left bank of the south fork of the Salt River; not monumented.
19.985	Point for the S. 1/16 sec. cor. of sec. 25, T. 2 N., R. 5 E., at proportionate dist.; this cor. fell in the Salt River during the 1910 resurvey; not monumented.
21.985	Point for the meander cor. of sec. 25, T. 2 N., R. 5 E., at proportionate dist.; there is no remaining evidence of the cor. set during the 1910 resurvey on the S. shore of an island; not monumented.
27.30	Present left bank of the S channel of the Salt River, bank bears S. 72°52' E. and N. 72°52' W.
36.30	Present right bank of the S channel of the Salt River, bank bears S. 61°49' E. and N. 61°49' W.
39.97	The 1/4 sec. cor. of sec. 25, T. 2 N., R. 5 E., monumented with a re-bar, 3/4 in. diam., set flush with the pavement in the center of Gilbert Road. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position; this cor. functions as the 1/4 sec. cor. of secs. 25 and 30, Tp. 2 N., Rs. 5 and 6 E.; not remonumented.
	<hr/> <p>N. 0°01' E., beginning new measurement.</p> <p>Along the center of Gilbert Road, bearing N and S.</p>

Dependent Resurvey of a Portion of the West Boundary of
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
9.995	Point for the meander cor. of sec. 25, T. 2 N., R. 5 E., at proportionate dist.; there is no remaining evidence of the cor. set on the N shore of an island during the 1910 resurvey; not monumented.	
14.43	Point for the witness point of secs. 25 and 30, Tp. 2 N., Rs. 5 and 6 E., used to determine the position of Angle Point 1 on the medial line of the Salt River. The witness point is located in the center of Gilbert Road on the present left bank of the N channel of the Salt River; bank bears N. 79°21' E. and S. 79°21' W. Set a railroad spike, flush with the pavement in the center of Gilbert Road, top mkd.	
	WP T 2 N S R I R R 5 E R 6 E S 25 S 30 1978	
18.275	Point for Angle Point 1, on the south bdy. of the Salt River Indian Reservation, on line bet. secs. 25 and 30, Tp. 2 N., Rs. 5 and 6 E. and at mid-point bet. the witness points on the present left and right banks of the N channel of the Salt River, hereinafter described.	
19.99	Point for the N. 1/16 sec. cor. of sec. 25, T. 2 N., R. 5 E., at proportionate dist.; this cor. point fell in the Salt River during the 1910 resurvey; not monumented.	
22.12	Point for the witness point of secs. 25 and 30, Tps. 2 N., Rs. 5 and 6 E., used for determining the position of Angle Point 1 on the medial line of the Salt River. The witness point is located in the center of Gilbert Road on the present right bank of the N channel of the Salt River; bank bears N. 73°59' E. and S. 73°59' W. Set a bolt, 8 ins. long, ½ in. diam., flush with the pavement, top mkd.	
	WP S 25 S 30 1978	
27.285	Point for the meander cor. of secs. 25 and 30, Tp. 2 N., Rs. 5 and 6 E., at proportionate dist.; there is no remaining evidence of the cor. set on the right bank of the Salt River during the 1910 resurvey; not monumented.	
39.98	The cor. of secs. 19, 24, 25 and 30, Tp. 2 N., Rs. 5 and 6 E., monumented with an unmarked railroad spike set flush with the pavement in the center of Gilbert Road. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position; not remonumented.	

Dependent Resurvey of a Portion of the West Boundary of
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Land, gently rolling to nearly level. Soil, sandy loam, gravelly and rocky in river bottom. No timber; undergrowth, scattered creosote brush and weeds.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines of T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona</p>
	<p>(Restoring the survey executed by George P. Ingalls south of the Salt River in 1868 and the survey executed by Robert A. Farmer north of the Salt River in 1911)</p> <hr/> <p>Beginning at the cor. of secs. 19, 24, 25 and 30, on the E. bdy. of the Tp., monumented by a 4 in. brass cap set 6 ins. below the surface in a receptacle in Bush Highway, bearing N and S, cap mkd. MARICOPA COUNTY ENGINEERING DEPT.; this position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best avail- able evidence of the original cor. position. Not remonu- mented.</p> <p>Cor. is located 10 lks. S of power line, bearing E and W. S. 89°13' W., bet. secs. 24 and 25.</p> <p>Over gently rolling land, along a power line, bearing E and W.</p>
0.14	Center of Bush Highway, bears N and S.
1.00	Power line, bears N and S; power line junction bears North 10 lks. dist., line bears N, S and E.
5.50	Wash, 10 lks. wide, 1 ft. deep, drains irregularly N. 15° W.; enter rolling hills.
21.40	Spur, slopes S. 10° W.
38.20	Cat road, bears N. 15° E. and S. 15° W., about 2.50 chs. thence NW.
39.78	<p>The ¼ sec. cor. of secs. 24 and 25, monumented by a galvanized pipe, ½ in. diam., 24 ins. long, projecting 14 ins. above ground, with scattered mound of stone W. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>At the cor. point</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 2 N R 6 E $\frac{1}{4}$ S 24 S 25 1974</p> <p>Deposit the ½ in. pipe alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°13' W., beginning new measurement.</p> <p>Over mountainous land.</p> <p>0.70 Draw, near head, drains NW.</p> <p>1.00 Same cat road, bears SE and NW.</p> <p>8.00 Top of hill, bears SE and NW.</p> <p>11.00 E end of abandoned fence, bears westerly.</p> <p>14.50 Enter gently rolling land.</p> <p>22.80 Wash, 25 lks. wide, 1 ft. deep, drains NW, curving N.</p> <p>24.60 Unimproved dirt road, bears S. 15° E. and N. 15° W.</p> <p>40.14 The cor. of secs. 23, 24, 25 and 26, monumented with an open end pipe, 1 ¾ ins. diam., 2 ft. long, projecting 12 ins. above ground, set in a collar of stone, 1 ft. base, 6 ins. high, with a wooden post, 4 ins. square, projecting 4½ ft. above a mound of stone, 2 ft. base, 1 ft. high, W of the cor. This position is harmoniously related to existing survey cors. in the area and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, 1 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T 2 N R 6 E S 23 S 24 S 26 S 25 1974</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A local wooden post, 4 ins. sq., projecting 4 ft. above a mound of stone, 2 ft. base, 1 ft. high, bears N. 88°57' E., 106 lks. dist.</p> <p>A fence cor. of abandoned fences extending easterly and southerly, bears East, 2 lks. dist.</p> <p>Reset the open end pipe alongside the iron post.</p> <p>Original wooden post W of the cor.</p> <p>Land, gently rolling to mountainous. Soil, gravelly, rocky loam and exposed granite. No timber; undergrowth, creosote brush.</p>
	<p>N. 0°36' W., bet. secs. 23 and 24.</p> <p>Over rolling land through scattering timber and medium undergrowth.</p>
38.70	Sandy wash, 50 lks. wide, 2 ft. deep, drains N. 70° W.
39.94	<p>The $\frac{1}{4}$ sec. cor. of secs. 23 and 24, monumented with an iron pipe, 32 ins. long, 1 in. diam., projecting 3 ins. above ground, with a wooden post, 4 ins. sq., projecting 4 ft. above a mound of stone, 2½ ft. base, 1 ft. high, 2 lks. S of the cor. This position is harmoniously related to existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 2 N R 6 E $\frac{1}{4}$ S 23 S 24 1974</p> <p>from which</p> <p>An ironwood, 8 ins. diam., bears S. 67½° E., 43 lks. dist., mkd. $\frac{1}{4}$ S24 BT.</p> <p>An ironwood, 4 ins. diam., bears N. 46½° W., 49 lks. dist., mkd. $\frac{1}{4}$ S23 BT.</p> <p>A local wooden post, 4 ins. sq., projecting 5 ft. above a mound of stone, 2½ ft. base, 1 ft. high, bears S. 88°39' E., 106.5 lks. dist.</p> <p>Reset the iron pipe alongside the iron post.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS									
	N. 2°16' E., beginning new measurement.								
	Over rolling land.								
4.40	Unimproved dirt road, bears S. 55° E. and N. 55° W., as scaled from U.S.G.S. quadrangle, Granite Reef Dam, Ariz., 1964.								
26.00	Spur, slopes N. 75° W.								
31.30	Unimproved dirt road, bears N. 60° E. and S. 60° W., as scaled from U.S.G.S. quadrangle, Granite Reef Dam, Ariz., 1964.								
34.20	Center of the Southern Canal, 110 lks. wide, flows S. 58° W.								
35.00	Graded gravel road, bears N. 58° E. and S. 58° W., paralleling the Southern Canal.								
37.70	Abandoned fence line, bears N. 50° E. and S. 50° W.								
38.40	Unimproved dirt road, bears NE and SW.								
41.36	The cor. of secs. 13, 14, 23 and 24, monumented with a mound of stone, painted white, 3 ft. base, 1 ft. high. This position is harmoniously related to existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.								
	At the cor. point								
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, and in a collar of stone, 2½ ft. base to top, with brass cap mkd.								
	<table border="0"> <tr> <td>T 2 N</td> <td>R 6 E</td> </tr> <tr> <td>S 14</td> <td>S 13</td> </tr> <tr> <td>S 23</td> <td>S 24</td> </tr> <tr> <td colspan="2" style="text-align: center;">1974</td> </tr> </table>	T 2 N	R 6 E	S 14	S 13	S 23	S 24	1974	
T 2 N	R 6 E								
S 14	S 13								
S 23	S 24								
1974									
	from which								
	A mesquite, 12 ins. diam., bears N. 10° E., 50 lks. dist., mkd. T2N R6E S13 BT.								
	A mesquite, 8 ins. diam., bears N. 76° W., 35 lks. dist., mkd. T2N R6E S14 BT.								
	Land, rolling.								
	Soil, rocky and shallow with granite outcroppings.								
	Timber, ironwood, palo-verde and mesquite.								
	Undergrowth, creosote brush and cacti.								
	N. 1°43' E., bet. secs. 13 and 14.								
	Descend into Salt River bottom, and enter scattering timber.								

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
0.61	Present left bank of the Salt River, bears N. 54°06' E. and S. 54°06' W. This point is used for determining the witness point of secs. 13 and 14 on the medial line of the Salt River.
7.915	Point for the witness point of secs. 13 and 14, on the South Boundary of the Salt River Indian Reservation, at the intersection of the medial line of the Salt River; hereinafter described.
15.22	Present right bank of the Salt River, bears N. 61°59' E. and S. 61°59' W. This point is used for determining the witness point of secs. 13 and 14 on the medial line of the Salt River.
15.93	Point for the witness point of secs. 13 and 14, on the right bank of the Salt River.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.
	W P T 2 N R 6 E S 14 S 13 1974
	from which
	A willow, 14 ins. diam., bears N. 51° W., 19 lks. dist., mkd. WP S14 BT.
23.70	Ascend from Salt River bottom, thence over level land, edge bears N. 50° E. and S. 50° W.
24.10	Graded gravel road, bears N. 50° E. and S. 50° W., paralleling the Arizona Canal, as scaled from U.S.G.S. quadrangle, Granite Reef Dam, Ariz., 1964.
26.30	Center of the Arizona Canal, 100 lks. wide, flows S. 50° W.
27.73	The meander cor. of secs. 13 and 14, set by Robert A. Farmer in 1911, on the N. bdy. of Right-of-Way of Arizona Canal, monumented with an iron post, 1 in. diam., set in concrete, projecting 6 ins. above ground, with brass cap mkd.
	T 2 N R 6 E S 14 S 13 M C 1911
	Remark the brass cap to read
	T 2 N R 6 E S 14 S 13 M C 1974 1911

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

Land, broken river bottom.
Soil, sandy and rocky.
Timber, cottonwood, salt cedar and mesquite; no under-
growth.

From the cor. of secs. 26, 27, 34 and 35, monumented with
a re-bar, 30 ins. long, $\frac{1}{2}$ in. diam., buried 18 ins. under
the earths surface. This position is harmoniously relat-
ed to existing survey cors. in the area, and is accepted
as the best available evidence of the original cor. posi-
tion.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins.
below the earths surface, with brass cap mkd.

T 2 N	R 6 E
S 27	S 26
S 34	S 35
1974	

from which

A power transmission pole, bears N. 46° E., 60 lks.
dist., with aluminum lettering of 34E7N and
19D4A nailed on opposite sides of the pole.

A $\frac{1}{2}$ in. re-bar, projecting 1 in. above the ground,
bears S. $43\frac{1}{4}^\circ$ E., 70.5 lks. dist.

A railroad spike, set flush with the pavement in
Higley Road, for a reference monument, bears
S. $48\frac{3}{4}^\circ$ W., 15.5 lks. dist., with top of the
spike mkd. RM S34 10.2 ft. 1974, and an arrow
pointing to the cor.

Reset the re-bar alongside the iron post.

N. $0^\circ 35'$ E., bet. secs. 26 and 27.

Over rolling land, along E. side of Higley Road and
along a power transmission line, bearing N and S.

13.30 Wash, drains N. 70° W., as scaled from U.S.G.S. quad-
rangle, Buckhorn, Ariz., 1956.

39.98 The $\frac{1}{4}$ sec. cor. of secs. 26 and 27, monumented with a
re-bar, $\frac{3}{4}$ in. diam., projecting 5 ins. above ground,
in a mound of stone, 1 ft. base, 6 ins. high. This
position is harmoniously related to existing survey cors.
in the area, and is accepted as the best available evi-
dence of the original cor. position.

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, and in a collar of stone, 2 ft. base to
top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

T 2 N R 6 E
 $\frac{1}{4}$
 S 27 | S 26
 1974

Reset the re-bar alongside the iron post.

Cor. is 60 lks. E of the center of Higley Road, and 3 lks. E of a power transmission line, both bearing northerly and southerly.

N. 0°36' E., beginning new measurement.

7.20 Wash, drains N. 30° W., as scaled from U.S.G.S. quadrangle, Buckhorn, Ariz., 1956.

13.00 Center of Higley Road, asphalt surfaced, bears NE, 40 lks. dist. to a graded gravel road and SW, 50 lks. dist.; thence southerly.

39.69 The cor. of secs. 22, 23, 26 and 27, monumented with a metal pipe, 12 ins. long, 1 in. diam., projecting 2 ins. above ground. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T 2 N R 6 E
 S 22 | S 23
 S 27 | S 26
 1974

Raise a mound of stone, 2 ft. base, 1½ ft. high, W of the cor.

Reset the metal pipe alongside the iron post.

The cor. is under a power transmission line, bearing N and S.

Land, rolling.
 Soil, sandy along washes, otherwise rocky.
 Timber, scattered palo-verde.
 Undergrowth, creosote brush and cacti.

From the cor. of secs. 23, 24, 25 and 26.

N. 88°47' W., bet. secs. 23 and 26.

Over rolling land, through scattering timber and medium undergrowth.

39.38 Point for the ¼ sec. cor. of secs. 23 and 26 at proportionate distance; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 2 N R 6 E ¼ S 23 S 26 1974</p> <p>from which</p> <p style="text-align: center;">A palo-verde, 6 ins. diam., bears S. 42½° E., 22 lks. dist., mkd. ¼ S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p>
70.60	Spur, slopes N. 30° W.
72.50	Track road, bears N. 10° E. and S. 10° W.
78.76	The cor. of secs. 22, 23, 26 and 27.
	<p>Land, rolling. Soil, sandy and rocky with granite outcroppings. Timber, scattered ironwood and palo-verde. Undergrowth, creosote brush, ocotillo and cacti.</p>
	<p>N. 1°07' E., bet. secs. 22 and 23.</p> <p>Over gently rolling land, through medium undergrowth, along a power transmission line.</p>
8.00	Unimproved dirt road, bears N. 75° E. and S. 75° W.
11.10	Center of Southern Canal, 160 lks. wide, flows S. 50° W.
12.00	Center of a graded gravel road, bears N. 50° E. and S. 50° W., paralleling the Southern Canal.
12.90	Graded road, bears N. 65° W. and S. 65° E. to Southern Canal access road.
13.10	Power transmission line, bears South and N. 65° W.
35.40	Point for the witness point of secs. 22 and 23.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W P T 2 N R 6 E S 22 S 23 1974</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
35.78	Present left bank of the Salt River, bears N. 45°45' E. and S. 64°14' W. This point is used for determining the witness point of secs. 22 and 23 on the medial line of the Salt River. Thence over river bottom, through salt cedar.	
39.83	The ¼ sec. cor. of secs. 22 and 23, monumented with a steel fence post, projecting 1 ft. above ground. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2½ ins. diam., over the top of the fence post, 16 ins. in the ground and in a collar of stone, 2 ft. base to top, with brass cap mkd.	
	T 2 N R 6 E ¼ S 22 S 23 1974	
	N. 0°14' E., beginning new measurement.	
	Over river bottom through salt cedar.	
4.505	Point for the witness point of secs. 22 and 23, on the South Boundary of the Salt River Indian Reservation, at the intersection of the medial line of the Salt River; hereinafter described.	
13.06	Present right bank of the Salt River, bears N. 52°10' E. and S. 52°10' W. This point is used for determining the witness point of secs. 22 and 23 on the medial line of the Salt River.	
13.26	Point for the meander cor. of secs. 22 and 23, set by Robert A. Farmer in 1911, on the right bank of the Salt River, at record bearing and dist. from the N. 1/16 sec. cor. of secs. 22 and 23. There is no remaining evidence of the original cor.; not monumented.	
	N. 0°01' W., beginning new measurement.	
	Ascend 10 ft. to gently rolling land with scattering timber and medium undergrowth.	
0.59	Point for the witness point of secs. 22 and 23.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a collar of stone, 3 ft. base to top, with brass cap mkd.	

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	W P T 2 N R 6 E S 22 S 23 1974
6.59	<p>The N. 1/16 sec. cor. of secs. 22 and 23, monumented with an iron post, 3 ft. long, 1 in. diam., buried 12 ins. below the earths surface, with brass cap mkd. as described in the official record of the 1911 survey.</p> <p>At the cor. point</p> <p>Reset the iron post, 24 ins. in the ground, and add the marks 1974 on the brass cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°09' W., beginning new measurement.</p> <p>Over gently rolling land.</p>
0.07	A re-bar, 1 in. diam., set flush with the ground, bears West, 3 lks. dist.
2.80	Unimproved dirt road, bears N. 65° E. and S. 65° W.
4.10	Wash, 10 lks. wide, 2 ft. deep, drains westerly.
16.32	<p>The meander cor. of secs. 22 and 23, set by Robert A. Farmer in 1911, on the S. bdy. of Right-of-Way of Arizona Canal, monumented with an iron post, 1 in. diam., set in a concrete block, 6 ins. sq., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> T 2 N R 6 E S 22 S 23 M C 1911 </p> <p>Remark the brass cap to read</p> <p style="text-align: center;"> M C S 22 S 23 T 2 N R 6 E 1974 1911 </p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°49' W., beginning new measurement.</p>
1.30	Graded gravel road, bears N. 80° E. and S. 80° W., paralleling the Arizona Canal.
2.30	Center of the Arizona Canal, 100 lks. wide, course S. 80° W.
3.30	Graded gravel road, bears N. 80° E. and S. 80° W., paralleling the Arizona Canal.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

3.65

Point for the cor. of secs. 14, 15, 22 and 23, and the meander cor., set by Robert A. Farmer in 1911, on the N. bdy. of Right-of-Way of Arizona Canal, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. below the earths surface, with brass cap mkd.

T 2 N R 6 E
S 15 | S 14
S 22 | S 23
M C
1974

from which

A mesquite, 8 ins. diam., bears N. 73½° E., 79 lks. dist., mkd. T2N R6E S14 BT.

A mesquite, 16 ins. diam., bears N. 26° W., 52 lks. dist., mkd. T2N R6E S15 BT.

Cor. is located in a ditch, draining S from NW, and N of a dip in an access road, bearing N. 80° E. and S. 80° W.

From this cor. the S. 1/16 sec. cor. of secs. 14 and 15, set by Robert A. Farmer in 1911, bears N. 0°08' E., 20.07 chs. dist., monumented with an iron post, 3 ft. long, 1 in. diam., buried 6 ins. below the earths surface, with brass cap mkd.

No 12
1/16 |
S 15 | S 14
191

At the cor. point

Reset the iron post, 28 ins. in the ground, correct date to read 1911, and add the marks 1974 on the brass cap.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of the cor.

From the same cor. the ¼ sec. cor. of secs. 15 and 22, set by Robert A. Farmer in 1911, bears N. 89°50' W., 40.08 chs. dist., monumented with an iron post, 1 in. diam., projecting 6 ins. above the ground, with brass cap mkd.

¼ S 15
S 22
191

Remark the brass cap to read

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T 2 N R 6 E $\frac{1}{4}$ $\frac{S 15}{S 22}$ 1974 1911</p> <p>The control line was fully retraced and no evidence of the intervening cor. was found.</p> <p>Land, gently rolling. Soil, sandy loam with rocks in river bed. Timber, scattering ironwood and palo-verde, with dense salt cedar in river bottom; no undergrowth.</p> <hr/> <p>N. 89°43' E., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through scattering timber and undergrowth.</p> <p>1.50 Graded gravel road, bears N. 80° E. and S. 80° W., paralleling the Arizona Canal.</p> <p>8.20 Center of the Arizona Canal, 8.40 chs. wide, on line, flows S. 80° W.</p> <p>14.70 Graded gravel road, bears N. 80° E. and S. 80° W., paralleling the Arizona Canal.</p> <p>18.32 The meander cor. of secs. 14 and 23, set by Robert A. Farmer in 1911 on the S. bdy. of Right-of-Way of Arizona Canal, monumented with an iron post, 1 in. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">$\frac{M C}{S 14}$ $\frac{1/16}{S 23}$ 191</p> <p>Remark the brass cap to read.</p> <p style="text-align: center;"> $\frac{M C}{S 14}$ $\frac{S 23}{R 6 E}$ 1974 1911</p> <hr/> <p>S. 88°58' E., beginning new measurement.</p> <p>Over level land with medium undergrowth.</p> <p>1.72 The W. 1/16 sec. cor. of secs. 14 and 23, set by Robert A. Farmer in 1911, monumented with an iron post, 1 in. diam., firmly set, with the top 12 ins. bent over against the ground, with brass cap removed.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 27 ins. in the ground, with brass cap mkd.

T 2 N R 6 E
W 1/16 $\frac{S 14}{S 23}$
1974

from which

A U.S. Coast and Geodetic Bench Mark, bears N. 63°02' E., 2.84 chs. dist., monumented with a standard brass tablet, 3 ins. diam., set in a concrete base, 8 ins. diam., projecting 2 ins. above the ground, with brass cap mkd. B 269 1948.

Raise a mound of stone, 2½ ft. base, 1 ft. high, N of the cor.

Reset the original iron post alongside the cor.

The cor. is located on the W. edge of an unimproved dirt road, bearing NE and SW.

—————
East, beginning new measurement.

Over nearly level land, through scattering timber and medium undergrowth.

0.04 Unimproved dirt road, bears NE and SW.

19.94 The ¼ sec. cor. of secs. 14 and 23, set by Robert A. Farmer in 1911, monumented with an iron post, 1 in. diam., projecting 6 ins. above the ground, with a mound of stone, 2½ ft. base, 1 ft. high, N of the cor., with brass cap mkd.

¼ $\frac{S 14}{S 23}$
191

Remark the brass cap to read

T 2 N R 6 E
¼ $\frac{S 14}{S 23}$
1974
1911

—————
East, beginning new measurement.

Over gently rolling land, through scattering timber and medium undergrowth.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
8.90	<p>Point for the witness point of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W P T 2 N R 6 E <u>S 14</u> S 23 1974</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of the cor.</p>
9.72	<p>Present right bank of the Salt River, bears N. 62°59' E. and S. 50°22' W. This point is used for determining the witness point of secs. 14 and 23 and Angle Point 33 on the medial line of the Salt River.</p>
11.00	<p>Point for the meander cor. of secs. 14 and 23, set by Robert A. Farmer in 1911, on the right bank of the Salt River, at record bearing and dist. from the ¼ sec. cor. of secs. 14 and 23. This point is now under water; not monumented.</p> <p style="text-align: center;">_____</p> <p>S. 89°53' E., beginning new measurement.</p> <p>Over river bottom.</p>
13.11	<p>Point for the witness point of secs. 14 and 23, on the South Boundary of the Salt River Indian Reservation at the intersection of the medial line of the Salt River; hereinafter described.</p>
27.50	<p>Present left bank of the Salt River, bears N. 39°19' E. and S. 39°19' W. This point is used for determining the witness point of secs. 14 and 23 on the medial line of the Salt River.</p>
28.21	<p>The cor. of secs. 13, 14, 23 and 24.</p> <p>Land, nearly level to gently rolling. Soil, mostly sandy loam; rocky in river bottom. Timber, mesquite and ironwood with cottonwood in the river bottom. Undergrowth, creosote brush and cacti.</p>
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 88°55' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>
0.33	<p>Center of Higley Road, asphalt surfaced, bears irregularly N and S.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
19.97	<p>The E. 1/16 sec. cor. of secs. 27 and 34, monumented by a local open end iron pipe, 3/4 in. diam., projecting 3 ins. above ground. This position is 2 lks. S of a fenceline bearing irregularly E and W; not remonumented.</p> <hr/> <p>N. 88°41' W., beginning new measurement.</p> <p>Over rolling land, along an E and W fenceline.</p>
14.50	<p>Unimproved dirt road, bears S. 10° E. and N. 10° W., as scaled from U.S.G.S. quadrangle, Buckhorn, Ariz., 1956.</p>
15.60	<p>Wash, drains N, as scaled from U.S.G.S. quadrangle, Buckhorn, Ariz., 1956.</p>
19.94	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron pipe, 20 ins. long, 1/2 in. diam., projecting 14 ins. above ground. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a collar of stone, 2 1/2 ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 2 N R 6 E</p> <p>1/4 $\frac{S 27}{S 34}$</p> <p>1974</p> </div> <p>from which</p> <p style="padding-left: 40px;">A palo-verde, 8 ins. diam., bears N. 67° W., 51 lks. dist., mkd. 1/4 S27 BT.</p> <p>Reset the local cor. alongside the iron post.</p> <p>The cor. is located in an E and W fenceline.</p> <hr/>
31.90	<p>N. 88°49' W., beginning new measurement.</p> <p>Over rolling land, through medium undergrowth.</p>
39.97	<p>Unimproved road, bears N and S as scaled from U.S.G.S. quadrangle, Buckhorn, Ariz., 1956.</p> <p>The cor. of secs. 27, 28, 33 and 34, monumented with an iron pipe, 16 ins. long, 1/2 in. diam., projecting 6 ins. above ground. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS					
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 2 N R 6 E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 28</td> <td style="padding: 0 5px;">S 27</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 33</td> <td style="padding: 0 5px;">S 34</td> </tr> </table> <p>1974</p> </div> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears S. 46° E., 63 lks. dist., mkd. with aluminum lettering 13E646, 33E7N and scribed LBD-578 #2-50.</p> <p>Deposit broken glass at the base of the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W of the cor.</p> <p>Reset the local pipe alongside the iron post.</p> <p>The cor. is located 3 lks. S of a fence cor.; fences extend E and S.</p> <p>Land, rolling. Soil, sandy loam. Timber, scattering palo-verde. Undergrowth, creosote brush and cacti.</p>	S 28	S 27	S 33	S 34
S 28	S 27				
S 33	S 34				
	<p>N. 1°02' E., bet. secs. 27 and 28.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>				
1.00	Greenfield Road, bears SW and N. 70° E.				
15.80	Unimproved dirt road, bears N. 60° E. and S. 60° W., as scaled from U.S.G.S. quadrangle, Buckhorn, Ariz., 1956.				
21.50	Center of Southern Canal, 100 lks. wide, flows S. 80° W.				
22.40	Graded gravel road, bears N. 80° E. and S. 80° W., paralleling the Southern Canal.				
38.92	The ¼ sec. cor. of secs. 27 and 28, monumented with a re-bar, 18 ins. long, ½ in. diam., set flush with the ground. This position is harmoniously related to existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.				
	<p>At the cor. point</p>				

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a collar of stone, 2½ ft. base to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T 2 N R 6 E S 28 S 27 1974</p>	
	<p>Reset the re-bar alongside the iron post.</p>	
	<p>The cor. is 70 lks. W of a powerline bearing N and S.</p>	
	<p>N. 1°00' E., beginning new measurement.</p>	
	<p>Over rolling land.</p>	
4.60	<p>Power transmission line, bears N. 10° E. and S. 10° W.</p>	
23.38	<p>Point for the witness point of secs. 27 and 28.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">W P T 2 N R 6 E S 28 S 27 1974</p>	
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.</p>	
23.81	<p>Present left bank of the Salt River, bears N. 35°08' E. and S. 50°36' W. This point is used for determining the witness point of secs. 27 and 28 on the medial line of the Salt River.</p>	
31.36	<p>Point for the witness point of secs. 27 and 28, on the South Boundary of the Salt River Indian Reservation, at the intersection of the medial line of the Salt River; hereinafter described.</p>	
38.91	<p>True point for the cor. of secs. 21, 22, 27 and 28, at record distances from the meander cors. of secs. 21 and 22, and secs. 21 and 28, set by Robert A. Farmer in 1911, and is used for determining Angle Point 21, and the witness points of secs. 27 and 28, and secs. 22 and 27 on the medial line of the Salt River. Point is located on the present right bank of the Salt River, bank bears N. 60°13' E. and S. 66°56' W. Impractical to monument.</p>	
	<p>From this point the meander cor. of secs. 21 and 22 set by Robert A. Farmer in 1911 on the right bank of the Salt River, bears N. 0°02' W., 0.70 chs. dist., monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, and in a collar of stone, 3 ft. base, 8 ins. high, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>T 2 N R 6 E S 21 S 22 M C 191</p>
	<p>Correct date to read 1911 and add the marks 1974 on the brass cap.</p> <p>From this same point, a local open end pipe, 1½ ins. diam., projecting 6 ins. above ground and in a mound of stone, 3 ft. base, 6 ins. high, on the right bank of the Salt River, bears S. 89°52' W., 1.84 chs. dist.; this is accepted as the best remaining evidence of the position of the meander cor. of secs. 21 and 28 set by Robert A. Farmer in 1911.</p> <p>Land, S. 24.00 chs. rolling; remainder, river bottom. Soil, sandy and rocky. Timber, scattering palo-verde. Undergrowth, creosote bush and cacti.</p>
	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°53' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land, through scattering palo-verde and medium undergrowth.</p>
3.00	Unimproved dirt road, bears N and S.
7.80	Center of Southern Canal, 100 lks. wide, flows S. 10° E.
8.40	Graded gravel road, bears S. 10° E. and N. 10° W., paralleling the Southern Canal.
26.00	Old canal, bears NE and SW, abandoned.
39.62	<p>The ¼ sec. cor. of secs. 22 and 27, monumented with an iron pipe, 20 ins. long, 1 in. diam., projecting 2 ins. above the ground. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>T 2 N R 6 E ¼ S 22 S 27 1974</p>
	<p>Reset the iron pipe alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
	S. 89°52' W., beginning new measurement.	
16.43	Point for the witness point of secs. 22 and 27.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">W P T 2 N R 6 E <u>S 22</u> S 27 1974</p>	
	Raise a mound of stone, 2 ft. base, 1 ft. high, N of the cor.	
16.98	Present left bank of the Salt River, bears N. 56°50' E. and S. 68°10' W. This point is used for determining the witness point of secs. 22 and 27 on the medial line of the Salt River.	
28.325	Point for the witness point of secs. 22 and 27, on the South Boundary of the Salt River Indian Reservation, at the intersection of the medial line of the Salt River; hereinafter described.	
39.67	The true point for the cor. of secs. 21, 22, 27 and 28.	
	<p>Land, E. 56.00 chs., gently rolling; remainder, river bottom. Soil, sandy loam. Timber, palo-verde. Undergrowth, creosote bush and cacti.</p>	
	From the cor. of secs. 27, 28, 33 and 34.	
	S. 88°22' W. bet. secs. 28 and 33.	
	Over rolling land, through scattering timber and medium undergrowth.	
0.60	Greenfield Road, asphalt surfaced, bears NE, curving N. 70° E and S. 40° W.	
9.83	Fenceline bears N and S, 16 lks. dist., to a fence cor.; fences extend N and W. Thence along fenceline.	
39.90	The ¼ sec. cor. of secs. 28 and 33, monumented with a granite stone, 16 x 8 x 6 ins. firmly set projecting 3 ins. above ground, mkd. ¼ on the N. face.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.	

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	T 2 N R 6 E $\frac{1}{4}$ $\frac{S 28}{S 33}$ 1974
	Bury the mkd. stone alongside the iron post.
	The cor. is 2 lks. NW of a fence cor.; fences extend E and S.

	S. 88°22' W., beginning new measurement.
	Over nearly level land, through medium undergrowth.
14.20	Center of Southern Canal, 100 lks. wide, flows SW.
16.50	Graded gravel road, bears NE and SW, paralleling the Southern Canal.
16.80	Center of E. edge of Lehi Road, asphalt surfaced, thence westerly along center of same road.
40.02	The cor. of secs. 28, 29, 32 and 33, monumented with an unmarked cobble stone, set in a receptacle, 10 ins. diam., 12 ins. deep, in the center of Lehi Road, bearing E and W, as recorded with the Arizona State Highway Department by Merle Brock on 5-25-44. This position has long been recognized by private surveyors as the cor., is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position; not remonumented.
	Land, E. 54.00 chs., rolling, remainder, level. Soil, sandy loam. Timber, scattering palo-verde E. 54.00 chs. Undergrowth, creosote bush E. 54.00 chs.
	N. 1°27' E., bet. secs. 28 and 29.
	Over nearly level land.
0.30	Enter citrus grove, edge bears E and W.
18.20	Enter medium creosote bush, edge bears E and W.
20.80	Old canal ditch, dry, bears N. 80° E. and S. 80° W.
23.54	Point for the witness point of secs. 28 and 29.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	W P T 2 N R 6 E S 29 S 28 1974
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS										
24.065	Present left bank of the Salt River, bears S. 83°04' E. and N. 83°04' W. This point is used for determining the witness point of secs. 28 and 29 on the medial line of the Salt River.									
31.675	Point for the witness point of secs. 28 and 29, on the South Boundary of the Salt River Indian Reservation at the intersection of the medial line of the Salt River; hereinafter described.									
39.285	Present right bank of the Salt River, bears N. 55°53' E. and S. 55°53' W. This point is used for determining the witness point of secs. 28 and 29 on the medial line of the Salt River. Thence through medium undergrowth, bears E and W.									
40.01	Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate distance; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T 2 N R 6 E $\frac{1}{4}$ S 29 S 28 1974 </div> Raise a mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of the cor.									
49.43	The meander cor. of secs. 28 and 29, set by Robert A. Farmer in 1911, on the right bank of the Salt River, monumented with an iron post, 1 in. diam., with the top 10 ins. bent over against the ground, with brass cap removed. The cor. is in the center of an unimproved dirt road, bearing N; not remonumented. <hr style="width: 20%; margin: 10px auto;"/> N. 0°03' E., beginning new measurement. Along an unimproved dirt road, bearing N.									
10.66	Point for the N. 1/16 sec. cor. of secs. 28 and 29, at proportionate dist., falls in an unimproved dirt road; there is no remaining evidence of the original cor.; not monumented.									
30.59	The cor. of secs. 20, 21, 28 and 29, monumented with an iron post, 1 in. diam., buried 2 ins. below the earths surface, with brass cap mkd. <div style="text-align: center;"> <table border="1" style="margin: auto;"> <tr> <td>S 20</td> <td>S 21</td> </tr> <tr> <td></td> <td>T 2 N</td> </tr> <tr> <td></td> <td>R 6 E</td> </tr> <tr> <td>S 29</td> <td>S 28</td> </tr> </table> 191 </div>	S 20	S 21		T 2 N		R 6 E	S 29	S 28	
S 20	S 21									
	T 2 N									
	R 6 E									
S 29	S 28									

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

Remark the brass cap to read

T 2 N	R 6 E
S 20	S 21
S 29	S 28
1974	
1911	

from which

A re-bar, $\frac{1}{2}$ in. diam., projecting 3 ins. above the ground, bears N. $50^{\circ}20'$ E., 46.5 lks. dist.

An Army Corps of Engineers survey marker bears S. $44^{\circ}30'$ W., 60 lks. dist., monumented with a brass tablet, $3\frac{1}{2}$ ins. diam., set in a concrete base, 6 ins. sq., projecting 6 ins. above the ground, and in a mound of stone, 10 ft. diam., 1 ft. high, with tablet mkd. TTAE-1 1948.

An Indian Allotment cor., bears S. $89^{\circ}51'$ W., 151.7 lks. dist., monumented with an iron post, 2 ins. diam., projecting 3 ins. above the ground, with brass cap mkd. +.

The cor. is located at a junction of unimproved dirt roads, extending N, S and W.

Land, nearly level to gently rolling.

Soil, sandy loam; rocky in river bottom.

Timber, citrus trees S. 18.00 chs.

Undergrowth, N. 60.00 chs., creosote bush and cacti.

From the cor. of secs. 28, 29, 32 and 33.

N. $89^{\circ}49'$ W., bet. secs. 29 and 32.

Along the center of Lehi Road, asphalt surfaced, bearing E and W.

39.81 The $\frac{1}{4}$ sec. cor. of secs. 29 and 32, monumented by a cobble stone, set in a receptacle, 10 ins. diam., 1 ft. deep, with stone mkd. + on top, in the center of Lehi Road, as recorded with the Arizona State Highway Department by Merle Brock on 5-25-44. This position has long been recognized by private surveyors as the cor., is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position; not remonumented.

N. $89^{\circ}49'$ W., beginning new measurement.

Along the center of Lehi Road, asphalt surfaced, bearing E and W.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
14.00	Leave Lehi Road, on curve, bears E and SW; thence over nearly level land.
18.00	Irrigation ditch, 15 lks. wide, 3 ft. deep, course SW.
20.50	Power transmission line and fenceline, bears N and S.
20.70	Gravel road, bears N and S.
20.90	Center of concrete ditch, bears N and S.
21.20	Enter citrus grove, edge bears N and S.
39.81	<p>The cor. of secs. 29, 30, 31 and 32, monumented with a re-bar, 3/4 in. diam., set flush with the earths surface on the N. shoulder of a dozed dirt road, bearing E and W. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position; not remonumented.</p> <p>Land, nearly level. Soil, sandy loam. Timber, W. 60.00 chs., citrus trees; undergrowth, weeds and grass.</p> <hr/> <p>From the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., heretofore described.</p> <p>N. 89°51' E., bet. secs. 30 and 31.</p> <p>Over level land.</p>
0.55	Power transmission line, bears N and S. Also, fence cor.; fences extend E and S. Enter citrus grove, edge bears E and S. Thence along an E-W fenceline.
38.78	Point for the ¼ sec. cor. of secs. 30 and 31, at proportionate dist., there is no remaining evidence of the original cor.; not monumented.
39.81	Fence cor.; fences extend N, S and W. Enter adjacent citrus grove, edge bears N and S.
79.61	<p>The cor. of secs. 29, 30, 31 and 32.</p> <p>Land, level. Soil, sandy loam. Timber, citrus; undergrowth, weeds and grass.</p> <hr/> <p>N. 1°24' E., bet. secs. 29 and 30.</p> <p>Through a citrus grove.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
0.40	Canal ditch, 20 lks. wide, 4 ft. deep, flows W.
5.00	Leave citrus grove, bears E and W.
5.80	Fence line, bears E and W; enter medium undergrowth, edge bears E and W; thence over gently rolling land.
7.455	Point for the witness point of secs. 29 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	W P T 2 N R 6 E S 30 S 29 1974
7.94	Present left bank of the S channel of the Salt River, bears N. 84°38' E. and N. 86°34' W.
11.97	Present right bank of the S channel of the Salt River, bears N. 86°35' E. and S. 86°35' W.
13.27	Point for the witness point of secs. 29 and 30. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	W P T 2 N R 6 E S 30 S 29 1974
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of the cor.
39.89	The ¼ sec. cor. of secs. 29 and 30, monumented with an iron pipe, 18 ins. long, ¾ in. diam., projecting 3 ins. above the ground, set in a collar of stone, 1 ft. base, 8 ins. high. This position is harmoniously related to other existing survey cors. in the area, and is accepted as the best available evidence of the original cor. position.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T 2 N R 6 E ¼ S 30 S 29 1974
	Deposit broken glass at the base of the iron post.
	Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.
	Reset the iron pipe alongside the iron post.
	N. 0°15' W., beginning new measurement.
	Over gently rolling land.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
9.725	<p>Point selected for the witness point of secs. 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W P</p> <p>T 2 N R 6 E</p> <p>S 30 S 29</p> <p>1978</p> </div>	
10.58	<p>Present left bank of the N channel of the Salt River, bears S. 65°01' E. and N. 70°57' W. This point is used for determining the witness point of secs. 29 and 30 on the medial line of the Salt River.</p>	
14.395	<p>Point for the witness point of secs. 29 and 30, on the South Boundary of the Salt River Indian Reservation at the intersection of the medial line of the Salt River; hereinafter described.</p>	
18.21	<p>Present right bank of the N channel of the Salt River, bears S. 70°05' E. and N. 62°49' W. This point is used for determining the witness point of secs. 29 and 30 on the medial line of the Salt River.</p>	
23.59	<p>Point for the meander cor. of secs. 29 and 30, set by Robert A. Farmer in 1911, on the right bank of the Salt River, at record bearing and dist. from the sec. cor. of secs. 19, 20, 29 and 30; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T 2 N R 6 E</p> <p>S 30 S 29</p> <hr style="width: 50px; margin: 0 auto;"/> <p>MC</p> <p>1977</p> </div> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of the cor.</p> <div style="text-align: center; margin-top: 20px;"> <hr style="width: 100px; margin: 0 auto;"/> </div> <p>N. 0°03' W., beginning new measurement.</p>	
1.00	<p>Unimproved dirt road, bears E and W.</p>	
2.40	<p>Unimproved dirt road, bears NE and SW.</p>	
9.50	<p>Unimproved dirt road, bears E and W.</p>	
16.42	<p>The cor. of secs. 19, 20, 29 and 30, set by Robert A. Farmer in 1911, monumented with an iron post, 1 in. diam., projecting 3 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>S 19 S 20</p> <hr style="width: 50px; margin: 0 auto;"/> <p>T 2 N</p> <p>R 6 E</p> <p>S 30 S 29</p> <p>191</p> </div>	

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

Remark the brass cap to read

$$\begin{array}{r} T\ 2\ N\ R\ 6\ E \\ S\ 19\ |S\ 20 \\ S\ 30\ |S\ 29 \\ 1974 \\ 1911 \end{array}$$

from which

An Army Corps of Engineers survey marker, bears N. 89°05' E., 11.68 chs. dist., monumented with a brass tablet, 3½ ins. diam., set in a concrete base, 5 ins. diam., projecting 1 in. above ground with tablet mkd. TTADI 1948.

Land, nearly level to gently rolling.
Soil, sandy loam; rocky in river bottom.
Timber, citrus in S. 5.00 chs., scattered mesquite on remainder.
Undergrowth, creosote bush and cacti.

From the cor. of secs. 20, 21, 28 and 29.

N. 89°53' W., bet. secs. 20 and 29.

Over nearly level land, through scattering timber and undergrowth.

19.975 Point for the E. 1/16 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.

39.95 The ¼ sec. cor. of secs. 20 and 29, set by Robert A. Farmer in 1911, monumented with an iron post, 1 in. diam., projecting 2 ins. above the ground, with brass cap lying on the ground alongside mkd.

$$\frac{1}{4} \frac{S\ 20}{S\ 29}$$

191

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 2\ N\ R\ 6\ E \\ \frac{1}{4} \frac{S\ 20}{S\ 29} \\ 1974 \end{array}$$

Buried the original iron post and brass cap alongside the cor.

The cor. is 35 lks. N of an unimproved dirt road, bearing E and W.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 89°56' W., beginning new measurement.</p> <p>Over nearly level land.</p>
20.03	Point for the W. 1/16 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
20.10	Power transmission line, bears N and S.
20.30	Unimproved dirt road, bears N and S.
28.20	Junction of unimproved dirt roads; roads extend E, S. 60° W. and N. 35° W.
40.06	<p>The cor. of secs. 19, 20, 29 and 30.</p> <p>Land, nearly level. Soil, sandy loam. Timber, scattered palo-verde. Undergrowth, creosote bush and cacti.</p>
	<p>From the cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., heretofore described.</p> <p>N. 89°55' E., bet. secs. 19 and 30.</p> <p>Over gently rolling land, through scattering timber and undergrowth.</p>
10.10	Unimproved dirt road, bears N and S.
20.36	Point for the W. 1/16 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
40.34	<p>The 1/4 sec. cor. of secs. 19 and 30, set by Robert A. Farmer in 1911, monumented with an iron post, 1 in. diam., projecting 4 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$ 191 </p> <p>Remark the brass cap to read</p> <p style="text-align: center;"> T 2 N R 6 E $\frac{1}{4}$ $\frac{S\ 19}{S\ 30}$ 1974 1911 </p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 89°57' E., beginning new measurement.</p> <p>Over gently rolling land.</p>
20.03	The E. 1/16 sec. cor. of secs. 19 and 30, set by Robert A. Farmer in 1911, monumented with an iron post, 1 in. diam., set flush with the earths surface, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines
of T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	No. 2 1/16 $\frac{S\ 19}{S\ 30}$ 1911
	<hr style="width: 10%; margin: auto;"/>
	N. 89°55' E., beginning new measurement. Over gently rolling land.
20.04	The cor. of secs. 19, 20, 29 and 30. Land, gently rolling. Soil, sandy loam. Timber, palo-verde. Undergrowth, creosote brush and cacti.
	Completion Survey of the Subdivisional Lines, T. 2 N., R. 6 E., Gila and Salt River Meridian, Ariz.
	From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 5 ins. above the ground, with brass cap mkd. as described in the official record of the 1930-1932 resurvey of the W bdy. of T. 2 N., R. 7 E. The cor. is located in a fenceline, bearing N and S. N. 89°48' W., bet. secs. 13 and 24. Over rolling land, through scattered timber and moderate undergrowth.
1.50	Centerline of Bush Highway, asphalt surfaced, bears N and S.
2.10	Power transmission line, bears N and S.
7.70	Enter mountainous land, bears NW and SE; thence across the northern slopes of Schlechts Butte.
15.40	Spur, slopes N.
19.20	Spur, slopes N. 10° W.
25.70	Spur, slopes N. 30° W.
38.50	Small draw, drains N.
38.71	Point for the $\frac{1}{4}$ sec. cor. of secs. 13 and 24. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, encircled by a mound of stone, 3 ft. base to top, with brass cap mkd.
	T 2 N R 6 E $\frac{1}{4}$ $\frac{S\ 13}{S\ 24}$ 1974

Completion Survey of the Subdivisional Lines,
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
47.20	Enter gently rolling land, bears NE and SW.
47.80	Unimproved dirt road, bears N. 10° E. and S. 10° W.
65.30	Unimproved dirt road, bears NE and SW.
70.40	Center of Southern Canal, 120 lks. wide, flows S. 50° W.
71.40	Graded gravel road, bears N. 50° E. and S. 50° W., paralleling the Southern Canal.
78.71	The cor. of secs. 13, 14, 23 and 24; heretofore described.
	<p>Land, mountainous and rolling. Soil, rocky and shallow with granite outcroppings. Timber, palo-verde and mesquite. Undergrowth, creosote brush and cacti.</p>
	<p>The Informative Traverse of the Right Bank of the Salt River Through T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona, used to determine the medial line, the South Boundary of the Salt River Indian Reservation.</p>
	<p>The executive order of June 14, 1879 established the South Boundary of the Salt River Indian Reservation through Township 2 North, Ranges 6 and 7 East and into Township 3 North, Range 7 East as following the middle of the Salt River to a point where the easterly line of Camp McDowell Military Reservation, if prolonged South, would strike said river.</p>
	<p>To determine the medial line of the Salt River, an informational traverse was made of the present banks of the river, correlated with current aerial photos, and the medial line then established at mid-point between the banks. Temporary points were established along the informative traverse lines but no permanent monuments were set.</p>
	<p>From the witness point of secs. 25 and 30, T. 2 N., Rs. 5 and 6 E., on the present right bank of the N channel of the Salt River; heretofore described.</p>
	<p>Thence upstream with the traverse of the right bank of the N channel of the Salt River in sec. 30.</p>
	<p>N. 73°59' E., 4.55 chs.</p>
	<p>N. 78°44' E., 11.30 chs. At end of course.</p>
	<p>Point used for determining Angle Point 2 on the medial line.</p>

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS		
N. 82°19' E.,	10.00 chs.	At end of course.
		Point used for determining Angle Point 3 on the medial line.
N. 72°59' E.,	4.30 chs.	
S. 86°41' E.,	4.69 chs.	At end of course.
		Point used for determining Angle Point 4 on the medial line.
N. 86°34' E.,	16.79 chs.	At end of course.
		Point used for determining Angle Point 5 on the medial line.
S. 80°31' E.,	4.99 chs.	
S. 73°40' E.,	13.40 chs.	At end of course.
		Point used for determining Angle Point 6 on the medial line.
S. 62°49' E.,	13.25 chs.	At end of course.
		Intersect the sec. line bet. secs. 29 and 30. This point is used for determining Angle Point 7 on the medial line.
		From this point, the meander cor. of secs. 29 and 30, bears N. 0°15' W., 5.38 chs. dist.; heretofore described.
Thence in sec. 29.		
S. 70°05' E.,	3.40 chs.	
S. 43°15' E.,	4.68 chs.	At end of course.
		Point used for determining Angle Point 8 on the medial line.
S. 68°05' E.,	11.50 chs.	
S. 62°07' E.,	10.89 chs.	At end of course.
		Point used for determining Angle Point 9 on the medial line.
S. 52°47' E.,	11.71 chs.	
S. 67°47' E.,	7.19 chs.	At end of course.
		Point used for determining Angle Point 10 on the medial line.

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
S. 74°24' E.,	9.09 chs.	At 7.69 chs., the point used for determining Angle Point 11 on the medial line.
S. 81°49' E.,	5.32 chs.	At end of course.
Point used for determining Angle Point 12 on the medial line.		
N. 85°04' E.,	7.22 chs.	
N. 74°47' E.,	1.77 chs.	At end of course.
Point used for determining Angle Point 13 on the medial line.		
N. 65°00' E.,	13.40 chs.	
N. 55°53' E.,	2.47 chs.	At this point.
Intersect the sec. line bet. secs. 28 and 29. This point is used for determining the witness point of secs. 29 and 30 on the medial line.		
From this point, the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, bears N. 1°27' E., 0.725 chs. dist., heretofore described.		
Thence in sec. 28.		
Along a bank, 3 to 12 ft. high, through medium undergrowth.		
N. 55°53' E.,	1.53 chs.	
S. 83°43' E.,	4.40 chs.	
N. 75°09' E.,	6.90 chs.	
N. 78°36' E.,	3.70 chs.	At end of course.
Point used for determining Angle Point 14 on the medial line.		
N. 65°38' E.,	10.00 chs.	At end of course.
Point used for determining Angle Point 15 on the medial line.		
N. 79°34' E.,	4.20 chs.	At end of course.
Point used for determining Angle Point 16 on the medial line.		

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
	N. 60°11' E., 9.90 chs.	
	N. 52°38' E., 13.10 chs.	At end of course. Point used for determining Angle Point 17 on the medial line.
	N. 51°09' E., 12.70 chs.	At 6.30 chs., the point used for determining Angle Point 18 on the medial line. At end of course. Point used for determining Angle Point 19 on the medial line.
	N. 14°05' E., 4.40 chs.	
	N. 60°49' E., 3.50 chs.	At end of course. Point used for determining Angle Point 20 on the medial line.
	N. 73°08' E., 12.20 chs.	
	N. 66°56' E., 6.93 chs.	At end of course. True point for the cor. of secs. 21, 22, 27 and 28; heretofore described. This point is used for determining Angle Point 21, and the witness points of secs. 27 and 28, and secs. 22 and 27 on the medial line.
Thence in sec. 22.		
Along a well defined bank, 3 to 12 ft. high, through scattering mesquite and undergrowth.		
	N. 60°13' E., 9.20 chs.	At .80 chs., power transmission line, bears N and S.
	N. 56°45' E., 9.10 chs.	At 3.00 chs., thence through scattering salt cedar.
	N. 60°43' E., 26.60 chs.	At 14.70 chs., the point used for determining Angle Point 22 on the medial line.

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
		At end of course.
		Point used for determining Angle Point 23 on the medial line.
N. 51°33' E., 9.70 chs.		At end of course.
		Point used for determining Angle Point 24 on the medial line.
N. 71°48' E., 7.10 chs.		
N. 57°04' E., 2.50 chs.		At end of course.
		Point used for determining Angle Point 25 on the medial line.
N. 51°58' E., 6.50 chs.		At end of course.
		Point used for determining Angle Point 26 on the medial line.
N. 29°29' E., 2.80 chs.		At end of course.
		Point used for determining Angle Point 27 on the medial line.
N. 53°19' E., 5.50 chs.		
N. 50°18' E., 7.90 chs.		
N. 52°24' E., 4.80 chs.		
N. 52°10' E., 5.19 chs.		At this point
		Intersect the sec. line bet. secs. 22 and 23. This point is used for determining the witness point of secs. 22 and 23 on the medial line.
		From this point, the point for the meander cor. of secs. 22 and 23, set by Robert A. Farmer in 1911, bears N. 0°14' E., 0.20 chs. dist.; heretofore described.

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
	Thence in sec. 23.	
	Along a well defined bank, 3 to 10 ft. high, through scattering mesquite and medium undergrowth.	
	N. 52°10' E., 3.21 chs.	
	N. 53°21' E., 8.70 chs.	At end of course.
		Point used for determining Angle Point 28 on the medial line.
	N. 67°06' E., 10.00 chs.	At end of course.
		Point used for determining Angle Point 29 on the medial line.
	N. 84°51' E., 1.70 chs.	At end of course.
		Point used for determining Angle Point 30 on the medial line.
		Thence through dense salt cedar.
	N. 62°06' E., 2.10 chs.	
	N. 71°25' E., 1.80 chs.	
	N. 66°57' E., 10.20 chs.	At end of course.
		Point used for determining Angle Point 31 on the medial line.
	N. 50°42' E., 3.30 chs.	
	N. 51°32' E., 4.20 chs.	At end of course.
		Point used for determining Angle Point 32 on the medial line.
	N. 64°47' E., 9.90 chs.	
	N. 50°22' E., 1.86 chs.	At end of course.
		Point used for determining Angle Point 33 on the medial line.

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

Intersect the sec. line bet. secs. 14 and 23. This point is used for determining the true point for the witness point of secs. 14 and 23 on the medial line; not monumented.

From this point, the witness point of secs. 14 and 23 on the N side of the river, bears West, .82 chs. dist.; heretofore described.

Thence in sec. 14.

Through salt cedar, along a 2 to 6 ft. bank.

N. 62°59' E., 7.08 chs.

N. 64°22' E., 4.91 chs.

N. 75°42' E., 2.10 chs.

N. 54°49' E., 8.70 chs. At end of course.

Point used for determining Angle Point 34 on the medial line.

N. 72°43' E., 5.00 chs.

N. 61°59' E., 6.00 chs. At this point

Intersect the sec. line bet. secs. 13 and 14. This point is used for determining the witness point of secs. 13 and 14 on the medial line.

From this point, the witness point of secs. 13 and 14 on the N side of the river, bears N. 1°43' E., 0.71 chs. dist.; heretofore described.

Thence in sec. 13.

Along a bank, 2 to 8 ft. high, through medium timber.

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
N. 61°59' E., 2.42 chs.		
S. 55°55' E., 1.40 chs.	At end of course.	
	Point used for determining Angle Point 35 on the medial line.	
N. 82°11' E., 3.70 chs.		
N. 80°46' E., 3.10 chs.	At end of course.	
	Point used for determining Angle Point 36 on the medial line.	
N. 9°36' E., 4.41 chs.		
N. 28°33' E., 2.60 chs.		
N. 40°35' E., 2.00 chs.		
N. 44°31' E., 3.00 chs.		
N. 9°00' E., 2.90 chs.	At end of course.	
	Point used for determining Angle Point 37 on the medial line.	
N. 56°06' E., 4.70 chs.		
N. 64°38' E., 4.40 chs.	At .30 chs., graded gravel road, bears S. 10° E. and N. 10° W.	
N. 63°58' E., 4.40 chs.	At end of course.	
	Point used for determining Angle Point 38 on the medial line.	
N. 71°03' E., 8.90 chs.	At end of course.	
	Point used for determining Angle Point 39 on the medial line.	
	Thence along concreted bank, 10 to 15 ft. high.	
N. 76°30' E., 6.18 chs.	At end of course.	
	Point used for determining the point for Angle Point 40 on the medial line.	

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
		<p>This point is located in the middle of the axis of Granite Reef Dam, at the point where the N end of the dam intersects the inside edge of the walkway over the Arizona Canal.</p> <p>Thence along walkway over Arizona Canal outlet.</p>
N. 80°47' E., 2.48 chs.		At end of course.
		<p>Bureau of Reclamation Bench Mark Number 1, monumented with a brass tablet, 3 ins. diam., set in the walkway, flush with concrete, top mkd. 1 Elevation above Sea 1325.17 Feet PHX Datum.</p> <p>Thence along a well defined bank, 2 to 4 ft. high, through medium timber and undergrowth.</p>
N. 89°28' E., 2.04 chs.		At end of course.
		Point used for determining Angle Point 43 on the medial line.
		Thence along a bank, 2 to 6 ft. high, through medium mesquite timber.
S. 73°48' E., 4.10 chs.		
S. 85°28' E., 2.61 chs.		At end of course.
		Point used for determining Angle Point 44 on the medial line.
N. 83°36' E., 3.09 chs.		
S. 85°02' E., 3.86 chs.		At end of course.
		Point used for determining Angle Point 45 on the medial line.
S. 80°47' E., 9.06 chs.		At end of course.
		Point used for determining Angle Point 46 on the medial line.
S. 87°20' E., 6.86 chs.		At end of course.

Traverse of the Right Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>Point used for determining Angle Point 47 on the medial line.</p> <p>N. 79°11' E., 4.25 chs. At end of course.</p> <p>Intersect the sec. line bet. secs. 13 and 18 on the E. bdy. of the Tp.; not monumented.</p> <p>From this point, the $\frac{1}{4}$ sec. cor. of secs. 13 and 18 on the E. bdy. of the Tp., bears N. 2°37' E., 1.45 chs. dist., described in the field notes of the concurrent survey of T. 2 N., R. 7 E.</p>	
		<p>The informative traverse of the Left Bank of the Salt River through T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona, used to determine the medial line, the South Boundary of the Salt River Indian Reservation.</p>	
		<p>From the witness point of secs. 25 and 30, T. 2 N., Rs. 5 and 6 E., on the present left bank of the N channel of the Salt River; heretofore described.</p> <p>Thence upstream with the traverse of the left bank of the N channel of the Salt River in sec. 30.</p> <p>N. 79°21' E., 21.63 chs. At 14.03 chs., the point used for determining Angle Point 2 on the medial line.</p> <p>At end of course.</p> <p>Point used for determining Angle Point 3 on the medial line.</p> <p>S. 83°33' E., 16.23 chs. At end of course.</p> <p>Point used for determining Angle Point 4 on the medial line.</p> <p>S. 79°08' E., 8.12 chs. At end of course.</p> <p>Point used for determining Angle Point 5 on the medial line.</p> <p>S. 89°46' E., 9.93 chs.</p> <p>N. 89°03' E., 9.07 chs. At end of course.</p> <p>Point used for determining Angle Point 6 on the medial line.</p>	

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
S. 75°47' E.,	11.69 chs.	
S. 70°57' E.,	5.10 chs.	At end of course.
Intersect the sec. line bet. secs. 29 and 30. This point is used for determining Angle Point 7 on the medial line.		
From this point, the witness point of secs. 29 and 30, on the S side of the N channel of the Salt River, bears S. 0°15' E., 0.855 chs. dist.; heretofore described.		
Thence in sec. 29.		
S. 65°01' E.,	5.85 chs.	At end of course.
Point used for determining Angle Point 8 on the medial line.		
S. 63°00' E.,	13.08 chs.	
S. 71°39' E.,	6.20 chs.	At end of course.
Point used for determining Angle Point 9 on the medial line.		
S. 57°34' E.,	9.845 chs.	
S. 51°54' E.,	12.13 chs.	At end of course.
Point used for determining Angle Point 10 on the medial line.		
S. 52°28' E.,	2.85 chs.	At end of course. Junction of the right bank of the S channel and the left bank of the N channel. This point is used for determining Angle Point 11 on the medial line.
S. 52°17' E.,	7.43 chs.	At 3.715 chs., the center of the S channel of the Salt River, 7.43 chs. wide, drains S. 82°44' W. At end of course.
Point on the left bank of the S channel used for determining Angle Point 11 on the medial line.		

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 86°05' E., 7.045 chs.</p> <p>S. 89°47' E., 4.20 chs. At end of course.</p> <p style="padding-left: 150px;">Point used for determining Angle Point 12 on the medial line.</p> <p>N. 77°16' E., 9.80 chs. At end of course.</p> <p style="padding-left: 150px;">Point used for determining Angle Point 13 on the medial line.</p> <p>N. 83°21' E., 3.60 chs.</p> <p>S. 87°54' E., 5.10 chs.</p> <p>S. 83°04' E., 1.00 chs. At this point</p> <p style="padding-left: 150px;">Intersect the line bet. secs. 28 and 29. This point is used to determine the witness point of secs. 28 and 29 on the medial line.</p> <p style="padding-left: 150px;">From this point, the witness point of secs. 28 and 29 on the S. side of the river, bears S. 1°27' W., 0.525 chs. dist.; heretofore described.</p>
	<p>Thence in sec. 28.</p> <p>Along a well defined cut bank, 3 to 10 ft. high, through scattering mesquite timber.</p> <p>S. 83°04' E., 6.50 chs.</p> <p>S. 77°19' E., 2.10 chs.</p> <p>S. 84°56' E., 16.70 chs. At end of course.</p> <p style="padding-left: 150px;">Point used for determining Angle Point 14 on the medial line.</p> <p>S. 89°34' E., 5.30 chs. At end of course.</p> <p style="padding-left: 150px;">Point used for determining Angle Point 15 on the medial line.</p>

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
N. 64°38' E., 6.10 chs.		
N. 58°37' E., 6.70 chs.	At end of course.	
	Point used for determining Angle Point 16 on the medial line.	
N. 72°10' E., 3.10 chs.		
N. 54°03' E., 3.40 chs.		
N. 60°42' E., 10.20 chs.		
N. 72°45' E., 6.20 chs.	At end of course.	
	Point used for determining Angle Point 17 on the medial line.	
N. 57°02' E., 5.50 chs.		
N. 46°12' E., 6.20 chs.	At end of course.	
	Point used for determining Angle Point 18 on the medial line.	
N. 31°28' E., 8.90 chs.		
N. 34°45' W., 4.70 chs.	At end of course.	
	Point used for determining Angle Point 19 on the medial line.	
N. 12°12' E., 1.40 chs.	At end of course.	
	Thence along a bank, 2 to 5 ft. high.	
N. 50°45' E., 1.60 chs.		
N. 31°05' E., 4.00 chs.	At end of course.	
	Point used for determining Angle Point 20 on the medial line.	
N. 45°07' E., 2.10 chs.		

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona

CHAINS	
N. 50°36' E., 2.77 chs.	At end of course.
	Intersect the sec. line bet. secs. 27 and 28. This point is used to determine the witness point of secs. 27 and 28 on the medial line.
	From this point, the witness point of secs. 27 and 28 on the S side of the river, bears S. 1°00' W., 0.43 chs. dist.; heretofore described.
Thence in sec. 27.	
Along a cut bank, 2 to 5 ft. high, through scattering mesquite timber.	
N. 35°08' E., 5.40 chs.	At 1.10 chs., power transmission line, bears N and S.
N. 23°22' E., 3.60 chs.	At end of course.
	Point used for determining Angle Point 21 on the medial line.
N. 72°52' E., 3.90 chs.	
S. 89°13' E., 2.50 chs.	
N. 62°09' E., 9.60 chs.	
N. 58°28' E., 1.90 chs.	
N. 68°10' E., 2.23 chs.	At end of course.
	Intersect the sec. line bet. secs. 22 and 27. This point is used to determine the witness point of secs. 22 and 27 on the medial line.
	From this point, the witness point of secs. 22 and 27 on the S side of the river, bears N. 89°52' E., 0.55 chs. dist.; heretofore described.
Thence in sec. 22.	
Along a cut bank, 3 to 5 ft. high, through scattering mesquite timber.	

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
N. 56°50' E., 13.40 chs.	At end of course. Point used for determining Angle Point 22 on the medial line.	
S. 80°44' E., 10.30 chs.	At end of course Point used for determining Angle Point 23 on the medial line.	
N. 57°28' E., 12.60 chs.	At end of course. Point used for determining Angle Point 24 on the medial line.	
N. 46°19' E., 11.00 chs.	At end of course. Point used for determining Angle Point 25 on the medial line.	
	Thence through medium salt cedar.	
N. 43°51' E., 10.40 chs.	At end of course. Point used for determining Angle Point 26 on the medial line.	
N. 47°07' E., 4.30 chs.	At end of course. Point used for determining Angle Point 27 on the medial line.	
N. 49°47' E., 7.40 chs.		
N. 64°14' E., 1.47 chs.	At end of course. Intersect the sec. line bet. secs. 22 and 23. This point is used to determine the wit- ness point of secs. 22 and 23 on the medial line. From this point, the witness point of secs. 22 and 23 on the S side of the river, bears S. 1°07' W., 0.38 chs. dist.; heretofore described.	
	Thence in sec. 23.	

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

	CHAINS		
		Along a well defined bank, 2 to 8 ft. high, through medium mesquite and dense salt cedar.	
		N. 45°45' E., 5.70 chs.	
		N. 53°43' E., 4.40 chs.	
		N. 59°40' E., 4.40 chs.	At end of course.
			Point used for determining Angle Point 28 on the medial line.
		N. 62°52' E., 11.90 chs.	At end of course.
			Point used for determining Angle Point 29 on the medial line.
		N. 17°26' E., 4.50 chs.	At end of course.
			Point used for determining Angle Point 30 on the medial line.
			Thence along a sandy bank, 1 to 2 ft. high.
		N. 65°21' E., 23.00 chs.	At 16.90 chs., the point used for determining Angle Point 31 on the medial line.
		N. 25°50' W., 2.60 chs.	At end of course.
			Point used for determining Angle Point 32 on the medial line.
			Thence along a well defined bank, 2 to 4 ft. high, through scattering salt cedar, mesquite and cottonwood timber.
		N. 54°47' E., 11.30 chs.	
		N. 48°42' E., 4.40 chs.	At end of course.
			Point used for determining Angle Point 33 on the medial line.
		S. 84°55' E., 1.60 chs.	
		S. 63°19' E., 5.27 chs.	
		N. 81°36' E., 12.80 chs.	At end of course.

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

Point used for determining
Angle Point 34 on the medial
line.

N. 39°19' E., 6.04 chs. At this point

Intersect the sec. line bet.
secs. 14 and 23. This point
is used to determine the
point for the witness point of
secs. 14 and 23 on the medial
line.

From this point, the cor. of
secs. 13, 14, 23 and 24, bears
S. 89°53' E., 0.71 chs. dist.;
heretofore described.

Thence in sec. 14.

Along a well defined bank, 1 to 8 ft. high.

N. 39°19' E., .26 chs.

N. 54°06' E., .70 chs. At this point

Intersect the sec. line bet.
secs. 13 and 14. This point
is used to determine the wit-
ness point of secs. 13 and 14
on the medial line.

From this point, the cor. of
secs. 13, 14, 23 and 24, bears
S. 1°43' W., 0.61 chs. dist.;
heretofore described.

Thence in sec. 13.

Along a well defined bank, 2 to 12 ft. high, through
scattering mesquite, salt cedar and cottonwood timber.

N. 54°06' E., 2.60 chs.

N. 65°49' E., 6.50 chs. At end of course.

Point used for determining
Angle Point 35 on the medial
line.

N. 54°10' E., 4.00 chs.

N. 31°04' E., 4.40 chs. At end of course.

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

	CHAINS		
			Point used for determining Angle Point 36 on the medial line.
	N. 51°46' E., 2.60 chs.		
	N. 40°22' E., 5.70 chs.		
	N. 63°56' E., 2.00 chs.	At end of course.	
			Point used for determining Angle Point 37 on the medial line.
	N. 72°29' E., 11.50 chs.	At .40 chs., graded gravel road, bears N. 20° E. and S. 20° W.	
			Thence over partially dozed area, bears N. 20° E. and S. 20° W., through scattering salt cedar and medium undergrowth.
		At end of course.	
			Point used for determining Angle Point 38 on the medial line.
	N. 70°59' E., 8.85 chs.	At end of course.	
			Point used for determining Angle Point 39 on the medial line. This point is on the West end of a concrete lined bank.
			Thence along concrete lined banks, 12 to 20 ft. high.
	S. 65°26' E., 2.46 chs.		
	N. 76°47' E., 2.20 chs.	At end of course.	
			Point used for determining the point for Angle Point 40 on the medial line.
			From this point, U.S.C. & G.S. Triangulation Station, Granite Reef, bears N. 7°33' W., 0.635 chs. dist., monumented with a standard brass disk, 3½ ins. diam., set flush with concrete on Granite Reef Dam, mkd. GRANITE REEF 1935 1973 and a triangle.

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

from the triangulation station

Reference monument number
1, bears S. 43°51' E.,
0.812 chs. dist., monu-
mented with a standard
brass disk, 3½ ins.
diam., set flush with
the concrete of the dam
with the top mkd.
GRANITE REEF No. 1 1935
and an arrow pointing
to the triangulation
station.

Reference monument number
2, bears S. 19°53' W.,
0.715 chs. dist., monu-
mented with Bureau of
Reclamation Bench Mark
number 10, a brass tab-
let, 3 ins. diam., set
flush with the concrete
of the dam, top mkd. 10
ELEVATION ABOVE SEA
1325.16 FEET PHX DATUM.

The azimuth mark, Bureau
of Reclamation Bench
Mark number 6, bears
N. 14°15'57" W., monu-
mented with a brass
tablet, 3 ins. diam.,
set flush with the con-
crete of the spillway
on the North side of
the dam, top mkd. 6
ELEVATION ABOVE SEA
1325. PHX DATUM.
(Record calls this
point B.M. No. 9). No
dist. measured.

Thence along concrete walkway.

N. 85°55' E., 1.265 chs. At end of course.

Bureau of Reclamation Bench
Mark number 9, monumented with
a brass tablet, 3 ins. diam.,
set flush with the concrete,
with top mkd. 9 ELEVATION ABOVE
SEA 1325.24 FEET PHX DATUM.

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS		
		<p>This point is located at the NW edge of the Southern Canal outlet.</p>
		<p>Thence over the Southern Canal outlet on a concrete walkway.</p>
S. 83°01' E.,	.85 chs.	At end of course.
		<p>Bureau of Reclamation Bench Mark number 8, monumented with a brass tablet, 3 ins. diam., set flush with the concrete, with top mkd. 8 ELEVATION ABOVE SEA 1325.21 FEET PHX DATUM.</p>
		<p>This point is located at the SE edge of the Southern Canal outlet.</p>
		<p>Thence along a slanted dirt bank, 2 to 8 ft. high.</p>
N. 69°09' E.,	2.29 chs.	
N. 79°58' E.,	3.19 chs.	At end of course.
		<p>Thence through heavy gravel operations.</p>
N. 29°15' W.,	2.51 chs.	
N. 14°11' W.,	3.56 chs.	
N. 7°24' E.,	2.42 chs.	At end of course.
		<p>Point used for determining Angle Point 43 on the medial line.</p>
N. 73°41' E.,	3.63 chs.	At end of course.
		<p>Point used for determining Angle Point 44 on the medial line.</p>
		<p>Thence along a well defined cut bank, 2 to 5 ft. high, through medium mesquite and Salt cedar.</p>
S. 84°21' E.,	4.02 chs.	At end of course.
		<p>Point used for determining Angle Point 45 on the medial line.</p>

Traverse of the Left Bank of the Salt River through
T. 2 N., R. 6 E., Gila and Salt River Mer., Arizona

CHAINS

S. 87°44' E., 11.49 chs. At end of course.
Point used for determining
Angle Point 46 on the medial
line.

S. 87°25' E., 8.23 chs. At end of course.
Point used for determining
Angle Point 47 on the medial
line.

S. 84°27' E., 2.61 chs. At end of course.
Intersect the sec. line bet.
secs. 13 and 18 on the E.
bdy. of the Tp.

from which

The ¼ sec. cor. of secs.
13 and 18, on the E.
bdy. of the Tp.,
bears N. 2°37' E.,
7.57 chs. dist.;
described in the
field notes of the
concurrent survey of
T. 2 N., R. 7 E.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

The medial line (the South Boundary of the Salt River
Indian Reservation) as surveyed, is not a permanently
fixed boundary as its location is subject to movement
in order to accommodate to "the middle of (the Salt
River)," which is designated in the Executive Order of
June 14, 1879 as the south boundary of the reservation.

The South Boundary of the Salt River Indian Reservation
through T. 2 N., R. 6 E., was determined by use of the
informative traverse correlated with current aerial
photos of the right and left banks of the Salt River.
Considering the channels, their depth and nature and
the river changes, this is considered the best solu-
tion for placing the boundary in its intended position.
This survey is made running out the predetermined
courses and distances and refer to the true cardinal
directions.

At Angle Point No. 1 on the West bdy. of the Tp., at
the intersection of the medial line.

Set a railroad spike, flush with the pavement, with
top mkd.

SRIR
AP 1
S 25 | S 30
R 5 E R 6 E
T 2 N
1978

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

from which

The witness point of secs. 25 and 30 on the present
right bank of the N channel of the Salt River,
and on the W. bdy. of the Tp., bears N. 0°01' E.,
3.845 chs. dist.; heretofore described.

The witness point of secs. 25 and 30 on the present
left bank of the N channel of the Salt River,
and on the W. bdy. of the Tp., bears S. 0°01' W.,
3.845 chs. dist.; heretofore described.

The cor. is located near the center of Gilbert Road,
asphalt surfaced, bearing N and S.

Thence upstream, with the survey of the medial line of
the N channel of the Salt River, in sec. 30, by calcula-
ted courses and distances across the river bed, along
the South Boundary of the Salt River Indian Reservation.

Over nearly level, rocky river bottom.

N. 78°18' E., 14.93 chs. Point for Angle Point 2.

Set a re-bar, 4 ft. long,
5/8 in. diam., 34 ins. in
the ground, attach an alumi-
num cap mkd.

SRIR
AP 2
S 30
T 2 N R 6 E
1978

from which

The determining point
on the right bank,
bears N. 10°57' E.,
4.36 chs. dist.

The determining point
on the left bank,
bears S. 10°57' W.,
4.36 chs. dist.

N. 81°02' E., 8.80 chs. Point for Angle Point 3.

Set a re-bar, 4 ft. long,
5/8 in. diam., 3 ft. in
the ground, attach an alumi-
num cap mkd.

SRIR
AP 3
S 30
T 2 N R 6 E
1978

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

from which

The determining point
on the right bank,
bears N. 25°45' E.,
4.715 chs. dist.

The determining point
on the left bank,
bears S. 25°45' W.,
4.715 chs. dist.

S. 88°05' E., 12.465 chs. Point for Angle Point 4.

Set a re-bar, 4 ft. long,
5/8 in. diam., 36 ins. in
the ground, attach an alumi-
num cap mkd.

SRIR
AP 4
S 30
T 2 N R 6 E
1978

from which

The determining point
on the right bank,
bears N. 15°58' W.,
5.88 chs. dist.

The determining point
on the left bank,
bears S. 15°58' E.,
5.88 chs. dist.

S. 88°47' E., 12.37 chs. Point for Angle Point 5.

Set a re-bar, 4 ft. long,
5/8 in. diam., 34 ins. in
the ground, attach an alu-
minum cap mkd.

SRIR
AP 5
S 30
T 2 N R 6 E
1978

from which

The determining point
on the right bank,
bears N. 21°51' E.,
7.455 chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins.
long, 2½ ins. diam.,
set 24 ins. in the
ground for a refer-
ence monument, bears
N. 21°51' E., 7.727
chs. dist., with
brass cap mkd. T2N
R6E SRIR AP 5 S30
RM 510 FT. 1978 and
an arrow pointing to
the cor.

The determining point
on the left bank,
bears S. 21°51' W.,
7.455 chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground for a refer-
ence monument, bears
S. 21°51' W., 7.727
chs. dist., with
brass cap mkd. T2N
R6E AP 5 S30 RM 510
FT. 1978 and an arrow
pointing to the cor.

S. 83°03'30" E., 18.525 chs. Point for Angle Point 6.

Set a re-bar, 4 ft. long,
5/8 in. diam., 34 ins.
in the ground, attach an
aluminum cap mkd.

SRIR
AP 6

S 30
T 2 N R 6 E
1978

from which

The determining point
on the right bank,
bears N. 25°22' E.,
5.06 chs. dist.


The determining point
on the left bank,
bears S. 25°22' W.,
5.06 chs. dist.

S. 69°15' E., 14.94 chs. Intersect the sec. line
bet. secs. 29 and 30.
Point for Angle Point 7.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

Set a re-bar, 4 ft. long,
5/8 in. diam., 36 ins. in
the ground, attach an alu-
minum cap mkd.



from which


The determining point
on the right bank,
bears N. 0°15' W.,
3.815 chs. dist.

The determining point
on the left bank,
bears S. 0°15' E.,
3.815 chs. dist.

Thence in sec. 29.

S. 58°59' E., 6.83 chs. Point for Angle Point 8.

Set a re-bar, 4 ft. long,
5/8 in. diam., 34 ins. in
the ground, attach an alu-
minum cap mkd.




from which

The determining point
on the right bank,
bears N. 10°55' E.,
2.815 chs. dist.

The determining point
on the left bank,
bears S. 10°55' W.,
2.815 chs. dist.

S. 65°27'30" E., 20.795 chs. Point for Angle Point 9.

Set a re-bar, 4 ft. long,
5/8 in. diam., 36 ins. in
the ground, attach an
aluminum cap mkd.



Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

from which

The determining point
on the right bank,
bears N. 43°33' E.,
2.77 chs. dist.

The determining point
on the left bank,
bears S. 43°33' W.,
2.77 chs. dist.

S. 55°57'30" E., 20.355 chs. Point for Angle Point 10.

Set a re-bar, 4 ft. long,
5/8 in. diam., 36 ins. in
the ground, attach an alu-
minum cap mkd.

SRIR
~~AP 10~~
S 29
T 2 N R 6 E
1978

from which

The determining point
on the right bank,
bears N. 15°19' E.,
3.495 chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 24 ins. in the
ground for a refer-
ence monument, bears
N. 15°19' E., 3.652
chs. dist., with
brass cap mkd. T2N
R6E SRIR AP 10 S 29
RM 241 FT. 1978 and
an arrow pointing to
the cor.

The determining point
on the left bank,
bears S. 15°19' W.,
3.495 chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 24 ins. in the
ground for a reference
monument, bears
S. 15°19' W., 3.652
chs. dist., with
brass cap mkd. T2N
R6E AP 10 S29 RM 241
FT. 1978 and an arrow
pointing to the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

S. 59°09'30" E., 7.95 chs. Point for Angle Point 11.

Set a re-bar, 4 ft. long,
5/8 in. diam., 36 ins. in
the ground, attach an alu-
minum cap mkd.

SRIR
AP 11
S 29
T 2 N R 6 E
1978

from which

The determining point
on the right bank
of the N channel,
bears N. 15°36' E.,
5.59 chs. dist.

The determining point
on the left bank
of the S channel,
bears S. 3°55' E.,
5.59 chs. dist.

The determining point
at the junction of
the right bank of
the S channel and the
left bank of the N
channel, bears S.
79°22' W., 5.59 chs.
dist.

S. 87°30' E., 9.87 chs. Point for Angle Point 12.

Set a re-bar, 4 ft. long,
5/8 in. diam., 34 ins. in
the ground, attach an alu-
minum cap mkd.

SRIR
AP 12
S 29
T 2 N R 6 E
1978

from which

The determining point
on the right bank,
bears N. 20°30' W.,
4.99 chs. dist.

The determining point
on the left bank,
bears S. 20°30' E.,
4.99 chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

N. 80°02' E., 9.375 chs. Point for Angle Point 13.

Set a re-bar, 4 ft. long,
5/8 in. diam., 34 ins. in
the ground, attach an alu-
minum cap mkd.

SRIR
AP 13
— S 29
T 2 N R 6 E
1974

from which

The determining point
on the right bank,
bears N. 26°38' W.,
4.63 chs. dist.

The determining point
on the left bank,
bears S. 26°38' E.,
4.63 chs. dist.

N. 73°18' E., 12.455 chs. Intersect the sec. line
bet. secs. 28 and 29.
Point for the witness point
of secs. 28 and 29 on the
medial line.

Set a re-bar, 4 ft. long,
5/8 in. diam., 32 ins.
in the ground, attach an
aluminum cap mkd.

SRIR
W P
T 2 N R 6 E
S 29 | S 28
1974

from which

The determining point
the right bank, bears
N. 1°27' E., 7.61
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

The determining point
on the left bank,
bears S. 1°27' W.,
7.61 chs. dist.

Thence in sec. 28.

Along a rocky river bottom.

N. 89°47' E., 20.50 chs. Point for Angle Point 14.

Set a re-bar, 4 ft. long,
5/8 in. diam., 30 ins. in
the ground, attach an alu-
minum cap mkd.

SRIR
AP 14
S 28
T 2 N R 6 E
1974

from which

The determining point
on the right bank,
bears N. 22°46' W.,
11.29 chs. dist.

The determining point
on the left bank,
bears S. 22°46' E.,
11.29 chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

N. 74°10' E., 7.49 chs. Point for Angle Point 15.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 15
S 28
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 11°09' W., 12.72
chs. dist.

The determining point on
the left bank, bears
S. 11°09' E., 12.72
chs. dist.

N. 65°56' E., 8.415 chs. Point for Angle Point 16.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 16
S 28
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 31°31' W., 11.505
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground and in a col-
lar of stone, 2½ ft.
base to top, for a
reference monument,
bears N. 31°31' W.,
11.758 chs. dist.,
with brass cap mkd.
T2N R6E SRIR AP 16
S28 RM 776 FT. 1974
and an arrow pointing
to the cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

The determining point on
the left bank, bears
S. 31°31' E., 11.505
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 24 ins. in the
ground and in a col-
lar of stone, 3 ft.
base to top, for a
reference monument,
bears S. 31°31' E.,
11.758 chs. dist.,
with brass cap mkd.
T2N R6E AP 16 S28 RM
776 FT. 1974 and an
arrow pointing to the
cor.

N. 60°11' E., 22.77 chs.

Point for Angle Point 17.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 17
S 28
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 30°49' W., 13.215
chs. dist.

The determining point on
the left bank, bears
S. 30°49' E., 13.215
chs. dist.

N. 51°14'30" E., 8.975 chs. Point for Angle Point 18.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 18
S 28
T 2 N R 6 E
1974

from which

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

The determining point on
the right bank, bears
N. 42°29' W., 13.21
chs. dist.

The determining point on
the left bank, bears
S. 42°29' E., 13.21
chs. dist.

N. 24°07'30" E., 8.48 chs. Point for Angle Point 19.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 19
S 28
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 50°58' W., 9.46
chs. dist.

The determining point on
the left bank, bears
S. 50°58' E., 9.46
chs. dist.

N. 33°16' E., 7.045 chs. Point for Angle Point 20.

Set a re-bar, 4 ft. long, 5/8
in. diam., 18 ins. in the
ground and in a mound of
stone, 3 ft. base, 1½ ft.
high, attach an aluminum cap
mkd.


SRIR
AP 20
S 28
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 49°33' W., 9.31
chs. dist.

The determining point on
the left bank, bears
S. 49°33' E., 9.31
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>N. 66°20'30" E., 11.835 chs.</p>	<p>Intersect the sec. line bet. secs. 27 and 28. Point for the witness point of secs. 27 and 28 on the medial line</p> <p>Set a re-bar, 4 ft. long, 5/8 in. diam., 30 ins. in the ground, attach an aluminum cap mkd.</p> <p style="text-align: center;">SRIR W P T 2 N R 6 E S 28 S 27 1974</p> <p>from which</p> <p>The determining point on the right bank, bears N. 1°00' E., 7.55 chs. dist.</p> <p>The determining point on the left bank, bears S. 1°00' W., 7.55 chs. dist.</p>
	<p>Thence in sec. 27.</p> <p>Over sandy gravelly river bed.</p> <p>N. 30°26' E., 4.48 chs.</p>	<p>Point for Angle Point 21.</p> <p>Set a re-bar, 4 ft. long, 5/8 in. diam., 30 ins. in the ground, attach an aluminum cap mkd.</p> <p style="text-align: center;">SRIR AP 21  S 27 T 2 N R 6 E 1974</p> <p>from which</p> <p>The determining point on the right bank, bears N. 30°09' W., 4.255 chs. dist.</p> <p>The determining point on the left bank, bears S. 30°09' E., 4.255 chs. dist.</p>
	<p>N. 68°02' E., 9.92 chs.</p>	<p>Intersect the sec. line bet. secs. 22 and 27. Point for the witness point of secs. 22 and 27 on the medial line.</p>

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
W P
T 2 N R 6 E
S 22
S 27
1974

from which

The determining point on
the right bank, bears
S. 89°52' W., 11.345
chs. dist.

The determining point on
the left bank, bears
N. 89°52' E., 11.345
chs. dist.

Thence in sec. 22.

Over sandy gravelly river bed.

N. 58°43' E., 23.19 chs. Point for Angle Point 22.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 22
S 22
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 30°25' W., 5.425
chs. dist.

The determining point on
the left bank, bears
S. 30°25' E., 5.425
chs. dist.

N. 78°33' E., 10.48 chs. Point for Angle Point 23.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

SRIR
AP 23
S 22
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 17°25' W., 8.83
chs. dist.

The determining point on
the left bank, bears
S. 17°25' E., 8.83
chs. dist.

N. 54°54' E., 11.14 chs. Point for Angle Point 24.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 24
S 22
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 27°19' W., 9.06
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 24 ins. in the
ground for a reference
monument, bears N. 27°
19' W., 9.578 chs.
dist., with brass cap
mkd. T2N R6E SRIR
AP 24 S22 RM 632 FT.
1974 and an arrow
pointing to the cor.

The determining point on
the left bank, bears
S. 27°19' E., 9.06
chs. dist.


An iron post, 28 ins.
long, 2½ ins. diam.,
set 24 ins. in the
ground for a reference
monument, bears S. 27°
19' E., 9.578 chs.
dist., with brass cap
mkd. T2N R6E AP 24 S22
RM 632 FT. 1974 and an
arrow pointing to the
cor.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

N. $56^{\circ}22'$ E., 10.09 chs. Point for Angle Point 25.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.



SRIR
AP 25
S 22
T 2 N R 6 E
1974


from which

The determining point on
the right bank, bears
N. $31^{\circ}40'$ W., 7.095
chs. dist.

The determining point on
the left bank, bears
S. $31^{\circ}40'$ E., 7.095
chs. dist.

N. $46^{\circ}58'$ E., 8.43 chs. Point for Angle Point 26.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.



SRIR
AP 26
S 22
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. $48^{\circ}03'$ W., 6.405
chs. dist.

The determining point on
the left bank, bears
S. $48^{\circ}03'$ E., 6.405
chs. dist.

N. $40^{\circ}10'$ E., 3.51 chs. Point for Angle Point 27.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

SRIR
AP 27
S 22
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 54°27' W., 6.94
chs. dist.

The determining point on
the left bank, bears
S. 54°27' E., 6.94
chs. dist.

N. 52°01' E., 16.13 chs.

Intersect the sec. line bet.
secs. 22 and 23.

Point for the witness point of
secs. 22 and 23 on the medial
line.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
W P
T 2 N R 6 E
S 22 | S 23
1974

from which

The determining point on
the right bank, bears
N. 0°14' E., 8.555
chs. dist.

The 1/4 sec. cor. of secs.
22 and 23, bears S.
0°14' W., 4.505 chs.
dist.; heretofore
described.

The determining point on
the left bank, bears
S. 0°14' W., 4.505
chs. dist., thence
S. 1°07' W., 4.05 chs.
dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

Thence in sec. 23.

Over rocky river bed.

N. $52^{\circ}36'$ E., 13.145 chs. Point for Angle Point 28.

Set a re-bar, 4 ft. long, $5/8$
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 28
S 23
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. $6^{\circ}36'$ W., 7.78
chs. dist.

The determining point on
the left bank, bears
S. $6^{\circ}36'$ E., 7.78
chs. dist.

N. $64^{\circ}47'30''$ E., 10.94 chs. Point for Angle Point 29.

Set a re-bar, 4 ft. long, $5/8$
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 29
S 23
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. $12^{\circ}49'$ W., 7.14
chs. dist.

The determining point on
the left bank, bears
S. $12^{\circ}49'$ E., 7.14
chs. dist.

N. $34^{\circ}23'$ E., 2.695 chs. Point for Angle Point 30.

Set a re-bar, 4 ft. long, $5/8$
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

SRIR
AP 30
S 23
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 16°06' W., 5.085
chs. dist.

The determining point on
the left bank, bears
S. 16°06' E., 5.085
chs. dist.

N. 66°07' E., 15.49 chs. Point for Angle Point 31.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 31
S 23
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 32°25' W., 4.90
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground and in a collar
of stone, 2½ ft. base
to top, for a refer-
ence monument, bears
N. 32°25' W., 5.896
chs. dist., with brass
cap mkd. T2N R6E SRIR
AP 31 S23 RM 389 FT.
1974 and an arrow
pointing to the cor.

The determining point on
the left bank, bears
S. 32°25' E., 4.90
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins.
long, 2½ ins. diam.,
set 10 ins. in the
ground and in a mound
of stone, 3 ft. base
to top, for a refer-
ence monument, bears
S. 32°25' E., 5.896
chs. dist., with brass
cap mkd. T2N R6E AP 31
S23 RM 389 FT. 1974
and an arrow pointing
to the cor.

N. 46°56' E., 7.02 chs.

Point for Angle Point 32.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 32
S 23
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 25°17' W., 4.48
chs. dist.

The determining point on
the left bank, bears
S. 25°17' E., 4.48
chs. dist.

N. 57°07' E., 13.65 chs.

Point for Angle Point 33.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 33
S 23
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 55°41' W., 3.62
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

The determining point on
the left bank, bears
S. 55°41' E., 3.62
chs. dist.

N. 79°57' E., 11.575 chs. Intersect the sec. line bet.
secs. 14 and 23. Point for
the witness point of secs. 14
and 23 is under water; not
monumented.

From this point, the determin-
ing point on the right bank,
bears N. 89°53' W., 13.11 chs.
dist., thence West 1.28 chs.
dist.

From this point, the determin-
ing point on the left bank,
bears S. 89°53' E., 14.39 chs.
dist.


From this point, the point for
the meander cor. of secs. 14
and 23, on the right bank at
the time of the 1911 survey,
bears N. 89°53' W., 13.11 chs.
dist.

Thence in sec. 14.

Over river bottom through ponded water extending approx.
4 chs.

N. 68°51' E., 8.61 chs. Point for Angle Point 34.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.



from which

The determining point on
the right bank, bears
N. 18°03' W., 8.19
chs. dist.

The determining point on
the left bank, bears
S. 18°03' E., 8.19
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

N. 56°47' E., 8.74 chs. Intersect the sec. line bet.
secs. 13 and 14. Point for
the witness point of secs. 13
and 14, on the medial line.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
W P
T 2 N R 6 E
S 14 | S 13
1974

from which

The determining point on
the right bank, bears
N. 1°43' E., 7.305
chs. dist.

The determining point on
the left bank, bears
S. 1°43' W., 7.305
chs. dist.

Thence in sec. 13.

Over sandy rocky land, through scattering cottonwoods and
salt cedar.

N. 68°10' E., 6.10 chs. Point for Angle Point 35.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 35
S 13
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 21°49' W., 5.79
chs. dist.

The determining point on
the left bank, bears
S. 21°49' E., 5.79
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

N. 59°50' E., 7.08 chs. Point for Angle Point 36.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 36
S 13
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 28°47' W., 3.22
chs. dist.

The determining point on
the left bank, bears
S. 28°47' E., 3.22
chs. dist.

N. 33°45' E., 12.02 chs. Point for Angle Point 37.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 37
S 13
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 21°53' W., 6.44
chs. dist.

The determining point on
the left bank, bears
S. 21°53' E., 6.44
chs. dist.

N. 66°32' E., 12.43 chs. At 3.40 chs. dist., graded
gravel road, bears S. 5° E.
and N. 5° W.

At end of course.

Point for Angle Point 38.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 38

S 13
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 14°45' W., 7.74
chs. dist.

The determining point on
the left bank, bears
S. 14°45' E., 7.74
chs. dist.

N. 71°01' E., 8.87 chs.

Point for Angle Point 39.

Set a re-bar, 4 ft. long, 5/8
in. diam., 30 ins. in the
ground, attach an aluminum
cap mkd.

SRIR
AP 39

S 13
T 2 N R 6 E
1974

from which

The determining point on
the right bank, bears
N. 14°34' W., 7.74
chs. dist.

The determining point on
the left bank, bears
S. 14°34' E., 7.74
chs. dist.

N. 84°55' E., 5.21 chs.

Point for Angle Point 40 is
in the middle of Granite
Reef Dam. Water is seeping
over the top of the dam
making it impossible to
monument the cor. position.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>The determining point on the right edge of the dam, bears N. 7°33' W., 8.55 chs. dist.</p> <p>The determining point on the left edge of the dam, bears S. 7°33' E., 8.55 chs. dist.</p> <p>Thence over flowing water within the Salt River. Cors. on the medial line fall in the flowing waters of the Salt River and were not monumented.</p>	
N. 82°27' E., 3.39 chs.	<p>Point for Angle Point 41, on a line normal with the dam and at half the departure bet. Angle Point 40 and the determining point on the left bank.</p> <p>from which</p> <p>The determining point on the left bank, identical with the point used to determine Angle Point 43, bears N. 81°55' E., 3.39 chs. dist.</p> <p>U.S.C. & G.S. triangulation station, Granite Reef, bears S. 15°39' W., 8.61 chs. dist.; heretofore described.</p> <p>Thence on a line parallel to the dam.</p>	
N. 7°33' W., 4.20 chs.	<p>Point for Angle Point 42, at the intersection of a line normal to the dam, calculated to intersect Angle Point 43.</p> <p>from which</p> <p>Bureau of Reclamation bench mark number 1, bears N. 19°14' W., 4.51 chs. dist.; heretofore described.</p>	

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

N. 82°27' E., 2.25 chs. Point for Angle Point 43.

from which

The determining point on
the right bank, bears
N. 22°50' W., 4.32
chs. dist.

The determining point on
the left bank, bears
S. 22°50' E., 4.32
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground for a refer-
ence monument, bears
S. 22°50' E., 4.471
chs. dist., with
brass cap mkd. T2N
R6E AP 43 S13 RM
295.1 FT. 1974 and an
arrow pointing to the
cor. pt.

S. 88°08' E., 5.01 chs. Point for Angle Point 44.

from which

The determining point on
the right bank, bears
N. 3°08' W., 2.80
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground for a refer-
ence monument, bears
N. 3°08' W., 2.972
chs. dist., with brass
cap mkd. T2N R6E SRIR
AP 44 S13 RM 196.1 FT.
1974 and an arrow
pointing to the cor.
pt.

from the reference monu-
ment

A mesquite, 8 ins.
diam., bears N.
78° E., 17 lks.
dist., mkd. RM S13
BT.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

The determining point on
the left bank, bears
S. 3°08' E., 2.80 chs.
dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 20 ins. in the
ground for a refer-
ence monument, bears
S. 3°08' E., 2.922 chs.
dist., with brass cap
mkd. T2N R6E AP 44 S13
RM 192.9 FT. 1974 and
an arrow pointing to
the cor. pt.

S. 87°58' E., 5.46 chs. Point for Angle Point 45.

from which

The determining point on
the right bank, bears
N. 23°30' E., 3.27
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 20 ins. in the
ground, with glass
deposited at the base,
for a reference monu-
ment, bears N. 23°30'
E., 3.472 chs. dist.,
with brass cap mkd.
T2N R6E SRIR AP 45 S13
RM 229.2 FT. 1974 and
an arrow pointing to
the cor. pt.

from the reference monu-
ment

A concrete post, 8 ins.
diam., projecting
1 in. above the
ground, mkd. 04 on
top, bears N. 11½°
E., 32 lks. dist.

A mesquite, 8 ins.
diam., bears N.
38° E., 17 lks.
dist., mkd. RM S13
BT.

The determining point on
the left bank, bears
S. 23°30' W., 3.27
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground and in a collar
of stone, 2½ ft. base
to top, for a refer-
ence monument, bears
S. 23°30' W., 3.422
chs. dist., with brass
cap mkd. T2N R6E AP 45
S13 RM 225.9 FT. 1974
and an arrow pointing
to the cor. pt.

S. 84°40' E., 10.25 chs. Point for Angle Point 46.

from which

The determining point on
the right bank, bears
N. 0°47' E., 2.50 chs.
dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground for a refer-
ence monument, bears
N. 0°47' E., 2.903
chs. dist., with brass
cap mkd. T2N R6E SRIR
AP 46 S13 RM 191.6 FT.
1974 and an arrow
pointing to the cor.
pt.

from the reference monu-
ment

A mesquite, 5 ins.
diam., bears N.
21½° E., 43 lks.
dist., mkd. RM S13
BT.

A mesquite, 10 ins.
diam., bears N.
71½° W., 50.5 lks.
dist., mkd. RM S13
BT.

The determining point on
the left bank, bears
S. 0°47' W., 2.50 chs.
dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground, for a refer-
ence monument, bears S.
0°47' W., 2.804 chs.
dist., with brass cap
mkd. T2N R6E AP 46 S13
RM 185.1 FT. 1974 and
an arrow pointing to
the cor. pt.

S. 87°22' E., 7.55 chs. Point for Angle Point 47.

from which

The determining point on
the right bank, bears
N. 14°27' W., 2.61
chs. dist.

An iron post, 28 ins.
long, 2½ ins. diam.,
set 22 ins. in the
ground for a refer-
ence monument, bears
N. 14°27' W., 2.882
chs. dist., with brass
cap mkd. T2N R6E SRIR
AP 47 S13 RM 190.2 FT.
1974 and an arrow
pointing to the cor.
pt.

from the reference monu-
ment

A mesquite, 5 ins.
diam., bears S. 31°
E., 14.5 lks. dist.,
mkd. RM S13 BT.

A mesquite, 5 ins.
diam., bears S. 77°
W., 7 lks. dist.,
mkd. RM S13 BT.

The determining point on
the left bank, bears
S. 14°27' E., 2.61
chs. dist.

Survey of the South Boundary of the Salt River Indian
Reservation through Township 2 North, Range 6 East,
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins.
long, 2½ ins. diam.,
set 20 ins. in the
ground for a refer-
ence monument, bears
S. 14°27' E., 2.711
chs. dist., with brass
cap mkd. T2N R6E AP 47
S13 RM 178.9 FT. 1974
and an arrow pointing
to the cor. pt.

from the reference monument

A cottonwood, 32 ins.
diam., bears S. 80° E.,
11 lks. dist., mkd.
RM S13 BT.

N. 88°08' E., 3.38 chs. Intersect the sec. line bet.
secs. 13 and 18, Tp. 2 N.,
Rs. 6 and 7 E. Point for the
witness point on the medial
line.

from which

The right bank, bears
N. 2°37' E., 3.22 chs.
dist.

The ¼ sec. cor. of secs.
13 and 18, Tp. 2 N.,
Rs. 6 and 7 E., bears
N. 2°37' E., 4.67 chs.
dist., described in the
field notes of the
concurrent survey of
T. 2 N., R. 7 E.

The left bank, bears
S. 2°37' W., 2.90 chs.
dist.

GENERAL DESCRIPTION

A variety of land and soil are found in the area sur-
veyed in T. 2 N., R. 6 E., Gila and Salt River Meridian,
Arizona. The SE portion of the area surveyed varies
from gently rolling land to low rolling hills to granite
peaks. The remainder of the Tp. surveyed is gently
rolling to nearly level. The elevation varies from
about 1250 ft. above sea level in sec. 30 to 1737 ft.
above sea level in sec. 24. The soil is mostly sandy
gravel loam and rocky except for portions in the SW
part of the Tp., which is a sandy clay loam under cul-
tivation. Palo-verde is found throughout most of the
Tp., with salt cedar, mesquite, cottonwoods, and iron
wood predominant in the vicinity of Granite Reef Dam.
Undergrowth consists of creosote bush, cacti, weeds and
grass.

General Description, Township 2 North, Range 6 East,
Gila and Salt River Mer., Arizona

CHAINS

The Salt River, the center of which is the south boundary of the Salt River Indian Reservation, enters the Tp. a few chains S of the $\frac{1}{4}$ sec. cor. of secs. 13 and 18 on the E. bdy. of the Tp., meanders SW leaving the Tp. through sec. 30. The Salt River, downstream from Granite Reef Dam located in sec. 13, is dry except for periods of heavy storms or high run off, at which time water is released from Granite Reef Dam, causing considerable flooding. Above Granite Reef Dam there is a continual flow of water which the Dam diverts into the Southern Canal which runs in a southwesterly direction leaving the Tp. near the $\frac{1}{4}$ sec. cor. of sec. 31, and into the Arizona Canal which runs westerly through the Tp. leaving through sec. 19.

There are citrus groves located along the southern portions of secs. 28, 29 and 30, with recent mining evident in sec. 24. The remainder of the Tp. surveyed under this group, is unimproved, except for the numerous roads which provide easy access to most of the area.

Along the dry channel of the Salt River, monumentation consisted of $\frac{5}{8}$ in. re-bars instead of regulation iron posts. We felt the re-bars would provide adequate monumentation and withstand the flood waters better than regulation monuments.

The mean of several observations of the magnetic declination throughout the township is 14° E. with very little local attraction.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT



FIELD ASSISTANTS

NAMES	CAPACITY
Paul L. Reeves	Surveying Technician
Rex D. Krusell	Survey Aid
George T. Cummings	Survey Aid
Douglas R. Lenhares	Survey Aid
David G. Oltman	Survey Aid

CERTIFICATE OF SURVEY

(X) (We), Paul G. Bauer and Harry K. Smith, HEREBY
 CERTIFY upon honor that, in pursuance of ^{supplemental} special instructions bearing date of the 15th day
 of January, 1974, (X) (We) have made a dependent resurvey of a por-
 tion of the west boundary and subdivisional lines, a completion survey
 of the subdivisional lines, an informational traverse of the present
 right and left banks of the Salt River and a survey of the South
 Boundary of the Salt River Indian Reservation, Township 2 North, Range
 6 East

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (X) (us) and under (X) (our)
 direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

<u>December 9, 1974</u> (Date)	 (Cadastral Surveyor)
<u>December 9, 1974</u> (Date)	 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the resurvey of a portion of the west boundary and
 subdivisional lines, survey completing the subdivisional lines,
 informational traverse of the present right and left banks of the Salt
 River and the survey of the South Boundary of the Salt River Indian
 Reservation, T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona

executed by Paul G. Bauer and Harry K. Smith
 having been critically examined and found correct, are hereby approved.

_____ (Date)	_____ (Chief, Division of Cadastral Survey)
-----------------	--

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

_____ (Date)	_____ (Chief, Division of Cadastral Survey)
-----------------	--

CERTIFICATE OF SURVEY

(I) (~~We~~), Harry K. Smith, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 12th day of December, 1977, (I) (~~We~~) have surveyed the south boundary of the Salt River Indian Reservation along the medial line of the abandoned north channel fo the Salt River in sections 29 and 30, T. 2 N., R. 6 E.,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

June 14, 1978

 (Date)

Harry K. Smith

 (Cadastral Surveyor)

 (Date)

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the west boundary and subdivisional lines, survey of a portion of the subdivisional lines completing the subdivision, an informational traverse of the present right and left banks of the Salt River and the survey of the medial line (South Boundary of the Salt River Indian Reservation) in T. 2 N., R. 6 E., Gila and Salt River Meridian, Arizona.

executed by Paul G. Bauer and Harry K. Smith, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

JUL 25 1978

 (Date)

Bernard W. Fisher

 (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 2 N., R. 6 E., G&SRM., Arizona, is a true copy of the original field notes.

 (Date)

 (Chief, Division of Cadastral Survey)