

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

 Dependent Resurvey

 of a Portion of the East Boundary

 and a

 Survey of a Portion of the East Boundary

 Township 26 North, Range 30 East

 and a

 Survey of the Boundaries and Subdivision Lines of Section 7

 Township 26 North, Range 31 East

Of the Gila and Salt River Meridian,
 In the State of Arizona

EXECUTED BY

Paul L. Reeves Cadastral Surveyor

Under special instructions dated April 21, 19 78, approved April 21, 1978,

_____, which provided for the surveys included under ~~U.S. Survey~~ Group
 Number 604, and assignment instructions dated April 21, 19 78.

Survey commenced April 25, 19 78

Survey completed May 4, 19 78

1A

BOOK 5067

INDEX DIAGRAM

Township 26 North, Range 31 East,

	6	5	4	3	2	1
	12					
	7 11	8	9	10	11	12
	10					
7	18	17	16	15	14	13
5	19	20	21	22	23	24
4	30	29	28	27	26	25
3	31	32	33	34	35	36
1						

Subdivision of sec. 7: pages 12-13.

Township 26 North, Range 31 East,
Gila and Salt River Meridian, Arizona

CHAINS

The east boundary of T. 26 N., R. 31 E. is coincident with a portion of the western boundary of the state of New Mexico which was surveyed by Chandler Robbins, U.S. Astronomer and surveyor in 1875. The south four miles of the west boundary were surveyed by James A. Lamport, U.S. Deputy Surveyor, in 1900. The southwest township corner was remonumented and a closing corner for Tps. 25 N., Rs. 30 and 31 E., was established on the south boundary of sec. 31, T. 26 N., R. 31 E. by Sidney E. Blout, U.S. Cadastral Engineer, in 1927. In 1884-85, John G. Evans, U.S. Deputy Surveyor, surveyed the then south boundary of the Navajo Indian Reservation through Range 31 East. This boundary is now abandoned.

The following field notes are those of a dependent resurvey of a portion of the E. bdy. and a survey of a portion of the E. bdy., T. 26 N., R. 30 E., and a survey of the boundaries and subdivision lines of section 7, T. 26 N., R. 31 E., Gila and Salt River Meridian., Ariz.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 604, Arizona dated April 21, 1978.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast cor. of Township 26 North, Range 30 East, as scaled from the U.S. Geological Survey Quadrangle Map, "Hunters Point, Ariz.-N.Mex.," prepared in 1971, is as follows

Latitude 35°36.3' N. Longitude 109°04.9' W.

The mean magnetic declination is 13°30' E.

Dependent Resurvey of a Portion of the East Boundary,
T. 26 N., R. 30 E., Gila and Salt River Mer., Ariz.

(Restoring the survey executed by James A. Lamport
in 1900.)

Note: This boundary was found to be out of limits northerly from the south mile. A separate set of corners was therefore established to control the subdivision of T. 26 N., R. 31 E.

Beginning at the cor. of secs. 31 and 36, T. 26 N., Rs. 30 and 31 E. only, monumented with an iron post 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the E. Bdy.
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

T26N
R30E | R31E
S36 | S31

T25N R30E
S1

1927

From this point the cor. of secs. 1 and 6, T. 25 N.,
Rs. 30 and 31 E. only, bears S. 89°36'30" E., 2.93 chs.
dist., monumented with an iron post, 3 ins. diam.,
projecting 8 ins. above the ground, with brass cap mkd.

T26N R30E S31
S1 | S6
R30E | R31E
T25N

1927

Remark the brass cap to read

T26N R31E S31
S1 | S6
R30E | R31E
T25N

1978

1927

North, along the E. bdy. of sec. 36, T. 26 N., R. 30 E.

Over rolling land, through scattered cedar pinyon and
sage brush.

24.20 Track road, bears N. 50° E., curving northerly and
S. 50° W., curving southerly.

24.80 Fence line, bears N. 15° E. and S. 15° W., 15 lks.
thence SW.

39.85 The 1/4 sec. cor. originally set for secs. 31 and 36,
monumented with a sand stone, 14x12x3 ins. firmly set
projecting 8 ins. above the ground mkd. 1/4 on the E.
face.

This cor. now functions as the 1/4 sec. cor. of sec.
36, T. 26 N., R. 30 E., only.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, with brass cap mkd.

T26N
R30E | R31E
1/4 |
S36 |

1978

Deposit the mkd. stone alongside the iron post.
Raise a mound of stone, 2 ft. base, 1 1/2 ft.
high, W. of cor.

Dependent Resurvey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>North, beginning new measurement.</p>
.15	<p>Point for the 1/4 sec. cor. of sec. 31 T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap. mkd.</p>
	<div style="text-align: center;"> <p>T26N R30E R31E 1/4 S31</p> <p>1978</p> </div>
	<p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E. of the cor.</p>
15.65	<p>Fence line, bears S. 65° E. and N. 65° W.</p>
26.45	<p>Graded road, bears E. and W.</p>
26.55	<p>Telephone line, bears S. 85° E. and N. 85° W.</p>
39.35	<p>Track road, bears N. 50° E. and S. 50° W.</p>
40.15	<p>Point for the cor. of secs. 30 and 31, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T26N R30E R31E S30 S36 ——— S31</p> <p>1978</p> </div> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, E. of cor.</p>
40.37	<p>Point for the cor. originally set for secs. 25, 30, 31 and 36, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>This cor. now functions as the cor. of secs. 25 and 36, T. 26 N., R. 30 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S25 ——— S30 S36</p> <p>1978</p> </div> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>

Dependent Resurvey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
39.78	<p>North, along the E. bdy. of sec. 25 T. 26 N., R. 30 E. Over gently rolling land, through sage brush.</p> <p>Point for the 1/4 sec. cor. of sec. 30, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E 1/4 S30</p> <p>1978</p> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.</p>
39.85	<p>Track road, bears E. and W.</p>
40.37	<p>Point for the 1/4 sec. cor. originally set for secs. 25 and 30, at proportionate dist., there is no re- maining evidence of the original cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 25, T. 26 N., R. 30 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E 1/4 S25</p> <p>1978</p> </div> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Fence cor. bears S. 86°51' E. 109 lks. dist., fences extend N. and W.</p>
79.78	<p>Point for the cor. of secs. 19 and 30, T.26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S19 S25 S30</p> <p>1978</p> </div>

Dependent Resurvey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS		
80.74	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, E. of cor.</p> <p>The cor. originally set for secs. 19, 24, 25, and 30, monumented with a sandstone 18x10x6 ins. firmly set projecting 9 ins. above the ground mkd. with 2 notches on S. face and 4 notches on N. face, with local reinforcement rod 1/2 in. diam., 18 ins. long, alongside the mkd. stone.</p> <p>This cor. now functions as the cor. of secs. 24 and 25, T. 26 N., R. 30 E., only.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S24 — S19 S25 </p> <p>1978</p> </div> <p>Deposit the mkd. stone and reinforcement rod alongside the cor.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	
39.90	<p>N. 0°39' E., along the E. bdy. of sec. 24, T. 26 N., R. 30 E.</p> <p>Over gently rolling land, through sage brush.</p> <p>1.50 Wash, 3 chs. wide, 10 ft. deep, drains SE.</p> <p>6.90 Powerline, bears N. 85° E. and S. 85° W.</p> <p>9.10 Chain link fence around Sewage Disposal Pond, bears S. 85° E. and N. 85° W.</p> <p>38.30 Chain link fence around Sewage Disposal Pond, bears N. 37° E. and S. 37° W.</p> <p>39.04 Point for the 1/4 sec. cor. of sec. 19, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E 1/4 S19</p> <p>1978</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Point for the 1/4 sec. cor. originally set for secs. 19 and 24, at proportionate dist., there is no remaining evidence of the original cor.</p>	

Dependent Resurvey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS

This cor. now functions as the 1/4 sec. cor. of sec. 24,
T. 26 N., R. 30 E., only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam.,
21 ins. in the ground with brass cap mkd.

T26N
R30E | R31E
1/4
S24

1978

Raise a mound of stone, 2 ft. base, 1 ft. high, W.
of cor.

Cor. is located 2 chs. E. of center of a wash 2 chs.
wide, 12 ft. deep, drains S. 35° W.

79.04

Point for the cor. of secs. 18 and 19, T. 26 N.,
R. 31 E., only.

Set an iron post, 28 ins. long, 2 1/2 ins diam., 21 ins.
in the ground, with brass cap mkd.

T26N
R30E | R31E
S18
S24 —
S19

1978

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,
E. of cor.

Cor. is located on W. edge of a dirt dike around
abandoned Sewage Disposal Pond, dike, bears S. 10° E.
and N. 10° W.

79.80

Point for the cor. originally set for secs. 13, 18, 19
and 24, determined from ties obtained from the Navajo
control system, from which:

A brass cap 3 ins. diam., set in a 6 in. diam.
concrete cylinder, 6 ins. below surface of
ground, bears S. 51°59' W., 60.54 chs. dist.,
mkd.

WR 22
9.18
+
1959

A brass cap 3 ins. diam., set in a 6 in. diam., concrete
cylinder, flush with ground, bears N. 73°16' W.,
70.57 chs. dist., mkd.

WR 23
9.86
+
1959

This position is accepted as the best available evidence
of the original corner position.

Dependent Resurvey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>This cor. now functions as the cor. of sec. 13 and 24, T. 26 N., R. 30 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., flush with surface of a dirt dike around an abandoned Sewage Disposal Pond, bears S. 10° E. and N. 10° W., with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S13 ----- S18 S24 </p> <p>1978</p> </div>
39.24	<p>N. 0°24' E., along the E. bdy. of sec. 13, T. 26 N. R. 31 E.</p> <p>Over gently rolling land, through sage brush.</p> <p>Point for the 1/4 sec. cor. of sec. 18, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E 1/4 S18</p> <p>1978</p> </div>
40.09	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E. of cor.</p> <p>The 1/4 sec. cor. originally set for secs. 13 and 18, monumented with a sandstone 20x20x4 ins. firmly set projecting 6 ins. above the ground, mkd. 18 on E. face and 13 on W. face, with mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>This cor. now functions as the 1/4 sec. cor. of sec. 13, T. 26 N., R. 30 E., only.</p> <p>At the cor point</p> <p>Set an iron post, 28 ins. long, 2 1/2 diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E 1/4 S13 </p> <p>1978</p> </div> <p>Deposit the mkd. stone alongside the iron post. Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of cor.</p>
14.60	<p>N. 0°52' W., beginning new measurement.</p>
16.30	<p>Fence and powerline, bears N. 75° E. and S. 75° W.</p> <p>Highway No. 264, bears N. 75° E. and S. 75° W.</p>

Dependent Resurvey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS		
18.80	Fence line, bears N. 75° E. and S. 75° W.	
20.00	Telephone line, bears N. 75° E. and S. 75° W.	
36.50	<p>Intersect the abandoned south boundary of the Navajo Indian Reservation.</p> <p>Point for the closing cor. originally set for secs. 13 and 18. This position was determined at record distance in latitude from the 1/4 sec. cor. of sec. 13, only, and at record distance in longitude from the closing cor. of secs. 13 and 14, T. 26 N., R. 31 E., established by James P. Lamport, U.S. Deputy Surveyor in 1900, on the abandoned south boundary of the Navajo Indian Reservation. Retracement along the abandoned boundary failed to locate any of the original monuments established by John G. Evans, U.S. Deputy Surveyor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S12 — S18 S13 cc</p> <p>1978</p> </div> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, S. of cor.</p> <p>From this point the closing cor. of secs. 13 and 14, T. 26 N., R. 30 E., on the abandoned south bdy. of the Navajo Indian Reservation, heretofore mentioned, bears S. 89°52' W., 80.00 chs. dist. monumented with a local iron pipe 1 in. diam., 2 ft. below surface of ground, with cap attached and mkd. Perce Engr. LS 2615. This is accepted as the best available evidence of the original cor. position.</p> <p>From this same point the 1/4 sec. cor. of sec. 13, T. 26 N., R. 30 E., bears N. 89°28' W., 40.12 chs. dist., monumented with a local iron pipe 1 in. diam., projecting 14 ins. above the ground, with cap attached and mkd. Perce Engr. TCG No. 2 LS 2615, with a sandstone, 30x10x8 ins. lying loose alongside local cor. mkd. 1/4.</p> <p>Note: James A. Lamport, U.S. Deputy Surveyor, retraced the north boundary of sec. 13 in 1900 and established the 1/4 sec. cor.; however, the pages in the field notes pertaining to this retracement were crossed out prior to their official approval.</p>	
	<p>Survey of a Portion of the East Boundary, T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona</p>	
	<p>North, along the E. bdy. of sec. 12.</p>	
	<p>Over gently rolling land, through medium undergrowth.</p>	
.21	Fence line, bears N. 80° E. and S. 80° W.	

Survey of a Portion of the E. Boundary,
T. 26 N., R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS		
2.65	<p>Point for the cor. of secs. 7 and 18, T. 26 N., R. 31 E., 40.00 chs. in Latitude from the established 1/4 sec. cor. of sec. 18, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<pre> T26N R30E R31E S7 S12 — S18 1978 </pre>	
40.00	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E. of cor.</p> <p>Point for the 1/4 sec. cor. of sec. 12, T. 26 N., R. 30 E.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<pre> T26N R30E R31E 1/4 S12 1978 </pre>	
42.65	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 60 lks. W. of a N. and S. fence line,</p> <p>Point for the 1/4 sec. cor. of sec. 7, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<pre> T26N R30E R31E 1/4 S7 1978 </pre>	
47.80	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E. of cor.</p> <p>Cor. is located 60 lks. W. of a N and S fenceline.</p> <p>Powerline, bears N. 78° E. and S. 78° W.</p>	
80.00	<p>Point for the cor. of sec. 1 and 12, T. 26 N., R. 30 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<pre> T26N R30E R31E S1 — S7 S12 1978 </pre>	
	<p>Deposit broken glass at base of iron post.</p>	

Survey of a Portion of the East Boundary,
T. 26 N. R. 30 E., Gila and Salt River Meridian, Arizona

CHAINS		
2.65	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Fence cor. bears N. 32°44' E., 83 lks. dist.; fences extend N., S. and W.</p> <p>Land, level Soil, sandy loam Timber, none Undergrowth, sage and rabbit brush</p> <hr/> <p>North, along the E. bdy. of sec. 1, T. 26 N., R. 30 E.,</p> <p>Over nearly level land, through medium undergrowth.</p> <p>Point for the cor. of secs. 6 and 7, T. 26 N., R. 31 E., only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R30E R31E S6 S1 — S7 1978</p> </div> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, E. of cor.</p> <p>Land, level Soil, sandy loam Timber, none Undergrowth, sage brush</p>	
40.00	<p style="text-align: center;">Survey of Sec. 7, T. 26 N., R. 31 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 7 and 18, T. 26 N., R. 31 E., heretofore described.</p> <p>East, along the S. bdy. of sec. 7, on a transit line describing the tangent.</p> <p>Over gently rolling land, through medium undergrowth.</p> <p>Point for the 1/4 sec. cor. of sec. 7 only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T26N R31E <u>1/4 S7</u> 1978</p> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>	

Survey of Sec. 7, T. 26 N., R. 31 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point the most northerly cor. of a stone building 34x21 ft., bears S. 9°19' W., 5.03 chs. dist., long side bears NE and SW.</p>
	<p>From this same point a local cor. bears S. 10°19' W., 2.35 chs. dist. monumented with a sandstone, firmly set projecting 6 ins. above the ground mkd. with a cross on top.</p>
64.60	<p>Rocky ridge, bears S. 10° E. and N. 10° W.</p>
80.00	<p>Point for the cor. of secs. 7 and 8 only, North 1 link from the tangent.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R31E <u>S7 S8</u></p>
	<p style="text-align: center;">1978</p>
	<p>Deposit broken glass at base of iron post.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A brass tablet, 3 ins. diam., in the E. end of a concrete abutment of a cattle guard, bears S. 27°26' E., 242 lks. dist. mkd.</p>
	<p style="text-align: center;">Arizona Highway Dept.</p>
	<p style="text-align: center;">Elev. 6742.02 662 x 45</p>
	<p style="text-align: center;">1977</p>
	<p>Land, rolling Soil, sandy loam Timber, scattered, cotton wood, pinyon and cedar Undergrowth, sage brush</p>
	<p>N. 0°01' E., bet. secs. 7 and 8.</p>
	<p>Over gently rolling open land.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 7 and 8.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T26N R31E 1/4 <u>S7 S8</u></p>
	<p style="text-align: center;">1978</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>

Survey of Sec. 7, T. 26 N., R. 31 E.,
Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>80.00</p>	<p>Point for the cor. of secs. 5, 6, 7 and 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below surface of ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E S6 S5 S7 S8</p> <p style="text-align: center;">1978</p> <p>from which</p> <p style="padding-left: 40px;">A fire hydrant, bears S. 12°34' E., 141 lks. dist.</p> <p style="padding-left: 40px;">X B O stamped on the center of a cover over a water meter bears N. 45°27' E., 70 lks. dist.</p> <p>Cor. is located in partially developed housing subdivision.</p> <p>Land, rolling Soil, sandy loam Timber, scattered cedar and pinyon Undergrowth, sage brush</p>	
<p>40.00</p>	<p>West, bet. secs. 6 and 7.</p> <p>Over rolling land, through scattered cedar and pinyon.</p> <p>Point for the 1/4 sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E S6 1/4 — S7</p> <p style="text-align: center;">1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>From this point a rebar 1/2 in. diam., bears N. 31°21' W., 98 lks. dist.</p>	
<p>80.00</p>	<p>The cor. of secs. 6 and 7, heretofore described.</p> <p>Land, rolling Soil, sandy loam Timber, scattered cedar and pinyon Undergrowth, sage brush</p>	
	<p>Subdivision of Sec. 7, T. 26 N., R. 31 E., Gila and Salt River Meridian, Arizona</p>	

Subdivision of Sec. 7, T. 26 N., R. 31 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.00	<p>From the 1/4 sec. cor. of sec. 7 only, on the south boundary of the sec.</p> <p>N. 0°00'30" E., along the N. and S. center line of sec. 7.</p> <p>Over rolling land, through medium undergrowth and scattered cedar and pinyon.</p> <p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T26N R31E C 1/4 S7</p> <p style="text-align: center;">1978</p> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>From this point a windmill, bears N. 14°06' W., 17.02 chs. dist.</p>
56.30	<p>Powerline, bears N. 78° E. and S. 78° W.</p>
80.00	<p>The 1/4 sec. cor. of secs. 6 and 7.</p>
28.00	<p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>S. 89°59'30" W., along the E. and W. center line of sec. 7.</p> <p>Over rolling land, through scattered cedar and pinyon.</p> <p>Rocky ridge, bears S. 30° E. and N. 30° W.</p>
40.00	<p>The C 1/4 sec. cor. of sec. 7.</p>
80.00	<p>The 1/4 sec. cor. of sec. 7 only, on the west boundary of the Tp., heretofore described.</p>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located at Window Rock, Arizona. The general elevation ranges from about 6670 to 6800 feet above sea level. The soil is a sandy loam.</p> <p>Access is by way of Highway No. 12 and 264, and numerous unimproved or lightly gravelled roads.</p> <p>The vegetation consists of sage brush, scattered cedar and pinyon.</p> <p>There is no evidence of mining activity or minerals.</p>

CHAINS	
--------	--

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Tech.
John J. Bulinski	Survey Aid
Jay D. Lytle	Survey Aid
Duane R. Ferneau	Survey Aid
William J. Anderson	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 21st day of April, 1978, (I) ~~(We)~~ have dependently resurveyed a portion of the east boundary, surveyed a portion of the east boundary of Township 26 North, Range 30 East, and surveyed the boundaries and subdivision lines of Section 7, Township 26 North, Range 31 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 29, 1978 (Date) Paul L. Reeves (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the east boundary and the survey of a portion of the east boundary, Township 26 North, Range 30 East; and a survey of the boundaries and subdivision lines of Section 7, Township 26 North, Range 31 East, of the Gila and Salt River Meridian, Arizona,

executed by Paul L. Reeves, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

SEP 15 1978 (Date) [Signature] (Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 26 N., R. 31 E., G&SRM., Arizona, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626