

BOOK 5068

Form 9180-6
(April 1974)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

of the

 Dependent Resurvey of a Portion

 of the

 South Boundary (First Standard Parallel South),

 and a

 Portion of the Subdivisional Lines;

 and the

 Survey

 of the

 Subdivision of Sections

 8, 17, 21, 27, 28, 34, and 36,

 Township 5 South, Range 24 East

Of the _____ Gila and Salt River _____ Meridian,
 In the State of _____ Arizona _____

EXECUTED BY

_____ Harry K. Smith _____ Cadastral Surveyor

Under special instructions dated _____ January 3 _____, 19 77, approved _____ January 5, 1977 _____,

_____, which provided for the surveys included under U.S. Survey/Group
 Number _____ 593 _____, and assignment instructions dated _____ March 14 _____, 19 77.

Survey commenced _____ March 16 _____, 1977
 Survey completed _____ April 22 _____, 1977

1A

BOOK 5068

INDEX DIAGRAM

Township 5 South, Range 24 East

6	5 24	4	3	2	1
7	24 8 23	20 9	10	11	12
18	22 17 21	18 16 18	15	14	13
19	20	17 21 16	13 22 12	23	24
30	29	28 15 14	27 11 10	26 8 8	25 7 6
31 2	32 2	33 2	34 9 3	35 7 4	36 5 5

Subdivision of Secs.

<u>Sec.</u>	<u>Page</u>
8	25
17	27
21	28
27	30
28	32
34	33
36	34

Township 5 South, Range 24 East,
Gila and Salt River Meridian, Arizona

CHAINS

The history of surveys of Township 5 South, Range 24 East, Gila and Salt River Meridian, Arizona is as follows:

The boundaries and subdivisional lines were surveyed in 1874-75 by Theodore F. White. The south boundary was resurveyed by Albert B. Rich in 1916 and was partially resurveyed by Leonard W. Murphy, Frank W. Rogers and Paul G. Bauer in 1964-72. Paul L. Reeves resurveyed the east half of the south boundary of sec. 36 in 1976-77. The east boundary was resurveyed by William H. Thorn in 1921. The east, south and west boundaries of section 6 were resurveyed by Leonard Murphy in 1965. The north boundary was resurveyed by Donald Harding and Fred Chappell in 1955 and by Paul G. Bauer in 1963. A portion of the west boundary was resurveyed concurrently by Paul L. Reeves in 1976, under Group No. 581, Arizona.

The following field notes are those of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), a portion of the subdivisional lines and the subdivision of sections 8, 17, 21, 27, 28, 34, and 36, Township 5 South, Range 24 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions 1973, and the Special Instructions for Group No. 593, Arizona, dated January 3, 1977.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian. Measurements were made using electronic distance measuring equipment making it impractical to record all topographic items.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions; lost corners were reestablished at proportionate positions but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the SE corner of this Township, as scaled from U. S. Geological Survey Quadrangle Map, "Thatcher, Arizona", prepared in 1960, is as follows:

Latitude 32°56.8' N. Longitude 109°49.7' W.

The mean magnetic declination is 13°30' E.

Dependent Resurvey of a Portion of the South
Boundary (First Standard Parallel South) T. 5 S.,
R. 24 E., Gila and Salt River Meridian, Arizona

Dependent Resurvey of a Portion of the
 South Boundary (First Standard Parallel South)
 T. 5 S., R. 24 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>(Restoring the resurvey executed by Leonard W. Murphy, Frank W. Rogers and Paul G. Bauer in 1964-72)</p> <p>Beginning at the stan. $\frac{1}{4}$ sec. cor. of sec. 31, monumented with an iron post, 1 in. diam., projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p> <p>S. 89°52' E., on the S bdy. of sec. 31.</p> <p>Over nearly level land, through medium undergrowth.</p> <p>Topography is as recorded in the 1964-72 resurvey and is omitted from these notes.</p>	
12.29	<p>Point for the closing cor. of secs. 5 and 6, T. 6 S., R. 24 E., at proportionate dist. There is no evidence of the cor.; not monumented.</p>	
39.90	<p>Point for the stan. cor. of secs. 31 and 32, at proportionate dist. There is no evidence of the cor.; not monumented.</p>	
	<p>S. 89°52' E., on the S bdy of sec. 32.</p> <p>Over nearly level land.</p> <p>Topography is as recorded in the 1964-72 resurvey and is omitted from these notes.</p>	
12.28	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 5, T. 6 S., R. 24 E., at proportionate dist. There is no evidence of the cor.; not monumented.</p>	
39.90	<p>Point for the stan. $\frac{1}{4}$ sec. cor. of sec. 32, at proportionate dist. There is no evidence of the cor.; not monumented.</p>	
52.17	<p>Point for the closing cor. of secs. 4 and 5, T. 6 S., R. 24 E., at proportionate dist. There is no evidence of the cor.; not monumented.</p>	
79.80	<p>Point for the stan. cor. of secs. 32 and 33, at proportionate dist. There is no evidence of the cor.; not remonumented. This point is in an overflow area.</p>	
	<p>S. 89°52' E., on the S bdy. of sec. 33.</p> <p>Over river bottom land, through scattering patches of timber and undergrowth.</p>	
1.00	<p>Present left bank of the Gila River, 4 ft. high, bears SE and NW.</p>	
5.00	<p>Present right bank of the Gila River, 8 ft. high, bears SE and NW.</p>	
12.28	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 4, T. 6 S., R. 24 E., at proportionate dist. There is no evidence of the cor; not monumented.</p>	

Dependent Resurvey of a Portion of the South
Boundary (First Standard Parallel South) T. 5 S.,
R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
39.90	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 33, monumented with an iron post, 1 in. diam., projecting 5 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p>	
	<p>From the standard cor. of secs. 33 and 34, monumented with an iron post, 3 ins. diam., projecting 11 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p>	
	<p>S. 89°57' E., on the S bdy. of sec. 34.</p>	
	<p>Over rolling land, through medium undergrowth.</p>	
12.18	<p>The $\frac{1}{4}$ sec. cor. of sec. 3, T. 6 S., R. 24 E., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1964-72 resurvey, T. 6 S., R. 24 E. A mound of stone, 2 ft. base, 1 ft. high, is S of the cor. Add marks for T. 5 S., R. 24 E.; the cap is now mkd.</p>	
	<p style="text-align: center;">T 5 S R 24 E</p>	
	<p style="text-align: center;"><u>$\frac{1}{4}$ S3</u></p>	
	<p style="text-align: center;">T 6 S R 24 E</p>	
	<p style="text-align: center;">1977</p>	
	<p style="text-align: center;">1965</p>	
39.91	<p>The stan. $\frac{1}{4}$ sec. cor. of sec. 34, monumented with an iron post, 1 in. diam., projecting 10 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1916 resurvey.</p>	
	<p style="text-align: center;">S. 89°58' E., beginning new measurement.</p>	
12.19	<p>The closing cor. of secs. 2 and 3, monumented with an iron post, $2\frac{1}{2}$ ins. diam., set in a mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, to top of brass cap, mkd. as described in the official record of the 1964-72 resurvey of T. 6 S., R. 24 E. Add marks for T. 5 S., R. 24 E.; the cap is now mkd.</p>	
	<p style="text-align: center;">T 5 S R 24 E</p>	
	<p style="text-align: center;">S34</p>	
	<p style="text-align: center;"><u>S3 S2</u></p>	
	<p style="text-align: center;">T 6 S R 24 E</p>	
	<p style="text-align: center;">CC</p>	
	<p style="text-align: center;">1977</p>	
	<p style="text-align: center;">1965</p>	
19.83	<p>Point for the stan. E 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">S C</p>	
	<p style="text-align: center;">T 5 S R 24 E</p>	
	<p style="text-align: center;"><u>E 1/16 S34</u></p>	
	<p style="text-align: center;">1977</p>	

Dependent Resurvey of a Portion of the South
Boundary (First Standard Parallel South) T. 5 S.,
R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS																		
39.66	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, N of the cor.</p> <p>Cor. is located 21 lks. East of a fence cor.; fences extend E and S.</p> <p>The stan. cor. of secs. 34 and 35, monumented with an iron post, 3 ins. diam., projecting 15 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p> <p>A mound of stone, 3 ft. base, 1 ft. high, is N of the cor.</p> <p>Cor. is located in an abandoned E and W fence.</p>																	
39.67	<p>(Restoring the 1916 resurvey by Albert B. Rich)</p> <p>S. 89°48' E., on the S bdy. of sec. 35.</p> <p>Over rolling land, through medium undergrowth.</p> <p>The stan. ¼ sec. cor. of sec. 35, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p> <p>Cor. is located in an E and W fence.</p>																	
7.10	<p>(Restoring the 1964-72 resurvey by Leonard W. Murphy, Frank W. Rogers and Paul G. Bauer)</p> <p>S. 89°48' E., beginning new measurement.</p> <p>Graded road, bears NE and SW.</p>																	
12.04	<p>The closing cor. of secs. 1 and 2, T. 6 S., R. 24 E., monumented with an iron post, 2½ ins. diam., set flush with the ground in a concrete base, with brass cap mkd. as described in the official record of the 1965 resurvey of T. 6 S., R. 24 E. Add marks for T. 5 S., R 24 E.; the cap is now mkd.</p> <div style="text-align: center;"> <table border="0"> <tr> <td>T 5 S</td> <td>R 24 E</td> </tr> <tr> <td colspan="2">S35</td> </tr> <tr> <td colspan="2">-----</td> </tr> <tr> <td>S2</td> <td>S1</td> </tr> <tr> <td>T 6 S</td> <td>R 24 E</td> </tr> <tr> <td colspan="2">CC</td> </tr> <tr> <td colspan="2">1977</td> </tr> <tr> <td colspan="2">1965</td> </tr> </table> </div>	T 5 S	R 24 E	S35		-----		S2	S1	T 6 S	R 24 E	CC		1977		1965		
T 5 S	R 24 E																	
S35																		

S2	S1																	
T 6 S	R 24 E																	
CC																		
1977																		
1965																		
16.90	<p>Cor. is located 15 lks. W of a wash, 20 lks. wide, 1½ ft. deep, draining SW.</p> <p>Center of an earth dike, bearing S. 55° E., 1.80 chs. dist. and N. 55° W., 14.00 chs. dist.</p>																	

Dependent Resurvey of a Portion of the South Boundary (First Standard Parallel South) T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
39.71	<p>The stan. cor. of secs. 35 and 36, monumented with an iron post, 3 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p>	
12.145	<p>(Restoring the 1916 resurvey by Albert B. Rich)</p> <p>S. 89°47' E., on the S bdy. of sec. 36.</p> <p>Over rolling land, through medium undergrowth.</p> <p>Point for the ¼ sec. cor. of sec. 1, T. 6 S., R. 24 E., is at midpoint on the N bdy. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 5 S R 24 E</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">¼ S1</p> <p style="text-align: center;">T 6 S R 24 E</p> <p style="text-align: center;">1977</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor. for support.</p>	
39.71	<p>The stan. ¼ sec. cor. of sec. 36, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1916 resurvey.</p> <p>A mound of stone, 2½ ft. base, 1 ft. high, is N of the cor.</p> <p>From this point, "Corners 19" vertical angle bench mark, bears S. 26°47' W., 11.01 chs. dist., monumented with a bronze disc, 3½ ins. diam., set in a concrete base.</p> <p>From this same point, the closing corner of secs. 1 and 6, Tps. 6 S., Rs. 24 and 25 E., monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, 2½ ft. base, 1½ ft. high, and with brass cap mkd. as described in the field notes of the resurvey of T. 6 S., R. 25 E., executed by Paul L. Reeves in 1976-77, bears S. 89°46' E., 12.25 chs. dist.</p>	
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona.</p>	
	<p>(Restoring the 1875 survey by Theodore F. White.)</p> <p>From the stan. cor. of secs. 35 and 36, on the S bdy. of the Tp.</p> <p>N. 0°34' E., bet. secs. 35 and 36.</p>	

Dependent Resurvey of a Portion of the
 Subdivisional Lines, T. 5 S., R. 24 E.,
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Over broken rolling land, through medium undergrowth.</p>	
40.54	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 in. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E $\frac{1}{4}$ S35 S36 1977</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is located on a SE slope.</p>	
43.10	<p>Leave broken rolling land, bears NE and SW, thence over mesa.</p>	
81.08	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a volcanic stone, 17x8x8 ins., firmly set 9 ins. in the ground, mkd. with 1 notch on the E and 1 notch on the S edges with a mound of stone, 2 ft. base, 1 ft. high, N of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S26 S25 S35 S36 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>	
	<p>From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground with brass cap erroneously mkd. for the cor. of secs. 19, 24, 25 and 30. The markings were changed so that the cap is now mkd.</p> <p style="text-align: center;">T5S R24E R25E S25 S30 S36 S31 1977 1921</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A mesquite, 7 ins. diam., bears N. 83° W., 42 lks. dist., mkd. with a healed blaze.</p> <p>Cor. is in a fence cor.; fences extend S and NW.</p> <p>N. 88°55' W., bet. secs. 25 and 36.</p> <p>Over broken rolling land, through medium undergrowth.</p>	
.90	<p>Billingsley Creek, 50 lks. wide, 3 ft. deep, drains SE. curving to SW.</p>	
1.70	<p>Fence, bears N. 30° E. and S. 30° W.</p>	
39.35	<p>Point for the ¼ sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S25 S36</p> <p style="text-align: center;">1977</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p>	
78.69	<p>The cor. of secs. 25, 26, 35 and 36.</p>	
40.12	<p>From the stan. cor. of secs. 34 and 35, on the S bdy. of the Tp.</p> <p>N. 0°09' E., bet. secs. 34 and 35.</p> <p>Over gently rolling mesa, through medium undergrowth.</p> <p>Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S34 S35</p> <p style="text-align: center;">1977</p>	
52.60	<p>Track road, bears N. 80° E. and S. 80° W.</p>	
80.24	<p>True point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor. This point falls in a washed area where it is impractical to monument.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.01	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>West bet. secs. 26 and 35.</p> <p>Over gently rolling mesa, through medium undergrowth.</p> <p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with a volcanic stone, 17x8x6 ins., firmly set 7 ins. in the ground, mkd. $\frac{1}{4}$ on the N face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E $\frac{1}{4}$ $\frac{S26}{S35}$</p> <p style="text-align: center;">1977</p> <p>Deposit the mkd. stone alongside, the iron post.</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, 2 ft. high, N of the cor.</p> <p style="text-align: center;">_____</p> <p>S. $89^{\circ}10'$ W., beginning new measurement.</p>
39.92	<p>The true point for the cor. of secs. 26, 27, 34 and 35.</p>
.40	<p>N. $0^{\circ}29'$ W., bet. secs. 26 and 27.</p> <p>Over gently rolling land, through scattering undergrowth.</p> <p>Point selected for the witness cor. of secs. 26, 27, 34 and 35.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W C T5S R24E $\frac{S27}{S34}$ $\frac{S26}{S35}$ ↓</p> <p style="text-align: center;">1977</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W of the cor.</p>
14.90	<p>Dim track road, bears N. 70° E. and S. 70° W.</p>
20.20	<p>Fence, bears N. 70° E. and S. 70° W.</p>
40.12	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E $\frac{1}{4}$ S27 S26 1977</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p> <p>from which</p> <p style="text-align: center;">A mesquite, 4 ins. diam., bears S. 75° W., 67 lks. dist., mkd. ¼ S 27 BT.</p> <p>57.10 Track road, bears N. 70° E. and S. 70° W.</p> <p>67.70 Track road, bears S. 80° E. and N. 80° W.</p> <p>80.24 The cor. of secs. 22, 23, 26 and 27, monumented with a volcanic stone, 21x12x10 ins., firmly set 10 ins. in the ground, mkd. with 2 grooves on the S. face and 2 grooves on the E. face, with a scattered mound of stone N of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S22 S23 S27 S26 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p>
	<p>From the stan. cor. of secs. 33 and 34, on the S bdy. of the Tp.</p> <p>N. 0°01' E., bet. secs. 33 and 34.</p> <p>Over rolling land, through medium undergrowth.</p> <p>33.30 Track road, bears NE and SW.</p> <p>40.28 Point for the ¼ sec. cor. of secs. 33 and 34, at proportionate dist. There is no remaining evidence of the original cor.; not monumented.</p> <p>51.90 Track road, bears S. 60° E. and N. 35° W., irregularly.</p> <p>58.20 Center of a cleared area, bears SE and NW.</p> <p>79.80 Track road, bears irregularly E and SW.</p> <p>80.16 Fence, bears E and W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
80.56	<p>The cor. of secs. 27, 28, 33 and 34, monumented with traces of a decayed wooden post in a scattered mound of stone, verified by the remains of the original bearing trees</p> <p>A mesquite stump, 8 ins. diam., bears S. 68° E., 183 lks. dist., no marks visible.</p> <p>A mesquite stump, 8 ins. diam., bears S. 52° E., 71 lks. dist., no marks visible.</p> <p>A mesquite stump, 10 ins. diam., bears S. 31½° W., 162 lks. dist., no marks visible.</p> <p>At the center of the mound</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S28 S27 S33 S34 1977</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of the cor.</p>	
15.80 23.40 39.96	<p>From the true point for the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°18' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through medium undergrowth.</p> <p>Enter nearly level mesa, edge bears NE and SW.</p> <p>Track road, bears irregularly NE and SW.</p> <p>The ¼ sec. cor. of secs. 27 and 34, monumented with a mound of stone, 3 ft. base, 1 ft. high, with a weathered wooden post lying on the ground alongside the mound.</p> <p>At the center of the mound</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, over a cross chiseled in solid rock, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S27 S34 1977</p> <p>Set the wooden post alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°50' W., beginning new measurement.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
19.30	Fence, bears N. 75° E. and S. 75° W.
19.89	<p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, on solid rock in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E W 1/16 $\frac{S27}{S34}$ 1977</p>
20.80	Fence, bears N and S, 48 lks. dist. to fence cor.; fences extend N, N. 75° E., S and W.
39.78	The cor. of secs. 27, 28, 33 and 34.
	N. 0°27' W., bet. secs. 27 and 28.
	Over rolling land, through medium undergrowth.
7.40	Track road, bears E and W.
19.70	Fence, bears E and W.
19.925	<p>Point for the S 1/16 sec. cor. of secs. 27 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S 1/16 S28 S27 1977</p>
	from which
	<p style="text-align: center;">A fence cor., bears S. 71° W., 77 lks. dist.; fences extend N and E.</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.
39.85	<p>Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate dist., is 5 lks. N of the center of a track road, bears S. 75° E. and N. 75° W. There is no evidence of the original cor.</p> <p>Set a brass tablet, 3¼ ins. diam., 3½ inch stem, in a drill hole in solid rock, 12 ins. below the ground, with top mkd.</p> <p style="text-align: center;">T5S R24E ¼ S28 S27 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p>	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 45° E., 45.5 lks. dist., with brass cap mkd. T5S R24E ¼ S 27 RM 30 FT 1977 and an arrow pointing to the cor.</p>	
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, for a reference monument, bears N. 45° W., 45.5 lks. dist., with brass cap mkd. T5S R24E ¼ S 28 RM 30 FT 1977 and an arrow pointing to the cor.</p>	
	<p>A fence cor., bears S. 88° W., 86 lks. dist.; fences extend S and W.</p>	
59.40	<p>Spur, slopes S. 50° W.</p>	
79.70	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a mound of stone, 3 ft. base, 1 ft. high, with a weathered wooden post, 4 ins. diam., 4½ ft. long, flattened on one side, lying on the ground alongside the mound.</p>	
	<p>At the center of the mound</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 2½ ft. base to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T5S R24E S21 S22 S28 S27 1977</p>	
	<p>Set the wooden post alongside the iron post.</p>	
	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W. of the cor.</p>	
	<p>From this point Eden Spring, bears S. 78°39' E., 14.74 chs. dist.</p>	
	<p>Cor. is on a N slope.</p>	
	<p>From the cor. of secs. 22, 23, 26 and 27.</p>	
	<p>S. 89°53' W., bet. secs. 22 and 27.</p>	
	<p>Over nearly level mesa, through medium undergrowth.</p>	
39.95	<p>The ¼ sec. cor. of secs. 22 and 27, monumented with a mound of stone, 3 ft. base, 2 ft. high, with a weathered wooden post lying on the ground alongside the mound.</p>	
	<p>At the center of the mound</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S22 S27 1977</p> <p>Set the wooden post alongside the iron post.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°52' W., beginning new measurement.</p> <p>30.20 Ridge, bears N. 65° E. and S. 65° W.</p> <p>39.71 The cor. of secs. 21, 22, 27 and 28.</p>
	<p>N. 0°18' W., bet. secs. 21 and 22.</p> <p>Over rolling land, through medium to scattering undergrowth.</p> <p>39.97 Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S21 S22 1977</p> <p>56.40 Track road, bears N. 80° E. and S. 80° W.</p> <p>79.94 The cor. of secs. 15, 16, 21 and 22, monumented with a volcanic stone, 19x8x8 ins., firmly set 10 ins. in the ground, mkd. with 3 notches on the E edge and 3 notches on the S edge, with a scattered mound of stone around the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S16 S15 S21 S22 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 2.5 lks. south of a fence, bears E and W.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>S. 89°55' W., bet. secs. 28 and 33.</p>
	<p>Over gently rolling land, through dense undergrowth.</p>
39.50	<p>Graded gravel road, bears N and S.</p>
39.98	<p>Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist. There is no remaining evidence of the original cor.; not monumented. This point falls in Curtis Canal, 15 lks. wide, flows N. 20° W.</p>
	<p>Thence along a paved road, bears E and W.</p>
79.95	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set a railroad spike flush with the surface of a paved road, with top mkd.</p>
	<p style="text-align: center;">T5S R24E S29 S28 S32 S33 1977</p>
	<p>Cor. is located 3 lks. S. of the center of a paved road bearing E and W, and 9 lks. E. of the center of a paved road projecting N.</p>
	<p>from which</p>
	<p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 18 ins. in the ground for a reference monument, bears N. 44°29' E., 68.2 lks. dist., with brass cap mkd. T5S R24E S 28 RM 45 FT 1977 and an arrow pointing to the cor.</p>
	<p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 31°54' W., 60.6 lks. dist., with brass cap mkd. T5S R24E S 29 RM 40 FT 1977 and an arrow pointing to the cor.</p>
	<p>From this point the point for the stan. cor. of secs. 32 and 33, on the S bdy. of the Tp., bears S. 0°01' E., 80.14 chs. dist., heretofore described.</p>
	<p>From this same point the point for the cor. of secs. 25, 30, 31 and 36 on the W bdy. of the Tp., bears N. 89°53' W., 159.87 chs. dist., previously described in the field notes of the dependent resurvey of a portion of the E bdy. of T. 5 S., R. 23 E., concurrently resurveyed by Paul L. Reeves under Group No. 581, Arizona.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>These control lines were fully retraced and careful search was made for intervening cors., none of which were recovered.</p>	
40.07	<p>N. 0°30' W., bet. secs. 28 and 29.</p> <p>Along a paved road.</p> <p>Point for the ¼ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a copper coated steel rod, 30 ins. long, 3/4 ins. diam., flush with the surface of a paved road, with cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S29 S28 1977</p> <p>from which</p> <p style="padding-left: 40px;">XBO chisled on a concrete irrigation canal, bears S. 32°44' W., 41.4 lks. dist.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 81°10' W., 28.8 lks. dist., with brass cap mkd. T5S R24E ¼ S 29 RM 19 FT 1977 and an arrow pointing to the cor.</p> <p>Cor. is located 12.5 lks. W of the center of a paved road bearing N and S, and 45 lks. W of a fence and telephone line, bearing N and S.</p>	
80.14	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 15 ins. long, 2½ ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S20 S21 S29 S28 1977</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears N. 31°30' E., 121.5 lks. dist.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears S. 65°35' E., 66.7 lks. dist., with brass cap mkd. T5S R24E S 28 RM 44 FT 1977 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A fence cor., bears S. 50° E., 84 lks. dist.; fences extend N., E. and S.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 24.5 lks. W. of center of a paved road, bearing N and S, 64 lks. W of a fence and telephone line, bearing N and S, and 8 lks. E of a power line, bearing N and S.</p> <p>From this point the point for the cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp., bears N. 89°55' W., 159.51 chs. dist., previously described in the field notes of the dependent resurvey of a portion of the E bdy. of T. 5 S., R. 23 E., concurrently resurveyed by Paul L. Reeves under Group No. 581, Arizona.</p> <p>This control line was fully retraced and careful search was made for intervening cors., none of which were recovered.</p>
20.00	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°45' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through medium undergrowth.</p> <p>Point for the E 1/16 sec. cor. of secs. 21 and 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E E 1/16 $\frac{S21}{S28}$</p> <p style="text-align: center;">1977</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of the cor.</p> <p>Cor. is located 36 lks. E. of a fence, bears N and S.</p>
40.00	<p>Point for the ¼ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ $\frac{S21}{S28}$</p> <p style="text-align: center;">1977</p>
80.01	<p>The cor. of secs. 20, 21, 28 and 29.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.07	<p>N. 0°13' W., bet. secs. 20 and 21.</p> <p>Along a paved road.</p> <p>Point for the ¼ sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 15 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ S20 S21 1977</p> <p>from which</p> <p style="padding-left: 40px;">A telephone pole, bears N. 34°28' E., 115 lks. dist.</p> <p style="padding-left: 40px;">A fence cor., bears S. 39°38' E., 109 lks. dist.; fences extend E and S.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 52°16' W., 15.2 lks. dist., with brass cap mkd. T5S R24E S20 ¼ RM 10 FT 1977 and an arrow pointing to the cor.</p> <p>Cor. is located at the W edge of a graded road, bearing N and S, and 13 lks. E of a fence, bears N and S.</p>
80.14	<p>Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 15 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E S17 S16 S20 S21 1977</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, bears S. 83°03' E., 58 lks. dist.</p> <p style="padding-left: 40px;">A fence cor., bears S. 41°05' E., 94.5 lks. dist., fences extend N and E.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears N. 60°41' W., 27.3 lks. dist., with brass cap mkd. T5S R24E S17 RM 18 FT 1977 and an arrow pointing to the cor.</p> <p>Cor. is located at the W edge of a graded road, bearing N and S, 56 lks. E of a power line, bearing N and S, 63 lks. W of a fence, bears N and S, and 58 lks. W of a telephone line, bearing N and S.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>S. 89°55' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land, through medium undergrowth, along a fence bearing E and W.</p>	
40.05	<p>The ¼ sec. cor. of secs. 16 and 21, monumented with a volcanic stone, 30x11x10 ins., firmly set 12 ins. in the ground, mkd. ¼ on the E face, with a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R24E</p> <p>¼ $\frac{S16}{S21}$</p> <p>1977</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.</p> <p>Cor. is located in a fence, bears E and W.</p>	
19.93	<p>N. 89°06' W., beginning new measurement.</p> <p>Point for the W 1/16 sec. cor. of secs. 16 and 21.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T5S R24E</p> <p>W 1/16 $\frac{S16}{S21}$</p> <p>1977</p> </div> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 10° W., 37 lks. dist.; fences extend E, S and W.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N of the cor.</p>	
39.86	<p>The cor. of secs. 16, 17, 20 and 21.</p>	
40.07	<p>N. 0°18' W., bet. secs. 16 and 17.</p> <p>The ¼ sec. cor. of secs. 16 and 17, monumented with an open end iron pipe, 2 ins. diam., projecting 12 ins. above a concrete base. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.

T5S R24E

¼

S17|S16

1977

Reset the local iron pipe alongside the iron post.

Cor. is located in a fence, bears N and S.

From this point a spring 13 ft. diam., bears N. 18° W., 90 lks. dist., producing approximately 1.5 gallons of hot water per minute.

N. 0°14' W., beginning new measurement.

19.71 Point for the N 1/16 sec. cor. of secs. 16 and 17.

Set an iron post, 28 ins. long, 2½ ins. diam., 36 ins. in the ground, with brass cap mkd.

T5S R24E

N 1/16

S17|S16

1977

from which

An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 45° E., 37.9 lks. dist., with brass cap mkd. T5S R24E S16 N 1/16 RM 25 FT 1977 and an arrow pointing to the cor.

A fence cor., bears S. 19° E., 23 lks. dist.; fences extend S and W.

An iron post, 28 ins. long, 2½ ins. diam., set 18 ins. in the ground, for a reference monument, bears N. 45° W., 37.9 lks. dist., with brass cap mkd. T5S R24E S17 N 1/16 RM 25 FT 1977 and an arrow pointing to the cor.

Cor. is located in the bend of a bladed road, bearing S and W.

39.42 The cor. of secs. 8, 9, 16 and 17, monumented with a mound of stone, 3½ ft. base, 2 ft. high.

At the center of the mound

Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T5S R24E

S8|S9

S17|S16

1977

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>
	<p>N. 0°23' E., bet. secs. 8 and 9.</p>
	<p>Over rolling land, through medium undergrowth.</p>
8.50	<p>Bladed road, bears S. 80° E. and N. 80° W.</p>
20.635	<p>Point selected for the witness S 1/16 sec. cor. of secs. 8 and 9.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> W C T5S R24E S 1/16 ↑ S8 S9 1977 </p>
	<p>from which</p>
	<p style="text-align: center;"> A mesquite, 12 ins. diam., bears N. 34° W., 72 lks. dist., mkd. X at breast height and BT at the base. </p>
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of the cor.</p>
20.935	<p>True point for the S 1/16 sec. cor. of secs. 8 and 9 falls in the center of a wash, 40 lks. wide, 2 ft. deep, drains W., where it is impractical to monument.</p>
30.90	<p>Ridge, bears N. 60° E. and S. 60° W.</p>
41.87	<p>The ¼ sec. cor. of secs. 8 and 9, monumented with a volcanic stone, 16x11x7 ins., lying in a mound of stone, 2 ft. base, 1 ft. high, mkd. ¼ on one face.</p>
	<p>At the center of the mound</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;"> T5S R24E ¼ S8 S9 1977 </p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of the cor.</p>
	<p style="text-align: center;"> _____ N. 1°19' W., beginning new measurement. </p>
2.30	<p>Fence, bears N. 65° E. and S. 65° W.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
22.60	Spur, slopes E.
38.46	The cor. of secs. 4, 5, 8 and 9, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above the ground, with brass cap mkd.
	T5S R24E S5 S4 S8 S9 1965
	from which
	A mesquite, 8 ins. diam., bears S. 40° W., 195 lks. dist., with an open blaze, no scribe marks visible.
	A mound of stone, 4 ft. base, 3 ft. high, is W of the cor.
	From the cor. of secs. 16, 17, 20 and 21.
	N. 89°33' W., bet. secs. 17 and 20.
39.76	Point for the ¼ sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 15 ins. long, 2½ ins. diam., 23 ins. below the surface of the ground, with brass cap mkd.
	T5S R24E ¼ S17 S20 1977
	from which
	A power pole, bears N. 54°39' E., 92 lks. dist.
	An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 24°04' W., 24.2 lks. dist., with brass cap mkd. T5S R24E ¼ S17 RM 16 FT 1977 and an arrow pointing to the cor.
	Cor. is located at the N edge of a graded road, bearing E and W, and 56 lks. S of a power line, bearing E and W.
79.52	Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T5S R24E S18 S17 S19 S20 1977

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From this point, a stock pond, 2.00 chs. diam., bears N. 20° W., 3.20 chs. dist.</p>
	<p>From this same point the point for the cor. of secs. 13, 18, 19 and 24, on the W bdy. of the Tp., bears S. 89° 40' W., 80.00 chs. dist., previously described in the field notes of the dependent resurvey of a portion of the E bdy. of T. 5 S., R. 23 E., concurrently resurveyed by Paul L. Reeves under Group No. 581, Arizona.</p>
	<p>From this same point the point for the stan. cor. of secs. 31 and 32, on the S. bdy. of the Tp., bears S. 0°11' E., 240.84 chs, dist., heretofore described.</p>
	<p>These control lines were fully retraced and careful search was made for the intervening cors., none of which were recovered.</p>
	<p>N. 0°22' W., bet. secs. 17 and 18.</p>
	<p>Over nearly level land.</p>
<p>1.10</p>	<p>Fence line, bears irregularly E and W,</p>
<p>3.00</p>	<p>Enter cultivated land, edge bears E and W.</p>
<p>40.14</p>	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 15 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T5S R24E ¼ S18 S17 1977</p>
	<p>from which</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground for a reference monument, bears N. 19°56' E., 15.2 lks. dist., with brass cap mkd. T5S R24E ¼ S17 RM 10 FT 1977 and an arrow pointing to the cor.</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground for a reference monument, bears N. 71°43' W., 40.9 lks. dist., with brass cap mkd. T5S R24E ¼ S18 RM 27 FT 1977 and an arrow pointing to the cor.</p>
	<p>Cor. is located at the E edge of a graded road, bearing N and S, and 5 lks. W of a fence, bearing N and S.</p>
<p>80.28</p>	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T5S R24E S7 S8 S18 S17 1965</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Cor. is located at a fence cor.; fences extend N, S and W.</p>	
		<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>N. 89°41' W., bet. secs. 8 and 17.</p> <p>Over rolling land, through medium undergrowth.</p>	
	14.70	Bladed road, bears S. 30° E. and N. 30° W.	
	15.30	Fence, bears S. 20° E. and N. 20° W.	
	19.97	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17.</p> <p>Set an iron post, 28 ins. long 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E E 1/16 $\frac{S8}{S17}$</p> <p style="text-align: center;">1977</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of the cor.</p> <p>From this point a spring fed pond, 2.00 chs. diam., bears N. 54½° W., 10.70 chs. dist.</p> <p>From this same point a spring fed pond 1.50 chs. diam., bears N. 43° W., 10.15 chs. dist.</p> <p>From this same point a spring, bears N. 26½° W., 9.20 chs. dist., producing approximately 1 gallon of water per minute, drains W.</p>	
	39.94	<p>The ¼ sec. cor. of secs. 8 and 17, a local cor., monumented with an open end iron pipe, 2½ ins. diam., 36 ins. long, projecting 16 ins. above ground, from which an original bearing tree.</p> <p style="padding-left: 40px;">A dead mesquite, 8 ins. diam., bears S. 83° E., 289 lks. dist., mkd. with a healed blaze. (Record 287 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E ¼ $\frac{S8}{S17}$</p> <p style="text-align: center;">1977</p> <p>Reset the local iron pipe alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, N of the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	N. 88°20' W., beginning new measurement.
39.40	Graded road, bears N and S.
39.75	The cor. of secs. 7, 8, 17 and 18.
	N. 0°30' W., bet. sec. 7 and 8.
39.78	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R24E $\frac{1}{4}$ S7 S8 1977</p>
	Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the cor.
79.56	The cor. of secs. 5, 6, 7 and 8, monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above ground, with brass cap mkd.
	<p style="text-align: center;">T5S R24E S6 S5 S7 S8 1965</p>
	A mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, is W of the cor.
	From the cor. of secs. 4, 5, 8 and 9.
	N. 89°33' W., bet. secs. 5 and 8.
	Over rolling land, through scattering to medium undergrowth.
21.10	Spur, slopes SW.
38.00	Fence line, bears S and N, 76 lks. dist. to a fence cor.; fences extend S and W.
39.86	Point for the $\frac{1}{4}$ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R24E $\frac{1}{4}$ $\frac{S5}{S8}$ 1977</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W of the cor. for support.</p> <p>Cor. is located 79 lks. S of an E. and W. fence line.</p>
58.40	Bladed road, bears irregularly N. and S.
79.73	The cor. of secs. 5, 6, 7 and 8.
<p>Subdivision of Section 8, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona</p>	
	<p>From the ¼ sec. cor. of secs. 8 and 17.</p> <p>N. 0°24' W., on the N and S center line of sec. 8.</p> <p>Over rolling land, through medium undergrowth.</p>
7.10	Bladed road, bears E. and N. 65° W.
20.30	Wash, 25 lks. wide, 1 ft. deep, drains W.
20.645	Point for the C-S 1/16 sec. cor. of sec. 8.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E C S 1/16 S8 C 1977</p> <p>from which</p> <p style="text-align: center;">A mesquite, 10 ins. diam., bears S. 17° W., 58 lks. dist., mkd. C-S 1/16 S8 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high W of the cor.</p> <p>Cor. is located 67 lks. W of a fence, bearing N and S.</p>
41.29	Point for the C¼ sec. cor. of sec. 8, at intersection with the E and W center line.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E C¼ S8 1977</p>
	<p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W of the cor.</p> <p>Cor is located 105 lks. W of a fence, bearing N and S.</p>
80.43	The ¼ sec. cor. of secs. 5 and 8.

Subdivision of Section 8, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 8 and 9.</p> <p>S. $89^{\circ}30'$ W., on the E and W center line of sec. 8.</p> <p>Over rolling land, through medium undergrowth.</p>
5.80	Fence, bears N. 65° E. and S. 65° W.
20.25	<p>Point for the C-E $\frac{1}{16}$ sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T5S R24E C <u> E $\frac{1}{16}$ </u> C S8 1977</p>
	<p>Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N of the cor.</p>
40.50	The $\frac{1}{4}$ sec. cor. of sec. 8.
54.90	Bladed road, bears S. 10° E. and N. 10° W.
79.60	Fence, bears N and S.
80.00	Graded road, bears N and S.
80.29	The $\frac{1}{4}$ sec. cor. of secs. 7 and 8.
	<p><u>SE$\frac{1}{4}$, Section 8</u></p>
	<p>From the E $\frac{1}{16}$ sec. cor. of secs. 8 and 17.</p> <p>North, on the N and S center line of the SE$\frac{1}{4}$ of sec. 8.</p> <p>Over rolling land, through medium undergrowth.</p>
6.60	Fence, bears E and W.
7.00	Bladed road, bears E and N. 40° W.
7.70	Same bladed road, bears N. 60° E. and S. 60° W.
11.00	Bladed road, bears S. 70° E. and N. 70° W.
17.80	Wash, 80 lks. wide, 1 ft. deep, drains SW.
20.785	<p>Point for the SE $\frac{1}{16}$ sec. cor. of sec. 8, at inter- section with the E and W center line of the SE$\frac{1}{4}$ of sec. 8.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
	<p>T5S R24E SE $\frac{1}{16}$ S8 1977</p>

Subdivision of Section 8, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	from which
	A mesquite, 14 ins. diam., bears S. 69° W.,
	146 lks, dist., mkd. SE 1/16 S8 BT.
	Raise a mound of stone, 4 ft. base, 3 ft. high, W of
	the cor.
35.50	Fence, bears N. 65° E. and S. 65° W.
41.58	The C-E 1/16 sec. cor. of sec. 8.
	From the true point for the S 1/16 sec. cor. of secs.
	8 and 9.
	S. 89°55' W., on the E and W center line of the SE $\frac{1}{4}$ of
	sec. 8.
	Over nearly level land, through medium undergrowth.
20.10	The SE 1/16 sec. cor. of sec. 8.
40.21	The C-S 1/16 sec cor. of sec. 8.
Subdivision of Section 17, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona	
	From the $\frac{1}{4}$ sec. cor. of secs. 17 and 20.
	N. 0°22' W., on the N and S center line of sec. 17.
	Over gently rolling land, through medium undergrowth.
19.50	Dirt road, bears S. 85° E. and N. 85° W.
40.11	Point for the C $\frac{1}{4}$ sec. cor. of sec. 17, at intersection
	with the E and W center line.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins.
	in the ground to solid rock, and in a mound of stone,
	2 $\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	T5S R24E
	C $\frac{1}{4}$ S17
	1977
	Deposit broken clear bottle at the base of iron post.
59.00	Fence, bears E and W.
59.76	Point for the C-N 1/16 sec. cor. of sec. 17; not
	monumented.
79.41	The $\frac{1}{4}$ sec. cor. of secs. 8 and 17.
	From the $\frac{1}{4}$ sec. cor. of secs. 16 and 17.
	N. 89°31' W., on the E and W center line of sec 17.
	Over nearly level land, through medium undergrowth.

Subdivision of Section 17, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>19.91 Point for the C-E 1/16 sec. cor. of sec. 17; not monumented.</p> <p>39.82 The $C\frac{1}{4}$ sec. cor. of sec. 17.</p> <p>55.60 Enter cultivated land, edge bears N and S.</p> <p>79.50 Fence bears N and S, leave cultivated land.</p> <p>79.56 The $\frac{1}{4}$ sec. cor. of secs. 17 and 18.</p>
	<p>NE$\frac{1}{4}$, Section 17</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the C-E 1/16 sec. cor. of sec. 17.</p> <p>N. 0°16' W., on the N and S center line of the NE$\frac{1}{4}$ of sec. 17.</p> <p>Over nearly level land, through medium to dense mesquite and salt cedar.</p>
19.15	Fence. bears E and W.
19.68	<p>Point for the NE 1/16 sec cor. of sec. 17, at intersection with the E and W center line of the NE$\frac{1}{4}$ of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T5S R24E NE 1/16 S17 1977</p>
	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of the cor.</p>
39.37	<p>The E 1/16 sec. cor. of secs. 8 and 17.</p> <hr style="width: 20%; margin: auto;"/> <p>From the N 1/16 sec. cor. of secs. 16 and 17.</p> <p>N. 89°36' W., on the E and W center line of the NE$\frac{1}{4}$ of sec 17.</p> <p>Over gently rolling land, through medium undergrowth.</p>
19.94	The NE 1/16 sec. cor. of sec. 17.
39.88	The point for the C-N 1/16 sec. cor. of sec. 17
	<p>Subdivision of Section 21, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 21 and 28.</p> <p>N. 0°20' W., along the N. and S. center line of Sec. 21.</p> <p>Over gently rolling land, through medium undergrowth.</p>

Subdivision of Section 21, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
23.00	Center of a flood control dike, bears SE and NW.
39.38	Fence, bears E and W.
40.02	Point for the $C\frac{1}{4}$ sec. cor. of sec. 21, at intersection with the E and W center line. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T5S R24E C $\frac{1}{4}$ S21 1977 Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.
44.40	Track road, bears N. 70° E. and S. 70° W.
79.70	The $\frac{1}{4}$ sec. cor. of secs. 16 and 21.
20.01	From the $\frac{1}{4}$ sec. cor. of secs. 21 and 22. N. 89°40' W., on the E and W center line of sec. 21. Over rolling land, through medium undergrowth. Point for the C-E 1/16 sec. cor. of sec. 21. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd. T5S R24E C— $\frac{E\ 1/16}{S21}$ —C 1977 from which A fence cor., bears S. 25° E., 73 lks. dist.; fences extend S and W.
40.02	The $C\frac{1}{4}$ sec. cor. of sec. 21.
56.00	Flood control dike, bears SE and NW.
59.99	Point for the C-W 1/16 sec. cor. of sec. 21. Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd. T5S R24E C— $\frac{W\ 1/16}{S21}$ —C 1977 from which A fence cor., bears S. 42° W., 82.5 lks. dist.; fences extend N, E and W. Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, N of the cor.

Subdivision of Section 21, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
79.96	The ¼ sec. cor. of secs. 20 and 21.
Subdivision of Section 27, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona	
From the ¼ sec. cor. of secs. 27 and 34.	
N. 0°30' W., on the N and S center line of sec. 27.	
Over rolling land, through medium undergrowth.	
6.30	Fence line, bears N. 70° E. and S. 70° W.
19.84	True point for the C-S 1/16 sec. cor. of sec. 27, falls in a wash, 20 lks. wide 2 ft. deep, draining westerly, where it is impractical to monument.
20.04	Point selected for the witness C-S 1/16 sec. cor. of sec. 27.
Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	
W C T5S R24E C S 1/16 ↓ S27 C 1977	
from which	
A mesquite, 7 ins. diam., bears S. 50° W., 7 lks. dist., mkd. X at breast height and BT at base.	
Raise a mound of stone, 2 ft. base, 2 ft. high, W of the cor.	
38.00	Track road, bears N. 75° E. and S. 75° W.
39.68	Point for the C¼ sec. cor. of sec. 27, at intersection with the E and W center line.
Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.	
T5S R24E C¼ S27 1977	
Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.	
56.40	Track road, bears N. 40° E. and S. 40° W.
79.67	The ¼ sec. cor. of secs. 22 and 27.
From the ¼ sec. cor. of secs. 26 and 27.	
N. 89°55' W., on the E and W center line of sec. 27.	

Subdivision of Section 27, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	Over nearly level land, through scattering undergrowth.
39.96	The C $\frac{1}{4}$ sec. cor. of sec. 27.
46.80	Track road, bears N. 85° E. and S. 85° W.
59.83	Point for the C-W 1/16 sec. cor. of sec. 27.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T5S R24E C $\frac{W\ 1/16}{S27}$ C 1977</p>
	Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, N of the cor.
	Cor. is located on a N slope, 30 lks. from the base.
79.70	The $\frac{1}{4}$ sec. cor. of secs. 27 and 28.
	<p>SW$\frac{1}{4}$, Section 27</p> <hr/>
	From the W 1/16 sec. cor. of secs. 27 and 34.
	N. 0°28' W., on the N and S center line of the SW $\frac{1}{4}$ of sec. 27.
	Over rolling land, through medium undergrowth.
19.88	Point for the SW 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the SW $\frac{1}{4}$ of sec. 27.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. in the ground to solid rock, and in a mound of stone, 3 $\frac{1}{2}$ ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T5S R24E SW 1/16 S27 1977</p>
36.30	Track road, bears S. 85° E. and N. 85° W.
37.00	Descend N slope.
39.76	The C-W 1/16 sec. cor. of sec. 27.
	<p style="text-align: center;">_____</p>
	From the true point for the C-S 1/16 sec. cor. of sec. 27.
	S. 89°57' W., on the E and W center line of the SW $\frac{1}{4}$ of sec. 27.
	Over rolling land, through medium undergrowth.
19.88	The SW 1/16 sec. cor. of sec. 27.

Subdivision of section 27, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>20.63 A fence cor., bears South, 1 lk. dist.; fences extend S and W, thence along the N side of fence.</p> <p>30.70 Spur, slopes S. 30° W.</p> <p>37.30 Spur, slopes SW.</p> <p>39.77 The S 1/16 sec. cor. of secs. 27 and 28.</p>
<p>Subdivision of Section 28, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona</p>	
<p>39.20</p> <p>39.96</p> <p>59.30</p> <p>79.91</p>	<p>From the point for the 1/4 sec. cor. of secs. 28 and 33. N. 0°28' W., on the N and S center line of sec. 28. Over nearly level land, along the W side of a graded road.</p> <p>Fence, bears E and W, thence through medium undergrowth.</p> <p>Point for the C 1/4 sec. cor. of sec. 28, at intersection with the E and W center line. Set an iron post, 15 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E C 1/4 S28 1977</p> <p>Bury a 12 inch file inside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>Fence line, bears E. and W.</p> <p>The 1/4 sec. cor. of secs. 21 and 28.</p>
<p>13.90</p> <p>19.995</p>	<p>From the 1/4 sec. cor. of secs. 27 and 28. N. 89°55' W., on the E and W center line of sec. 28. Over rolling land, through medium undergrowth.</p> <p>Flood control dike, bears S. 40° E. and N. 40° W.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 28. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E E 1/16 C ——— C S28 1977</p>

Subdivision of Section 28, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.
	Cor. is located 26.5 lks. N of a fence, bearing E and W.
20.60	Bladed road, bears N. 35° E. and S. 35° W.
20.80	Fence, bears N and S.
39.99	The $\frac{1}{4}$ sec. cor. of sec. 28.
79.98	The $\frac{1}{4}$ sec. cor. of secs. 28 and 29.
Subdivision of Section 34, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona	
	From the stan. $\frac{1}{4}$ sec. cor. of sec. 34, on the S bdy. of the Tp.
	N. 0°04' W., on the N and S center line of sec. 34.
	Over rolling land, through medium undergrowth.
40.15	Fence, bears E and W.
40.20	Point for the $\frac{1}{4}$ sec. cor. of sec. 34, at intersection with the E and W center line.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T5S R24E $\frac{1}{4}$ S34 1977
	Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.
40.60	Track road, bears E and W.
55.60	Vertical cliff, 40 ft. high, bears N. 20° E. and S. 20° W.
70.50	Track road, bears N. 60° E. and S. 60° W.
79.40	Wash, 10 lks. wide, 1 ft. deep, drains W.
80.71	The $\frac{1}{4}$ sec. cor. of secs. 27 and 34.
	From the $\frac{1}{4}$ sec. cor. of secs. 34 and 35.
	N. 89°50' W., on the E and W center line of sec. 34.
	Over nearly level mesa, through medium undergrowth.
12.70	Track road, bears N. 25° E. and S. 25° W.

Subdivision of Section 34, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
19.75	Curve in track road, bears S and N, 20 lks. dist., thence W.
19.905	Point for the C-E 1/16 sec. cor. of sec. 34.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p>T5S R24E C $\frac{E\ 1/16}{S\ 34}$ C 1977</p>
	Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.
	From this point a fence cor., bears N. 89°50' W., 18 lks. dist.; fences extend S and W.
39.81	The C¼ sec. cor. of sec. 34.
49.20	Markham Wash, 50 lks. wide, 1 ft. deep, drains SW.
52.30	Track road, bears N. 20° E. and S. 50° W.
59.735	Point for the C-W 1/16 sec. cor. of sec. 34.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p>T5S R24E C $\frac{W\ 1/16}{S\ 34}$ C 1977</p>
	Raise a mound of stone, 2½ ft. base, 2½ ft. high, N of the cor.
	From this point a fence cor., bears S. 85° W., 92 lks. dist.; fences extend N and E.
79.66	The point for the ¼ sec. cor. of secs. 33 and 34.
<p>Subdivision of Section 36, T. 5 S., R. 24 E., Gila and Salt River Meridian, Arizona.</p>	
	From the stan. ¼ sec. cor. of sec. 36, on the S bdy. of the Tp.
	N. 0°18' E., on the N and S center line of sec. 36.
	Ascending a SW slope, through medium undergrowth.
2.80	Ridge, bears S. 85° E. and N. 85° W.
16.90	Ridge, bears N. 85° E. and S. 85° W.
40.30	Point for the C¼ sec. cor. of sec. 36, at intersection with the E and W center line.

Subdivision of Section 36, T. 5 S., R. 24 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T5S R24E C¼ S36 1977</p> <p>Cor. is located on a small spur, sloping SW.</p>	
47.40	Billingsly Creek, 150 lks. wide, 3 ft. deep, drains SW.	
49.90	Fence, bears N. 50° E. and S. 50° W.	
80.50	The ¼ sec. cor. of secs. 25 and 36.	
	<p>From the ¼ sec. cor. of secs. 31 and 36, on the E bdy. of Tp., monumented with an iron post, 1 inch diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1920-21 resurvey and with a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <p>N. 89°24' W., on the E and W center line of sec. 36.</p> <p>Over broken rolling land, through medium undergrowth.</p>	
18.985	<p>Point selected for the witness C-E 1/16 sec. cor. of sec. 36.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">W C T5S R24E E 1/16 C ← S 36 → C 1977</p>	
19.785	Point for the C-E 1/16 sec. cor. of sec. 36, falls in the center of a wash, 30 lks. wide, 3 ft. deep, drains westerly, where it is impractical to monument.	
39.57	The C¼ sec. cor. of sec. 36.	
79.10	The ¼ sec. cor. of secs. 35 and 36.	
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>Section 8 of this survey is located 4 miles southeast of Fort Thomas, Arizona. The general elevation of this township ranges from about 2730 to 3550 feet above sea level. The soil is a rocky, sandy loam in the eastern half and a rich, silty, clay loam in the western half, much of which is under cultivation.</p>	

General Description T. 5 S., R. 24 E., G&SRM, Arizona

CHAINS

The drainage of the east half is generally south westerly into the Gila River which flows northerly through the west portion of the township;

Access is by way of U.S. Highway No. 70 which crosses the southwest corner of the township on a SE and NW direction. There are several bladed and graded roads throughout the township.

Several dwellings are located along the Gila River, including the small community of Eden, located in sections 28 and 33. The historical Indian Hot Springs is located in the NE $\frac{1}{4}$ of sec. 17.

The vegetation consists of willows, salt cedar and cotton wood trees along the Gila River and irrigation canals, with creosote, mesquite and cacti scattered throughout the remainder of the township that is not under cultivation.

There is no evidence of mining activity in the area.

The mean of a considerable number of observations of the magnetic declination throughout the township is 13°30' E., with a range of 1° in local attraction.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Survey Aid
John J. Bulinski	Survey Aid
Duane R. Ferneau	Survey Aid
Dirk L. Peterson	Survey Aid
Charles J. Nelson	Survey Aid

CERTIFICATE OF SURVEY

(I) (~~W~~), Harry K. Smith, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of January, 1977, (I) (~~W~~) have dependently resurveyed a portion of the south boundary (First Standard Parallel South), and a portion of the subdivisional lines; and surveyed the subdivision in sections 8, 17, 21, 27, 28, 34 and 36, Township 5 South, Range 24 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~u~~) and under (my) (~~o~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

August 9, 1978
(Date)

Harry K. Smith
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the south boundary (First Standard Parallel South), and a portion of the subdivisional lines; and survey of the subdivisions in section 8, 17, 21, 27, 28, 34 and 36 of Township 5 South, Range 24 East, of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

OCT 11 1978
(Date)

Bernard W. J. Lopez
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626