

Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF PORTIONS OF THE

SOUTH, EAST, AND NORTH BOUNDARIES,

AND A

PORTION OF THE SUBDIVISIONAL LINES,

AND THE SURVEY OF THE SUBDIVISION OF CERTAIN SECTIONS OF

TOWNSHIP 11 NORTH, RANGE 18 EAST,

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

HARRY K. SMITH,

CADASTRAL SURVEYOR

PAUL L. REEVES,

CADASTRAL SURVEYOR

Under special instructions dated JUNE 3, 19 77, approved JUNE 3, 1977,

_____, which provided for the surveys included under U.S. Survey/Group
Number 599, and assignment instructions dated JUNE 3, 1977.

AND AUGUST 15, 1977.

Survey commenced JUNE 20, 19 77

Survey completed NOVEMBER 22, 19 77

1A

BOOK 5071

INDEX DIAGRAM

Township 11N., Range 18E.

17 6	15 55 5 54	14 53 4 52	12 48 3 47	11 39 2 38	9 28 1
7	8	51 9 50	46 10 45	36 11 36	27 12 26
18	17	16	15 44	35 14 34	25 13 23
19	20	21	42 22 41	32 23 31	21 24 8 21
30	29	28	27	31 26 29	20 25 6 19
31	32	33	34	28 35 4	18 36 5 2

Section Subdivision

Section Page

- 2 ----- 56-60
- 3 ----- 60-67
- 4 ----- 67-69
- 5 ----- 70-73
- 9 ----- 73-75
- 11 ----- 75-78
- 13 ----- 78-79
- 22 ----- 79-85
- 23 ----- 85-89
- 24 ----- 89-93
- 25 ----- 93-95
- 26 ----- 95-96
- 35 ----- 96-97
- 36 ----- 97-98

General Description ----- page 98-99

1.β

Township 11 North, Range 18 East,
Gila and Salt River Mer., Arizona

CHAINS

The history of surveys of Township 11 North, Range 18 East, Gila and Salt River Meridian, Arizona, is as follows:

The township boundaries and subdivisional lines were surveyed by H. A. Coe in 1883. A portion of the south and west boundaries and a portion of the subdivisional lines were resurveyed by S. E. Blout in 1915. A portion of the west boundary was resurveyed by A. N. Kimmell in 1935. The east boundary was resurveyed by R. F. Wilson in 1936.

The following field notes describe the dependent resurvey of portions of the south, east, and north boundaries and a portion of the subdivisional lines and the survey of the subdivision of certain sections of T. 11 N., R. 18 E., Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 599, Arizona, dated June 3, 1977.

The history of dependent resurveys in this township has revealed numerous discrepancies in the original survey of 1883 regarding bearing trees. Sidney E. Blout, in 1915, and Roger F. Wilson, in 1936, both recorded gross inaccuracies in the original record between found monuments and found bearing trees. This resurvey also revealed that the original record had errors regarding species, size and the position of bearing trees. Therefore, original monuments, when found, were always accepted and remonumented in their original position; however, when only one bearing tree was found and the description of this one tree varied from the record, the corner point was reestablished by the rules for proportionate measurement. This procedure gave results which made the corner positions more harmoniously related with the original survey.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances were measured with electronic distance measuring equipment.

The geographic position of the southeast corner of the township, as scaled from the U.S. Geological Survey quadrangle map CLAY SPRINGS, ARIZ., prepared in 1961, is as follows:

Latitude 34°18.0' N. Longitude 110°22.4' W.

Township 11 North, Range 18 East,
Gila and Salt River Mer., Arizona

CHAINS

The mean magnetic declination is 14°00' E.

Dependent Resurvey of a Portion of the South Boundary,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona.

(Restoring the 1883 survey by H. A. Coe)

Beginning at the cor. of Tps. 10 and 11 N., Rs. 18 and 19 E., monumented with an iron post, 3 ins. diam., projecting 6 ins. above a mound of stone, 3 ft. base, 8 ins. high, with brass cap mkd. as described in the official record of the 1936 resurvey of the S. bdy. of T. 11 N., R. 19 E., from which

A yellow pine stump, 48 ins. diam., mkd. in 1883, bears N. 30 1/2° E., 90 lks. dist., no marks are visible.

A stump hole, bears S. 25° E., 69 lks. dist.; an uprooted oak tree, 8 ins. diam., mkd. in 1883, is lying alongside, mkd. with an open blaze.

A pine stump, 24 ins. diam., mkd. in 1936, bears S. 42 1/2° W., 46 lks. dist., no marks are visible.

A stump hole, bears N. 27° W., 34 lks. dist.; an uprooted oak tree, 12 ins. diam., mkd. in 1936, is lying alongside, mkd. T11N R18E S36 BT.

from which new bearing trees

A ponderosa pine, 7 ins. diam., bears N. 70° E., 78 lks. dist., mkd. T11N R19E S31 BT.

A ponderosa pine, 7 ins. diam., bears S. 51° E., 52 lks. dist., mkd. T10N R19E S6 BT.

A ponderosa pine, 7 ins. diam., bears S. 18° W., 30 lks. dist., mkd. T10N R18E S1 BT.

A ponderosa pine, 10 ins. diam., bears N. 88° W., 75 lks. dist., mkd. T11N R18E S36 BT.

Add the marks 1977 on the brass cap.

N. 89°55' W., bet. secs. 1 and 36.

Over rolling land, through dense timber.

39.97

The 1/4 sec. cor. of secs. 1 and 36, monumented with a granite stone, 13 x 9 x 2 ins., firmly set in a mound of stone, 2 1/2 ft. base, 6 ins. high, mkd. 1/4 on the N face.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS

At the cor. point.

Set an iron post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.

T11N R18E
S36
1/4 ———
S 1
T10N
1977

from which

A ponderosa pine, 9 ins. diam., bears N. 4° E.,
57 lks. dist., mkd. 1/4 S36 BT.

A ponderosa pine, 9 ins. diam., bears S. 22 1/2° W.,
10 lks. dist., mkd. 1/4 S1 BT.

Desposit the mkd. stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 1 ft. high, N of the
cor.

West, beginning new measurement.

39.75

The cor. of secs. 1, 2, 35 and 36, monumented with a
granite stone, 14 x 10 x 6 ins., firmly set 7 ins. in
the ground, mkd. with 1 groove on the E and 5 grooves
on the W faces, from which

A yellow pine, 16 ins. diam., mkd. in 1915,
bears N. 44° E., 143 lks. dist.; mkd.
T11N R18E S36 BT.

A yellow pine, 26 ins. diam., mkd. in 1883,
bears S. 42 3/4° E., 101 lks. dist., mkd.
T10N R18E S1 BT.

A pine stump, 32 ins. diam., mkd. in 1915,
bears S. 4 1/2° W., 67 lks. dist., mkd. with
a charred blaze.

A pine stump, 19 ins. diam., mkd. in 1915, bears
N. 81 1/2° W., 84 lks. dist., no marks are
visible.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.

T11N R18E
S35| S36
S 2| S 1
T10N
1977

Dependent Resurvey of a Portion of the S Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
40.02	<p>from which new bearing trees</p> <p>A ponderosa pine, 9 ins. diam., bears S. 41 1/2° W., 73 lks. dist., mkd. T10N R18E S2 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 80 1/2° W., 44 lks. dist., mkd. T11N R18E S35 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <hr/> <p>(Restoring the 1915 resurvey by Sidney E. Blout)</p> <hr/> <p>N. 89°58' W., bet. secs. 2 and 35.</p> <p>Over rolling land, through dense timber.</p> <p>The 1/4 sec. cor. of secs. 2 and 35, monumented with a granite stone, 17 x 12 x 5 ins., loosely set in a mound of stone, 2 ft. base, 8 ins. high, mkd. 1/4 one the N face, from which the original bearing trees</p> <p>A stump hole, bears S. 57 1/2° W., 18 lks. dist.; an uprooted pine, 11 ins. diam., is lying along- side, mkd. 1/4 S2 BT.</p> <p>A yellow pine, 11 ins. diam., bears N. 66 1/2° W., 19 lks. dist., mkd. 1/4 S35 BT. (Record bearing: N. 72 1/4° W.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S35 1/4 ——— S 2 T10N 1977</p>	
40.00	<p>from which a new bearing tree</p> <p>A yellow pine, 14 ins. diam., bears S. 69 1/2° W., 20 lks. dist., mkd. 1/4 S2 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.</p> <hr/> <p>N. 89°53' W., beginning new measurement.</p> <p>The cor. of secs. 2, 3, 34 and 35, monumented with a granite stone, 19 x 9 x 7 ins., firmly set 16 ins. in the ground, mkd. with 2 grooves on the E and 4 grooves on the W faces, from which</p>	

Dependent Resurvey of a Portion of the S Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>An oak, 15 ins. diam., mkd. in 1883, bears N. 4 3/4° E., 28 lks. dist., mkd. with visible but illegible scribe marks.</p> <p>A pine stump, 30 ins. diam., mkd. in 1915, bears S. 75° E., 161 lks. dist., mkd. T10N R18E S2 BT.</p> <p>A yellow pine, 26 ins. diam., mkd. in 1883, bears S. 15 1/2° W., 25 lks. dist., mkd. T10N R18E S3 BT.</p> <p>A pine, stump, 32 ins. diam., mkd. in 1915, bears N. 41 3/4° W., 136 lks. dist., mkd. T11N R18E S34 BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T11N R18E S34 S35 S 3 S 2 T10N 1977 </p> <p>from which new bearing trees</p> <p>A ponderosa pine, 9 ins. diam., bears N. 58° E., 146 lks. dist., mkd. T11N R18E S35 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S. 83 1/2° E., 55 lks. dist., mkd. T10N R18E S2 BT.</p> <p>A ponderosa pine, 23 ins. diam., bears S. 40° W., 35 lks. dist., mkd. T10N R18E S3 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 35° W., 57 lks. dist., mkd. T11N R18E S34 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, E of the cor. due to the cor. location.</p> <p>Cor. is located at the E edge of a dim track road, bears SW and NW in a curve.</p>
	<p>Dependent Resurvey of a Portion of the E Bdy. of T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>
	<p>(Restoring the 1936 resurvey by Roger F. Wilson)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of Tps. 10 and 11 N., Rs. 18 and 19 E. N. 0°04' W., bet secs. 31 and 36.</p> <p>Over rolling land, through dense timber.</p>
19.40	Forest Service road No. 161, dirt surface, bears E and W.
19.815	Point for the S 1/16 sec. cor. of secs. 31 and 36.

Dependent Resurvey of a Portion of the E Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam.,
22 ins. in the ground, with brass cap mkd.

T11N
S 1/16
R18E | R19E
S36 | S31
1977

from which

A pine, 15 ins. diam., bears S. 65 1/2° E.,
123 lks. dist., mkd. S 1/16 S31 BT.

A pine, 11 ins. diam., bears S. 3 1/2° W.,
126 lks. dist., mkd. S 1/16 S36 BT.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high,
W of the cor.

39.63

The 1/4 sec. cor. of secs. 31 and 36, monumented with
an iron post, 1 in. diam., projecting 8 ins. above
ground, with brass cap mkd. as described in the official
record of the 1936 resurvey of the W bdy. of T. 11 N.,
R. 19 E., from which the bearing trees mkd. in 1936

A pine, 16 ins. diam., bears S. 39 1/4° E., 48 lks.
dist., mkd. with a healed blaze. (record bearing:
S. 46 1/2° E.)

A pine, 21 ins. diam., bears S. 51 1/4° W., 40 lks.
dist., mkd. with a healed blaze.

The cor. is on a steep S slope.

From the cor. of secs. 25, 30, 31 and 36, on the E bdy.
of Tp., monumented with an iron post, 2 ins. diam.,
projecting 12 ins. above ground, with brass cap mkd. as
described in the official record of the 1936 resurvey of
the W bdy. of T. 11 N., R. 19 E., from which

An oak, 9 ins. diam., mkd. in 1936, bears
N. 43° E., 59 lks. dist., mkd. T11N R19E S30 BT.
(Record, S. 43° W., 167 lks. dist.)

An oak, 17 ins. diam., mkd. in 1883, bears
S. 68° E., 63 lks. dist., mkd. with a healed
blaze.

An oak, 11 ins. diam., mkd. in 1936, bears
S. 17 1/2° W., 170 lks. dist., mkd. with a healed
blaze. (Record dist., 59 lks.)

A pine, 20 ins. diam., mkd. in 1936, bears
N. 84 1/2° W., 35 lks. dist., mkd.
T11N R18E S25 BT.

Cor. is 45 lks. E of a wash, 10 lks. wide, 3 ft. deep,
drains N. 25° W., curving N, and 110 lks. E of a track
road, bears N. 10° E. and S. 20° W.

N. 0°09' W., bet secs. 25 and 30.

Over rolling land, through dense timber.

Dependent Resurvey of a Portion of the E Bdy.,
T. 11 N., R. 8 E., Gila and Salt River Mer., Arizona

CHAINS	
20.015	<p>Point for the S 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N S 1/6 R18E R19E S25 S30 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 27 1/2° E., 55 lks. dist., mkd. S 1/16 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 31 1/2° W., 86 lks. dist., mkd. S 1/6 S25 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
21.00	<p>Graded dirt road, bears S. 25° E. and N. 25° W.</p>
40.03	<p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., bent over and projecting 6 ins. above the ground, with brass cap. mkd. as described in the official record of the 1936 resurvey of the W bdy. of T. 11 N., R. 19 E., from which</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., mkd. in 1883, bears S. 79° E., 26 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A juniper stump, 18 ins. diam., mkd. in 1936, bears S. 6° E., 71 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A juniper stump, 20 ins. diam., mkd. in 1936, bears S. 1 1/2° W., 71 lks. dist., mkd. BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N 1/4 R18E R19E S25 S30 1977</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 15° E., 58 lks. dist., mkd. 1/4 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 11° W., 56 lks. dist., mkd. 1/4 S25 BT.</p> <p>Reset the 1 in. iron post, inverted, alongside the new monument.</p>

Dependent Resurvey of a Portion of the E Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS

40.12

Raise a mound of stone, 3 1/2 ft. base, 1 ft. high,
W of the cor.

The cor. is 50 lks. E of a graded dirt road, bears
N. 10° E. and S. 10° W.

N. 0°31' E., beginning new measurement.

The cor. of secs. 19, 24, 25 and 30, monumented with an
iron post, 2 ins. diam., projecting 4 ins. above a
mound of stone, 5 ft. base, 2 1/2 ft. high, with brass
cap mkd. as described in the official record of the 1936
resurvey of the W bdy. of T. 11 N., R. 19 E., from which

A pine, 18 ins. diam., mkd. in 1883, bears
N. 51 1/2° E., 67 lks. dist., mkd.
T11N R19E S19 BT.

A pine, 30 ins. diam., mkd. in 1936, bears
S. 78° E., 138 lks. dist., mkd. T11N R19E S30 BT.

A pine stump, 24 ins. diam., mkd. in 1883, bears
S. 38° E., 120 lks. dist., mkd. BT.

A pine, 30 ins. diam., mkd. in 1883, bears
N. 41° W., 61 lks. dist., mkd. T11N R18E S24 BT.

A new bearing tree, a pine, 9 ins. diam., bears
S. 39° W., 74 lks. dist., mkd. T11N R18E S25 BT.

Add the marks 1977 to the brass cap.

From the 1/4 sec. cor. of secs. 19 and 24, on the E bdy.
of the Tp., monumented with an iron post, 1 in. diam.,
12 ins. long, bent over level with the ground and broken
off, from which the bearing trees mkd. in 1883

A yellow pine, 30 ins. diam., bears N. 72 1/2° E.,
26 lks. dist., mkd. 1/4 S19 BT. (Record
dist., 30 lks.)

A yellow pine, 30 ins. diam., bears S. 12° W.,
67 lks. dist., mkd. 1/4 S24 BT.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam.,
18 ins. in the ground and in a mound of stone, 3 ft.
base, to top, with brass cap mkd.

T11N
1/4
R18E | R19E
S24 | S19
1977

Reset the 1 in. iron post alongside the new monument.

Cor. is at the S edge of a dim logging road, bears E
and W.

N. 0°05' E., bet. secs. 19 and 24.

Over rolling land, through dense to medium timber.

Dependent Resurvey of a Portion of the E Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
28.00	Track road, bears N. 75° E. and S. 75° W.	
40.22	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., projecting 4 ins. above the ground, with brass cap mkd. as described in the official record of the 1936 resurvey of the W bdy. of T. 11 N., R. 19 E., from which</p> <p>A juniper, 11 ins. diam., mkd. in 1883, bears N. 54 1/2° E., 69 lks. dist., mkd. T11N R19E S18 BT.</p> <p>A ponderosa pine, 20 ins. diam., mkd. in 1883, bears S. 45° E., 96 lks. dist., mkd. T11N R19E S19 BT.</p> <p>A pine stump, 24 ins. diam., mkd. in 1883, bears S. 39 1/2° W., 88 lks. dist., no marks are visible.</p> <p>A ponderosa pine, 19 ins. diam., mkd. in 1936, bears N. 46 1/2° W., 78 lks. dist., mkd. T11N R18E S13 BT.</p> <p>A new bearing tree, a ponderosa pine, 10 ins. diam., bears S. 5°45' W. 124 lks. dist., mkd. T11N R18E S24 BT.</p> <p>Add the marks 1977 to the brass cap.</p>	
<p>Dependent Resurvey of a Portion of the N Bdy. of T. 11 N., R. 18 E., Gila and Salt River Meridian, Arizona</p>		
<p>(Restoring the 1883 survey by H. A. Coe)</p>		
<p>From the cor. of Tps. 11 and 12 N., Rs. 18 and 19 E., monumented with an iron post, 3 ins. diam., projecting 8 ins. above a mound of stone, 3 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1936 resurvey of the W bdy. of T. 11 N., R. 19 E., from which</p> <p>A juniper, 12 ins. diam., mkd. in 1883, bears N. 66°45' E., 35 lks. dist., mkd. T12N R19E S31 BT. (Record: an oak, bearing N. 73° E.)</p> <p>An alligator juniper, 15 ins. diam., mkd. in 1936, bears S. 48 1/2° E., 101 lks. dist., mkd. T11N R19E S6 BT. (Record dist., 79 lks.)</p> <p>A stump hole, bears S. 31° E., 74 lks. dist.; an uprooted pine, 12 ins. diam., mkd. in 1883, is lying alongside, mkd. T11N R18E S6 BT.</p> <p>An oak, 9 ins. diam., mkd. in 1936, bears S. 44 1/2° W., 79 lks. dist., mkd. with a healed blaze.</p> <p>An alligator juniper, 12 ins. diam., mkd. in 1936, bears N. 13°45' W., 116 lks. dist., mkd. T12N R18E S36 BT. (Record dist., 118 lks.)</p> <p>S. 89°57' W., bet. secs. 1 and 36.</p> <p>Over rolling land, through medium to dense timber.</p>		

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
40.02	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T12N R18E S36 1/4 ——— S 1 T11N 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N. 42° E., 42 lks. dist., mkd. 1/4 S36 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears S. 53° W., 11 lks. dist., mkd. 1/4 S1 BT.</p>
60.00	<p>Enter open grass land, bears N and S.</p>
80.04	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence conforming to the original record.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R18E S35 S36 S 2 S 1 T11N 1977</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 25° E., 9 lks. dist., mkd. T12N R18E S36 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S. 40° E., 115 lks. dist.; fences extend N and E.</p> <p style="padding-left: 40px;">A juniper 13 ins. diam., bears S. 29° W., 74 lks. dist., mkd. T11N R18E S2 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 18 ins. diam., bears N. 68 1/2° W., 96 lks. dist., mkd. T12N R18E S35 BT.</p> <p>From this point a juniper, 18 ins. diam., bears S. 12° E., 98 lks. dist., mkd. T11N R18E S1 BT on a partially healed blaze. (Record, a yellow pine, 4 ins. diam., S. 16 1/2° E., 274 lks. dist.)</p> <p>From the same point a local cor., bears N. 17°09' W., 177 lks. dist., monumented with an open end metal pipe, 1 1/2 ins. diam., projecting 15 ins. above ground.</p> <p>Cor. is 30 lks. N of a dirt road, bearing irregularly E and W.</p>

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	S. 89°57' W., bet. secs. 2 and 35.	
	Over rolling land, through medium to dense timber.	
36.00	Dirt road, bears N and S.	
36.40	Fence, bears N and S; enter open grass land.	
40.02	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T12N R18E S35 1/4 ——— S 2 T11N 1977	
	from which	
	A ponderosa pine, 10 ins. diam., bears S. 78 1/4° E., 361 lks. dist., mkd. X at breast height and BT at the base.	
	A ponderosa pine, 12 ins. diam., bears S. 26° W., 361 lks. dist., mkd. 1/4 S2 BT.	
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.	
42.50	Wash, 35 lks. wide, 6 ft. deep, drains N. 55° E.	
42.80	Power line, bears N and S.	
43.00	Enter medium to dense timber, bears N and S.	
80.04	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence conforming to the original record.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T12N R18E S34 S35 S 3 S 2 T11N 1977	
	from which	
	A ponderosa pine, 6 ins. diam., bears N. 22° E., 42 lks. dist., mkd. T12N R18E S35 BT.	
	A ponderosa pine, 7 ins. diam., bears S. 50° E., 42 lks. dist., mkd. T11N R18E S2 BT.	
	A ponderosa pine, 7 ins. diam., bears S. 38 1/2° W., 41 lks. dist., mkd. T11N R18E S3 BT.	

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 6 ins. diam., bears N. 62 1/2° W., 47 lks. dist., mkd. T12N R18E S34 BT.</p> <p>From this point, a local cor., bears S. 51° W., 94 lks. dist., monumented with an open end pipe, 1 1/2 ins. diam., projecting 18 ins. above a mound of stone, 1 1/2 ft. base, 6 ins. high.</p> <p>From this same point a dead pine, 32 ins. diam., bears S. 63 1/2° W., 205 lks. dist., mkd. T11N R18E S3 BT. (Record, a yellow pine, 14 ins. diam., bears N. 63° W., 115 lks. dist., mkd. T12N R18E S34 BT)</p>
20.01	<p>S. 89°57' W., bet. sec. 3 and 34.</p> <p>Over rolling land, through medium to dense timber.</p> <p>Point for the E 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R18E S34 E 1/16 — S 3 T11N 1977</p>
	<p>from which</p>
	<p>A ponderosa pine, 11 ins. diam., bears N. 11° E., 7 lks. dist., mkd. E 1/16 S34 BT.</p>
	<p>A ponderosa pine, 7 ins. diam., bears S. 80° E., 63 lks. dist., mkd. E 1/16 S3 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>
22.50	<p>Cor. is 45 lks. N of a dim logging road, bears E and W.</p>
23.30	<p>Trail road, bears N and S.</p>
23.30	<p>Ridge, bears N and S.</p>
30.015	<p>Point for the W-E 1/64 sec. cor. of secs. 3 and 34.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S34 W-E 1/64 S 3 1977</p>
	<p>from which</p>
	<p>A ponderosa pine, 9 ins. diam., bears S. 10° E., 26 lks. dist., mkd. W E 1/64 S3 BT.</p>
	<p>A ponderosa pine, 8 ins. diam., bears N. 8° W., 44 lks. dist., mkd. W E 1/64 S34 BT.</p>

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
39.00	Old highway No. 160, gravel surfaced, bears N and S.	
40.02	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T12N R18E S34 1/4 — S 3 T11N 1977</p>	
	from which	
	A fence cor., bears N. 75° E., 36 lks. dist.; fences extend S and W.	
	A ponderosa pine, 8 ins. diam., bears N. 81° E., 165 lks. dist., mkd. X at breast height and BT at the base.	
	A ponderosa pine, 8 ins. diam., bears N. 18° W., 29 lks. dist., mkd. 1/4 S34 BT.	
56.00	Dirt road, bears N. 15° E. and S. 15° W.	
60.03	Point for the W 1/16 sec. cor. of secs. 3 and 34.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T12N R18E S34 W 1/16 — S 3 T11N 1977</p>	
	from which	
	A ponderosa pine, 6 ins. diam., bears N. 40 1/2° E., 68 lks. dist., mkd. W 1/16 S34 BT.	
	A ponderosa pine, 5 ins. diam., bears S. 15° E., 39 lks. dist., mkd. W 1/16 S3 BT.	
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.	
	Cor. is at the S edge of a track road, bears E and W.	
64.30	Power line, bears N and S.	
80.04	The cor. of secs. 3, 4, 33 and 34, monumented with a sandstone, 12 x 10 x 8 ins., mkd. with 3 notches on the E and W edges, set in a mound of stone, 2 ft. base, 6 ins. high, from which	

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS

A stump hole, bears N. 5 1/4° E., 88 lks. dist.,
a yellow pine, 22 ins. diam., lying alongside
is mkd. T12N R18E S33 BT. (Record, a juniper,
10 ins. diam., bears N. 15° E., 100 lks. dist.,
mkd. T12N R18E S34 BT)

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins.
in the ground, to solid rock, and in a mound of stone,
2 ft. base, to top, with brass cap mkd.

T12N R18E
S33|S34
S 4 | S 3
T11N
1977

from which new bearing trees

A ponderosa pine, 6 ins. diam., bears N. 60 1/2° E.,
72 lks. dist., mkd. T12N R18E S34 BT.

A ponderosa pine, 5 ins. diam, bears S. 50° E.,
23 lks. dist., mkd. T11N R18E S3 BT.

A ponderosa pine, 6 ins. diam., bears S. 34 1/2° W.,
60 lks. dist., mkd. T11N R18E S4 BT.

A ponderosa pine, 6 ins. diam., bears N. 53 1/2° W.,
73 lks. dist., mkd. T12N R18E S33 BT.

Deposit the mkd. stone alongside the iron post.

Cor. is in a fence cor.; fences extend N and W, with an
abandoned fence E.

S. 89°18' W., bet. secs. 4 and 33.

Over rolling land, through medium to dense timber,
along an E-W fence.

40.04

The 1/4 sec. cor. of secs. 4 and 33, monumented with
a mound of stone, 2 ft. base, 1 ft. high.

At the center of the mound

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

T12N R18E
S33
1/4 —
S 4
T11N
1977

from which a new bearing tree

A pinyon, 5 ins. diam., bears S. 15° W., 34 lks.
dist., mkd. 1/4 S4 BT.

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
	40.09	<p>Deposit broken glass at the base of the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N of the cor.</p> <p>Cor. is in an E-W fence, 25 lks. S of a track road that parallels the fence.</p> <p>From this point a juniper, 14 ins. diam., not of record, bears N. 32° W., 12 lks. dist., mkd. 1/4 S BT.</p> <hr/> <p>N. 89°58' W., beginning new measurement.</p> <p>Along an E-W fence.</p> <p>The cor. of secs. 4, 5, 32 and 33, monumented with a sandstone, 8 x 6 x 6 ins., mkd. with 4 grooves on the E and 2 grooves on the W faces, set in a mound of stone, 2 1/2 ft. base, 6 ins. high, from which</p> <p style="padding-left: 40px;">A pinyon, 12 ins. diam., bears S. 45° W., 29 lks. dist., mkd. T11N R18E S5 BT. (Record, a juniper, 15 ins. diam., bears S. 50° W., 81 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T12N R18E S32 S33 S 5 S 4 T11N 1977</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 54° E., 108 lks. dist., mkd. T12N R18E S33 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 59° E., 15 lks. dist., mkd. T11N R18E S4 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears N. 37 1/2° W., 53 lks. dist., mkd. T12N R18E S32 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is in an E-W fence.</p>	
	10.00	<p>N. 89°51' W., bet. secs. 5 and 32.</p> <p>Over rolling land, through medium to dense timber, along an E-W fence.</p> <p>Point for the E-E 1/64 sec. cor. of secs. 5 and 32.</p>	

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S32 E-E 1/64 S 5 1977</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 41° E., 21 lks. dist., mkd. E E 1/64 S32 BT.</p>
	<p style="padding-left: 40px;">A fence cor., bears S. 49° E., 5 lks. dist.; fences extend easterly and southerly.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 6° E., 28 lks. dist., mkd. E E 1/64 S5 BT.</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, N of the cor.</p>
11.80	<p>Track road, bears N. 5° E. and S. 5° W.</p>
20.00	<p>Point for the E 1/16 sec. cor. of secs. 5 and 32.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R18E S32 E 1/16 — S 5 T11N 1977</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 83° W., 72 lks. dist., mkd. E 1/16 S5 BT.</p>
	<p style="padding-left: 40px;">A fence cor., bears S. 66° E., 6 lks. dist., fences extend S and W.</p>
	<p>Thence along an E-W fence.</p>
40.00	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a sandstone, 14 x 8 x 8 ins., mkd. 1/4 on the N face, set in a mound of stone, 2 1/2 ft. base, 6 ins. high.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T12N R18E S32 1/4 — S 5 T11N 1977</p>

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
	40.22	<p>from which</p> <p>An alligator juniper, 8 ins. diam., bears N. 58 1/2° E., 20 lks. dist., mkd. 1/4 S32 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 12° W., 38 lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N of the cor.</p> <p>Cor. is 3 lks. S of an E-W fence.</p> <hr/> <p>S. 89°57' W., beginning new measurement.</p> <p>Along an E-W fence.</p> <p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R18E S31 S32 S 61 S 5 T11N 1977</p> <p>from which</p> <p>An alligator juniper, 8 ins. diam., bears N. 39° E., 109 lks. dist., mkd. T12N R18E S32 BT.</p> <p>A juniper, 6 ins. diam., bears S. 34 1/2° E., 224 lks. dist., mkd. T11N R18E S5 BT.</p> <p>An alligator juniper, 8 ins. diam., bears S. 73° W., 98 lks. dist., mkd. T11N R18E S6 BT.</p> <p>An alligator juniper, 12 ins. diam., bears N. 12 1/2° W., 121 lks. dist., mkd. T12N R18E S31 BT.</p> <p>Cor. is 19 lks. S of an E-W fence and 130 lks. E of a dirt road, bearing N. 35° E. and S. 35° W.</p>	
	40.22	<p>S. 89°57' W., bet. secs. 6 and 31.</p> <p>Over rolling land, through medium to dense timber.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a sandstone, 10 x 8 x 6 ins., firmly set 4 ins. in the ground, mkd. 1/4 on the N face, from which</p> <p>A juniper, 38 ins. diam., bears N. 16° W., 17 lks. dist., mkd. 1/4 S BT. (Record, a juniper 14 ins. diam., bears N. 15° W., 60 lks. dist.)</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of the N Bdy.,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	<p>Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T12N R18E S31 1/4 — S 6 T11N 1977</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 11 ins. diam., bears S. 59° E., 17 lks. dist., mkd. 1/4 S6 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S. 85° E., 132 lks. dist.; fences extend E, S, NW and irregularly W.</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines of T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>
	<p>(Restoring the 1883 survey by H. A. Coe)</p> <hr style="width: 20%; margin: auto;"/> <p>From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the Tp.</p> <p>N. 0°03' W., bet. secs. 35 and 36.</p> <p>Over rolling land, through dense timber.</p>
17.00	Forest Service road No. 161, bears N. 85° E. and S. 85° W.
39.60	Small draw, drains S. 65° E.
40.01	<p>Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no evidence of the ori- ginal cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S35 S36 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 58 1/2° E., 57 lks. dist., mkd. 1/4 S36 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 48 1/4° W., 56 lks. dist., mkd. 1/4 S35 BT.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>60.70 Spur, slopes easterly.</p> <p>80.02 The cor. of secs. 25, 26, 35 and 36, monumented with a scattered mound of stone, verified by an original bearing tree, an alligator juniper, 38 ins. diam., mkd. T11N R18E S25 BT, bears N. 42 1/2° E., 68 lks. dist.</p> <p>At the center of the mound</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E S26 S25 S35 S36 1977</p> </div> <p>from which new bearing trees</p> <p>A pine, 8 ins. diam., bears S. 40° E., 104 lks. dist., mkd. T11N R18E S36 BT.</p> <p>A pine, 6 ins. diam., bears S. 36 1/4° W., 90 lks. dist., mkd. T11N R18E S35 BT.</p> <p>A pine, 14 ins. diam., bears N., 74° W., 109 lks. dist., mkd. T11N R18E S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p>	
39.81	<p>From the cor. of secs. 25, 30, 31 and 36, on the E bdy. of the Tp.</p> <p>N. 89°30' W., bet. secs. 25 and 36.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E S25 1/4 — S36 1977</p> </div> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S. 50° W., 3 1/2 lks. dist., mkd. 1/4 S36 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 24 1/2° W., 56 lks. dist., mkd. 1/4 S25 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, E of the cor. to prevent erosion.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is on a steep W slope, about 1 ch. E of Miller Canyon, which drains northerly.</p>	
79.63	<p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°30' E., bet. secs. 25 and 26.</p> <p>Over rolling land, through dense timber.</p>	
9.00	<p>Dirt road, bears N. 80° E. and S. 80° W.</p>	
39.91	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a sandstone, 14 x 12 x 10 ins., firmly set in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on the W face, from which an original bearing tree</p> <p style="padding-left: 40px;">A dead yellow pine, 15 ins. diam., bears S. 85° W., 52 lks. dist., mkd. 1/4 S BT. (Record bearing, S. 75 1/2° W.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S26 S25 1977</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 49° E., 90 lks. dist., mkd. 1/4 S25 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 89° W., 57 lks. dist., mkd. 1/4 S26 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>N. 0°01' E., beginning new measurement.</p>	
39.93	<p>The cor. of secs. 23, 24, 25 and 26, monumented with a granite stone, 16 x 7 x 5 ins., firmly set 9 ins. in the ground, mkd. with 1 groove on the E and 2 grooves on the S faces, from which an original bearing tree</p> <p style="padding-left: 40px;">A pine stump, 26 ins. diam., bears S. 60° E., 38 lks. dist., mkd. with visible but illegible scribe marks through a partially healed blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S23 S24 S26 S25 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>from which new bearing trees</p> <p>A ponderosa pine, 15 ins. diam., bears N. 58° E., 153 lks. dist., mkd. T11N R18E S24 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S. 5° E., 183 lks. dist., mkd. T11N R18E S25 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 34 1/2° W., 109 lks. dist., mkd. T11N R18E S26 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 38 1/2° W., 80 lks. dist., mkd. T11N R18E S23 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30, on the E bdy. of the Tp.</p> <p>N. 89°43' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through dense timber.</p>	
	39.75	<p>Point for the 1/4 sec. cor. of secs. 24 and 25, at propor- tionate dist.; there is no remaining evidence of the ori- ginal cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S24 1/4 — S25 1977</p>	
		<p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears N. 11° E., 46 lks. dist., mkd. 1/4 S24 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 77° W., 26 lks. dist., mkd. 1/4 S25 BT.</p>	
	45.00	Dirt road, bears NE and SW.	
	69.00	Wash, 20 lks. wide, 3 ft. deep, drains N, curving W.	
	79.51	The cor. of secs. 23, 24, 25 and 26.	
		<hr/> <p>N. 0°19' E., bet. secs. 23 and 24.</p> <p>Over rolling land, through medium timber, partially burned.</p>	
	36.50	Dirt road, bears NE and SW.	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
39.99	<p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 18 x 9 x 3 ins., firmly set in a mound of stone, 3 ft. base, 1 1/2 ft. high, mkd. 1/4 on the W face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S23 S24 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°12' W., beginning new measurement.</p>	
2.70	<p>Dirt road, bears SE and NW.</p>	
9.99	<p>Point for the S-N 1/64 sec. cor. of secs. 23 and 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S-N 1/64 S23 S24 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 31° W., 114 lks. dist., mkd. S N 1/64 S23 BT.</p> <p style="padding-left: 40px;">A fence cor., bears S. 64° W., 43 lks. dist.; fences extend northerly and easterly.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of the cor.</p> <p>Cor. is 21 lks. N of an E-W fence.</p>	
19.98	<p>Point for the N 1/16 sec. cor. of secs. 23 and 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E N 1/16 S23 S24 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
	39.96	<p>from which</p> <p>An alligator juniper, 7 ins. diam., bears S. 17° W., 104 lks. dist., mkd. N 1/16 S23 BT.</p> <p>An alligator juniper, 3 ins. diam., bears N. 46 1/2° W., 31 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Cor. is in a N-S fence.</p> <p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S14 S13 S23 S24 1977</p>	
	40.12	<p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears N. 57° E., 60 lks. dist., mkd. T11N R18E S13 BT.</p> <p>A fence cor., bears S. 80° E., 76 lks. dist.; fences extend easterly and southerly.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 75° W., 58 lks. dist., mkd. T11N R18E S23 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N. 20° W., 62 lks. dist., mkd. T11N R18E S14 BT.</p> <hr/> <p>From the cor. of secs. 13, 18, 19 and 24, on the E bdy. of the Tp.</p> <p>S. 89°52' W., bet secs. 13 and 24.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S13 1/4 — S24 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A pinyon pine, 9 ins. diam, bears N. 52 1/2° E., 39 lks. dist., mkd. 1/4 S13 BT.</p> <p>A juniper, 8 ins. diam., bears S. 31 1/2° E., 18 lks. dist., mkd. 1/4 S24 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N of the cor.</p>
49.60	Dirt road, bears NE and SW.
58.00	Dirt road, bears SE and NW.
58.30	Fence, bears SE and NW, 70 lks. dist., thence westerly.
60.18	Point for the W 1/16 sec. cor. of secs. 13 and 24.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S13 W 1/16 — S24 1977</p>
	<p>from which</p> <p>An alligator juniper, 5 ins. diam., bears N. 28° E., 33 lks. dist., mkd. W 1/16 S13 BT.</p> <p>A ponderosa pine, 4 ins. diam., bears S. 26° E., 18 lks. dist., mkd. W 1/16 S24 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p> <p>Cor. is 71 lks. S of an E-W fence.</p>
62.80	Dirt road, bears N. 10° E. and S. 10° W.
70.21	Point for the W-W 1/64 sec. cor. of secs. 13 and 24.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S13 W-W 1/64 S24 1977</p>
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N. 62° E., 62 lks. dist., mkd. W W 1/64 S13 BT.</p> <p>An alligator juniper, 8 ins. diam., bears S. 55° E., 60 lks. dist., mkd. W W 1/64 S24 BT.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
80.24	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N of the cor.</p> <p>Cor. is 69 lks. S of an E-W fence.</p> <p>The cor. of secs. 13, 14, 23 and 24.</p>	
3.50	<p>N. 0°35' E., bet. secs. 13 and 14.</p> <p>Over rolling land, through dense timber.</p> <p>Dirt road, bears S. 70° E. and N. 70° W.</p>	
39.95	<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S14 S13 1977</p>	
48.00	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>Cor. is in a burned area.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N.</p>	
52.30	<p>Dirt road, bears N. 60° E. and S. 60° W.</p>	
59.30	<p>Dirt road, bears N. 25° E. and S. 25° W.</p>	
79.90	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a sandstone, 13 x 5 x 3 ins., firmly set 6 ins. in the ground, mkd. with 1 notch on the E and 4 notches on the S edges, from which an original bearing tree</p> <p style="text-align: center;">A juniper, 30 ins. diam., bears S. 55° W., 35 lks. dist., mkd. T11N R18E S14 BT. (Record bearing, S. 71° W.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S11 S12 S14 S13 1977</p> <p>from which new bearing trees</p> <p style="text-align: center;">A pinyon pine, 8 ins. diam., bears N. 23° E., 89 lks. dist., mkd. T11N R18E S12 BT.</p> <p style="text-align: center;">A pinyon pine, 8 ins. diam., bears S. 36 1/2° E., 72 lks. dist., mkd. T11N R18E S13 BT.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	<p>CHAINS</p>	<p>A juniper, 8 ins. diam., bears N. 38° W., 107 lks. dist., mkd. T11N R18E S11 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>From the cor. of secs. 7, 12, 13 and 18, on the E bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1936 resurvey of the W bdy. of T. 11 N., R. 19 E., from which the bearing trees mkd. in 1936</p> <p>A juniper, 28 ins. diam., bears N. 55 3/4° E., 185 lks. dist., mkd. T11N R19E S7 BT.</p> <p>A juniper, 52 ins. diam., bears S. 76 1/2° E., 215 lks. dist., mkd. T11N R19E S18 BT.</p> <p>A juniper, 15 ins. diam., bears N. 17° W., 19 lks. dist., mkd. T11N R18E S12 BT.</p> <p>Cor. is 2 lks. N of a fence cor.; fences extend S and W.</p> <p>S. 89°29' W., bet secs. 12 and 13.</p> <p>Over rolling land, along an E-W fence.</p> <p>39.77 Point for the 1/4 sec. cor. of secs. 12 and 13, at the NW edge of a fence cor.; fences extend southerly and easterly. This position has been established as the 1/4 sec. cor. for many years, is harmoniously related to identified original cors. in the immediate area, and is accepted as the best available evidence of the ori- ginal cor. positions. From this point</p> <p>A juniper stump, 20 ins. diam., bears S. 17°45' W., 89 lks. dist., mkd. BT. (Record bearing and dist., S. 25° W., 100 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S12 1/4 — S13 1977</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 5 ins. diam., bears S. 8 1/2° W., 51 lks. dist., mkd. 1/4 S13 BT.</p> <p>A juniper, 6 ins. diam., bears N. 3°45' W., 90 lks. dist., mkd. 1/4 S12 BT.</p>
--	---------------	--

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p> <p style="text-align: center;">—————</p> <p>S. 89°17' W., beginning new measurement.</p>	
1.30	Dirt road, bears S. 10° E. and N. 10° W.	
2.00	Enter medium to dense timber, bears N and S.	
39.83	The cor. of secs. 11, 12, 13 and 14.	
	<p>N. 1°24' W., bet. secs. 11 and 12.</p> <p>Over rolling land, through dense timber.</p>	
29.90	Abandoned highway No. 160, gravel surfaced, bears N. 60° E. and S. 60° W.	
39.70	<p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S11 S12 1977</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon pine, 6 ins. diam., bears N. 5° E., 40 lks. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 56° W., 30 lks. dist., mkd. 1/4 S11 BT.</p>	
57.50	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>State Highway No. 260, asphalt surfaced, bears S. 85° E. and N. 85° W.</p>	
79.40	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a sandstone, 11 x 9 x 4 ins., firmly set in a mound of stone, 2 ft. base, 6 ins. high, mkd. with 1 notch on the E and 5 notches on the S edges, from which</p> <p style="padding-left: 40px;">A juniper, 16 ins. diam., bears S. 37° E., 50 lks. dist., mkd. T11N R18E S12 BT. (Record bearing and dist., S. 8° E., 128 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T11N R18E S 2 S 1 S11 S12 1977</p> <p>from which new bearing trees</p> <p>A pine, 10 ins. diam., bears N. 37° E., 15 lks. dist., mkd. T11N R18E S1 BT.</p> <p>A pine, 12 ins. diam., bears S. 64° E., 17 lks. dist., mkd. T11N R18E S12 BT.</p> <p>A pine, 6 ins. diam., bears S. 39° W., 5 lks. dist., mkd. T11N R18E S11 BT.</p> <p>An alligator juniper, 6 ins. diam., bears N. 70° W., 16 lks. dist., mkd. T11N R18E S2 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p>	
40.54	<p>N. 1°06' E., bet. secs. 1 and 2.</p> <p>Over rolling land, through medium to dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
81.32	<p style="text-align: center;">T11N R18E 1/4 S 2 S 1 1977</p> <p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears S. 3° E., 68 lks. dist., mkd. 1/4 S1 BT.</p> <p>An alligator juniper, 8 ins. diam., bears S. 88° W., 59 lks. dist., mkd. 1/4 S2 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <p>The cor. of secs. 1, 2, 35 and 36, on the N bdy. of the Tp., heretofore described.</p> <hr/> <p style="text-align: center;">(Restoring the resurvey by Sidney E. Blout in 1915)</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the Tp.</p> <p>N. 0°05' E., bet. secs. 34 and 35.</p> <p>Over rolling land, through dense timber.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
1.20	Forest Service road No. 161, bears NE and SW.	
18.10	Dirt road, bears S. 60° E. and N. 60° W.	
32.40	Dirt road, bears N. 50° E. and S. 50° W.	
33.60	Dirt road, bears N. 30° E. and S. 30° W.	
39.48	<p>The 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., projecting 8 ins. above a mound of stone, 3 ft. base, 8 ins. high, with brass cap mkd. as described in the official record of the 1915 resurvey, from which the bearing trees mkd. in 1915</p> <p>An alligator juniper, 22 ins. diam., bears S. 67° E., 120 lks. dist., mkd. 1/4 S35 BT. (Record dist., 122 lks.)</p> <p>A dead pine, 20 ins. diam., bears N. 40° W., 65 lks. dist., mkd. 1/4 S34 BT.</p> <p>and a new bearing tree</p> <p>A pine, 7 ins. diam., bears S. 54 1/4° W., 19 lks. dist., mkd. 1/4 S34 BT.</p> <p>Add the marks 1977 to the brass cap.</p> <hr/> <p>(Restoring the 1883 survey by H. A. Coe)</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°18' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through dense timber.</p>	
7.70	Dirt road, at a curve, bears N. 20° E. and S. 10° E.	
19.955	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S26 E 1/16 — S35 1977</p> <p>from which</p> <p>A pine, 8 ins. diam., bears S. 9 1/4° E., 53 lks. dist., mkd. E 1/16 S35 BT.</p> <p>A pine, 12 ins. diam., bears N. 30 1/4° W., 15 lks. dist., mkd. E 1/16 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p> <p>Cor. is 2.00 chs. S of a gully draining N. 75° W.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
39.91	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S26 1/4 — S35 1977</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 89° W., 37 lks. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 36° W., 70 lks. dist., mkd. 1/4 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p>
47.60	Track road, bears N and S.
72.20	Track road, bears N. 20° E. and S. 20° W.
79.82	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., projecting 6 ins. above ground, set at the base of the original tree cor., with brass cap mkd. as described in the official record of the 1915 resurvey, from which</p> <p style="padding-left: 40px;">An oak, 18 ins. diam., mkd. in 1915, bears N. 33°45' E., 85 lks. dist., mkd. with illegible scribe marks.</p> <p style="padding-left: 40px;">A pine stump, 24 ins. diam., mkd. in 1915, bears S. 69 1/2° E., 68 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A stump hole, bears S. 64° W., 74 lks. dist.; an uprooted pine, 18 ins. diam., mkd. in 1883, is lying alongside, mkd. T11N R18E S34 BT.</p> <p style="padding-left: 40px;">A pine stump, 18 ins. diam., mkd. in 1883, bears N. 45 1/2° W., 24 lks. dist.; no scribe marks are visible.</p> <p>and the new bearing trees</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 46 1/2° E., 23 lks. dist., mkd. T11N R18E S26 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 60° E., 77 lks. dist., mkd. T11N R18E S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 31 1/2° W., 50 lks. dist., mkd. T11N R18E S34 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears N. 72° W., 17 lks. dist., mkd. T11N R18E S27 BT.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Add the marks 1977 to the brass cap.</p> <hr/> <p>N. 0°10' E., bet. secs. 26 and 27. Over rolling land, through dense timber.</p>	
39.63	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with a sandstone, 18 x 15 x 6 ins., firmly set 18 ins. in the ground, mkd. 1/4 on the W face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S27 S26 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>Cor. is in a burned area.</p> <hr/> <p>N. 0°19' W., beginning new measurement.</p> <p>Over a burned area.</p>	
1.30	<p>Track road, bears NE and SW.</p>	
39.89	<p>The cor. of secs. 22, 23, 26 and 27, monumented with a granite stone, 13 x 8 x 6 ins., firmly set 5 ins. in the ground, mkd. with 2 grooves on the E and S faces, from which the remains of an original bearing tree</p> <p style="text-align: center;">A charred pine stump, 20 ins. diam., bears N. 76° E., 29 lks. dist., mkd. T11N R18E, through a partially healed and burned blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S22 S23 S27 S26 1977</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <hr/> <p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°04' W., bet. secs. 23 and 26.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	Over rolling land, through a burned area.	
33.30	Dirt road, bears N. 15° E. and S. 15° W.	
40.14	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T11N R18E S23 1/4 — S26 1977</p>	
	from which	
	A ponderosa pine, 11 ins. diam., bears N. 19° W., 94 lks. dist., mkd. 1/4 S23 BT.	
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of the cor.	
65.60	Track road, bears N. 5° E. and S. 5° W.	
80.27	The cor. of secs. 22, 23, 26 and 27.	
	N. 0°22' W., bet. secs. 22 and 23.	
	Over rolling land, through a burned area.	
19.825	Point for the S 1/16 sec. cor. of secs. 22 and 23.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T11N R18E S 1/16 S22 S23 1977</p>	
	Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of the cor.	
	Cor. is in a burned area.	
39.65	The 1/4 sec. cor. of secs. 22 and 23, monumented with a sandstone, 20 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. 1/4 on the W face.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T11N R18E 1/4 S22 S23 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears N. 77 1/2° W., 120 lks. dist., mkd. 1/4 S22 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°03' E., beginning new measurement.</p>	
	11.20	Dirt road, bears N. 40° E. and S. 40° W.	
	20.06	<p>Point for the N 1/16 sec. cor. of secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E N 1/16 S22 S23 1977</p>	
	24.00	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <p>N edge of burned area, enter medium to dense timber, edge bears E and W.</p>	
	40.12	<p>The cor. of secs. 14, 15, 22 and 23, monumented with an oak post, 4 ft. long, 4 ins. squared, firmly set 12 ins. in the ground, from which</p> <p>A dead pine, 29 ins. diam., bears S. 52° E., 17 lks. dist., mkd. T11N R18E S23. (Record bearing and dist., S. 15° E., 174 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S15 S14 S22 S23 1977</p>	
		<p>from which the new bearing trees</p> <p>A ponderosa pine, 5 ins. diam., bears N. 46° E., 14 lks. dist., mkd. T11N R18E S14 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears S. 42 1/2° E., 97 lks. dist., mkd. T11N R18E S23 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 80° W., 90 lks. dist., mkd. T11N R18E S22 BT.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
39.92	<p>A ponderosa pine, 11 ins. diam., bears N. 46 1/2° W., 43 lks. dist., mkd. T11N R18E S15 BT.</p> <p>Invert and reset the oak post alongside the iron post.</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24. S. 88°58' W., bet. secs. 14 and 23. Over rolling land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.,; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S14 1/4 — S23 1977</p> <p>from which</p> <p style="text-align: center;">A fence cor., bears S. 6 1/2° E., 105 lks. dist.; fences extend southerly and westerly.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p> <p>Cor. is in a burned area, 20 lks. N of a dirt road, bears N. 65° E. and S. 65° W., curving northwesterly.</p>
59.88	<p>Point for the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S14 W 1/16 — S23 1977</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 10 ins. diam., bears N. 30° E., 63 lks. dist., mkd. W 1/16 S14 BT.</p> <p style="text-align: center;">A ponderosa pine, 7 ins. diam., bears N. 54 1/2° W., 59 lks. dist., mkd. W 1/16 S14 BT.</p> <p>Cor. is 55 lks. N of an E-W fence.</p>
64.87	<p>Point for the E-W-W 1/256 sec. cor. of secs. 14 and 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S14 E-W-W 1/256 S23 1977</p> <p>from which</p> <p>A fence cor., bears S. 12° E., 46 lks. dist.; fences extend easterly and southerly.</p> <p>A ponderosa pine, 5 ins. diam., bears S. 37° W., 113 lks. dist., mkd. E W W 1/256 S23 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 44° W., 62 lks. dist., mkd. E W W 1/256 S14 BT.</p>	
68.70	Dirt road, bears N and S.	
79.84	The cor. of secs. 14, 15, 22 and 23.	
	<hr/> <p>N. 1°00' E., bet. secs. 14 and 15.</p> <p>Over rolling land, through medium to dense timber.</p>	
8.00	Dirt road, bears NE and SW.	
20.00	Enter open grass land, edge bears E and W.	
38.00	Enter dense timber, edge bears E and W.	
40.31	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S15 S14 1977</p> <p>from which</p> <p>A ponderosa pine, 23 ins. diam., bears S. 12° E., 142 lks. dist., mkd. 1/4 S14 BT.</p> <p>A ponderosa pine, 26 ins. diam., bears N. 84° W., 51 lks. dist., mkd. 1/4 S15 BT.</p>	
80.62	<p>Point for the cor. of secs. 10, 11, 14 and 15, at propor- tionate dist.; there is no remaining evidence of the origi- nal cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S10 S11 S15 S14 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N. 79° E., 42 lks. dist., mkd. T11N R18E S11 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 24° E., 66 lks. dist., mkd. T11N R18E S14 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 54° W., 60 lks. dist., mkd. T11N R18E S15 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 36 1/2° W., 18 lks. dist., mkd. T11N R18E S10 BT.</p> <p>From this point a local cor., bears S. 84° W., 157 lks. dist., monumented with an open end pipe, 2 ins. diam., projecting 12 ins. above ground.</p>
39.60	<p>From the cor. of secs. 11, 12, 13 and 14. S. 89°30' W., bet. secs. 11 and 14. Over rolling land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14, at pro- portionate dist.; there is no evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S11 1/4 — S14 1977</p>
70.00	<p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears S. 20° W., 37 lks. dist., mkd. 1/4 S14 BT.</p> <p>A juniper, 5 ins. diam., bears N. 53° W., 40 lks. dist., mkd. 1/4 S11 BT.</p> <p>Dirt road, bears S. 30° E. and N. 30° W.</p>
79.20	<p>The cor. of secs. 10, 11, 14 and 15.</p>
14.50	<p>N. 1°38' W., bet secs. 10 and 11. Over rolling land, through medium timber.</p> <p>Dirt road, bears S. 25° E. and N. 25° W.</p>
26.70	<p>Dirt road, bears S. 70° E. and N. 70° W.</p>
34.20	<p>Dirt road, bears N. 40° E. and S. 40° W.</p>
40.32	<p>Point for the 1/4 sec. cor. of secs. 10 and 11, at pro- portionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S10 S11 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 19° E., 62 lks. dist., mkd. 1/4 S11 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 35° W., 30 lks. dist., mkd. 1/4 S10 BT.</p>	
52.70		State Highway No. 260, asphalt surfaced, bears S. 70° E. and N. 70° W., thence through scattering timber.	
60.48		<p>Point for the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E N 1/16 S10 S11 1977</p> <p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 8 1/2° W., 16 lks. dist.; fences extend N and E.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 66° W., 115 lks. dist., mkd. N 1/16 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 22° W., 73 lks. dist., mkd. N 1/16 S10 BT.</p> <p>Cor. is 53 lks. E of an abandoned N-S fence.</p> <p>From this point a local cor., bears S. 13° W., 16 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 3 ft. above ground.</p>	
80.64		<p>Point for the cor. of secs. 2, 3, 10 and 11, at proportionate dist., from which a dead pine, 36 ins. diam., bears N. 79 1/2° W., 194 lks. dist., mkd. T11N R18E. No trace of the original monument could be found at record bearing and dist. (S. 20° E., 70 lks. dist.) from this tree. Due to the numerous discrepancies reported in previous resurveys from the 1883 record to bearing trees from found cor. monuments, which were also found in this resurvey, this tree was not used to reestablish the sec. cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 3 S 2 S10 S11 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS

from which

A ponderosa pine, 5 ins. diam., bears S. 63° W.,
33 lks. dist., mkd. T11N R18E S10 BT.

A ponderosa pine, 11 ins. diam., bears N. 38° W.,
81 lks. dist., mkd. T11N R18E S3 BT.

Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W
of the cor.

Cor. is 31 lks. W of an old N-S fence and 37 lks. E
of a new N-S fence.

From this point a local cor., bears S. 57° E., 45 lks.
dist., monumented with an open end metal pipe, projecting
12 ins. above ground.

From the cor. of secs. 1, 2, 11 and 12.

S. 89°47' W., bet. secs. 2 and 11.

Over rolling land, through dense to medium timber.

25.00 Old Highway No. 160, gravel surface, bears SE and NW.

36.50 Old Highway No. 160, gravel surface, bears NE and SW.

39.79 The 1/4 sec. cor. of secs. 2 and 11, monumented with a
granite stone, 12 x 8 x 8 ins., firmly set 8 ins. in the
ground, mkd. 1/4 on the N face, from which

A dead juniper, 8 ins. diam., bears S. 79 1/2° E.,
35 lks. dist., mkd. 1/4 S BT. (Record, a pine,
13 ins. diam., bears S. 24° E., 57 lks. dist.)

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins.
in the ground to solid rock, and in a mound of stone,
4 ft. base, to top, with brass cap mkd.

T11N R18E
S 2
1/4 —
S11
1977

from which

A ponderosa pine, 12 ins. diam., bears N. 34° E.,
18 lks. dist., mkd. 1/4 S2 BT.

An alligator juniper, 12 ins. diam., bears
S. 35° W., 21 lks. dist., mkd. 1/4 S11 BT.

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	N. 89°00' W., beginning new measurement.
3.50	Old Highway No. 160, gravel surface, bears S. 60° E. and N. 60° W.
9.40	Fence, bears N and S.
9.94	Point for the E-W 1/64 sec. cor. of secs. 2 and 11, is 5 lks. E of the center of a dirt road, bearing S. 20° E. and N. 20° W.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 31 ins. in the ground, with brass cap mkd.
	S 2 E-W 1/64 S11 1977
	from which
	A juniper, 12 ins. diam., bears N. 5°45' E., 99 lks. dist., mkd. E W 1/64 S2 BT.
	A ponderosa pine, 12 ins. diam., bears S. 54 1/2° E., 36 lks. dist., mkd. E W 1/64 S11 BT.
	Deposit broken glass at the base of the iron post.
	From this point a local cor., bears N. 38°30' E., 110.5 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 12 ins. above ground.
17.00	Enter open grass land, edge bears N and S.
19.88	Point for the W 1/16 sec. cor. of secs. 2 and 11, not monumented.
24.50	Fence, bears N and S.
39.76	The cor. of secs. 2, 3, 10 and 11.
	N. 0°45' E., bet. secs. 2 and 3.
	Over nearly level land, through scattering timber.
19.00	Enter rolling land, covered with dense timber.
20.15	Point for the S 1/16 sec. cor. of secs. 2 and 3.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T11N R18E S 1/16 S 3 S 2 1977
	from which
	A juniper, 5 ins. diam., bears S. 48° W., 25 lks. dist., mkd. S 1/16 S3 BT.

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	Cor. is 29 lks. W of a N-S fence.
30.225	Point for the N-S 1/64 sec. cor. of secs. 2 and 3.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	N-S
	1/64
	S 3/S 2
	1977
	from which
	A juniper, 5 ins. diam., bears N. 51° E., 82 lks. dist., mkd. N S 1/64 S2 BT.
	A ponderosa pine, 6 ins. diam., bears N. 29° W., 62 lks. dist., mkd. N S 1/64 S3 BT.
	Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of the cor.
	Cor is 65 lks. W of a N-S fence.
	From this point a local cor., bears S. 11° W., 41.4 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 30 ins. above ground.
30.40	Fence, bears NE and SW.
40.30	Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground to solid rock, and in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.
	T11N R18E
	1/4
	S 3/S 2
	1977
	from which
	A ponderosa pine, 6 ins. diam., bears S. 19° E., 25 lks. dist., mkd. 1/4 S2 BT.
	A pinyon pine, 5 ins. diam., bears N. 78° W., 28 lks. dist., mkd. 1/4 S3 BT.
60.45	Point for the N 1/16 sec. cor. of secs. 2 and 3, at pro- portionate dist.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T11N R18E
	N 1/6
	S 3/S 2
	1977

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>from which</p> <p>A juniper, 8 ins. diam., bears N. 81° E., 6 lks. dist., mkd. N 1/16 S2 BT.</p> <p>A pinyon pine, 8 ins. diam., bears S. 63° W., 16 lks. dist., mkd. N 1/16 S3 BT.</p> <p>Cor. is at the S edge of a juniper, 20 ins. diam.</p>	
	80.67	<p>The cor. of secs. 2, 3, 34 and 35, on the N bdy. of the Tp., heretofore described.</p>	
	20.12	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 88°36' W., bet sec. 22 and 27.</p> <p>Over rolling land, through a burned area.</p> <p>Point for the E 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S22 E 1/16 — S27 1977</p>	
	21.50	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p> <p>Cor. is in a burned area.</p> <p>Forest Service road, No. 107, dirt surface, bears NE and SW.</p>	
	40.24	<p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S22 1/4 — S27 1977</p>	
	41.10	<p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of the cor.</p> <p>Wash, 10 lks. wide, 2 ft. deep, drains N.</p>	
	60.36	<p>Point for the W 1/16 sec. cor. of secs. 22 and 27.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
80.48	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S22 W 1/16 — S27 1977</p> <p>Raise a mound of stone, 3 ft. base 1 1/2 ft. high, N of the cor.</p> <p>Cor. is in a burned area.</p> <p>The cor. of secs. 21, 22, 27 and 28, monumented with a ponderosa pine, 19 ins. diam., mkd. T11N R18E S22 on the NE face, healed blazes on the SE and SW faces, and S21 on the NW face, from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., mkd. in 1915, bears N. 22° E., 21 lks. dist., mkd. T11N R18E S22.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., mkd. in 1883, bears S. 62 1/2° E., 16 lks. dist., mkd. T11N R18E S27.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., mkd. in 1915, bears S. 53° W., 61 lks. dist., mkd. T11N R18E S28.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., mkd. in 1883, bears N. 56°45' W., 31 lks. dist., mkd. T11N R18E S21.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 10 ins. in the ground, to solid rock and in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 44° W., 7.6 lks. dist., with brass cap mkd. T11N R18E S28 RM 5 FT. 1977 and an arrow pointing to the cor.</p>
20.00	<p>N. 0°20' E., bet. secs. 21 and 22.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the S 1/16 sec. cor. of secs. 21 and 22.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 1/16 S21 S22 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 80° E., 4 lks. dist., mkd. S 1/16 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 51° W., 71 lks. dist., mkd. S 1/16 S21 BT.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
30.60	Dirt road, bears S. 70° E. and N. 70° W.	
40.00	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a sandstone, 22 x 12 x 4 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. 1/4 on the E face, from which</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S. 70° W., 60 lks. dist., mkd. BT. (Record, a yellow pine, 5 ins. diam., bears S. 86° W., 60 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S21 S22 1977</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 48° E., 65 lks. dist., mkd. 1/4 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 50° W., 3 lks. dist., mkd. 1/4 S21 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°11 W., beginning new measurement.</p>	
24.10	Dirt road, bears SE and NW.	
39.85	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an oak post, 4 ft. long, 3 ins. squared, firmly set 12 ins. in a mound of stone, 2 1/2 ft. base, 1 ft. high, from which</p> <p style="padding-left: 40px;">An oak, 13 ins. diam., bears S. 72° E., 20 lks. dist., mkd. with a healed blaze and BT at the base. (Record, a yellow pine, 28 ins. diam., bears S. 10° E., 90 lks. dist.)</p> <p style="padding-left: 40px;">An oak, 8 ins. diam., bears S. 60° W., 77 lks. dist., mkd. with a healed blaze and BT at the base. (Record, an oak, 16 ins. diam., bears S. 8° W., 21 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S16 S15 S21 S22 1977</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which new bearing trees</p> <p>A ponderosa pine, 9 ins. diam., bears N. 9 1/2° E., 64 lks. dist., mkd. T11N R18E S15 BT.</p> <p>An alligator juniper, 5 ins. diam., bears S. 13° E., 11 lks. dist., mkd. T11N R18E S22 BT.</p> <p>An alligator juniper, 6 ins. diam., bears S. 61 1/2° W., 28 lks. dist., mkd. T11N R18E S21 BT.</p> <p>A ponderosa pine, 11 ins. diam., bears N. 9° W., 59 1/2 lks. dist., mkd. T11N R18E S16 BT.</p> <p>Invert and reset the wood post alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
<p>7.10</p> <p>17.40</p> <p>21.40</p> <p>34.60</p> <p>40.06</p>	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>N. 88°32' W., bet. secs. 15 and 22.</p> <p>Over rolling land, through dense timber.</p> <p>Forest Service road No. 107, dirt surface, bears NE and SW.</p> <p>Dirt road, bears S. 60° E. and N. 60° W.</p> <p>Dirt road, bears NE and SW.</p> <p>Dirt road, bears N. 65° E. and S. 65° W.,</p> <p>Point for the 1/4 sec. cor. of secs. 15 and 22, at pro- portionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S15 1/4 — S22 1977</p>
<p>51.70</p>	<p>from which</p> <p>An alligator juniper, 12 ins. diam., bears N. 19° E., 57 lks. dist., mkd. 1/4 S15 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 27 1/2° W., 68 lks. dist., mkd. 1/4 S22 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p> <p>Cor. is 2.50 chs. N of a dirt road, bearing N. 60° E. and S. 60° W.</p> <p>Same dirt road, bears S. 20° E. and N. 20° W.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
59.50	Same dirt road, bears NE and SW.
71.80	N end of a dirt road, projects S.
80.13	The cor. of secs. 15, 16, 21 and 22.
	From the cor. of secs. 10, 11, 14 and 15.
	S. 89°50' W., bet. secs. 10 and 15.
	Over rolling land, through dense timber.
32.70	Top of ridge, bears N. 10° E. and S. 10° W.
39.70	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T11N R18E \\ S10 \\ 1/4 \text{ ---} \\ S15 \\ 1977 \end{array}$
	from which
	A ponderosa pine, 5 ins. diam., bears N. 87° E., 12 lks. dist., mkd. 1/4 S10 BT.
	A ponderosa pine, 9 ins. diam., bears S. 70 1/2° W., 34 lks. dist., mkd. 1/4 S15 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.
79.40	The cor. of secs. 9, 10, 15 and 16, monumented with a sandstone, 12 x 10 x 4 ins., firmly set in a mound of stone, 3 ft. base, 1 ft. high, mkd. with 3 notches on the E and 4 notches on the S edges.
	At the cor. point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$\begin{array}{r} T11N R18E \\ S 9 S10 \\ S16 S15 \\ 1977 \end{array}$
	from which
	A juniper, 5 ins. diam., bears N. 26 1/4° E., 81 lks. dist., mkd. T11N R18E S10 BT.
	An alligator juniper, 16 ins. diam., bears S. 86 1/4° E., 56 lks. dist., mkd. T11N R18E S15 BT.

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
5.00	<p>An alligator juniper, 7 ins. diam., bears S. 42 1/2° W., 36 lks. dist., mkd. T11N R18E S16 BT.</p> <p>An alligator juniper, 5 ins. diam., bears N. 53 1/4° W., 68 lks. dist., mkd. T11N R18E S9 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
39.75	<p>N. 2°06' W., bet. secs. 9 and 10.</p> <p>Over rolling land, through dense timber.</p> <p>Bladed road, not in use, bears S. 70° E. and N. 80° W.</p> <p>The 1/4 sec. cor. of secs. 9 and 10, monumented with a ponderosa pine, 18 ins. diam., mkd. 1/4 S on the W face, from which new accessories</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 12.2 lks. dist., with brass cap mkd. T11N R18E S10 1/4 RM 8 FT. 1977 and an arrow pointing to the cor.</p> <p>A ponderosa pine, 8 ins. diam., bears S. 58 1/2° W., 37 lks. dist., mkd. 1/4 S9 BT.</p>
20.17	<p>N. 1°22' W., beginning new measurement.</p> <p>Point for the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E N 1/16 S 9 S10 1977</p> <p>from which</p> <p>An alligator juniper, 6 ins. diam., bears S. 23° E., 12 lks. dist., mkd. N 1/16 S10 BT.</p> <p>An alligator juniper, 5 ins. diam., bears S. 21° W., 46 lks. dist., mkd. N 1/16 S9 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p>
20.40	<p>Fence, bears S. 70° E. and N. 70° W.</p>
21.90	<p>State Highway No. 260, bears S. 70° E. and N. 70° W.</p>
23.40	<p>Fence, bears S. 70° E. and N. 70° W.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
	40.34	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a rotted wooden hub, 6 ins. long, 1 1/2 ins. squared, set in a scattered mound of stone, verified by the remains of an original bearing tree</p> <p>A stump hole, bears S. 37° E., 73 lks. dist.; a downed pine, 36 ins. diam., mkd. T11N R18E S3 BT, is lying alongside.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 4 S 3 S 9 S10 1977</p> <p>from which</p> <p>A fence cor., bears S. 14° E., 72 lks. dist.; fences extend easterly and southerly.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 4° E., 24 lks. dist., mkd. T11N R18E S10 BT.</p> <p>Deposit the wood hub alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p>	
		<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>S. 88°28' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through dense timber.</p>	
	4.80	<p>Dirt road, bears N. 20° E. and S. 20° W.</p>	
	39.71	<p>The 1/4 sec. cor. of secs. 3 and 10, a stump hole, with the cor. tree, a pine 9 ins. diam., mkd. 1/4 S lying alongside.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 3 1/4 — S10 1977</p> <p>from which</p> <p>An alligator juniper, 8 ins. diam., bears S. 20 1/2° W., 38 lks. dist., mkd. 1/4 S10 BT.</p> <p>An alligator juniper, 8 ins. diam., bears N. 80° W., 56 lks. dist., mkd. 1/4 S3 BT.</p>	

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cut out the 1 ft. section of the cor. tree containing the blaze and set it alongside the iron post.</p>
	<p>N. 89°36' W., beginning new measurement.</p>
19.10	<p>Dirt road, bears N. 25° E. and S. 25° W.</p>
19.89	<p>Point for the W 1/16 sec. cor. of secs. 3 and 10.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R18E S 3 W 1/16 — S10 1977</p>
	<p>from which</p>
	<p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears N. 30° E., 103 lks. dist., mkd. W 1/16 S3 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 16 1/2° W., 47 lks. dist., mkd. W 1/16 S10 BT.</p>
29.20	<p>Old fence, bears irregularly NE and SW.</p>
29.835	<p>Point for the W-W 1/64 sec. cor. of secs. 3 and 10.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S 3 W-W 1/64 S10 1977</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A pinyon pine, 5 ins. diam., bears N. 28° E., 21 lks. dist., mkd. W W 1/64 S3 BT.</p>
	<p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears S. 68° E., 23 lks. dist., mkd. W W 1/64 S10 BT.</p>
	<p>Cor. is on top of a ridge bearing NE and SW.</p>
39.78	<p>The cor. of secs. 3, 4, 9 and 10.</p>
	<hr/> <p>N. 0°21' E., bet. secs. 3 and 4.</p>
	<p>Over rolling land, through dense timber.</p>
4.70	<p>Enter nearly level, open grass land, edge bears N. 30° E. and S. 10° W.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
20.10	Enter medium to dense timber, edge bears N. 70° E. and S. 70° W.
20.385	<p>Point for the S 1/16 sec. cor. of secs. 3 and 4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 1/16 S 4 S 3</p> <p style="text-align: center;">1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 71° W., 62 lks. dist., mkd. S 1/16 S4 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of the cor.</p>
28.50	Wash, 45 lks. wide, 3 ft. deep, drains northeasterly.
33.80	Dirt road, bears N. 20° E. and S. 20° W.
40.77	<p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S 4 S 3</p> <p style="text-align: center;">1977</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 29° E., 46 lks. dist., mkd. 1/4 S3 BT.</p> <p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 13° W., 30 lks. dist., mkd. 1/4 S4 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of the cor.</p>
52.00	Top of a hill, slopes E.
55.10	Dirt road, bears N. 75° E. and S. 75° W.
61.155	<p>Point for the N 1/16 sec. cor. of secs. 3 and 4, at proportionate dist.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E N 1/16 S 4 S 3 1977</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
81.40	<p>from which</p> <p>A juniper, 5 ins. diam., bears N. 72° E., 13 lks. dist., mkd. N 1/16 S3 BT.</p> <p>A ponderosa pine, 5 ins. diam., bears S. 31° W., 43 lks. dist., mkd. N 1/16 S4 BT.</p> <p>The cor. of secs. 3, 4, 33 and 34, on the N bdy. of the Tp., heretofore described.</p>
40.37	<hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>West, bet. secs. 9 and 16.</p> <p>Over rolling land, through dense timber.</p> <p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a sandstone, 14 x 10 x 8 ins., set flush with the ground, mkd. 1/4 on the N face, from which an original bearing tree</p> <p>A ponderosa pine, 28 ins. diam., bears S. 20° W., 181 lks. dist., to the blaze, mkd. 1/4 S BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 9 1/4 — S16 1977</p> <p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears N. 20° E., 30.3 lks. dist., mkd. T11N R18E 1/4 S9 RM 20 FT. 1977 and an arrow pointing to the cor.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is located at the E edge of Forest Service road No. 124, and N. 5° E., 69 lks. dist., from a cattle guard.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°50' W., beginning new measurement.</p>
.20	<p>Forest Service road No. 124, bears S. 5° E. and N. 5° W.</p>
5.80	<p>Wash, 20 lks. wide, 6 ft. deep, drains northeasterly.</p>
40.20	<p>The cor. of secs. 8, 9, 16 and 17, a juniper, 16 ins. diam., mkd. T11N R18E S9 on the NE, S16 on the SE, S17 on the SW and S8 on the NW faces, from which</p> <p>A partially dead pinyon pine, 8 ins. diam., not of record, bears N. 30° W., 23 lks. dist., mkd. T11N R with the other markings deteriorated.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>and the new accessories</p> <p>A ponderosa pine, 13 ins. diam., bears N. 81° E., 91 lks. dist., mkd. T11N R18E S9 BT.</p> <p>A juniper, 8 ins. diam., bears S. 18° E., 74 lks. dist., mkd. T11N R18E S16 BT.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 71° W., 15 lks. dist., with brass cap mkd. T11N R18E S17 RM 9.9 FT. 1977 and an arrow pointing to the cor.</p> <p>A ponderosa pine, 5 ins. diam., bears N. 53 1/2° W., 43 lks. dist., mkd. X at breast height and BT at the base.</p>
	<p>N. 0°14' W., bet. secs. 8 and 9.</p> <p>Over rolling land, through dense to medium timber.</p>
24.30	Dirt road, bears N. 65° E. and S. 65° W.
40.29	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S 8 S 9 1977</p>
	<p>from which</p> <p>A ponderosa pine, 5 ins. diam., bears N. 19° E., 18 lks. dist., mkd. 1/4 S9 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 70° W., 13 lks. dist., mkd. 1/4 S8 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
46.80	State Highway No. 260, asphalt surfaced, bears E and W.
48.30	Fence, bears E and W.
59.30	Dirt road, bears S. 40° E. and N. 40° W.
80.58	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no acceptable evidence of the original cor. remaining.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 5 S 4 S 8 S 9 1977</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears N. 47° E., 29 lks. dist., mkd. T11N R18E S4 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 60° E., 12 lks. dist., mkd. T11N R18E S9 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 44 1/2° W., 30 lks. dist., mkd. T11N R18E S8 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears N. 87° W., 58 lks. dist., mkd. T11N R18E S5 BT.</p> <p>Deposit a granite stone, 10 x 7 x 2 ins. mkd. with 5 grooves on one face and 4 grooves on an adjacent face, alongside the iron post. This stone was found on top of a pine stump, 22 ins. diam., not of record, bearing S. 34° E., 175 lks. dist., mkd. BT.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10. N. 89°43' W., bet. secs. 4 and 9. Over rolling land, through dense timber.</p>
1.90	Enter nearly level, open grass land, edge bears N. 30° E. and S. 30° W.
9.81	Point for the E-E 1/64 sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>S 4 E-E 1/64 S 9 1977</p>
	<p>from which</p> <p>A ponderosa pine, 34 ins. diam., bears N. 32° W., 63 lks. dist., mkd. E E 1/64 S4 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the cor.</p>
14.00	Enter rolling land, covered with medium to dense timber, edge bears NE and SW.
19.62	Point for the E 1/16 sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p>T11N R18E S 4 E 1/16 — S 9 1977</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS	
		<p>from which</p> <p>A ponderosa pine, 7 ins. diam., bears N. 36° E., 36 lks. dist., mkd. E 1/16 S4 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 24 1/2° W., 19 lks. dist., mkd. E 1/16 S9 BT.</p> <p>A granite stone, of unknown origin, 20 x 15 x 10 ins., firmly set 10 ins. in the ground, bears S. 60° W., 94 lks. dist., mkd. K 15 on the W face.</p> <p>Deposit broken clear glass at the base of the iron post.</p>
22.00		Dirt road, bears N. 35° E. and S. 35° W.
39.24		<p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 4 1/4 — S 9 1977</p>
		<p>from which</p> <p>A ponderosa pine, 5 ins. diam., bears S. 62° W., 58 lks. dist., mkd. 1/4 S9 BT.</p> <p>A ponderosa pine, 19 ins. diam., bears N. 11 1/2° W., 54 1/2 lks. dist., mkd. 1/4 S4 BT.</p>
78.48		The cor. of secs. 4, 5, 8, and 9.
		<p>N. 0°49' W., bet. secs. 4 and 5.</p> <p>Over rolling land, through dense timber.</p>
40.29		<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E 1/4 S 5 S 4 1977</p>
		<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears S. 45° E. 42 lks. dist., mkd. 1/4 S4 BT.</p> <p>A pinyon pine, 8 ins. diam., bears N. 73° W., 33 lks. dist., mkd. 1/4 S5 BT.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
60.435	<p>Point for the N 1/16 sec. cor. of secs. 4 and 5, at proportionate dist.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E N 1/16 S 5/S 4</p> <p style="text-align: center;">1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 30° E., 67 lks. dist., mkd. N 1/16 S4 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 41° W., 69 lks. dist., mkd. N 1/16 S5 BT.</p>
80.48	<p>The cor. of secs. 4, 5, 32 and 33, on the N bdy. of the Tp., heretofore described.</p>
39.47	<hr/> <p>From the cor. of secs. 4, 5, 8 and 9.</p> <p>S. 86°38' W., bet. secs. 5 and 8.</p> <p>Over rolling land, through dense timber.</p> <p>The 1/4 sec. cor. of secs. 5 and 8, monumented with a sandstone, 7 x 6 x 4 ins., firmly set in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on the N face, from which</p> <p style="padding-left: 40px;">A dead pinyon pine, 15 ins. diam., bears S. 79° W., 66 lks. dist., mkd. 1/4 S BT. (Record bearing and dist., S. 38° W., 153 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E S 5 1/4 — S 8 1977</p> <p>from which the new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 36° W., 31 lks. dist., mkd. 1/4 S5 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p>
23.60	<hr/> <p>N. 89°01' W., beginning new measurement.</p> <p>State Highway No. 260, asphalt surfaced, bears SE and NW.</p>

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS					
40.59	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a sandstone, 8 x 4 x 6 ins., firmly set in a mound of stone, 2 ft. base, 8 ins. high, mkd. with 5 notches on the E and S edges, from which</p> <p style="padding-left: 40px;">A pine stump, 16 ins. diam., bears S. 40° E., 133 lks. dist., mkd. with a blaze, no scribe marks visible. (Record bearing and dist., S. 38° E., 145 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> </table> <p>1977</p> </div> <p>from which the new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 16 1/2° E., 71 lks. dist., mkd. T11N R18E S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 21° E., 28 lks. dist., mkd. T11N R18E S8 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 80° W., 35 lks. dist., mkd. T11N R18E S7 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 18 1/2° W., 64 lks. dist., mkd. T11N R18E S6 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of the cor.</p> <hr/> <p>N. 0°59' W., bet. secs. 5 and 6.</p> <p>Over rolling land, through dense to medium timber.</p>	S 6	S 5	S 7	S 8
S 6	S 5				
S 7	S 8				
11.60	State Highway No. 260, asphalt surfaced, bears SE and NW.				
39.30	Dim logging road, bears N. 10° E. and S. 10° W.				
41.25	<p>Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1/4</td> <td></td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 6</td> <td style="padding: 0 5px;">S 5</td> </tr> </table> <p>1977</p> </div>	1/4		S 6	S 5
1/4					
S 6	S 5				

Dependent Resurvey of Subdivisional Lines,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
82.18	<p>from which</p> <p>A ponderosa pine, 8 ins., diam., bears N. 79° E., 15 lks. dist., mkd. 1/4 S5 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 54° W., 13 lks. dist., mkd. 1/4 S6 BT.</p> <p>Cor. is 25 lks. W of a dim logging road, bearing N. 10° E. and S. 10° W.</p> <p>The cor. of secs. 5, 6, 31 and 32, on the N bdy. of the Tp., heretofore described.</p>
20.43	<p style="text-align: center;">Subdivision of Section 2, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 11. N. 0°56' E., on the N and S center line of sec. 2. Over rolling land, through dense timber.</p> <p>Point for the center S 1/16 sec. cor. of sec. 2. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C</p> <p>S 1/16 S 2</p> <p>C</p> <p>1977</p> </div>
40.86	<p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears N. 78° E., 41 lks. dist., mkd. C S 1/16 S2 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 53° W., 50 lks. dist., mkd. C S 1/16 S2 BT.</p> <p>Cor. is at the bottom of a draw, draining NW.</p> <p>Point for the center 1/4 sec. cor. of sec. 2, at inter- section with the E and W center line of sec. 2. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C 1/4 S 2</p> <p>1977</p> </div>
	<p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N. 18 1/2° E., 91 lks. dist., mkd. C 1/4 S2 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 78° W., 42 lks. dist., mkd. C 1/4 S2 BT.</p>

Subdivision of Section 2,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
81.43	<p>The 1/4 sec. cor. of secs. 2 and 35, on the N bdy. of the Tp.</p>	
	<p>From the 1/4 sec. cor. of secs. 1 and 2. N. 89°46' W., on the E and W center line of sec. 2. Over rolling land, through medium to dense timber.</p>	
39.90	<p>The center 1/4 sec. cor. of sec. 2.</p>	
59.84	<p>Point for the center W 1/16 sec. cor. of sec. 2.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E W 1/16 C-----C S 2 1977</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 82° W., 62 lks. dist., mkd. C W 1/16 S2 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 3° W., 14 lks. dist., mkd. C W 1/16 S2 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of the cor.</p> <p>From this point a local cor., bears N. 14° W., 38.5 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 42 ins. above ground.</p>	
69.81	<p>Point for the center W-W 1/64 sec. cor. of sec. 2.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 2 C-W-W 1/64 1977</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pinyon pine, 5 ins. diam., bears S. 44° W., 8 lks. dist., mkd. C W W 1/64 S2 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears N. 9° W., 14 lks. dist., mkd. C W W 1/64 S2 BT.</p> <p>Cor. is 59 lks. W of a fence, bearing NE and SW.</p> <p>From this point a local cor., bears S. 48° W., 23.6 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 36 ins. above ground.</p>	

Subdivision of Section 2,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
79.78	The 1/4 sec. cor. of secs. 2 and 3.
	<hr/> SW 1/4, Section 2 <hr/>
	From the point for the W 1/16 sec. cor. of secs. 2 and 11.
	N. 0°49' E., on the N and S center line of the SW 1/4 of sec. 2.
	Over nearly level land, through scattering timber.
10.145	Point for the center S-SW 1/64 sec. cor. of sec. 2.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 2 C-S-SW 1/64 1977
	from which
	A ponderosa pine, 8 ins. diam., bears N. 20 1/2° E., 27 lks. dist., mkd. C S SW 1/64 S2 BT.
	A ponderosa pine, 8 ins. diam., bears N. 76° E., 26 lks. dist., mkd. C S SW 1/64 S2 BT.
	A fence cor., bears S. 33 1/2° E., 70 lks. dist., fences extend N, S and E.
	Cor. is 40 lks. W of a N-S fence.
	From this point a local cor., bears N. 45° E., 55.3 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 36 ins. above ground.
20.29	Point for the SW 1/16 sec. cor. of sec. 2, at intersection with the E and W center line of the SW 1/4 of sec. 2.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T11N R18E SW 1/16 S2 1977
	from which
	A ponderosa pine, 10 ins. diam., bears S. 85° E., 15 lks. dist., mkd. SW 1/16 S2 BT.
	A ponderosa pine, 9 ins. diam., S. 23 1/2° E., 26 lks. dist., mkd. SW 1/16 S2 BT.
	Cor. is 30 lks. W of a N-S fence.
25.00	Enter rolling land, covered with dense timber.
40.58	The center W 1/16 sec. cor. of sec. 2.

Subdivision of Section 2,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	From the center S 1/16 sec. cor. of sec. 2.
	N. 89°22' W., on the E and W center line of the SW 1/4 of sec. 2.
	Over rolling land, through dense to medium timber.
19.91	The SW 1/16 sec. cor. of sec. 2.
	Thence through scattering to medium timber.
39.82	The S 1/16 sec. cor. of secs. 2 and 3.
	From the E-W 1/64 sec. cor. of secs. 2 and 11.
	N. 0°52'30" E., on the N and S center line of the SE 1/4 of the SW 1/4 of sec. 2.
	Over nearly level land, through scattering timber.
3.78	Fall 5 lks. W of the SW cor. of a chicken coop 16 ft. wide.
4.14	Fall 5 lks. W of the NW cor. of the same coop.
4.50	Intersect the S side of a small shed, 10 ft. wide, at a point 2 lks. E of the SW cor.
4.68	Intersect the N side of the same shed, at a point 2 lks. E of the NW cor.
4.87	Intersect the S side of a house, at a point 11 lks. W of the SE cor. The S side is 41 ft. long.
5.60	Intersect the N side of the same house at a point 1 lk. W of the NE cor. The N side is 28 ft. long.
8.63	Fall 1 lk. W of the SW cor. of a wooden pump house. The building is 16 ft. long.
8.75	Fall 1 lk. W of the NW cor. of the same pump house.
9.80	Intersect the S side of a wooden shed at a point 6 lks. E of the SW cor. The S side is 11 ft. long.
9.97	Intersect the N side of the same shed at a point 6 lks. E of the NW cor.
10.18	Point for the SE-SW 1/64 sec. cor. of sec. 2.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	S 2
	SE-SW
	1/64
	1977
	from which
	A ponderosa pine, 6 ins. diam., bears N. 36° E., 74 lks. dist., mkd. SE SW 1/64 S2 BT.

Subdivision of Section 2,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>A ponderosa pine, 6 ins. diam., bears N. 41° W., 75 lks. dist., mkd. SE SW 1/64 S2 BT.</p> <p>Cor. is 49 lks. W of a N-S fence and 74 lks. S of an E-W fence.</p> <p>From this point a local cor., bears N. 45° E., 91 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 36 ins. above ground. This local cor. is set in a fence cor.; fences extend southerly and westerly.</p> <hr/> <p>N. 89°11' W., on the E and W center line of the SE 1/4 of the SW 1/4.</p> <p>Over rolling land, through scattering to medium timber.</p>	
9.95	<p>The center S-SW 1/64 sec. cor. of sec. 2.</p> <hr/> <p>From the center W-W 1/64 sec. cor. of sec. 2.</p> <p>S. 0°47' W., on the N and S center line of the NW 1/4 of the SW 1/4.</p> <p>Over rolling land, through dense timber.</p>	
10.11	<p>Point for the NW-SW 1/64 sec. cor. of sec. 2.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S 2 NW-SW 1/64 1977</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N. 58° W., 53 lks. dist., mkd. NW SW 1/64 S2 BT.</p> <p>A pinyon pine, 6 ins. diam., bears N. 4° W., 54 lks. dist., mkd. X BT.</p> <p>From this point a local cor., bears S. 1° E., 8.8 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 40 ins. above ground.</p> <hr/> <p>N. 89°34' W., on the E and W center line of the NW 1/4 of the SW 1/4.</p> <p>Over rolling land, through dense timber.</p>	
9.96	<p>The N-S 1/64 sec. cor. of secs. 2 and 3.</p> <hr/> <p style="text-align: center;">Subdivision of Section 3, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 3 and 10.</p>	

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
	20.61	<p>N. 0°32' E., on the N and S center line of sec. 3. Over rolling land, through dense to medium timber.</p> <p>Point for the center S 1/16 sec. cor. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C</p> <p>S 1/16 S 3</p> <p>C</p> <p>1977</p> </div> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears N. 45° E., 30 lks. dist., mkd. C S 1/16 S3 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 22° W., 58 lks. dist., mkd. C S 1/16 S3 BT.</p>	
	41.22	<p>Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E and W center line of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C 1/4 S 3</p> <p>1977</p> </div> <p>from which</p> <p>A pinyon pine, 8 ins. diam., bears N. 8° E., 14 lks. dist., mkd. C 1/4 S3 BT.</p> <p>A juniper, 6 ins. diam., bears S. 47 1/2° E., 43 lks. dist., mkd. C 1/4 S3 BT.</p>	
	43.00	<p>Fence, bears N. 50° E. and S. 50° W.</p>	
	51.355	<p>Point for the center S-N 1/64 sec. cor. of sec. 3, at proportionate dist.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>S 3</p> <p>C-S-N</p> <p>1/64</p> <p>1977</p> </div> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears N. 51° E., 196 lks. dist., mkd. C S N 1/64 S3 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 11° W., 18 lks. dist., mkd. C S N 1/64 S3 BT.</p>	

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Cor. is near the S edge of abandoned highway No. 160, dirt surfaced, bearing SE and NW.</p>
61.49	<p>Point for the center N 1/16 sec. cor. of sec. 3, at proportionate dist.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T11N R18E</p> <p>C</p> <p>N 1/16 S 3</p> <p>C</p> <p>1977</p> </div>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 51° E., 15 lks. dist., mkd. C N 1/16 S3 BT.</p>
81.72	<p>The 1/4 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3.</p>
	<p>S. 89°46' W., on the E and W center line of sec. 3.</p>
	<p>Over rolling land, through dense timber.</p>
19.93	<p>Point for the center E 1/16 sec. cor. of sec. 3.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T11N R18E</p> <p>E 1/16</p> <p>C-----C</p> <p>S 3</p> <p>1977</p> </div>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 55° W., 8 lks. dist., mkd. C E 1/16 S3 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 58° W., 19 lks. dist., mkd. C E 1/16 S3 BT.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N of the cor.</p>
	<p>Cor. is 10 lks. E of a wash, 10 lks. wide, 3 ft. deep, drains N.</p>
33.70	<p>Abandoned highway No. 160, dirt surface, bears S. 35° E. and N. 35° W.</p>
39.86	<p>The center 1/4 sec. cor. of sec. 3.</p>
49.835	<p>Point for the center E-W 1/64 sec. cor. of sec. 3.</p>

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-E-W 1/64 1977</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears N. 63° E., 65 lks. dist., mkd. C E W 1/64 S3 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 11° E., 63 lks. dist., mkd. C E W 1/64 S3 BT.</p>	
	58.82	Fence, bears N and S.	
	59.81	Point for the center W 1/16 sec. cor. of sec. 3.	
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E W 1/16 C-----C S 3 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 77° E., 84 lks. dist., mkd. C W 1/16 S3 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 4 ins. diam., bears S. 26° E., 101 lks. dist., mkd. X BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N of the cor.</p>	
	79.76	The 1/4 sec. cor. of sec. 3.	
		<p>NE 1/4, Section 3,</p> <hr style="width: 20%; margin: auto;"/>	
		<p>From the center E 1/16 sec. cor. of sec. 3.</p> <p>N. 0°37' E., on the N and S center line of the NE 1/4 of sec. 3.</p> <p>Over rolling land, through dense timber.</p>	
	6.00	Fence, bears E and W.	
	20.21	Point for the NE 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the NE 1/4 of sec. 3.	
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E NE 1/16 S 3 1977</p>	

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
40.45	<p>from which</p> <p>A ponderosa pine, 4 ins. diam., bears S. 63° E., 55 lks. dist., mkd. NE 1/16 S3 BT.</p> <p>A pinyon pine, 8 ins. diam., bears N. 87° W., 28 lks. dist., mkd. NE 1/16 S3 BT.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of the cor.</p> <p>The E 1/16 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp.</p>
19.97	<p>From the N 1/16 sec. cor. of secs. 2 and 3.</p> <p>S. 89°57' W., on the E and W center line of the NE 1/4 of sec. 3.</p> <p>Over rolling land, through dense timber.</p> <p>The NE 1/16 sec. cor. of sec. 3.</p>
29.955	<p>Point for the center W-NE 1/64 sec. cor. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p>
39.94	<p style="text-align: center;">S 3 C-W-NE 1/64 1977</p> <p>from which</p> <p>A pinyon pine, 5 ins. diam., bears N. 34° E., 38 lks. dist., mkd. C W NE 1/64 S3 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 12° E., 30 lks. dist., mkd. C W NE 1/64 S3 BT.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of the cor.</p> <p>The center N 1/16 sec. cor. of sec. 3.</p>
20.50	<p style="text-align: center;">SW 1/4, Section 3,</p> <hr style="width: 20%; margin: auto;"/> <p>From the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°29' E., on the N and S center line of the SW 1/4 of sec. 3.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the SW 1/16 sec. cor. of sec. 3, at inter- section with the E and W center line of the SW 1/4 of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	T11N R18E SW 1/16 S 3 1977
	from which An alligator juniper, 18 ins. diam., bears N. 33° E., 15 lks. dist., mkd. SW 1/16 S3 BT. A ponderosa pine, 8 ins. diam., bears S. 37° E., 42 lks. dist., mkd. SW 1/16 S3 BT. Cor. is 12 lks. E of an old N-S fence.
41.00	The center W 1/16 sec. cor. of sec. 3. <hr style="width: 30%; margin: 10px auto;"/> From the center S 1/16 sec. cor. of sec. 3. N. 89°55' W., on the E and W center line of the SW 1/4 of sec. 3. Over rolling land, through dense timber.
19.91	The SW 1/16 sec. cor. of sec. 3.
29.87	Point for the center W-SW 1/64 sec. cor. of sec. 3. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. S 3 C-W-SW 1/64 1977
	from which A ponderosa pine, 12 ins. diam., bears S. 58°45' E., 133 lks. dist., mkd. C W SW 1/64 S3 BT. A pinyon pine, 9 ins. diam., bears S. 13°45' E., 76 lks. dist., mkd. C W SW 1/64 S3 BT.
39.83	The S 1/16 sec. cor. of secs. 3 and 4.
	<hr style="width: 80%; margin: 10px auto;"/> NW 1/4, Section 3 <hr style="width: 30%; margin: 10px auto;"/> From the center W 1/16 sec. cor. of sec. 3. N. 0°26'30" E., on the N and S center line of the NW 1/4 of sec. 3. Over rolling land, through scattering to dense timber.
20.32	Point for the NW 1/16 sec. cor. of sec. 3, at inter- section with the E and W center line of the NW 1/4 of sec. 3, not monumented.
30.49	Point for the center N-NW 1/64 sec. cor. of sec. 3, at proportionate dist.

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-N-NW 1/64 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 19° W., 25 lks. dist., mkd. C N NW 1/64 S3 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
33.20	Fence, bears N. 35° E. and S. 35° W.
33.60	Dirt road, bears N. 35° E. and S. 35° W.
40.57	The W 1/16 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the center N 1/16 sec. cor. of sec. 3.</p> <p>S. 89°56'30" W., on the E and W center line of the NW 1/4 of sec. 3.</p> <p>Over rolling land, through dense to scattering timber.</p>
19.975	The point for the NW 1/16 sec. cor. of sec. 3.
29.965	Point for the center W-NW 1/64 sec. cor. of sec. 3.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 C-W-NW 1/64 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 23° E., 17 lks. dist., mkd. C W NW 1/64 S3 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 81° W., 25 lks. dist., mkd. C W NW 1/64 S3 BT.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, N of the cor.</p> <p>Cor. is 32 lks. W of a dirt road and 52 lks. W of a fence, both bear NE and SW.</p>
39.955	The N 1/16 sec. cor. of secs. 3 and 4.
	<hr style="width: 20%; margin: 10px auto;"/> <p>From the center E-W 1/64 sec. cor. of sec. 3.</p> <p>N. 0°29' E., on the N and S center line of the SE 1/4 of the NW 1/4 of sec. 3.</p> <p>Over rolling land, through medium timber.</p>
10.15	Point for the SE-NW 1/64 sec. cor. of sec. 3.

Subdivision of Section 3,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 SE-NW 1/64 1977</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 6 ins. diam., bears S. 82° E., 48 lks. dist., mkd. SE NW 1/64 S3 BT.</p> <hr/> <p>N. 89°51' E., on the E and W center line of the SE 1/4 of the NW 1/4.</p> <p>Over rolling land, through medium timber.</p>
7.70	Dirt road, bears N. 30° E. and S. 30° W.
8.30	Fence, bears N. 30° E. and S. 30° W.
9.98	The center S-N 1/64 sec. cor. of sec. 3.
	<hr/> <p>From the center W-NW 1/64 sec. cor. of sec. 3.</p> <p>N. 0°24' E., on the N and S center line of the NW 1/4 of the NW 1/4 of sec. 3.</p>
10.18	<p>Point for the NW-NW 1/64 sec. cor. of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S-3 NW-NW 1/64 1977</p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 8 ins. diam., bears N. 54° E., 43 lks. dist., mkd. NW NW 1/64 S3 BT.</p> <p style="text-align: center;">A ponderosa pine, 14 ins. diam., bears N. 82° W., 60 lks. dist., mkd. NW NW 1/64 S3 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <hr/> <p>N. 89°59' E., on the E and W center line of the NW 1/4 of the NW 1/4 of sec. 3.</p> <p>Over rolling land, through medium timber.</p>
10.00	The center N-NW 1/64 sec. cor. of sec. 3.
	<hr/> <p style="text-align: center;">Subdivision of Section 4, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 9.</p>

Subdivision of Section 4,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
20.26	<p>N. 0°14' W., on the N and S center line of sec. 4. Over rolling land, through dense timber.</p> <p>Point for the center S 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R18E C S 1/16 S 4 C 1977</p>
	<p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 11 ins. diam., bears S. 32° E., 20 lks. dist., mkd. C S 1/16 S4 BT.</p> <p style="padding-left: 40px;">A pinyon pine, 8 ins. diam., bears N. 3 1/2° W., 40 lks. dist., mkd. C S 1/16 S4 BT.</p>
40.52	<p>Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E and W center line of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R18E C 1/4 S 4 1977</p>
	<p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears S. 77° E., 57 lks. dist., mkd. C 1/4 S4 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 79° W., 91 lks. dist., mkd. C 1/4 S4 BT.</p>
80.67	<p>The 1/4 sec. cor. of secs. 4 and 33, on the N bdy. of the Tp.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4. S. 89°57' W., on the E and W center line of sec. 4. Over rolling land through dense timber.</p>
19.82	<p>Point for the center E 1/16 sec. cor. of sec. 4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R18E E 1/16 C ——— C S 4 1977</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 44° E., 51 lks. dist., mkd. C E 1/16 S4 BT.</p>

Subdivision of Section 4,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	A pine, 5 ins. diam., bears N. 34° W., 31 lks. dist., mkd. C E 1/16 S4 BT.
39.64	The center 1/4 sec. cor. of sec. 4.
79.32	The 1/4 sec. cor. of secs. 4 and 5.
<hr/>	
SE 1/4, Section 4	
<hr/>	
	From the E 1/16 sec. cor. of secs. 4 and 9.
	N. 0°03' E., on the N and S center line of the SE 1/4 of sec. 4.
	Over rolling land, through dense timber.
5.50	Dirt road, bears NE and SW.
20.32	Point for the SE 1/16 sec. cor. of sec. 4, at intersection with the E and W center line of the SE 1/4 of sec. 4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T11N R18E SE 1/16 S 4 1977
	from which
	An alligator juniper, 7 ins. diam., bears N. 45° E., 41 lks. dist., mkd. SE 1/16 S4 BT.
	A ponderosa pine, 9 ins. diam., bears S. 88° W., 43 lks. dist., mkd. SE 1/16 S4 BT.
27.80	Dirt road, bears N. 65° E. and S. 65° W.
40.64	The center E 1/16 sec. cor. of sec. 4.
<hr/>	
	From the S 1/16 sec. cor. of secs. 3 and 4.
	N. 89°53' W., on the E and W center line of the SE 1/4 of sec. 4.
	Over rolling land, through dense timber.
9.86	Point for the center E-SE 1/64 sec. cor. of sec. 4.
14.10	Dirt road, bears N. 15° E. and S. 15° W.
19.72	The SE 1/16 sec. cor. of sec. 4.
30.40	Dirt road, bears N. 15° E. and S. 15° W.
39.44	The center S 1/16 sec. cor. of sec. 4.

Subdivision of Section 5,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">Subdivision of Section 5, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 5 and 8.</p> <p>N. 1°13' W., on the N and S center line of sec. 5.</p> <p>Over rolling land, through dense timber.</p> <p>42.29 Point for the center 1/4 sec. cor. of sec. 5, at intersection with the E and W center line of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C 1/4 S 5 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 35° E., 29 lks. dist., mkd. C 1/4 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears S. 43° W., 86 lks. dist., mkd. C 1/4 S5 BT.</p> <p>62.71 Point for the center N 1/16 sec. cor. of sec. 5, at proportionate dist.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C N 1/16 S 5 C 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 44° W., 90 lks. dist., mkd. C N 1/16 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 32° W., 78 lks. dist., mkd. C N 1/16 S5 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>65.70 Wash, drains NE.</p> <p>82.92 The 1/4 sec. cor. of secs. 5 and 32, on the N bdy. of the Tp.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>S. 89°32' W., on the E and W center line of sec. 5.</p> <p>Over rolling land, through dense timber.</p> <p>19.855 Point for the center E 1/16 sec. cor. of sec. 5.</p>

Subdivision of Section 5,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E E 1/16 C-----C S 5 1977</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears S. 64° W., 9 lks. dist., mkd. C E 1/16 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 4 1/2° W., 67 lks. dist., mkd. C E 1/16 S5 BT.</p>	
39.71	The center 1/4 sec. cor. of sec. 5.	
80.10	The 1/4 sec. cor. of secs. 5 and 6.	
<hr/>		
NE 1/4, Section 5		
	<p>From the center E 1/16 sec. cor. of sec. 5.</p> <p>N. 1°00' W., on the N and S center line of the NE 1/4 of sec. 5.</p> <p>Over rolling land, through dense timber.</p>	
20.28	<p>Point for the NE 1/16 sec. cor. of sec. 5, at intersection with the E and W center line of the NE 1/4 of sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E NE 1/16 S 5 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 5° E., 21 lks. dist., mkd. NE 1/16 S5 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 63° W., 13 lks. dist., mkd. NE 1/16 S5 BT.</p>	
30.425	<p>Point for the center N-NE 1/64 sec. cor. of sec. 5, at proportionate dist.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 5 C-N-NE 1/64 1977</p>	

Subdivision of Section 5,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S. 46° E., 14 lks. dist., mkd. C N NE 1/64 S5 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 77° W., 15 lks. dist., mkd. C N NE 1/64 S5 BT.</p> <p>A fence cor., bears S. 88° W., 19 lks. dist.; fences extend N and E.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is 1 lk. S of an E-W fence.</p>
40.415	<p>The E 1/16 sec. cor. of secs. 5 and 32, on the N bdy. of the Tp.</p>
	<p>From the N 1/16 sec. cor. of secs. 4 and 5.</p> <p>S. 89°56' W., on the E and W center line of the NE 1/4 of sec. 5.</p> <p>Over rolling land, through dense timber.</p>
19.925	<p>The NE 1/16 sec. cor. of sec. 5.</p>
39.85	<p>The center N 1/16 sec. cor. of sec. 5.</p>
	<p>From the E-E 1/64 sec. cor. of secs. 5 and 32, on the N bdy. of the Tp.</p> <p>S. 0°54'30" E., on the N and S center line of the NE 1/4 of the NE 1/4 of sec. 5.</p> <p>Over rolling land, through dense timber.</p>
9.98	<p>Point for the NE-NE 1/64 sec. cor. of sec. 5.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S 5 NE-NE 1/64 1977</p>
	<p>from which</p> <p>A fence cor., bears N. 14° E., 11 lks. dist.; fences extend northerly and westerly.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 60° E., 44 lks. dist., mkd. NE NE 1/64 S5 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 46° W., 10 lks. dist., mkd. NE NE 1/64 S5 BT.</p> <p>N. 89°53' W., on the E and W center line of the NE 1/4 of the NE 1/4 of sec. 5.</p> <p>Over rolling land, through dense timber.</p>

Subdivision of Section 5,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
9.98	The center N-NE 1/64 sec. cor. of sec. 5.
	<p style="text-align: center;">Subdivision of Section 9, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 9 and 16. N. 0°54' W., on the N and S center line of sec. 9. Over rolling land, through scattering to dense timber.</p>
39.96	<p>Point for the center 1/4 sec. cor. of sec. 9, at intersection with the E and W center line of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C 1/4 S 9 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 41° E., 19 lks. dist., mkd. C 1/4 S9 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 70° W., 59 lks. dist., mkd. C 1/4 S9 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
55.30	State Highway No. 260, asphalt surfaced, bears N. 60° E. and S. 60° W.
57.30	Fence, bears N. 70° E. and S. 70° W.
58.30	Dirt road, bears N. 50° E. and S. 50° W.
60.115	<p>Point for the center N 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C N 1/16 S 9 C 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 16 1/2° E., 77 lks. dist., mkd. C N 1/16 S9 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 35° W., 63 lks. dist., mkd. C N 1/16 S9 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of the cor.</p>

Subdivision of Section 9,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
80.27	The 1/4 sec. cor. of secs. 4 and 9.
	<hr/> From the 1/4 sec. cor. of secs. 9 and 10. N. 89°42' W., on the E and W center line of sec. 9. Over rolling land, through dense timber.
18.70	Fence, bears N and S.
19.77	Point for the center E 1/16 sec. cor. of sec. 9. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	$ \begin{array}{c} \text{T11N R18E} \\ \text{E 1/16} \\ \text{C} \text{-----} \text{C} \\ \text{S 9} \\ \text{1977} \end{array} $
	from which
	A ponderosa pine, 8 ins. diam., bears S. 56° E., 47 lks. dist., mkd. C E 1/16 S9 BT.
	A ponderosa pine, 8 ins. diam., bears N. 31 1/2° W., 15 lks. dist., mkd. C E 1/16 S9 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.
	Cor. is located at the N edge of an oak, 12 ins. diam.
23.20	Wash, 40 lks. wide, 3 ft. deep, drains N. 30° E.
26.00	Enter open grass land, edge bears N. 30° E. and S. 30° W.
38.00	Enter medium to dense timber, edge bears N and S.
39.54	The center 1/4 sec. cor. of sec. 9.
41.80	Dirt road, bears S. 5° E. and N. 5° W.
53.40	Dirt road, bears NE and SW.
79.25	The 1/4 sec. cor. of secs. 8 and 9.
	$ \text{NE 1/4, Section 9} $ <hr/>
	From the center E 1/16 sec. cor. of sec. 9. N. 1°09' W., on the N and S center line of the NE 1/4 of sec. 9.
	Over gently rolling land, through scattering to medium timber.
20.16	Point for the NE 1/16 sec. cor. of sec. 9, at intersec- tion with the E and W center line of the NE 1/4 of sec. 9.

Subdivision of Section 9,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E NE 1/16 S 9 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 17° E., 82 lks. dist., mkd. NE 1/16 S9 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 31° W., 22 lks. dist., mkd. NE 1/16 S9 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W of the cor.</p>	
20.60	Fence, bears N. 80° E. and S. 80° W.; enter open grass land, edge bears N. 80° E. and S. 80° W.	
22.10	State Highway No. 260, asphalt surfaced, bears N. 80° E. and S. 80° W.	
23.50	Fence, bears N. 80° E. and S. 80° W.	
40.32	The E 1/16 sec. cor. of secs. 4 and 9.	

	<p>From the N 1/16 sec. cor. of secs. 9 and 10.</p> <p>N. 89°43' W., on the E and W center line of the NE 1/4 of sec. 9.</p> <p>Over rolling land, through dense to scattering timber.</p>	
19.695	The NE 1/16 sec. cor. of sec. 9.	
26.50	State Highway No. 260, asphalt surfaced, bears N. 70° E. and S. 70° W.	
37.80	Dirt road, bears N. 50° E. and S. 50° W.	
39.39	The center N 1/16 sec. cor. of sec. 9.	
	<p>Subdivision of Section 11, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 1°31' W., on the N and S center line of sec. 11.</p> <p>Over rolling land, through dense timber.</p>	
40.01	<p>Point for the center 1/4 sec. cor. of sec. 11, at intersection with E and W center line of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Subdivision of Section 11,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T11N R18E C 1/4 S11 1977</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 6° E., 24 lks. dist., mkd. C 1/4 S11 BT.</p>
	<p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 50° W., 2 1/2 lks. dist., mkd. C 1/4 S11 BT.</p>
59.805	<p>Point for the center N 1/16 sec. cor. of sec. 11.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R18E C N 1/6 S11 C 1977</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 28° E., 36 lks. dist., mkd. C N 1/16 S11 BT.</p>
	<p style="padding-left: 40px;">A juniper, 8 ins. diam., bears S. 22 1/2° W., 26 lks. dist., mkd. C N 1/16 S11 BT.</p>
	<p>Cor. is 39 lks. S of an E-W fence.</p>
62.70	<p>State Highway No. 260, asphalt surfaced, bears E and W.</p>
78.00	<p>Old highway No. 160, dirt surfaced, bears E curving NE and W curving NW.</p>
79.60	<p>The 1/4 sec. cor. of sec. 2 and 11.</p>
	<p>From the 1/4 sec. cor. of secs. 11 and 12.</p>
	<p>S. 89°58' W., on the E and W center line of sec. 11.</p>
	<p>Over rolling land, through dense timber.</p>
20.50	<p>Old highway No. 160, dirt surfaced bears S. 10° E. and N. 10° W.</p>
39.71	<p>The center 1/4 sec. cor. of sec. 11.</p>
49.625	<p>Point for the center E-W 1/64 sec. cor. of sec. 11.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S11 C-E-W 1/64 1977</p>

Subdivision of Section 11,
T. 11 N. R. 18 E., Gila and Salt River Mer., Arizona

	CHAINS		
	59.54	<p>from which</p> <p>A ponderosa pine, 5 ins. diam., bears N. 72° E., 37 lks. dist., mkd. C E W 1/64 S11 BT.</p> <p>A fence cor., bears S. 22 1/4° W., 61 lks. dist.; fences extend northerly and westerly.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 46° W., 20 lks. dist., mkd. C E W 1/64 S 11 BT.</p> <p>Point for the center W 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E</p> <p style="text-align: center;">W 1/16 C-----C S11 1977</p>	
	79.37	<p>from which</p> <p>A ponderosa pine, 7 ins. diam., bears S. 6° E., 21 lks. dist., mkd. C W 1/16 S11 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 64° W., 46 lks. dist., mkd. C W 1/16 S11 BT.</p> <p>From this point a local cor., bears N. 43 1/2° W., 31 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 14 ins. above ground.</p> <p>The 1/4 sec. cor. of secs. 10 and 11.</p> <hr/> <p style="text-align: center;">NW 1/4, Section 11</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 11.</p> <p>N. 1°35' W., on the N and S center line of the NW 1/4 of sec. 11.</p> <p>Over gently rolling land, through scattering timber.</p> <p>18.90 State Highway No. 260, asphalt surfaced, bears N. 80° E. and S. 80° W.</p> <p>19.975 Point for the NW 1/16 sec. cor. of sec. 11, at inter- section with the E and W center line of the NW 1/4 of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E NW 1/16 S11 1977</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p>	

Subdivision of Section 11,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	<p>From this point a local cor., bears N. 23° E., 46.8 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 12 ins. above ground.</p> <p>From this same point a local cor., bears N. 26° W., 38.5 lks. dist., monumented with an open end metal pipe, 2 ins. diam., projecting 3 ft. above ground.</p> <p>20.35 Fence, bears N. 80° E. and S. 80° W.</p> <p>39.95 Point for the W 1/16 sec. cor. of secs. 2 and 11.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the center N 1/16 sec. cor. of secs. 11.</p> <p>N. 89°31' W., on the E and W center line of the NW 1/4 of sec. 11.</p> <p>Over gently rolling land, through scattering timber.</p> <p>9.93 Point for the center E-NW 1/64 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S11 C-E-NW 1/64 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 45° E., 62 lks. dist., mkd. C E NW 1/64 S11 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 41° W., 104 lks. dist., mkd. C E NW 1/64 S11 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p> <p>Cor. is 71 lks. N of an E-W fence, and 82 lks. S of State Highway No. 260, bearing E and W.</p> <p>14.30 State Highway No. 260, asphalt, bears N. 85° E. and S. 85° W.</p> <p>19.86 The NW 1/16 sec. cor. of sec. 11.</p> <p>39.72 The N 1/16 sec. cor. of secs. 10 and 11.</p>
	<p>Subdivision of Section 13, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>
40.08	<p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°19' E., on the N and S center line of sec. 13.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the center 1/4 sec. cor. of sec. 13, at a fence cor. from which fences extend northerly and easterly. This point has long been recognized as a property boundary and is accepted as the cor. position.</p>

Subdivision of Section 13,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
<p>26.90</p> <p>40.20</p>	<p>At the SW cor. of the fence cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C 1/4 S13 1977</p> <p>from which</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears S. 56° E., 37 lks. dist., mkd. C 1/4 S13 BT.</p> <p style="padding-left: 40px;">An oak, 10 ins. diam., bears N. 33 1/2° W., 72 lks. dist., mkd. C 1/4 S13 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°25' E., beginning new measurement.</p> <p>Along a N-S fence.</p> <p>Dirt road, bears E and W.</p> <p>The 1/4 sec. cor. of secs. 13 and 24.</p>
<p>39.97</p> <p>1.00</p> <p>39.93</p>	<p>From the 1/4 sec. cor. of secs. 13 and 18, on the E bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1936 resurvey of the W bdy. of T. 11 N., R. 19 E., from which bearing trees recorded in 1936</p> <p style="padding-left: 40px;">A juniper 34 ins. diam., bears S. 69° E., 67 lks. dist., mkd. 1/4 S18 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 68° W., 50 lks. dist., mkd. 1/4 S13 BT.</p> <p>From this point a fence cor., bears South, 2 lks. dist.; fences extend N and W.</p> <p>S. 89°35' W., on the E and W center line of sec. 13.</p> <p>Along an E-W fence.</p> <p>The center 1/4 sec. cor. of sec. 13.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°41' W., beginning new measurement.</p> <p>Over rolling land, through a burned area.</p> <p>Dirt road, bears N and S.</p> <p>The 1/4 sec. cor. of secs. 13 and 14.</p>
	<p style="text-align: center;">Subdivision of Section 22, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 22 and 27.</p>

Subdivision of Section 22,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	N. 0°03' W., on the N and S center line of sec. 22.
	Over rolling land, through scattering timber.
2.50	Fence, bears E and W.
8.90	Fence, bears irregularly E and W; enter open grass land.
14.932	Point for the center N-S-S 1/256 sec. cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S22 C-N-S-S 1/256 1977</p>
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.
	Cor. is 30 lks. S of the S edge of an earthen stock pond, approximately 4.00 chs. diam., S. 30° W., about 2.00 chs. dist., from the center of said stock pond.
19.91	Point for the center S 1/16 sec. cor. of sec. 22, not monumented.
21.00	Enter medium to dense timber, edge bears E and W.
29.865	Point for the center N-S 1/64 sec. cor. of sec. 22.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">S22 C-N-S 1/64 1977</p>
	from which
	<p style="text-align: center;">A pinyon pine, 12 ins. diam., bears S. 55° E., 36 lks. dist., mkd. C N S 1/64 S22 BT.</p>
	<p style="text-align: center;">A ponderosa pine, 15 ins. diam., bears N. 38 1/2° W., 37 lks. dist., mkd. C N S 1/64 S22 BT.</p>
30.55	Fence, bears E and W.
37.40	Dirt road, bears NE and SW.
39.82	Point for the center 1/4 sec. cor. of sec. 22, at intersection with E and W center line of sec. 22.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T11N R18E C 1/4 S22 1977</p>

Subdivision of Section 22,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
79.80	<p>from which</p> <p>A juniper, 16 ins. diam., bears N. 49° E., 36 lks. dist., mkd. C 1/4 S22 BT</p> <p>A pine, 10 ins. diam., bears S. 14° E., 69 lks. dist., mkd. C 1/4 S22 BT.</p> <p>The 1/4 sec. cor. of secs. 15 and 22.</p>	
2.50	<p>From the 1/4 sec. cor. of secs. 22 and 23.</p> <p>N. 88°20' W., on the E and W center line of sec. 22.</p> <p>Over rolling land, through dense timber.</p> <p>Forest Service road No. 107, dirt surface, bears N and S.</p>	
20.00	<p>Point for the center E 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E E 1/16 C-----C S22 1977</p>	
34.20	<p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears N. 23° E., 25 lks. dist., mkd. C E 1/16 S22 BT.</p> <p>An alligator juniper, 5 ins. diam., bears S. 84° E., 10 lks. dist., mkd. C E 1/16 S22 BT.</p> <p>Dirt road, bears N. 80° E. and S. 80° W.</p>	
38.90	<p>Dirt road, bears N and S.</p>	
40.00	<p>The center 1/4 sec. cor. of sec. 22.</p>	
58.50	<p>Dirt road, bears N and S.</p>	
59.99	<p>Point for the center W 1/16 sec. cor. of sec. 22.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E W 1/16 C-----C S22 1977</p>	
	<p>from which</p> <p>A juniper, 18 ins. diam., bears N. 85° E., 42 lks. dist., mkd. C W 1/16 S22 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 28 1/2° W., 84 lks. dist., mkd. C W 1/16 S22 BT.</p>	

Subdivision of Section 22,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
79.98	The 1/4 sec. cor. of secs. 21 and 22.
SE 1/4, Section 22	
From the E 1/16 sec. cor. of secs. 22 and 27.	
N. 0°14' W., on the N and S center line of the SE 1/4 of sec. 22.	
Over rolling land, through a burned area.	
1.50	Forest Service road No. 107, dirt surface, bears NE and SW.
14.903	Point for the center N-S-SE 1/256 sec. cor. of sec. 22.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.	
<p>S22 C-N-S-SE 1/256 1977</p>	
from which	
<p>A ponderosa pine, 5 ins. diam., bears N. 75° E., 89 lks. dist., mkd. C N S SE 1/256 S22 BT.</p>	
<p>A ponderosa pine, 8 ins. diam., bears S. 53° W., 17 lks. dist., mkd. C N S SE 1/256 S22 BT.</p>	
Raise a mound of stone, 3 ft. base, 1/12 ft. high, W of the cor.	
15.30	Fence, bears irregularly NE and SW; enter scattering to medium timber.
19.87	Point for the SE 1/16 sec. cor. of secs. 22, at intersection with the E and W center line of the SE 1/4 of sec. 22.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
<p>T11N R18E SE 1/16 S22 1977</p>	
from which	
<p>A ponderosa pine, 5 ins. diam., bears N. 22 1/2° E., 23 lks. dist., mkd. SE 1/16 S22 BT.</p>	
<p>A ponderosa pine, 9 ins. diam., bears S 15 1/2° E., 47 lks. dist., mkd. SE 1/16 S22 BT.</p>	
Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.	
27.10	Fence, bears irregularly S. 30° E. and N. 30° W.
29.80	Point for the center N-SE 1/64 sec. cor. of sec. 22.

Subdivision of Section 22,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S22 C-N-SE 1/64 1977</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 19° E., 29 lks. dist., mkd. C N SE 1/64 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 34° W., 23 lks. dist., mkd. C N SE 1/64 S22 BT.</p> <p>Deposit broken brown glass at the base of the iron post.</p> <p>Cor. is at the E edge of a wash, 10 lks. wide, 1 ft. deep, draining N, curving NE, and 26 lks. E of a N-S fence.</p>
34.90	Dirt road, bears N. 15° E. and S. 15° W.
39.73	The center E 1/16 sec. cor. of sec. 22.
	<p style="text-align: center;">—————</p> <p>From the S 1/16 sec. cor. of secs. 22 and 23.</p> <p>N. 88°29' W., on the E and W center line of the SE 1/4 of sec. 22.</p> <p>Over a burned area.</p>
7.00	Forest Service road No. 107, dirt surface, bears N. 10° E. and S. 10° W.
18.20	Fence, bears N and S.
20.06	The SE 1/16 sec. cor. of sec. 22.
25.95	Fence, bears N. 30° E. and S. 30° W.; enter open grass land, edge bears N. 30° E. and S. 30° W.
40.12	The point for the center S 1/16 sec. cor. of sec. 22.
	<p style="text-align: center;">—————</p> <p style="text-align: center;">SW 1/4, Section 22</p> <p style="text-align: center;">—————</p> <p>From the W 1/16 sec. cor. of secs. 22 and 27.</p> <p>N. 0°10' E., on the N and S center line of the SW 1/4 of sec. 22.</p> <p>Over rolling land, through medium to dense timber.</p>
12.30	Fence, bears E and W.
14.97	Point for the center N-S-SW 1/256 sec. cor. of sec. 22.

Subdivision of Section 22,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S22 C-N-S-SW 1/256 1977</p>
	from which
	<p style="text-align: center;">An aspen, 14 ins. diam., bears N. 77 1/2° W., 68 lks. dist., mkd. C N S SW 1/256 S22 BT.</p>
17.30	The center of an earthen stock pond, 2.50 chs. diam., bears East, about 140 lks. dist.,
19.96	Point for the SW 1/16 sec. cor. of sec. 22, at intersection with the E and W center line of the SW 1/4 of sec. 22.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T11N R18E SW 1/16 S22 1977</p>
	from which
	<p style="text-align: center;">A pine, 5 ins. diam., bears S. 72° W., 18 lks. dist., mkd. SW 1/16 S22 BT.</p>
20.30	Abandoned fence, bears E and W.
20.60	Dirt road, bears E and W.
27.80	Fence, bears E and W.
29.94	Point for the center N-SW 1/64 sec. cor. of sec. 22.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">S22 C-N-SW 1/64 1977</p>
	from which
	<p style="text-align: center;">A fence cor., bears N. 53 1/2° E., 52 lks. dist.; fences extend easterly and southerly.</p>
	<p style="text-align: center;">A ponderosa pine, 10 ins. diam., bears S. 29° W., 115 lks. dist., mkd. C N SW 1/64 S22 BT.</p>
	<p style="text-align: center;">A ponderosa pine, 12 ins. diam., bears N. 5° W., 68 lks. dist., mkd. C N SW 1/64 S22 BT.</p>
39.92	The center W 1/16 sec. cor. of sec. 22.
	<p style="text-align: center;">From the point for the center S 1/16 sec. cor. of sec. 22.</p>

Subdivision of Section 22,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 88°29' W., on the E and W center line of the SW 1/4 of sec. 22.</p> <p>Over rolling land, through scattering timber.</p> <p>20.055 The SW 1/16 sec. cor. of sec. 22.</p> <p>25.30 Fence, bears N and S; enter dense timber, edge bears N and S.</p> <p>25.40 Dirt road, bears N and S.</p> <p>40.11 The S 1/16 sec. cor. of secs. 21 and 22.</p>
	<p style="text-align: center;">Subdivision of Section 23, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 23 and 26.</p> <p>N. 0°20' W., on the N and S center line of sec. 23.</p> <p>Over rolling land, through a burned area.</p> <p>39.81 Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E and W center line of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C 1/4 S23 1977</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p> <p>59.84 Point for the center N 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C N 1/16 S23 C 1977</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>64.847 Point for the center S-N-N 1/256 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S23 C-S-N-N 1/256 1977</p>

Subdivision of Section 23,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
79.87	<p>from which</p> <p>A fence cor., bears S. 4 1/2° E., 123 lks. dist.; fences extend northerly and westerly.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p> <p>The 1/4 sec. cor. of secs. 14 and 23.</p>
40.55	<p>From the 1/4 sec. cor. of secs. 23 and 24.</p> <p>S. 88°52' W., on the E and W center line of sec. 23.</p> <p>Over rolling land, through a burned area.</p> <p>The center 1/4 sec. cor. of sec. 23.</p>
47.80	<p>Dirt road, bears N. 10° E. and S. 10° W.</p>
60.64	<p>Point for the center W 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
80.73	<p style="text-align: center;">T11N R18E W 1/16 C-----C S23 1977</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p> <p>The 1/4 sec. cor. of secs. 22 and 23.</p>
14.40 14.55 15.03 20.04	<p style="text-align: center;">NW 1/4, Section 23 -----</p> <p>From the center W 1/16 sec. cor. of sec. 23.</p> <p>N. 0°07' W., on the N and S center line of the NW 1/4 of sec. 23.</p> <p>Over rolling land, through a burned area.</p> <p>Dirt road, bears E and W.</p> <p>Fence, bears E and W.</p> <p>Point for the center N-S-NW 1/256 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S23 C-N-S-NW 1/256 1977</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>Point for the NW 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the NW 1/4 of sec. 23, not monumented.</p>

Subdivision of Section 23,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
40.08	<p>The W 1/16 sec. cor. of secs. 14 and 23.</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 23.</p> <p>S. 88°54' W., on the E and W center line of the NW 1/4 of sec. 23.</p> <p>Over rolling land, through a burned area.</p>
9.89	Fence, bears N and S.
10.012	<p>Point for the center E-NW 1/64 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p>S23 C-E-NW 1/64 1977</p>
20.025	The point for the NW 1/16 sec. cor. of sec. 23.
25.034	<p>Point for the center E-W-NW 1/256 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p>S23 C-E-W-NW 1/256 1977</p>
	Deposit broken glass at the base of the iron post.
25.13	Fence, bears N and S.
40.06	<p>The N 1/16 sec. cor. of secs. 22 and 23.</p> <hr/> <p>From the center E-NW 1/64 sec. cor. of sec. 23.</p> <p>S. 0°14' E., on the N and S center line of the SE 1/4 of the NW 1/4 of sec. 23.</p> <p>Over rolling land, through a burned area.</p>
5.01	<p>Point for the center N-SE-NW 1/256 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p>S23 C-N-SE-NW 1/256 1977</p>
	from which
	<p>A fence cor., bears S. 8° W., 76 lks. dist.; fences extend northerly and westerly.</p>

Subdivision of Section 23,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	Deposit broken glass at the base of the iron post.	
	<p style="text-align: center;">_____</p> S. 88°53' W., on the E and W center line of the NW 1/4 of the SE 1/4 of the NW 1/4 of sec. 23.	
	Over rolling land, through a burned area.	
.08	Fence, bears N and S.	
10.025	The center N-S-NW 1/256 sec. cor. of sec. 23.	
	<p style="text-align: center;">_____</p> S. 88°53' W., on the E and W center line of the NE 1/4 of the SW 1/4 of the NW 1/4 of sec. 23.	
	Over gently rolling land, through a burned area.	
5.012	Point for the NE-SW-NW 1/256 sec. cor. of sec. 23.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">S23 NE-SW-NW 1/256 1977</p>	
	from which	
	<p style="text-align: center;">A ponderosa pine, 14 ins. diam., bears S. 19° E., 39 lks. dist., mkd. NE SW NW 1/256 S23 BT.</p>	
	<p style="text-align: center;">A fence cor., bears S. 13 1/2° W., 37 lks. dist., fences extend northerly and easterly.</p>	
	Deposit broken glass at the base of the iron post.	
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.	
	<p style="text-align: center;">_____</p> N. 0°04'30" W., on the N and S center line of the NE 1/4 of the SW 1/4 of the NW 1/4 of sec. 23.	
	Over nearly level land, through a burned area.	
5.015	The center E-W-NW 1/256 sec. cor. of sec. 23.	
	From the center E-NW 1/64 sec. cor. of sec. 23.	
	N. 0°14' W., on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 23.	
	Over nearly level, open grass land.	
5.01	Point for the center S-NE-NW 1/256 sec. cor. of sec. 23.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">S23 C-S-NE-NW 1/256 1977</p>	

Subdivision of Section 23,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
10.004	<p>from which</p> <p>A fence cor., bears S. 23° E., 86 lks. dist.; fences extend easterly and southerly.</p> <p>Deposit broken glass at the base of the iron post.</p> <hr/> <p>N. 88°54' E., on the E and W center line of the SE 1/4 of the NE 1/4 of the NW 1/4 of sec. 23.</p> <p>Over rolling land, through scattering timber.</p> <p>The center S-N-N 1/256 sec. cor. of sec. 23.</p>
40.10	<p style="text-align: center;">Subdivision of Section 24, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 24 and 25.</p> <p>N. 0°09' W., on the N and S center line of sec. 24.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the center 1/4 sec. cor. of sec. 24, at intersection with the E and W center line of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C 1/4 S24 1977</p> <p>from which</p> <p>A ponderosa pine, 11 ins. diam., bears N. 59° E., 25 lks. dist., mkd. C 1/4 S24 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S. 34 1/2° E., 15 lks. dist., mkd. C 1/4 S24 BT.</p> <p>Thence over partially burned area, through scattering timber.</p> <p>Point for the center S-N 1/64 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S24 C-S-N 1/64 1977</p> <p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears S. 70 1/2° E., 110 lks. dist., mkd. C S N 1/64 S24 BT.</p>

Subdivision of Section 24,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
59.69	<p>An earthen stock pond, 3.50 chs. diam., bears S. 75° E., 12.50 chs. dist.</p> <p>A fence cor., bears S. 1° W., 121 lks. dist.; fences extend northerly and westerly.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is 3 lks. W of a N-S fence.</p> <p>Thence along W side of a fence, over open grass land.</p> <p>Fence, bears easterly and westerly; enter scattering timber.</p>	
60.145	<p>Point for the center N 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C</p> <p>N 1/16 S24</p> <p>C</p> <p>1977</p> </div> <p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears S. 78° E., 20 lks. dist., mkd. C N 1/16 S24 BT.</p> <p>A fence cor., bears S. 41 1/2° E., 69 lks. dist.; fences extend southerly and westerly.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 75° W., 25 lks. dist., mkd. C N 1/16 S24 BT.</p>	
80.19	<p>The 1/4 sec. cor. of secs. 13 and 24.</p>	
40.02	<p>From the 1/4 sec. cor. of secs. 19 and 24, on the E bdy. of the Tp.</p> <p>N. 89°56' W., on the E and W center line of sec. 24.</p> <p>Over rolling land, through scattering to medium timber.</p> <p>The center 1/4 sec. cor. of sec. 24.</p> <p>Thence over a burned area.</p>	
43.00	<p>Dirt road, bears N. 15° E. and S. 15° W.</p>	
59.725	<p>Point for the center W 1/16 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>W 1/16</p> <p>C ——— C</p> <p>S24</p> <p>1977</p> </div>	

Subdivision of Section 24,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>
79.43	<p>The 1/4 sec. cor. of secs. 23 and 24.</p>
<p>NW 1/4, Section 24</p>	
	<p>From the center W 1/16 sec. cor. of sec. 24.</p>
	<p>N. 0°41' W., on the N and S center line of the NW 1/4 of sec. 24.</p>
	<p>Over rolling land, through scattering timber, mostly burned.</p>
8.80	<p>Dirt road, bears E and W.</p>
9.30	<p>Fence, bears E and W.</p>
10.01	<p>Point for the center S-NW 1/64 sec. cor. of sec. 24.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>S24 C-S-NW 1/64 1977</p>
	<p>from which</p>
	<p>A ponderosa pine, 11 ins. diam., bears S. 58° E., 71 lks. dist., mkd. C S NW 1/64 S24 BT.</p>
	<p>A ponderosa pine, 9 ins. diam., bears S. 64° W., 78 lks. dist., mkd. C S NW 1/64 S24 BT.</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 1 ft. high, W of the cor.</p>
20.02	<p>Point for the NW 1/16 sec. cor. of sec. 24, at intersection with the E and W center line of the NW 1/4 of sec. 24, not monumented.</p>
20.10	<p>Fence, bears E and W.</p>
22.50	<p>Fence, bears E and W, thence through scattering to medium timber.</p>
30.03	<p>Point for the center N-NW 1/64 sec. cor. of sec. 24.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>S24 C-N-NW 1/64 1977</p>
	<p>from which</p>
	<p>A juniper, 8 ins. diam., bears N. 85° E., 24 lks. dist., mkd. C N NW 1/64 S24 BT.</p>

Subdivision of Section 24,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>A pinyon pine, 9 ins. diam., bears N. 60° W., 67 lks. dist., mkd. C N NW 1/64 S24 BT.</p>	
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p>	
40.04	<p>The W 1/16 sec. cor. of secs. 13 and 24.</p> <hr/>	
	<p>From the center N 1/16 sec. cor. of sec. 24.</p>	
	<p>S. 89°59' W., on the E and W center line of the NW 1/4 of sec. 24.</p>	
	<p>Over rolling land, through medium to scattering timber.</p>	
9.62	<p>Fence, bears N and S.</p>	
9.945	<p>Point for the center E-NW 1/64 sec. cor. of sec. 24.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">S24 C-E-NW 1/64 1977</p>	
	<p>from which</p>	
	<p>A fence cor., bears N. 20° E., 102 lks. dist.; fences extend N, E, and S.</p>	
	<p>A ponderosa pine, 8 ins. diam., bears N. 32° E., 144 lks. dist., mkd. C E NW 1/64 S24 BT.</p>	
19.89	<p>The point for the NW 1/16 sec. cor. of sec. 24.</p>	
39.77	<p>The N 1/16 sec. cor. of secs. 23 and 24.</p> <hr/>	
	<p>From the center N-NW 1/64 sec. cor. of sec. 24.</p>	
	<p>S. 89°55' W., on the E and W center line of the NW 1/4 of the NW 1/4 of sec. 24.</p>	
	<p>Over rolling land, through scattering timber.</p>	
8.80	<p>Dirt road, bears N. 85° E., curving northerly, and S. 85° W., curving southerly.</p>	
9.99	<p>Point for the NW-NW 1/64 sec. cor. of sec. 24, is 9 lks. N of the center of a dirt road which bears N. 85° E. and S. 85° W.</p>	
	<p>Set a red sandstone, 12 x 7 x 5 ins., 6 ins. underground, mkd. X on the N face, from which</p>	
	<p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 6 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, for a reference monument, bears N. 18 1/2° E., 22.7 lks. dist., with brass cap mkd. NW-NW 1/64 S24 RM 15 FT. 1977 and an arrow pointing to the cor.</p>	

Subdivision of Section 24,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A juniper, 14 ins. diam., bears N. 63° E., 38 lks. dist., mkd. NW NW 1/64 S24 BT.</p> <p>Deposit broken glass at the base of the mkd. stone.</p> <hr/> <p>N. 0°57' W., on the N and S center line of the NW 1/4 of the NW 1/4 of sec. 24.</p> <p>Over rolling land, through scattering timber.</p>
10.00	<p>The W-W 1/64 sec. cor. of secs. 13 and 24.</p> <hr/> <p>From the center E-NW 1/64 sec. cor. of sec. 24.</p> <p>N. 0°25' W., on the N and S center line of the NE 1/4 of the NW 1/4 of sec. 24.</p> <p>Over rolling land, through scattering to medium timber.</p>
10.017	<p>Point for the NE-NW 1/64 sec. cor. of sec. 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S24 NE-NW 1/64 1977</p> <p>from which</p> <p>A fence cor., bears N. 60° E., 60 lks. dist.; fences extend SE and NW.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 25° E., 51 lks. dist., mkd. NE NW 1/64 S24 BT.</p> <p>A pinyon pine, 9 ins. diam., bears N. 38° W., 49 lks. dist., mkd. NE NW 1/64 S24 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <hr/> <p>S. 89°55' W., on the E and W center line of the NE 1/4 of the NW 1/4 of sec. 24.</p> <p>Over rolling land, through scattering timber.</p>
9.99	<p>The center N-NW 1/64 sec. cor. of sec. 24.</p> <hr/> <p style="text-align: center;">Subdivision of Section 25, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 36.</p> <p>N. 0°12' E., on the N and S center line of sec. 25.</p> <p>Over rolling land, through dense timber.</p>

Subdivision of Section 25,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
19.985	<p>Point for the center S 1/16 sec. cor. of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C</p> <p>S 1/16 S25</p> <p>C</p> <p>1977</p> </div> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 75 1/2° E., 43 lks. dist., mkd. C S 1/16 S25 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 17° W., 49 lks. dist., mkd. C S 1/16 S25 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p>	
39.97	<p>Point for the center 1/4 sec. cor. of sec. 25, at intersection with the E and W center line of sec. 25.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R18E</p> <p>C 1/4 S25</p> <p>1977</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 23° E., 9 lks. dist., mkd. C 1/4 S25 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears S. 39° W., 8 lks. dist., mkd. C 1/4 S25 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>	
80.00	<p>The 1/4 sec. cor. of secs. 24 and 25.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 30, on the E bdy. of the Tp.</p> <p>N. 89°35' W., on the E and W center line of sec. 25.</p> <p>Over rolling land, through dense timber.</p>	
39.56	<p>The center 1/4 sec. cor. of sec. 25.</p>	
59.10	<p>Dirt road, bears N and S.</p>	

Subdivision of Section 25,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS	
79.18	The 1/4 sec. cor. of secs. 25 and 26.
	<p style="text-align: center;">Subdivision of Section 26, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>
	From the 1/4 sec. cor. of secs. 26 and 35.
	N. 0°06' E., on the N and S center line of sec. 26.
	Over rolling land, through dense timber.
37.40	Dirt road, bears N. 55° E. and S. 55° W.
38.70	Dirt road, bears S. 75° E. and N. 75° W.
39.76	Point for the center 1/4 sec. cor. of sec. 26,
	at intersection with the E and W center line of
	sec. 26.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
	in the ground, with brass cap mkd.
	<p style="text-align: center;">T11N R18E C 1/4 S26 1977</p>
	from which
	<p style="text-align: center;">A pine, 8 ins. diam., bears N. 82° E., 38 lks. dist., mkd. C 1/4 S26 BT.</p>
	<p style="text-align: center;">A pine, 10 ins. diam., bears S. 45° W., 31 lks. dist., mkd. 1/4 S26 BT.</p>
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high,
	W of the cor.
79.67	The 1/4 sec. cor. of secs. 23 and 26.
	From the 1/4 sec. cor. of secs. 25 and 26.
	S. 89°05' W., on the E and W center line of sec. 26.
	Over rolling land, through scattering timber, partially
	burned.
20.10	Point for the center E 1/16 sec. cor. of sec. 26.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins.
	in the ground, to solid rock, and in a mound of stone,
	2 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T11N R18E E 1/16 C—C S26 1977</p>
	from which
	<p style="text-align: center;">A pine, 7 ins. diam., bears S. 6 1/2° E., 22 lks. dist., mkd. C E 1/16 S26 BT.</p>

Subdivision of Section 26,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>An alligator juniper, 6 ins. diam., bears N. 46 1/2° W., 43 lks. dist., mkd. C E 1/16 S26 BT.</p>	
40.20	The center 1/4 sec. cor. of sec. 26.	
42.30	Dirt road, bears N and S.	
55.70	Dirt road, bears N. 65° E. and S. 65° W.	
80.06	The 1/4 sec. cor. of secs. 26 and 27.	
<p>Subdivision of Section 35, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>		
	<p>From the 1/4 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp.</p> <p>N. 0°02' E., on the N and S center line of sec. 35.</p> <p>Over rolling land, through dense timber.</p>	
3.50	Dirt road, bears N. 80° E. and S. 80° W.	
39.78	<p>Point the center 1/4 sec. cor. of sec. 35, at inter- section with the E and W center line of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C 1/4 S35 1977</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 68 1/2° W., 39 lks. dist., mkd. C 1/4 S35 BT.</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 21 1/2° W., 48 lks. dist., mkd. C 1/4 S35 BT.</p> <p>Cor. is in a wash, 5 lks. wide, 6 ins. deep draining S. 25° W.</p>	
47.00	Dirt road, bears N. 80° E. and S. 80° W.	
48.00	Top of ridge, bears E and W.	
79.51	The 1/4 sec. cor. of secs. 26 and 35.	
	<p>From the 1/4 sec. cor. of secs. 35 and 36.</p> <p>S. 89°41' W., on the E and W center line of sec. 35.</p> <p>Over rolling land, through dense timber.</p>	
19.98	Point for the center E 1/16 sec. cor. of sec. 35.	

Subdivision of Section 35,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E E 1/16 C-----C S35 1977</p> <p>from which</p> <p>An alligator juniper, 5 ins. diam., bears N. 36 1/2° E., 29 lks. dist., mkd. C E 1/16 S35 BT.</p> <p>A pine, 8 ins. diam., bears S. 24° W., 12 lks. dist., mkd. C E 1/16 S35 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>	
39.96	The center 1/4 sec. cor. of sec. 35.	
79.92	The 1/4 sec. cor. of secs. 34 and 35.	
<p>Subdivision of Section 36, T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona</p>		
	<p>From the 1/4 sec. cor. of secs. 1 and 36, on the S bdy. of the Tp.</p> <p>N. 0°01' E., on the N and S center line of sec. 36.</p>	
7.70	Wash, 20 lks. wide, 1 ft. deep, drains N. 70° E.	
14.90	Dirt road, bears N. 80° E. and S. 80° W.	
19.90	Point for the center S 1/16 sec. cor. of sec. 36.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R18E C S 1/16 S36 C 1977</p> <p>from which</p> <p>A pine, 9 ins. diam., bears S. 17° E., 53 lks. dist., mkd. C S 1/16 S36 BT.</p> <p>A pine, 12 ins. diam., bears N. 50° W., 25 lks. dist., mkd. C S 1/16 S36 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>	

Subdivision of Section 36,
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is 10 lks. W of a dirt road, bearing N. 10° E. and S. 10° W.</p>	
39.80	<p>Point for the center 1/4 sec. cor. of sec. 36, at intersection with the E and W center line of sec. 36.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T11N R18E C 1/4 S36 1977</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 65 1/2° W., 59 lks. dist., mkd. C 1/4 S36 BT.</p>	
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 49° W., 92 lks. dist., mkd. C 1/4 S36 BT.</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p>	
45.00	<p>Dirt road, bears S. 55° E. and N. 55° W.</p>	
55.90	<p>Dirt road, bears E and W.</p>	
79.70	<p>The 1/4 sec. cor. of sec. 25 and 36.</p>	
	<hr/> <p>From the 1/4 sec. cor. of secs. 31 and 36, on the E bdy. of the Tp.</p>	
	<p>N. 89°40' W., on the E and W center line of sec. 36.</p>	
	<p>Over rolling land, through dense timber.</p>	
39.91	<p>The center 1/4 sec. cor. of sec. 36.</p>	
79.70	<p>The 1/4 sec. cor. of secs. 35 and 36.</p>	
	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p>	
	<p>The land encompassed in this survey is located about 9 miles southwest of Overgaard, Arizona. The area surveyed varies from rolling and mountainous in the southern portion to rolling in the remainder, except for a few cleared occupied areas that are nearly level. Elevation ranges from about 7,100 to 6,400 feet above sea level. The soil is a black clay loam with rock deposits along most of the ridges. The southern portion of the township is covered with dense pine timber, along with scattering oak and juniper, except for portions of sections 13, 22, 23, 24, 25 and 26, where a forest fire has burned the timber which has been replaced with a thick undergrowth of oak brush. The northern portion of the township has a cover of pine, oak and juniper, with juniper being the dominating growth. Drainage is generally north and east, except for the southern portions of section 35 and 36, where the drainage is south and east.</p>	

General Description
T. 11 N., R. 18 E., Gila and Salt River Mer., Arizona

CHAINS

Access is provided by State Highway No. 260, passing through the township from east to west, with several forest service roads and track roads branching off in all directions.

Earthen stock ponds are located in sections 13, 22 and 24. A house is located on patented land in the NW 1/4 of the SW 1/4 of section 2, with another house and a well pump house located partly on patented land and partly on public land, in the south one half of the SE 1/4 of the SW 1/4 of section 2. Several buildings are located on patented land in the NW 1/4 of section 3, none of which are occupied. A cabin is located in the NE 1/4 of section 5. A trailer home, partially enclosed, is located on the east and west center line of section 5, partly on patented and partly on public land. A house is located on patented land in the NE 1/4 of section 13. Homes are located on patented land in sections 22 and 23.

There is no active mining or visible trace of minerals in the area.

CHAINS		

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Survey Aid
Dirk L. Peterson	Survey Aid
Richard H. Bancroft	Survey Aid
Duane R. Ferneau	Survey Aid
Jay D. Lytle	Survey Aid
Dickie L. Knight	Survey Aid

CERTIFICATE OF SURVEY

~~(X)~~(We), Harry K. Smith and Paul L. Reeves, Cadastral Surveyors , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day of June , 19 77 , ~~(X)~~(We) have dependently resurveyed portions of the south, east, and north boundaries and a portion of the subdivisional lines, and surveyed the subdivision of certain sections of Township 11 North, Range 18 East,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by ~~(X)~~(us) and under ~~(X)~~(our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Sept. 22, 1978
(Date)

Harry K. Smith
(Cadastral Surveyor)

Sept. 22, 1978
(Date)

Paul L. Reeves
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

The foregoing field notes of the dependent resurvey of portions of the south, east, and north boundaries and a portion of the subdivisional lines, and the survey of the subdivision of certain sections of T. 11 N., R. 18 E., of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith and Paul L. Reeves, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

NOV 28 1978
(Date)

Bernard W. Zolner
(Chief, Division of Cadastral Survey)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 11 N., R. 18 E., G&SRM, Arizona , is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849 - 626