

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE  
DEPENDENT RESURVEY OF A PORTION OF THE  
SUBDIVISIONAL LINES  
AND THE  
SURVEY OF THE  
SUBDIVISION OF SECTIONS 22, 23, 26, 27, AND 35,  
TOWNSHIP 8 NORTH, RANGE 27 EAST

Of the GILA AND SALT RIVER Meridian,  
ARIZONA  
In the State of \_\_\_\_\_

EXECUTED BY

HARRY K. SMITH, CADASTRAL SURVEYOR

Under special instructions dated AUGUST 19, 19 76, approved AUGUST 20, 1976,

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 589, and assignment instructions dated AUGUST 19,, 19 76.

Survey commenced SEPTEMBER 8, 19 76  
Survey completed SEPTEMBER 11, 19 78

1A

BOOK 5 088

INDEX DIAGRAM

Township 8 North, Range 27 East

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
			12	9 8	
30	29	28	11 27	6 26	1 25
			10	4	
31	32	33	34	3 35	36

Subdivision,	Sec. 22	-----	Page 13
"	Sec. 23	-----	" 16
"	Sec. 26	-----	" 20
"	Sec. 27	-----	" 30
"	Sec. 35	-----	" 32

Township 8 North, Range 27 East,  
Gila and Salt River Meridian, Arizona

## CHAINS

The south boundary was surveyed in 1883 by W. R. Fitzgerald. The subdivisional lines were surveyed in 1883 by A. E. Shoemaker. The south boundary and the subdivisional lines were resurveyed in 1940 by Ty White, Claud F. Warner and Frank Motoh.

The following field notes describe the dependent resurvey of a portion of the subdivisional lines and the survey of the subdivision of sections 22, 23, 26, 27 and 35 of Township 8 North, Range 27 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 589, Arizona, dated August 19, 1976.

The directions of lines were determined by direct solar observations and refer to the true meridian. Preliminary to the resurvey, the lines of the 1940 resurvey were retraced and all of the corners recovered. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of section 35, as scaled from United States Geological Survey quadrangle map, "GREER, ARIZ.", prepared in 1969, is as follows:

Latitude 34°02.3' N.      Longitude 109°27.3' W.

The mean magnetic declination is 15° E.

---

Dependent Resurvey of a Portion of the Subdivisional Lines of T. 8 N., R. 27 E., Gila & Salt River Mer., Ariz.

---

(Restoring the survey executed in 1883 by A. E. Shoemaker and the 1940 resurvey by Ty White, Claud F. Warner and Frank Motoh.)

---

From the cor. of secs. 25, 26, 35 and 36, monumented with an iron post, 2 ins. diam., projecting 6 ins. above a mound of stone, 3 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940

A pine, 18 ins. diam., bears N. 32° E.,  
87 lks. dist., mkd. S25 BT, through a partially  
healed blaze.

A pine, 14 ins. diam., bears S. 77 1/2° E.,  
34 lks. dist., mkd. T8N R27E S36 BT.

A pine, 14 ins. diam., bears S. 39 1/4° W.,  
8 lks. dist., mkd. with a healed blaze.

A pine, 22 ins. diam., bears N. 62 1/4° W.,  
155 lks. dist., mkd. T8N R27E S26 BT.

N. 0°27' E., bet. secs. 25 and 26.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	Over gently rolling land through dense pine timber.
4.70	Bladed road, abandoned, bears S. 85° E. and N. 85° W.; enter scattering pine timber.
5.035	Point for the S-S-S 1/256 sec. cor. of secs. 25 and 26.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>S-S-S 1/256 S26   S25 1976</p>
	from which
	A pine, 7 ins. diam., bears S. 78 1/2° E., 11 lks. dist., mkd. S S S 1/256 S25 BT.
	A pine, 7 ins. diam., bears S. 79° W., 75.5 lks. dist., mkd. S S S 1/256 S26 BT.
	A fence cor., bears S. 75° E., 2.5 lks. dist.; fences extend westerly and irregularly N. 0°40' E.
	Continue through fenced grass land and scattering pine timber, along the W side of a fence.
20.14	Point for the S 1/16 sec. cor. of secs. 25 and 26, not monumented.
34.60	Rim of Benny Creek Canyon, bears S. 30° E. and N. 30° W. The N end of a fence line extending irregularly S. 0°40' W., bears East, 12 lks. dist., descend over NE slope, through dense timber.
35.245	Point for the N-N-S 1/256 sec. cor. of secs. 25 and 26.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>N-N-S 1/256 S26   S25 1976</p>
	from which
	A fir, 10 ins. diam., bears S. 71° E., 72 lks. dist., mkd. N N S 1/256 S25 BT.
	A volcanic stone, 4 x 3 x 4 ft. high, bears N. 42 1/2° W., 13 lks. dist., mkd. XBO on the S face.
40.28	The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 30 ins. diam., bears N. 55 1/2° E., 42 lks. dist., mkd. 1/4 S25 BT.</p> <p>A fir, 11 ins. diam., bears S. 67 1/2° W., 42 lks. dist., mkd. with a healed blaze.</p> <hr/> <p>N. 0.27° E., beginning new measurement.</p>
14.00	Benny Creek with a stream of water 15 lks. wide and 3 ins. deep., flowing NW.
17.00	Rim of Benny Creek Canyon bears NW and SE.
20.15	Point for the N 1/16 sec. cor. of secs. 25 and 26, not monumented.
30.20	Benny creek, course N. 75° E.
31.20	Spur, slopes E.
32.40	Long Creek, with a stream of water running, 5 lks. wide, 3 ins. deep, flowing E.
40.30	The cor. of secs. 23, 24, 25 and 26, monumented with an iron post, 2 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940
	<p>A pine, 18 ins. diam., bears N. 46° E., 222 lks. dist., mkd. with a healed blaze. (Record bearing, N. 32 1/2° E.)</p> <p>A pine, 18 ins. diam., bears S. 75° E., 28 lks. dist., mkd. with a healed blaze. (Record bearing, S. 83 3/4° E.)</p> <p>A pine, 20 ins. diam., bears S. 47° W., 137 lks. dist., mkd. with a healed blaze. (Record bearing, S. 32° W.)</p> <p>A pine, 14 ins. diam., bears N. 3° W., 200 lks. dist., mkd. with a healed blaze. (Record, N. 22° W., 203 lks. dist.)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 34 and 35, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A pine, 15 ins. diam., bears S. 43 1/2° E., 64 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 22 ins. diam., bears N. 86° W., 28 lks. dist., mkd. 1/4 S34 BT.</p> <p>N. 0°20' W., bet. secs. 34 and 35.</p> <p>Over rolling land, through dense pine and fir timber.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS		
20.985	<p>Point for the N 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E N 1/16 S34   S35 1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 43° E., 31.5 lks. dist., mkd. N 1/16 S35 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 71 1/2° W., 54 lks. dist., mkd. N 1/16 S34 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of the cor.</p>	
41.97	<p>The cor. of secs. 26, 27, 34 and 35, monumented with an iron post, 2 ins. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A fir, 13 ins. diam., bears N. 74° E., 73 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 32°45' E., 75 lks. dist., mkd. T8N R27E S35 BT.</p> <p style="padding-left: 40px;">The stumphole of an unrooted pine, bears S. 37 1/2° W., 138 lks. dist.; pine tree lying alongside is mkd. T8N R27E S34 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N. 39 1/2° W., 45 lks. dist., mkd. T8N R27E S27 BT.</p> <p>Add the date 1976 to the brass cap, from which a new bearing tree</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 31°45' W., 39.5 lks. dist., mkd. T8N R27E S34 BT.</p>	
19.30	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 86°33' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through dense timber and scattering undergrowth.</p> <p>Power line, bears S. 20° E. and N. 20° W.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
20.06	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E</p> <p style="text-align: center;">E 1/16 <math>\frac{S26}{S35}</math></p> <p style="text-align: center;">1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 47 1/2° E., 53 lks. dist., mkd. E 1/16 S26 BT.</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 62 1/2° E., 78 lks. dist., mkd. E 1/16 S35 BT.</p> <p style="padding-left: 40px;">A local cor., a re-bar, 1/2 in. diam., projecting 5 ins. above ground, bears N. 82 1/4° W., 13 lks. dist.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, N of the cor.</p>
21.15	State Highway No. 373, asphalt surfaced, bears N and S.
21.90	Fence projects westerly along the sec. line.
27.40	Fence projects N; continue along fence line.
33.50	Fence projects N; continue along fence line.
36.43	Fence cor.; fences extend E, along the sec. line, and irregularly S.
39.70	Cindered road, bears N and SW.
40.12	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine stump, 14 ins. diam., sawed off 4 ins. above ground, bears N. 1/2° E., 48 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 14 1/2° W., 40 lks. dist., mkd. with a healed blaze.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 86°35' W., beginning new measurement.</p>
16.00	Fence, bears S. and N. 10° W.
16.50	Rocky rim; edge bears N and S.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS		
20.06	<p>The W 1/16 sec. cor. of secs. 26 and 35, monumented with a local cor., an open end pipe, 1 in. diam., set in a mound of stone, 2 ft. base, 6 ins. high. This position is accepted as the cor. position; not remonumented.</p> <hr/> <p>N. 86°35' W., beginning new measurement.</p>	
1.20	<p>Hall Creek, with a stream of water, 10 lks. wide, 8 ins. deep, flows N.</p>	
4.00	<p>Cindered road, bears S. 5° E. and N. 5° W.</p>	
5.005	<p>The E-W-W 1/256 sec. cor. of secs. 26 and 35, monumented with a local cor., a re-bar, 5/8 in. diam., projecting 2 ins. above ground. This position is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">E-W-W 1/256    <u>S26</u>                               S35</p> <p style="text-align: center;">1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 26 1/2° W., 25 lks. dist., mkd. E W W 1/256 S35 BT.</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 67 1/4° W., 30.5 lks. dist., mkd. E W W 1/256 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N of the cor.</p> <p>Reset the local cor. alongside the iron post.</p> <hr/> <p>N. 86°37' W., beginning new measurement.</p> <p>Ascending over mountainous land, covered with dense timber.</p>	
.01	<p>Fence, bears N and S.</p>	
15.03	<p>The cor. of secs. 26, 27, 34 and 35.</p> <hr/> <p>N. 0°06' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through dense pine and fir timber.</p>	
21.01	<p>Point for the S 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	



Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>T8N R27E</p> <p>S 1/16</p> <p>S27   S26</p> <p>1976</p>	
	<p>from which</p> <p>A pine, 11 ins. diam., bears N. 62° E., 10 lks. dist., mkd. 1/4 S26 BT.</p> <p>A pine, 10 ins. diam., bears S. 54° W., 14.5 lks. dist., mkd. 1/4 S27 BT.</p> <p>Raise a mound of stone, 4 ft. base, 2 ft. high, W of the cor.</p>	
41.55	Ravine, drains N. 80° E.	
42.02	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official notes of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A fir, 10 ins. diam., bears S. 42°45' E., 98 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 16 ins. diam., bears N. 73° W., 10 lks. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°08' W., beginning new measurement.</p>	
16.30	Fence, bears E and W.	
18.00	Bladed dirt road, bears N. 80° E. and S. 80° W.	
21.00	<p>Point for the N 1/16 sec. cor. of secs. 26 and 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p>T8N R27E</p> <p>N 1/16</p> <p>S27   S26</p> <p>1976</p>	
	<p>from which</p> <p>A pine, 8 ins. diam., bears S. 29 1/4° E., 33 lks. dist., mkd. N 1/16 S26 BT.</p> <p>A pine, 10 ins. diam., bears S. 62°45' W., 73 lks. dist., mkd. N 1/16 S27 BT.</p> <p>A metal rod, 1 in. diam., projecting 8 ins. above ground, bears S. 4°38' E., 103 lks. dist.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS					
23.80	Fence, bears N. 50° E. and S. 50° W.; enter open field, edge bears N. 50° E. and S. 50° W.				
42.00	<p>The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 ins. diam., buried 12 ins. below the earth's surface, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 82 1/2° E., 462 lks. dist., mkd. with a healed blaze.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears S. 59°45' E., 389 lks. dist., mkd. T8N R27E S26 BT.</p> <p>Add the date 1976 to the brass cap.</p> <p>At the land owner's request, directly over the iron post set in 1940</p> <p>Set an iron post, 28 ins. long 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T8N R27E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S22</td> <td style="padding: 0 5px;">S23</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S27</td> <td style="padding: 0 5px;">S26</td> </tr> </table> <p>1976</p> </div>	S22	S23	S27	S26
S22	S23				
S27	S26				
	From the cor. of secs. 23, 24, 25 and 26.				
	N. 84°09' W., bet. secs. 23 and 26.				
	Over rolling land, through scattered timber.				
17.30	Rim of Lang Creek Canyon, bears N and S.				
20.31	Point for the E 1/16 sec. cor. of secs. 23 and 26, not monumented.				
22.30	Lang Creek, with a stream of running water 5 lks. wide 3 ins. deep, flowing SE.				
30.40	Rim of Lang Creek Canyon, bears N and S.				
40.62	<p>The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 1 in. diam., projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the remains of the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A rotted pine stump, 12 ins. diam., bears N. 5°45' E., 63 lks. dist., mkd. BT.</p> <p style="padding-left: 40px;">A rotted pine stump, 26 ins. diam., bears S. 19° E., 54 lks. dist.</p> <p>Build a mound of stone, 3 ft. base, to the top of the iron post, and add the date 1976 to the brass cap, from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears S. 7°45' W., 67 lks. dist., mkd. 1/4 S26 BT.</p>				

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

	CHAINS	
		<p>A pine, 10 ins. diam., bears N 12° W., 59 lks. dist., mkd. 1/4 S23 BT.</p> <p>The cor. is under a combination power and telephone line, N. 14° E., 11.5 lks. dist., from a bend in the line; at the bend, lines extend N. 14° E. and S. 20° E.</p> <hr/> <p>N. 84°09' W., beginning new measurement.</p> <p>Over gently rolling grass land, through scattering pine timber.</p>
	6.55	State Highway No. 373, asphalt surfaced, bears S. 25° E., and N. 25° W.
	17.62	Fence, bears northerly and southerly.
	20.295	Point for the W 1/16 sec. cor. of secs. 23 and 26.
		Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
		T8N R27E
		W 1/16 $\frac{S23}{S26}$
		1976
		from which the nearest bearing trees
		A pine, 8 ins. diam., bears N. 40°42' E., 500 lks. dist., mkd. W 1/16 S23 BT.
		A pine, 12 ins. diam., bears S. 12°30' E., 756.5 lks. dist., mkd. W 1/16 S26 BT.
		Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.
	21.25	Irrigation ditch, dry, flows S. 25° W.
	31.00	Ridge, bears N. 40° E. and S. 40° W.
	36.90	Fence, bears N. 30° E. and S. 30° W.; enter open field, edge bears N. 30° E. and S. 30° W.
	40.59	The cor. of secs. 22, 23, 26 and 27.
		<hr/> N. 0°42' E., bet. secs. 22 and 23.
		Over gently rolling land, through an alfalfa field.
	19.47	Point for the S 1/16 sec. cor. of secs. 22 and 23.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E</p> <p style="text-align: center;">S 1/16</p> <p style="text-align: center;">S22   S23</p> <p style="text-align: center;">1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 83 1/4° E., 94 lks. dist., mkd. S 1/16 S23 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 15 1/4° W., 257 lks. dist., mkd. S 1/16 S22 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p>	
20.00	Fence, bears S. 85° E. and N. 85° W.	
20.80	Bladed dirt road, bears S. 80° E. and N. 80° W.	
30.00	Spur, slopes N. 80° E.	
38.94	<p>The 1/4 sec. cor. of secs. 22 and 23, monumented with an iron post, 1 in. diam., projecting 4 ins. above a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 49°45' E., 35 lks. dist., mkd. 1/4 S23 BT.</p> <p style="padding-left: 40px;">A pine stump, 12 ins. diam., bears S. 84° W. 20 lks. dist.</p> <p>Add the date 1976 to the brass cap, from which a new bearing tree</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 41°45' W., 14.5 lks. dist., mkd. 1/4 S22 BT.</p>	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 88°30' W., bet. secs. 27 and 34.</p> <p>Over mountainous land, through medium to dense timber and undergrowth.</p> <p>This line was measured with an electronic measuring instrument and the topographic calls along this line are omitted.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
40.05	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the remains of the bearing trees mkd. in 1940</p> <p>A stump hole, bears N. 23°45' E., 27 lks. dist.</p> <p>A pine, 18 ins. diam., bears South, 85 lks. dist., mkd. 1/4 S34 BT. (Record: 80 lks. dist.)</p> <p>Add the date 1976 to the brass cap, from which a new bearing tree</p> <p>A pine, 8 ins. diam., bears N. 6 1/2° W., 149.5 lks. dist., mkd. 1/4 S27 BT.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34, monumented with an iron post, 2 ins. diam., projecting 9 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A pine 15 ins. diam., bears N. 54 1/4° E., 246 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 13 ins. diam., bears S. 52 1/4° E., 108 lks. dist., mkd. with a healed blaze.</p> <p>A pine stump, 18 ins. diam., bears S. 74° W., 400 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 22 ins. diam., bears N. 46 1/2° W., 387 lks. dist., mkd. with a partially healed blaze.</p> <p>Add the date 1976 to the brass cap, from which a new bearing tree</p> <p>A pine, 16 ins. diam., bears S. 75 1/4° W., 399 lks. dist., mkd. T8N R27E S33 BT.</p> <p>N. 0°41' W., bet. secs. 27 and 28.</p> <p>Over rolling, open meadow.</p>
12.40	Enter medium to dense timber, edge bears NE and SW.
40.91	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with an iron post, 1 in. diam., projecting 8 ins. above the ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A pine stump, 14 ins. diam., bears N. 66 1/2° E., 19 lks. dist., mkd. T.</p> <p>A pine, 13 ins. diam., bears N. 69 1/2° W., 49 lks. dist., mkd. with a healed blaze. (Record: 48 lks. dist.)</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Add the date 1976 to the brass cap, from which a new bearing tree</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 61 1/4° E., 67 lks. dist., mkd. 1/4 S27 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°32' W., beginning new measurement.</p>
18.20	Logging road, dirt, bears N. 80° E. and S. 80° W.
21.00	State Highway No. 260, asphalt surfaced, bears N. 70° E. and S. 70° W.
40.83	<p>The cor. of secs. 21, 22, 27 and 28, monumented with an iron post, 2 ins. diam., set in a mound of stone, 4 ft. base, 3 ft. high, to top of the iron post, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 54 1/4° E., 88 lks. dist., mkd. with a healed blaze. (Record: N. 54°45' E., 56 lks. dist.)</p> <p style="padding-left: 40px;">A pine stump, 25 ins. diam., bears S. 26° E., 56 lks. dist., mkd. T8N R27E S27 BT. (Record: 89 lks. dist.)</p> <p style="padding-left: 40px;">A pine, 34 ins. diam., bears S. 44 1/4° W., 111 lks. dist., mkd. T8N R27E S28 BT.</p> <p style="padding-left: 40px;">A pine stump, 15 ins. diam., bears N. 69° W., 73 lks. dist., mkd. BT.</p> <p>Add the date 1976 to the brass cap, from which new bearing trees</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 56° E., 136 lks. dist., mkd. T8N R27E S27 BT.</p> <p style="padding-left: 40px;">A pine, 18 ins. diam., bears N. 15 1/4° W., 49 lks. dist., mkd. T8N R27E S21 BT.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 86°56' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land, through an alfalfa field.</p>
12.70	Fence, bears northerly and southerly; enter open pasture.
19.10	Enter medium to dense pine timber, edge bears N. 25° E. and S. 25° W.
20.00	Bladed dirt road, bears N. 25° E. and S. 25° W.
20.22	Point for the E 1/16 sec. cor. of secs. 22 and 27.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E S22 E 1/16 S27 1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 52 1/4° W., 46 lks. dist., mkd. E 1/16 S27 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 55° W., 32 lks. dist., mkd. E 1/16 S22 BT.</p>
21.15	Fence, bears irregularly N and S.
21.90	Irrigation ditch, with a stream of water, 2 lks. wide, 3 ins. deep, flows S. 5° E.
35.00	Logging road, dirt, bears N. 40° E. and S. 40° W.
40.44	<p>The 1/4 sec. cor. of secs. 22 and 27, monumented with an iron post, 1 in. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine, 14 ins. diam., bears N. 3°45' E., 48 lks. dist., mkd. 1/4 S22 BT.</p> <p style="padding-left: 40px;">A pine, 23 ins. diam., bears S. 2 1/2° E., 56 lks. dist., mkd. 1/4 S27 BT. (Record: 55 lks. dist.)</p>
<p>Subdivision of Sec. 22, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 22 and 27.</p> <p>N. 0°38' E., on the N and S center line of sec. 22.</p> <p>Over rolling land, through medium to dense pine timber.</p>
9.30	Irrigation ditch, with a stream of water, 2 lks. wide, 6 ins. deep, flows S. 85° E.
10.80	Lang Creek, with a stream of water, 4 lks. wide, 6 ins. deep, flows N. 55° E.
17.15	State Highway No. 260, asphalt surfaced, bears N. 55° E. and S. 55° W.
20.13	Point for the center S 1/16 sec. cor. of sec. 22, is in a track road that is no longer graded and is seldom used.

Subdivision of Sec. 22, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T8N R27E C S 1/16   S22 C 1976</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears N. 2°07' E., 113 lks. dist., mkd. C S 1/16 S22 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 2 1/2° W., 94 lks. dist., mkd. C S 1/16 S22 BT.</p>
20.15	Center of track road, bears N. 40° E. and S. 40° W.
24.05	Trail road, bears N. 60° E. and S. 60° W.
40.26	<p>Point for the center 1/4 sec. cor. of sec. 22, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T8N R27E C 1/4 S22 1976</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears N. 84°45' E., 92 lks. dist., mkd. C 1/4 S22 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 45°10' W., 84 lks. dist., mkd. C 1/4 S22 BT.</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of the cor.</p>
46.00	Enter open grassland, edge bears N. 60° E. and S. 60° W.
50.00	Graded dirt road, bears S. 75° E. and N. 75° W.
63.90	Enter scattering pine timber, edge bears N. 25° E. and S. 45° W.
80.15	Fish Creek, 15 lks. wide, 2 ft. deep, drains NE.
80.50	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 42 1/4° E., 207 lks. dist., mkd. with a healed blaze.</p>



Subdivision of Sec. 22, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A pine, 23 ins. diam., bears N. 9° W., 105 lks. dist., mkd. with a healed blaze.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23. S. 88°48' W., on the E and W center line of sec. 22. Over rolling land, through medium pine timber.</p>
8.10	Lang Creek, 3 lks. wide, 1 ft. deep, dry, drains N. 60° E.
19.30	State Highway No. 260, asphalt surfaced, bears NE and SW.
20.21	Point for the center E 1/16 sec. cor. of sec. 22.  Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	<p>T8N R27E E 1/16 C_____C S22 1976</p>
	<p>from which</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 86°45' W., 65 lks. dist., mkd. C E 1/16 S22 BT.</p> <p style="padding-left: 40px;">A pine 11 ins. diam., bears N. 36° W., 52 lks. dist., mkd. C E 1/16 S22 BT.</p> <p>Deposit brown broken glass at the base of the iron post.</p>
40.42	The center 1/4 sec. cor. of sec. 22.
76.80	Fish Creek, with a stream of water, 15 lks. wide, 8 ins. deep, flows N. 35° E.
80.81	The 1/4 sec. cor. of secs. 21 and 22, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940
	<p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 46° E., 49 lks. dist., mkd. 1/4 S22 BT.</p> <p style="padding-left: 40px;">A pine, 12 ins. diam., bears S. 80° W., 22 lks. dist., mkd. with a healed blaze.</p> <p>A mound of stone, 3 ft. high, 2 ft. base, is W of the cor.</p>
	<p>SE 1/4, Section 22</p> <hr/>
	<p>From the E 1/16 sec. cor. of secs. 22 and 27. N. 0°41'30" E., on the N and S center line of the SE 1/4 of sec. 22.</p>

Subdivision of Sec. 22, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS		
	Over rolling land, through medium to dense undergrowth.	
19.81	Point for the SE 1/16 sec. cor. of sec. 22, at intersection with the E and W center line of the SE 1/4.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.	
	T8N R27E SE 1/16 S22 1976	
	from which	
	A pine, 12 ins. diam., bears S. 75 1/4° W., 108 lks. dist., mkd. SE 1/16 S22 BT.	
	A pine, 10 ins. diam., bears N. 40°45' W., 102 lks. dist., mkd. SE 1/16 S22 BT.	
32.00	Lang Creek, flows NE, as scaled from U.S.G.S. topographic map, Greer, Ariz., dated 1969.	
38.73	State Highway No. 260, asphalt surfaced, bears NE and SW.	
39.62	The center E 1/16 sec. cor. of sec. 22.	
	_____	
	From the S 1/16 sec. cor. of secs. 22 and 23.	
	S. 87°52' W., on the E and W center line of the SE 1/4 of sec. 22.	
	Along the S edge of timber, over gently rolling land.	
7.00	Fence, bears N. 20° E. and S. 20° W.; enter rolling land, with a medium to dense cover of timber.	
7.80	Bladed dirt road, bears N and S.	
20.00	Fence, bears N and S.	
20.21	The SE 1/16 sec. cor. of sec. 22.	
27.50	Lang Creek, with a stream of water, 7 lks. wide, 4 ins. deep, flows N. 35° E.	
36.50	State Highway No. 260, asphalt surfaced, bears N. 55° E. and S. 55° W.	
40.42	The center S 1/16 sec. cor. of sec. 22.	
	Subdivision of Section 23, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona	
	_____	
	From the 1/4 sec. cor. of secs. 23 and 26.	
	N. 0°43' E., on the N and S center line of sec. 23.	
	Over rolling land, through medium pine timber.	

Subdivision of Section 23, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
5.90	Lang Creek, with a stream, of water, 3 lks. wide, 3 ins. deep, flows S. 55° E.
19.805	<p>Point for the center S 1/16 sec. cor. of sec. 23.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R27E</p> <p>C</p> <p>S 1/16   S23</p> <p>C</p> <p>1976</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 16 ins. diam., bears N. 28 1/2° E., 45.5 lks. dist., mkd. CS 1/16 S23 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 3° W., 125 lks. dist., mkd. CS 1/16 S23 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
36.70	Track road, bears S. 15° E. and N. 15° W.
39.61	<p>Point for the center 1/4 sec. cor. of sec. 23, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R27E</p> <p>C 1/4 S23</p> <p>1976</p> </div> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 61°45' E., 52 lks. dist., mkd. C 1/4 S23 BT.</p> <p style="padding-left: 40px;">A pine, 11 ins. diam., bears S. 61° W., 119.5 lks. dist., mkd. C 1/4 S23 BT.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of the cor.</p>
42.85	Cindered road, bears S. 55° E. and N. 55° W.
44.40	State Highway No. 260, asphalt surfaced, bears N. 74° E. and S. 74° W.
47.60	Fence, bears N. 74° E. and S. 74° W.
50.30	Fish Creek, with a stream of water, 5 lks. wide, 3 ins. deep, flows SE.
79.05	Cindered road, bears S. 70° E. and N. 70° W.

Subdivision of Section 23, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
79.22	<p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 1 in. diam., projecting 10 ins. above ground, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A pine, 14 ins. diam., bears N. 32 1/2° E., 255 lks. dist., mkd. with a healed blaze.</p> <p>A pine stump, 20 ins. diam., bears S. 19° W., 129 lks. dist.</p> <p>Add the date 1976 to the brass cap, from which</p> <p>A new bearing tree, a pine, 7 ins. diam., bears S. 33°45' E., 232 lks. dist., mkd. 1/4 S23 BT.</p> <p>A fence cor., bears S. 30° W., 3 lks. dist.; fences extend N and E.</p>
	<p>From the 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1 in. diam., projecting 1 in. above a mound of stone, 2 1/2 ft. base, 6 ins. high, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A pine, 13 ins. diam., bears N. 61 1/4° E., 50 lks. dist., mkd. with a healed blaze.</p> <p>A pine, 24 ins. diam., bears S. 47 1/4° W., 175 lks. dist., mkd. with a healed blaze.</p> <p>N. 85°05' W., on the E and W center line of sec. 23.</p> <p>Over rolling land, through scattering to medium timber.</p>
7.20	A combination power and telephone line, bears NE and SW.
12.00	Cindered road, bears N. 10° E. and S. 10° W.
35.65	Fish Creek, with a stream of water, 4 lks. wide, 2 ins. deep, flows S. 40° E.
36.80	Cindered road, bears S. 40° E. and N. 40° W.
40.56	The center 1/4 sec. cor. of sec. 23.
41.30	Track road, bears S. 10° E. and N. 10° W.
49.50	Cindered road, bears NE and SW.
52.35	State Highway No. 373, asphalt surfaced, bears NE and SW.
55.90	Fence, bears N. 30° E. and S. 30° W.
60.84	Point for the center W 1/16 sec. cor. of sec. 23.

Subdivision of Section 23, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T8N R27E W 1/16 C_____C S23 1976
	from which
	A pine, 13 ins. diam., bears N. 43° E., 61 lks. dist., mkd. CW 1/16 S23 BT.
	A pine, 10 ins. diam., bears S. 10 1/2° W., 87.5 lks. dist., mkd. CW 1/16 S23 BT.
	Raise a mound of stone, 3 1/2 ft. base, 3 ft. high, N of the cor.
67.30	Lang Creek, with a stream of water, 5 lks. wide, 5 ins. deep, flows S. 70° E.
81.12	The 1/4 sec. cor. of secs. 22 and 23.
<hr/>	
SW 1/4, Section 23	
<hr/>	
	From the W 1/16 sec. cor. of secs. 23 and 26.
	N. 0°42' E., on the N and S center line of the SW 1/4 of sec. 23.
	Over gently rolling meadow.
3.00	Irrigation ditch, dry, flows S. 25° W.
6.10	Same irrigation ditch, dry, flows S. 5° E.
13.60	Same irrigation ditch, dry, flows S. 60° W.
13.80	Fence, bears N. 80° E. and S. 80° W.
18.30	Enter scattering to medium timber, edge bears E and W.
19.64	Point for the SW 1/16 sec. cor. of sec. 23, at intersection with the E and W center line of the SW 1/4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 17 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T8N R27E SW 1/16 S23 1976
	from which
	A pine, 9 ins. diam., bears N. 18° E., 58 lks. dist., mkd. SW 1/16 S23 BT.
	A pine, 9 ins. diam., bears S. 33 1/4° E., 88 lks. dist., mkd. SW 1/16 S23 BT.

Subdivision of Section 23, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
26.70	Fence, bears N. 10° E. and S. 10° W.
35.30	Same irrigation ditch, dry, flows SE.
37.20	Lang Creek, with a stream of water, 4 lks. wide, 2 ins. deep, flows S. 40° E.
39.27	The center W 1/16 sec. cor. of sec. 23.
	<hr/> From the center S 1/16 sec. cor. of sec. 23.
	N. 84°36'30" W., on the E and W center line of the SW 1/4 of sec. 23.
	Over rolling land, through medium timber.
.65	Track road, bears S. 15° E. and N. 30° W.
10.90	Lang Creek, with a stream of water, 5 lks. wide, 2 ins. deep, flows S. 25° W.
16.50	Cindered road, bears S. 55° E. and N. 55° W.
18.20	State Highway No. 373, asphalt surfaced, bears S. 25° E. and N. 15° W.
19.40	Irrigation ditch, dry, flows S.
19.90	Fence, bears S. 25° E. and N. 25° W.
20.29	The SW 1/16 sec. cor. of sec. 23.
	Continue measurement along the S edge of pine timber.
40.57	The S 1/16 sec. cor. of secs. 22 and 23.
	<hr/> Subdivision of Section 26, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona
	<hr/> From the 1/4 sec. cor. of secs. 26 and 35.
	N. 0°10'30" E., on the N and S center line of sec. 26.
	Over gently rolling land, through dense pine timber.
20.575	The center S 1/16 sec. cor. of sec. 26, monumented with a local cor., a re-bar, 5/8 in. diam., projecting 8 ins. above ground. This position is accepted as the cor. position; not remonumented.
	<hr/> N. 0°08' E., beginning new measurement.
	Through scattering timber.
20.56	The center 1/4 sec. cor. of sec. 26, monumented with a local cor., a re-bar, 3/4 in. diam., projecting 2 ins. above a concrete base, 18 ins. diam. This position is accepted as the cor. position.

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Marked the top of the re-bar, C 1/4 S26, from which</p> <p>A pine, 10 ins. diam., bears N. 27°45' E., 144 lks. dist., mkd. C 1/4 S26 BT.</p> <p>A gray granite boulder, 4x4x5 1/2 ft. high, bears N. 13 1/4° W., 164.5 lks. dist., mkd. XBO on the SW face, 1 ft. from the top and 1 ft. from the W edge.</p> <hr/> <p>N. 0°09'30" E., beginning new measurement.</p>	
.20	Fence, bears E and W.	
3.50	Hall Creek, with a stream of water, 15 lks. wide, 8 ins. deep, flows N. 60° E.	
6.60	Cindered road, bears NE and SW.	
20.575	Point for the center N 1/16 sec. cor. of sec. 26.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8N R27E</p> <p>C</p> <p>N 1/16   S26</p> <p>C</p> <p>1976</p> </div>	
	<p>from which</p> <p>A pine, 7 ins. diam., bears N. 78 1/2° E., 103 lks. dist., mkd. CN 1/16 S26 BT.</p> <p>A pine, 9 ins. diam., bears S. 83 1/2° W., 26.5 lks. dist., mkd. CN 1/16 S26 BT.</p>	
29.70	State Highway No. 373, asphalt surfaced, bears S. 25° E. and N. 25° W.	
41.15	The 1/4 sec. cor. of secs. 23 and 26.	
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>N. 85°20'30" W., on the E and W center line of sec. 26.</p> <p>Ascending a steep, rocky E slope, covered with medium timber.</p>	
3.50	Top of ascent; rocky rim, bears N and S.	
5.045	Point for the center E-E-E 1/256 sec. cor. of sec. 26.	

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">S26 C-E-E-E 1/256 1976</p>
	from which
	<p style="text-align: center;">A pine, 10 ins. diam., bears N. 60 1/2° E., 104 lks. dist., mkd. CEEE 1/256 S26 BT.</p>
	<p style="text-align: center;">A pine, 6 ins. diam., bears S. 21° E., 47 lks. dist., mkd. CEEE 1/256 S26 BT.</p>
20.18	Point for the center E 1/16 sec. cor. of sec. 26, not monumented.
22.90	Enter open grassy meadow, edge bears N and S. 60° W.
30.00	Enter scattering pine timber, edge bears NE and S. 10° E.
30.27	Point for the center W-E 1/64 sec. cor. of sec. 26.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">S26 C-W-E 1/64 1976</p>
	from which
	<p style="text-align: center;">A pine, 12 ins. diam., bears N. 66 1/2° W., 70 lks. dist., mkd. CWE 1/64 S26 BT.</p>
	<p style="text-align: center;">A local cor., a re-bar, 5/8 in. diam., bears N. 87 1/4° E., 6.2 lks. dist. This local cor. is set in a fence cor.; fences extend N and N. 80° W.</p>
30.32	Combination power and telephone lines, bear S. 25° E. and N. 25° W.
33.20	Fence, bears S. 60° E. and N. 60° W.
35.85	State Highway No. 373, asphalt surfaced, bears S. 60° E. and N. 60° W.
37.05	Fence, bears S. 60° E. and N. 60° W.
40.36	The center 1/4 sec. cor. of sec. 26.



Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 85°21' W., beginning new measurement.
3.60	Hall Creek, with a stream of water, 15 lks. wide, 8 ins. deep, flows N. 85° E.
4.40	Cindered road, bears N. 65° E. and S. 65° W.
14.30	Intersect fence cor.; fences extend S and easterly.
20.15	The center W 1/16 sec. cor. of sec. 26, monumented with a local cor., an open end pipe, 24 ins. long, 3/4 in. diam., set flush with the ground, with a metal tag attached, mkd. LS5703. This position is accepted as the cor. position.
	At the cor. point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T8N R27E
	W 1/16
	C_____C
	S26
	1976
	from which
	A pine, 12 ins. diam., bears S. 44° W., 57 lks. dist., mkd. CW 1/16 S26 BT.
	A pine, 8 ins. diam., bears N. 41°15' W., 103 lks. dist., mkd. CW 1/16 S26 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.
	Reset the local cor. alongside the iron post.
	The cor. is at the W edge of an open meadow; edge bears S. 30° E. and N. 30° W.
	_____
	N. 85°22' W., beginning new measurement.
	Through dense timber.
7.90	Fence, bears N and S.
19.00	Ravine, drains NE, curving easterly.
20.15	The 1/4 sec. cor. of secs. 26 and 27.
	_____
	NE 1/4, Section 26
	_____
	From the point for the center E 1/16 sec. cor. of sec. 26.
	N. 0°19' E., on the N and S center line of the NE 1/4 of sec. 26.
	Over nearly level land, through medium pine timber.

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS		
5.09	Point for the center S-S-NE 1/256 sec. cor. of sec. 26, not monumented.	
20.36	Point for the NE 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NE 1/4, not monumented.	
40.72	The point for the E 1/16 sec. cor. of secs. 23 and 26.	
	<hr/> From the point for the N 1/16 sec. cor. of secs. 25 and 26.	
	N. 84°44' W., on the E and W center line of the NE 1/4 of sec. 26.	
	Over nearly level land, through medium timber.	
20.24	The point for the NE 1/16 sec. cor. of sec. 26.	
40.48	The center N 1/16 sec. cor. of sec. 26.	
	<hr/> From the center E-E-E 1/256 sec. cor. of sec. 26.	
	N. 0°25' E., on the N and S center line of the SE 1/4 of the SE 1/4 of the NE 1/4 of sec. 26.	
	Over nearly level land, through medium pine timber.	
5.051	Point for the SE-SE-NE 1/256 sec. cor. of sec. 26.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	<p style="text-align: center;">S26 SE-SE-NE 1/256 1976</p>	
	from which	
	<p style="padding-left: 40px;">A pine, 6 ins. diam., bears S. 22° E., 103 lks. dist., mkd. SE SE NE 1/256 S26 BT.</p>	
	<p style="padding-left: 40px;">A pine, 6 ins. diam., bears N. 36°45' W., 20 lks. dist., mkd. SE SE NE 1/256 S26 BT.</p>	
	<p style="padding-left: 40px;">A local cor., a re-bar, 3/8 in. diam., projecting 10 ins. above ground, bears N. 5° W., 106 lks. dist.</p>	
	<hr/> N. 85°11'30" W., on the E and W center line of the S 1/2 of the SE 1/4 NE 1/4 of sec. 26.	
	Over gently rolling land, through medium timber.	
15.15	The point for the center S-S-NE 1/256 sec. cor. of sec. 26.	
	<hr/> N. 85°11'30" W., on the E and W center line of the S 1/2 of the SW 1/4 NE 1/4 of sec. 26	
10.10	Point for the center S-SW-NE 1/256 sec. cor. of sec. 26.	

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">S26 C-S-SW-NE 1/256 1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 8 ins. diam., bears N. 45°30' E., 30.5 lks. dist., mkd. C S SW NE 1/256 S26 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 85°30' W., 66 lks. dist., mkd. C S SW NE 1/256 S26 BT.</p> <p style="padding-left: 40px;">A local cor., a re-bar, 5/8 in. diam., projecting 8 ins. above ground, bears S. 86°45' W., 15 lks. dist. This local cor. is 1 lk. E of a fence cor.; fences extend southerly and westerly.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 0°14' W., on the N and S center line of the SW 1/4 of the NE 1/4 of sec. 26.</p> <p>Over rolling land, through scattering pine timber.</p> <p>3.20 Fence, bears irregularly N and S.</p> <p>5.10 Fence, bears irregularly E and W.</p> <p>5.117 The center W-E 1/64 sec. cor. of sec. 26.</p> <hr/> <p style="text-align: center;">SE 1/4, Section 26</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°18' E., on the N and S center line of the SE 1/4 of sec. 26.</p> <p>Over nearly level land, through medium pine timber.</p> <p>1.70 Bladed road, abandoned, bears S. 85° E. and N. 85° W.</p> <p>2.00 Combination power and telephone lines, bear S. 20° E. and N. 20° W.</p> <p>5.09 Point for the center S-S-SE 1/256 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S26 C-S-S-SE 1/256 1976</p>

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A pine, 8 ins. diam., bears S. 41°15' E., 91.5 lks. dist., mkd. C S S SE 1/256 S26 BT.</p> <p>A wood stake, 1 x 1/4 in., 12 ins. long, set in a mound of stone, 2 ft. base, 10 ins. high, bears N. 14°15' E., 16.2 lks. dist.</p> <p>A fence cor., bears N. 31° W., 20.5 lks. dist.; fences extend irregularly N, E and S.</p>
20.36	<p>Deposit broken glass at the base of the iron post.</p> <p>Point for the SE 1/16 sec. cor. of sec. 26, at the intersection with the E and W center line of the SE 1/4, not monumented.</p>
40.71	<p>The point for the C-E 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>N. 85°56' W., on the E and W center line of the SE 1/4 of sec. 26.</p> <p>Over gently rolling land, through medium timber.</p>
20.12	<p>The point for the SE 1/16 sec. cor. of sec. 26.</p>
40.23	<p>The center S 1/16 sec. cor. of sec. 26.</p> <hr/> <p>From the N-N-S 1/256 sec. cor. of secs. 25 and 26.</p> <p>N. 85°29' W., on the E and W center line of the NE 1/4 of the NE 1/4 of the SE 1/4 of sec. 26.</p> <p>Ascending rocky E slope, through medium timber.</p>
.90	<p>Rocky rim, edge bears SE and NW.</p>
5.038	<p>Point for the NE-NE-SE 1/256 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., over an X chiseled in solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S26 NE-NE-SE 1/256 1976</p>
	<p>from which</p> <p>A pine, 7 ins. diam., bears N. 63°45' E., 71 lks. dist., mkd. NE NE SE 1/256 S26 BT.</p> <p>A local cor., an open end pipe, 1 in. diam., projecting 16 ins. above ground, bears N. 17°54' E., 112.3 lks. dist.</p> <hr/>

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

	CHAINS	
		<p>N. 0°25' E., on the N and S center line of the NE 1/4 of the NE 1/4 of the SE 1/4.</p> <p>Over nearly level land, through medium pine timber.</p>
	5.047	<p>The center E-E-E 1/256 sec. cor. of sec. 26.</p> <hr/> <p>From the S-S-S 1/256 sec. cor. of secs. 25 and 26.</p> <p>N. 86°23'45" W., on the E and W center line of the S 1/2 of the SE 1/4 of the SE 1/4 of sec. 26.</p> <p>Over gently rolling land, through scattering pine timber.</p>
	20.08	<p>The center S-S-SE 1/256 sec. cor. of sec. 26.</p> <hr/> <p style="text-align: center;">SW 1/4, Section 26</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 26 and 35.</p> <p>N. 0°02' W., on the N and S center line of the SW 1/4 of sec. 26.</p> <p>Over nearly level bottom land, through scattering willows.</p>
	.75	<p>Hall Creek, with a stream of water, 15 lks. wide, 6 ins. deep, flows N. 70, E., curving northerly.</p>
	8.00	<p>Fence, bears S. 80° E. and N. 80° W.</p>
	11.60	<p>Cindered road, bears NE and SW; enter rolling land, covered with medium pine timber, edge bears NE and SW.</p>
	20.805	<p>The SW 1/16 sec. cor. of sec. 26, monumented with a local cor., a re-bar, 24 ins. long, 5/8 ins. diam., projecting 6 ins. above ground, with a tag attached mkd. PE 6123. This position is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E SW 1/16 S26 1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears N. 41°45' W., 37 lks. dist., mkd. SW 1/16 S26 BT.</p> <p style="padding-left: 40px;">An open end pipe, 1 in. diam., projecting 14 ins. above ground, bears N. 25° E., 7.9 lks. dist.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, NW of the cor., due to a fence projecting W.</p> <p>Reset the 5/8 in. re-bar alongside the iron post.</p>

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is at a fence cor.; fences extend N. 86°04' W. and northerly.</p>
	<p>N. 0°07'30" E., beginning new measurement.</p>
	<p>Along a N and S fence.</p>
9.00	<p>Spur, slopes NE.</p>
12.55	<p>Fence, bears E and W, 23 lks. dist., thence southerly.</p>
20.795	<p>The center W 1/16 sec. cor. of sec. 26.</p>
	<p>From the center S 1/16 sec. cor. of sec. 26.</p>
	<p>N. 85°58' W., on the E and W center line of the SW 1/4 of sec. 26.</p>
	<p>Over rolling land, through scattering to medium timber.</p>
13.20	<p>Hall Creek, with a stream of water, 20 lks. wide, 8 ins. deep, flows N. 30° E.</p>
15.20	<p>Cindered road, bears S. 30° W. and N. 10° W.</p>
18.60	<p>Cindered road, bears N. 35° E. and S. 35° W., for a short distance, to cabins.</p>
20.14	<p>The SW 1/16 sec. cor. of sec. 26.</p>
	<p>N. 86°04' W., beginning new measurement.</p>
	<p>Along an E-W fence.</p>
5.025	<p>The center E-W-SW 1/256 sec. cor. of sec. 26, monumented with a local cor., a re-bar, 24 ins. long, 5/8 in. diam., projecting 6 ins. above ground. This position is accepted as the cor. position.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p>S26 C-E-W-SW 1/256 1976</p>
	<p>from which</p>
	<p>A pine, 13 ins. diam., bears S. 80° W., 83 lks. dist., mkd. C E W SW 1/256 S26 BT.</p>
	<p>A pine, 8 ins. diam., bears N. 30°15' W., 32.5 lks. dist., mkd. C E W SW 1/256 S26 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of the cor.</p>
	<p>Reset the re-bar alongside the iron post.</p>

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The cor. is at a fence cor.; fences extend easterly and southerly.</p> <hr/> <p>N. 85°58' W., beginning new measurement.</p>
1.65	Partially abandoned fence, bears S. 20° E. and N. 20° W., curving northerly.
15.06	The S 1/16 sec. cor. of secs. 26 and 27.
	<hr/> <p style="text-align: center;">NW 1/4, Section 26</p> <hr/> <p>From the center W 1/16 sec. cor. of sec. 26.</p> <p>North, on the N and S center line of the NW 1/4 of sec. 26.</p> <p>Over gently rolling land, through an open meadow.</p>
12.40	Enter medium pine timber, edge bears SE and NW.
18.80	Partially abandoned fence, bears E and W.
20.795	<p>Point for the NW 1/16 sec. cor. of sec. 26, at intersection with the E and W center line of the NW 1/4.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E NW 1/16 S26 1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears N. 80° E., 9 lks. dist., mkd. NW 1/16 S26 BT.</p> <p style="padding-left: 40px;">A pine, 10 ins. diam., bears S. 7°15' E., 30 lks. dist., mkd. NW 1/16 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
29.60	Enter open meadow, edge bears irregularly E and W.
41.59	The W 1/16 sec. cor. of secs. 23 and 26.
	<hr/> <p>From the center N 1/16 sec. cor. of sec. 26.</p> <p>N. 84°45'30" W., on the E and W center line of the NW 1/4 of sec. 26.</p> <p>Over rolling land, through dense to scattering pine timber.</p>
14.10	Fence, bears irregularly S. 30° E. and N. 30° W.
20.22	The NW 1/16 sec. cor. of sec. 26.

Subdivision of Section 26, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

<p>CHAINS</p> <p>26.00</p> <p>33.80</p> <p>36.20</p> <p>40.44</p>	<p>Enter open meadow, edge bears S. 20° E. and N. 20° W.</p> <p>Enter medium pine timber, edge bears N and S.</p> <p>Bladed dirt road, bears S. 20° E. and N. 20° W.</p> <p>The N 1/16 sec. cor. of secs. 26 and 27.</p>
<p>Subdivision of Section 27, T. 8 N., R. 27 E., Gila and Salt River Meridian, Arizona</p>	
<p>19.00</p> <p>28.40</p> <p>41.47</p>	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°20' W., on the N and S center line of sec. 27.</p> <p>Over rolling land, through medium to dense timber.</p> <p>Enter grass covered dry lake bed, edge bears S. 65° E. and N. 65° W.</p> <p>Enter medium to dense timber, edge bears S. 75° E. and N. 75° W.</p> <p>Point for the center 1/4 sec. cor. of sec. 27, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E C 1/4 S27 1976</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 9 ins. diam., bears N. 10°15' E., 54 lks. dist., mkd. C 1/4 S27 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 52° W., 63 lks. dist., mkd. C 1/4 S27 BT.</p>
<p>46.50</p> <p>62.185</p>	<p>Descend steep N slope.</p> <p>Point for the center N 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E C N 1/16   S27 C 1976</p>



Subdivision of Section 27, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A pine, 8 ins. diam., bears N. 62° E., 88 lks. dist., mkd. C N 1/16 S27 BT.</p> <p>A pine, 7 ins. diam., bears N. 89°45' W., 36.5 lks. dist., mkd. C N 1/16 S27 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
82.90	<p>The 1/4 sec. cor. of secs. 22 and 27.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S. 87°44' W., on the E and W center line of sec. 27.</p> <p>Ascending a mountainous E slope, through medium to dense pine timber.</p> <p>Due to the rugged terrain, this line was measured with an electronic measuring instrument, limiting the number of topographic calls along the line.</p>
20.125	<p>Point for the center E 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E E 1/16 C _____ C S27 1976</p> <p>from which</p> <p>A pine, 11 ins. diam., bears N. 24° E., 48.5 lks. dist., mkd. C E 1/16 S27 BT.</p> <p>A pine, 10 ins. diam., bears S. 5° W., 32 lks. dist., mkd. C E 1/16 S27 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor., to prevent the cor. from being covered with dirt and pine needles.</p>
33.20	<p>Top of ascent, edge bears N and S.</p>
40.25	<p>The center 1/4 sec. cor. of sec. 27.</p>
69.60	<p>Dirt logging road, bears N and S.</p>
80.50	<p>The 1/4 sec. cor. of secs. 27 and 28.</p> <hr/> <p style="text-align: center;">NE 1/4, Section 27</p> <hr/> <p>From the center E 1/16 sec. cor. of sec. 27.</p> <p>N. 0°13'30" W., on the N and S center line of the NE 1/4 of sec. 27.</p>

Subdivision of Section 27, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land, through medium to dense timber.
19.50	Fence, bears S. 70° E. and N. 70° W.
20.865	Point for the NE 1/16 sec. cor. of sec. 27, at intersection with the E and W center line of the NE 1/4.
	Set an iron post, 28 ins. long 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T8N R27E NE 1/16 S27 1976
	from which
	A pine, 12 ins. diam., bears S. 85°30' E., 48 lks. dist., mkd. NE 1/16 S27 BT.
	A pine, 13 ins. diam., bears S. 4° W., 6 lks. dist., mkd. NE 1/16 S27 BT.
	A local cor., an open end pipe, 1 in. diam., projecting 18 ins. above ground, bears N. 79°30' E., 44 lks. dist.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.
	The cor. is in a ravine, drains N. 85° E.
36.50	Bladed dirt road, bears S. 5° E. and N. 5° W.
41.30	Same bladed dirt road, bears N. 25° E. and S. 25° W.
41.73	The E 1/16 sec. cor. of secs. 22 and 27.
	—————
	From the N 1/16 sec. cor. of secs. 26 and 27.
	S. 87°18' W., on the E and W center line of the NE 1/4 of sec. 27.
	Over rolling land, through medium to dense timber.
2.50	Fence, bears S. 30° W. and N. 30° E., 90 lks. dist., to a fence cor., from which fences extend N. 50° E. and N. 50° W.
8.60	Bladed dirt road, bears S. 35° E. and N. 35° W.
20.18	The NE 1/16 sec. cor. of sec. 27.
21.20	Fence, bears N and S.
33.00	Spur, slopes N. 40° E.
40.36	The center N 1/16 sec. cor. of sec. 27.

Subdivision of Section 35, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

Subdivision of Section 35, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 6 ins. above a mound of stone, 3 ft. base, 8 ins. high, with brass cap mkd. as described in the official record of the 1940 dependent resurvey of the S bdy. of T. 8 N., R. 27 E., from which the bearing trees described in 1940</p> <p>A pine, 20 ins. diam., bears N. 30° E., 39 lks. dist., mkd. 1/4 S35 BT.</p> <p>A pine, 18 ins. diam., bears S. 40 1/4° E., 97 lks. dist., mkd. 1/4 S2 BT.</p> <p>N. 0°22' W., on the N and S center line of sec. 35.</p> <p>Over gently rolling land, through medium to dense pine timber.</p>
19.10	Rosey Creek, with a stream of water, 5 lks. wide, 4 ins. deep, flows N. 80° E.
28.60	Fence, bears S. 30° E. and N. 30° W.
41.06	<p>Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E C 1/4 S35 1976</p> <p>from which</p> <p>A pine, 8 ins. diam., bears N. 64°30' E., 22 lks. dist., mkd. C 1/4 S35 BT.</p> <p>A pine, 8 ins. diam., bears S. 9° E., 41.5 lks. dist., mkd. C 1/4 S35 BT.</p>
61.53	<p>The center N 1/16 sec. cor. of sec. 35, monumented with a local cor., a re-bar, 3/4 in. diam., projecting 12 ins. above ground. This position is identical with the calculated point for the center N 1/16 sec. cor. of sec. 35, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T8N R27E C N 1/16   S35 C 1976</p>

Subdivision of Section 35, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A pine, 11 ins. diam., bears N. 74°45' E., 42.5 lks. dist., mkd. C N 1/16 S35 BT.</p> <p>A pine, 14 ins. diam., bears S. 31°15' E., 11.5 lks. dist., mkd. C N 1/16 S35 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <hr/> <p>N. 0°22' W., beginning new measurement.</p>	
.03	Fence, bears W and E, 15 lks. dist., to its terminus.	
2.35	Abandoned fence, bears E and W.	
19.85	Cindered road, bears W and NE, 40 lks. dist., thence northerly.	
20.47	The 1/4 sec. cor. of secs. 26 and 35.	
	<hr/> <p>From the 1/4 sec. cor. of secs. 35 and 36, monumented with an iron post, 1 in. diam., projecting 6 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1940 dependent resurvey, from which the bearing trees mkd. in 1940</p> <p>A pine, 13 ins. diam., bears N. 56° E., 21 lks. dist., mkd. 1/4 S36 BT.</p> <p>A pine, 10 ins. diam., bears N. 40° W., 20 lks. dist., mkd. 1/4 S35 BT.</p> <p>N. 88°03'30" W., on the E and W center line of sec. 35.</p> <p>Over rolling land, through medium to dense timber.</p>	
11.70	Combination power and telephone lines, bear S. 10° E. and N. 10° W.	
18.60	State Highway No. 373, asphalt surfaced, bears S. 25° E. and N. 25° W.	
40.54	The center 1/4 sec. cor. of sec. 35.	
77.00	Hall Creek, 10 lks. wide, 4 ins. deep, flows NE.	
80.61	The 1/4 sec. cor. of secs. 34 and 35.	
	<hr/> <p>NW 1/4, Section 35</p> <hr/> <p>From the center N 1/16 sec. cor. of sec. 35.</p> <p>N. 87°22' W., on the E and W center line of the NW 1/4 of sec. 35.</p> <p>Over rolling land, through medium to dense timber, along an E-W fence.</p>	

Subdivision of Section 35, T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

## CHAINS

- 17.90 Fence cor.; fences extend NE and easterly.
- 20.06 Fence cor.; fences extend northerly and westerly, thence along fence.
- 23.50 Hall Creek, with a stream of water, 10 lks. wide, 4 ins. deep, flows N.
- 25.025 The center E-W-NW 1/256 sec. cor. of sec. 35, monumented with a local cor, a re-bar, 18 ins. long 3/4 in. diam., projecting 8 ins. above ground. This position is accepted as the cor. position.
- At the cor. point
- Set an iron post, 28 ins. long 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
- S35  
C-E-W-NW  
1/256  
1976
- from which
- A pine, 13 ins. diam., bears S. 25° W.,  
67 lks. dist., mkd. C E W NW 1/256 S35 BT.
- A pine, 19 ins. diam., bears N. 83°45' W.,  
62 lks. dist., mkd. C E W NW 1/256 S35 BT.
- Reset the re-bar alongside the iron post.
- The cor. is 1 lk. S of a fence cor.; fences extend northerly and westerly.
- \_\_\_\_\_
- N. 87°16' W., beginning new measurement.
- 15.055 The N 1/16 sec. cor. of secs. 34 and 35.

## GENERAL DESCRIPTION

The southeast corner of section 35 is about 1 3/4 miles north of Greer, Arizona. Elevation ranges from near 8,900 feet above sea level to about 7,850 feet above sea level. The land varies from rolling and mountainous to nearly level. The soil is of black loam and clay and is rocky. Most of the area is covered with pine, fir, spruce and a few scattered juniper, with pine being the predominant species. Those portions of the land that are not covered with timber have an abundance of native grasses that are used for livestock grazing. An alfalfa field covers portions of the SE 1/4 of section 22, the SW 1/4 of section 23, the NW 1/4 of section 26 and the NE 1/4 of section 27.

Drainage in the area is provided by Hall Creek, Lang Creek and Fish Creek, which flow into the Little Colorado River, the general drainage being easterly. Rosey Creek and Benny Creek provide drainage for the south 1/2 of section 35, draining easterly.

T. 8 N., R. 27 E.,  
Gila and Salt River Meridian, Arizona

## CHAINS

Access is provided by State Highway No. 260, which enters the east boundary of section 23 and traverses through sections 22 and 27, exiting the west boundary of section 27. State Highway No. 373 projects southerly from State Highway No. 260 near the center of section 23 and traverses through sections 26 and 35, exiting the east boundary of section 35. Further access is provided by numerous cindered roads, track roads and logging roads. Residences are located in the SE 1/4 and the SW 1/4 of section 26 and the NW 1/4 of section 35.

There is no evidence of mineral activity.

Form 9180-8  
(March 1969)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Technician
Duane R. Ferneau	Survey Aid
Edward J. Linck	Survey Aid
Jay D. Lytle	Survey Aid
John J. Bulinski	Survey Aid
William Anderson	Survey Aid
Daniel Simpson	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Harry K. Smith, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day of August, 1976, (I) ~~(We)~~ have dependently resurveyed a portion of the subdivisional lines and surveyed the subdivision of sections 22, 23, 26, 27 and 35 of Township 8 North, Range 27 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

April 17, 1979  
\_\_\_\_\_  
(Date)

*Harry K. Smith*  
\_\_\_\_\_  
(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Washington, D.C.

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and survey of the subdivision of sections 22, 23, 26, 27 and 35, of T. 8 N., R. 27 E., of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor, having been critically examined and found correct, are hereby approved.

AUG 15 1979  
\_\_\_\_\_  
(Date)

*[Signature]*  
\_\_\_\_\_  
~~Chief, Division of Cadastral Survey~~  
Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_, is a true copy of the original field notes.