

BOOK 5091

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF

A PORTION OF THE WEST BOUNDARY

THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

/ AND THE

SURVEY OF SUBDIVISIONS IN

SECTIONS 15, 26, 34 and 35,

TOWNSHIP 10 NORTH, RANGE 22 EAST

GILA AND SALT RIVER

Of the _____ Meridian,

ARIZONA

In the State of _____

EXECUTED BY

HARRY K. SMITH, SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated JUNE 23, 19 78, approved JUNE 23, 1978,

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED OCTOBER 17, 1978, APPROVED

OCTOBER 18, 1978, which provided for the surveys included under U.S. Survey/Group

Number 605, and assignment instructions dated JUNE 23, 19 78.

AND OCTOBER 19, 1978

Survey commenced SEPTEMBER 7, 19 78

Survey completed NOVEMBER 17, 19 78

1A

INDEX DIAGRAM

Township 10 NORTH, Range 22 EAST

12 6 39	10 5	9 4	9 8	7 2	6 1
7	38 8 37	9 34	10 30	11 26	12
18 36	17	33 16 31	29 15 28	24 14 24	18 13
5 19 35	36 20	21	22	23 28	17 24
3 30	29	28	27 28	22 26 21	15 25
31	32	33	26 34	20 35	13 36

- Subdivision of sec. 15 p. 40
- Subdivision of sec. 26 p. 43
- Subdivision of sec. 34 p. 45
- Subdivision of sec. 35 p. 47



United States Department of the Interior

BUREAU OF LAND MANAGEMENT
DENVER SERVICE CENTER
DENVER FEDERAL CENTER, BUILDING 50
DENVER, COLORADO 80225

1AA
IN REPLY REFER TO

9622.1 (D-401)
Group No.605
Arizona

July 8, 1981

ARIZONA STATE OFFICE BU. LAND MANAGEMENT	
JUL 13 '81	
SD	_____
ASSOC. SD	_____
PUB. AFF.	_____
EEO	_____
PLANN.	_____
RESOURCES	_____
TECH SER	_____
MGMT SER	_____
PHX. TRNG CNTR	_____
CF	_____
SEE ME	ACTION
	INFO

Memorandum

To: State Director, Arizona (942)

From: Director, BLM

Subject: Field Notes and Plat Corrections, T. 10 N.,
R. 22 E., Gila and Salt River Meridian, Arizona

The field investigation, conducted by personnel of your office, revealed that the plat and field notes of above-mentioned township and supplemental plat of section 19, same township, both accepted December 11, 1979, contain erroneous bearings and distances.

This office concurs with the suggested recommendation set forth in your memorandum dated June 17, 1981.

The following notation should be added to the Original and Triplicate Original plats of T. 10 N., R. 22 E. and the supplemental plat of section 19, same township.

Bearing of E1/2 mile between sec's. 18 and 19, should be
S. 87°59' W.

Bearing and distance of W1/2 mile between secs. 18 and 19,
should be S. 88°42' W., 36.41 chs.

Parenthetical distance of W1/2 mile between secs. 18 and
19, should be 18.935 chs. (E1/2W1/2) and 17.475 chs.
(W1/2W1/2).

See Memorandum dated July 8, 1981, file 9622.1 (D-401)

The following corrections should be made in the field notes of T. 10 N.,
R. 22 E., Gila and Salt River Meridian, Arizona, approved December 11, 1979.

On page 36, the bearing N. 89°42' W. should be S. 87°59' W.

bearing and distance of the tie at the bottom of the page should
be S. 42°14' W., 67.6 lks.

On page 37, description of corner at top of page, should read - "Cor. point is in the center of a gravel road, bears N and S."

On page 37, the bearing S. 86°09' W. should be S. 88°42' W.

the distance 36.46 should be 36.41

The following notation will be placed in the margin of pages 36 and 37 of the field notes:

Corrections made pursuant to authority of
Memorandum dated July 8, 1981, File 9622.1 (D-401)

The duplicate original plats and duplicate field notes which are in the custody of this office will be noted accordingly.

Enclosed are copies of the plats and field note pages showing the preferred method and positioning of corrected data.

For the Director, BLM

A handwritten signature in black ink, appearing to read "D. Voorhees". The signature is written in a cursive style with a large initial "D" and a checkmark-like flourish at the end.

Chief, Cadastral Survey
Examination and Approval Staff

Township 10 North, Range 22 East
Gila and Salt River Meridian, Arizona

CHAINS

The history of surveys of Township 10 North, Range 22 East, Gila and Salt River Meridian, Arizona, is as follows:

The north boundary was surveyed in 1882 by O. D. Wheeler, Deputy Surveyor, who in 1883 surveyed the south, east and west boundaries and the subdivisional lines. Sidney E. Blout, U. S. Surveyor, resurveyed the west two miles of the south boundary in 1915. In 1926, Thomas F. Myers, Chief Surveyor, Forest Service, retraced the north, south and west boundaries of section 29, resurveyed the east boundary of sec. 29, subdivided the section and surveyed Homestead Entry Survey No. 647. The east boundary of the township was resurveyed by Theodore Vander Meer, U. S. Transitman, in 1935. A portion of the west boundary was resurveyed in 1969 by Gary T. Oviatt and Ira M. Thiessen, Cadastral Surveyors. Certain corners were remonumented in 1969 by John H. Witmer, Cadastral Surveyor. A portion of the south boundary was resurveyed by Harry K. Smith, Cadastral Surveyor, in 1978, under the same group number. Several private surveys have also been performed in the area.

The following field notes describe the dependent resurvey of a portion of the west boundary, the north boundary and a portion of the subdivisional lines, and the survey of subdivisions in sections 15, 26, 34 and 35.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions and Supplemental Special Instructions for Group No. 605, Arizona, dated June 23, 1978 and October 17, 1978, respectively.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances were measured with the Zeiss, SM-4.

Preliminary to the resurvey the lines of previous surveys and resurveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 1, 2, 35 and 36, on the south boundary of the township as scaled from the quadrangle map "Lakeside, Ariz.," published by the U. S. Geological Survey in 1977, is as follows:

Latitude $34^{\circ} 12.8' N.$ Longitude $109^{\circ} 58.3' W.$

The mean magnetic declination is $14^{\circ} 00' E.$

Dependent Resurvey of a Portion of the W Bdy. of
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

(Restoring the 1883 survey by O. D. Wheeler)

Dependent Resurvey of a Portion of the W Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Beginning at the cor. of Tps. 9 and 10 N., Rs. 21 and 22 E., monumented with an iron post, 3 ins. diam., projecting 10 ins. above the ground, with brass cap mkd. as described in the official record of the 1915 resurvey from which the remains of the original bearing trees</p> <p>A ponderosa pine, 21 ins. diam., bears S. 35° E., 131 lks. dist., mkd. with a healed blaze.</p> <p>A stump hole, bears S. 21° W., 148 lks. dist.; an uprooted ponderosa pine, 16 ins. diam., lying alongside is mkd. S1.</p> <p>A dead pine, 12 ins. diam., bears N. 21° W., 96 lks. dist., mkd. T10N R21E S36 BT.</p> <p>Add the date 1978 to the brass cap from which new bearing trees</p> <p>A ponderosa pine, 6 ins. diam., bears N. 19° E., 36.5 lks. dist., mkd. T10N R22E S31 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 60° W., 44 lks. dist., mkd. T9N R21E S1 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 87° W., 61 lks. dist., mkd. T10N R21E S36 BT.</p> <p>N. 0°13' E., bet. secs. 31 and 36.</p> <p>Over rolling land, through dense timber.</p>
38.72	<p>The 1/4 sec. cor. of secs. 31 and 36, monumented with a volcanic stone, 12 x 9x 5 ins., loosely set in a scattered mound of stone, mkd. 1/4 S on one face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N 1/4 R21E R22E S36 S31 1978</p>
1.00	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N. 73° E., 26 lks. dist., mkd. 1/4 S31 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 23° W., 34.5 lks. dist., 1/4 S36 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is in an abandoned N-S fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°54' E., beginning new measurement.</p> <p>Draw, 20 lks. wide, drains N. 65° W.</p>

Dependent Resurvey of a Portion of the W Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS

39.82

The cor. of secs. 25, 30, 31 and 36, monumented with a wood post, 42 ins. long, 4 ins. squared, firmly set 18 ins. in the ground, surrounded by a scattered mound of stone, from which the remains of the original bearing trees

A dead oak, 12 ins. diam., bears N. 57° E.,
47 lks. dist., mkd. with a healed blaze.
(Record N. 51° E., 57 lks. dist.)

A stumphole, bears S. 30° E., 90 lks. dist.; an
uprooted pine 17 ins. diam., lying alongside is
mkd. TXN R22E S31 BT. (Record dist. 45 lks.)

A stumphole, bears S. 43° W., 46 lks. dist.; an
uprooted pine 13 ins. diam., lying alongside is
mkd. with a healed blaze. (Record dist. 86 lks.)

A pine stump, 13 ins. diam., bears N. 50° W.,
86 lks. dist., no marks visible.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, with brass cap mkd.

T10N
R21E|R22E
S25|S30
S36|S31
1978

from which new bearing trees

A ponderosa pine, 13 ins. diam., bears N. 13° E.,
92 lks. dist., mkd. T10N R22E S30 BT.

A juniper, 7 ins. diam., bears S. 41° E.,
79.5 lks. dist., mkd. T10N R22E S31 BT.

A ponderosa pine, 8 ins. diam., bears S. 12° W.,
75.5 lks. dist., mkd. T10N R21E S36 BT.

A ponderosa pine, 7 ins. diam., bears N. 34° W.,
146.5 lks. dist., mkd. T10N R21E S25 BT.

Reset the wood post alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of
the cor.

N. 0°22' E., bet. secs. 25 and 30.

Over rolling land, through medium to dense timber.

40.03

The 1/4 sec. cor. of secs. 25 and 30, monumented with an
iron post, 2 1/2 ins. diam., projecting 8 ins. above
ground, with brass cap mkd. as described in the official
record of the 1969 remonumentation notes, from which

An alligator juniper, 11 ins. diam., mkd. in
1969, bears S. 71° E., 16 lks. dist., mkd.
T10N R22E 1/4 S30 BT.

A pine stump, 18 ins. diam., mkd. in 1883, bears
S. 60° E., 49 lks. dist., mkd. 1/4.

Dependent Resurvey of a Portion of the W Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>An oak, 14 ins. diam., mkd. in 1883, bears S. 50° W., 60 lks. dist., mkd. with a healed blaze.</p> <p>An alligator juniper, 9 ins. diam., mkd. in 1969, bears N. 62° W., 33 lks. dist., mkd. T10N R21E S25 1/4 BT.</p>
	<p>N. 0°27' E., beginning new measurement.</p>
20.23	<p>Point for the N 1/16 sec. cor. of secs. 25 and 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N N 1/16 R21E R22E S25 S30 1978</p> <p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears S. 12° E., 10 lks. dist., mkd. N 1/16 S30 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S. 82° W., 27.5 lks. dist., mkd. N 1/16 S25 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is in a fence, bears E and West, 12 lks. dist., thence N.</p>
33.014	<p>The center of State Highway No. 60, asphalt surfaced, bears northeasterly and southwesterly.</p>
40.46	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a steel rod, 36 ins. long, 5/8 in. diam., set flush with the ground. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R21E R22E <u>S24 S19</u> S25 S30 1978</p> <p>from which</p> <p>A ponderosa pine, 21 ins. diam., bears S. 49° E., 91 lks. dist., not mkd.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 33° W., 203 lks. dist., mkd. T10N R21E S24 BT.</p> <p>Reset the steel rod alongside the iron post.</p>

Dependent Resurvey of a Portion of the W Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

	CHAINS		
		<p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is 136 lks. E of State Highway No. 260 which bears SE and NW.</p> <p>From this point an elevation marker set by the Bureau of Public Roads, bears S. 38°26' W., 17.775 chs. dist., monumented with an iron post, 2 1/2 ins. diam., projecting 7 ins. above ground, with brass cap mkd. U. S. Dept. of Agriculture 141+00 Elevation 6260.28 Feet 1935.</p> <p>This bench mark is located at the S right-of-way of State Highway No. 60.</p> <p>From this same point, the SW cor. of a baseball field, bears N. 2° E., 83.3 lks. dist.</p>	
		<p>N. 0°07' W., bet. secs. 19 and 24.</p> <p>Over gently rolling land, through scattering timber.</p>	
	20.11	<p>Point for the S 1/16 sec. cor. of secs. 19 and 24.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> T10N S 1/16 R21E R22E S24 S19 1978 </p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 9° W., 66 lks. dist., mkd. S 1/16 S24 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 9 ins. diam., bears S. 86° W., 65 lks. dist., mkd. S 1/16 S24 BT.</p> <p>Cor. is 18 lks. W of a N-S power line.</p> <p>From this point, a re-bar, 3/8 in. diam., set flush with the ground, bears S. 29 1/2° E., 47.7 lks. dist., identified as the SW cor. of Lot. No. 8, Park Plaza Subdivision, as surveyed by Clifford B. Potts, Registered Civil Engineer No. 4836, in Arizona, a record of which is on file with the Transamerica Title Company in Show Low Arizona. This re-bar was established in 1954 by Mr. Potts from the SW cor. of Lot No. 6 of the Willard Wipple Survey, executed in 1918 by J. H. Frost, surveyor, a record of which is on file with the Transamerica Title Company in Show Low, Arizona. The 1918 survey did not follow the laws of legal subdivision, therefore, the survey cannot be used to control legal subdivision cors. of this survey.</p> <p>From this same point, the SW cor. of a house, bears S. 38° E., 45 lks. dist.</p>	

Dependent Resurvey of a Portion of the W Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
40.22	<p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a re-bar, 5/8 in. diam., set 3 ins. below the surface of a graded gravel road, which in a curve, bears N and E. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position, not remonumented.</p>
	<p>N. 0°36' E., beginning new measurement.</p>
40.00	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 1/2 ins. diam., set 20 ins. below the earth's surface, on the S shoulder of a paved road, with brass cap mkd. as described in the official record of the 1969 resurvey of a portion of the E bdy. of T. 10 N., R. 21 E., from which reference monuments set in 1969</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., projecting 4 ins. above ground, bears S. 45° E., 34.8 lks. dist., with brass cap mkd. T10N R22E S19 RM 23 FT. 1969 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., projecting 3 ins. above ground, bears S. 45° W., 34.8 lks. dist., with brass cap mkd. T10N R21E S24 RM 23 FT. 1969 and an arrow pointing to the cor.</p> <p>Cor. is 22 lks. S of paved road, bears E and W.</p>
	<p>Dependent Resurvey of the N Bdy., T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona</p>
	<p>(Restoring the 1882 survey by O. D. Wheeler)</p>
	<p>From the cor. of Tps. 10 and 11 N., Rs. 22 and 23 E., monumented with an iron post, 2 1/2 ins. diam., projecting 12 ins. above ground, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes, from which the tree mkd. in 1969</p> <p style="padding-left: 40px;">A forked juniper, 10 ins. diam., bears S. 2 1/2° E., 275 lks. dist., mkd. T10N R23E S6 BT. (Record dist. 270 lks.)</p>
	<p>A mound of stone 3 ft. base, 2 ft. high is S of the cor.</p>
	<p>Cor. is 2 lks. N of an E-W fence and 53 lks. S of a dirt road, bears E and W.</p>
	<p>N. 89°56' W., bet. secs. 1 and 36.</p>
	<p>Over rolling land.</p>
	<p>Along an E-W fence.</p>
40.03	<p>The 1/4 sec. cor. of secs. 1 and 36, monumented with a basalt stone, 24 x 12 x 6 ins., loosely set in a scattered mound of stone, mkd. 1/4 on one face.</p> <p>At the cor. point</p>

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T11N R22E

1 S36

4 S 1

T10N

1978

from which

A juniper, 6 ins. diam., bears S. 66 1/2° E.,
97 lks. dist., mkd. 1/4 S1 BT.

A juniper, 6 ins. diam., bears S. 45° W.,
50 lks. dist., mkd. 1/4 S1 BT.

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, N of the cor.

Cor. is located in an E-W fence, 42 lks. S of a dirt road, bears E and W.

N. 89°48' W., beginning new measurement.

Continue along an E-W fence.

40.09

The cor. of secs. 1, 2, 35 and 36, is determined at record bearing and dist. from the SE cor. of Lot No. 512 of the Silver Lake Estates subdivision in sec. 35, T. 11 N., R. 22 E., surveyed in 1961 by Frank E. Glindmeier of Delta Surveying Inc., Scottsdale, Arizona.

From the cor. point, the SE cor. of Lot No. 512 of the Silver Lake Estate subdivision, bears N. 45°14' W., 64.3 lks. dist. monumented by an open end metal pipe, 1 in. diam., projecting 4 ins. above ground.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.

T11N R22E

S35 | S36

S 2 | S 1

T10N

1978

from which

A fence cor., bears South, 6 lks. dist.;
fences extend E, S and W.

A juniper, 4 ins. diam., bears S. 37° W.,
87.5 lks. dist., mkd. X at breast height and BT
at the base.

Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of the cor.

Cor. is 50 lks. S of a dirt road,, bears E and W.

N. 89°48' W., bet. secs. 2 and 35.

Over rolling land.

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Along an E-W fence.</p> <p>40.15 The point for the 1/4 sec. cor. of secs. 2 and 35 is determined at record bearing and dist. from the SE cor. of Lot No. 496 of the Silver Lake Estates subdivision in sec. 35, T. 11 N., R. 22 E., surveyed in 1961 by Frank E. Glindmeier of Delta Surveying Inc., Scottsdale, Arizona</p> <p>From the cor. point, the SE cor. of Lot No. 496 of the Silver lake Estates subdivision, bears N. 40°03' W., 58.9 lks. dist., monumented by an open metal pipe, 1 in. diam., projecting 4 ins. above ground.</p> <p>The cor. point falls in the center of a cattle guard in an E-W fence which crosses a graded road bearing N and S, where it is impractical to set a monument.</p> <p>from the cor. point</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 45° E., 60.6 lks. dist., with brass cap mkd. T10N R22E 1/4 S2 RM 40 FT. 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 26 ins. in the ground for a reference monument, bears S. 45° W., 60.6 lks. dist., with brass cap mkd. T10N R22E 1/4 S2 RM 40 FT. 1978 and an arrow pointing to the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°56' W., beginning new measurement.</p> <p>Continue along an E-W fence.</p>
40.07	<p>The cor. of secs. 2, 3, 34 and 35 is determined at record bearing and dist. from the SW cor. of Lot No. 481 of sec. 35, T. 11 N., R. 22 E., surveyed in 1961 by Frank E. Glindmeier of Delta Surveying Inc., Scottsdale, Arizona</p> <p>From the cor. point, the SW cor. of lot No. 481, bears N. 44°45' E., 64.6 lks. dist., monumented by an open end pipe, 3/4 ins. diam., projecting 4 ins. above ground.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 5 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T11N R22E</p> <p>S34 S35</p> <p>S 3 S 2</p> <p>T10N</p> <p>1978</p> </div> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S. 8° E., 84 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 75° W., 158 lks. dist., mkd. T10N R22E S3 BT.</p> <p>Cor. is 9 lks. N of an E-W fence, 22 lks. E of a telephone line which bears N and S, and 26 lks. W of a fence bearing N and S.</p>

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS

S. 89°58' W., bet. secs. 3 and 34.

Over rolling land, through a railed area, along an E-W fence.

39.96

The 1/4 sec. cor. of secs. 3 and 34, monumented with a basalt stone, 24 x 12 x 7 ins., loosely set 6 ins. in the ground, mkd. 1/4 on the N face.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, over an X chiseled in solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T11N R22E

$\frac{1}{4}$ S34

$\frac{4}{S}$ 3

T10N

1978

from which

A juniper, 4 ins. diam., bears N. 5° W.,
63 lks. dist., mkd. X BT at the base.

Deposit the mkd. stone in the mound alongside the iron post.

Cor. is in an E-W fence.

N. 89°51' W., beginning new measurement.

40.08

The cor. of secs. 3, 4, 33 and 34, monumented with a basalt stone, 16 x 12 x 4 ins., firmly set 10 ins. in the ground, mkd. with 2 grooves on the E and 4 grooves on the W faces.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.

T11N R22E

$\frac{S33|S34}{S}$

$\frac{4|S}{S}$ 3

T10N

1978

from which

A juniper, 7 ins. diam., bears S. 25° W.,
132 lks. dist., mkd. T10N R22E S4 BT.

A fence cor., bears South, 10 lks. dist., fences extend E, S and W, 12 lks. dist., thence N.

An alligator juniper, 11 ins. diam., bears
N. 81° W., 255.5 lks. dist., mkd. T11N R22E
S33 BT.

Deposit the mkd. stone alongside the iron post.

S. 89°01' W., bet. secs. 4 and 33.

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	Over rolling land, through scattering timber.
40.21	<p>The 1/4 sec. cor. of secs. 4 and 33, monumented with a basalt stone, 19 x 15 x 12 ins., firmly set in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. 1/4 on the N face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} T11N \\ \underline{1\ S33} \\ 4\ S\ 4 \\ T10N \\ 1978 \end{array}$ <p>from which</p> <p>A juniper, 7 ins. diam., bears N. 31° E., 74.5 lks. dist., mkd. 1/4 S33 BT.</p> <p>A juniper, 7 ins. diam., bears S. 24° E., 56.5 lks. dist., mkd. 1/4 S4 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>S. 88°42' W., beginning new measurement.</p>
40.23	<p>The cor. of secs. 4, 5, 32 and 33, monumented with a basalt stone, 24 x 12 x 9 ins., loosely set in a mound of stone, mkd. with 4 notches on the E and 2 notches on the W edges.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> $\begin{array}{r} T11N\ R22E \\ \underline{S32\ S33} \\ S\ 5\ S\ 4 \\ T10N \\ 1968 \end{array}$ <p>from which</p> <p>A juniper, 9 ins. diam., bears N. 46° E., 59 lks. dist., mkd. T11N R22E S33 BT.</p> <p>A juniper, 10 ins. diam., bears S. 36° E., 68 lks. dist., mkd. T10N R22E S4 BT.</p> <p>A juniper, 8 ins. diam., bears S. 63° W., 225.5 lks. dist., mkd. T10N R22E S5 BT.</p> <p>A juniper, 7 ins. diam., bears N. 58° W., 55 lks. dist., mkd. T11N R22E S32 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is 34 lks. N of a fence, bears S. 80° E. and N. 80° W.</p> <hr/> <p>S. 89°21' W., bet. secs. 5 and 32.</p> <p>Over rolling land, through medium timber.</p>

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS		
40.52	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with a basalt stone, 24 x 16 x 6 ins., firmly set 12 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, 6 ins. high, mkd. 1/4 on the N face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R22E 1 S32 4 S 5 T10N 1978</p> <p>from which</p> <p style="padding-left: 40px;">A forked juniper, 16 ins. diam., bears S. 41° W., 25.5 lks. dist., mkd. 1/4 S5 BT.</p> <p style="padding-left: 40px;">A juniper, 14 ins. diam., bears N. 2° W., 73 lks. dist., mkd. 1/4 S32 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="padding-left: 40px;">S. 88°08' W., beginning new measurement.</p>	
2.90	Fence, bears S. 18° E. and N. 18° W.	
4.50	State Highway No. 77, asphalt surfaced, bears S. 18° E. and N. 18° W.	
6.10	Fence, bears S. 18° E. and N. 18° W.	
7.80	Power line, bears S. 18° E. and N. 18° W.	
9.10	Power line, bears S. 18° E. and N. 18° W.	
40.01	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an unmarked basalt stone of record size, 24 x 10 x 7 ins., lying in a scattered mound of stone, with a 2 x 2 in. wooden stake, 12 ft. long, lying on the ground alongside, from which the original bearing trees</p> <p style="padding-left: 40px;">A juniper, 36 ins. diam., bears N. 5 3/4° E., 419 lks. dist., mkd. T11N through a partially overgrown blaze. (Record N. 14° E., 175 lks. dist.)</p> <p style="padding-left: 40px;">A dead juniper, 14 ins. diam., bears N. 21 3/4° W., 303 lks. dist., mkd. T11N R22E S31 BT. (Record N. 50° W., 232 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R22E S31 S32 S 6 S 5 T10N 1978</p>	

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 6 ins. diam., bears N. 42° E., 52.5 lks. dist., mkd. T11N R22E S32 BT.</p> <p>A juniper, 8 ins. diam., bears S. 45° E., 72 lks. dist., mkd. T10N R22E S5 BT.</p> <p>A juniper, 11 ins. diam., bears S. 50° W., 71 lks. dist., mkd. T10N R22E S6 BT.</p> <p>A juniper, 3 ins. diam., bears N. 52° W., 78 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Deposit the unmarked stone alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>
40.20	<p>S. 88°22' W, bet. secs. 6 and 31.</p> <p>Over gently rolling land, through medium timber.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a basalt stone 18 x 12 x 9 ins., loosely set in a scattered mound of stone, mkd. 1/4 on the N face, from which the original bearing tree</p> <p>A pinyon pine, 14 ins. diam., bears N. 3 3/4° W., 256 lks. dist., mkd. 1/4 on the NE face. (Record S. 16° W., 51 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R22E 1 S31 4 S 6 T10N 1978</p>
36.10	<p>from which</p> <p>A juniper, 15 ins. diam., bears N. 24° E., 67 lks. dist., mkd. 1/4 S31 BT.</p> <p>A juniper, 11 ins. diam., bears S. 36° E., 39 lks. dist., mkd. 1/4 S6 BT.</p> <p>Deposit the mkd. stone in the mound alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 87°20' W., beginning new measurement.</p> <p>The cor. of Tps. 10 and 11 N., Rs. 21 and 22 E., monumented with an iron post, 3 ins. diam., projecting 13 ins. above ground, with brass cap mkd. as described in the official record of the 1920 resurvey of the S bdy. of T. 11 N., R. 21 E., from which the original bearing trees</p> <p>A juniper, 25 ins. diam., bears N. 10° E., 58 lks. dist., mkd. T11N R22E S31 BT. (Record bearing N. 8° E.)</p>

Dependent Resurvey of the N Bdy.,
T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A juniper, 13 ins. diam., bears S. 78° E., 38 lks. dist., mkd. T10N R22E S6 BT. (Record bearing S. 81° E.)</p> <p>A juniper, 25 ins. diam., bears S. 70° W., 44 lks. dist., mkd. T10N R21E S1 BT. (Record bearing S. 66° W.)</p> <p>A juniper, 15 ins. diam., bears N. 65° W., 83 lks. dist., mkd. T11N R21E S36 BT. (Record, N. 66° W., 82 lks. dist.)</p>
	<p>Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.</p>
	<p>(Restoring the 1883 survey by O. D. Wheeler)</p>
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.</p> <p>N. 0°27' E., bet. secs. 35 and 36.</p> <p>Over rolling land, through dense timber.</p>
19.79	<p>Point for the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S 1/16 S35 S36 1978</p> <p>from which</p> <p>An alligator juniper, 8 ins. diam., bears S. 66° E., 31.5 lks. dist., mkd. S 1/16 S36 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 50° W., 80.5 lks. dist., mkd. S 1/16 S35 BT.</p>
39.58	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p> <p>The 1/4 sec. cor. of secs. 35 and 36, monumented with a basalt stone, 13 x 11 x 5 ins., loosely set in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on the W face, from which the original bearing trees</p> <p>An alligator juniper, 30 ins. diam., bears S. 45° E., 55 lks. dist., mkd. 1/4 S BT. (Record dist. 51 lks.)</p> <p>An alligator juniper, 19 ins. diam., bears S. 55° W., 18 lks. dist., mkd. 1/4 S BT. (Record, S. 70° W., 23 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p style="text-align: center;">T10N R22E 1/4 S35 S36 1978</p> <p>from which new accessories</p> <p>A volcanic boulder, 5 x 5 x 1 1/2 ft. above ground, bears S. 83 3/4° E., 22 lks. dist., mkd. X B0 on top.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 18 1/4° W., 47 lks. dist., mkd. 1/4 S35 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°47' E., beginning new measurement.</p>
19.79	<p>Point for the N 1/16 sec. cor. of secs. 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E N 1/16 S35 S36 1978</p> <p>from which</p> <p>A ponderosa pine, 13 ins. diam., bears S. 53° E., 76 lks. dist., mkd. N 1/16 S36 BT.</p> <p>An alligator juniper, 12 ins. diam., bears S. 37° W., 17.5 lks. dist., mkd. N 1/16 S35 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p>
39.58	<p>The cor. of secs. 25, 26, 35 and 36, monumented with a wooden stake, 12 ins. long, 2 ins. squared, projecting 6 ins. above a scattered mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best remaining evidence of the original cor. position.</p> <p>from which an unrecorded bearing tree</p> <p>An alligator juniper, 17 ins. diam., bears N. 57° W., 73 lks. dist., mkd. T10N R22E S26 on the SE face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T10N R22E S26 S25 S35 S36 1978</p> <p>from which new bearing trees</p> <p>An alligator juniper, 9 ins. diam., bears N. 51° E., 145 lks. dist., mkd. T10N R22E S25 BT.</p> <p>An alligator juniper, 9 ins. diam., bears S. 10° E., 29 lks. dist., mkd. T10N R22E S36 BT.</p> <p>An alligator juniper, 9 ins. diam., bears S. 50° W., 97 lks. dist., mkd. T10N R22E S35 BT.</p> <p>An alligator juniper, 7 ins. diam., bears N. 6° W., 94.5 lks. dist., mkd. T10N R22E S26 BT.</p> <p>Deposit the wooden stake alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is 13 lks. E of a track road which bears N. 20° E. and S. 20° W., and 42.5 lks. S of an E-W fence.</p>	
	<p>N. 0°03' W. bet. secs. 25 and 26.</p> <p>Over gently rolling land, through medium to scattering timber.</p>	
20.10	<p>Point for the S 1/16 sec. cor. of secs. 25 and 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S 1/16 S26 S25 1978</p> <p>from which</p> <p>An alligator juniper, 12 ins. diam., bears N. 39° E., 115 lks. dist., mkd. S 1/16 S25 BT.</p> <p>An alligator juniper, 5 ins. diam., bears S. 34° W., 162 lks. dist., mkd. S 1/16 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is 30 lks. W of a track road, bears irregularly N and S.</p>	
40.20	<p>The 1/4 sec. cor. of secs. 25 and 26, monumented with a juniper post, 24 ins. long, 5 ins. diam., set 12 ins. in the ground and in a scattered mound of stone. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T10N R22E
1/4
S26|S25
1978

from which

An alligator juniper, 6 ins. diam., bears
S. 67° E., 58.5 lks. dist., mkd. 1/4 S25 BT.

An alligator juniper, 4 ins. diam., bears
S. 1/2° E., 62 lks. dist., mkd. X at breast
height and BT at the base.

Reset the juniper post alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of
the cor.

Cor. is 15 lks. E of a track road and 47 lks. E of an
abandoned fence, both bear N and S.

N. 0°25' W., beginning new measurement.

40.07

The cor. of secs. 23, 24, 25 and 26, monumented with a
scattered mound of stone at a fence cor. This position is
harmoniously related to existing original cors. and is
accepted as the best available evidence of the original
cor. position.

from which the remains of an unrecorded bearing tree

An alligator juniper, 36 ins. diam., bears
S. 26° W., 36.5 lks. dist., mkd. BT.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins.
in the ground, with brass cap mkd.

T10N R22E
S23|S24
S26|S25
1978

from which new bearing trees

An alligator juniper, 7 ins. diam., bears
N. 74° E., 145.5 lks. dist., mkd.
T10N R22E S24 BT.

An alligator juniper, 14 ins. diam., bears
S. 11° E., 173 lks. dist., mkd. T10N R22E S25 BT.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of
the cor.

Cor. is located at a fence cor. from which fences extend
N, E and W.

Cor. is also 47 lks. N of a track road, bears E and W,
curving southerly.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>N. 1°29' W., bet. secs. 23 and 24.</p> <p>Over gently rolling land, through scattering timber.</p> <p>Along a N-S fence.</p> <p>40.15 The 1/4 sec. cor. of secs. 23 and 24, monumented with a volcanic stone, 13 x 6 x 4 ins., lying on a scattered mound of stone, mkd. 1/4 on one face, from which an unrecorded bearing tree</p> <p style="padding-left: 40px;">An alligator juniper, 24 ins. diam., bears S. 81° E., 39 lks. dist., mkd. 1/4 S.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1/4 S23 S24 1978</p> <p>from which</p> <p style="padding-left: 40px;">U.S.C. & G.S. triangulation station "WEST 1936," bears N. 4°20' E., 29.60 chs. dist., a brass tablet, 3 1/2 ins. diam., cemented in a boulder, 2 x 1 1/2 x 1 ft. above ground.</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 26° E., 139 lks. dist., mkd. 1/4 S24 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is in a N-S fence.</p> <p style="text-align: center;">_____</p> <p>N. 0°13' E., beginning new measurement.</p> <p>Over rolling land.</p>	
28.00	Spur, slopes southwesterly.	
40.76	<p>The cor. of secs. 13, 14, 23 and 24, monumented with a re-bar, 18 ins. long, 1/2 in., diam., set flush with the ground in a cindered road, immediately N of a cinder pit. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 33 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S14 S13 S23 S24 1978</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>from which</p> <p>An alligator juniper, 12 ins. diam., bears N. 62° E., 406.5 lks. dist., mkd. T10N R22E S13 BT.</p> <p>A power pole, bears N. 79° W., 320 lks. dist.</p> <p>Deposit broken brown glass at the base of the iron post.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Set a railroad spike directly over the iron post, flush with the cindered road which bears S. 75° E. and N. 75° W.</p> <p>Cor. is 59 lks. S of a power line, bears E and W.</p> <p>From this point the 1/4 sec. cor. of secs. 13 and 24, bears N. 88°49' E., 39.13 chs. dist., monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 2 1/2 ft. base, 10 ins. high, to top, with brass cap mkd. as described in the official record of the 1969 remonumentation notes, from which</p> <p>A ponderosa pine, 24 ins. diam., mkd. in 1883, bears N. 12° E., 116 lks. dist., mkd. with a healed blaze.</p> <p>A ponderosa pine stump, 35 ins. diam., mkd. in 1883, bears S. 73° E., 110 lks. dist., mkd. 1/4 S.</p> <p>A ponderosa pine, 11 ins. diam., mkd. in 1969, bears S. 34° E., 83 lks. dist., mkd. 1/4 S24 BT.</p> <p>A ponderosa pine, 10 ins. diam., mkd. in 1969, bears N. 50° W., 130 lks. dist., mkd. 1/4 S13 BT.</p> <p>A mound of stone, 3 ft. base, 2 1/2 ft. high, is N of the cor.</p> <p>Cor. is 5 lks. S of a power line, bears E and W.</p>
	<p>N. 0°05' W., bet. secs. 13 and 14.</p>
	<p>Over rolling land, through scattering to dense timber.</p>
29.80	<p>Telephone line, bears E and W.</p>
32.90	<p>State Highway No. 60, asphalt surfaced, bears E and W.</p>
40.45	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an open end metal pipe, 30 ins. long, 1 1/2 ins. diam., projecting 2 ins. above ground; a re-bar, 15 ins. long, 1/2 in. diam., is set alongside with an aluminum cap mkd. 5047. This position is shown by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, on a survey plat a record of which is on file at Matkin Engineering in Show Low, Arizona. This position is harmoniously to existing original cors., and is accepted as the best available evidence of the original cor. position.</p>
	<p>At the cor. point</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T10N R22E
1/4
S14|S13
1978

from which

A forked juniper, 14 ins. diam., bears S. 24° E.,
36 lks. dist., mkd. 1/4 S13 BT.

An alligator juniper, 10 ins. diam., bears
S. 22° W., 63 lks. dist., mkd. 1/4 S14 BT.

Reset both local cors. alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.

Cor. is 90 lks. E of a graded road, bears N and S.

N. 0°05' W., beginning new measurement.

Over nearly level land, through medium timber.

40.38

The cor. of secs. 11, 12, 13 and 14, monumented with an open end metal pipe, 36 ins. long, 1 in. diam., projecting 8 ins. above ground; with a metal tag attached mkd. 5047. This position is shown by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, on a survey plat a record of which is on file at Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T10N R22E
S11|S12
S14|S13
1978

from which

A juniper, 3 ins. diam., bears N. 31° E.,
178.5 lks. dist., mkd. X BT at the base.

An alligator juniper, 4 ins. diam., bears
S. 9° E., 215.5 lks. dist., mkd. X at breast
height and BT at the base.

An alligator juniper, 4 ins. diam., bears
S. 55° W., 138.5 lks. dist., mkd. X at breast
height and BT at the base.

A juniper, 17 ins. diam., bears N. 46° W.,
252.5 lks. dist., mkd. T10N R22E S11 BT.

Reset the open end pipe alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is 85 lks. E of a track road, bears N and S.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.</p> <p>N. 0°44' W., bet. secs. 34 and 35.</p> <p>Over rolling land, through medium to dense timber.</p> <p>39.54 The 1/4 sec. cor. of secs. 34 and 35, monumented with a basalt stone, 26 x 20 x 6 ins., lying on top of a scattered mound of stone, mkd. 1/4 on one face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1/4 S34 S35 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 78° E., 69.5 lks. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N. 83° W., 31.5 lks. dist., mkd. 1/4 S34 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is 1 lk. E of a N-S fence.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°11' W., beginning new measurement.</p> <p>Along a N-S fence.</p>	
16.80	<p>Stock pond, 4 chs. diam., bears West, 2.50 chs. dist.</p>	
40.11	<p>The cor. of secs. 26, 27, 34 and 35, at the intersection of fences extending N, S and W. This position is harmoniously related to existing original cors., has been used for many years as the property bdy. and is accepted as the best available evidence of the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S27 S26 S34 S35 1978</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

	CHAINS		
		<p>Because of the fence cor. being W, raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, E of the cor.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>West, bet. secs. 26 and 35.</p> <p>Over gently rolling land, through dense timber.</p>	
	10.075	<p>Point for the E-E 1/64 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S26 E-E 1/64 S35 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 17° E., 35.5 lks. dist., mkd. E-E 1/64 S26 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 30° E., 18 lks. dist., mkd. E-E 1/64 S35 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N. 11° W., 26.5 lks. dist.; fences extend E, S and W.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.</p>	
	20.15	<p>Point for the E 1/16 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E E 1/16 <u>S26</u> S35 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N. 38° E., 62 lks. dist., mkd. E 1/16 S26 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 9 ins. diam., bears N. 46° W., 67 lks. dist., mkd. E 1/16 S26 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.</p> <p>Cor. is 18.5 lks. S of an E-W fence.</p>	
	30.225	<p>Point for the W-E 1/64 sec. cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S26 W-E 1/64 S35 1978</p> <p>from which</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>An alligator juniper, 8 ins. diam., bears S. 68° W., 40.5 lks. dist., mkd. W-E 1/64 S35 BT.</p>
	<p>An alligator juniper, 4 ins. diam., bears N. 38° W., 36.5 lks. dist., mkd. X at breast height and BT at the base.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.</p>
	<p>Cor. is 8 lks. S of an E-W fence.</p>
40.30	<p>The 1/4 sec. cor. of secs. 26 and 35, monumented with a basalt stone, 21 x 12 x 10 ins., lying in a scattered mound of stone, mkd. 1/4 on one face.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T10N R22E 1 S26 4 S35 1978</p>
	<p>from which</p>
	<p>An pinyon pine, 8 ins. diam., bears N. 12° E., 59 lks. dist., mkd. 1/4 S26 BT.</p>
	<p>An alligator juniper, 7 ins. diam., bears S. 39° E., 50 lks. dist., mkd. 1/4 S35 BT.</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base 2 1/2 ft. high, N of the cor.</p>
	<p>Cor. is at a fence cor.; fences extend E and S.</p>
	<p style="text-align: center;">—————</p> <p>N. 89°31' W., beginning new measurement.</p>
7.00	<p>Enter railed area.</p>
40.83	<p>The cor. of secs. 26, 27, 34 and 35.</p>
	<p>N. 0°50' E., bet. secs. 26 and 27.</p>
	<p>Over nearly level land, through a railed area, along a N-S fence.</p>
39.27	<p>The 1/4 sec. cor. of secs. 26 and 27, monumented with an iron post, 2 1/2 ins., diam., projecting 14 ins. above a scattered mound of stone, with brass cap mkd. as described in the official record of the 1969 remonu- mentation notes.</p>
	<p>Rebuild the mound of stone, 3 ft. base, 14 ins. high, around the iron post and add 1978 to the brass cap, from which a new bearing tree</p>
	<p>An alligator juniper, 3 ins. diam., bears S. 5° E., 54.5 lks. dist., mkd. X at breast height and BT at the base.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>Cor. is in a N-S fence.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p> <p>40.48 The cor. of secs. 22, 23, 26 and 27, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 2 1/2 ft. base, 20 ins. high, to top, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes, from which the original bearing trees</p> <p style="padding-left: 40px;">A pinyon pine, 20 ins. diam., bears N. 85° E., 76 lks. dist., mkd. with a healed blaze. (Record N. 81° E., 81 lks. dist.)</p> <p style="padding-left: 40px;">An alligator juniper, 38 ins. diam., bears S. 18° W., 151 lks. dist., with scribe marks visible through a partially healed blaze. (Record S. 16° W., 140 lks. dist.)</p> <p style="padding-left: 40px;">An alligator juniper, 48 ins. diam., bears N. 29° W., 130 lks. dist., mkd. with a healed blaze. (Record N. 24° W., 137 lks. dist.)</p> <p>Add the date 1978 to the brass cap from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 75° E., 26 lks. dist., mkd. T10N R22E S26 BT.</p>	
	<p>From the cor. of secs. 23, 24, 25 and 26.</p> <p>S. 89°55' W., bet. secs. 23 and 26.</p> <p>Over gently rolling land, through scattering timber, along an E-W fence.</p> <p>20.12 Point for the E 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E E 1/16 $\frac{S23}{S26}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 4 ins. diam., bears S. 10° W., 65.5 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.</p> <p>Cor. is 1 lk. S of an E-W fence.</p> <p>40.24 The 1/4 sec. cor. of secs. 23 and 26, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 2 ft. base, 14 ins. high, to top, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes.</p> <p>A mound of stone, 2 1/2 ft. base, 1 ft. high, is N of the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
39.94	<p>Cor. is in an E-W fence.</p> <hr/> <p>S. 89°51' W., beginning new measurement.</p> <p>The cor. of secs. 22, 23, 26 and 27.</p>
39.10	<p>From the cor. of secs. 13, 14, 23 and 24, heretofore described.</p> <p>S. 89°15' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through medium to scattering timber.</p> <p>The 1/4 sec. cor. of secs. 14 and 23, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 2 ft. base, 1 ft. high, to top, with brass cap mkd. as described in the official record of the 1969 remonumentation notes, from which the remains of an original bearing tree.</p> <p style="padding-left: 40px;">A juniper stump, 36 ins. diam., bears N. 85° W., 226 lks. dist., mkd. BT.</p> <p>A mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, is N of the cor.</p> <p>Cor. is 5 lks. N of an E-W fence and 80 lks. S of a power line and track road, both bear E and W.</p>
40.35	<p>S. 89°55' W., beginning new measurement.</p> <p>The cor. of secs. 14, 15, 22 and 23, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 2 1/2 ft. base, 15 ins. high, to top, with brass cap mkd. as described in the official record of the 1969 remonumentation notes. A mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, is W of the cor.</p> <p>Add 1978 to the brass cap from which a new bearing tree</p> <p style="padding-left: 40px;">An alligator juniper, 6 ins. diam., bears N. 76° E., 150.5 lks. dist., mkd. T10N R22E S14 BT.</p> <p>Cor. is 63 lks. S of a power line and track road, both bear E and W. and 28.5 lks. W of a fence cor.; fences extend E and NW.</p>
25.50	<p>N. 0°02' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through medium timber.</p> <p>State Highway No. 60, asphalt surfaced, bears N. 85° E. and S. 85° W.</p>
40.27	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with basalt stone, 13 x 10 x 5 ins., diam., loosely set in a scattered mound of stone, mkd. 1/4 on one face. An axle, 30 ins. long, 1 1/4 ins. diam., set flush with the ground was found at the center of the mound.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T10N R22E 1/4 S15 S14 1978</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 49° E., 201 lks. dist., mkd. 1/4 S14 BT.</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 56° W., 117 lks. dist., mkd. 1/4 S15 BT.</p> <p>Deposit the mkd. stone and reset the axle alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is 10 lks. E of a telephone line, bears N and S.</p> <p style="text-align: center;">—————</p> <p>N. 1°13' W., beginning new measurement.</p>	
15.293	<p>Point for the N-S-N 1/256 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">N-S-N 1/256 S15 S14 1978</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 55° E, 54 lks. dist., mkd. N-S-N 1/256 S14 BT.</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 12° W., 128 lks. dist., mkd. N-S-N 1/256 S15 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is under telephone line, bears N and S.</p>	
17.70	<p>Enter a dry lake bed, the edge bears E and W.</p>	
20.39	<p>Point for the N 1/16 sec. cor. of secs. 14 and 15.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E N 1/16 S15 S14 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. 32° E., 370.5 lks. dist., mkd. N 1/16 S14 BT.</p> <p style="padding-left: 40px;">A basalt boulder, 10 x 10 x 4 ft. above ground, bears S. 31° W., 256.5 lks. dist., mkd. X B0 on the NE face.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
40.78	<p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>From this point a spring, 15 ft. diam., 6 ins. deep, bears S. 39° W., 385 lks. dist.</p> <p>Cor. is 10 lks. W of underground telephone cable which bears N and S.</p> <p>The cor. of secs. 10, 11, 14 and 15, monumented with a basalt stone, 16 x 12 x 6 ins., loosely set in a scattered mound of stone, mkd. with 2 notches on the E and 4 notches on the S edges.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E $\frac{S10}{S15} \frac{S11}{S14}$ 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>
40.10	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°44' W., bet. secs. 11 and 14.</p> <p>Over gently rolling land, through scattering timber.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E $\frac{1}{4} \frac{S11}{S14}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 5 x 3 x 1 1/2 ft. above ground, bears N. 44° E., 73.5 lks. dist., mkd. X B0 on top.</p> <p style="padding-left: 40px;">A boulder, 3 x 2 x 1/2 ft. above ground, bears S. 40° W., 86.5 lks. dist., mkd. X B0 on top.</p>
47.60	<p>Enter a dry lake bed, the edge at a curve, bears SW and NW.</p>
80.19	<p>The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>From the cor. of secs. 3, 4, 33 and 34, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>N. 0°08' W., bet. secs. 33 and 34.</p> <p>Over rolling land, through medium timber.</p> <p>19.665 Point for the S 1/16 sec. cor. of secs. 33 and 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S 1/16 S33 S34 1978</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 5 ins. diam., bears S. 52° E., 59 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 14° E., 140 lks. dist., mkd. S 1/16 S34 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p>	
36.10	Show Low Creek, 30 lks. wide, course NW.	
39.33	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., over a 20d nail, driven in a crack in bedrock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1/4 S33 S34 1978</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 3 1/2 x 3 x 2 ft. above ground, bears N. 39° E., 10 lks. dist., mkd. X BO on top.</p> <p style="padding-left: 40px;">A boulder, 7 x 4 x 2 ft. above ground, bears S. 38° E., 52 lks. dist., mkd. X BO on top.</p> <p>Cor. is on a small rocky plateau overlooking Show Low Creek.</p>	
78.66	<p>The cor. of secs. 27, 28, 33 and 34, monumented with a basalt stone, 19 x 15 x 12 ins., firmly set 10 ins. in the ground, mkd. with 3 grooves on the E and 1 groove on the S faces, surrounded with a scattered mound of stone.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S28 S27 S33 S34 1978</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.
	From this point a fence cor., bears S. 86 1/2° E., 26 lks. dist., from which fences extend N, E, S and W.
	From the cor. of secs. 26, 27, 34 and 35.
	S. 88°57' W., bet. secs. 27 and 34.
	Over gently rolling land, through scattering timber, along an E-W fence.
39.97	The 1/4 sec. cor. of secs. 27 and 34, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 3 ft. base, 16 ins. high, to top, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes, with a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.
	Add 1978 to the brass cap from which a new bearing tree
	An alligator juniper, 8 ins. diam., bears S. 66° E., 142 lks. dist., mkd. 1/4 S34 BT.
	Cor. is 12 lks. S of an E-W fence.
	S. 89°09' W., beginning new measurement.
31.10	Power line, bears S. 15° E. and N. 15° W.
31.70	Power line, bears S. 15° E. and N. 15° W.
31.80	Track road, bears S. 15° E. and N. 15° W.
39.99	The cor. of secs. 27, 28, 33 and 34.
	From the cor. of secs. 14, 15, 22 and 23, heretofore described.
	N. 89°59' W., bet. secs. 15 and 22.
	Over rolling land, through medium to dense timber.
40.26	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 2 1/2 ft. base, 10 ins. high, to top, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes.
	from which
	A re-bar, 5/8 in. diam., projecting 3 ins. above ground, bears S. 49° W., 8.2 lks. dist.
	A mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, is N of the cor.
	Cor. is 21 lks. S of an E-W fence, and 36 lks. S of a power line and track road bearing E and W.
	S. 89°48' W. beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
40.35	<p>The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2 1/2 ins., diam., set in a mound of stone, 3 ft. base, 1 ft. high, to top, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes, with a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor., from which the remains of the original bearing trees</p> <p>A stumphole, bears S. 32° E., 158 lks. dist.</p> <p>An alligator juniper, 36 ins. diam., bears N. 88° W., 132 lks. dist., no marks are visible.</p> <p>Add 1978 to the brass cap from which a new bearing tree</p> <p>A juniper, 9 ins. diam., bears N. 38° W., 123 lks. dist., mkd. T10N R22E S16 BT.</p> <p>Cor. is 65 lks. E of a fence cor., from which fences extend S, W and NE, curving E.</p>	
	<p>N. 0°26' W., bet. secs. 15 and 16.</p>	
	<p>Over rolling land, through dense timber.</p>	
8.50	<p>Telephone line, bears N. 80° E. and S. 80° W.</p>	
10.50	<p>Fence, bears N. 80° E. and S. 80° W.</p>	
12.00	<p>State Highway No. 60, asphalt surfaced, bears N. 80° E. and S. 80° W.</p>	
13.60	<p>Fence, bears N. 80° E. and S. 80° W.; enter nearly level open land.</p>	
15.10	<p>Telephone line, bears N. 80° E. and S. 80° W.</p>	
38.50	<p>Gravel road, bears N. 80° E. and S. 80° W.</p>	
40.37	<p>Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1/4 S16 S15 1978</p>	
	<p>from which</p>	
	<p>A juniper, 7 ins. diam., bears S. 1° W., 88.5 lks. dist., mkd. 1/4 S16 BT.</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p>	
50.40	<p>Show Low airport runway, asphalt surfaced, bears N. 80° E. and S. 80° W.</p>	
58.20	<p>Fence, bears N. 80° E. and S. 80° W.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS

80.74

The cor. of secs. 9, 10, 15 and 16, monumented with a re-bar, 18 ins., long, 1/2 in. diam., projecting 2 ins. above, ground, with an aluminum cap mkd. 5047. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T10N R22E
S 9 | S10
S16 | S15
1978

from which

An alligator juniper, 5 ins. diam., bears N. 25° E., 315.5 lks. dist., mkd. T10N R22E S10 BT.

A juniper, 8 ins. diam., bears S. 71° E., 174 lks. dist., mkd. T10N R22E S15 BT.

A juniper, 9 ins. diam., bears S. 9° W., 260.5 lks. dist., mkd. T10N R22E S16 BT.

A fence cor., bears N. 37° W., 68.5 lks. dist.; fences extend N and W.

Buried a horseshoe at the base of the iron post, and reset the re-bar alongside.

Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.

Cor. is in an E-W fence.

From the cor. of secs. 10, 11, 14 and 15.

S. 89°42' W., bet. secs. 10 and 15.

Over dry lake bed.

20.075

Point for the E 1/16 sec. cor. of secs. 10 and 15.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T10N R22E
E 1/16 | S10
S15
1978

from which

A boulder, 3 x 3 x 1 ft. above ground, bears S. 53° W., 186 lks. dist., mkd. X B0 on top.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

	CHAINS	
		<p>A boulder, 8 x 6 x 2 ft. above ground, bears N. 66° W., 165 lks. dist., mkd. X B0 on top.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.</p>
	21.40	Enter rolling land with a cover of scattering timber.
	25.094	Point for the E-W-E 1/256 sec. cor. of secs. 10 and 15.
		<p>Set an iron post, 28 ins. long, 8 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S10 E-W-E 1/256 S15 1978</p> <p>from which</p> <p>A juniper, 5 ins. diam., bears S. 47° W., 106 lks. dist., mkd. E-W-E 1/256 S15 BT.</p> <p>A juniper, 7 ins. diam., bears N. 30° W., 36.5 lks. dist., mkd. E-W-E 1/256 S10 BT.</p>
	40.15	Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1 S10 4 S15 1978</p> <p>from which</p> <p>A juniper, 8 ins. diam., bears N. 11° E., 36.5 lks. dist., mkd. 1/4 S10 BT.</p> <p>A pine, 12 ins. diam., bears S. 65° E., 53 lks. dist., mkd. 1/4 S15 BT.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 3 ft. high, N of the cor.</p> <p>Cor. is 87 lks. S of an abandoned E-W fence.</p>
	49.90	Fence, bears S. 65° E. and N. 65° W.
	80.30	The cor. of secs. 9, 10, 15 and 16.
		<p>From the cor. of secs. 15, 16, 21 and 22, heretofore de- scribed.</p> <p>S. 89°47' W., bet. secs. 16 and 21.</p> <p>Over rolling land, through medium timber.</p>
	38.60	Power line, bears N and S.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
39.00	Graded gravel road, bears N and S.
39.20	Power line, bears N and S.
40.19	<p>The 1/4 sec cor. of secs. 16 and 21, monumented with a re-bar, 5/8 in. diam., 16 ins. long, set flush with the ground, with an aluminum cap mkd. 5047. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position.</p>
	At the cor. point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	<p>T10N R22E $\frac{1}{4} \frac{S16}{S21}$ 1978</p>
	Reset the re-bar alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.
	Cor. is 268 lks. S of a telephone line and 384 lks. S of State Highway No. 60, asphalt surfaced, both bear N. 72° E. and S. 72° W.
	From the cor. the NE cor. of Williams Energy office building, 46.5 x 24.5 ft., bears S. 19° W., 73.3 lks. dist., long side bears E and W.
	<hr style="width: 20%; margin: auto;"/> <p>S. 89°46' W., beginning new measurement.</p>
	Over nearly level open land.
2.70	Telephone line, bears NW and SE to Williams Energy office building.
9.70	Power line, bears N. 75° E. and S. 75° W.
11.90	State Highway No. 60, asphalt surfaced, bears N. 75° E. and S. 75° W.
14.20	Approach to State Highway No. 77, asphalt surfaced, bears N. 55° E. and S. 55° W.
17.30	Fence, bears N. 55° E. and S. 55° W.
40.18	The cor. of secs. 16, 17, 20 and 21, monumented with an iron post, 2 ins. diam., set flush with the ground, with brass cap mkd.
	<p>Lacy T10N R22E $\frac{17}{20} \frac{16}{21}$ ENGR.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>This position is harmoniously related to existing original cors., has been accepted and used by private surveyors in the area and is accepted as the best available evidence of the original cor. position; not remonumented.</p> <p>Cor. is 2 lks. E of a power line which bears N and S.</p> <p>From this point a fence cor., bears East, 50 lks. dist., from which fences extend E and S.</p> <p>From this same point a re-bar, 3/4 in. diam., projecting 6 ins. above ground, bears N. 89°23' W., 47.6 lks. dist. This re-bar is set at a fence cor., from which fences extend N and W.</p>	
	<p>N. 0°16' W., bet. secs. 16 and 17.</p> <p>Over nearly level open land.</p>	
0.28	Power line, bears E and W.	
40.30	<p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a basalt stone, 19 x 10 x 8 ins., firmly set 10 ins. in the ground, mkd. 1/4 on the W face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1/4 S17 S16 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is 47.5 lks. E of a N-S fence.</p>	
40.32	<p>N. 0°16' W., beginning new measurement.</p> <p>The cor. of secs. 8, 9, 16 and 17, monumented with a re-bar, 18 ins. long, 5/8 in. diam., projecting 4 ins. above ground. This monument is described as being the cor. on a survey plat by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file at Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S 8 S 9 S17 S16 1978</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears West, 45 lks. dist.; fences extend S, W and irregularly E.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 4 ft. base, 3 1/2 ft. high, W of the cor.</p> <p>Cor. is 11.5 lks. S of a fence, bears irregularly E and W.</p>
<p>40.04</p> <p>30.90</p> <p>32.50</p> <p>34.10</p> <p>36.45</p> <p>36.95</p> <p>37.55</p>	<hr/> <p>From the cor. of secs. 9, 10 and 15 and 16.</p> <p>S. 89°41' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through scattering timber, along an E-W fence.</p> <p>The 1/4 sec. cor. of secs. 9 and 16, monumented with a basalt stone, 16 x 12 x 3 ins. lying in a scattered mound of stone, mkd. 1/4 on one face. A rebar, 3/4 in. diam., projecting 3 ins. above ground is also set at the center of the mound.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E $\frac{1}{4}$ S 9 $\frac{1}{4}$ S16 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 61° E., 309.5 lks. dist., mkd. 1/4 S9 BT.</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 8° W., 236 lks. dist., mkd. 1/4 S16 BT.</p> <p>Deposit the mkd. stone and reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.</p> <p>Cor. is 20.5 lks. S of an E-W fence.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°41' W., beginning new measurement.</p> <p>Fence, bears S. 17° E. and N. 17° W.</p> <p>State Highway No. 77, asphalt surfaced, bears S. 17° E. and N. 17° W.</p> <p>Fence, bears S. 17° E. and N. 17° W.</p> <p>Power line, bears S. 17° E. and N. 17° W.</p> <p>Buried gas line, bears S. 17° E. and N. 17° W.</p> <p>Power line, bears S. 17° E. and N. 17° W.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS		
40.10	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 1/2 ins. diam., set 24 ins. below the surface of a graded gravel road, with brass cap mkd. as described in the official record of the 1969 re-monumentation notes, from which the original bearing trees</p> <p>A ponderosa pine, 21 ins. diam., bears N. 18° E., 86 lks. dist., with scribe marks visible.</p> <p>A ponderosa pine, 28 ins. diam., bears S. 54° E., 88 lks. dist., mkd. with a healed blaze.</p> <p>A ponderosa pine, 20 ins. diam., bears N. 54° W., 124 lks. dist., mkd. T10N R22E S19</p> <p>Cor. is 25 lks. N of a fence, bears W and South, 18 lks. dist., thence bearing S and E.</p> <p>S. 88°58' W. bet. secs. 19 and 30.</p> <p>Along the center of a road.</p>	
38.58	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 2 1/2 ins., diam., set 8 ins. below the surface of a blacktop road, with brass cap mkd. as described in the official record of the 1969 remonumentation notes.</p> <p>from which</p> <p>The SW cor. of a church building, bears N. 38°37' E., 105.5 lks. dist.</p> <p>A power pole, bears N. 46°35' E., 52.5 lks. dist.</p> <p>A power pole, bears N. 47°36' W., 51 lks. dist.</p> <p>Cor. is located in the center of W. Whipple St. which bears E and W, and in line with the center of S. 17th Ave., projecting N.</p> <hr/> <p>S. 89°19' W., beginning new measurement.</p>	
20.01	<p>Point for the W 1/16 sec. cor. of secs. 19 and 30, is in the center of a paved road, bears E and W.</p> <p>Set a railroad spike flush with the pavement, with top mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S19}{S30}$ 1978</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N. 22° E., 127.5 lks. dist., mkd. W 1/16 S19 BT.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45° W., 81.8 lks. dist., with brass cap mkd. T10N R22E W 1/16 S19 RM 54 FT. 1978 and an arrow pointing to the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
30.004	Center of State Highway No. 60, asphalt surfaced, bears northeasterly and southwesterly.
38.10	The cor. of secs. 19, 24, 25 and 30, on the W bdy. of the Tp.
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°06' E., bet. secs. 19 and 20.</p> <p>Over gently rolling land, along a dirt road.</p>
40.45	Power line, bears E and W.
40.80	Asphalt road, bears E and W.
41.11	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with an open end pipe, 1 3/8 ins. diam., set flush with the ground, in a concrete base, with a tag attached, mkd. 4083. This monument was shown to me by George O. Matkin, Registered Civil Engineer No. 5047, in Arizona as having been used by private surveyors in the area as the cor., and is accepted as the best available evidence of the original cor. position; not remonumented.</p> <hr/> <p>N. 0°16' E., beginning new measurement.</p>
4.10	State Highway No. 60, asphalt surfaced, bears N. 60° E. and S. 60° W., thence along a blacktop road.
38.35	Road intersection; roads bear N, S. 55° E., S and N. 55° W.
39.30	Dim dirt road, bears E and W.
40.19	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a re-bar 5/8 in. diam., buried 4 ins. under ground, with an aluminum cap mkd. 5047. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position; not remonumented.</p> <p>Cor. is at the E edge of an asphalt surfaced road, bears N and S.</p> <hr/> <p>S. 87°59' W. N. 89°42' W., bet. secs. 18 and 19.</p> <p>Over nearly level land.</p>
40.19	<p>Point for the 1/4 sec. cor. of secs. 18 and 19, determined from the NE cor. of Lot No. 36 of the Navajo Pines Estates subdivision, as shown on the survey plat of Aztec Estates, prepared by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file with Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors. and is accepted as the best available evidence of the original cor. position; not monumented.</p> <p>From this point the NE cor. of Lot No. 36, Navajo Pines Estates, bears S. 40°04' W., 67.4 lks. ^{5.42° 14' W., 67.6 lks.} dist., monumented with a re-bar, 5/8 in. diam., projecting 3 ins. above ground.</p>

Corrections made pursuant to Authority of Memorandum dated July 8, 1981, File 9622.1 (D-401)

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
36.41 36.46	<p>Cor. point is in an asphalt surfaced ^{the center of a gravel} road, bears N ^N and #. ^{#.}</p> <p>S. 88°42' W. _____</p> <p>S. 86°09' W., beginning new measurement.</p>
26.80	<p>The cor. of secs. 13, 18, 19 and 24, on the W bdy. of the Tp.</p>
39.72	<p>From the cor. of secs. 8, 9, 16 and 17, heretofore described.</p> <p>S. 89°59' W., bet. secs. 8 and 17.</p> <p>Over rolling land, through scattering timber.</p>
26.80	<p>Show Low Creek, course NE, curving NW. (Scaled)</p>
39.72	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a re-bar, 18 ins. long, 5/8 in. diam., projecting 4 ins. above ground. This monument is described as being the cor. on a survey plat of by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a record of which is on file at Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E 1 S 8 4 S17 1978</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 8 x 4 x 2 ft. above ground, bears N. 56° E., 76 lks. dist., mkd. X B0 on top.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 27° W., 14.5 lks. dist., mkd. 1/4 S8 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Cor. is 38 lks. W of a N-S fence.</p> <p style="text-align: center;">_____</p> <p>S. 89°59' W., beginning new measurement.</p>
0.43	<p>Fence cor.; fences extend S and W.</p>
39.72	<p>The cor. of secs. 7, 8, 17 and 18, monumented with an iron pipe, 12 ins. long, 2 ins. diam., projecting 3 ins. above a concrete base, located at a fence cor. from which fences extend N and E. This monument is described as being the cor. on a survey plat by George O. Matkin, Registered Civil Engineer No. 5047, Arizona, a copy of which is on file at Matkin Engineering in Show Low, Arizona. This position is harmoniously related to existing original cors., and is accepted as the best available of the original cor. position.</p> <p>At the cor. point</p>

Corrections made pursuant to Authority of Memorandum dated July 8, 1981, File 9622.1(0-40)

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S 7 S 8 S18 S17 1978</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N. 18° E., 130 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 78° E., 129 lks. dist., mkd. T10N R22E S8 BT.</p> <p>Reset the 2 in. pipe alongside the iron post.</p> <p>Cor. is located in the center of a road projecting S.</p>
	<hr/>
	<p>N. 0°02' E., bet. secs. 7 and 8.</p>
	<p>Over rolling land, through scattering timber.</p>
	<p>Along a N-S fence.</p>
<p>20.70</p>	<p>Show Low Creek, 50 lks. wide, course W.</p>
<p>39.40</p>	<p>Track road, bears E and W.</p>
<p>39.91</p>	<p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T10N R22E $\frac{1}{4}$ S 7 S 8 1978</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N. 64° E., 125.5 lks. dist., mkd. X at breast height and BT at the base.</p>
	<p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 31° E., 88.5 lks. dist., mkd. 1/4 S8 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p>
	<p>Cor. is 4 lks. W of a N-S fence.</p>
<p>79.82</p>	<p>The cor. of secs. 5, 6, 7 and 8, monumented with a basalt stone, 14 x 10 x 6 ins., firmly set 8 ins. in the ground, mkd. with 5 notches on the SE edge, surrounded by a scattered mound of stone.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T10N R22E
S 6 | S 5
S 7 | S 8
1978

from which

A pinyon pine, 8 ins. diam., bears N. 36° E.,
123 lks. dist., mkd. T10N R22E S5 BT.

A juniper, 5 ins. diam., bears S. 11° E.,
125.5 lks. dist., mkd. T10N R22E S8 BT.

A juniper, 5 ins. diam., bears N. 72° W.,
194 lks. dist., mkd. T10N R22E S6 BT.

Deposit the mkd. stone alongside the iron post.

Cor. is at a fence cor., from which fences extend
N. 78° E., S and W, with an abandoned fence extending E.

Cor. is 100 lks. S of a power line, bears S. 65° E. and
N. 65° W.

From this cor., the cor. of secs. 5, 6, 31 and 32, on the
N bdy. of the Tp., bears N. 0°45' W., 80.48 chs. dist.,
heretofore described. The 1/4 sec. cor. of secs. 5 and 6
falls in Telephone Lake and could not be found, not mon-
umented.

S. 89°34' W., bet. secs. 6 and 7.

Over rolling land, through medium timber.

39.29

The 1/4 sec. cor. of secs. 6 and 7, monumented with an
unmarked basalt stone of record size, 20 x 10 x 9 ins.,
loosely set in an old mound of stone, 2 ft. base, 6 ins.
high.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins.
in the ground, to solid rock, and in a mound of stone, 5
ft. base, to top, with brass cap mkd.

T10N R22E
1 S 6
4 S 7
1978

from which

A juniper, 7 ins. diam., bears N. 46° E.,
32.5 lks. dist., mkd. 1/4 S6 BT.

A juniper, 4 ins. diam., bears N. 49° W.,
40.5 lks. dist., mkd. X at breast height and BT at
the base.

Deposit the unmarked stone alongside the iron post.

Cor. is 105 lks. N of an E-W fence.

S. 86°16' W., beginning new measurement.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 10 N., R. 22 E., Gila & Salt River Mer., Ariz.

CHAINS	
37.07	<p>The cor. of secs. 1, 6, 7 and 12, on the W bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 9 ins. above ground with brass cap mkd. as described in the official record of the 1969 resurvey of a portion of the E bdy. of T. 10 N., R. 21 E. A mound of stone, 3 ft. base, 2 ft. high, is W of the cor.</p> <p>Cor. is 1 lk. S of a fence cor. from which fences extend S and E.</p>
<p>Subdivision of Sec. 15, T. 10 N., R. 22 E., Gila and Salt River Mer., Arizona</p>	
<p>From the 1/4 sec. cor. of secs. 15 and 22.</p>	
<p>N. 0°34' W., on the N and S center line of sec. 15.</p>	
<p>Over rolling land, through scattering timber.</p>	
0.21	<p>Fence, bears E and W.</p>
0.36	<p>Power line and track road, bear E and W.</p>
15.20	<p>Telephone line, bears N. 80° E. and S. 80° W.</p>
17.10	<p>Fence, bears N. 80° E. and S. 80° W.</p>
18.70	<p>State Highway No. 60, asphalt surfaced, bears N. 80° E. and S. 80° W.</p>
20.20	<p>Fence, bears N. 80° E. and S. 80° W.</p>
40.25	<p>Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E and W center line of the sec.</p>
<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
<p>T10N R22E C 1/4 S15 1978</p>	
<p>Raise a mound of stone, 3 1/2 ft. base, 3 ft. high, W of the cor.</p>	
49.05	<p>Fence, bears N. 50° E. and S. 50° W.</p>
51.40	<p>Access road, asphalt surfaced, bears N. 50° E. and S. 50° W.</p>
54.95	<p>Runway at Show Low Airport, asphalt surfaced, bears N. 50° E. and S. 50° W.</p>
60.20	<p>Main runway at Show Low Airport, asphalt surfaced, bears N. 72° E. and S. 72° W.</p>
60.535	<p>Point for the center N 1/16 sec. cor. of sec. 15, falls in the Show Low Airport runway where it is unsafe to set a monument, not monumented.</p>
68.00	<p>Fence, bears N. 77° E. and S. 77° W.</p>
76.00	<p>Fence, bears N. 60° E. and S. 60° W.</p>
80.82	<p>The 1/4 sec. cor. of secs. 10 and 15.</p>

Subdivision of Sec. 15, T. 10 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S. 89°59' W., on the E and W center line of sec. 15.</p> <p>Over rolling land, through scattering timber.</p>	
20.31	<p>Point for the center E 1/16 sec. cor. of sec. 15.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E E 1/16 C ————— C S15 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 46 1/2° W., 103 lks. dist., mkd. C E 1/16 S15 BT.</p> <p style="padding-left: 40px;">A boulder, 3 x 2 x 2 ft. above ground, bears N. 50° W., 116 lks. dist., mkd. X BO on top.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>	
40.62	The center 1/4 sec. cor. of sec. 15.	
49.00	Fence, bears SE and NW.	
53.00	Access road, asphalt surfaced, bears N. 50° E. and S. 50° W.	
57.10	Runway at Show Low Airport, asphalt surfaced, bears N. 50° E. and S. 50° W.	
68.50	Access road, bears SE and NW.	
80.87	The 1/4 sec. cor. of secs. 15 and 16.	
	<p>NE 1/4, Sec. 15</p> <hr style="width: 20%; margin: auto;"/>	
15.255	<p>From the center E 1/16 sec. cor. of sec. 15.</p> <p>N. 0°54' W., on the N and S center line of the NE 1/4 of sec. 15.</p> <p>Over rolling land, through scattering timber.</p> <p>Point for the center N-S-NE 1/256 sec. cor. of sec. 15.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S15 C-N-S-NE 1/256 1978</p> <p>from which</p>	

Subdivision of Sec. 15, T. 10 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>A fence cor., bears N. 8 1/2° E., 201.5 lks. dist., from which fences extend S. 75° W. and N. 10° W.</p> <p>A juniper, 5 ins. diam., bears S. 51 1/2° E., 50.5 lks. dist., mkd. C-N-S-NE 1/256 S15 BT.</p> <p>A juniper, 5 ins. diam., bears S. 3° W., 88 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
17.20	Fence, bears S. 75° W. and N. 75° E., 27 lks. dist., thence N. 10° W.
18.50	Same fence, bears S. 10° E. and N. 10° W.
20.34	Point for the NE 1/16 sec. cor. of sec. 15, at intersection with the E and W center line of the NE 1/4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p>T10N R22E NE 1/16 S15 1978</p>
	from which
	<p>A juniper, 12 ins. diam., bears S. 33 1/2° E., 78 lks. dist., mkd. NE 1/16 S15 BT.</p> <p>A juniper, 6 ins. diam., bears S. 60 1/2° W., 184.5 lks. dist., mkd. NE 1/16 S15 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W of the cor.</p>
32.40	Enter a dry lake bed, the edge bears SE and NW.
40.68	The E 1/16 sec. cor. of secs. 10 and 15.
	<hr style="width: 20%; margin: 0 auto;"/>
	From the N 1/16 sec. cor. of secs. 14 and 15.
	S. 89°51' W., on the E and W center line of the NE 1/4 of sec. 15.
	Over a dry lake bed.
4.00	Enter gently rolling land, with a cover of scattering timber.
20.19	The NE 1/16 sec. cor. of sec. 15.
20.62	Fence, bears S. 10° E. and N. 10° W.
25.237	Point for the center E-W-NE 1/256 sec. cor. of sec. 15.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p>S15 C-E-W-NE 1/256 1978</p>

Subdivision of Sec. 15, T. 10 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 11 ins. diam., bears S. 85° E., 157 lks. dist., mkd. C-E-W-NE 1/256 S15 BT.</p> <p>A juniper, 4 ins. diam., bears N. 62° W., 111.5 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.</p>
34.35	N end of a runway at Show Low Airport, asphalt surfaced, projects S. 50° W.
39.10	The center of the main runway at Show Low Airport, asphalt surfaced, bears N. 72° E. and S. 72° W.
40.38	Point for the center N 1/16 sec. cor. of sec. 15.
	<hr/> <p>From the center N-S-NE 1/256 sec. cor. of sec. 15.</p> <p>S. 89°53' W., on the E and W center line of the NE 1/4 SW 1/4 NE 1/4 of sec. 15.</p> <p>Over rolling land, through scattering timber.</p>
5.051	Point for the NE-SW-NE 1/256 sec. cor. of sec. 15.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S15 NE-SW-NE 1/256 1978</p>
	<p>from which</p> <p>A juniper, 8 ins. diam., bears S. 33 1/2° E., 14 lks. dist., mkd. NE-SW-NE 1/256 S15 BT.</p> <p>A juniper, 10 ins. diam., bears S. 47° W., 46.5 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
	<hr/> <p>N. 0°49' W., on the N and S center line of the NE 1/4 SW 1/4 NE 1/4 of sec. 15.</p> <p>Over nearly level land, through scattering timber.</p>
0.66	Fence, bears N. 75° E. and S. 75° W.
5.082	The center E-W-NE 1/256 sec. cor. of sec. 15.
	<hr/> <p style="text-align: center;">Subdivision of Sec. 26, T. 10 N., R. 22 E., Gila & Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 26 and 35.</p>

Subdivision of Sec. 26, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 0°11' W., on the N and S center line of sec. 26. Over rolling land, through scattering timber.</p> <p>19.94 Point for the center S 1/16 sec. cor. of sec. 26. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C S 1/16 S26 C 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 4 ins. diam., bears S. 70° E., 152.5 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears S. 30° W., 89.5 lks. dist., mkd. C S 1/16 S26 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p>
39.88	<p>Point for the center 1/4 sec. cor. of sec. 26, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S26 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p>
80.18	<p>The 1/4 sec. cor. of secs. 23 and 26.</p>
20.20	<p>From the 1/4 sec. cor. of secs. 25 and 26.</p> <p>S. 89°35' W., on the E and W center line of sec. 26. Over gently rolling land, through scattering timber.</p> <p>Point for the center E 1/16 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E E 1/16 C ————— C S26 1978</p> <p>from which</p> <p style="padding-left: 40px;">An old fence cor., bears N. 45° E., 28.5 lks. dist., from which fences extend northerly and S. 55° E.</p>

Subdivision of Sec. 26, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>An alligator juniper, 8 ins. diam., bears N. 1° W., 34.5 lks. dist., mkd. C E 1/16 S26 BT.</p>	
40.40	The center 1/4 sec. cor. of sec. 26.	
80.53	The 1/4 sec. cor. of secs. 26 and 27.	
<p>Subdivision of Sec. 34, T. 10 N., R. 22 E., Gila & Salt River Mer., Arizona</p>		
	<p>From the 1/4 sec. cor. of secs. 3 and 34, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.</p> <p>N. 0°13' W., on the N and S center line of sec. 34.</p> <p>Over rolling land, through medium to scattering timber.</p>	
19.73	<p>Point for the center S 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C S 1/16 S34 C 1978</p> <p>Deposit an aluminum orange soda can at the base of the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W of the cor.</p>	
39.46	<p>Point for the center 1/4 sec. cor. of sec. 34, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S34 1978</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p>	
79.11	The 1/4 sec. cor. of secs. 27 and 34.	
	<p>From the 1/4 sec. cor. of secs. 34 and 35.</p> <p>S. 89°37' W., on the E and W center line of sec. 34.</p> <p>Over rolling land, through scattering timber.</p>	
39.95	The center 1/4 sec. cor. of sec. 34.	
58.50	Power line, bears S. 15° E. and N. 15° W.	
58.80	Track road, bears S. 15° E. and N. 15° W.	

Subdivision of Sec. 34, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS	
59.10	Power line, bears S. 15° E. and N. 15° W.
59.98	Point for the center W 1/16 sec. cor. of sec. 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T10N R22E W 1/16 C-----C S34 1978</p>
	from which
	An alligator juniper, 10 ins. diam., bears S. 63° E., 171.5 lks. dist., mkd. C W 1/16 S34 BT.
	A ponderosa pine, 10 ins. diam., bears S. 89° W., 99.5 lks. dist., mkd. C W 1/16 S34 BT.
	Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.
80.01	The 1/4 sec. cor. of secs. 33 and 34.
	<hr/> <p>SW 1/4, Sec. 34</p> <hr/>
	From the true point for the W 1/16 sec. cor. of secs. 3 and 34, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.
	N. 0°10' W., on the N and S center line of the SW 1/4 of sec. 34.
	Over rolling land, through medium to scattering timber.
19.70	Point for the SW 1/16 sec. cor. of sec. 34, at intersection with the E and W center line of the SW 1/4 of sec. 34.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p>T10N R22E SW 1/16 S34 1978</p>
	from which
	A ponderosa pine, 7 ins. diam., bears N. 34° E., 64 lks. dist., mkd. SW 1/16 S34 BT.
	An alligator juniper, 5 ins. diam., bears S. 53° E., 22.5 lks. dist., mkd. SW 1/16 S34 BT.
	Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.
39.40	The center W 1/16 sec. cor. of sec. 34.
	<hr/>
	From the center S 1/16 sec. cor. of sec. 34.
	S. 89°42' W., on the E and W center line of the SW 1/4 of sec. 34.

Subdivision of Sec. 34, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Over rolling land, through scattering timber.</p> <p>12.10 Power line, bears S. 15° E. and N. 15° W.</p> <p>12.40 Track road, bears S. 15° E. and N. 15° W.</p> <p>12.70 Power line, bears S. 15° E. and N. 15° W.</p> <p>20.04 The SW 1/16 sec. cor. of sec. 34.</p> <p>30.00 Show Low Creek, scaled, course NW.</p> <p>40.08 The S 1/16 sec. cor. of secs. 33 and 34.</p>
	<p style="text-align: center;">Subdivision of Sec. 35, T. 10 N., R. 22 E., Gila & Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.</p> <p>N. 0°17'30" E., on the N and S center line of sec. 35.</p> <p>Over rolling land, through dense timber.</p> <p>19.78 Point for the center S 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C S 1/16 S35 C 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 77° E., 13.5 lks. dist., mkd. C S 1/16 S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 38° W., 19 lks. dist., mkd. C S 1/16 S35 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is 40 lks. E of a N-S fence.</p> <p>25.00 Timber Mesa Fire Road, bears N. 70° E. and S. 70° W.</p> <p>39.56 Point for the center 1/4 sec. cor. of sec. 35, at intersection with the E and W center line of the sec.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E C 1/4 S35 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 18° W., 106 lks. dist., mkd. C 1/4 S35 BT.</p>

Subdivision of Sec. 35, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS


An alligator juniper, 4 ins. diam., bears N. 83° W.,
68.5 lks. dist., mkd. X at breast height and BT at
the base.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of
the cor.

Cor. is 64 lks. E of a N-S fence.

59.39 Point for the center N 1/16 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, with brass cap mkd.



from which

An alligator juniper, 6 ins. diam., bears
S. 19° W., 42 lks. dist., mkd. C N 1/16 S35 BT.


An alligator juniper, 9 ins. diam., bears
N. 49° W., 53 lks. dist., mkd. C N 1/16 S35 BT.

Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W
of the cor.

Cor. is 31 lks. E. of a N-S fence.

69.305 Point for the center N-N 1/64 sec. cor. of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, with brass cap mkd.



from which

An alligator juniper, 7 ins. diam., bears N. 38° E.,
114 lks. dist., mkd. C N-N 1/64 S35 BT.

An alligator juniper, 5 ins. diam., bears S. 79° W.,
94 lks. dist., mkd. C N-N 1/64 S35 BT.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of
the cor.

Cor. is 18.5 lks. E of a N-S fence.

79.22 The 1/4 sec. cor. of secs. 26 and 35.

From the 1/4 sec. cor. of secs. 35 and 36.

S. 89°53' W., on the E and W center line of sec. 35.

Over rolling land, through dense timber.

Subdivision of Sec. 35, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS		
4.33	Fence, bears N and S.	
4.995	Point for the center E-E-E 1/256 sec. cor. of sec. 35.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">S35 C-E-E-E 1/256 1978</p>	
	from which	
	<p style="text-align: center;">A ponderosa pine, 6 ins. diam., bears N. 13° E., 28 lks. dist., mkd. C-E-E-E 1/256 S35 BT.</p>	
	<p style="text-align: center;">A ponderosa pine, 7 ins. diam., bears S. 33° E., 9 lks. dist., mkd. C-E-E-E S35 BT.</p>	
19.98	Point for the center E 1/16 sec. cor. of sec. 35, not monumented.	
39.96	The center 1/4 sec. cor. of sec. 35.	
80.48	The 1/4 sec. cor. of secs. 34 and 35.	
	NE 1/4, Sec. 35,	

	From the point for the center E 1/16 sec. cor. of sec. 35.	
	N. 0°32' E., on the N and S center line of the NE 1/4 of sec. 35.	
	Over rolling land, through dense timber.	
19.82	Point for the NE 1/16 sec. cor. of sec. 35, at intersection with the E and W center line of the NE 1/4 of sec. 35, not monumented.	
39.64	The E 1/16 sec. cor. of secs. 26 and 35.	

	From the N 1/16 sec. cor. of secs. 35 and 36.	
	S. 89°56' W., on the E and W center line of the NE 1/4 of sec. 35.	
	Over rolling land, through dense timber.	
10.03	Point for the center E-NE 1/64 sec. cor. of sec. 35.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">S35 C-E-NE 1/64 1978</p>	
	from which	
	<p style="text-align: center;">An alligator juniper, 4 ins. diam., bears N. 77° E., 11 lks. dist., mkd. X at breast height and BT at the base.</p>	

Subdivision of Sec. 35, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 11 ins. diam., bears S. 36° E., 91.5 lks. dist., mkd. C-E-NE 1/64 S35 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.</p> <p>Cor. is 42 lks. W of a fence which bears N. 10° E. and S. 10° W.</p>
20.06	The point for the NE 1/16 sec. cor. of sec. 35.
40.12	The center N 1/16 sec. cor. of sec. 35.
	<hr/> <p>From the center E-E-E 1/256 sec. cor. of sec. 35.</p> <p>N. 0°43' E., on the N and S center line of the SE 1/4 SE 1/4 NE 1/4 of sec. 35.</p> <p>Over rolling land, through dense timber.</p>
4.30	Fence, bears S. 10° E. and N. 10° W.
4.95	Point for the SE-SE-NE 1/256 sec. cor. of sec. 35.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S35 SE-SE-NE 1/256 1978</p> <p>from which</p> <p>An alligator juniper, 5 ins. diam., bears N. 75° E., 28 lks. dist., mkd. SE-SE-NE 1/256 S35 BT.</p> <p>An alligator juniper, 6 ins. diam., bears S. 7° E., 88.5 lks. dist., mkd. SE-SE-NE 1/256 S35 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <hr/> <p>S. 89°54' W., on the E and W center line of the SE 1/4 SE 1/4 NE 1/4 of sec. 35.</p> <p>Over rolling land, through dense timber.</p>
5.00	Point for the center S-SE-NE 1/256 sec. cor. of sec. 35.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S35 C-S-SE-NE 1/256 1978</p> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N. 7° E., 10 lks. dist., mkd. C-S-SE-NE 1/256 S35 BT.</p> <p>An alligator juniper, 6 ins. diam., bears S. 20° E., 35 lks. dist., mkd. C-S-SE-NE 1/256 S35 BT.</p>

Subdivision of Sec. 35, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS		
	<p>N. 0°39'30" E., on the N and S center line of the SE 1/4 NE 1/4 of sec. 35.</p>	
	<p>Over rolling land, through medium to dense timber.</p>	
4.95	<p>Point for the SE-NE 1/64 sec. cor. of sec. 35.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">S35 SE-NE 1/64 1978</p>	
	<p>from which</p>	
	<p>A boulder, 3 x 2 x 2 ft. above ground, bears N. 47° E., 28 lks. dist., mkd. X BO on the SW face.</p>	
	<p>A boulder, 5 1/2 x 3 1/2 x 3 1/2 ft. above ground, bears S. 25° E., 30.3 lks. dist., mkd. X BO on the N face.</p>	
14.85	<p>The center E-NE 1/64 sec. cor. of sec. 35.</p>	
	<p style="text-align: center;">_____</p> <p>From the center N-N 1/64 sec. cor. of sec. 35.</p>	
	<p>N. 89°58' E., on the E and W center line of the NW 1/4 NE 1/4 of sec. 35.</p>	
	<p>Over rolling land, through dense timber.</p>	
10.052	<p>Point for the NW-NE 1/64 sec. cor. of sec. 35.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">S35 NW-NE 1/64 1978</p>	
	<p>from which</p>	
	<p>An alligator juniper, 5 ins. diam., bears N. 72° W., 18 lks. dist., mkd. NW-NE 1/64 S35 BT.</p>	
	<p>An alligator juniper, 4 ins. diam., bears N. 20° W., 38 lks. dist., mkd. X at breast height and BT at the base.</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p>	
	<p style="text-align: center;">_____</p> <p>N. 0°25' E., on the N and S center line of the NW 1/4 NE 1/4 of sec. 35.</p>	
	<p>Over rolling land, through medium timber.</p>	
9.912	<p>The W-E 1/64 sec. cor. of secs. 26 and 35.</p>	
	<p style="text-align: center;">_____</p>	

Subdivision of Sec. 35, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the E 1/16 sec. cor. of secs. 2 and 35, on the S bdy. of the Tp., described in the field notes of the dependent resurvey of a portion of the N bdy. of T. 9 N., R. 22 E., executed concurrently.</p> <p>N. 0°22' E., on the N and S center line of the SE 1/4 of sec. 35.</p> <p>Over rolling land, through dense timber.</p>
19.78	<p>Point for the SE 1/16 sec. cor. of sec. 35, at intersection with the E and W center line of the SE 1/4 of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E SE 1/16 S35 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 18 ins. diam., bears S. 79° E., 95 lks. dist., mkd. SE 1/16 S35 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 87° W., 92 lks. dist., mkd. SE 1/16 S35 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is 2 lks. E of a fence bearing NE and SW.</p>
29.67	<p>Point for the center N-SE 1/64 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S35 C-N-SE 1/64 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 88° E., 46 lks. dist., mkd. X at breast height and BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 38° E., 33 lks. dist., mkd. C-N-SE 1/64 S35 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of the cor.</p>
34.615	<p>Point for the center N-N-SE 1/256 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S35 C-N-N-SE 1/256 1978</p> <p>from which</p>

Subdivision of Sec. 35, T. 10 N., R. 22 E.,
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A forked pinyon pine, 16 ins. diam., bears S. 87 1/2° E., 35 lks. dist., mkd. C-N-N-SE 1/256 S35 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears S. 25° E., 86 lks. dist., mkd. C-N-N-SE 1/256 S35 BT.</p>
39.56	<p>The point for the center E 1/16 sec. cor. of sec. 35.</p> <hr/> <p>From the S 1/16 sec. cor. of secs. 35 and 36.</p> <p>S. 89°54' W., on the E and W center line of the SE 1/4 of sec. 35.</p> <p>Over rolling land, through dense timber.</p>
19.95	<p>The SE 1/16 sec. cor. of sec. 35.</p>
39.90	<p>The center S 1/16 sec. cor. of sec. 35.</p> <hr/> <p>From the center E-E-E 1/256 sec. cor. of sec. 35.</p> <p>S. 0°26' W., on the N and S center line of the NE 1/4 NE 1/4 SE 1/4 of sec. 35.</p> <p>Over rolling land, through dense timber.</p>
4.947	<p>Point for the NE-NE-SE 1/256 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S35 NE-NE-SE 1/256 1978</p> <p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears S. 74° E., 40 lks. dist., mkd. NE-NE-SE 1/256 S35 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 72° W., 46 lks. dist., mkd. NE-NE-SE 1/256 S35 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is 82 lks. S of a track road, which in a curve bears NE and N. 50° W.</p> <hr/> <p>S. 89°53' W., on the E and W center line of the N 1/2 of the N 1/2 of the NE 1/4 SE 1/4 of sec. 35.</p> <p>Over rolling land, through dense timber.</p>
14.98	<p>The center N-N-SE 1/256 sec. cor. of sec. 35.</p> <hr/>

Township 10 North, Range 22 East,
Gila and Salt River Mer., Arizona

CHAINS

GENERAL DESCRIPTION

The area surveyed within T. 10 N., R. 22 E., varies from rolling to nearly level. The elevation ranges from about 6,300 to 6,900 ft. above ground. The soil is a rocky clay loam. The vegetation consists of pine, juniper and oak in the higher elevations with a good cover of native grasses in the open areas. Drainage is generally westerly.

Access is provided by State Highway No. 60, which enters on the west boundary of section 19 and traverses easterly through the town of Show Low, exiting at the east boundary of section 13. State Highway No. 77 projects N-NW from Highway No. 60 in section 16 and passes through north boundary of section 5. Show Low Municipal Airport is located in section 15. Telephone Lake is located mostly in section 6 and partly in section 5. A cinder pit is located immediately south of the corner of sections 13, 14, 23 and 24; this pit is presently in operation.

An average number of readings throughout the area surveyed gives a mean magnetic declination of 14° E., with a range of 5° in local attraction.

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Harry K. Smith, Supervisory Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day of June 1978, and supplemental special instructions dated the 17th day of October, 1978, ~~(I)~~ ~~(We)~~ have dependently resurveyed a portion of the west boundary, the north boundary and a portion of the subdivisional line, and surveyed subdivisions in sections 15, 26, 34 and 35 of Township 10 North, Range 22 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(I)~~ and under (my) ~~(my)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9-26-79
(Date)

Harry K. Smith
Supervisory (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.

Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the west boundary, the north boundary and a portion of the subdivisional lines, and subdivisions in sections 15, 26, 34 and 35 of T. 10 N., R. 22 E., of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Supervisory Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

DEC 11 1979
(Date)

[Signature]
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey)