

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

(1)

FIELD NOTES

of the

Dependent Resurvey of a Portion of the

Exterior Boundaries and Subdivisional Lines

and

Dependent Resurvey of a Portion of the

Subdivisions of Section 18

and

A Survey of a Portion of the Subdivisional Lines

and

Survey of Subdivisions of Sections 1, 3, 7, 9, 10, 14,

15, 17, 18, 19, 20, 22, 33 and 35

of

Township 15 North, Range 4 East

Of the Gila and Salt River Meridian,

In the State of Arizona

EXECUTED BY

Harry K. Smith,

Cadastral Surveyor

Under special instructions dated October 19, 19⁷³, approved October 19, 1973,

_____, which provided for the surveys included under U.S. Survey/Group
Number 564, and assignment instructions dated October 19, 19⁷³.

Survey commenced September 17, 19⁷⁴

Survey completed April 2, 19⁷⁵

1A

BOOK 5095

INDEX DIAGRAM

Township 15 North, Range 4 East
11 10

	6 60	61 5 59	46 4 45	35 8 34	25 2 16	1 5 64
8	7 56	58 8 55	44 9 42	33 10 32	24 11 15 23	12
7	18 53	54 17 52	42 16	31 15 30	22 14 13 21	13
	19 49	50 20 47	40 21 39	29 22 29	19 23	24
	30	29 47	38 28 37	28 27 27	18 26 63	25 63
	31	32	36 33	26 34	17 35 3	62 36 1

Subdivision	Sec.	1	-----	Page	65
"	"	3	-----	"	66
"	"	7	-----	"	70
"	"	9	-----	"	74
"	"	10	-----	"	76
"	"	14	-----	"	78
"	"	15	-----	"	80
"	"	17	-----	"	82
"	"	18	-----	"	84
"	"	19	-----	"	88
"	"	20	-----	"	91
"	"	22	-----	"	94
"	"	33	-----	"	96
"	"	35	-----	"	100

Dependent Resurvey of T. 15 N., R. 4 E.,
Gila and Salt River Meridian, Arizona

CHAINS

The history of surveys of Township 15 North, Range 4 East, Gila and Salt River Meridian, Arizona, is as follows:

The south, west and north boundaries and a portion of the subdivisional lines were surveyed in 1877 by C. Burton Foster. A portion of the north boundary was resurveyed in 1916 by William H. Richards, Jr. A portion of the south and west boundaries were resurveyed in 1917 by Sidney E. Blout. The east boundary was surveyed in 1918 by William B. Kimmel and Sidney E. Blout. A portion of the south boundary was retraced in 1915 in connection with Homestead Entry Surveys Nos. 329 and 330 by the U.S. Forest Service. A portion of the north boundary was resurveyed in 1938 by Ty White, Norville Shearer and Frank Kennon. Certain corners along the south and west boundaries and within the township were remonumented in 1964 by Boyd S. Owens. The boundaries of Section 18 were resurveyed and Section 18 was partially subdivided by Boyd S. Owens in 1965. A portion of the south boundary was resurveyed by Harry K. Smith in 1972-74.

The following field notes are those of the dependent resurvey of a portion of the exterior boundaries, a portion of the subdivisional lines, a portion of the subdivisions of Sec. 18, survey of a portion of the subdivisional lines and the survey of subdivisions in Sections 1, 3, 7, 9, 10, 14, 15, 17, 18, 19, 20, 22, 33 and 35.

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1947 and the Special Instructions for Group No. 564, Arizona, dated October 19, 1973.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The direction of lines were determined by direct solar observations and refer to the true meridian.

The geographic position of the southeast corner of the township as scaled from the U.S. Geological Survey quadrangle map, "Cornville, Arizona," prepared in 1968, is as follows:

Latitude, $34^{\circ}38'36''$ N. Longitude, $111^{\circ}52'06''$ W.

The mean magnetic declination is $13\frac{1}{2}^{\circ}$ E.

Dependent Resurvey of a Portion of the S. Bdy., T. 15 N.,
R. 4 E., Gila and Salt River Meridian, Arizona
(Restoring the Dependent Resurvey in 1974 by Harry
K. Smith)

The 1974 resurvey of the south boundary of Sec. 36, indicates this boundary is out of limits in measurement

Dependent Resurvey of
S. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

for initiating the survey of the first meridional line, therefore original cors. were altered to function for T. 14 N., R. 4 E. and new corners, as needed, set for T. 15 N., R. 4 E.

Beginning at the Tp. cor. of Tps. 14 and 15 N., Rs. 4 E., monumented by an iron post, 2½ ins. diam., projecting 20 ins. above the ground, mound of stone, 4 ft. base to top, with brass cap mkd.

T15N	T15N
R4E	R5E
<u>S36</u>	<u>S31</u>
S 1	
T14N	
	1974

from which

The cor. of Tps. 14 and 15 N., Rs. 5 E., bears south, 3.57 chs. dist., monumented by an iron post, 3 ins. diam., firmly set in a mound of stone, 3 ft. base, 2 ft. high, with brass cap mkd.

T14N	T15N
R4E	R5E
S 1	<u>S31</u>
	S 6
	1974
	1918

N. 88°43' W., bet. Secs. 1 and 36.

Ascend over rolling land.

27.10 N. side of bluff, descend over general W. slope.

36.40 Draw, drains NW.

40.01 Point for the ¼ sec. cor. of Sec. 36 only.

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.

T15N	R4E
¼	<u>S36</u>
T14N	R4E
	1975

from which

A cedar, 4 ins. diam., bears N. 22° E., 28 lks. dist., mkd. ¼ S36 BT.

40.20 Fence, bears S. 62° E. and N. 62° W.

Dependent Resurvey of
S. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
40.83	<p>The $\frac{1}{4}$ sec. cor., originally set to function for Secs. 1 and 36, monumented by an iron post, $2\frac{1}{2}$ ins. diam., projecting 20 ins. above ground, mound of stone, 3 ft. base to top. This cor. now functions as the $\frac{1}{4}$ sec. cor. of Sec. 1, T. 14 N., R. 4 E. only. Remark the brass cap to read</p> <p style="text-align: center;"> <u>T15N R4E</u> $\frac{1}{4}$ S 1 T14N R4E 1975 1974 </p> <hr/>
	<p>N. $89^{\circ}47'$ W., beginning new measurement.</p>
	<p>Descend over gentle NW slope.</p>
13.80	<p>Descend over steep NW slope.</p>
28.20	<p>Grandpa Wash, 1 ch. wide, 3 ft. deep, drains S curving W.</p>
36.20	<p>Fence, bears N. 75° E. and S. 75° W.</p>
38.46	<p>The cor. originally set as the cor. of Secs. 1, 2, 35 and 36, monumented by an iron post, $2\frac{1}{2}$ ins. diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high. This cor. now functions as the cor. of Secs. 1 and 2, T. 14 N., R. 4 E. only. Remark the brass cap to read.</p> <p style="text-align: center;"> T15N R4E <u>S36</u> S 2 S 1 T14N R4E 1964 1975 </p>
	<p>Land, rolling and broken. Soil, sandy loam and rocky with limestone outcrops. Timber, scattered juniper, palo-verde and mesquite. Undergrowth, creosote brush, oakbrush and cacti.</p>
	<p style="text-align: center;">(Restoring the survey executed by C. Burton Foster in 1877)</p>
	<p>From the cor. of Secs. 1 and 2 only.</p>
	<p>N. $89^{\circ}16'$ W., bet. Secs. 2 and 36.</p>
	<p>Over mountainous land through moderate undergrowth.</p>
0.72	<p>Point for the cor. of Secs. 35 and 36, T. 15 N., R. 4 E., only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.</p>

Dependent Resurvey of
S. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p style="text-align: center;">T15N R4E S35 S36 ----- S 2 T14N R4E 1975</p> <p>Continue measurement bet. Secs. 2 and 35.</p>
20.00	Spur, slopes SW.
39.60	<p>The ¼ sec. cor. of Secs. 2 and 35, monumented by a limestone, 18x9x6 ins., firmly set 10 ins. in the ground, mkd. ¼ on E face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ S35 ----- S 2 T14N 1975</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89°15' W., beginning new measurement.</p> <p>Over gently rolling land, through scattering undergrowth.</p>
19.415	<p>Point for the W. 1/16 sec. cor. of Secs. 2 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E W 1/16 S35 ----- S 2 T14N 1975</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
38.83	<p>The cor. of Secs. 2, 3, 34 and 35, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S34 S35 ----- S 3 S 2 T14N 1964</p> <p>Mound of stone, 2 ft. base, 2 ft. high, W of cor.</p>

Dependent Resurvey of
S. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

Land, rolling to gently rolling.
Soil, sandy loam with some limestone outcrops.
Timber, scattering cedar, and palo-verde.
Undergrowth, creosote bush, sage and cacti.

Dependent Resurvey of a Portion of the E. Bdy., T. 15 N.,
R. 4 E., Gila and Salt River Meridian, Arizona
(Restoring the Survey executed by William B. Kimmel
and Sidney E. Blout in 1918)

From the Tp. cor. of T. 15 N., Rs. 4 and 5 E., monumented
with an iron post, 3 ins. diam., projecting 10 ins. above
the ground, with a mound of stone, 3 ft. base, 6 ins.
high SE of the cor., with brass cap mkd.

S 1	S 6
R4E	R5E
T15N	
1917	

Remark the brass cap to read

T16N R4E	
S36	
S 1	S 6
R4E	R5E
T15N	
1917	
1975	

Rebuild mound of stone, 2½ ft. base, 1½ ft. high, S of
cor.

S. 0°05' W., bet. secs. 1 and 6.

Over gently rolling land, through scattering timber and
medium undergrowth.

0.46 Abandoned fenceline, bears E and W.

0.60 Wash, 10 lks. wide, 4 ft. deep, drains N. 70° W.

39.50 Wash, 1 chain wide, 5 ft. deep, drains S. 70° W.

40.00 Point for the ¼ sec. cor. of sec. 1 only, T. 15 N.,
R. 4 E., based on the protracted area for sec. 1 as shown
on the plat approved December 27, 1877. The point falls
in a wash draining SW where it is impractical to set a
monument.

40.10 Point selected for the witness ¼ sec. cor. of sec. 1
only.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in
the ground, with brass cap mkd.

W C	
T15N	
R4E	R5E
↑	
¼ S 1	
1975	

Dependent Resurvey of
E. Bdy., T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS

Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.

47.24 The $\frac{1}{4}$ sec. cor. of sec. 1, T. 15 N., R. 4 E., only, monumented with an iron post, 1 in. diam., projecting 7 ins. above the ground. This cor. now functions as an amended monument. Remark the brass cap to read.

A M
|
 $\frac{1}{4}$
|
S 1
|
1975
1918

Mound of stone, $2\frac{1}{2}$ ft. base, 1 ft. high, W of cor.

S. $0^{\circ}05'$ W., beginning new measurement.

Over gently rolling land, through medium undergrowth.

0.50 Dirt road, bears N. 50° E. and S. 50° W.

9.59 The $\frac{1}{4}$ sec. cor. of sec. 6, T. 15 N., R. 5 E., only, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, with brass cap mkd.

$\frac{1}{4}$
|
S 6
|
1918

Mound of stone, 2 ft. base, 1 ft. high, E of cor.

S. $0^{\circ}05'$ W., beginning new measurement.

Over gently rolling land, through scattering undergrowth.

30.41 The cor. of secs. 1 and 12, T. 15 N., R. 4 E., only, monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.

T15N
|
S 1
|
S12
|
R4E
|
1918

Remark the brass cap to read

T15N
R4E | R5E
S 1 | S 6
S12 |
1975
1918

Mound of stone, 3 ft. base, 1 ft. high, W of cor.


Dependent Resurvey of
E. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

Land, gently rolling.
Soil, sandy loam.
Timber, scattering cedar.
Undergrowth, creosote bush, sage and cacti.

Dependent Resurvey of a Portion of the W. Bdy., T. 15 N.,
R. 4 E., Gila and Salt River Meridian, Arizona
(Restoring the Resurvey executed by
Boyd S. Owens in 1965)

From the $\frac{1}{4}$ sec. cor. of Secs. 13 and 18, on the W. Bdy.
of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam.,
projecting 2 ins. above the ground, with brass cap mkd.



Corner is located in a N and S fence.


N. $0^{\circ}11'$ E., bet. Secs. 13 and 18.

Over gently rolling land, through scattering undergrowth,
along a fenceline.

- 15.30 Wash, 25 lks. wide, 2 ft. deep, drains NE.
- 19.81 Old fence, bears N, new fence bears E and S.
- 19.84 The N. $\frac{1}{16}$ sec. cor. of Secs. 13 and 18, monumented with
a $\frac{1}{2}$ in. reinforcement rod, 18 ins. long, firmly set, pro-
jecting 3 ins. above ground.

At the corner point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins.
in the ground, with brass cap mkd.



Reset the reinforcement rod alongside the iron post.

Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of
cor.

- 22.20 Paved road, bears E and W.
- 26.30 Paved road, bears E and W.
- 31.20 Wash, 20 lks. wide, 4 ft. deep, drains N. 80° E., curving
northerly.

Dependent Resurvey of
W. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS		
39.50	Bladed road, bears N. 40° E. and S. 40° W.	
39.68	The cor. of Secs. 7, 12; 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.	
	<p style="text-align: center;">T15N R3E R4E S12 S 7 S13 S18 1965</p>	
	<p>Land, rolling to gently rolling. Soil, sandy loam and rocky. Timber, palo-verde and mesquite. Undergrowth, creosote and cacti.</p>	
	<p>(Restoring the Survey executed by C. Burton Foster in 1877)</p>	
	<p>_____</p> <p>N. 0°15' E., bet. Secs. 7 and 12.</p>	
	<p>Over gently rolling land, through scattering timber and undergrowth.</p>	
1.80	Paved road, bears S. 35° E. and N. 35° W.	
13.30	Paved road, bears S. 20° E. and N. 20° W.	
19.67	Point for the S. 1/16 sec. cor. of Secs. 7 and 12.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	
	<p>T15N S 1/16 R3E R4E S12 S 7 1975</p>	
	from which	
	<p>A cottonwood, 15 ins. diam., bears N. 13¾° E., 102 lks. dist., mkd. S 1/16 S7 BT.</p>	
	<p>A local monument, a 5/8 in. rod, projecting 4 ins. above the ground, bears N. 7° W., 18.5 lks. dist.</p>	
	Deposit broken glass at base of iron post.	
22.80	Dirt road, bears S. 55° E. and N. 55° W.	
23.90	Fence, bears S. 60° E. and N. 60° W.; enter river bottom.	
29.10	Right bank of S channel of Verde River, 3 ft. banks, bears N. 55° E. and S. 55° W.	
29.80	Left bank of S channel of Verde River; thence, over small island.	

Dependent Resurvey of
W. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
31.60	Right bank of N channel of Verde River, 6 ft. banks, bears S. 80° E. and N. 80° W.
32.40	Left bank of N channel of Verde River; thence across open field.
37.30	Power line, bears S. 55° E. and N. 55° W.
39.34	<p>Point for the ¼ sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R3E R4E ¼ S 12 S 7 1975</p> <p>from which</p> <p style="padding-left: 40px;">A power pole, #22919, bears S. 49°57' W., 158 lks. dist.</p> <p style="padding-left: 40px;">A local monument, a re-bar, ½ in. diam., set flush with the ground, bears N. 32° W., 61.7 lks. dist.</p>
39.80	Fence, bears E and W.
42.90	Fence, bears S. 80° E. and N. 80° W.; enter dense mesquite, bears E. and W.
45.70	Fence, bears S. 65° E. and N. 65° W., leave dense mesquite; thence over gently rolling land, through medium undergrowth.
45.90	Dirt road, bears S. 85° E. and N. 85° W.
58.00	Fence, bears S. 25° E. and N. 25° W., 28 lks. dist. to cor. of fence, extending southerly.
58.60	Gravel road, bears N. 50° W. and S. 50° E., curving to S. 25° E.
59.01	<p>Point for the N. 1/16 sec. cor. of secs. 7 and 12.</p> <p>Bury an iron post, 14 ins. long, 2½ ins. diam., 6 ins. below the surface of gravel road, with brass cap mkd.</p> <p style="text-align: center;">T15N R3E R4E N 1/16 S 12 S 7 1975</p>

Dependent Resurvey of
W. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

from which

A local monument, an iron rod, 3/4 in. diam., set flush with the ground, bears N. 7° E., 22.4 lks. dist.

An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, mound of stone, 2½ ft. base to top, for a reference monument, bears N. 45° E., 100 lks. dist., with brass cap mkd. T15N R4E N 1/16 S7 R M 66 ft. 1975 and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 4 ins. in the ground, mound of stone, 3½ ft. base to top, for a reference monument, bears S. 45° W., 100 lks. dist., with brass cap mkd. T15N R3E N 1/16 S12 R M 66 ft. 1975 and an arrow pointing to the cor.

63.80

Fence, bears S. 78° E. and N. 78° W.

69.00

Fence, bears West and East 21 lks. to cor. of fences, extending northerly, southerly and westerly.

70.40

Wash, 50 lks. wide, 6 ft. deep, drains S. 70° W.

72.30

Fence, bears irregularly N and S.

78.68

The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp., monumented with a spike nail in a mound of stone, 2½ ft. base, 8 ins. high, located at the cor. of fences extending N, S, and W. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original corner positions.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3½ ft. base to top, with brass cap mkd.

T15N	
R3E	R4E
S 1	S 6
S12	S 7
1975	

Deposit broken glass at the base of the iron post.

Land, rolling.

Soil, sandy loam with some limestone outcrops.

Timber, juniper, mesquite, palo-verde, with cottonwood along the river

Undergrowth, creosote, oak brush, cacti and sparse grass.

Dependent Resurvey of a Portion of the N. Bdy., T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona
(Restoring the Resurvey executed by William H. Richards, Jr. in 1916)

Dependent Resurvey of
N. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>From the Tp. cor. of Tp. 15 N., Rs. 4 and 5 E., on the S. bdy. of T. 16 N., R. 4 E., heretofore described.</p> <p>West, bet. secs. 1 and 36.</p> <p>Over gently rolling land, through scattering undergrowth</p> <p>34.28 The ¼ sec. cor. of secs. 1 and 36, monumented with a limestone 14x14x8 ins., projecting 7 ins. above the ground, mkd. ¼ on E face, with a mound of stone, 3½ ft. base, 1 ft. high, N of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T16N R4E ¼ <u>S36</u> S 1 T15N 1975</p> <p>Deposit the mkd. stone alongside the iron post, in the mound of stone.</p> <p>Cor. is located in a fenceline, fence bears N and S for 46 lks. to cor. of fences extending N, S and W, abandoned fence extends E.</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89°55' W., beginning new measurement.</p> <p>Over gently rolling land, through medium undergrowth.</p>
33.00	<p>Dirt road, bears irregularly SE and westerly,</p>
40.09	<p>The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R4E <u>S35 S36</u> S 2 S 1 T15N 1916</p> <p>Mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located 30 lks. S of a dirt road, bearing N. 60° E. curving E. and S. 60° W. curving W.</p>
<p style="text-align: center;">(Restoring the Resurvey executed by Ty White, Norville E. Shearer and Frank Kennon in 1938)</p> <hr style="width: 20%; margin: auto;"/> <p>From the true point for the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp.</p> <p>N. 89°44' W., bet. secs. 4 and 33.</p> <p>Through farm yard.</p>	

Dependent Resurvey of
N. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
2.90	<p>The witness sec. cor. for secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., 2 ins. below the surface of the ground, encircled by a mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">T16N R4E S33 S34 S 4 S 3 W C T15N 1938</p> <p>from which</p> <p style="padding-left: 40px;">A willow, 14 ins. diam., bears N. 17 3/4° E., 122 lks. dist., with healed blaze. (Record 119 lks.)</p> <p style="padding-left: 40px;">An ash, 29 ins. diam., bears S. 72 1/4° E., 49 lks. dist., with healed blaze. (Record S 72 3/4° E., 48 lks.)</p> <p style="padding-left: 40px;">A dead mesquite, 8 ins. diam., bears S. 78 3/4° W., 13.5 lks. dist., with healed blaze. (Record S. 76 3/4° W., 14 lks.)</p> <p style="padding-left: 40px;">A mesquite stump, 7 ins. diam., bears N. 19° W., 51 lks. dist., mkd. W C BT.</p> <p>Reset the cor., with 10 ins. projecting above the ground.</p> <p>Rebuild mound of stone around cor., 2 ft. base to top, and remark the brass cap to read</p>
11.80	<p>Power line, bears N. 35° E. and S. 35° W.</p>
14.50	<p>Fence, bears N. 30° E. and S. 30° W.; thence across creek bottom.</p>
17.40	<p>Oak Creek, 3.80 chs. wide, course S. 15° W.</p>
19.70	<p>Cornville ditch, 10 lks. wide, flows S.</p>
20.205	<p>Point for the E. 1/16 sec. cor. of secs. 4 and 33.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T16N R4E E 1/16 S33 S 4</p> <p style="text-align: center;">T15N 1975 1938</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of cor.</p>
20.80	<p>Low spur, slopes S. 25° E.</p>
24.20	<p>Jeep trail, bears N. 15° E. and S. 15° W.; ascend E slope.</p>
35.80	<p>End of ascent; thence along N slope.</p>

Dependent Resurvey of
N. Bdy., T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

40.41 The $\frac{1}{4}$ sec. cor. of Secs. 4 and 33, on the N. bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 3 ins. above the ground, mound of stone, 2 ft. base to top, with brass cap mkd.

$\frac{1}{4}$ $\frac{S33}{S 4}$
1938

from which

A juniper, 12 ins. diam., bears S. 18° W., 24 lks. dist., mkd. $\frac{1}{4}$ S BT, at chest height.

A juniper, 17 ins. diam., bears N. 17 $\frac{1}{4}$ ° W., 132 lks. dist., mkd. $\frac{1}{4}$ S 33 BT, at chest height. (record 129 lks.)

Remark the brass cap to read

T16N R4E
 $\frac{1}{4}$ $\frac{S33}{S 4}$
T15N
1975
1938

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 15 N., R. 4 E., Gila and Salt River Mer., Arizona
(Restoring the Survey executed by C. Burton Foster
in 1877)

Retracements within the Tp., prior to monumentation indicate that certain original cors. along the 1st and 2nd Meridional lines would be out of limits for completing the survey of the remaining unsurveyed sections. Therefore these corners were marked to function for surveyed sections only.

From the cor. of Secs. 13, 14, 23 and 24, monumented with a limestone, 15x10x7 ins., firmly set, projecting 8 ins. above the ground, no marks visible, with mound of stone, 3 ft. base, 1 ft. high, N of cor. This cor. now functions as the cor. of Secs. 14 and 23, only.

At the corner point

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R4E
 $\frac{S14}{S23}$ S13
1975

from which

A cedar, 12 ins. diam., bears S. 45 $\frac{3}{4}$ ° W., 224 lks. dist., mkd. T15N R4E S23 BT.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS		
	Deposit the unmkd. stone alongside the iron post.	
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.	
	N. 0°09' E., on the E. bdy. of Sec. 14.	
	Over rolling land, through scattering timber and medium undergrowth.	
28.00	Draw, drains irregularly W.	
39.95	The ¼ sec. cor. of Secs. 13 and 14, monumented with a limestone, 20x14x8 ins., firmly set, projecting 12 ins. above ground, no marks visible, with scattered mound of stone alongside. This cor. now functions as the ¼ sec. cor. of Sec. 14, only.	
	At the corner point.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.	
	T15N R4E ¼ S14 1975	
	Rebuild mound of stone, 2½ ft. base, 1½ ft. high, W of cor.	
	Bury the unmkd. stone in base of mound.	
	N. 0°12' E., beginning new measurement.	
	Over rolling land, through medium undergrowth.	
14.00	Draw, drains N. 70° W., curving to SW.	
29.60	Jeep trail, bears N. 80° E. and S. 80° W.	
39.91	The cor. of Secs. 11, 12, 13 and 14, monumented with a limestone, 14x12x7 ins., firmly set, projecting 8 ins. above the ground, no marks visible, with mound of stone, 2½ ft. base, 1½ ft. high, N of cor. This cor. now functions as the cor. of Secs. 11 and 14, only.	
	At the corner point.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.	
	T15N R4E S11 S12 S14 1975	
	Deposit the unmkd. stone alongside the iron post.	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>Rebuild mound of stone, 3 ft. base, 2½ ft. high, W of cor.</p> <p>Land, rolling. Soil, sandy, with limestone outcrops. Timber, cedar and palo-verde. Undergrowth, creosote, scrub oak and sage.</p>
	<p>N. 0°51' W., on E. bdy. of Sec. 11.</p> <p>Over rolling land, through scattering timber, and medium undergrowth.</p>
6.10	Ridge, bears N. 30° E. and S. 30° W.
8.60	Fence, bears S. 20° W. and N. 20° E., 54 lks. to cor. of fences extending northerly and S. 20° W.
12.30	Spur, slopes N. 50° W.
12.90	Fence, bears S. 20° E. and N. 20° W.
17.40	Fence, bears N. 8° E. and S. 8° W.
25.40	Fence, bears S. 28° E. and N. 28° W., 11 lks. to jog in fence extending northerly.
29.00	Wash, 20 lks. wide, 3 ft. deep, drains S. 35° W.
29.70	Fence, bears northerly and southerly.
39.70	<p>The ¼ sec. cor. of Sec. 11 and 12, monumented with a mound of stone, 2 ft. base, 1 ft. high. This position has been accepted as the best evidence of the original cor. position. This cor. now functions as the ¼ sec. cor. of Sec. 11, only. Not remonumented.</p> <p>Cor. is located 12 lks. W of a fence, bears N and S.</p>
	<p>N. 0°08' E., beginning new measurement.</p> <p>Over rolling land, through scattering timber and undergrowth.</p>
17.40	Powerline, bears S. 75° E. and N. 75° W.
24.10	Fence, bears N. 75° W. and S. 75° E., 1.5 lks. to cor. of fences extending S. 75° E., South and N. 75° W.
24.80	Paved Forest Service road, No. 119, bears S. 75° E. and N. 75° W.
25.60	Fence, bears N. 75° W. and S. 75° E., 1.5 lks. to cor. of fences extending S. 75° E., South and N. 75° W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G.SRM., Arizona

CHAINS		
40.53	<p>The cor. of Secs. 1, 2, 11 and 12, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S 2 S 1 S11 S12 1964</p> <p>This cor. was remonumented by Boyd S. Owens in 1964, and now functions for the cor. of Secs. 2 and 11, only.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T15N R4E S 2 S 1 S11 S 1 1975 1964</p> <p>Raise a mound of stone, 2½ ft. base, 6 ins. high, W of cor.</p> <p>Cor. is located 2.5 lks. W of fence, bears N and S.</p> <p>Land, gently rolling. Soil, sandy, with limestone outcrops. Timber, juniper and palo-verde. Undergrowth, creosote.</p>	
10.00	<p>Draw, drains W.</p>	
39.90	<p>The ¼ sec. cor. of Secs. 1 and 2, monumented with a limestone, 20x9x4 ins., firmly set, projecting 6 ins. above the ground, mkd. ¼ on S face, with scattered mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ S 2 S 1 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p>	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>Cor. is located 10.5 lks. N of fence cor., fences extending S, W and E, 42.5 lks. to cor. of fences extending N, E and W.</p> <hr/> <p>N. 0°10' E., beginning new measurement.</p> <p>Over gently rolling land, through medium undergrowth.</p> <p>34.00 Draw, drains S. 75° W.</p> <p>40.10 Fence, bears W. and E, 36 lks. to cor. of fences extending E, S and W.</p> <p>40.56 The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., heretofore described.</p> <p>Land, medium rolling. Soil, sandy loam. Timber, mesquite and scattered juniper on ½ mile. Undergrowth, catclaw, sage and cacti.</p>
	<p>From the cor. of secs. 2, 3, 34 and 35, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°53' E., bet. secs. 34 and 35.</p> <p>Over rolling land, through scattering undergrowth and timber.</p> <p>2.12 Fence, bears S. 85° E. and N. 85° W.</p> <p>7.60 Small saddle, bears S. 20° E. and N. 20° W.</p> <p>19.79 Point for the S. 1/16 sec. cor. of secs. 34 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S 1/16 S34 S35 1975</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.</p> <p>Cor. is at the base of a spur, slopes southerly,</p> <p>38.70 Dirt Forest Service road, No. 119 A, bears N. 53° E. and S. 53° W.</p> <p>39.58 Point for the ¼ sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ S34 S35 1975</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.</p>
	<p>Cor. is 10 lks. W of a dirt road, bears N. 30° E. and S. 30° W.</p>
53.90	<p>Fence, bears S. 80° E. and N. 80° W.</p>
65.60	<p>Spur, slopes S. 80° E.</p>
77.97	<p>Point for the closing cor. of secs. 26 and 35, hereinafter described.</p>
79.16	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist. latitudinally and at record dist. longitudinally, 40.10 chs. dist. in easting, from the ¼ sec. cor. of secs. 27 and 34. There is no remaining evidence of the original cor. This cor. now functions as the cor. of secs. 27 and 34, only.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R4E $\frac{S}{S} \frac{27}{34} S 26$</p> <p>1975</p> </div> <p>Land, medium rolling. Soil, sandy loam, with limestone outcrops. Timber, scattered juniper and palo-verde. Undergrowth, creosote and cacti.</p>
23.60	<p>N. 0°28' E., bet. secs. 26 and 27.</p> <p>Over medium rolling land, through medium undergrowth.</p> <p>Unimproved dirt road, bears S. 75° E. and N. 75° W.</p>
38.81	<p>Point for the ¼ sec. cor. of sec. 26 only, at 40.00 chs. North Lat. from the closing cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 1 in. in the ground to bedrock, encircled by a mound of stone, 4½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R4E $\frac{1}{4} S 26$</p> <p>1975</p> </div>
39.58	<p>The ¼ sec. cor. of sec. 27 only, monumented with a reinforcement bar, ½ in. diam., projecting 12 ins. above the ground, mound of stone, 2 ft. base to top. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original corner position; not remonumented.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

N. 0°03' W., beginning new measurement.

Over medium rolling land, through scattering timber and medium undergrowth.

7.00 Draw, drains irregularly N.

28.00 Same draw, drains NW.

40.45 The cor. of Secs. 22, 23, 26 and 27, monumented with a limestone, 22x15x5 ins., no marks visible, encircled by a mound of stone, 2 ft. base, 1½ ft. high.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.

T15N R4E
S22|S23
S27|S26

1975

Raise a mound of stone, 2½ ft. base, 2 ft. high, W of cor.

Bury the unmkd. stone in base of mound.

Land, medium rolling.
Soil, sandy loam, with limestone outcrops.
Timber, scattered juniper and palo-verde.
Undergrowth, creosote, scrub oak, sage and cacti.

N. 0°51' E., bet. Secs. 22 and 23.

Over medium rolling land, through scattering timber and undergrowth.

15.00 Draw, drains SW curving to NW.

43.12 Point for the ¼ sec. cor. of Secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.

Set a brass tablet, 3½ ins. diam., 3½ in. stem in drill hole in a limestone outcrop, flush with the ground, with top mkd.

T15N R4E
¼
S22|S23
1975

from which

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>A juniper, 13 ins. diam., bears S. 79° E., 98 lks. dist., mkd. ¼ S23 BT.</p> <p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of cor.</p>
43.60	Jeep trail, bears S. 85° E. and N. 85° W.
47.90	Spur, slopes N. 55° W.
63.10	Draw, drains N. 80° W.
64.68	<p>Point for the N. 1/16 sec. cor. of Secs. 22 and 23.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E N 1/16 S22 S23 1975</p> <p>from which</p> <p>A juniper, 7 ins. diam., bears N. 31° E., 46 lks. dist., mkd. N 1/16 S23 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>
66.20	Spur, slopes N. 65° W.
85.20	Oak Creek, 150 lks. wide, course S. 60° W.
86.24	<p>The cor. of Secs. 14, 15, 22 and 23, monumented with an open end pipe, 1 in. diam., 30 ins. long, projecting 12 ins. above the ground. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S15 S14 S22 S23 1975</p> <p>from which</p> <p>A willow, 18 ins. diam., bears N. 66° E., 9.5 lks. dist., mkd. T15N R4E S14 BT.</p> <p>Reset the iron pipe alongside the iron post.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.

Land, medium rolling.
Soil, sandy loam, with limestone outcrops.
Timber, cotton wood, willows, mesquite and palo-verde.
Undergrowth, creosote.

From the cor. of Secs. 14 and 23, only.

N. 89°43' W., bet. Secs. 14 and 23.

Over rolling land, through scattering timber and undergrowth.

39.80 The $\frac{1}{2}$ sec. cor. of Secs. 14 and 23, monumented with a limestone, 16x12x6 ins., projecting 6 ins. above the ground, no marks visible, with a mound of stone, 4 ft. base, 1 ft. high, N of cor.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R4E

$\frac{1}{2}$ $\frac{S14}{S23}$

1975

from which

A juniper, 8 ins. diam., bears N. 76° E., 178.5 lks. dist., mkd. $\frac{1}{2}$ S14 BT.

Deposit the unmkd. stone alongside the iron post.

Rebuild mound of stone, 3½ ft. base, 2 ft. high, N of cor.

N. 88°45' W., beginning new measurement.

Over rolling land, through scattering timber and undergrowth.

20.35 Point for the W. 1/16 sec. cor. of Secs. 14 and 23.

Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.

T15N R4E

W 1/16 $\frac{S14}{S23}$

1975

22.70 Wash, 45 lks. wide, 5 ft. deep, drains S. 35° W.

25.90 Jeep trail, bears N. 40° E. and S. 40° W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS		
37.20	Oak Creek, 150 lks. wide, course S. 20° W.	
40.70	The cor. of Secs. 14, 15, 22 and 23.	
	Land, medium rolling. Soil, sandy loam, with limestone outcrops. Timber, cottonwood, cedar and willows. Undergrowth, creosote, mesquite, palo-verde and cacti.	
	N. 0°41' W., bet. Secs. 14 and 15.	
	Over creek bottom land, through dense undergrowth.	
3.50	Leave creek bottom land; thence over open land.	
10.50	Gravel road, bears N. 30° E. and S. 30° W., as scaled from U.S. Geological Survey Quadrangle Map, Cornville, Arizona 1968.	
19.715	Point for the S. 1/16 sec. cor. of Secs. 14 and 15.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground; with brass cap mkd.	
	T15N R4E S 1/16 S15 S14 1975	
	Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.	
21.80	Gravel road, bears S. 80° E. and N. 80° W., as scaled from U.S. Geological Survey Quadrangle Map, Cornville, Arizona 1968.	
23.50	Enter creek bottom land; thence through medium timber and undergrowth, bears S. 75° E. and N. 75° W.	
27.00	Oak Creek, 80 lks. wide, course S. 75° E.	
32.90	Leave creek bottom land, bears S. 65° E. and N. 65° W.; thence over rolling land.	
39.43	The ¼ sec. cor. of Secs. 14 and 15, monumented with an open end pipe, 1 in. diam., projecting 2½ ft. above the ground. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original corner position.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T15N R4E ¼ S15 S14 1975	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

Bury the open end pipe horizontally alongside the iron post.

Raise a mound of stone, 2 ft. base, 1½ ft. high, W of cor.

Cor. is located in cor. of fences, extending N, S. 30° E. and W.

N. 0°08' W., beginning new measurement.

Over rolling land, through scattering timber and undergrowth.

20.20 Fence, bears NE and SW, 31.5 lks. to cor. of fences extending NE, S and W.

21.90 Wash, 20 lks. wide, 3 ft. deep, drains S. 85° W.

26.60 Gravel road, bears N. 60° E. and S. 60° W.

31.20 Ridge, bears N. 40° E. and S. 40° W.; descend into creek bottom.

39.57 The cor. of secs. 10, 11, 14 and 15, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, mound of stone, 2 ft. base to top, with brass cap mkd.

T15N R4E	
S10	S11
S15	S14
1964	

Land, rolling.

Soil, sandy loam, with limestone outcrops.

Timber, juniper, mesquite and palo-verde.

Undergrowth, creosote, scrub oak and cacti.

From the cor. of secs. 11 and 14 only.

N. 89°49' W., bet. secs. 11 and 14.

Over rolling land, through scattering timber and undergrowth.

2.45 Fence, bears N. 5° E. and S. 5° W.

40.32 Point selected for the witness ¼ sec. cor. of secs. 11 and 14.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS		
	<p style="text-align: center;">W C</p> <p style="text-align: center;">T15N R4E</p> <p style="text-align: center;"> $\frac{1}{4}$ ← $\frac{S11}{S14}$ 1975 </p> <p>Raise a mound of stone, 3½ ft. base, 2 ft. high, N of cor.</p>	
40.62	<p>True point for the ¼ sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor. Cor. point falls on the E bank of a wash, 35 lks. wide, 2 to 8 ft. banks, drains S. 50° W.; impractical to monument.</p>	
72.60	<p>Gravel road, bears N. 10° E. and S. 10° W.</p>	
72.80	<p>Fence, bears N. 10° E. and S. 10° W.</p>	
77.10	<p>Ridge, bears N. 15° E. and S. 15° W.; descend W. slope into creek bottom.</p>	
81.24	<p>The cor. of secs. 10, 11, 14 and 15.</p> <p>Land, rolling. Soil, sandy, with limestone outcrops. Timber, cedar and palo-verde. Undergrowth, creosote, scrub oak and sage.</p>	
	<p>N. 0°27' E., bet. secs. 10 and 11.</p> <p>Over rolling land, through medium to scattering timber, and medium undergrowth.</p>	
10.00	<p>Draw, drains S. 60° W.</p>	
40.58	<p>The ¼ sec. cor. of secs. 10 and 11, monumented with a sandstone, 19x9x7 ins., firmly set, projecting 6 ins. above the ground, mkd. ¼ on W face.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E</p> <p style="text-align: center;"> $\frac{1}{4}$ S10 S11 1975 </p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. located on steep W slope.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	N. 0°20' E., beginning new measurement.
	Over gently rolling land, through scattering undergrowth.
15.60	Fence, bears S. 65° W. and N. 65° E., 19 lks. to cor. of fences extending northerly and S. 65° W.
17.30	Wash, 20 lks. wide, 6 ft. deep, drains S. 55° W.
19.36	Fence cor., bears W, 1.5 lks. dist., fences extend N and E.
19.40	Power line, bears N and E.
39.34	The cor. of Secs. 2, 3, 10 and 11, monumented by an iron post, 2½ ins. diam., projecting 4 ins. above the ground, with brass cap mkd.
	T15N R4E <u>S 3 S 2</u> <u>S10 S11</u> 1964
	Mound of stone, 2½ ft. base, 1 ft. high, W of cor.
	Land, rolling to gently rolling. Soil, sandy loam, with limestone outcrops. Timber, scattered mesquite. Undergrowth, creosote, sage and cacti.
	N. 0°07' E., bet. Secs. 2 and 3.
	Over gently rolling land, along E. side of powerline.
1.00	Intersection of paved Forest Service roads, No. 134, extends N and No. 119, extends S. 75° E. and N. 75° W.
20.005	Point for the S. 1/16 sec. cor. of Secs. 2 and 3, falls in the center of paved road; not monumented.
29.60	Leave paved road, bears S and N. 5° E.; thence through medium timber and undergrowth.
40.01	Point for the ¼ sec. cor. of Secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
40.20	Dirt road, bears E and W.
41.15	Gravel road, curves from E to N.
41.25	Powerline, bears S. 25° W. and N. 25° E. to powerline extending northerly.
80.37	The cor. of Secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 12 ins. above the ground, with brass cap mkd.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS		
	<p style="text-align: center;">T16N R4E $\frac{S34}{S3} \frac{S35}{S2}$ T15N 1938</p>	
	<p>Cor. is located 4.5 lks. W of N-S powerline.</p>	
	<p>Land, nearly level.</p>	
	<p>Soil, sandy loam.</p>	
	<p>Timber, cottonwood and mesquite.</p>	
	<p>Undergrowth, sage and cacti.</p>	
	<hr/> <p>From the cor. of Secs. 3, 4, 33 and 34, on the S bdy. of Tp., monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, mound of stone, 1½ ft. base to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T15N R4E $\frac{S33}{S4} \frac{S34}{S3}$ T14N 1964</p>	
	<p>N. 0°20' W., bet. Secs. 33 and 34.</p>	
	<p>Over rolling land, through medium undergrowth and scattering timber.</p>	
1.40	<p>Gravel road, bears E and W.</p>	
5.30	<p>Fence, bears E and W.</p>	
39.84	<p>The ¼ sec. cor. of Secs. 33 and 34, monumented with a 2 in. x 4 in. x 4 ft. wooden post, encircled by a mound of stone, 3 ft. base, 2 ft. high. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original corner position.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground; mound of stone, 4 ft. base to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T15N R4E $\frac{1}{4}$ $\frac{S33}{S3} \frac{S34}{S3}$ 1975</p>	
	<p>Bury the wooden post horizontally in base of mound.</p>	
	<hr/> <p>N. 0°48' E., beginning new measurement.</p>	
	<p>Over medium rolling land, through scattering timber and undergrowth.</p>	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
5.40	Ridge, bears N. 60° E. and S. 60° W.
20.00	Draw, drains irregularly SW.
40.00	Wash, 20 lks. wide, 6 ft. deep, drains S. 85° E.
40.60	Point selected for the witness sec. cor. of secs. 27, 28, 33 and 34.
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">W C T15N R4E S28 S27 S33 S34 1975</p>
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.
40.80	True point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist., falls in a wash, 15 lks. wide, 4 ft. deep, drains SE. There is no remaining evidence of the original cor.
	Land, rolling.
	Soil, sandy loam, with limestone outcrops.
	Timber, scattered juniper and palo verde.
	Undergrowth, creosote, catclaw and cacti.
	From the cor. of secs. 27 and 34 only.
	N. 88°26' W., bet. secs. 27 and 34.
	Over medium rolling land, through medium undergrowth.
1.20	Wash, 20 lks. wide, 3 ft. deep, drains southerly; ascend steep E slope.
6.10	End of ascent; thence over rolling land,
19.30	Fence, bears S. 10° E. and N. 10° W.
40.12	The ¼ sec. cor. of secs. 27 and 34, monumented with a limestone, 24 x 12 x 8 ins., in a mound of stone, 2 ft. base, 1 ft. high, mkd, with a faint 4.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., over an X mkd. on solid rock, mound of stone 5 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T15N R4E ¼ S27 S34 1975</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>Bury the mkd. stone in base of mound, alongside the iron post.</p> <hr/> <p>N. 88°03' W., beginning new measurement.</p> <p>Over rolling land, through scattered undergrowth.</p>
0.40	Wash in draw, 20 lks. wide, 2 ft. deep, drains S. 10° E.
34.95	Unimproved dirt road, bears S. 20° E. and N. 20° W.
35.05	Telephone line, bears S. 20° E. and N. 20° W.
40.23	The true pt. for the cor. of secs. 27, 28, 33 and 34.
	<p>Land, rolling. Soil, rocky. Timber, scattered palo verde, Undergrowth, creosote and cacti.</p>
	<p>N. 0°18' E., bet. secs. 27 and 28.</p> <p>Over rolling land, through medium undergrowth.</p>
15.70	Track road, bears E and W.
15.90	Telephone line, bears S. 16° E. and N. 16° W.
26.20	Unimproved dirt road, bears S. 53° E. and N. 53° W.
40.80	Point for the ¼ sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, 2½ ins diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E ¼ S28 S27 1975</p>
	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>
70.60	Spur, slopes N. 80° W.
81.60	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E S21 S22 S28 S27 1975</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor. Land, rolling. Soil, sandy loam. Timber, scattered cedar and palo verde. Undergrowth, creosote and cacti.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27. N. 87°07' W., bet. secs. 22 and 27. Over medium rolling land, through scattering timber and medium undergrowth.</p>
16.00	Draw, drains irregularly NW.
34.10	Fence, bears S. 30° E. and N. 30° W.
40.12	Point for the ¼ sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p>T15N R4E ¼ $\frac{S22}{S27}$ 1975</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
45.60	Spur, slopes N.
58.00	Draw, drains N.
65.10	Small spur, slopes N. 20° W.
80.24	The cor. of secs. 21, 22, 27 and 28. Land, rolling. Soil, rocky and sandy loam. Timber, scattered cedar and palo verde. Undergrowth, creosote, scrub oak and sage.
	<hr/> <p>N. 0°16' E., bet. secs. 21 and 22. Over rolling land, through medium undergrowth and scattering timber.</p>
29.10	Edge of bluff, bears N. 75° E. and S. 75° W.
36.70	Oak Creek, 120 lks. wide, course S. 80° W.
40.79	Point for the ¼ sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p style="text-align: center;">T15N R4E</p> <p style="text-align: center;"> $\frac{1}{4}$ S21 S22 1975 </p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located S. 16°30' W., 86.7 lks. dist., from the cor. of fences extending N, E and W.</p>
61.00	Draw, drains SE.
61.19	Point for the N 1/16 sec. cor. of secs. 21 and 22; not monumented.
81.59	The cor. of secs. 15, 16, 21 and 22, monumented with an iron post, 2½ ins. diam., projecting 10 ins. above the ground, mound of stone, 2 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T15N R4E</p> <p style="text-align: center;"> S16 S15 S21 S22 1964 </p> <p>Cor. is located 0.5 lks. W of fence, bears N. 1½° E. and S. 1½° W., 13 lks. to cor. of fences extending N. 1½° E., S. 1½° W. and Easterly.</p> <p>Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, scattered cedar and palo verde. Undergrowth, creosote, scrub oak and sage.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p> <p>S. 89°13' W., bet. secs. 15 and 22.</p> <p>Over rolling land, through medium timber and undergrowth.</p>
20.00	Gravel road, bears N. 8° E. and S. 8° W.
25.70	Oak Creek, 150 lks. wide, course N. 5° E.
37.20	Dirt road, bears S. 35° E. and N. 35° W.
40.83	The ¼ sec. cor. of secs. 15 and 22, monumented with a granite stone, 15 x 10 x 5 ins., firmly set, projecting 7 ins. above the ground, mkd. ¼ on E face.
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E</p> <p style="text-align: center;"> $\frac{1}{4}$ S15 S22 1975 </p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Deposit the mkd. stone alongside the iron post.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	N. 89°57' W., beginning new measurement.
	Over rolling land, through medium undergrowth.
16.70	Oak Creek, 120 lks. wide, course S. 25° W.
20.09	Point for the W. 1/16 sec. cor. of secs. 15 and 22.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T15N R4E W 1/16 $\frac{S15}{S22}$ 1975</p>
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
22.60	Unimproved dirt road, bears N and S.
36.20	Begin ascent over SE slope.
40.18	The cor. of secs. 15, 16, 21 and 22.
	Land, rolling.
	Soil, sandy loam.
	Timber, cedar, cottonwoods, willows and palo verde.
	Undergrowth, creosote, scrub oak, sage and cacti.
	N. 0°19' W., bet. secs. 15 and 16.
	Over rolling land, through scattering timber and undergrowth.
11.95	Power line, bears NE and SW.
19.745	Point for the S. 1/16 sec. cor. of secs. 15 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, mound of stone, 4 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T15N R4E S 1/16 S16 S15 1975</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located, N. 58°15' W., 69.5 lks. of the cor. of fences, extending E and S. 1½° W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS					
39.49	Point for the ¼ sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.				
42.00	Draw, drains E.				
67.70	Jeep trail on spur, bears S. 50° E. and N. 50° W.				
78.98	The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, with brass cap mkd.				
	<p style="text-align: center;">T15N R4E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S9</td> <td style="padding: 0 5px;">S10</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S16</td> <td style="padding: 0 5px;">S15</td> </tr> </table> <p style="text-align: center;">1964</p> <p>Mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p> <p>Land, medium rolling. Soil, sandy loam with limestone outcrops. Timber, scattered juniper and palo verde. Undergrowth, creosote, sage and cacti.</p>	S9	S10	S16	S15
S9	S10				
S16	S15				
	<hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°50' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p> <p>2.90 Oak Creek, 100 lks. wide, course S. 25° E.</p> <p>32.00 Fence, bears N. 8° E. and S. 8° W.</p> <p>32.60 Gravel road, bears N. 52° E. and S. 52° W.</p> <p>34.05 Power line, bears N. 35° E. and S. 35° W.</p>				
39.94	The ¼ sec. cor. of secs. 10 and 15, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.				
	<p style="text-align: center;">T15N R4E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">¼</td> <td style="border-right: 1px solid black; padding: 0 5px;">S10</td> <td style="padding: 0 5px;">S15</td> </tr> </table> <p style="text-align: center;">1964</p> <p>Mound of stone, 2½ ft. base, 1 ft. high, N of cor.</p> <p>Cor. located 5 lks. W of cor. of fences extending N and E.</p>	¼	S10	S15	
¼	S10	S15			
	<hr/> <p>S. 89°23' W., beginning new measurement.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>				

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
7.20	Oak Creek, 60 lks. wide, course N. 27° E., from S. 10° W.
19.80	Oak Creek, 140 lks. wide, course SW.
28.40	Private road, bears S. 35° E. and N. 35° W.
31.70	Gravel road, bears N and S.
40.94	The cor. of secs. 9, 10, 15 and 16.
	<p>Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, scattered mesquite and palo verde. Undergrowth, creosote and sage.</p>
	N. 0°53' E., bet. secs. 9 and 10.
	Ascend over S slope, through scattering timber and medium undergrowth.
1.70	Spur, slopes S. 70° E.
3.50	Wash in draw, drains Easterly.
7.00	Spur, slopes S. 55° E.
17.70	Wash, 20 lks. wide, 4 ft. deep, drains Easterly.
20.13	Point for the S. 1/16 sec. cor. of secs. 9 and 10.
	Set a basalt stone, 10 x 8 x 4 ins., 8 ins. below the surface of a gravel road, mkd. X at the exact cor. point.
	from which
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 45° E., 83.3 lks. dist., with brass cap mkd. T15N R4E S 1/16 S10 55 ft. RM 1975 and an arrow pointing to the cor.</p>
	<p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° W., 83.3 lks. dist., with brass cap mkd. T15N R4E S 1/16 S9 55 ft. RM 1975 and an arrow pointing to the cor.</p>
	<p>A power pole, bears N. 23¼° W., 75 lks. dist., with aluminum tag mkd. PS 138078. This is the beginning of power line extending North.</p>
	<p>Cor. is located in the center of a gravel road, North 40 lks. to the beginning of asphalt and South 320 lks. to a curve, thence S. 20° E.</p>
40.26	<p>The ¼ sec. cor. of secs. 9 and 10, monumented with a limestone, 20 x 8 x 9 ins., 6 ins. below the surface of paved road, mkd. ¼ on S face and an X on top. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original corner position.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 24 ins. in the ground, for a reference monument, bears East, 39.4 lks. dist., mound of stone, 1½ ft. base to top, with brass cap mkd. T15N R4E ¼ S10 26 ft. RM 1975 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears West, 39.4 lks. dist., mound of stone, 1½ ft. base to top, with brass cap mkd. T15N R4E ¼ S9 26 ft. RM 1975 and an arrow pointing to the cor.</p>
	<p>N. 0°47' E., beginning new measurement.</p>
	<p>Over paved road.</p>
40.32	<p>The cor. of secs. 3, 4, 9 and 10, monumented with an iron pipe, 1 ¾ ins. diam., flush with the surface of paved road bearing N and S and on S side of E-W road.</p> <p>This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent land owners, and is accepted as the best available evidence of the original corner position; not remonumented.</p> <p>Land, rolling to nearly level. Soil, sandy and rocky. Timber, mesquite and palo verde. Undergrowth, creosote.</p>
	<p>From the cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 89°24' W., bet. secs. 3 and 10.</p>
	<p>Over gently rolling land, through scattering timber and medium undergrowth, along a telephone line bearing W from S.</p>
19.99	<p>Point for the E. 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E E 1/16 $\frac{S3}{S10}$ 1975</p>
	<p>from which</p> <p>A reinforcement bar, ½ in. diam., projecting 2 ins. above the ground, bears N. 89°24' W., 23.3 lks. dist.</p> <p>The cor. of fences, bears S. 53° W., 28 lks. dist., fences extending N, E and W.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Cor. is located 35 lks. N of a telephone line, bearing irregularly E and W.
35.50	Gravel road, bears N and S.
39.98	The 1/4 sec. cor. of secs. 3 and 10, monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.
	T15N R4E 1/4 S3 S10 1964
	Mound of stone, 3 ft. base, 1 ft. high, N of cor.
	S. 89°34' W., beginning new measurement.
	Over gently rolling land, through scattering timber and undergrowth.
14.00	Oak Creek, 240 lks. wide, course S. 25° E.
20.125	Point for the W. 1/16 sec. cor. of secs. 3 and 10.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E W 1/16 S3 S10 1975
	Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, N of cor.
	Cor. is located 47 lks. N of combination telephone and power line, bearing E and W.
40.25	The cor. of secs. 3, 4, 9 and 10.
	Land, gently rolling. Soil, sandy loam. Timber, cottonwoods along the river, with scattered mesquite throughout. Undergrowth, catclaw, creosote and sage.
	N. 0°08' W., bet. secs. 3 and 4.
	Over gently rolling land, through medium timber and undergrowth.
0.34	Paved Forest Service road, No. 119, bears E and W.
20.11	Point for the S. 1/16 sec. cor. of secs. 3 and 4; not monumented.
	Cor. point is located 2 lks. E of the cor. of fences extending W and N. 15° W.
20.60	Irrigation ditch, flows S. 30° E.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
40.22	Point for the $\frac{1}{2}$ sec. cor. of secs. 3 and 4, at proportionate dist.; cor. falls in Oak Creek; not monumented.
41.50	Oak Creek, 270 lks. wide course, S. 65° E.
68.00	Gravel road, bears SE and NW.
80.60	True point for the cor. of secs. 3, 4, 33 and 34, on the N. bdy. of the Tp., heretofore described.
	<p>Land, gently rolling. Soil, sandy loam. Timber, cottonwood and mesquite. Undergrowth, creosote and cacti.</p>
	<p>From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, $2\frac{1}{2}$ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E S32 S33 S5 S4 T14N 1964</p>
	<p>Mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p>
	<p>N. $0^{\circ}12'$ W., bet. secs. 32 and 33.</p>
	<p>Over rolling land, through medium timber and undergrowth.</p>
17.10	Begin descent over NW slope into draw.
20.33	Point for the S. $\frac{1}{16}$ sec. cor. of secs. 32 and 33, falls on a limestone outcrop.
	<p>Set a brass tablet, $3\frac{1}{2}$ ins. diam., $3\frac{1}{2}$ ins. stem, in a drill hole in outcrop, with top mkd.</p>
	<p style="text-align: center;">T15N R4E S $\frac{1}{16}$ S32 S33 1975</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>
23.10	Draw, drains NE; ascend SE slope.
30.00	Spur, slopes S. 80° E.
40.66	Point for the $\frac{1}{4}$ sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E $\frac{1}{4}$ S32 S33 1975</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Raise a mound of stone, 3½ ft. base, 2 ft. high, W of cor.
42.50	Draw, drains E.
44.30	Spur, slopes S. 55° E.
51.00	Draw, drains N. 80° E.
53.50	Spur, slopes S. 50° E.
55.90	Descend bluff, bears S. 25° E. and N. 25° W.; thence over river bottom land.
60.99	Point for the N. 1/16 sec. cor. of secs. 32 and 33.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T15N R4E N 1/16 S32 S33 1975
	from which
	A juniper, 5 ins. diam., bears N. 79°40' W., 74.5 lks. dist., mkd. N 1/16 S32 BT.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W of cor.
61.60	Right bank of Verde River, 2 to 3 ft. banks, bears S. 20° E. and N. 20° W.
63.10	Left bank of Verde River.
81.32	Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E S29 S28 S32 S33 1975
	from which
	An ash, 4 ins. diam., bears N. 23 3/4° W., 142 lks. dist., mkd. X at breast height and BT at base.
	Deposit broken glass at base of iron post.
	Land, medium rolling to river bottom. Soil, sandy loam, with limestone outcrops. Timber, cedar, cottonwood, mesquite, palo verde and ash. Undergrowth, creosote, catclaw, sage and arrow weed.
	From the cor. of secs. 27, 28, 33 and 34.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS		
	N. 88°45' W., bet. secs. 28 and 33. Over rolling land, through medium undergrowth.	
27.00	Draw, drains S. 15° W.	
40.22	Point for the ¼ sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd. T15N R4E. ¼ $\frac{S28}{S33}$ 1975	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.	
41.30	Draw, drains N. 15° W.	
48.20	Descend W slope.	
60.33	Point for the W. 1/16 sec. cor. of secs. 28 and 33. Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd. T15N R4E W 1/16 $\frac{S28}{S33}$ 1975	
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.	
61.90	Power line, bears S. 20° E. and N. 20° W.	
66.90	Jeep trail, bears N. 25° E. and S. 25° W.	
71.00	Fence, bears N. 2° E. and S. 2° W.	
73.70	OK Ditch, 20 lks. wide, flows S. 3° E.	
80.44	The cor. of secs. 28, 29, 32 and 33. Land, rolling to river bottom. Soil, sandy. Timber, cottonwood and palo verde. Undergrowth, creosote, and arrow weed.	
	N. 0°29' E., bet. secs. 28 and 29. Over river bottom land, through medium timber and dense undergrowth.	
4.00	Left bank of Verde River, 6 to 10 ft. banks, bears S. 15° W. from N; thence along left bank.	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS		
28.00	Power line, bears S. 65° E. and N. 65° W., approx. 2 chs. to intersection of power line which bears S. 10° E. and N. 10° W.	
30.70	Left bank of Verde River, banks 2 to 3 ft. high, bears NE and SW, 30 lks., curving Southerly.	
31.90	Right bank of Verde River, bears NE and SW, 90 lks., curving Southerly.	
40.66	<p>Point for the $\frac{1}{4}$ sec. cor. of secs. 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E $\frac{1}{4}$ S29 S28 1975</p> <p>Raise a mound of stone, 2 ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p>	
46.10	Wash, 30 lks. wide, 3 ft. deep, drains S. 60° E.	
46.50	Jeep trail, bears S. 50° E. and N. 50° W.	
81.32	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S20 S21 S29 S28 1975</p> <p>Raise a mound of stone, $2\frac{1}{2}$ ft. base, $1\frac{1}{2}$ ft. high, W of cor.</p> <p>Land, river bottom. Soil, sandy loam and rocky. Timber, mesquite and cottonwood. Undergrowth, arrow weed and catclaw.</p>	
18.00	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 88°58' W., bet. secs. 21 and 28.</p> <p>Over medium rolling land, through medium undergrowth.</p> <p>Jeep trail, bears S. 13° E. and N. 13° W.; telephone line, bears S. 16° E. and N. 16° W.</p>	
40.08	Point for the $\frac{1}{4}$ sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ $\frac{S21}{S28}$ 1975</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.</p>
69.50	Bluff, bears N and S; descend into river bottom.
75.00	Left bank of Verde River, 2 to 3 ft. banks, bear N. 8° E. and S. 8° W.
76.50	Right bank of Verde River.
80.16	The cor. of secs. 20, 21, 28 and 29.
	<p>Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, cedar and palo verde. Undergrowth, creosote, scrub oak and sage.</p> <hr/> <p>N. 0°25' W., bet. secs. 20 and 21.</p> <p>Over river and creek bottom land, through scattering timber and medium undergrowth.</p>
5.40	Right bank of Verde River, banks 3 to 6 ft. high, bears S. 60° E. and N. 60° W.
6.60	Left bank of Verde River.
20.33	Point for the S. 1/16 sec. cor. of secs. 20 and 21.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S 1/16 S20 S21 1975</p> <p>from which</p> <p style="text-align: center;">A mesquite, 4 ins. diam., bears N. 69° W., 225 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Set a juniper post, 8 ft. long, 4 ins. diam., 2 ft. in the ground, alongside the cor.</p>
33.00	Oak Creek, 40 lks. wide, course S. 60° W.
34.80	Limestone cliff, 20 ft. high, bears S. 75° E. and S. 50° W.
35.20	Beginning of fence, bearing Northerly.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
40.66	<p>The $\frac{1}{4}$ sec. cor. of secs. 20 and 21, monumented with a basalt stone, 16 x 8 x 6 ins., projecting 8 ins. above the ground, mkd. $\frac{1}{4}$ on E face, encircle by a mound of stone, 3 ft. base.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E $\frac{1}{4}$ S20 S21 1975</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>The cor. is located at the cor. of fences, extending N, E and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. $0^{\circ}19'$ E., beginning new measurement.</p> <p>Over medium rolling land, through scattering undergrowth.</p>
9.60	Fence line ends.
11.10	Gravel road, bears S. 75° E. and S. 75° W.
12.60	Wash, 30 lks. wide, 4 ft. deep, drains N. 25° E.
20.20	Telephone line, bears SE and NW.
21.00	Power line, bears E and W.
39.90	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a sandstone, 32 x 11 x 10 ins., firmly set, projecting 14 ins. above the ground, mkd. with 4 notches on E and 3 notches on S edges, mound of stone, 3 ft. base, 2 ft. high, S of cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone, $2\frac{1}{2}$ ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S17 S16 S20 S21 1975</p> <p>Bury the mkd. stone alongside the iron post.</p> <p>Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, cedar, sycamore, palo verde and mesquite. Undergrowth, creosote and cacti.</p> <hr style="width: 50%; margin: 10px auto;"/>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>N. 0°18' E., bet. secs. 16 and 17.</p>
	<p>Over medium rolling land, through medium timber and scattering undergrowth.</p>
10.60	<p>Ridge, bears N. 65° E. and S. 65° W.</p>
39.84	<p>The ¼ sec. cor. of secs. 16 and 17, monumented with a sandstone, 8 x 8 x 5 ins., firmly set, projecting 4 ins. above the ground, mkd. ¼ on S face, with a mound of stone, 2 ft. base, 2 ft. high, E of cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E</p>
	<p style="text-align: center;"> ¼</p>
	<p style="text-align: center;">S17 S16</p>
	<p style="text-align: center;">1975</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Raise a mound of stone, 2 ft. base, 2 ft. high, W of cor.</p>
	<p>Note.—This cor. was deteriorating badly and was monumented to perpetuate the cor. position.</p>
	<p>N. 0°19' E., beginning new measurement.</p>
	<p>Over gently rolling land, through scattering timber and undergrowth.</p>
2.50	<p>Small spur, slopes S. 65° W.</p>
16.50	<p>Jeep trail, bears N. 80° E. and S. 80° W.</p>
39.88	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron post, 2½ ins. diam., projecting 5 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E</p>
	<p style="text-align: center;"> S 8 S 9</p>
	<p style="text-align: center;">S17 S16</p>
	<p style="text-align: center;">1964</p>
	<p>Mound of stone, 2 ft. base, 1 ft. high, W of cor.</p>
	<p>Land, medium rolling to gently rolling.</p>
	<p>Soil, sandy loam.</p>
	<p>Timber, cedar and palo verde.</p>
	<p>Undergrowth, creosote, sage and cacti.</p>
	<p>From the cor. of secs. 9, 10, 15 and 16.</p>
	<p>N. 89°04' W., bet. secs. 9 and 16.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Ascending along S slope, through scattering timber and undergrowth.
15.90	Ridge, bears N and S.
20.395	Point for the E. 1/16 sec. cor. of secs. 9 and 16.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E
	E 1/16 $\frac{S\ 9}{S16}$
	1975
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Cor. is located 48 lks. N of a fenceline, bears E and W.
38.96	Fence, bears N. 35° W. and S. 35° E., 8 lks. to the cor. of fences extending Easterly and N. 35° W.
39.74	Jeep trail, bears SE and NW.
40.79	The ¼ sec. cor. of secs. 9 and 16, monumented with a wooden stake, 20 ins. long, 1 in. square, projecting 8 ins. above the ground, mkd. with a scribed 4 and a sandstone, 14 x 9 x 5 ins., lying alongside the stake, no marks on stone. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original corner position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E
	¼ $\frac{S\ 9}{S16}$
	1975
	Deposit the wooden stake and stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located 32 lks. S of a jeep trail, bears S. 80° E. and N. 80° W.
	N. 89°18' W., beginning new measurement.
	Over gently rolling land, through scattering timber and undergrowth.
8.10	Wash, 5 lks. wide, 2 ft. deep, drains Southerly.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
11.30	Ridge, bears N. 5° E. and S. 5° W.
23.10	Wash, 10 lks. wide, 3 ft. deep, drains S. 35° W.
29.80	Ridge, bears N. 20° E. and S. 20° W.
38.95	The cor. of secs. 8, 9, 16 and 17.
	Land, rolling to gently rolling. Soil, sandy loam and rocky. Timber, juniper. Undergrowth, scrub oak, creosote, sage and cacti.
	N. 0°18' W., bet. secs. 8 and 9.
	Over gently rolling land, through scattering timber and undergrowth.
2.10	Fence, bears E and W.
3.20	Ridge, bears N. 50° E. and S. 50° W.
39.91	Point for the ½ sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E ½ S 8 S 9 1975
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
67.20	Unimproved dirt road, bears S. 85° E. and N. 85° W.
79.82	The cor. of secs. 4, 5, 8 and 9, monumented with a mound of stone, 1½ ft. base, 10 ins. high. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners and is accepted as the best available evidence of the original corner position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T15N R4E S 5 S 4 S 8 S 9 1975
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	Cor. is located 2 lks. S of power line, bears E and W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, juniper and palo verde. Undergrowth, creosote, scrub oak, sage and cacti.</p>
	<p>From the cor. of secs. 3, 4, 9 and 10. N. 89°43' W., bet. secs. 4 and 9. Along S side of paved Forest Service road, No. 119, and power line.</p>
10.50	Paved Forest Service road, No. 119, curves NW.
20.09	Point for the E. 1/16 sec. cor. of secs. 4 and 9. Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in the ground, with brass cap mkd.
	<p>T15N R4E E 1/16 $\frac{S \cdot 4}{S \ 9}$ 1975</p>
	from which
	<p>A power pole, bears NE, 2 lks. dist., No. PS32778. A reinforcement bar, 3/8 in. diam., projecting 4 ins. above ground, bears West, 2 lks. dist. A fence cor., bears SW, 2 lks. dist., fences extend N, irregularly E and W.</p>
	Ascend steep E slope.
26.30	End of ascent, bears N. 15° E. and S. 15° W.; thence over mesa.
27.80	Jeep trail, bears N and S.
28.80	Descend W slope.
40.18	The ¼ sec. cor. of secs. 4 and 9, monumented with an iron post, 2½ ins. diam., projecting 4 ins. above the ground, with brass cap mkd.
	<p>T15N R4E ¼ $\frac{S \ 4}{S \ 9}$ 1964</p>
	<p>Mound of stone, 3½ ft. base, 2 ft. high, N of cor. Cor. is located 1 lk. S of power line, bears E and W.</p>
	<p>_____</p>
	N. 89°45' W., beginning new measurement.
	Over medium rolling land, through scattering undergrowth.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
30.00	Ridge, bears N and S.
30.60	Unimproved dirt road, bears N. 10° E. and S. 10° W.
40.29	The cor. of secs. 4, 5, 8 and 9.
	Land, rolling to medium rolling. Soil, sandy loam. Timber, cedar and mesquite. Undergrowth, oak brush, creosote and cacti.
	N. 0°18' W., bet. secs. 4 and 5.
	Over gently rolling land, through scattering timber and undergrowth.
17.40	Unimproved dirt road, bears S. 35° E. and N. 35° W.
19.40	Paved Forest Service road, No. 119, bears E and W.
40.11	The ¼ sec. cor. of secs. 4 and 5, monumented with an open end pipe, 2 ins. diam., firmly set, projecting 2 ins. above the ground, encircled by a mound of stone, 1½ ft. base. Accepted as the best available evidence of the original corner position.
	At the corner point
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.
	<p>T15N R4E ¼ S 5 S 4 1975</p>
	Reset the open end pipe alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
	N. 0°18' W., beginning new measurement.
	Over gently rolling land, through scattering timber and undergrowth.
40.19	The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 5 ins. above the ground, with brass cap mkd.
	<p>T16N R4E S32 S33 S 5 S 4 T15N 1938</p>
	Mound of stone, 3 ft. base, 1 ft. high, NW of cor.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Land, rolling. Soil, sandy and rocky. Timber, juniper and palo verde. Undergrowth, catclaw and cacti.</p> <hr/> <p>From the cor. of secs. 28, 29, 32 and 33. N. 88°27' W., bet. secs. 29 and 32. Over river bottom land, through scattering timber and dense undergrowth.</p>
1.15	Left bank of Verde River, 6 to 10 ft. banks, bear N. 15° E. and S. 15° W.
2:65	Right bank of Verde River; ascend steep E slope.
9.70	End of ascent, bears N and S; thence over rolling land, through scattering timber and medium undergrowth.
24.30	Spur, slopes N. 40° E.
30.00	Unimproved dirt road, bears N. 50° E. and S. 50° W.
40.13	<p>Point for the ¼ sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ $\frac{S29}{S32}$ 1975</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.</p>
80.26	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2½ ins. diam., projecting 5 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S30 S29 S31 S32 1964</p> <p>Mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>Land, rolling. Soil, sandy and rocky. Timber, cottonwoods along river, scattered palo verde and mesquite. Undergrowth, catclaw, cacti and arrow weed.</p> <hr/> <p>From the cor. of secs. 20, 21, 28 and 29. N. 88°43' W., bet. secs. 20 and 29.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Over river bottom land, through medium undergrowth.
6.70	Leave river bottom land, bears S. 20° E. and N. 20° W.; thence over rolling land, through scattering timber and undergrowth.
9.30	Fence, bears S and N, 157 lks. to cor. of fences extending E, S and W.
10.90	Jeep trail, bears S. 40° W. and N. 40° E., 210 lks. to curve; thence N. 40° W.
24.30	Power line, bears S. 30° E. and N. 30° W.
28.90	Wash, 10 lks. wide, 3 ft. deep, drains N. 25° E.
32.40	Fence, bears S. 33° W. and N. 33° E., 142 lks. to cor. of fences extending E and S. 33° W.
33.20	Bluff, bears N. 40° E. and S. 40° W.; descend into river bottom.
37.10	Right bank of Verde River, 2 to 3 ft. banks, bears N. 30° E. and S. 30° W.
38.20	Left bank of Verde River, bears N. 10° E. and S. 10° W.
40.08	Point for the ¼ sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.; not monumented.
59.80	Left bank of Verde River, 2 to 3 ft. banks, bear S. 30° E. and N. 30° W.
60.12	Point for the W. 1/16 sec. cor. of secs. 20 and 29, falls in Verde River, impracticable to establish a monument.
61.20	Right bank of Verde River; ascend vertical cliff, 50 ft. high, bears S. 30° E. and N. 30° W.
61.35	Top of cliff; ascend steep NE slope.
61.72	Point selected for the witness W. 1/16 sec. cor. of secs. 20 and 29. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, mound of stone, 5 ft. base to top, with brass cap mkd.
	W C T15N R4E W 1/16 $\frac{S20}{S29}$ 1975
64.30	End of steep ascent; thence over rolling and broken land.
64.60	Spur, slopes N. 30° E.
73.90	Wash, 15 lks. wide, 5 ft. deep, drains N. 15° W., curving Northerly.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15. N., R. 4. E., G&SRM, Arizona

CHAINS	
74.60	Fence, bears N. 50° E. and S. 50° W.
80.16	<p>The cor. of secs. 19, 20, 29 and 30, monumented by a copperweld, ½ in. diam., projecting 8 ins. above solid limestone, with top mkd. CV-28 A H D. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners and is accepted as the best available evidence of the original corner position.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over copperweld, on solid limestone, mound of stone, 3½ ft. base to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R4E $\frac{S19}{S30} \frac{S20}{S29}$ 1975</p> </div> <p>Cor. is located on edge of a 40 ft. cliff, bears irregularly E and W.</p> <p>Land, river bottom to medium rolling. Soil, sandy loam, with limestone outcrops. Timber, mesquite and cottonwood. Undergrowth, creosote and catclaw.</p>
	N. 89°56' W. bet. secs. 19 and 30.
	Over rolling land, through medium timber and undergrowth.
4.00	Wash, in canyon, 20 lks. wide, 5 ft. deep, drains N. 85° E.
8.00	Spur, slopes S.
25.00	Ridge, bears NE and SW.
40.05	Wash, 110 lks. wide, 4 ft. deep, drains N. 20° W.
40.65	Point for the ¼ sec. cor. of secs. 19 and 30, at proportionate dist., falls on edge of W bank of wash; there is no remaining evidence of the original cor.
40.75	<p>Point selected for the witness ¼ sec. cor. of secs. 19 and 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>W C T15N R4E $\frac{1}{4} \frac{S19}{S30} \rightarrow$ 1975</p> </div>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15. N., R. 4. E., G&SRM, Arizona

CHAINS	
64.30	Trail road, bears S. 5° E. and N. 5° W.
66.55	Fence, bears S. 15° E. and N. 15° W.
68.15	Paved State Highway, No. 279, bears S. 15° E. and N. 15° W.
69.65	Fence, bears S. 15° E. and N. 15° W.
75.50	Trail road, bears S. 25° E. and N. 25° W.
80.18	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., 13 ins. above the ground, with brass cap mkd.
	<p style="text-align: center;">T15N R4E $\frac{S24}{S25} \frac{S19}{S30}$ R3E 1917</p>
	Remark the brass cap to read
	<p style="text-align: center;">T15N R3E R4E $\frac{S24}{S25} \frac{S19}{S30}$ 1975 1917</p>
	Mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	<p>Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, cedar and palo verde. Undergrowth, creosote and cacti.</p>
	From the cor. of secs. 19, 20, 29 and 30.
	N. 0°08' E., bet. secs. 19 and 20.
	Over medium rolling land, through scattering timber and undergrowth.
0.50	Wash, in canyon, 20 lks. wide, 5 ft. deep, drains N. 85° E.
8.10	Spur, slopes S.
33.80	Fence, bears S. 60° E. and N. 60° W.
38.85	Point selected for the witness ¼ sec. cor. of secs. 19 and 20.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">W C T15N R4E $\frac{1}{4}$ \uparrow $\frac{S19}{S20}$ 1975</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>from which</p> <p>A willow, 10 ins. diam., bears S. 65° W., 7.5 lks. dist., mkd. X BT at base.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p>
39.00	Right bank of Verde River, 6 to 8 ft. banks, bears SE and NW.
39.95	Point for the ¼ sec. cor. of secs. 19 and 20, at proportionate dist., falls in the Verde River; there is no remaining evidence of the original cor.
41.00	Left bank of Verde River.
59.30	Graded dirt road, bears N. 50° E. and S. 50° W.
59.50	Power line, bears N, E and W; thence along the side of dirt road and power line.
59.925	<p>Point for the N. 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E N 1/16 S19 S20 1975</p>
	<p>from which</p> <p>A power pole, bears S. 51½° W., 75.5 lks. dist., with aluminum tag, mkd. PS30546.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.</p> <p>Cor. is located at the cor. of fences extending N and W.</p> <p>From this point, a reinforcement bar, ½ in. diam., projecting 3 ins. above the ground, bears S. 57°51' W., 4 lks. dist.</p>
78.80	Graded dirt road, bears E and W.
79.90	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2½ ins. diam., projecting 6 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S18 S17 S19 S20 1964</p> <p>Mound of stone, 2 ft. base, 1½ ft. high, W of cor.</p> <p>Cor. is located at the cor. of fences extending N, E and S.</p> <p>Land, rolling to gently rolling.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Soil, sandy loam, with limestone outcrops. Timber, cottonwood and willows in river bottom. Undergrowth, creosote and catclaw.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°12' W., bet. secs. 17 and 20.</p> <p>Descend over rolling land, through scattering timber and medium undergrowth.</p>
8.50	Wash, in draw, drains S. 40° W.
14.70	Wash, in draw, drains SW; thence over nearly level land, through dense creosote.
17.90	Telephone line, bears S. 30° E. and N. 30° W.
20.10	Fence, bears Easterly and Westerly.
20.90	Jeep trail, bears N. 20° E. and S. 25° W.
39.95	The ¼ sec. cor. of secs. 17 and 20, monumented by an iron post, 2½ ins. diam., projecting 3 ins. above the ground, with brass cap mkd.
	<p>T15N R4E ¼ <u>S17</u> S20 1964</p>
	<p>Mound of stone, 2 ft. base, 1 ft. high, N of cor. Cor. is located 2 lks. S of E and W fenceline.</p> <hr/> <p>N. 89°11' W., beginning new measurement.</p> <p>Over nearly level land, through scattering timber and dense undergrowth.</p>
1.60	Wash, 30 lks. wide, 6 ft. deep, drains S. 15° E.
19.96	The W. 1/16 sec. cor. of secs. 17 and 20, monumented with an iron pipe, ½ in. diam., 12 ins. long, set flush with the ground.
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p>T15N R4E W 1/16 <u>S17</u> S20 1975</p>
	<p>Reset the iron pipe alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor. Cor. is located 1.5 lks. N of fence, bears E and W.</p>

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
25.00	Gravel road, bears N and S.
39.92	The cor. of secs. 17, 18, 19 and 20. Land, rolling to gently rolling. Soil, sandy loam. Timber, mesquite and cedar. Undergrowth, creosote and catclaw.
	(Restoring the resurvey executed by Boyd S. Owens in 1965)
	From the E. 1/16 sec. cor. of secs. 18 and 19, monumented with an iron post, 2½ ins. diam., projecting 8 ins. above the ground, with brass cap mkd.
	$E \frac{1}{16} \frac{S18}{S19}$ 1965
	Mound of stone, 2 ft. base, 1½ ft. high, N of cor. N. 89°58' W., bet. secs. 18 and 19. Descend gradually over nearly level land, through scattering timber.
17.40	Fence, bears N and S.
17.485	Point selected for the witness ¼ sec. cor. of secs. 18 and 19. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	$W C$ $T15N R4E$ $\frac{1}{4} \leftarrow \frac{S18}{S19}$ 1975
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N of cor. From this point, a reinforcement bar, ½ in. diam., projecting 5 ins. above the ground, bears S. 35°32' E., 1.7 lks. dist.
19.00	Left bank of Verde River, 3 to 5 ft. banks, bear S. 5° E. and N. 5° W.
20.385	True point for the ¼ sec. cor. of secs. 18 and 19, determined from a bearing tree A cottonwood, 42 ins. diam., bears S. 39°15' E., 325 lks. dist., with an open blaze, no scribe marks visible. True cor. point is located 115 lks. E of right bank of Verde River, bears N and S.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>From the S. 1/16 sec. cor. of secs. 17 and 18, monumented with an iron post, 2½ ins. diam., 5 ins. below the ground, with brass cap mkd.</p> <p style="text-align: center;">S 1/16 S18 S17 1965</p> <p>Reset the iron post, with 8 ins. projecting above the ground. Add the mks. 1975 to the brass cap.</p> <p>Raise a mound of stone, 2½ ft. base, 10 ins. high, W of cor.</p> <p>North, bet. secs. 17 and 18.</p> <p>Over open river bottom land.</p>
6.10	Enter busy gravel pit area.
19.83	<p>Point for the ¼ sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the cor. set during the 1965 survey.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ S18 S17 1975</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
21.70	Right bank of the Verde River, 3 to 6 ft. banks, bear S. 60° E. and N. 60° W.
23.20	Left bank of the Verde River; leave river bottom land, over rolling land, through medium undergrowth.
29.40	Knoll.
39.66	<p>Point for the N. 1/16 sec. cor. of secs. 17 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E N 1/16 S18 S17 1975</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p>
59.49	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2½ ins. diam., projecting 11 ins. above the ground, with brass cap mkd.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	T15N R4E $\frac{S\ 7}{S\ 18} \frac{S\ 8}{S\ 17}$ 1964
	Mound of stone, 2½ ft. base, 1½ ft. high, W of cor. Land, river bottom to rolling. Soil, sandy loam and rocky. Timber, cottonwood and palo verde. Undergrowth, creosote and catclaw.
	(Restoring the survey executed by C. Burton Foster in 1877)
	From the cor. of secs. 8, 9, 16 and 17. N. 89°26' W., bet. secs. 8 and 17. Over rolling land, through scattering timber and undergrowth.
3.20	Spur, slopes S. 80° W.
11.00	Fence, bears N. 10° E. and S. 10° W.
11.60	Dirt road, bears N. 30° E. and S. 5° W.
11.90	Fence, bears N and S.
15.20	Ridge, bears N. 5° E. and S. 5° W.
27.10	Dirt road, bears N. 25° E. and S. 25° W.
38.40	Ridge, bears N. 3° E. and S. 3° W.
40.20	The ¼ sec. cor. of secs. 8 and 17, monumented with an iron post, 2½ ins. diam.; projecting 8 ins. above the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
	T15N R4E $\frac{1}{4} \frac{S\ 8}{S\ 17}$ 1964
	N. 89°28' W., beginning new measurement. Over rolling land, through scattering timber and medium undergrowth.
7.50	Shallow wash, drains S. 25° W.
14.60	Telephone line, bears S. 25° E. and N. 25° W.
18.50	Graded road, bears S. 28° E. and N. 28° W.
20.04	Point for the W. 1/16 sec. cor. of secs. 8 and 17.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E W 1/16 $\frac{S}{S17}$ 1975</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
26.10	Ridge, bears N. and S.
32.10	Draw, drains S. 50° W.
35.70	Spur, slopes Westerly.
38.70	Wash, in draw, drains Southerly.
40.08	The cor. of secs. 7, 8, 17 and 18.
	<p>Land, gently rolling to rolling. Soil, sandy loam. Timber, juniper, palo verde and mesquite. Undergrowth, creosote, sage, and cacti.</p>
	<p>(Restoring the resurvey executed by Boyd S. Owens in 1965)</p>
	<p style="text-align: center;">_____</p> <p>N. 89°44' W., bet. secs. 7 and 18.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>
3.70	Dirt road, on ridge, bears N and S.
17.40	Spur, slopes S. 35° W.
20.51	The E. 1/16 sec. cor. of secs. 7 and 18, monumented with a reinforcement bar, ½ in. diam., projecting 2 ins. above the ground.
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E E 1/16 $\frac{S}{S18}$ 1974</p>
	<p>Deposit the reinforcement bar inside the iron post.</p>
21.80	Draw, drains SW.
28.00	Wash, 15 lks. wide, 2 ft. deep, drains S. 10° W.
32.00	Spur, slopes S.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
39.30	Wash, 5 lks. wide, 5 ft. deep, drains S. 10° W.
41.02	The ¼ sec. cor. of secs. 7 and 18, monumented by an iron post, 2½ ins. diam., projecting 5 ins. above the ground, with brass cap mkd.
	T15N R4E ¼ $\frac{S 7}{S18}$ 1965
	Mound of stone, 2 ft. base, 1½ ft. high, N of cor.

	N. 89°44' W., beginning new measurement.
	Over gently rolling land, through dense creosote brush.
0.20	Wash, 5 lks. wide, 2½ ft. deep, drains S.
5.40	Fence, bears S. 35° E. and N. 35° W.
6.40	Intersection of dirt roads, extending S. 35° E., S. 55° W., and N. 35° W.
7.00	Fence, bears S. 35° E. and N. 35° W.
11.80	Power and telephone lines, bear S. 25° E. and N. 25° W.; enter dense mesquite and catclaw, bears N and S.
16.00	Fence, bears N. 30° E. and S. 30° W.
18.20	Dirt road, bears N. 40° E. and S. 40° W.
19.30	Fence, bears N. 10° E. and S. 10° W.
19.50	Enter river bottom, bears S. 20° E. and N. 20° W.
20.30	Fence, bears S. 20° E. and N. 20° W.
20.54	Point for the W. 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T15N R4E W 1/16 $\frac{S 7}{S18}$ 1974
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
20.60	Dirt road, bears S. 35° E. and N. 35° W.
25.60	Left bank of Verde River, banks 2 to 4 ft. high, bears S. 10° E. and N. 10° W.
26.40	Right bank of Verde River.
28.90	Abandoned fence, bears S. 20° E. and N. 20° W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
32.20	Paved road, bears S. 40° E. and N. 40° W.
39.56	Graded road, bears N. 40° E. and S. 40° W. Power line, bears SE and NW.
39.76	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of the Tp., heretofore described.
	Land, gently rolling to river bottom. Soil, sandy loam. Timber, cottonwood and mesquite. Undergrowth, creosote and catclaw.
	(Restoring the Survey Executed by C. Burton Foster in 1877)
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°34' W., bet. secs. 7 and 8.
	Ascend over SE slope, along W side of a draw, draining southerly, through medium timber and undergrowth.
0.54	Fence, bears E and W.
23.80	Graded road, bears N. 85° E. and S. 85° W.
25.00	Ridge, bears E and W.
35.60	Spur, slopes W curving NW.
38.70	Draw, drains S. 80° W.
39.90	Small spur, slopes S. 75° W.
39.83	Point for the ¼ sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	<p>T15N R4E $\frac{1}{4}$ S 7 S 8 1975</p>
	from which
	A telephone pole bears S. 79¼° E., 89 lks. dist.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
40.55	Telephone line, bears SE and NW.
55.30	Dirt road, bears irregularly E and W.
56.50	Enter open land, with scattering undergrowth, bears NE and N. 65° W.
72.40	Low ridge, bears SE and NW.
78.80	Gravel road, bears S. 35° E. and N. 35° W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
79.30	Power line, bears E and W.
79.66	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E S 6 S 5 S 7 S 8 1974
	from which A power pole, bears S. 73 3/4° W., 99 lks. dist., with aluminum tag, mkd. MST&TC°.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	Land, rolling. Soil, sandy loam and rocky. Timber, juniper, palo verde and mesquite Undergrowth, sagebrush, creosote and cacti.
	From the cor. of secs. 4, 5, 8 and 9.
	N. 89°34' W., bet. secs. 5 and 8.
	Over rolling land, through scattering undergrowth.
3.80	Low ridge, bears N and S.
9.00	Unimproved dirt road, bears S. 10° E. and N. 10° W.
22.30	Low ridge, bears S. 10° E. and N. 10° W.
40.73	Point for the ¼ sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T15N R4E ¼ S 5 S 8 1975
	Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.
	Cor. is located 13 lks. N of power line, bearing E and W.
59.60	Dirt road, bears S. 65° E. and N. 65° W.
64.20	Wash, 10 lks. wide, 3 ft. deep, drains NW.
72.70	Low spur, slopes NW.
81.46	The cor. of secs. 5, 6, 7 and 8.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Land, gently rolling. Soil, sandy loam. Timber, mesquite. Undergrowth, oak brush and cacti.</p>
	<p>S. 89°35' W., bet. secs. 6 and 7.</p> <p>Over gently rolling land, through scattering undergrowth.</p>
0.50	Gravel road, bears S. 35° E. and N. 35° W.
7.20	Top of a hill.
33.25	Power line, bears S. 89°48' E. and N. 89°48' W.
40.63	<p>Point for the ¼ sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ $\frac{S}{S}$ $\frac{6}{7}$ 1975</p> <p>Deposit broken glass at base of iron post.</p> <p>Cor. is located 15 lks. S of power line, bearing S. 89°48' E. and N. 89°48' W.</p>
41.40	Dirt road, bears N and S.
47.60	Dirt road, bears S. 15° E. and N. 15° W.
57.50	Bladed road, bears N. 70° E. and S. 70° W.
60.945	<p>Point for the W. 1/16 sec. cor. of secs. 6 and 7.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground to bedrock, over chiseled cross, mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E W 1/16 $\frac{S}{S}$ $\frac{6}{7}$ 1975</p> <p>Cor. is located 37 lks. S of power line, bearing S. 89°48' E. and N. 89°48' W.</p>
64.00	Same bladed road, bears S. 35° E. and N. 35° W., 126 lks. dist. to a washed out bridge.
66.40	Wash, 70 lks. wide, 15 ft. deep, drains S. 40° W.
65.50	Telephone line, bears S. 60° E. and N. 60° W., 180 lks. dist. to power line, bearing S. 89°48' E. and N. 89°48' W.

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS		
68.70	Wash, 30 lks. wide, 7 ft. deep, drains irregularly S.	
79.64	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., heretofore described.	
	Land, rolling. Soil, sandy loam with limestone outcrops. Timber, palo verde, mesquite and juniper. Undergrowth, creosote, oak brush, cacti and sparse grass.	
	From the cor. of secs. 5, 6, 7 and 8.	
	N. 0°36' E., bet. secs. 5 and 6.	
	Over gently rolling land, through thinly scattering undergrowth.	
4.50	Wash, 5 lks. wide, 1 ft. deep, drains NW.	
7.50	Dirt road, bears S. 85° E. and N. 85° W.	
14.60	Wash, 20 lks. wide, 8 ft. deep, drains S. 40° W.	
35.90	Wash, 15 lks. wide, 3 ft. deep, drains W.	
39.83	Point for the ¼ sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground to bedrock, mound of stone, 4 ft. base to top, with brass cap mkd.	
	<p style="text-align: center;">T15N R4E $\frac{1}{4}$ S 6 S 5 1975</p>	
44.90	Paved Forest Service road, No. 119, bears S. 70° E. and N. 70° W.	
45.90	Wash, 50 lks. wide, 10 ft. deep, drains N. 70° W.	
50.80	Gully, 30 lks. wide, 15 ft. deep, drains SW.	
69.70	Dirt road, bears N. 75° E. and S. 75° W.	
78.20	Gully, 20 lks. wide, 10 ft. deep, drains SW.	
79.35	Gully, 15 lks. wide, 3 ft. deep, drains S. 25° W.	
79.86	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 2 ins. above the ground, with brass cap mkd.	
	<p style="text-align: center;">T16N R4E S31 S32 S 6 S 5 T15N 1938</p>	
	Mound of stone, 3 ft. base, 1½ ft. high, W of cor.	

Dependent Resurvey Portion of Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>Land, rolling to gently rolling. Soil, sandy loam, with limestone outcrops. Timber, palo verde. Undergrowth, creosote, sagebrush and cacti.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivisional Lines, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the cor. of secs. 35 and 36, on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°01' W., bet. secs. 35 and 36.</p> <p>Ascend steep S slope, through scattering undergrowth.</p>
6.70	End of ascent; thence over rolling land.
21.60	Spur, slopes S. 70° E.
35.00	Spur, slopes S. 55° E.
39.00	Point for the ¼ sec. cor. of sec. 36 only. Set an iron post, 28 ins. long, 2½ ins. diam., 4 ins. in the ground, to bedrock, mound of stone, 4 ft. base to top, with brass cap mkd.
	<p>T15N R4E ¼ S36 1975</p>
40.00	Point for the ¼ sec. cor. of sec. 35 only. Set an iron post, 28 ins. long, 2½ ins. diam., 2 ins. in the ground, to bedrock, mound of stone, 4½ ft. base to top, with brass cap mkd.
	<p>T15N R4E ¼ S35 1975</p>
58.60	Spur, slopes S. 50° E.
79.00	Point for the cor. of secs. 25, 26, 35 and 36, at inter- section with sectional correction line West. Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 3½ ft. base to top, with brass cap mkd.
	<p>T15N R4E S26 S25 S35 S36 1975</p>
	<p>from which</p> <p style="text-align: center;">A cedar, 12 ins. diam., bears N. 49° W., 21.5 lks. dist., mkd. T15N R4E S26 BT.</p>

Survey of a Portion of the Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

	CHAINS	
		<p>Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, juniper and palo verde. Undergrowth, creosote, sage and cacti.</p>
		<p>The South boundary of the Tp. was found defective in alignment for surveying new subdivisional lines, therefore a sectional correction line was necessary.</p> <p>From the cor. of secs. 25 and 36, on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 2 ft. above the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N S25 S36 R4E 1918</p> <p>West, bet. secs. 25 and 36, on a sectional correction line.</p> <p>Over rolling land, through medium undergrowth.</p>
27.60		Ridge, bears N and S.
39.95		Point for the ¼ sec. cor. of secs. 25 and 36.
		<p>Set an iron post, 28 ins. long, 2½ ins. diam., over a chiseled cross in limestone bedrock, mound of stone, 6 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E ¼ S25 S36 1975</p>
63.50		Spur, slopes S. 10° W.
79.90		The cor. of secs. 25, 26, 35 and 36.
		<p>Land, rolling. Soil, shallow and rocky, with limestone outcrops. Timber, scattered cedar, mesquite and palo verde. Undergrowth, creosote, scrub oak, sage and cacti.</p>
		<p>West, bet. secs. 26 and 35 on a sectional correction line.</p> <p>Over rolling land, through medium undergrowth.</p>
9.90		Spur, slopes S. 75° W.
21.00		Wash, 20 lks. wide, 3 ft. deep, drains S. 65° W. from N. 18° E.
22.20		Dirt Forest Service road, No. 119A, bears N. 50° E. and S. 50° W.

Survey of a Portion of the Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
35.80	Spur, slopes S. 15° W.
36.52	Point for the ¼ sec. cor. of sec. 35 only.
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, mound of stone, 3½ ft. base to top, with brass cap mkd.
	T15N R4E
	$\frac{\frac{1}{4} \text{ S } 35}{1975}$
	from which
	A juniper, 8 ins. diam., bears S. 10°45' E., 168 lks. dist., mkd. ¼ S35 BT.
40.00	Point for the ¼ sec. cor. of sec. 26 only.
	Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, with brass cap mkd.
	T15N R4E $\frac{\frac{1}{4} \text{ S } 26}{1975}$
	Raise a mound of stone, 2 ft. base, 2 ft. high, N of cor.
53.40	Top of hill.
76.52	Intersect the E. bdy. of sec. 34.
	Point for the closing cor. of secs. 26 and 35.
	Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
	T15N R4E $\begin{array}{c} \\ \text{S34} \text{---} \text{S26}_{cc} \\ \\ \text{S35} \\ \\ 1975 \end{array}$
	from which
	The cor. of secs. 27 and 34, bears N. 0°53' E., 1.19 chs. dist., heretofore described.
	Land, rolling. Soil, sandy loam, with limestone outcrops. Timber, scattered palo verde and juniper. Undergrowth, creosote, sage and cacti.
	From the cor. of secs. 1 and 12, on the E. bdy. of the Tp., heretofore described.
	West, bet. secs. 1 and 12.
	Over gently rolling land, through scattered timber and medium undergrowth.

Survey of a Portion of the Subdivisional Lines,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
34.53	<p>Point for the $\frac{1}{4}$ sec. cor. of sec. 1 only.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E $\frac{1}{4}$ S 1 1975</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.</p>
35.20	<p>Jeep trail, bears S. 60° E. and N. 60° W.</p>
52.70	<p>Dirt road, bears N and S.</p>
74.53	<p>Intersect the E. bdy. of sec. 11.</p> <p>Point for the closing cor. of secs. 1 and 12.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E S11 $\frac{S}{S12}$ 1 cc 1975</p>
	<p>from which</p>
	<p style="text-align: center;">The cor. of secs. 2 and 11, bears N. $0^\circ 08'$ E., 6.70 chs. dist., heretofore, described.</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, E of cor.</p>
	<p>Land, gently rolling.</p>
	<p>Soil, sandy.</p>
	<p>Timber, mesquite.</p>
	<p>Undergrowth, creosote, catclaw and cacti.</p>
<hr/>	
<p>Survey of Subdivision of sec. 1, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the $\frac{1}{4}$ sec. cor. of sec. 1 only, on the S. bdy. of the sec.</p>
	<p>N. $0^\circ 15'$ E., on the N and S centerline of sec. 1.</p>
	<p>Over nearly level land, through scattering timber and undergrowth.</p>
13.30	<p>Dirt road, bears N. 80° E. and S. 80° W.</p>
46.55	<p>Abandoned fence, bears E and W.</p>
46.93	<p>Point for the $C\frac{1}{4}$ sec. cor. of sec. 1 at intersection with the E and W centerline of sec. 1.</p> <p>Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.</p>

Survey of Subdivision of sec. 1,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	T15N R4E C $\frac{1}{4}$ S1 1975
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.
	From this point, a cor. of fences, bear S. 30° W., 42 lks. dist., fences extending N, E and W.
71.00	Wash, 30 lks. wide, 7 ft. deep, drains N. 75° W.
86.77	Intersect cor. of fences, extending N, S, W and an abandoned fence E.
87.22	The ¼ sec. cor. of secs. 1 and 36, on the N. bdy. of the Tp., heretofore described.
<hr/>	
	From the ¼ sec. cor. of sec. 1 only, on the E. bdy. of the Tp.
	S. 89°32' W., on the E and W centerline of sec. 1.
	Over gently rolling land, through scattering timber and medium undergrowth.
3.00	Wash, 100 lks. wide, 5 ft. deep, drains S. 70° W.
34.40	The C¼ sec. cor. of sec. 1.
34.60	Fence, bears N and S.
74.00	Fence, bears N and S.
74.46	The ¼ sec. cor. of secs. 1 and 2.
<hr/>	
Survey of Subdivision of sec. 3, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona	
<hr/>	
	From the ¼ sec. cor. of secs. 3 and 10.
	N. 0°01' E., on the N and S centerline of sec. 3.
	Over gently rolling land, through scattering timber and undergrowth.
7.00	Paved Forest Service road, No. 119, bears N. 70° E. and S. 70° W.
18.35	Intersection of gravel roads, extending N, S. 30° E., and W; thence along road.
19.88	Point for the CS 1/16 sec. cor. of sec. 3.
	Set an iron post, 14 ins. long, 2½ ins. diam., 6 ins. below surface of gravel road, with brass cap mkd.
	T15N R4E C S 1/16 S 3 C 1975

Survey of Subdivision of sec. 3,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>from which</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° E., 37.9 lks. dist., with brass cap mkd. T15N R4E CS 1/16 S3 25 ft. RM 1975 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2½ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° W., 37.9 lks. dist., with brass cap mkd. T15N R4E CS 1/16 S3 25 ft. RM 1975 and an arrow pointing to the cor.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of both reference monuments.</p>
39.76	Point for the ¼ sec. cor. of sec. 3, at intersection with the E and W centerline of sec. 3; not monumented.
54.60	Gravel road curves W; enter dense mesquite.
58.75	Begin descent into creek bottom land, bears N. 80° E. and S. 80° W.
61.10	Oak Creek, 100 lks. wide, 2 to 4 ft. banks, course S. 80° W.
64.30	Fence, bears N. 60° E. and S. 60° W.; thence across open field.
68.00	Fence, bears E and W.
73.00	Enter timber, bears E and W.
73.20	Irrigation ditch, 10 lks. wide, flows W.
74.00	Leave timber, bears E and W.
74.40	Fence, bears E and W, powerline bears N. 80° E. and S. 80° W.; thence across open field.
80.12	<p>The ¼ sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp., monumented with a steel pipe, 6 ins. diam., 6 ins. below surface of ground. This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners and is accepted as the best available evidence of the original cor. position; not remonumented.</p> <p>Cor. is located 3 lks. S of the cor. of fences, extending N and W and in the bend of an irrigation ditch, flows N from W.</p>
	<p>From the point for the ¼ sec. cor. of secs. 2 and 3.</p> <p>N. 89°46' W., on the E and W centerline of sec. 3.</p> <p>Over gently rolling land, along dirt road.</p>
20.01	Point for the CE 1/16 sec. cor. of sec. 3; not monumented.

Survey of Subdivision of sec. 3,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
40.02	The point for the C $\frac{1}{4}$ sec. cor. of sec. 3.
40.20	Intersection of roads, extending N, E, S and W.
60.19	Point for the CW 1/16 sec. cor. of sec. 3; not monumented.
63.00	Road, curves N. 25° W. from E.
63.30	Cor. of fences, extending W and N. 25° W.
75.80	Cor. of fences, extending NW, N. 23° W. and S. 88° W.
78.40	Oak Creek, 4 chs. wide, course S. 65° E.
80.36	The point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4.
<p>Subdivision, SE$\frac{1}{4}$ sec. 3</p> <hr/>	
<p>From the E 1/16 sec. cor. of secs. 3 and 10.</p>	
<p>N. 0°04' E., on the N and S centerline of the SE$\frac{1}{4}$ of sec. 3.</p>	
<p>Over gently rolling land, through scattering timber and undergrowth.</p>	
5.10	Paved Forest Service road, No. 119, bears S. 82° E. and N. 82° W.
5.80	Fence, bears S. 80° E. and N. 80° W., 35 lks. to cor. of fences, extending N, S. 80° E. and S.
19.97	<p>Point for the SE 1/16 sec. cor. of sec. 3 at intersection with the E and W centerline of the SE$\frac{1}{4}$ of sec. 3.</p>
<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
<p>T15N R4E SE 1/16 S3 1975</p>	
<p>from which</p>	
<p>A well, 8 ins. diam., in concrete base, 3$\frac{1}{2}$ ft. square, 5 ins. high, bears S. 42° W., 94 lks. dist.</p>	
<p>Raise a mound of stone, 3 ft. base, 1$\frac{1}{2}$ ft. high, W of cor.</p>	
26.80	Fence, bears E and W.
39.91	The point for the CE 1/16 sec. cor. of sec. 3.
<hr/> <p>From the point for the S 1/16 sec. cor. of secs. 2 and 3.</p>	

Survey of Subdivision of sec. 3,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>N. 89°35' W., on the E and W centerline of the SE$\frac{1}{4}$ of sec. 3.</p> <p>Over gently rolling land, through scattering timber and medium undergrowth.</p>
20.01	The SE 1/16 sec. cor. of sec. 3.
38.90	Gravel road, bears N. 10° E., curving NE and S. 10° E., curving SE.
39.75	Fence, bears N and S.
40.01	The CS 1/16 sec. cor. of sec. 3.
<p>Subdivision, SW$\frac{1}{4}$ sec. 3</p> <hr/>	
	<p>From the W 1/16 sec. cor. of secs. 3 and 10.</p> <p>N. 0°03' W., on the N and S centerline of the SW$\frac{1}{4}$ of sec. 3.</p> <p>Over medium rolling land, through scattering timber and dense undergrowth.</p>
1.05	Paved Forest Service road, No. 119, bears N. 75° E. and S. 75° W.
11.10	Oak Creek, 150 lks. wide, 2 to 4 ft. banks, course S. 15° E.
19.50	Enter W edge of a dirt road, bears N and E.
20.01	Point for the SW 1/16 sec. cor. of sec. 3, at intersection with the E and W centerline of the SW $\frac{1}{4}$ of sec. 3.
	<p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 6 ins. below the surface of a dirt road, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E SW 1/16 S3 1975</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 16 ins. in the ground, for a reference monument, bears S. 45° E., 75.8 lks. dist., mound of stone, 2$\frac{1}{2}$ ft. base to top, with brass cap mkd. T15N R4E SW 1/16 S3 50 ft. RM 1975 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., set 22 ins. in the ground, for a reference monument, bears S. 45° W., 75.8 lks. dist., mound of stone, 2$\frac{1}{2}$ ft. base to top, with brass cap mkd. T15N R4E SW 1/16 S3 50 ft. RM 1975 and an arrow pointing to the cor.</p>
25.50	Curve in dirt road, bears S and W.
38.80	Fence, bears E and W.

Survey of Subdivision of sec. 3,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
39.00	Gravel road, bears E and W.
40.01	The point for the CW 1/16 sec. cor. of sec. 3.
	<hr/> From the CS 1/16 sec. cor. of sec. 3. S. 89°54' W., on the E and W centerline of the SW ¹ / ₄ of sec. 3. Over gently rolling land, through scattering timber and medium undergrowth.
0.20	Fence, bears N and S.
19.90	Fence, bears N. 5° E. and S. 5° W.
20.00	Dirt road, bears N and S.
20.16	The SW 1/16 sec. cor. of sec. 3.
23.90	Oak Creek, 160 lks. wide, 2 to 3 ft. banks, course S. 30° E.
40.00	Irrigation ditch, flows S. 30° E.
40.29	The point for the S 1/16 sec. cor. of secs. 3 and 4.
	<hr/> <p style="text-align: center;">Survey of Subdivision of sec. 7, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	From the ¹ / ₄ sec. cor. of secs. 7 and 18. N. 0°18' W., on the N and S centerline of sec. 7. Over rolling land, through medium timber and dense undergrowth.
6.70	Ascend over rolling land, bears N. 75° E. and S. 75° W.
18.10	Spur, slopes N. 85° W.
19.795	Point for the CS 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.
	T15N R4E C S 1/16 S 7 C 1975
20.00	Draw, drains N. 70° W.
21.60	Spur, slopes N. 75° W.
25.40	Draw, drains westerly.
28.10	Spur, slopes N. 85° W.

Survey of Subdivision of sec. 7,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
34.60	Spur, slopes N. 55° W.
39.59	Point for the C $\frac{1}{4}$ sec. cor. of sec. 7, at intersection with the E and W centerline of sec. 7.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T15N R4E C $\frac{1}{4}$ S 7 1975
	Raise a mound of stone, 4 ft. base, 2 ft. high, W of cor.
39.90	Draw, drains westerly.
43.60	Spur, slopes N. 85° W.
46.60	Wash, 40 lks. wide, 5 ft. deep, drains S. 65° W.
49.60	Ridge, bears N. 70° E. and N. 80° W.
54.30	Wash, 10 lks. wide, 6 ft. deep, drains westerly.
59.20	Spur, slopes S. 35° W.
59.37	Point for CN 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E C N 1/16 S 7 C 1975
	Raise a mound of stone, 4 ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.
66.30	Telephone line and dirt road, bears S. 62° E. and N. 62° W.
69.30	Wash, 20 lks. wide, 3 ft. deep, drains NW.
70.90	Wash, 20 lks. wide, 6 ft. deep, drains W.
77.60	Spur, slopes N. 70° W.
79.15	The $\frac{1}{4}$ sec. cor. of secs. 6 and 7.
	From the $\frac{1}{4}$ sec. cor. of secs. 7 and 8. S. 89°56'30" W., on the E and W centerline of sec. 7. Over rolling land, through medium undergrowth and scattering timber.
5.20	Draw, drains SW.
9.60	Spur, slopes S.

Survey of Subdivision of sec. 7,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
11.00	Draw, drains S. 20° E.
12.20	Spur, slopes S. 25° E.
14.90	Spur, slopes S. 25° W.
21.20	Draw, drains S. 10° W.
22.60	Spur, slopes S.
23.90	Draw, drains S.
27.60	Spur, slopes S.
40.84	The $C\frac{1}{4}$ sec. cor. of sec. 7.
49.40	Wash, 5 lks. wide, 1 ft. deep, drains N approximately 4 chs. to large wash, draining westerly.
58.00	Wash, 5 lks. wide, 1 ft. deep, drains S.
61.00	Fence, bears N and S 53 lks. dist. to cor. of fences, extending N and S. 20° E.
61.265	Point for the CW 1/16 sec. cor. of sec. 7.
	Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd.
	T15N R4E W 1/16 C ————— C S 7 1974
64.90	Gravel road, bears S. 10° E. and N. 10° W.
71.50	Enter river bottom land, bears S. 75° E. and N. 75° W.; thence through scattering cottonwoods.
73.90	Power line, bears N. 35° E. and S. 35° W.
74.70	Irrigation ditch, 20 lks. wide, 4 ft. deep, flows S. 30° W.
80.22	The $\frac{1}{4}$ sec. cor. of secs. 7 and 12.
	Subdivision, SW $\frac{1}{4}$ sec. 7 _____
	From the W 1/16 sec. cor. of secs. 7 and 18.
	N. 0°06' W., on the N and S centerline of the SW $\frac{1}{4}$ of sec. 7.
	Over rolling land, through medium timber and undergrowth.
0.40	Fence, bears S. 30° E. and N. 30° W.
6.44	The most westerly cor. of a stucco type building, 60.5 ft. x 20.3 ft., bears East 8.5 lks. dist., long side bears SE and NW.
17.90	Power line, bears S. 25° E. and N. 25° W.

Survey of Subdivision of sec. 7,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

- 19.73 Point for the SW 1/16 sec. cor. of sec. 7, at intersection with the E and W centerline of the SW $\frac{1}{4}$ of sec. 7.
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, mound of stone, 2 ft. base to top, with brass cap mkd.
- T15N R4E
SW 1/16 S 7
1975
- from which
- A local monument, a 5/8 in. re-bar, projecting 6 ins. above ground, bears N. 80° E., 146 lks. dist.
- 30.70 Gravel road, bears S. 40° E. and N. 40° W.
- 39.46 The CW 1/16 sec. cor. of sec. 7.
- _____
- From the CS 1/16 sec. cor. of sec. 7.
- N. 89°54' W., on the E and W centerline of the SW $\frac{1}{4}$ of sec. 7.
- Over gently rolling land, through scattering timber and undergrowth.
- 3.60 Spur, slopes N. 50° W.
- 12.80 Fence, bears N and S.
- 13.20 Gravel road, bears N and S.
- 14.70 Dirt road, bears N. 30° E. and S. 30° W.
- 20.49 The SW 1/16 sec. cor. of sec. 7.
- 21.40 Power line, bears S. 25° E. and N. 25° W.
- 29.20 Left bank of the Verde River, 2 to 5 ft. banks, bears N. 5° E. and S. 5° W.
- 30.30 Right bank of the Verde River, thence over washed area, subject to overflow.
- 37.75 Abandoned fence, bears S. 55° E. and N. 55° W. West edge of overflow area bears same as fence.
- 39.555 The S 1/16 sec. cor. of secs. 7 and 12.

Subdivision, NW $\frac{1}{4}$ sec. 7

From the CW 1/16 sec. cor. of sec. 7.

N. 0°08' W., on the N and S centerline of the NW $\frac{1}{4}$ of sec. 7.

Survey of Subdivision of sec. 7,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	Over rolling land, through medium undergrowth.
19.00	Fence, bears N. 88° E. and S. 88° W.
19.75	Point for the NW 1/16 sec. cor. of sec. 7, at intersection with the E and W centerline of the NW¼ sec. 7. Set an iron post, 28 ins. long, 2½ ins. diam., 13 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd. T15N R4E NW 1/16 S 7 1975 Cor. is located 102 lks. NW of a fence cor.
21.60	Ridge, bears S. 50° E. and N. 50° W.
36.60	Wash, 30 lks. wide, 2 ft. deep, drains S. 80° W.
37.60	Telephone line, bears S. 60° E. and N. 60° W.
39.20	Dirt road, bears N. 70° E. and S. 70° W.
39.47	The W 1/16 sec. cor. of secs. 6 and 7. From the CN 1/16 sec. cor. of sec. 7. S. 89°46' W., on the E and W centerline of the NW¼ of sec. 7. Over rolling land, through scattering undergrowth.
13.90	Spur, slopes S. 35° W.
20.37	The NW 1/16 sec. cor. of sec. 7.
28.40	Spur, slopes N. 10° E.
34.40	Ridge, bears S. 25° E. and N. 25° W.
39.18	The N 1/16 sec. cor. of secs. 7 and 12.
Survey of Partial Subdivision of sec. 9, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona	
	From the ¼ sec. cor. of secs. 9 and 16. N. 1°16' E., on the N and S centerline of sec. 9. Over rolling land, through scattering timber and medium undergrowth.
0.20	Jeep trail, bears E and W.
2.47	Fence, bears S. 40° E. and N. 40° W., 9.5 lks. to cor. of fences, extending N. 2° E., S. 40° E. and West.
4.00	Fence, bears N. 2° E. and S. 2° W.
20.00	Point for the CS 1/16 sec. cor. of sec. 9.

Survey of Partial Subdivision of sec. 9,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground to bedrock, mound of stone, 3 ft. base to top, with brass cap mkd.

T15N R4E
C
S 1/16 | S 9
C
1975

from which

The cor. of abandoned fences, bears N. 53½° E.,
55 lks. dist.; fences extend N, E and S.

40.00 Point for the C¼ sec. cor. of sec. 9, at intersection with the E and W centerline of sec. 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground over chiseled cross in limestone bedrock, mound of stone, 4 ft. base to top, with brass cap mkd.

T15N R4E
C¼ S 9
1975

80.12 The ¼ sec. cor. of secs. 4 and 9.

From the ¼ sec. cor. of secs. 9 and 10.

N. 89°26' W., on the E and W centerline of sec. 9.

Over rolling land, through dense mesquite.

0.09 Center of a paved road, bears irregularly N and S.

0.37 Fence, bears N and S.

20.26 Point for the CE 1/16 sec. cor. of sec. 9.

Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.

T15N R4E
E 1/16
C ————— C
S 9
1975

Raise a mound of stone, 3 ft. base, 1½ ft. high, N of cor.

From this point, an open-end iron pipe, 1 in. diam., projecting 15 ins. above ground, bears N. 67° E., 29.5 lks. dist., in the cor. of fences extending Easterly and Southerly.

24.10 Leave dense mesquite.

40.06 Fence, bears S. 5° E. and N. 5° W.

40.52 The C¼ sec. cor. of sec. 9.

63.10 Jeep trail, bears S. 65° E. and N. 65° W.

Survey of Partial Subdivision of sec. 9,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
80.14	The ¼ sec. cor. of secs. 8 and 9.
Subdivision, SE¼ sec. 9.	
From the E 1/16 sec. cor. of secs. 9 and 16.	
N. 1°02' E., on the N and S centerline of the SE¼ of sec. 9.	
Over rolling land, through scattering timber and medium undergrowth.	
2.20	Jeep trail, bears S. 70° E. and N. 70° W.
20.06	Point for the SE 1/16 sec. cor. of sec. 9 at intersection with the E and W centerline of the SE¼ of sec. 9.
Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, mound of stone, 2½ ft. base to top, with brass cap mkd.	
T15N R4E SE 1/16 S 9 1975	
Raise a mound of stone, 3 ft. base, 2½ ft. high, W of cor.	
40.12	The CE 1/16 sec. cor. of sec. 9,
From the S 1/16 sec. cor. of secs. 9 and 10.	
N. 89°15' W., on the E and W centerline of the SE¼ of sec. 9.	
Over rolling land, through scattering timber and undergrowth.	
20.33	The SE 1/16 sec. cor. of sec. 9.
23.40	Ridge, bears NE and SW.
40.66	The CS 1/16 sec. cor. of sec. 9.
Survey of Subdivision of sec. 10, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona	
From the ¼ sec. cor. of secs. 10 and 15.	
N. 0°22' E., on the N and S centerline of sec. 10.	
Over medium rolling land, through scattering timber and undergrowth.	
9.60	Oak Creek, 100 lks. wide, course N. 30° E.
12.62	Fence cor., bears East, 9 lks. dist.; fences extend Northerly and N. 55° W.
12.80	Fence, bears S. 70° W. and N. 70° E., 50 lks. dist. to end of fence.

Survey of Subdivision of sec. 10,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
13.80	Fence, extends irregularly SW along SE edge of gravel road; thence along E edge of gravel road, bears Northerly and irregularly SW.
19.70	Power line, bears S. 80° E. and N. 80° W.
20.80	Gravel road, bears S. 80° E., to ranch house.
23.00	Gravel road, bears N. 85° E. and S. 85° W., 20 lks. to junction of roads extending N. 85° E., Southerly and S. 85° W.
29.20	Fence, extending W from N and S fence.
32.50	Fence, extending W from N and S fence.
39.26	Fence, extending W from N and S fence.
40.26	<p>Point for the $C\frac{1}{4}$ sec. cor. of sec. 10, at intersection with the E and W centerline of sec. 10.</p> <p>Set an iron post, 14 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. below the surface of a gravel road, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E C$\frac{1}{4}$ S10 1975</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, for a reference monument, mound of stone, $2\frac{1}{2}$ ft. base, to top, bears N. 45° E., 53 lks. dist., mkd. T15N R4E C$\frac{1}{4}$ S10 RM 35 ft. 1975 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., set 22 ins. in the ground, for a reference monument, mound of stone, 2 ft. base, to top, bears S. 45° W., 53 lks. dist., mkd. T15N R4E C$\frac{1}{4}$ S10 RM 35 ft. 1975 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">The cor. of fences, bears S. 8° E., 22.5 lks. dist., fences extend N. 80° E. and Southerly.</p> <p>Cor. is located in gravel road, bears N. 75° E. and S. 75° W.</p>
53.36	Fence, bears E and W, 4 lks. to cor. of fences extending N, E and W.
79.80	Telephone line, bears E and W.
80.40	Cor. of fences extending S and W.
80.44	The $\frac{1}{4}$ sec. cor. of secs. 3 and 10.
	<p>From the $\frac{1}{4}$ sec. cor. of secs. 10 and 11.</p> <p>S. 89°23' W., on the E and W centerline of sec. 10.</p> <p>Descend steep SW slope, through scattering timber and medium undergrowth.</p>


Survey of Subdivision of sec. 10,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
5.30	Left bank of Oak Creek, bears S. 55° E. and N. 55° W.; thence along Oak Creek.
10.10	Left bank of Oak Creek, bears N. 70° E. and S. 40° W.
19.80	Fence, bears S and N, 37 lks. to cor. fences extend N, S and W, abandoned N.
20.70	Power line, bears N and S, 17 lks. to junction of power lines extending N, SE and W.
32.90	Gravel road, bears N. 35° E. and S. 35° W.
40.00	The $\frac{1}{4}$ sec. cor. of sec. 10.
57.20	Oak Creek, 80 lks. wide, 2 to 10 ft. banks, course S. 30° E.
60.80	Cor. of fences, extending S. 60° E., West and N. 60° W., thence along E and W fence and irrigation ditch, flows East. Enter level pasture land, bears S. 60° E. and N. 60° W.
66.50	Fence, extends S.
66.60	Irrigation ditch, flows S.
68.50	Power line, bears N. 40° E. and S. 40° W.
73.00	Power line, bears E and W.
73.20	Irrigation ditch, flows E from S. 55° W.
80.57	The $\frac{1}{4}$ sec. cor. of secs. 9 and 10.

Survey of Subdivision of sec. 14,
T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona

From the $\frac{1}{4}$ sec. cor. of secs. 14 and 23.
N. 0°26' W., on the N and S centerline of sec. 14.
Over rolling land, through medium timber and undergrowth.

19.73 Point selected for the witness CS 1/16 sec. cor. of sec. 14.
Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 2½ ft. base, 2½ ft. high, W of cor.

20.03 True point for the CS 1/16 sec. cor. of sec. 14, falls on a small rock ledge, impracticable to monument.

Survey of Subdivision of sec. 14,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
40.06	<p>Point for the C$\frac{1}{4}$ sec. cor. of sec. 14, at intersection with the E and W centerline of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E C$\frac{1}{4}$ S14 1975</p> <p>Raise a mound of stone, 3$\frac{1}{2}$ ft. base, 2 ft. high, W of cor.</p> <p>Cor. is located 130 lks. E of a draw, drains S. 40° W.</p>
50.00	Jeep trail, bears NE and SW.
79.79	The true point for the $\frac{1}{4}$ sec. cor. of secs. 11 and 14.
	<p>From the $\frac{1}{4}$ sec. cor. of sec. 14 only, on the E. bdy. of the sec.</p> <p>N. 89°34' W., on the E and W centerline of sec. 14.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>
40.19	The C $\frac{1}{4}$ sec. cor. of sec. 14.
59.20	Top of rounded hill.
60.615	<p>Point for the CW 1/16 sec. cor. of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E W 1/16 C ——— C S14 1975</p> <p>Raise a mound of stone, 2$\frac{1}{2}$ ft. base, 2 ft. high, N of cor.</p>
62.40	Jeep trail, bears N. 15° E. and S. 15° W.
70.40	Ridge, bears N and S.
81.04	The $\frac{1}{4}$ sec. cor. of secs. 14 and 15.
	<p style="text-align: center;">Subdivision of SW$\frac{1}{4}$ sec. 14</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 14 and 23.</p> <p>N. 0°33' W., on the N and S centerline of the SW$\frac{1}{4}$ of sec. 14.</p> <p>Over rolling land, through scattering timber and undergrowth.</p>

Survey of Subdivision of sec. 14,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
1.60	Wash, 45 lks. wide, 5 ft. deep, drains S. 35° W.
12.90	Spur, slopes S. 15° W.
19.88	<p>Point for the SW 1/16 sec. cor. of sec. 14 at intersection with the E and W centerline of the SW¼ of sec. 14.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E SW 1/16 S14 1975</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>From this cor., an open-end pipe, 1 in. diam., projecting 3 ins. above ground, bears N. 23°16' E., 10 lks. dist.</p>
39.77	<p>The CW 1/16 sec. cor. of sec. 14.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the CS 1/16 sec. cor. of sec. 14.</p> <p>N. 89°09'30" W., on the E and W centerline of the SW¼ of sec. 14.</p> <p>Over rolling land, through scattering timber and undergrowth.</p>
20.39	The SW 1/16 sec. cor. of sec. 14.
23.50	Jeep trail, bears SE and NW.
24.00	Descend over steep W slope into creek bottom.
28.10	Oak Creek, 80 lks. wide, 2 to 5 ft. banks, course S. 10° E., curving Westerly.
37.50	Gravel road, bears S. 10° E. and N. 10° W.
40.78	The S 1/16 sec. cor. of secs. 14 and 15.
<hr/> <p>Survey of Subdivision of sec. 15, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
<p>From the ¼ sec. cor. of secs. 15 and 22.</p> <p>N. 0°16' E., on the N and S centerline of sec. 15.</p> <p>Over rolling land, through scattering timber and undergrowth.</p>	
5.50	Dirt road, bears S. 30° E. and N. 15° W.
11.40	Same road, bears S. 10° W. and N. 30° E., curving Easterly.
19.875	Point for the CS 1/16 sec. cor. of sec. 15.

Survey of Subdivision of sec. 15,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T15N R4E C S 1/16 S15 C 1975
	from which
	A mesquite, 7 ins. diam., bears S. 53° W., 38 lks. dist., mkd. CS 1/16 S15 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
22.60	Oak Creek, 140 lks. wide, 3 to 6 ft. banks, course N. 85° W.
38.50	Gravel road, bears N. 75° E. and S. 75° W.
39.75	Point for the C¼ sec. cor. of sec. 15, at intersection with the E and W centerline of sec. 15; not monumented.
40.20	Power line, bears S. 58° E. and N. 58° W.
40.55	Fence, bears N. 87° E. and S. 87° W.
70.00	Power line, bears N. 12° E. and S. 12° W.
72.30	Gravel road, bears N. 50° E. and S. 50° W.
79.46	The ¼ sec. cor. of secs. 10 and 15.
	From the ¼ sec. cor. of secs. 14 and 15.
	S. 89°39' W., on the E and W centerline of sec. 15.
	Over rolling land, through scattering timber and medium undergrowth.
28.50	Oak Creek, 150 lks. wide, 2 ft. banks, course S. 20° E.
39.50	Power line, bears S. 50° E. and N. 58° W.
40.19	The point for the C¼ sec. cor. of sec. 15.
40.80	Power line, bears S and N, 85 lks. to junction of power lines extending S. 58° E., S and N. 58° W.
40.90	Fence, bears S and N, 80 lks. to cor. of fences extending E and S.
43.60	Gravel road, bears S. 55° E. and N. 55° W.
50.30	Spur, slopes N.
52.50	Power line, bears N. 40° E. and S. 40° W.
59.90	Gravel road, bears S. 20° E. and N. 20° W.
60.70	Fence, bears S. 13° E. and N. 13° W.

Survey of Subdivision of sec. 15,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
61.10	Wash, 20 lks. wide, 3 ft. deep, drains S. 65° E.
80.76	The point for the ¼ sec. cor. of secs. 15 and 16.
<hr/> Survey of Subdivision of sec. 17, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona <hr/>	
From the ¼ sec. cor. of secs. 17 and 20.	
N. 0°07' E., on the N and S centerline of sec. 17.	
Over gently rolling land, through scattering timber and medium undergrowth.	
7.20	Wash, 40 lks. wide, 7 ft. deep, drains S. 40° W.
11.80	Wash, 10 lks. wide, 3 ft. deep, drains SE.
27.90	Wash, 50 lks. wide, 8 ft. deep, drains SE.
39.76	Point for the C¼ sec. cor. of sec. 17, at intersection with the E and W centerline of sec. 17; not monumented.
40.60	Jeep trail, bears S. 20° E. and N. 20° W.
45.50	Telephone line, bears S. 16° E. and N. 16° W.
47.40	Wash, 20 lks. wide, 3 ft. deep, drains N. 85° E.
55.70	Wash, 20 lks. wide, 4 ft. deep, drains S. 20° E.
59.64	Point for the CN 1/16 sec. cor. of sec. 17; not monumented.
62.60	Jeep trail, bears N. 40° E. and S. 40° W.
72.70	Spur, slopes S. 75° W.
76.80	Spur, slopes S. 70° W.
79.52	The ¼ sec. cor. of secs. 8 and 17.
<hr/> From the ¼ sec. cor. of secs. 16 and 17.	
N. 89°18' W., on the E and W centerline of sec. 17.	
Over rolling land, through scattering timber and medium undergrowth.	
30.50	Wash, 30 lks. wide, 3 ft. deep, drains S. 50° W.
31.50	Spur, slopes S. 5° W.
32.60	Wash, 30 lks. wide, 3 ft. deep, drains S. 15° E.
35.30	Ridge, bears S. 35° E. and N. 35° W.
38.60	Telephone line, bears S. 15° E. and N. 15° W.
39.80	Jeep trail, bears SE and NW.

Survey of Subdivision of sec. 17,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
40.08	The point for the C $\frac{1}{4}$ sec. cor. of sec. 17.
51.30	Graded road, bears N. 15° E. and S. 15° W.
55.80	Ridge, bears N and S.
60.08	Point for the CW 1/16 sec. cor. of sec. 17. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T15N R4E W 1/16 C ————— C S17 1975 </div>
	Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, N of cor.
68.80	Spur, slopes S.
76.80	Left bank of Verde River, 8 to 15 ft. banks, bear S. 35° E. and N. 35° W.
78.10	Right bank of Verde River; thence over busy gravel pit area, bears S. 35° E. and N. 35° W.
80.08	The $\frac{1}{4}$ sec. cor. of secs. 17 and 18.
<hr/> Subdivision of NW $\frac{1}{4}$ sec. 17 <hr/>	
	From the CW 1/16 sec. cor. of sec. 17. N. 0°14' E., on the N and S centerline of the NW $\frac{1}{4}$ of sec. 17. Ascend over broken S. slope, through medium undergrowth.
3.20	Top of ascent; thence over gently rolling land.
19.85	Point for the NW 1/16 sec. cor. of sec. 17, at intersection with the E and W centerline of the NW $\frac{1}{4}$ of sec. 17. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T15N R4E NW 1/16 S17 1975 </div>
	Raise a mound of stone, 3 ft. base, 1 $\frac{1}{2}$ ft. high, W of cor.
39.72	The W 1/16 sec. cor. of secs. 8 and 17. <hr/> From the point for the CN 1/16 sec. cor. of sec. 17. N. 89°24' W., on the E and W centerline of the NW $\frac{1}{4}$ of sec. 17.

Survey of Subdivision of sec. 17,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Over rolling land, through scattering timber and undergrowth.
2.10	Dirt road, in wash, bears N and S, wash 10 lks. wide, 4 ft. deep, drains SE.
4.90	Telephone line, bears S. 25° E. and N. 25° W.
5.10	Dirt road, bears SE and NW.
11.20	Graded road, bears N and S.
19.70	Ridge, bears N and S.
20.02	The NW 1/16 sec. cor. of sec. 17.
22.00	Descend steep W. slope.
26.60	Draw, drains S. 35° W.
30.60	Spur, slopes S. 40° W.
36.30	Wash in draw, drains Southerly; ascend E slope.
40.04	The N 1/16 sec. cor. of secs. 17 and 18.
<hr/> Dependent Resurvey of Partial Subdivision of sec. 18, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona	
<hr/> (Restoring the Survey Executed by Boyd S. Owens in 1965)	
<hr/> From the C ¹ / ₄ sec. cor. of sec. 18, monumented by an iron post, 2½ ins. diam., flush with the ground, with brass cap mkd.	
T15N R4E C ¹ / ₄ S18 1965	
Cor. is located in E and W fence line.	
N. 0°11' W., on the N and S centerline of sec. 18.	
Over nearly level open land.	
.20	Paved road, bears E and W.
10.30	Paved road, bears E and W.
14.30	Paved road, bears E and W.
15.60	Descend into river bottom, bears E and W.
18.00	Right bank of Verde River, 2 to 4 ft. banks, bear E and W.
19.40	Left bank of Verde River, bears S. 85° E. and N. 85° W.
19.835	Point for the CN 1/16 sec. cor. of sec. 18; not monumented.

Dependent Resurvey of Partial Subdivision of sec. 18,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
21.00	Cor. of fences, extend W and N, 20 lks. to cor. of fences extending N, E and S.
21.10	Old left bank of Verde River, bears S. 80° E. and N. 80° W.
31.20	Cor. of fences, extending N, S. 60° E. and S; enter dense creosote.
31.70	Telephone line, bears S. 60° E. and N. 60° W., along unimproved dirt road.
34.10	Graded road, bears S. 55° E. and N. 55° W.
38.30	Fence, bears E and W, 17 lks. to cor. of fences, extending Easterly, Southerly and Westerly.
39.67	The ¼ sec. cor. of secs. 7 and 18.
	From the C¼ sec. cor. of sec. 18.
	N. 89°43' W., on the E and W centerline of sec. 18.
	Over nearly level land, through scattering timber and undergrowth, along fence line.
19.80	Intersection of dirt roads, extending N, S. 80° E. and N. 60° W.
20.64	Point for the CW 1/16 sec. cor. of sec. 18.
	Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T15N R4E W 1/16 C ————— C S18 1974
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, N of cor.
	Fence cor., bears N. 89°52' E., 101 lks. dist., fences extending N and E.
	From this point enter rolling land, bears N and S.
36.50	Wash, 20 lks. wide, 1 ft. deep, drains N. 15° W., curving NE.
40.00	The ¼ sec. cor. of secs. 13 and 18.
	Subdivision of NE¼ sec. 18 <hr style="width: 30%; margin: auto;"/>
	From the CE 1/16 sec. cor. of sec. 18, monumented by an iron post, 2½ ins. diam., projecting 4 ins. above the ground, with brass cap mkd.

Dependent Resurvey of Partial Subdivision of sec. 18,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>E 1/16 C ————— C S18 1965</p>
	<p>Cor. is located in the cor. of fences, extending East- erly, Southerly and Westerly.</p> <p>N. 0°06' W., on the N and S centerline of the NE¼ of sec. 18.</p> <p>Through residential area.</p>
.18	Paved road, bears E and W.
10.80	Paved road, bears SE and NW, leave residential area.
12.00	Enter river bottom land, bears SE and NW.
18.40	Right bank of Verde River, 2 to 5 ft. banks, bear N. 80° E. and S. 80° W.
19.60	Left bank of Verde River.
19.82	Point for the NE 1/16 sec. cor. of sec. 18, at intersec- tion with the E and W centerline of the NE¼ of sec. 18, falls in eroded area impracticable to monument.
20.02	Point selected for the witness NE 1/16 sec. cor. of sec. 18.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> WC T15N R4E NE 1/16 S18 ↓ 1975 </p>
	<p>from which</p> <p style="padding-left: 40px;">A cottonwood, 34 ins. diam., bears N. 13 3/4° E., 112 lks. dist., mkd, X at breast height and BT at base.</p> <p style="padding-left: 40px;">A power pole, No. PS162949, bears N. 1½° W., 166 lks. dist.</p>
20.60	Fence, bears S. 75° E. and N. 75° W.
21.70	Power line, bears S. 75° E. and N. 75° W.
23,50	Fence, bears S. 75° E. and N. 75° W.
38.20	Fence, bears E and W.
39.66	The E 1/16 sec. cor. of secs. 7 and 18.
	<hr style="width: 20%; margin: 0 auto;"/>
	From the N 1/16 sec. cor. of secs. 17 and 18.

Dependent Resurvey of Partial Subdivision of sec. 18,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	N. 89°43'30" W., on the E and W centerline of the NE $\frac{1}{4}$ of sec. 18.
	Over rolling land, through scattering timber and medium undergrowth.
4.00	Dirt road, bears S. 25° E. and N. 25° W., on a spur sloping N. 25° W.
4.20	Descend SW slope into river bottom area.
14.80	Power line, bears S. 70° E. and N. 70° W.; thence over river bottom, bears SE and NW.
18.50	Fence, bears S. 75° E. and N. 75° W.
20.49	The true point for the NE 1/16 sec. cor. of sec. 18.
25.00	Wash, 15 lks. wide, 2 ft. deep, drains S. 30° E., from irregularly N.
40.97	The point for the CN 1/16 sec. cor. of sec. 18.
Subdivision of NW $\frac{1}{4}$ sec. 18	
	From the CW 1/16 sec. cor. of sec. 18.
	N. 0°01' W., on the N and S centerline of the NW $\frac{1}{4}$ of sec. 18.
	Over gently rolling land, through scattering undergrowth.
6.90	Dirt road, bears N. 65° E. and S. 65° W.
19.83	Point for the NW 1/16 sec. cor. of sec. 18, at intersection with the E and W centerline of the NW $\frac{1}{4}$ of sec. 18.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 13 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
T15N R4E NW 1/16 S18 1974	
20.40	Fence, bears E and W.
24.00	Descend over cliff, bears S. 65° E. and N. 65° W.
27.70	Right bank of Verde River, 2 to 4 banks, bear S. 35° E. and N. 35° W.
30.50	Left bank of Verde River.
36.40	Dirt road, bears S. 35° E. and N. 35° W.
39.66	The W 1/16 sec. cor. of secs. 7 and 18.
	From the point for the CN 1/16 sec. cor. of sec. 18.

Dependent Resurvey of Partial Subdivision of sec. 18,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	N. 89°42'30" W., on the E and W centerline of the NW¼ of sec. 18.
	Over river bottom land.
2.00	Left bank of Verde River, 2 to 4 ft. banks, bear S. 85° E. and N. 85° W.
9.90	Right bank of Verde River, 2 to 4 ft. banks, bear S. 65° E. and N. 65° W.
10.70	Ascend over cliff, bears S. 65° E. and N. 65° W.
15.40	Draw, drains NW.
18.00	Dirt road, bears S and N, curving W.
19.90	Fence, bears S and N, 57 lks. to cor. of fences, extending Southerly and Westerly.
20.60	The NW 1/16 sec. cor. of sec. 18.
27.70	Wash, 20 lks. wide, 1 ft. deep, drains N.
29.60	Ridge, bears N and S.
32.20	Wash, 30 lks. wide, 2 ft. deep, drains NE.
39.88	The N 1/16 sec. cor. of secs. 13 and 18.
<hr/> Survey of Subdivision of sec. 19, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the true point for the ¼ sec. cor. of secs. 19 and 30.
	N. 0°02' E., on the N and S centerline of sec. 19.
	Over rolling land, through scattering timber and medium undergrowth.
1.00	Wash, 110 lks. wide, 3 ft. deep, drains N. 25° E., from S. 15° E.
6.50	Spur, slopes N. 25° E.
39.93	Point for the C¼ sec. cor. of sec. 19, at intersection with the E and W centerline of sec. 19; not monumented.
41.00	Jeep trail, bears N. 25° E. and S. 25° W.
42.80	Jeep trail, bears N. 65° E. and S. 65° W.
59.90	Point for the CN 1/16 sec. cor. of sec. 19; not monumented.
60.40	Spur, slopes S. 75° E.
68.10	Right bank of Verde River, 4 to 6 ft. banks, bear S. 20° E. and N. 20° W.
79.87	True point for the ¼ sec. cor. of secs. 18 and 19.

Survey of Subdivision of sec. 19,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	From the true point for the $\frac{1}{4}$ sec. cor. of secs. 19 and 20.
	N. $89^{\circ}58'$ W., on the E and W centerline of sec. 19.
	Over rolling land, through scattering undergrowth.
1.50	Right bank of Verde River, 4 to 10 ft. banks, bear S. 65° E. and N. 65° W.
4.00	Wash, 40 lks. wide, 4 ft. deep, drains N. 30° W., 100 lks. to Verde River.
8.10	Fence, bears S. 60° E. and N. 60° W.
20.35	Point for the CE $\frac{1}{16}$ sec. cor. of sec. 19.
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground, mound of stone, 2 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T15N R4E E $\frac{1}{16}$ C ————— C S19 1975</p>
	Raise a mound of stone, 3 ft. base, 2 ft. high, N of cor.
40.70	The point for the C $\frac{1}{4}$ sec. cor. of sec. 19.
41.10	Jeep trail, bears N. 25° E. and S. 25° W.
80.22	The $\frac{1}{4}$ sec. cor. of secs. 19 and 24 on the W. bdy. of the Tp., monumented by the remains of a badly deteriorated 1 in. iron post, with brass cap mkd.
	<p style="text-align: center;">$\frac{1}{4}$ S24 S19 1917</p>
	Mound of stone, $3\frac{1}{2}$ ft. base, 2 ft. high, W of cor.
	At the cor. point
	Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
	<p style="text-align: center;">T15N R3E $\frac{1}{4}$ R4E S24 S19 1975</p>
	Deposit the remains of the 1 in. iron post, alongside the cor.
	Subdivision of NE $\frac{1}{4}$ of sec. 19
	From the CE $\frac{1}{16}$ sec. cor. of sec. 19.

Survey of Subdivision of sec. 19,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	N. 0°04' E., on the N and S centerline of the NE $\frac{1}{4}$ of sec. 19.
	Over rolling land, through scattering undergrowth.
1.90	Descend into river bottom, bears SE and NW.
6.90	Fence, bears S. 60° E. and N. 60° W.
10.60	Right bank of Verde River, 2 to 3 ft. banks, bears S. 62° E. and N. 62° W.
11.80	Left bank of Verde River.
19.975	Point for the NE 1/16 sec. cor. of sec. 19, at intersection with the E and W centerline of the NE $\frac{1}{4}$ of sec. 19.
	Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., 23 ins. in the ground, with brass cap mkd.
	T15N R4E NE 1/16 S19 1975
	from which
	A mesquite, 6 ins. diam., bears S. 52 $\frac{1}{2}$ ° E., 157 lks. dist., mkd. NE 1/16 S19 BT.
	Cor. is located in fence, bears W and E, 18 lks. to cor. of fences extending E, S and W.
30.60	Graded dirt road, bears E and W.
33.70	Graded dirt road, bears E and W.
38.80	Fence, bears E and W.
39.95	The E 1/16 sec. cor. of secs. 18 and 19.

	From the N 1/16 sec. cor. of secs. 19 and 20.
	N. 89°58' W., on the E and W centerline of the NE $\frac{1}{4}$ of sec. 19.
	Over rolling land, through scattering timber and undergrowth, along power line and fence.
20.37	The NE 1/16 sec. cor. of sec. 19.
28.50	Cor. of fences, extending E, W and N. 50° W.
31.90	Fence, bears S. 24° E. and N. 24° W.
33.60	Left bank of Verde River, 3 ft. banks, bears SE and NW.
36.60	Right bank of Verde River, 2 to 5 ft. bank, bears S. 15° E. and N. 15° W.
37.00	Ascend steep E NE slope.
40.74	The point for the CN 1/16 sec. cor. of sec. 19.

Survey of Subdivision of sec. 20,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS

Survey of Subdivision of sec. 20,
T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona


From the point for the ¼ sec. cor. of secs. 20 and 29.

N. 0°02' E., on the N and S centerline of sec. 20.

Over level river bottom land, through scattering timber and dense undergrowth.

- 5.80 Fence, bears N. 85° E. and S. 85° W.
- 10.80 Fence, bears N. 85° E. and S. 85° W.
- 13.80 Fence, bears S. 25° E. and N. 25° W.
- 17.945 Point selected for the witness CS 1/16 sec. cor. of sec. 20.


Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.



Raise a mound of stone, 2 ft. base, 1 ft. high, W of cor.

- 18.30 Left bank of Verde River, 2 to 5 ft. banks, bears S. 25° E. and N. 25° W., curving to N. 60° E.
- 20.145 True point for the CS 1/16 sec. cor. of sec. 20 falls in the Verde River, impracticable to monument.
- 22.30 Left bank of Verde River, bears N. 70° E. and S. 30° W.; ascend out of river bottom land, through medium undergrowth.
- 27.80 Power line, bears S. 30° E. and N. 30° W.
- 35.30 Track road, bears S. 5° E. and N. 5° W.
- 37.80 Fence, bears S. 5° E. and N. 5° W.
- 40.29 Point for the C¼ sec. cor. of sec. 20, at intersection with the E and W centerline of sec. 20.

Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.



Cor. is located 21 lks. E of fence, bears N. 5° W. and S. 5° E.

Survey of Subdivision of sec. 20,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>From this point a granite stone, 6 x 6 x 5 ins., above ground, mkd. 4/4 on W face, bears N. 80° W., 22 lks. dist.</p>
60.25	<p>Point for the CN 1/16 sec. cor. of sec. 20.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R4E C N 1/16 S20 C 1975</p>
	<p>Cor. of fences, bears N. 10° W., 19 lks. dist.; fences extend Southerly and Westerly.</p>
	<p>From this point a steel rod, 1 in. diam., projecting 4 ins. above ground, bears S. 69° W., 12.5 lks. dist.</p>
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W of cor.</p>
	<p>Deposit broken glass at base of the iron post.</p>
60.50	<p>Power line, bears E and W.</p>
60.70	<p>Gravel road, bears E and W.</p>
74.70	<p>Wash, 30 lks. wide, 6 ft. deep, drains S. 55° E., from N. 30° W.</p>
80.21	<p>The ¼ sec. cor. of secs. 17 and 20.</p>
	<hr/> <p>From the ¼ sec. cor. of secs. 20 and 21.</p>
	<p>N. 89°13' W., on the E and W centerline of sec. 20.</p>
	<p>Over gently rolling land, through scattering undergrowth.</p>
3.00	<p>Dirt road, bears S. 40° E. and N. 40° W.</p>
16.10	<p>Track road, bears N. 40° E. and S. 40° W.</p>
39.77	<p>The C¼ sec. cor. of sec. 20.</p>
41.00	<p>Track road, bears NE and SW.</p>
42.60	<p>Track road, bears N. 70° E. and S. 70° W.</p>
46.80	<p>Power line, bears S. 30° E. and N. 30° W.</p>
59.60	<p>Graded dirt road, bears N and S.</p>
59.76	<p>Point for the CW 1/16 sec. cor. of sec. 20.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 9 ins. below the surface on the W edge of the road, with brass cap mkd.</p>

Survey of Subdivision of Sec. 20,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS

T15N R4E
W 1/16
C ————— C
S20
1975

from which

An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears S. 45° W., 37.9 lks. dist., with brass cap mkd. T15N R4E S20 CW 1/16 RM 25 ft. 1975 and an arrow pointing to the cor.

An iron post, 28 ins. long, 2½ ins. diam., set 20 ins. in the ground, for a reference monument, bears N. 45° W., 30.3 lks. dist., with brass cap mkd. T15N R4E S20 CW 1/16 RM 20 ft. 1975 and an arrow pointing to the cor.

A reinforcement bar, ½ in. diam., bears N. 65°53' W., 14.7 lks. dist.

Raise a mound of stone, 3 ft. base, 1½ ft. high, W of both reference monuments.

- 72.30 Descend into river bottom, bears S. 40° E. and N. 40° W.
- 73.80 Left bank of Verde River, 1 to 4 ft. banks, bears S. 40° E. from S. 70° W.
- 74.80 Left bank of Verde River, 1 to 4 ft. banks, bears SE and NW.
- 79.75 The true point for the ¼ sec. cor. of secs. 19 and 20.

Subdivision of NW¼ sec. 20

From the CW 1/16 sec. cor. of sec. 20.

N. 0°05' E., on the N and S centerline of the NW¼ of sec. 20.

Over graded dirt road.

- 19.76 Cattle guard in fence, bears E and W, 14 lks. to cor. of fences extending E and S.
- 19.90 Power line, bears S. 89° E. and N. 89° W.
- 19.965 Point for the NW 1/16 sec. cor. of sec. 20 at intersection with the E and W centerline of the NW¼ of sec. 20.
- Cement a brass tablet, 3½ ins. diam., 3½ ins. stem, in bedrock, 9 ins. below the surface of road, with top mkd.

T15N R4E
NW 1/16 S20
1975

Survey of Subdivision of sec. 20,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	<p>from which</p> <p>A power pole, bears S. 81°47' E., 44.7 lks. dist., with aluminum tag mkd. 22863.</p> <p>An X BO, chiseled on W end of concrete cattle guard, bears S. 30°13' W., 19.6 lks. dist.</p>
21.30	Intersection of roads, bear SE, curving E, S and N. 20° W.
39.93	The W 1/16 sec. cor. of secs. 17 and 20.
	<hr/> <p>From the CN 1/16 sec. cor. of sec. 20.</p> <p>N. 89°12' W., on the E and W centerline of the NW¼ of sec. 20.</p> <p>Over gently rolling land, through scattering timber and medium undergrowth.</p>
14.00	Fence, bears E and W.
16.00	Power line, bears E and W.
19.98	The NW 1/16 sec. cor. of sec. 20.
39.94	The N 1/16 sec. cor. of secs. 19 and 20.
	<hr/> <p style="text-align: center;">Survey of Subdivision of sec. 22, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona</p> <hr/>
	<p>From the ¼ sec. cor. of secs. 22 and 27.</p> <p>N. 0°21' E., on the N and S centerline of sec. 22.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p>
11.00	Fence, bears S. 30° E. and N. 30° W.
36.80	Wash, 60 lks. wide, 2 ft. deep, drains N. 25° W.
39.20	Wash, 140 lks. wide, 4 ft. deep, drains N. 40° W.
41.95	Point for the C¼ sec. cor. of sec. 22 at intersection with the E and W centerline of sec. 22.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E C¼ S22 1975</p>
	<p>Raise a mound of stone, 3 ft. base, 3 ft. high, W of cor.</p>
62.77	Point for the CN 1/16 sec. cor. of sec. 22.
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 13 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.</p>

Survey of Subdivision of sec. 22,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	T15N R4E C N 1/16 S22 C 1975
65.80	Fence, bears S. 80° E. and N. 80° W.
83.59	The ¼ sec. cor. of secs. 15 and 22.
	<hr/> From the ¼ sec. cor. of secs. 22 and 23. N. 88°45' W., on the E and W centerline of sec. 22. Over rolling land, through medium timber and undergrowth.
.90	Jeep trail, bears N. 75° E. and S. 75° W.
4.10	Jeep trail, bears S. 15° E. and N. 15° W.
35.90	Knoll, bears N. 40 lks. dist.
40.45	The ¼ sec. cor. of sec. 22.
42.60	Wash, 210 lks. wide, 4 ft. deep, drains N. 30° W.
60.52	Point for the CW 1/16 sec. cor. of sec. 22. Set an iron post, 28 ins. long, 2½ ins. diam., 14 ins. in the ground, mound of stone, 3 ft. base to top, with brass cap mkd.
	T15N R4E W 1/16 C ————— C S22 1975
72.80	Oak Creek, 250 lks. wide, 3 to 6 ft. banks, course SW.
80.59	The ¼ sec. cor. of secs. 21 and 22.
	<hr/> Subdivision of NW¼ of sec. 22 <hr/> From the CW 1/16 sec. cor. of sec. 22. N. 0°19' E., on the N and S centerline of the NW¼ of sec. 22. Over rolling land, through scattering timber and medium undergrowth.
20.60	Point for the NW 1/16 sec. cor. of sec. 22, at intersection with the E and W centerline of the NW¼ of sec. 22. Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T15N R4E NW 1/16 S22 1975

Survey of Subdivision of sec. 22,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.
33.40	Oak Creek, 5 chs. wide, 2 to 6 ft. banks, course S. 30° W.
41.21	The W 1/16 sec. cor. of secs. 15 and 22.

	From the CN 1/16 sec. cor. of sec. 22.
	N. 89°22' W., on the E and W centerline of the NW ¹ / ₄ of sec. 22.
	Over rolling land, through scattering timber and undergrowth.
17.00	Fence, bears S. 8° E. and N. 8° W.
20.075	The NW 1/16 sec. cor. of sec. 22.
28.10	Oak Creek, 100 lks. wide, 2 to 6 ft. banks, course S.
33.90	Graded dirt road, bears N. 17° E. and S. 17° W. Power line, bears N. 14° E. and S. 14° W.
39.30	Wash, 30 lks. wide, 4 ft. deep, drains S. 35° E.
40.15	The point for the N 1/16 sec. cor. of secs. 21 and 22.


Survey of Subdivision of sec. 33,
T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona

From the ¹/₄ sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp., monumented by a reinforcement bar, ¹/₂ in. diam., 18 ins. long, buried 8 ins. below surface of ground. This position is harmoniously related to existing original cors., has long been recognized as the cor. by land owners, and is accepted as the best available evidence of the original corner position; not remonumented.

N. 0°01' E., on the N and S centerline of sec. 33.

Over medium rolling land, through scattering timber and undergrowth.

18.50	Fence, bears N. 55° E. and S. 55° W.
19.50	Track road, bears S. 20° W. and N. 20° E., curving East-erly.
19.625	Point selected for the witness CS 1/16 sec. cor. of sec. 33.
	Set an iron post, 28 ins. long, 2 ¹ / ₂ ins. diam., 21 ins. in the ground, with brass cap mkd.



Survey of Subdivision of sec. 33,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS	
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.
20.125	True point for the CS 1/16 sec. cor. of sec. 33, falls in a wash, 100 lks. wide, 6 ft. deep, drains S. 75° W.; impracticable to monument.
22.00	Track road, bears E and W.
23.40	Power line, bears S. 35° E. and N. 35° W.
40.25	Point for the C¼ sec. cor. of sec. 33, at intersection with the E and W centerline of sec. 33. Set an iron post, 28 ins. long, 2½ ins. diam., 7 ins. in the ground, mound of stone, 4 ft. base to top, with brass cap mkd. T15N R4E C¼ S33 1975
60.605	Point for the CN 1/16 sec. cor. of sec. 33. Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, mound of stone, 3½ ft. base to top, with brass cap mkd. T15N R4E C N 1/16 S33 C 1975
80.96	The ¼ sec. cor. of secs. 28 and 33. From the ¼ sec. cor. of secs. 33 and 34. N. 88°42' W., on the E and W centerline of sec. 33. Over rolling land, through scattering timber and medium undergrowth.
39.66	The C¼ sec. cor. of sec. 33.
49.40	Power line, bears S. 20° E. and N. 20° W.
56.00	Track road, bears Northerly and Southerly.
57.60	Fence, bears S. 7° E. and N. 7° W.
59.69	Point for the CW 1/16 sec. cor. of sec. 33. Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd. T15N R4E W 1/16 C ——— C S33 1975

Survey of Subdivision of sec. 33,
T. 15 N., R. 4 E., G&SRM, Arizona

CHAINS		
	Raise a mound of stone, 2½ ft. base, 2 ft. high, N of cor.	
66.40	OK Ditch, 20 lks. wide, flows S. 3° E.	
68.90	Left bank of Verde River, 5 ft. banks, bear S. 30° E. and N. 30° W.	
72.90	Right bank of Verde River.	
79.72	The ¼ sec. cor. of secs. 32 and 33.	
<hr/> Subdivision of SW¼ of sec. 33 <hr/>		
	From the W 1/16 sec. cor. of secs. 4 and 33 on the S. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., projecting 4 ins. above ground, with a mesquite post, 3 ins. diam., projecting 2 ft. above ground, 2 lks. N, with brass cap mkd.	
	T15N R4E W 1/16 $\frac{S33}{S 4}$ T14N 1972	
	N. 0°06' W., on the N and S centerline of the SW¼ of sec. 33.	
	Over rolling land, through scattering timber and medium undergrowth.	
17.32	Point selected for the witness SW 1/16 sec. cor. of sec. 33.	
	Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.	
	WC T15N R4E SW 1/16 \uparrow S33 1975	
	Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.	
18.10	Right bank of Verde River, 3 to 4 ft. banks, bears S. 35° E. and N. 35° W.	
20.22	True point for the SW 1/16 sec. cor. of sec. 33, at intersection with the E and W centerline of the SW¼ of sec. 33, falls in river bed; impracticable to monument.	
22.70	Left bank of Verde River.	
24.20	OK Ditch, 20 lks. wide, flows S. 30° E.	
35.60	Fence, bears S. 57° E. and N. 57° W.	
36.40	Track road, bears S. 50° E. and N. 50° W.	
40.45	The CW 1/16 sec. cor. of sec. 33.	

Survey of Subdivision of sec. 33,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>From the true point for the CS 1/16 sec. cor. of sec. 33.</p> <p>N. 88°58' W., on the E and W centerline of the SW$\frac{1}{4}$ of sec. 33.</p> <p>Along a wash, draining S. 75° W.</p> <p>2.00 Leave wash, 100 lks. wide, 6 ft. deep, drains S. 75° W.; thence over rolling land, through scattering timber and medium undergrowth.</p> <p>5.50 Track road, bears S. 40° E. and N. 40° W.</p> <p>16.00 OK Ditch, 20 lks. wide, flow S. 35° E.</p> <p>17.00 Left bank of Verde River, 6 to 10 ft. banks, bears S. 35° E. and N. 35° W.</p> <p>19.99 The true point for the SW 1/16 sec. cor. of sec. 33.</p> <p>21.50 Right bank of Verde River.</p> <p>39.98 The S 1/16 sec. cor. of secs. 32 and 33.</p>
	<p style="text-align: center;">Subdivision of NW$\frac{1}{4}$ of sec. 33</p> <hr/> <p>From the CW 1/16 sec. cor. of sec. 33.</p> <p>N. 0°06' W., on the N and S centerline of the NW$\frac{1}{4}$ of sec. 33.</p> <p>Over gently rolling land, through scattering timber and medium undergrowth.</p> <p>.75 Wash, 20 lks. wide, 2 ft. deep, drains irregularly W.</p> <p>19.00 Fence, bears S. 8° E. and N. 8° W., 64 lks. to cor. of fences extending S. 8° E. and NW.</p> <p>19.70 Track road, bears S. 10° E. and N. 10° W.</p> <p>20.35 Point for the NW 1/16 sec. cor. of sec. 33, at intersection with the E and W centerline of the NW$\frac{1}{4}$ of sec. 33.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E NW 1/16 S33 1975</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of cor.</p> <p>38.20 Power line, bears S. 17° E. and N. 17° W.</p> <p>40.69 The W 1/16 sec. cor. of secs. 28 and 33.</p> <hr/> <p>From the CN 1/16 sec. cor. of sec. 33.</p> <p>N. 88°43' W., on the E and W centerline of the NW$\frac{1}{4}$ of sec. 33.</p>

Survey of Subdivision of sec. 33,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>Over rolling land, through scattering timber and medium undergrowth.</p> <p>15.60 Power line, bears S. 15° E. and N. 15° W.</p> <p>20.08 The NW 1/16 sec. cor. of sec. 33.</p> <p>20.50 Track road, bears S. 40° E. and N. 40° W.</p> <p>21.10 Fence, bears S. 55° E. and N. 55° W.</p> <p>31.35 OK Ditch, 20 lks. wide, flows S. 5° E.</p> <p>33.90 Left bank of Verde River, 2 to 3 ft. banks, bears S. 15° E. and N. 15° W.</p> <p>39.95 Right bank of Verde River.</p> <p>40.15 The N 1/16 sec. cor. of secs. 32 and 33.</p>
	<p style="text-align: center;">Survey of Subdivision of sec. 35, T. 15 N., R. 4 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the ¼ sec. cor. of secs. 2 and 35 on the S. bdy. of the Tp.</p> <p>N. 1°43' E., on the N and S centerline of sec. 35.</p> <p>Over rolling land, through scattering timber and undergrowth.</p> <p>19.90 Point for the CS 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over a cross chiseled in solid limestone, mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R4E</p> <p>C</p> <p>S 1/16 S35</p> <p>C</p> <p>1975</p> </div> <p>Cor. is near the W edge of a limestone outcropping, 15 ft. high.</p>
	<p>39.80 Point for the C¼ sec. cor. of sec. 35, at intersection with the E and W centerline of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground over a cross chiseled in limestone bedrock, mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T15N R4E</p> <p>C¼ S35</p> <p>1975</p> </div>

Survey of Subdivision of sec. 35,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	
	<p>from which</p> <p>A juniper, 14 ins. diam., bears N. 29° W., 52 lks. dist., mkd. C$\frac{1}{4}$ S35 BT.</p> <p>66.30 Dirt Forest Service road, No. 119A, bears N. 50° E. and S. 50° W.</p> <p>66.80 Wash, 40 lks. wide, 8 ft. deep, drains S. 65° W.</p> <p>78.51 The $\frac{1}{4}$ sec. cor. of sec. 35 on the N. bdy. of the sec.</p>
	<p>From the $\frac{1}{4}$ sec. cor. of sec. 35 only on the E. bdy. of the sec.</p> <p>N. 89°35'30" W., on the E and W centerline of sec. 35.</p> <p>Over rolling land, through scattering timber and medium undergrowth.</p> <p>37.70 The C$\frac{1}{4}$ sec. cor. of sec. 35.</p> <p>57.405 Point for the CW 1/16 sec. cor. of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E W 1/16 C ————— C S35 1975</p> <p>77.11 The $\frac{1}{4}$ sec. cor. of secs. 34 and 35.</p>
	<p style="text-align: center;">Subdivision of SW$\frac{1}{4}$ of sec. 35.</p> <hr/> <p>From the W 1/16 sec. cor. of secs. 2 and 35 on the S. bdy. of the Tp.</p> <p>N. 1°16' E., on the N and S centerline of the SW$\frac{1}{4}$ of sec. 35.</p> <p>Over rolling land, through scattering timber and under- growth.</p> <p>19.83 Point for the SW 1/16 sec. cor. of sec. 35, at inter- section with the E and W. centerline of the SW$\frac{1}{4}$ of sec. 35.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R4E SW 1/16 S35 1975</p>

Survey of Subdivision of sec. 35,
T. 15 N., R. 4 E., G&SRM., Arizona

CHAINS	<p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W of cor.</p> <p>39.68 The CW 1/16 sec. cor. of sec. 35.</p> <hr/> <p>From the CS 1/16 sec. cor. of sec. 35.</p> <p>N. 89°22' W., on the E and W centerline of the SW¼ of sec. 35.</p> <p>Over rolling land, through scattering timber and undergrowth.</p> <p>19.57 The SW 1/16 sec. cor. of sec. 35</p> <p>39.13 The S 1/16 sec. cor. of secs. 34 and 35.</p>
	<p>GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about five miles southeast of the town of Cottonwood, Arizona. The southwest portion of the township is drained by the Verde River, which has a south-southeast course, entering the township near the southwest corner of Section 7 and leaving the township through Section 33. Oak Creek enters the township near the corner of Sections 3 and 4 taking a southerly winding course where it drains into the Verde River in Section 20. The land varies from heavily rolling to nearly level, ranging from 3,200 feet to 3,710 feet above sea level. A small portion of the land along the Verde River and Oak Creek is under irrigation.</p> <p>Access is by way of a paved Forest Service road, No. 119, which crosses the northern portion of the township. State Highway No. 279 crosses the southwest corner of the township. There are numerous unimproved or lightly graveled roads.</p> <p>Land along the Verde River and Oak Creek is covered with scattered to dense growth of cottonwoods and willows. Portions of the land are covered with mesquite, cedar, catclaw, creosote brush and cacti. The remainder is naturally open or has been cleared.</p> <p>The small community of Cornville is located in the southwest corner of Section 3, northwest corner Section 10, northeast corner Section 9 and the southeast corner of Section 4. There is an automobile repair shop and a combination store and gas station located in the southeast corner of Section 3. Several residential subdivisions are being developed throughout the township.</p> <p>The mean of a considerable number of observations of the magnetic declination throughout the township is 13°30' E., with a range of 45' in local attraction.</p>

CERTIFICATE OF SURVEY

(I) ~~(ME)~~, Harry K. Smith, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 19th day

of October, 1973, (I) ~~(ME)~~ have made a dependent resurvey of a portion of the Exterior Boundaries and Subdivisional Lines and a dependent resurvey of a portion of the subdivision of Section 18, and surveyed a portion of the subdivisional lines and surveyed subdivisions in Sections 1, 3, 7, 9, 10, 14, 15, 17, 18, 19, 20, 22, 33 and 35, Township 15 North, Range 4 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(NS)~~ and under (my) ~~(SM)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 24, 1976

(Date)

Harry K. Smith

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the Exterior Boundaries and Subdivisional Lines and dependent resurvey of a portion of the subdivisions of Section 18, and the survey of a portion of the subdivisional lines and survey of subdivisions in Sections 1, 3, 7, 9, 10, 14, 15, 17, 18, 19, 20, 22, 33 and 35, T. 15 N., R. 4 E., G&SRM., Arizona,

executed by Harry K. Smith, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

DEC 04 1979

(Date)

J. Voorhes

(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626