

FIELD NOTES

OF THE
 DEPENDENT RESURVEY OF
 A PORTION OF THE NORTH BOUNDARY
 A PORTION OF THE SUBDIVISIONAL LINES,
 A PORTION OF THE SUBDIVISION IN SECTION 13,
 AND
 THE SURVEY OF SUBDIVISION IN CERTAIN SECTIONS
 OF
 TOWNSHIP 9 NORTH, RANGE 22 EAST,

Of the GILA AND SALT RIVER Meridian,
 In the State of ARIZONA

EXECUTED BY
 SUPERVISORY
 HARRY K. SMITH, CADASTRAL SURVEYOR

Under special instructions dated JUNE 23, 19 78, approved JUNE 23, 1978,
 AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED AND APPROVED JUNE 5, 1979

, which provided for the surveys included under U.S. Survey/Group
 Number 605, and assignment instructions dated JUNE 23, 19 78.
 AND JUNE 5, 1979

Survey commenced JUNE 26, 19 78

Survey completed JUNE 8, 19 79



1A

BOOK 5096

INDEX DIAGRAM

Township 9 North, Range 22 East

			5	3	2
6	5	4	31 8	24 2	18 1
			30	23	17
7	8	9	29 10	22 11	15 12
			27	21	14
18	17	16	25 15	19 14	11 13
			24	18	10
19	20	21	22	23	24
30	29	28	27	26	9 25
				9	
31	32	33	34	35	7 36

- Subdivision of sec. 13 p. 32
- Subdivision of sec. 3 p. 38
- Subdivision of sec. 10 p. 40
- Subdivision of sec. 11 p. 47
- Subdivision of sec. 12 p. 48
- Subdivision of sec. 14 p. 52
- Subdivision of sec. 15 p. 54

Township 9 North, Range 22 East,
Gila and Salt River Meridian, Arizona

CHAINS

The history of surveys of Township 9 North, Range 22 East, Gila and Salt River Meridian, Arizona, is as follows:

The township boundaries and subdivisional lines were surveyed in 1883 by O. D. Wheeler, Deputy Surveyor. Portions of the south boundary (2nd Standard Parallel North) were resurveyed by Jesse B. Wright, U. S. Deputy Surveyor in 1908 and by William Strover, U. S. Examiner of Surveys in 1909. In 1914, C. A. Long, Surveyor, U. S. Forest Service, resurveyed a portion of the subdivisional lines, subdivided section 13, and surveyed Homestead Entry Survey No. 206 and Homestead Entry Survey No. 208. In 1915, Sidney E. Blout, U. S. Surveyor, resurveyed portions of the south, west and north boundaries and a portion of the subdivisional lines. In 1927, Thomas F. Myers, Chief Surveyor, Forest Service, resurveyed a portion of the subdivisional lines and surveyed Exchange Survey No. 649. A portion of the east boundary was resurveyed in 1967 by Paul G. Bauer, Kenneth D. Herman, Gary T. Oviatt and Jerrold E. Knight, Cadastral Surveyors.

The north boundary of the Fort Apache Indian Reservation through the township was surveyed in 1906 by Jesse B. Wright, U. S. Deputy Surveyor, resurveyed in 1915 by Sidney E. Blout, U. S. Surveyor, and a portion was resurveyed by Marlin G. Livermore II, Cadastral Surveyor, in 1970. Certain corners were remonumented in 1966 by Robert F. Johnson, Supervisory Surveying Technician, in 1968 by Howard Thomas, Cadastral Surveyor, in 1970 by Marlin G. Livermore II, Cadastral Surveyor, and in 1975 by Paul L. Reeves, Cadastral Surveyor. Numerous private surveys have also been performed in the area.

The following notes describe the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and a portion of the subdivision in section 13, with the survey of subdivisions in certain sections of Township 9 North, Range 22 East, of the Gila and Salt River Meridian, Arizona.

The resurvey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions and Supplemental Special Instructions for Group No. 605, Arizona, dated June 23, 1978 and June 5, 1979.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances were measured with the Zeiss, SM-4.

Preliminary to the resurvey the lines of previous surveys and resurveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the standard corner of sections 35 and 36, on the south boundary of the township, as scaled from the Quadrangle Map "Lakeside, Ariz.", published by the U. S. Geological Survey in 1977, is as follows:

Latitude 34°07.5' N. Longitude 109°58.2' W.

Township 9 North, Range 22 East,
Gila and Salt River Meridian, Arizona

CHAINS

The mean magnetic declination is $14^{\circ}00'$ E.

Dependent Resurvey of a Portion of the N. Bdy.,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

(Restoring the 1883 survey by O. D. Wheeler)

Beginning at the Tp. cor. of Tps. 9 and 10 N., Rs. 22 and 23 E., monumented with an iron post, 3 ins. diam., set in a mound of stone, 4 ft. base, 2 ft. high, to top, with brass cap mkd. as described in the official record of the 1935 resurvey from which

An alligator juniper, 9 ins. diam., mkd. in 1935, bears N. $73\frac{1}{4}^{\circ}$ E., 47 lks. dist., mkd. BT.

A stump hole, bears N. $81\frac{1}{4}^{\circ}$ E., 66 lks. dist.; a downed pine, 36 ins. diam., mkd. in 1883, is lying alongside with scribe marks visible but not legible.

A ponderosa pine, 28 ins. diam., mkd. in 1935, bears S. $7\frac{1}{2}^{\circ}$ E., 275 lks. dist., mkd. T9N R23E S6 BT.

A ponderosa pine, 24 ins. diam., mkd. in 1883, bears S. $60\frac{1}{2}^{\circ}$ W. 69 lks. dist., mkd. with a healed blaze.

An oak, 14 ins. diam., mkd. in 1883, bears N. $42\frac{1}{2}^{\circ}$ W., 27 lks. dist., mkd. with a healed blaze.

S. $89^{\circ}57'$ W., bet. secs. 1 and 36.

Over rolling land, through dense timber.

17.90 Track road, bears S. 10° E. and N. 10° W.

40.16 The $\frac{1}{4}$ sec. cor. of secs. 1 and 36, monumented with a basalt stone, 16 x 13 x 9 ins., set in a mound of stone, 2 ft. base, 6 ins. high, mkd. $\frac{1}{4}$ on the N face, from which the original bearing trees

An oak, 11 ins. diam., bears N. 5° E., 33 lks. dist., mkd. with a healed blaze. (Record, 35 lks. dist.)

A ponderosa pine, 16 ins. diam., bears S. 56° E., 38 lks. dist., mkd. with a healed blaze. (Record, 25 lks. dist.)

At the cor. point

Set an iron post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 22 ins. in the ground, with brass cap mkd.

T10N R22E

$\frac{1}{4}$ S36
S 1

T9N

1978

from which new bearing trees

Dependent Resurvey of a Portion of the N. Bdy.,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 9 ins. diam., bears S. 9° E., 64 lks. dist., mkd. 1/4 S1 BT.</p> <p>An alligator juniper, 17 ins. diam., bears N. 70° W., 18 lks. dist., mkd. 1/4 S36 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N of the cor.</p> <hr/> <p>S. 89°54' W., beginning new measurement.</p>
20.80	Track road, bears S and N, curving NE.
40.06	<p>The cor. of secs. 1, 2, 35 and 36, monumented with a basalt stone, 23 x 15 x 13 ins., loosely set in a scattered mound of stone, mkd. with 1 groove on the E and 5 grooves on the W faces, from which the original bearing trees</p> <p>An alligator juniper, 27 ins. diam., bears N. 27 1/4° E., 44 lks. dist., mkd. R22E S through a partially healed blaze. (Record, N. 21° E., 45 lks. dist.)</p> <p>A ponderosa pine, 26 ins. diam., bears S. 1 3/4° E., 111 lks. dist., mkd. T9N R22E S2 T. (Record, S. 12° E., 109 lks. dist.)</p> <p>A white oak, 12 ins. diam., bears N. 84° W., 40 lks. dist., mkd. with a healed blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T10N R22E S35 S36 S 2 S 1 T9N 1978</p> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 9 ins. diam., bears N. 60 1/2° E., 49.5 lks. dist., mkd. T10N R22E S36 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears S. 51 3/4° E., 53 lks. dist., mkd. T9N R22E S1 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears S. 47 1/2° W., 81 lks. dist., mkd. T9N R22E S2 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 50° W., 61.5 lks. dist., mkd. T10N R22E S35 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p> <hr/> <p>S. 89°55' W., bet. secs. 2 and 35.</p>

Dependent Resurvey of a Portion of the N. Bdy.,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS		
	Over rolling land, through dense timber.	
7.20	Track road, bears N and S.	
19.92	Point for the E 1/16 sec. cor. of secs. 2 and 35.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T10N R22E E 1/16 $\frac{S35}{S 2}$ T9N 1978</p>	
	from which	
	<p style="text-align: center;">An alligator juniper, 5 ins. diam., bears S. 4° W., 40.5 lks. dist., mkd. E 1/16 S2 BT.</p>	
	<p style="text-align: center;">A ponderosa pine, 9 ins. diam., bears N. 30° W., 61.5 lks. dist., mkd. E 1/16 S35 BT.</p>	
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.	
36.80	Fence, bears irregularly N and S.	
39.84	The 1/4 sec. cor. of secs. 2 and 35, monumented with a basalt stone, 15 x 12 x 6 ins., set in a scattered mound of stone, mkd. 1/4 on the N face.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T10N R22E $\frac{1}{4}$ $\frac{S35}{S 2}$ T9N 1978</p>	
	from which	
	<p style="text-align: center;">A ponderosa pine, 8 ins. diam., bears N. 6° E., 40 lks. dist., mkd. 1/4 S35 BT.</p>	
	<p style="text-align: center;">A juniper, 5 ins. diam., bears S. 58° W., 11 lks. dist., mkd. 1/4 S2 BT.</p>	
	Deposit the mkd. stone alongside the iron post.	
	Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.	
	Cor. is in a N and S fence.	
	<p style="text-align: center;">_____</p>	
	S. 89°51' W., beginning new measurement.	
29.30	Timber Mesa Fire Road, bears N. 30° E. and S. 30° W.	

Dependent Resurvey of a Portion of the N. Bdy.,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

	CHAINS		
	39.83	<p>The cor. of secs. 2, 3, 34 and 35, monumented with a basalt stone, 16 x 8 x 7 ins., loosely set in a scattered mound of stone, mkd. with 2 grooves on the E and 4 grooves on the W faces, from which the original bearing trees</p> <p>An alligator juniper, 32 ins. diam., bears N. 18° E., 69 lks. dist., scribe marks are visible through a partially healed blaze. (Record, N. 12° E., 71 lks. dist.)</p> <p>A pine snag, 30 ins. diam., bears S. 66° E., 86 lks. dist., mkd. 22 2. (Record, S. 68° E., 83 lks. dist.)</p> <p>A pine stump, 24 ins. diam., bears N. 63° W., 174 lks. dist., tree lying on the ground alongside is mkd. T9N R22 S BT. (Record, 172 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T10N R22E S34 S35 S 3 S 2 T9N 1978</p> <p>from which new bearing trees</p> <p>An alligator juniper, 5 ins. diam., bears N. 84° E., 12.5 lks. dist., mkd. T10N R22E S35 BT.</p> <p>An alligator juniper, 4 ins. diam., bears S. 4° E., 64.5 lks. dist., mkd. T9N R22E S2 BT.</p> <p>An alligator juniper, 7 ins. diam., bears S. 40° W., 23.5 lks. dist., mkd. T9N R22E S3 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears N. 51° W., 86 lks. dist., mkd. T10N R22E S34 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p>	
	40.31	<p>S. 89°44' W., bet. secs. 3 and 34.</p> <p>Over rolling to nearly level land, through dense timber, part of which has been railed.</p> <p>The 1/4 sec. cor. of secs. 3 and 34, monumented with a basalt stone, 24 x 9 x 5 ins. loosely set in a scattered mound of stone, mkd. 1/4 on the N face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the N. Bdy.,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T10N R22E $\frac{1}{4} \frac{S34}{S3}$ T9N 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears N. 73° E., 102 lks. dist., mkd. 1/4 S34 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 43° W., 6 lks. dist., mkd. 1/4 S3 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="padding-left: 40px;">S. 89°48' W., beginning new measurement.</p> <p>5.90 Power line and track road bear S. 16° E. and N. 16° W.</p> <p>6.50 Power line, bears S. 16° E. and N. 16° W.</p> <p>17.60 Descend rocky bluff to Show Low Creek.</p> <p>20.00 Show Low Creek, 20 lks. wide, course N. 20° W.</p> <p>20.06 True point for the W 1/16 sec. cor. of sec. 3 and 34, falls in Show Low Creek, not monumented.</p> <p>20.56 Point selected for the witness W 1/16 sec. cor. of secs. 3 and 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T10N R22E W 1/16 $\frac{S34}{S3}$ > T9N 1978</p> <p>from which</p> <p style="padding-left: 40px;">A volcanic boulder, 3.5 x 3.5 x 3 ft. high above ground, bears S. 1/2° W., 30.5 lks. dist., mkd. X BO on the NW face.</p> <p style="padding-left: 40px;">A volcanic boulder, 4 x 3 x 3 ft. high, bears N. 80° W., 38 lks. dist., mkd. X BO on the NE face.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.</p> <p>40.12 The cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 2 1/2 ft. base, 15 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonu- mentation notes, from which</p> <p style="padding-left: 40px;">A pine stump, 18 ins. diam., mkd. in 1883, bears S. 32° E., 185 lks. dist., mkd. S3 BT.</p>

Dependent Resurvey of a Portion of the N Bdy.,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

CHAINS

A dead pine, 22 ins. diam., mkd. in 1883, bears N. 59° W., 183 lks. dist., mkd. with a healed blaze.

An alligator juniper, 7 ins. diam., mkd. in 1975, bears N. 11 1/2° E. 225 lks. dist., mkd. T10N R22E S34 BT.

Cor. is 4 lks. S of an E-W fence.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Arizona

(Restoring the 1915 Resurvey by Sidney E. Blout)

From the standard cor. of secs. 35 and 36, on the S bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., buried 10 ins. under the surface of a graded gravel road, with brass cap mkd. as described in the official record of the 1966 remonumentation notes by Robert F. Johnson, from which

A rotted pine stump, 22 ins. diam., mkd. in 1883, bears N. 42° E., 66 lks. dist., no marks visible.

A ponderosa pine, 10 ins. diam., mkd. in 1966, bears S. 45 1/2° E., 64 lks. dist., mkd. with a healed blaze.

An alligator juniper, 9 ins. diam., mkd. in 1966, bears S. 40° W., 81 lks. dist., mkd. T8N R22E S1 BT.

An oak, 16 ins. diam., mkd. in 1883, bears S. 49° W., 110 lks. dist., mkd. with a healed blaze.

A ponderosa pine snag, 30 ins. diam., mkd. in 1883 and in 1966, bears N. 69° W., 92 lks. dist., the original markings are T9N R22E S35 BT, and the 1966 markings are SC T9N R22E S35 BT.

The cor. is located near the S edge of a graded gravel road bearing E and W, and 45 lks. E of the center of a graded gravel road projecting N.

N. 0°24' W., bet. secs. 35 and 36.

Along the E side of a graded gravel road.

39.60 Power line, bears W and E, approximately 17 lks. dist.

40.00 Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist., falls in a graded gravel road; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of the road, with brass cap mkd.

T9N R22E

$\frac{1}{4}$

S35|S36

1979

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	<p>from which</p> <p>A fence cor., bears S. 84° E., 36.5 lks. dist.; fences extend E and S.</p> <p>The center of a manhole cover, bears S. 72 1/2° E., 21 lks. dist.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 50 1/4° E., 50 lks. dist., with brass cap mkd. T9N R22E 1/4 S36 RM 33 FT. 1979 and an arrow pointing to the cor.</p> <p>A fence cor., bears S. 46 1/2° W., 60 lks. dist.; fences extend S and W.</p> <p>A fence cor., bears N. 65° W., 55 lks. dist.; fences extend N and W.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears S. 50 1/4° W., 65.2 lks. dist., with brass cap mkd. T9N R22E 1/4 S35 RM 43 FT. 1979 and an arrow pointing to the cor.</p> <p>The cor. is located 8 lks. E of the center of a graded gravel road, presently under construction, which bears N and S, and 9 lks. N. of the center of a graded gravel road projecting W.</p> <p>The cor. is also 26 lks. W of power and telephone line, bearing N and S.</p> <p>80.00 Point for the cor. of secs. 25, 26, 35 and 36, determined at record distances from previously established bearing trees</p> <p>A ponderosa pine, 14 ins. diam., mkd. in 1966, bears S. 82 1/2° E., 165 lks. dist., mkd. T9N R22E S36 BT. (Record bearing S. 86° E.)</p> <p>A ponderosa pine, 12 ins. diam., mkd. in 1966, bears S. 57 3/4° E., 166 lks. dist., with scribe marks visible through a partially healed blaze. (Record bearing S. 61° E.)</p> <p>An oak, 19 ins. diam., mkd. in 1883, bears N. 41 1/4° W., 112 lks. dist., mkd. with legible scribe marks T 2 R. (1883 record bearing N. 40° W., 1966 record bearing N. 43° W.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. below the surface of Woodland Road, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T9N R22E</p> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S26</td> <td style="padding: 0 5px;">S25</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S35</td> <td style="padding: 0 5px;">S36</td> </tr> </table> <p>1979</p> </div> <p>from which</p> <p>A ponderosa pine, 20 ins. diam., bears N. 83 1/2° E., 64.5 lks. dist., mkd. T9N R22E S25 BT. Tree mkd. at land owners request.</p>	S26	S25	S35	S36
S26	S25				
S35	S36				

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>A re-bar 3/4 in. diam., bent over flush with the surface of the road, bears S. 72°40' W., 34.5 lks. dist.</p> <p>The cor. is located about 3 lks. W of the center of Woodland Road, which is 50 lks. wide, bearing N and S, and about 4 lks. N of the center of Homestead Road, 43 lks. wide, projecting W.</p>	
40.26	<p>N. 0°07' W., bet. secs. 25 and 26.</p> <p>Along Woodland Road.</p> <p>The 1/4 sec. cor. of secs. 25 and 26, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground, with brass cap mkd. as described in the official record of the 1915 resurvey, from which the remains of the original bearing trees</p> <p>A pine stump, 24 ins. diam., bears S. 74° E., 77 lks. dist., mkd. S25 BT. (Record S. 61° E., 75 lks. dist.)</p> <p>Cor. is in a N-S fence, near the W edge of Woodland Road, bearing N and S.</p>	
40.28	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. 89°46' W., bet. secs. 26 and 35.</p> <p>Along Homestead road.</p> <p>The 1/4 sec. cor. of secs. 26 and 35, monumented with an iron post, 1 in. diam., 10 ins. long, filled with concrete and flanged at the bottom, buried 10 ins. under ground, with a spike nail, 10 ins. long set over the cor., from which the remains of the bearing trees mkd. in 1915.</p> <p>A badly decayed pine stump, 16 ins. diam., bears S. 9 1/2° E., 109 lks. dist.</p> <p>A ponderosa pine, 15 ins. diam., bears N. 77 3/4° W., 75 lks. dist., mkd. 1/4 S26 BT. (Record bearing N. 77 3/4° E.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1 S26 4 S35 1979</p> <p>from which</p> <p>An open end pipe, 1 1/2 ins. diam., set flush with the ground, bears S. 1 1/2° W., 8.6 lks. dist. This point has been mistakenly used as the 1/4 sec. cor. of secs. 26 and 35 by some private surveyors in the area.</p> <p>Deposit the 1 in. iron post and spike nail inside the new monument.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS

The cor. is 36 lks. N of the center of Homestead Road,
bears E and W.

(Restoring the 1883 survey by O. D. Wheeler)

From the cor. of secs. 13, 18, 19 and 24, on the E bdy.
of the Tp., monumented with an iron post, 2 1/2 ins.
diam., set in a mound of stone, 3 ft. base, 2 ft. high to
top of brass cap, mkd. as described in the 1967 dependent
resurvey of the W bdy. of T. 9 N., R. 23 E., from which

A ponderosa pine, 24 ins. diam., mkd. in 1883, bears
N. 61° E., 97 lks. dist., mkd. T9N R2E 1 through a
partially healed blaze. (Record, 94 lks. dist.)

A ponderosa pine, 16 ins. diam., mkd. in 1967, bears
N. 69° E., 97 lks. dist., mkd. T9N R23E S18 BT.

A ponderosa pine, 20 ins. diam., mkd. in 1883, bears
S. 36° E., 47 lks. dist., mkd. with scribe marks
visible through a partially healed blaze. (Record
bearing S. 41° E.)

A ponderosa pine, 20 ins. diam., mkd. in 1883, bears
S. 55° E., 45 lks. dist., mkd. with scribe marks
visible through a partially healed blaze.

A ponderosa pine, 16 ins. diam., mkd. in 1883, bears
N. 27° W., 17 lks. dist., mkd. with scribe marks
visible through a partially healed blaze.

Cor. is located in a N-S fence, 15 lks. S of a fence cor.
from which fences extend N, S and W.

S. 88°30' W., bet. secs. 13 and 24.

Over rolling land, through medium timber.

25.60 Creek, with a stream of water, 5 lks. wide, 4 ins. deep,
course N. 40° W.

31.80 Power line, bears S and N, turning W.

32.70 Power line, bears S and N, turning W.

38.13 The 1/4 sec. cor. of secs. 13 and 24, monumented with a
basalt stone, 12 x 12 x 6 ins., mkd. 1/4 on one face,
loosely set in a scattered mound of stone and alongside a
re-bar, 3/8 in diam., 15 ins. long, projecting 2 ins.
above ground.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins.
in the ground, with brass cap mkd.

T9N R22E

$\frac{1}{4}$ S13

$\frac{4}{4}$ S24

1978

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>from which</p> <p>A power pole, bears N. 35° E., 128 lks. dist.</p> <p>A fence cor., bears S. 45° E., 3.5 lks. dist., fences extend E, S and W.</p> <p>A power pole, bears N. 4° W., 42.5 lks. dist.</p> <p>Deposit the mkd. stone and reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N of the cor.</p> <hr/> <p>(Restoring the 1914 resurvey by C. A. Long and subsequent resurvey by Thomas F. Myers in 1927)</p> <hr/> <p>From the cor. of secs. 13, 14, 23 and 24, monumented with an iron post, 36 ins. long, 2 ins. diam., bent over, 4 ins. above ground, with brass cap mkd. as described in the 1927 resurvey.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E S14 S13 S23 S24 1978</p> <p>from which</p> <p>A fence cor., bears South, 3.5 lks. dist.; fences extend N, S and E.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 61° W., 225 lks. dist., mkd. T9N R22E S23 BT.</p> <p>Deposit the bent iron post alongside the new monument.</p> <p>Cor. is 29 lks. E of the center of a graded cindered road, bears N and S.</p> <p>N. 0°41' E., bet. secs. 13 and 14.</p> <p>Along the E edge of a graded cindered road.</p>	
9.40	Porter Creek, 30 lks. wide, course W.	
19.71	The S 1/16 sec. cor. of secs. 13 and 14, monumented with a re-bar, 24 ins. long, 3/8 in. diam., buried 1 in. under ground in the center of a N-S graded cindered road. This position is harmoniously related to existing original cors., has been used by private surveyors in the area and is accepted as the cor. position.	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	<p>At the cor. point</p> <p>Set an iron post, 12 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E S 1/16 S14 S13 1978</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears N. 41°34' E., 164.2 lks. dist., with brass cap mkd. T9N R22E S 1/16 S13 RM 108.4 FT. 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 74°05' E., 188 lks. dist., mkd. S 1/16 S13 BT.</p> <p style="padding-left: 40px;">A fence cor., bears N. 89°45' E., 35.3 lks. dist.; fences extend E and S.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Cor. is 31 lks. W of a N-S telephone line and 63 lks. E of a N-S power line.</p> <p>From this point, the point for Cor. No. 1 of Homestead Entry Survey No. 206, bears N. 89°27' E., 50 lks. dist., hereinafter described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°43' E., beginning new measurement.</p> <p>Along the center of a graded cindered road.</p> <p>19.71 The 1/4 sec. cor. of secs. 13 and 14, monumented with a re-bar, 24 ins. long, 3/8 in. diam., buried 3 ins. under ground in the center of a N-S graded cindered road. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the best available evidence of the original cor. position</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 31 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1/4 S14 S13 1978</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45° E., 151.5 lks. dist., with brass cap mkd. T9N R22E 1/4 S13 RM 100 FT. 1978 and an arrow pointing to the cor.</p> <p>Reset the re-bar alongside the iron post.</p>
--------	---

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>Cor. is 42 lks. W of a N-S telephone line and 43 lks. E of a N-S powerline.</p> <hr/> <p>N. 0°54' E., beginning new measurement.</p>	
19.74	<p>Point for the N 1/16 sec. cor. of secs. 13 and 14, determined from Cor. No. 2 of Homestead Entry Survey No. 206, is in the center of a graded cindered road, bears S and N, curving easterly. This position was established by projecting a line S. 88°22' W., from the point for Cor. 3 of Homestead Entry Survey No. 206, hereinafter described, through Cor. No. 2 of Homestead Entry Survey No. 206, record dist. of 50 lks., thence N. 0°54' E., along the sec. line bet. secs. 13 and 14, record dist., 50 lks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E N 1/16 S14 S13 1978</p> <p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, in a concrete base, for a reference monument, bears S. 86°33' E., 106 lks. dist., mkd. T9N R22E N 1/16 S13 RM 70 FT. 1977 and an arrow pointing to the cor.</p> <p>Cor. No. 2 of Homestead Entry Survey No. 206, bears S. 45°30' E., 69.3 lks. dist., monumented with a malpais stone, firmly set, 9 x 8 x 7 ins. above ground, mkd. 2 HES 206 on the SE face and a cross on top.</p> <p>A power pole, bears N. 87° W., 47.5 lks. dist., from which lines extend E and S.</p> <p>Cor. is in line with fences extending easterly and westerly.</p> <hr/> <p>N. 0°39' E. beginning new measurement.</p>	
19.72	<p>The cor. of secs. 11, 12, 13 and 14, monumented with a malpais stone, 21 x 18 x 12 ins., firmly set 15 ins. in the ground, mkd. with 1 notch on the E and 4 notches on the S edges.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E S11 S12 S14 S13 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
	<p>Raise a mound of stone, 4 ft. base, 3 ft. high, W of the cor.</p> <p>Cor. is 75 lks. W of an abandoned N-S fence.</p> <hr/> <p>(Restoring the 1914 resurvey by C. A. Long)</p> <hr/> <p>From the true point for the cor. of secs. 7, 12, 13 and 18, on the E bdy. of the Tp., determined at record bearing and dist. from an original bearing tree, falls in Porter Creek where it is impractical to set a monument, from which</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., mkd. in 1883, bears S. 63° W., 186 lks. dist., mkd. T9N R22E S13, through a partially healed blaze.</p> <p>From this point, the witness cor. of secs. 7, 12, 13 and 18, set in 1967, bears N. 0°01' W., 124 lks. dist., monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 2 1/2 ft. base, 12 ins. high, to top, with brass cap mkd. as described in the official notes of the 1967 dependent resurvey of the W bdy. of T. 9 N., R. 23 E. (Record, N. 0°01' W., 100 lks. dist.)</p> <p>from the witness cor., the trees mkd. in 1967</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N. 17 1/4° E., 54 lks. dist., mkd. WC T9N R23E S7 BT.</p> <p style="padding-left: 40px;">A pine, 15 ins. diam., bears S. 57 1/4° E. 17 lks. dist., mkd. WC T9N R23E S18 BT.</p> <p>A mound of stone, 3 ft. base, 2 ft. high, is W of the witness cor.</p> <p>Add the date 1978 to the iron post.</p> <p>S. 87°57' W., bet. secs. 12 and 13.</p> <p>Over rolling land, through medium timber.</p> <p>Topography for entire mile as scaled from U. S. Geological Survey Quadrangle Map, "LAKESIDE, ARIZ.", published in 1977.</p>
9.10	Irrigation ditch, flows SW.
13.30	Blacktop road, bears N. 65° E. and S. 65° W.
19.39	Point for the E 1/16 sec. cor. of secs. 12 and 13.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E E 1/16 $\frac{S12}{S13}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 81° E., 23 lks. dist., mkd. E 1/16 S12 BT.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
	<p>An alligator juniper, 11 ins. diam., bears N. 64° W., 66 lks. dist., mkd. E 1/16 S12 BT.</p> <p>Raise a mound of stone, 3 ft. base, 3 1/2 ft. high, N of the cor.</p> <p>Cor. is 10 lks. N of an E-W fence.</p>
38.78	<p>The 1/4 sec. cor. of secs. 12 and 13, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1975 remonumentation notes, from which the tree mkd. in 1975</p> <p>An alligator juniper, 8 ins. diam., bears N. 73° E., 23 lks. dist., mkd. 1/4 S12 BT.</p> <hr/> <p>S. 88°01' W., beginning new measurement.</p>
4.40	Track road, bears S. 50° E. and N. 50° W.
4.90	Irrigation ditch, flows N. 50° W.; enter nearly level open land, edge bears S. 50° E. and N. 50° W.
19.365	Point for the W 1/16 sec. cor. of secs. 12 and 13, not monumented.
38.73	The cor. of secs. 11, 12, 13 and 14.
	<hr/> <p>(Restoring the 1883 survey by O. D. Wheeler)</p> <hr/> <p>N. 1°04' E., bet. secs. 11 and 12.</p> <p>Over level open land.</p> <p>Topography as scaled from U. S. Geological Survey Quadrangle Map, "LAKESIDE, ARIZ.", published in 1977.</p>
19.38	Fence, bears E and W; enter scattering to medium timber.
19.79	Point for the S 1/16 sec. cor. of secs. 11 and 12.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E S 1/16 S11 S12 1978</p> <p>from which</p> <p>An alligator juniper, 6 ins. diam., bears N. 39° E., 30 lks. dist., mkd. S 1/16 S12 BT.</p> <p>An alligator juniper, 6 ins. diam., bears N. 65° W., 119 lks. dist., mkd. S 1/16 S11 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p>
28.10	Irrigation ditch, flows NW.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS						
30.00	Enter rolling land, covered with medium to dense timber, edge bears SE and NW.					
38.50	Track road, bears SE and NW.					
38.80	Fence, bears S. 35° E. and N. 35° W.					
39.58	<p>The 1/4 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., projecting 4 ins. above a mound of stone, 2 1/2 ft. base, 1 ft. high, with brass cap mkd. as described in the official record of the 1975 remonumentation notes, from which the trees mkd. in 1975</p> <p style="padding-left: 40px;">An alligator juniper, 18 ins. diam., bears N. 89° E., 55 lks. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears N. 62° W., 35 lks. dist., mkd. 1/4 S11 BT.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°04' E., beginning new measurement.</p>					
35.60	Jeep trail, bears NE and SW.					
39.47	<p>The cor. of secs. 1, 2, 11 and 12, monumented with a basalt stone, 19 x 12 x 8 ins., firmly set in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. with 1 notch on the E and 5 notches on the S edges, from which the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 32 ins. diam., bears N. 49 1/2° E., 80 lks. dist., mkd. R22E 1. (Record bearing, N. 70° E.)</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 51 3/4° W., 10 lks. dist., mkd. with a healed blaze. (Record, S. 35° W., 12 lks. dist.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T9N R22E</p> <table style="margin: 0 auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 2</td> <td style="padding: 0 5px;">S 1</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S11</td> <td style="padding: 0 5px;">S12</td> </tr> </table> <p>1978</p> </div> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 32° E., 44.5 lks. dist., mkd. T9N R22E S1 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 20° E., 55.5 lks. dist., mkd. T9N R22E S12 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 75° W., 65 lks. dist., mkd. T9N R22E S2 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p>	S 2	S 1	S11	S12	
S 2	S 1					
S11	S12					

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>From the cor. of secs. 1, 6, 7 and 12, on the E bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 20 ins. high, to top, with brass cap mkd. as described in the official record of the 1967 resurvey of the W bdy. of T. 9 N., R. 23 E., from which</p> <p>A pine, 18 ins. diam., mkd. in 1967, bears N. 86 1/4° E., 53 lks. dist., mkd. T9N R23E S6 BT.</p> <p>A pine stump, 22 ins. diam., bears S. 40 1/2° E., 134 lks. dist.; tree mkd. in 1883 is lying alongside, mkd. T9N R23E S7.</p> <p>A pine, 10 ins. diam., mkd. in 1967, bears S. 40 1/2° E., 44 lks. dist., mkd. T9N R23E S7 BT.</p> <p>A pine, 7 ins. diam., mkd. in 1967, bears S. 51 1/4° W., 47 lks. dist., scribe marks are visible through a partially healed blaze.</p> <p>A white oak snag, 16 ins. diam., mkd. in 1883, bears N. 84 1/2° W., 26 lks. dist., mkd. T9N R22 S1. (Record bearing, N. 89° W.)</p> <p>A pine, 10 ins. diam., mkd. in 1967, bears N. 21 3/4° W., 59 lks. dist., mkd. T9N R22E S1 BT.</p> <p>S. 83°42' W., bet. secs. 1 and 12.</p> <p>Over rolling land, through dense timber.</p> <p>30.40 Jeep Trail, as scaled from U. S. Geological Survey Quadrangle Map, "LAKESIDE, ARIZ.", bears N and S.</p> <p>37.09 The 1/4 sec. cor. of secs. 1 and 12, monumented with an unmarked stone, 19 x 14 x 10 ins., firmly set in a mound of stone, 2 ft. base, 1 ft. high, from which the original bearing trees</p> <p>A ponderosa pine, 22 ins. diam., bears N. 31° E., 43 lks. dist., mkd. with a healed blaze. (Record, N. 20° E., 48 lks. dist.)</p> <p>A stump hole, bears S. 30° W., 65 lks. dist.; the uprooted pine, 32 ins. diam., lying alongside is mkd. 1/4 S BT. (Record dist., 61 lks.)</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1/4 S 1 S12 1978</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 9 ins. diam., bears S. 36° W., 35 lks. dist., mkd. 1/4 S12 BT.</p> <p>A juniper, 6 ins. diam., bears N. 4° W., 36.5 lks. dist., mkd. 1/4 S1 BT.</p> <p>Deposit the unmarked stone alongside the iron post.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 89°35' W., beginning new measurement.</p>
39.60	<p>The cor. of secs. 1, 2, 11 and 12.</p> <hr/>
	<p>N. 0°07' E., bet. secs. 1 and 2.</p>
	<p>Over rolling land, through medium to dense timber.</p>
35.60	<p>Track road, bears N. 60° E. and S. 60° W.</p>
39.70	<p>The 1/4 sec. cor. of secs. 1 and 2, monumented with a basalt stone, 22 x 12 x 12 ins., firmly set 12 ins. in the ground, mkd. 1/4 on the W face, from which the remains of the original bearing trees</p>
	<p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., bears S. 70° E., 85 lks. dist., mkd. with a healed blaze.</p>
	<p style="padding-left: 40px;">A stump hole, bears N. 40° W., 95 lks. dist.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R22E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S 2 S 1</p>
	<p style="text-align: center;">1978</p>
	<p>from which new bearing trees</p>
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 85° E., 14.5 lks. dist., mkd. 1/4 S1 BT.</p>
	<p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears S. 51° W., 30 lks. dist., mkd. 1/4 S2 BT.</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p> <hr style="width: 20%; margin: auto;"/>
	<p>N. 4°39' W., beginning new measurement.</p>
45.28	<p>The cor. of secs. 1, 2, 35 and 36, on the N bdy. of the Tp., heretofore described.</p> <hr/>
	<p>From the 1/4 sec. cor. of secs. 14 and 23, monumented with a basalt stone, 18 x 14 x 10 ins., firmly set 10 ins. in the ground, mkd. 1/4 on the N face, from which an unrecorded bearing tree</p>
	<p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., bears N. 71° W., 60 lks. dist., mkd. 1/4 S14.</p>
	<p>At the cor. point</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1 S14 4 S23 1978</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is 8 lks. S of an E-W fence.</p> <p>N. 89°53' W., bet. secs. 14 and 23.</p> <p>Over rolling land, through medium timber.</p> <p>Along the S side of an E-W fence.</p>	
8.00	<p>End of E-W fence, thence along a graded road, bears E and W.</p>	
39.67	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a re-bar, 1 in. diam., buried 16 ins. under ground at the junction of graded cindered road, projecting N, E and S. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the best available evidence of the original cor. position, not remonumented. From this local cor., accessories established by local surveyors</p> <p style="padding-left: 40px;">A re-bar, 1 in. diam., set flush with the ground, bears S. 45° W., 38 lks. dist.</p> <p style="padding-left: 40px;">A re-bar, 1 in. diam., projecting 5 ins. above ground, bears N. 45° W., 38 lks. dist.</p> <p>Cor. is 17 lks. E of a N-S fence.</p> <hr/> <p>N. 0°07' E., bet. secs. 14 and 15.</p> <p>Along the center of a graded cindered road.</p>	
19.68	<p>The S 1/16 sec. cor. of secs. 14 and 15, monumented with a re-bar, 20 ins. long, 1 in. diam., set flush with the ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., flush with the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E S 1/16 S15 S14 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 32° E., 105 lks. dist., mkd. S 1/16 S14 BT.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
	<p>An X cut into a wood cattleguard, bears East, 3.6 lks. dist.</p> <p>A fence cor., bears N. 30° W., 30 lks. dist.; fences extend N, S, E and W.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Deposit broken glass at the base of the iron post.</p> <p>Cor. is 12 lks. W of a cindered road, bears N and S, and 15 lks. E of a N-S fence.</p> <hr/> <p>N. 0°03' E., beginning new measurement.</p>
18.90	Track road, bears N. 50° E. and S. 50° W.
19.68	<p>The 1/4 sec. cor. of secs. 14 and 15, monumented with a re-bar, 16 ins. long, 5/8 in. diam., projecting 2 ins. above ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1/4 S15 S14 1978</p> <p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears S. 38° E., 91 lks. dist., mkd. 1/4 S14 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 16° W., 35.5 lks. dist., mkd. 1/4 S15 BT.</p> <p>A fence cor., bears S. 5° E., 18 lks. dist.; fences extend E, S and W.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W of the cor.</p> <p>Cor. is 35 lks. W of a cindered road, bears irregularly N and S.</p> <hr/> <p>N. 0°11' E., beginning new measurement.</p> <p>Through scattering timber.</p>
13.30	Show Low Creek, 60 lks. wide, course, N. 80° W.
39.33	<p>The cor. of secs. 10, 11, 14 and 15, monumented with basalt stone, 14 x 10 x 9 ins., set in a mound of stone, 2 ft. base, 1 ft. high, mkd. with 2 notches on the E and 4 notches on the S edges.</p> <p>At the cor. point</p>

T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E S10 S11 S15 S14 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 62° E., 39.5 lks. dist., mkd. T9N R22E S11 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 16° E., 51 lks. dist., mkd. T9N R22E S14 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 26° W., 51.5 lks. dist., mkd. T9N R22E S15 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 55° W., 74.5 lks. dist., mkd. T9N R22E S10 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <hr/> <p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°43' W., bet. secs. 11 and 14.</p> <p>Over nearly level land, through scattering timber.</p>	
39.99	<p>The 1/4 sec. cor. of secs. 11 and 14, monumented with a re-bar, 12 ins. long, 3/8 in. diam., projecting 2 ins. above ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 in. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1 S11 4 S14 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 4 ins. diam., bears N. 13° W., 133 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°45' W., beginning new measurement.</p>	
14.30	Power line, bears S. 62° E. and N. 62° W.	
14.40	Track road, bears S. 62° E. and N. 62° W.	
15.20	Power line, bears S. 62° E. and N. 62° W.	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
40.02	The cor. of secs. 10, 11, 14 and 15.
	<hr/> N. 0°31' E., bet. secs. 10 and 11.
	Over gently rolling land, through scattering to medium timber.
3.60	Power line, bears S. 60° E. and N. 60° W.
14.50	Power line, bears S. 66° E. and N. 55° W.
15.30	Power line and track road, bear S. 55° E. and N. 55° W.
19.775	Point for the S 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T9N R22E S 1/16 S10 S11 1978
	from which
	A ponderosa pine, 6 ins. diam., bears N. 80° E., 15 lks. dist., mkd. S 1/16 S11 BT.
	A ponderosa pine, 8 ins. diam., bears N. 60° W., 52 lks. dist., mkd. S 1/16 S10 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.
39.55	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T9N R22E 1/4 S10 S11 1978
	from which
	A ponderosa pine, 6 ins. diam., bears S. 2 1/2° E., 20 lks. dist., mkd. 1/4 S11 BT.
	An alligator juniper, 8 ins. diam., bears S. 85° W., 35.5 lks. dist., mkd. 1/4 S10 BT.
59.325	Point for the N 1/16 sec. cor. of secs. 10 and 11.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T9N R22E N 1/16 S10 S11 1978</p> <p>from which</p> <p>An alligator juniper, 12 ins. diam., bears N. 10° E., 102 lks. dist., mkd. N 1/16 S11 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 4° E., 95 lks. dist., mkd. N 1/16 S11 BT.</p> <p>79.10 The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 20 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonu- mentation notes, from which</p> <p>An alligator juniper stump, 18 ins. diam., mkd. in 1883, bears S. 29° W., 35 lks. dist.; no marks visible.</p> <p>An alligator juniper, 10 ins. diam., mkd. in 1975, bears S. 67° W., 152.5 lks. dist., mkd. T9N R22E S10 BT.</p> <p>An alligator juniper, 8 ins. diam., mkd. in 1975, bears N. 51 1/2° W., 141 lks. dist., mkd. T9N R22E S3 BT.</p> <p>Add the marks 1978 to the brass cap, from which a new bearing tree</p> <p>An alligator juniper, 7 ins. diam., bears S. 27° E., 192 lks. dist., mkd. T9N R22E S11 BT.</p> <p>Cor. is located N. 21 1/2° E., 38 lks. dist. from a fence cor.; fences extend N and E.</p>	
40.03	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>S. 89°46' W., bet. secs. 2 and 11.</p> <p>Over rolling land, through dense timber.</p> <p>Point for the 1/4 sec. cor. of secs. 2 and 11, at pro- portionate distance; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1/4 S 2 4 S11 1978</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N. 11° E., 131 lks. dist., mkd. 1/4 S2 BT.</p> <p>An alligator juniper, 5 ins. diam., bears S. 55° W., 55.5 lks. dist., mkd. 1/4 S11 BT.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
80.06	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N of the cor.</p> <p>Cor. is 31 lks. S of an E-W fence.</p> <p>Continue along the S side of an E-W fence.</p> <p>The cor. of secs. 2, 3, 10 and 11.</p>
19.80	<p>N. 2°10' W., bet. secs. 2 and 3.</p> <p>Over gently rolling land, through medium timber.</p> <p>Along a N-S fence.</p> <p>Fence, bears W and E, 65 lks. dist. to a fence cor., thence N and S.</p>
42.31	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in ground to solid rock, and in mound of stone, 3 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R22E 1/4 S 3 S 2 1978</p>
85.04	<p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 8° E., 90 lks. dist., mkd. 1/4 S2 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 9 ins. diam., bears S. 71° W., 43 lks. dist., mkd. 1/4 S3 BT.</p> <p>Cor. is 15 lks. S of an E-W fence.</p> <p>The cor. of secs. 2, 3, 34, and 35, on the N. bdy. of the Tp., heretofore described.</p>
	<p>From the cor. of secs. 14, 15, 22 and 23.</p>
	<p>N. 89°45' W., between secs. 15 and 22.</p>
	<p>Over gently rolling land, through open pasture.</p>
.17	<p>Fence, bears N and S.</p>
.27	<p>Telephone and power lines, bear N and S.</p>
13.60	<p>Fence, bear N and S.</p>
21.10	<p>Fence, bears SE and NW.</p>
39.97	<p>Fence, bears N and S.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
40.39	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with an open end metal pipe, 5/8 in. diam., set flush with the ground and in a mound of stone, 2 ft. base, 6 ins. high, from which a pine stump, 28 ins. diam., bears N. 11° E., 128 lks. dist., agreeing with the record position of an original pine bearing tree. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the best available evidence of the original cor. position; not remonumented.</p>
	<p>N. 89°51' W. beginning new measurement.</p>
.17	<p>Paved driveway, bears S. 15° E. and N. 15° W.</p>
.32	<p>Fence, bears S. 15° E. and N. 15° W.</p>
6.80	<p>Center of State Highway No. 260, asphalt surfaced, bears S. 15° E. and N. 15° W., thence along the center of Valley Lane road, asphalt surfaced, projecting west.</p>
20.045	<p>Point for the W 1/16 sec. cor. of secs. 15 and 22, falls in the center of Valley Lane road, asphalt surface, bears E and W; not monumented.</p>
40.09	<p>The cor. of secs. 15, 16, 21 and 22, perpetuated by persons unknown with an unmarked brass tablet, 2 ins. diam., set in concrete, flush with surface of Valley Lane road, asphalt surface, bears E-W, from which</p> <p style="padding-left: 40px;">An alligator juniper, 19 ins. diam., mkd. in 1915, bears N. 55 1/4° E., 57 lks. dist., mkd. T9N R22E S15 BT.</p> <p style="padding-left: 40px;">An oak, 17 ins. diam., mkd. in 1883, bears S. 39° E., 82 lks. dist., mkd. with healed blaze. (Record dist. 79 lks.)</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 45 1/2° W., 128 lks. dist., mkd. 9N 16 BT.</p>
	<p>(Restoring the 1915 resurvey by Sidney E. Blout)</p>
	<p>N. 0°15' E., bet. secs. 15 and 16.</p>
	<p>Over gently rolling land, along the E side of a N-S fence.</p>
19.43	<p>The S 1/16 sec. cor. of secs. 15 and 16, monumented with a re-bar, 16 ins. long, 5/8 in. diam., set flush with the ground, with an aluminum cap, mkd. 5047. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the cor. position.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R22E S 1/16 S16 S15 1978</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 15 ins. diam., bears S. 36° W., 92.5 lks. dist., mkd. S 1/16 S16 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 76° W., 70 lks. dist., mkd. S 1/16 S16 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W of the corner.</p> <p>The cor. is 34 lks. E of a N-S fence.</p> <hr/> <p>N. 0°25' E., beginning new measurement.</p>
.92	Fence, bears E and W.
7.30	Fence, bears S. 40° E. and N. 40° W.
11.40	Center of State Highway No. 260, asphalt surface, bears S. 40° E. and N. 40° W.
15.40	Telephone line, bears S. 40° E. and N. 40° W.
17.80	Show Low Lake road, bears N. 40° E. and S. 40° W.
19.42	<p>The 1/4 sec. cor. of secs. 15 and 16, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 1 ft. high, to top, with brass cap mkd. as de- scribed in the official record of the 1975 remonumenta- tion notes, from which the original bearing trees</p> <p>A ponderosa pine, 17 ins. diam., bears N. 63 3/4° E., 58 lks. dist., mkd. with a healed blaze. (This bearing agrees with the 1915 resurvey; the 1975 record is N. 68° E.)</p> <p>A ponderosa pine, 12 ins. diam., bears N. 33 1/2° W., 45 lks. dist., mkd. 1/4 on a badly weathered blaze. (This bearing agrees with the 1915 resurvey; the 1975 record is N. 30 1/2° W.)</p> <hr/> <p>N. 0°29' E., beginning new measurement.</p>
9.30	Fence, bears E and W, 26 lks. dist., thence N.
9.94	<p>The S-N 1/64 sec. cor. of secs. 15 and 16, monumented with a steel rod, 18 ins. long, 1/2 in. diam., projecting 4 ins. above ground and set in concrete alongside a 3 3/4 ins. diam., open end steel pipe projecting 16 ins. above concrete. This position is harmoniously related to existing original corners, has been used by private surveyors in the area, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in concrete, with brass cap mkd.</p> <div style="text-align: center;"> <p>S-N 1/64 S16 S15 1978</p> </div>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S. 13° E., 96 lks. dist., mkd. S-N 1/64 S15 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 47° W., 75.5 lks. dist., mkd. S-N 1/64 S16 BT.</p> <p>Reset the steel rod alongside the iron post.</p> <hr/> <p>N. 0°36' E., beginning new measurement.</p>	
9.933	Point for N 1/16 sec. cor. of secs. 15 and 16, not monumented.	
29.80	<p>The cor. of secs. 9, 10, 15 and 16, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 22 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonumentation notes, from which</p> <p>A ponderosa pine, 8 ins. diam., mkd. in 1915, bears N. 61° E., 72 lks. dist., mkd. 9N R22E S10. (This bearing agrees with the 1915 resurvey; the 1975 record is N. 63° E.)</p> <p>A ponderosa pine, 21 ins. diam., mkd. in 1883, bears S. 21 1/4° E., 133 lks. dist., with a partially healed blaze. (The 1975 record bearing is S. 18° W.)</p> <p>A ponderosa pine, 18 ins. diam., mkd. in 1883, bears S. 10 1/4° W., 137 lks. dist., mkd. with a partially healed blaze. (The 1975 record bearing is S. 14° W.)</p> <p>A 1 in. open end pipe, bears S. 73° W., 4 lks. dist., projecting 16 ins. above ground.</p> <p>A fence cor. bears West, 13 lks. dist.; fences extend N, S, and W.</p> <p>A ponderosa pine, 16 ins. diam., mkd. in 1915, bears N. 32° W., 67 lks. dist., with illegible scribe marks visible through partially healed blaze. (The 1975 record bearing is N. 29 1/4° W.)</p> <hr/> <p>(Restoring the 1883 survey by O. D. Wheeler)</p> <p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>N. 89°51' W., bet. secs. 10 and 15.</p> <p>Over rolling land through medium timber.</p>	
6.10	Power line, bears N. 60° E. and S. 60° W.	
20.06	<p>Point for the E 1/16 sec. cor. of secs. 10 and 15.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R22E E 1/16 $\frac{S10}{S15}$ 1978</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS	
	<p>from which</p>
	<p>A ponderosa pine, 7 ins. diam., bears S. 28° E., 100 lks. dist., mkd. E 1/16 S15 BT.</p>
	<p>An alligator, juniper, 4 ins. diam., bears N. 59° W., 51 lks. dist., mkd. E 1/16 S10 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, N of the cor.</p>
40.12	<p>The 1/4 sec. cor. of secs. 10 and 15, monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 18 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonumen- tation notes, from which</p>
	<p>A stump hole, bears N. 8 1/2° E., 91 lks. dist.; a fallen pine lying alongside, 20 ins. diam., mkd. in 1883 is scribed 1/4 S BT.</p>
	<p>An alligator juniper, 8 ins. diam., mkd. in 1975, bears N. 29 1/4° E., 89 lks. dist., mkd. 1/4 S10 BT. (Record bearing N. 26 1/4° E.)</p>
	<p>An alligator juniper, 7 ins. diam., bears S. 52° W., 63 lks. dist., mkd. 1/4 S15 BT. (Record bearing S. 48 1/2° W.)</p>
	<p>N. 89°54' W., beginning new measurement.</p>
3.30	<p>Vertical ledge, bears N and S; descend.</p>
10.20	<p>East shore of Show Low Lake, bears N and S.</p>
13.90	<p>West shore of Show Low Lake, bears N and S.</p>
19.965	<p>Point for the W 1/16 sec. cor. of secs. 10 and 15.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in ground to solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R22E</p>
	<p style="text-align: center;">W 1/16 $\frac{S10}{S15}$</p>
	<p style="text-align: center;">1978</p>
	<p>from which</p>
	<p>A juniper, 8 ins. diam., bears S. 81° W., 46.5 lks. dist., mkd. W 1/16 S15 BT.</p>
	<p>A ponderosa pine, 7 ins. diam., bears N. 17° W., 29.5 lks. dist., mkd. W 1/16 S10 BT.</p>
24.955	<p>Point for the E-W-W 1/256 sec. cor. of secs. 10 and 15.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S10</p>
	<p style="text-align: center;">E-W-W</p>
	<p style="text-align: center;">1/256</p>
	<p style="text-align: center;">S15</p>
	<p style="text-align: center;">1978</p>

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>from which</p> <p>An alligator juniper, 6 ins. diam., bears N. 31° E., 81 lks. dist., mkd. E-W-W 1/256 S10 BT.</p> <p>An alligator juniper, 10 ins. diam., bears S. 21° E., 121 lks. dist., mkd. E-W-W 1/256 S15 BT.</p> <p>Raise a mound of stone 3 ft. base, 2 ft. high, N of the cor.</p> <p>Cor. is 2 lks. W of a N-S fence.</p>	
29.00	Show Low Lake road, asphalt surfaced, bears N and S. (Scaled)	
36.50	Road, asphalt surfaced, bears N and S. (Scaled)	
39.93	The cor. of secs. 9, 10, 15 and 16.	
	<hr/> <p>N. 0°38' W. bet. secs. 9 and 10.</p> <p>Over gently rolling land, through medium timber.</p>	
19.91	<p>The S 1/16 sec. cor. of secs. 9 and 10, monumented with a re-bar, 5/8 in. diam., projecting 4 ins. above the ground. This position is harmoniously related to exist- ing original cors., has been used by private surveyors in the area, and is accepted as the cor. position, not remonumented.</p> <p>The cor. is in a N-S fence.</p> <hr/> <p>N. 0°34' W., beginning new measurement.</p>	
19.91	<p>The 1/4 sec. cor. of secs. 9 and 10, a fence cor. from which fences extend North, South and East. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is ac- cepted as the cor. position, not remonumented.</p> <hr/> <p>N. 0°30' E., beginning new measurement.</p>	
19.875	<p>The N 1/16 sec. cor. of secs. 9 and 10, monumented with a re-bar, 3/4 in. diam., projecting 4 ins. above the ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the cor. position, not remonumented.</p> <p>The cor. is in a N-S fence.</p> <hr/> <p>N. 0°32' E., beginning new measurement.</p>	
4.10	Show Low Lake road, bears S. 60° E. curving South and N. 60° W. curving North.	
19.875	<p>The cor. of secs. 3, 4, 9 and 10 monumented with a steel plate, 8 ins. square, set in concrete flush with the ground. The original cor. was remonumented by Clifford B. Potts, Professional Engineer No. 838 in 1953 and an affidavit to the effect is filed with the Arizona State Office, Bureau of Land Management, Phoenix, Arizona. The plate is mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;"> $\frac{4 \mid 3}{9 \mid 10}$ </p> <p>from which</p> <p style="text-align: center;">A granite boulder, 5 x 2 1/2 x 2 1/2 ft. above ground, bears N. 31° E., 21 lks. dist., mkd. XBO on top.</p> <p>The cor. falls on Show Low Dam Spillway.</p>	
20.20	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°34' W., bet. secs. 3 and 10.</p> <p>Over gently rolling land, through scattering timber.</p> <p>Point for the E 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> T9N R22E E 1/16 $\frac{S \ 3}{S10}$ 1978 </p> <p>from which</p> <p style="text-align: center;">An alligator juniper, 8 ins. diam., bears N. 34° E., 112.5 lks. dist., mkd. E 1/16 S3 BT.</p> <p style="text-align: center;">An alligator juniper, 8 ins. diam., bears N. 57° W., 65.5 lks. dist., mkd. E 1/16 S3 BT.</p>	
22.10	<p>Power line, bears S. 15° E. and N. 15° W.</p>	
22.70	<p>Power line and track road, bear S. 15° E. and N. 15° W.</p>	
30.10	<p>Fence cor., bears South, 23 lks. dist.; fences extend N and W.</p>	
40.40	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> T9N R22E $\frac{1 \ S \ 3}{4 \ S10}$ 1978 </p> <p>from which</p> <p style="text-align: center;">A ponderosa pine, 6 ins. diam., bears S. 51° E., 128.5 lks. dist., mkd. 1/4 S10 BT.</p> <p style="text-align: center;">An alligator juniper, 8 ins. diam., bears N. 8° W., 60 lks. dist., mkd. 1/4 S3 BT.</p> <p>Cor. is located 47 lks. N of an E-W fence.</p>	
50.50	<p>Point for the E-W 1/64 sec. cor. of secs. 3 and 10.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S 3 E-W-1/64 S10 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 22 ins. diam., bears S. 31° E., 88 lks. dist., not mkd. From this tree, fences extend N, E, S and N. 55° W.</p> <p style="padding-left: 40px;">An alligator juniper, 12 ins. diam., bears N. 29° W., 42 lks. dist., mkd. E-W 1/64 S3 BT.</p>	
60.60	<p>Point for W 1/16 sec. cor. of secs. 3 and 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E W 1/16 $\frac{S\ 3}{S10}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 10 ins. diam., bears N. 70° E., 10 lks. dist., mkd. W 1/16 S3 BT.</p> <p>Cor. is located 4 lks. N of an E-W fence.</p>	
80.80	<p>The cor. of secs. 3, 4, 9, 10.</p> <hr/> <p>N. 1°27' W., bet. secs. 3 and 4.</p> <p>Over gently rolling land, through open area.</p>	
4.00	<p>Enter dense timber, edge bears E and W.</p>	
40.07	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with an open end pipe, 16 ins. long, 7/8 in. diam., set 4 ins. above ground and alongside a wood post, 30 ins. long, 3 ins. diam. set flush with the ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the best available evidence of the original cor. position</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E 1/4 S 4 S 3 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 89° E., 60.5 lks. dist., mkd. 1/4 S3 BT.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines,
T. 9 N., R. 22 E., Gila and Salt River Mer., Ariz.

CHAINS		
21.88	<p>Reset the open end pipe and wood post alongside the iron post.</p> <p>Raise a mound of stone 2 1/2 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is located 1.5 lks. North of a fence cor.; fences extend N and W.</p> <hr/> <p>N. 2°26' W., beginning new measurement.</p> <p>The N 1/16 sec. cor. of secs. 3 and 4, monumented with a re-bar, 16 ins. long, 5/8 in. diam., projecting 6 ins. above the ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R22E N 1/16 S 4 S 3 1978</p> </div> <p>from which</p> <p>An alligator juniper, 11 ins. diam., bears S. 8° E. 204 lks. dist., mkd. N 1/16 S3 BT.</p> <p>An alligator juniper, 4 ins. diam., bears S. 58° E., 58.5 lks. dist., mkd. X at breast height and BT at the base.</p> <p>Reset re-bar alongside iron post.</p> <p>Corner is located in a fence bearing W and E, 80 lks. dist., thence S.</p> <hr/> <p>N. 2°21' W., beginning new measurement.</p>	
22.15	<p>The Cor. of secs. 3, 4, 33, and 34 on the N bdy. of the Tp., heretofore described.</p> <hr/> <p>Dependent Resurvey of a Portion of the Subdivision of Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.</p> <hr/> <p>(Restoring the 1914 survey by C. A. Long, Surveyor, Forest Service)</p> <hr/> <p>From the 1/4 sec. cor. of secs. 13 and 24.</p> <p>N. 0°27' W., on the N and S center line of sec. 13.</p> <p>Over rolling land, through medium timber.</p>	
.45	<p>Power line, bears E and W.</p>	
1.10	<p>Power line, bears E and W.</p>	

Dependent Resurvey of a Portion of the Subdivision of
Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.

CHAINS		
8.80	Porter Creek, 20 lks. wide, 1 ft. deep, course N. 75° W.	
20.21	<p>The center S 1/16 sec. cor. of sec. 13, monumented with a re-bar, 12 ins. long, 5/8 in. diam., projecting 2 ins. above ground, with an aluminum cap, mkd. 5047. This monument was set in 1974 by George Matkin, Registered Civil Engineer No. 5047, in Arizona, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R22E</p> <p>C</p> <p> </p> <p>S 1/16 S13</p> <p> </p> <p>C</p> <p>1978</p> </div>	
	<p>from which</p> <p style="padding-left: 40px;">A fence cor., bears S. 45° E., 1.5 lks. dist., fences extend N and W.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 64° W., 17 lks. dist., mkd. CS 1/16 S13 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°22' W., beginning new measurement.</p> <p>Along a N-S fence.</p>	
20.10	Track road, bears E and W.	
20.25	<p>The center 1/4 sec. cor. of sec. 13, monumented with a re-bar, 12 ins. long, 5/8 ins. diam., projecting 4 ins. above ground, with aluminum cap mkd. 5047. This monument was set in 1974 by George Matkin, Registered Civil Engineer No. 5047, in Arizona, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R22E</p> <p>C 1/4 S13</p> <p>1978</p> </div>	
	<p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears N. 33° E., 231 lks. dist., mkd. C 1/4 S13 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 4 ins. diam., bears S. 27° W., 56 lks. dist., mkd. C 1/4 S13 BT.</p> <p>Reset the re-bar alongside the iron post.</p>	

Dependent Resurvey of a Portion of the Subdivision of
Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.

CHAINS	
	<p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, E of the cor. The mound could not be built W because of an existing track road.</p> <p>The cor. is adjacent to the N side of a fence cor.; fences extend E and S.</p> <hr/> <p>N. 0°24' W., beginning new measurement.</p> <p>Over nearly level open land.</p>
.25	Track road, bears E and W.
18.30	Telephone line, bears E and W.
18.50	Graded cinder road, bears E and W.
18.70	Power line, bears E and W.
19.10	Fence, bears E and W.
19.41	Point for Cor. No. 3 of Homestead Entry Survey No. 206, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
19.91	<p>The center N 1/16 sec. cor. of sec. 13, monumented with a re-bar, 12 ins. long, 5/8 in. diam., projecting 3 ins. above ground. This position is harmoniously related to existing original cors., has been used by private surveyors in the area, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R22E</p> <p>C</p> <p> </p> <p>N 1/16 S13</p> <p> </p> <p>C</p> <p>1978</p> </div> <p>from which</p> <p style="padding-left: 40px;">An alligator juniper, 7 ins. diam., bears S. 32° E., 233.5 lks. dist., mkd. CN 1/16 S13 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.</p> <hr/> <p>N. 0°23' W., beginning new measurement.</p>
13.00	Fence, bears N. 80° E. and S. 80° W.
13.80	Graded gravel road, bears N. 80° E. and S. 80° W.
14.60	Fence, bears N. 80° E. and S. 80° W.
16.00	Abandoned fence, bears S. 50° E. and N. 50° W.
16.30	Irrigation ditch, flows N. 55° W.

Dependent Resurvey of a Portion of the Subdivision of
Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.

CHAINS	
17.20	Track road, bears S. 55° E. and N. 55° W.
17.40	Enter dense timber, edge bears S. 55° E. and N. 55° W.
19.94	The 1/4 sec. cor. of secs. 12 and 13.
	<p>From the 1/4 sec. cor. of sec. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 1/2 ft. base, 1 ft. high, to top, with brass cap mkd. as described in the official record of the 1967 resurvey from which</p> <p>A ponderosa pine, 23 ins. diam., mkd. in 1967, bears N. 70 1/4° E., 189 lks. dist., mkd. 1/4 S18 BT.</p> <p>A ponderosa pine, 18 ins. diam., mkd. in 1967, bears S. 82 3/4° E., 93 lks. dist., mkd. 1/4 S18 BT.</p> <p>A ponderosa pine, 33 ins. diam., mkd. in 1883, bears S. 45 1/2° W., 61 lks. dist., mkd. 1/4 S.</p> <p>S. 88°36' W., on the E and W center line of sec. 13.</p> <p>Over rolling land, through dense timber.</p>
5.00	East shore of Scott Reservoir, bears N. 12° E. and S. 12° W.
19.24	True point for the center E 1/16 sec. cor. of sec. 13, falls in Scott Reservoir, not monumented.
21.00	West shore of Scott Reservoir, bears N and S.
21.14	Point selected for the witness center E 1/16 sec. cor. of sec. 13.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground in a concrete base, with brass cap mkd.
	<p style="text-align: center;">W C T9N R22E E 1/16 C—————>C S13 1978</p>
	<p>from which</p> <p>A boulder, 3 1/2 x 3 x 1/2 ft. above ground, bears N. 4° E., 23 lks. dist., mkd. XBO on top.</p> <p>A re-bar, 5/8 ins. diam., projecting 3 ins. above ground, bears S. 72° W., 1 lk. dist.</p> <p>A fence cor., bears N. 78° W., 4 lks. dist.; fences extend N. 18° E. and W.</p> <p>A boulder, 5 x 5 x 3 ft. above ground, bears N. 39° W., 14.5 lks. dist., mkd. XBO on top.</p>
24.05	Cor. No. 5 of Homestead Entry Survey No. 206, identical with the center E-W-E 1/256 sec. cor. of sec. 13, monumented with a malpais stone, 24 x 12 x 12 ins., firmly set 20 ins. in the ground, mkd. 5 on the W face and an X on top, from which the remains of an original bearing tree

Dependent Resurvey of a Portion of the Subdivision of
Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.

CHAINS		
	<p>A stump, bears N. 77°49' E., 70 lks. dist., with a fallen pine alongside, 17 ins. diam., mkd. HES 2.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S13 HES 206 Cor. 5 1978</p> <p>from which</p> <p>An alligator juniper, 6 ins. diam., bears N. 6° E., 138 lks. dist., mkd. 5 HES 206 S13 BT.</p> <p>An alligator juniper, 9 ins. diam., bears N. 44° W., 162.5 lks. dist., mkd. 5 HES 206 S13 BT.</p> <p>Reset the mkd. stone alongside the iron post.</p> <p>Cor. is located 4 lks. north of an E-W fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°38' W., beginning new measurement.</p>	
14.44	<p>The center 1/4 sec. cor. of sec. 13.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 88°38' W., beginning new measurement.</p>	
9.88	<p>Point for Cor. No. 6, Homestead Entry Survey No. 206, identical with the center E-W 1/64 sec. cor. of sec. 13, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>	
39.52	<p>The 1/4 sec. cor. of secs. 13 and 14.</p> <hr/> <p style="text-align: center;">NE 1/4, Sec. 13</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the true point for the center E 1/16 sec. cor. of sec. 13.</p> <p>N. 0°14' W., on the N and S center line of the NE 1/4 of sec. 13. Over Scott Reservoir.</p>	
6.00	<p>West shore of Scott Reservoir, bears N. 40° E. and S. 20° W.; enter medium timber. (Scaled)</p>	
20.04	<p>Point for the NE 1/16 sec. cor. of sec. 13, at intersection with the E and W center line of the NE 1/4 of sec. 13.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E NE 1/16 S13 1978</p> <p>from which</p> <p>A fence cor., bears South 138 lks. dist.; fences extend E, S, and W.</p>	

Dependent Resurvey of a Portion of the Subdivision of
Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.

CHAINS		
	<p>A power pole, bears S. 36° W., 176.5 lks. dist.; from which lines extend N and W.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.</p>	
35.40	Power and telephone lines, bear N. 60° E. curving southerly and S. 60° W.	
37.80	Graded cinder road, bears N. 70° E. and S. 70° W.	
38.60	Fence, bears N. 70° E. and S. 70° W.	
40.00	Fence, bears E. and W.	
40.08	The E 1/16 sec. cor. of secs. 12 and 13.	
	<hr/> <p>From the N 1/16 sec. cor. of secs. 13 and 18, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., set in a mound of stone, 3 ft. base, 20 ins. high, to top, with brass cap mkd. as described in the official record of the 1967 resurvey, from which</p> <p>A ponderosa pine, 11 ins. diam., bears S. 57° E., 108 lks. dist., mkd. N 1/16 S18 BT.</p> <p>S. 88°15' W., on the E. and W. center line of the NE 1/4 of sec. 13.</p> <p>Over rolling land, through dense timber.</p>	
7.20	East shore of Scott Reservoir, bears N. 40° E. and S. 40° W.	
10.20	West shore of Scott Reservoir, bears N. 30° E. and S. 30° W.	
19.31	The NE 1/16 sec. cor. of sec. 13.	
19.90	Telephone line, bears N and S.	
20.10	Abandoned graded cinder road, bears N and SW.	
20.30	Power line, bears N and S; enter open grass land.	
24.14	Point for the center E-W-NE 1/256 sec. cor. of sec. 13, not monumented.	
	<p>From this point, the point for Cor. No. 4 of Homestead Entry Survey No. 206, bears S. 0°16'30" E., 50 lks. dist. There is no remaining evidence of the original cor.; not monumented.</p>	
38.63	The center N 1/16 sec. cor. of sec. 13.	
	<hr/> <p style="text-align: center;">SW 1/4, Sec. 13</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 13.</p> <p>S. 89°27' W., on the E and W center line of the SW 1/4 of sec. 13.</p> <p>Over rolling land, through dense timber, along an E-W fence.</p>	

Dependent Resurvey of a Portion of the Subdivision of
Sec. 13, T9N R22E, Gila and Salt River Mer., Ariz.

CHAINS	
19.96	Point for Cor. No. 9 of Homestead Entry Survey No. 206, identical with the SW 1/16 sec. cor. of sec. 13, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
39.41	Point for Cor. No. 1 of Homestead Entry Survey No. 206, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
39.91	The S 1/16 sec. cor. of secs. 13 and 14.
<hr/> NW 1/4, Sec. 13 <hr/>	
From the center N 1/16 sec. cor. of sec. 13.	
S. 88°22' W., on the E and W center line of the NW 1/4 of sec. 13.	
Over gently rolling land, through open grass land.	
39.08	The N 1/16 sec. cor. of secs. 13 and 14.
<hr/> Subdivision of Sec. 3, T. 9 N., R. 22 E., Gila and Salt River Meridian, Arizona <hr/>	
From the 1/4 sec. cor. of secs. 3 and 10.	
N. 2°08' W., on the N and S center line of sec. 3.	
41.18	Point for the center 1/4 sec. cor. of sec. 3, at intersection with the E and W center line of sec. 3.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.	
T9N R22E C 1/4 S 3 1978	
from which	
A ponderosa pine, 8 ins. diam., bears N. 21° E., 7 lks. dist. mkd. C 1/4 S3 BT.	
A ponderosa pine, 9 ins. diam., bears S. 83° W., 46 lks. dist., mkd. C 1/4 S3 BT.	
42.80	Fence, bears irregularly E and W.
61.70	Power line and track road, bear S. 15° E. and N. 15° W.
62.68	Point for the center N 1/16 sec. cor. of sec. 3.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground with brass cap mkd.	
T9N R22E C N 1/16 S 3 C 1978	

Subdivision of Sec. 3, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 5 ins. diam., bears N. 78° E., 76 lks. dist., mkd. CN 1/16 S3 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S. 42° E., 189.5 lks. dist., mkd. CN 1/16 S3 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>Cor. is located 25 lks. E of a power line, bears S. 15° E. and N. 15° W., and 33 lks. W of a power line, bears S. 15° E. and N. 15° W.</p>	
63.90	Power line, bears S. 15° E. and N. 15° W.	
84.54	The 1/4 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp., heretofore described.	
	<hr/> <p>From the 1/4 sec. cor. of secs. 2 and 3. S. 88°50' W., on the E and W center line of sec. 3. Over gently rolling land through dense timber.</p>	
33.90	Power line, bears S. 15° E. and N. 15° W.	
34.50	Power line and track road, bear S. 15° E. and N. 15° W.	
40.33	The center 1/4 sec. cor. of sec. 3.	
44.90	Fence, bears N. 25° E. and S. 25° W.	
48.10	Show Low Creek, 50 lks. wide, 1 ft. deep, course N.	
60.28	Point for the center W 1/16 sec. cor. of sec. 3. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T9N R22E W 1/16 C_____C S 3 1978</p>	
	<p>from which</p> <p>An alligator juniper, 10 ins. diam., bears S. 58° E., 35 lks. dist., mkd. C-W 1/16 S3 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 62° W., 123 lks. dist., mkd. C-W 1/16 S3 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, N of the cor.</p>	
60.80	Fence, bears S and N 37 lks. dist., thence easterly.	
80.23	The 1/4 sec. cor. of secs. 3 and 4.	
	<hr/> <p style="text-align: center;">NW 1/4, Sec. 3</p> <hr/>	

Subdivision of Sec. 3, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the center W 1/16 sec. cor. of sec. 3.</p> <p>N. 2°16' W. on the N and S center line of the NW 1/4 sec. 3.</p> <p>Over rolling land, through medium timber.</p> <p>21.69 Point for the NW 1/16 sec. cor. of sec. 3, at intersection with the E and W center line of the NW 1/4 of sec. 3.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E NW 1/16 S 3 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 8° E., 128 lks. dist., mkd. NW 1/16 S3 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 18° W., 108.5 lks. dist., mkd. NW 1/16 S3 BT.</p>	
43.69	<p>The true point for the W 1/16 sec. cor. of secs. 3 and 34, on the N bdy. of the Tp., heretofore described.</p>	
13.90	<p>From the center N 1/16 sec. cor. of sec. 3.</p> <p>S. 89°23' W., on the E and W center line of the NW 1/4 sec. 3.</p> <p>Over gently rolling land, through medium timber.</p>	
20.01	<p>Show Low Creek, 25 lks. wide, 1 ft. deep, course N.</p>	
20.01	<p>The NW 1/16 sec. cor. of sec. 3.</p>	
40.03	<p>The N 1/16 sec. cor. of secs. 3 and 4.</p>	
<p>Subdivision of Sec. 10, T. 9 N., R. 22 E., Gila and Salt River Meridian, Arizona</p>		
2.80	<p>From the 1/4 sec. cor. of secs. 10 and 15.</p> <p>N. 0°18' E., on the N and S center line of sec. 10.</p> <p>Over rolling land, through medium timber.</p> <p>Fence, bears E and W.</p>	
11.23	<p>Point selected for the witness center S 1/16 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T9N R22E C S 1/16 S10 C 1978</p>	

Subdivision of Sec. 10, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS

from which

A volcanic boulder, 5 x 3 x 2 ft. above ground,
bears N. 60° E., 27.5 lks. dist., mkd. XBO on top.

A ponderosa pine, 4 ins. diam., bears S. 6 1/2° W.,
44 lks. dist., mkd. X at breast height and BT at
the base.

Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of
the cor.

11.50 South shore of Show Low Lake, bears N. 20° E. and
S. 20° W.

19.83 True point for the center S 1/16 sec. cor. of sec. 10
falls in Show Low Lake, not monumented.

39.66 True point for the center 1/4 sec. cor. of sec. 10, at
intersection with the E and W center line of sec. 10.
This point falls in Show Low Lake, not monumented.


48.80 North shore of Show Low Lake, bears S. 60° E. and
N. 60° W.

49.00 Track road, bears S. 60° E. and N. 60° W.

59.05 Fence, bears E and W.

59.49 Point for the center N 1/16 sec. cor. of sec. 10.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins.
in the ground to solid rock, and in a mound of stone, 3
ft. base, to top, with brass cap mkd.



from which

An alligator juniper, 21 ins. diam., bears
N. 30° E., 58.5 lks. dist. mkd. CN 1/16 S10 BT.

A pinyon pine, 6 ins. diam., bears N. 64° W.,
70.5 lks. dist. mkd. CN 1/16 S10 BT.

79.32 The 1/4 sec. cor. of secs. 3 and 10.

From the 1/4 sec. cor. of secs. 10 and 11.

N. 89°41 W. on the E and W center line of sec. 10.

Over gently rolling land, through medium timber.

6.90 Track road, bears N and S.

9.10 Power line, bears S. 15° E. and N. 15° W.

9.70 Power line, bears S. 15° E. and N. 15° W.

Subdivision of Sec. 10, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
19.37	Fence, bears N and S.	
20.13	Point for center E 1/16 sec. cor. of sec. 10.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.	
	T9N R22E E 1/16 C-----C S10 1978	
	from which	
	A juniper, 6 ins. diam., bears N. 54° E., 84 lks. dist., mkd. CE 1/16 S10 BT.	
	An alligator juniper, 5 ins. diam., bears S. 0°30' W., 43 lks. dist., mkd. CE 1/16 S10 BT.	
27.60	Track road, bears N and S.	
27.80	East shore of Show Low Lake, bears N and S.	
40.26	True point for center 1/4 sec. cor. of sec. 10.	
59.00	West shore of Show Low Lake, bears SE and NW.	
60.54	Point for center W 1/16 sec. cor. of sec. 10.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground in a concrete base, with brass cap mkd.	
	T9N R22E W 1/16 C-----C S10 1978	
	from which	
	A granite boulder, 14 x 9 x 4 ft. above ground, bears S. 67° E., 31 lks. dist., mkd. XBO on the NW face.	
	A granite boulder, 3 x 3 x 4 ft. above ground, bears S. 10° E., 69 lks. dist., mkd. XBO on the N face.	
	Cor. is located 12.5 lks. south of an E-W fence.	
64.50	Track road, bears S. 25° E. and N. 25° W.	
65.61	Point for the center E-W-W 1/256 sec. cor. of sec. 10.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.	
	S10 C-E-W-W 1/256 1978	
	from which	
	A ponderosa pine, 12 ins. diam., bears S. 1° E., 142.5 lks. dist., mkd. C-E-W-W 1/256 S10 BT.	

Subdivision of Sec. 10, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>A fence cor. bears N. 62° W., 22 lks. dist.; fences extend E, S and W.</p> <p>An axle, of unknown origin, projecting 8 ins. above ground, bears N. 59° W., 20.5 lks. dist.</p>	
73.40	Show Low Lake road, asphalt surfaced, bears S and NW.	
80.82	The 1/4 sec. cor. of secs. 9 and 10.	
<hr/> <p>NE 1/4, Sec. 10</p> <hr/>		
	<p>From the center E 1/16 sec. cor. of sec. 10.</p> <p>N. 0°25' E., on the N. and S center line of the NE 1/4 of sec. 10.</p> <p>Over gently rolling land, through medium timber.</p>	
19.80	<p>Point for NE 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the NE 1/4 of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E NE 1/16 S10 1978</p> <p>from which</p> <p>A ponderosa pine, 7 ins. diam., bears S. 79° E., 47 lks. dist., mkd. NE 1/16 S10 BT.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 5° W., 54.5 lks. dist., mkd. NE 1/16 S10 BT.</p> <p>A fence cor. bears S. 34° E., 52 lks. dist., fences extend S and W.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>	
30.30	Power line, bears S. 15° E. and N. 15° W.	
32.70	Power line, bears S. 15° E. and N. 15° W.	
39.60	The E 1/16 sec. cor. of secs. 3 and 10.	
<hr/>		
	<p>From the N 1/16 sec. cor. of secs. 10 and 11.</p> <p>N. 89°37' W., on the E and W center line of the NE 1/4 of sec. 10.</p> <p>Over gently rolling land, through medium timber.</p>	
15.20	Power line, bears S. 15° E. and N. 15° W.	
15.80	Power line, bears S. 15° E. and N. 15° W.	
20.16	The NE 1/16 sec. cor. of sec. 10.	

Subdivision of Sec. 10, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.32	The center N 1/16 sec. cor. of sec. 10.
	<hr/> SE 1/4, Sec. 10.
	From the E 1/16 sec. cor. of secs. 10 and 15.
	N. 0°25' E., on the N and S center line of the SE 1/4 of sec. 10.
	Over gently rolling land, through medium timber.
19.80	Point for the SE 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the SE 1/4 of sec. 10.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T9N R22E SE 1/16 S10 1978
	from which
	An alligator juniper, 5 ins. diam., bears S. 31° W., 155 lks. dist., mkd. SE 1/16 S10 BT.
	An alligator juniper, 4 ins. diam., bears S. 69° W., 66.5 lks. dist., mkd. X at breast height and BT at the base.
	Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.
	Cor. is located 86 lks. E. of a fence, bears N. 35° E. and S. 35° W.
21.10	Fence, bears N. 35° E. and S. 35° W.
39.60	The center E 1/16 sec. cor. of sec. 10.
	From the S 1/16 sec. cor. of secs. 10 and 11.
	N. 89°46' W., on the E. and W. center line of the SE 1/4 of sec. 10.
	Over rolling land, through medium timber.
2.50	Power line and track road, bear S. 15° E. and N. 15° W.
3.20	Power line, bears S. 15° E. and N. 15° W.
20.09	The SE 1/16 sec. cor. of sec.10.
40.18	The true point for the center S 1/16 sec. cor. of sec. 10.
	<hr/> SW 1/4, Sec. 10
	From the W 1/16 sec. cor. of secs. 10 and 15.

Subdivision of Sec. 10, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0°08' W., on the N and S center line of the SW 1/4 of sec. 10.</p> <p>Over rolling land through dense timber.</p>
9.50	Power line, bears N. 70° E. and S. 70° W.
10.00	Cinder road, bears N. 20° E. and S. 20° W.
19.87	<p>Point for the SW 1/16 sec. cor. of sec. 10, at intersection with the E and W center line of the SW 1/4 of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E SW 1/16 S10 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears S. 32° W., 88 lks. dist., mkd. SW 1/16 S10 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 65° W., 4.5 lks. dist., mkd. SW 1/16 S10 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W of the cor.</p>
39.74	<p>The center W 1/16 sec. cor. of sec. 10.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the true point for the center S 1/16 sec. cor. of sec. 10.</p> <p>N. 89°49' W., on the E and W center line of the SW 1/4 of sec. 10.</p> <p>Over Show Low Lake.</p>
9.00	West shore of Show Low Lake, bears N and S. (scaled)
20.12	The SW 1/16 sec. cor. of sec. 10.
25.15	<p>Point for the center E-W-SW 1/256 sec. cor. of sec. 10.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S10 C-E-W-SW 1/256 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 15 1/2° E., 74.5 lks. dist., mkd. C-E-W-SW 1/256 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 65° E., 96.5 lks. dist., mkd. C-E-W-SW 1/256 BT.</p> <p>Raise a mound of stone 2 1/2 ft. base, 2 ft. high, N of the cor.</p>

Subdivision of Sec. 10, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	Cor. is located 4 lks. E. of a N-S fence.
32.70	Show Low Lake road, asphalt surfaced, bears N and S.
40.24	The S 1/16 sec. cor. of secs. 9 and 10.
<hr/> <p>NW 1/4, Sec. 10</p> <hr/>	
	From the center W 1/16 sec. cor. of sec. 10.
	N. 0°25' E., on the N and S center line of the NW 1/4 of sec. 10. Over Show Low Lake.
1.50	Shore of Show Low Lake, bears NW and SE.
19.85	Point for the NW 1/16 sec. cor. of sec. 10, at intersection with the E. and W. center line of the NW 1/4 of sec. 10, falls in Show Low Lake, not monumented.
24.20	Show Low Lake Dam, bears SE and NW.
39.70	The W 1/16 sec. cor. of secs. 3 and 10.
<hr/>	
	From the Center N 1/16 sec. cor. of sec. 10.
	N. 89°37' W. on the E. and W. center line of the NW 1/4 of sec. 10.
	Over gently rolling land, through medium timber.
10.12	Point for the center E-NW 1/64 sec. cor. of sec. 10.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 9 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	<p>S10 C-E-NW 1/64 1978</p>
	from which
	An alligator juniper, 5 ins. diam., bears N. 44° E., 31 lks. dist., mkd. C-E-NW 1/64 S10 BT.
	A fence cor. bears S. 65° E., 102 lks. dist., with fences extending N, S, and E.
	A granite boulder, 6 x 6 x 4 ft. above ground, bears S. 43 1/2° W., 54 lks. dist., mkd. XBO on top.
18.20	East shore of Show Low Lake, bears S. 65° E. and N. 65° W.
20.24	True point for the NW 1/16 sec. cor. of sec. 10.
34.70	West shore of Show Low Lake, bear N and S.
37.00	Show Low Lake road, asphalt surfaced, bears N and S.
40.49	The N 1/16 sec. cor. of secs. 9 and 10.

Subdivision of Sec. 11, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Subdivision of Sec. 11, T. 9 N., R. 22 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 14.</p> <p>N. 0°32' E., on the N and S. center line of sec. 11.</p> <p>Over gently rolling land, through scattered timber.</p> <p>19.79 Point for the center S 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R22E</p> <p>C</p> <p> </p> <p>S 1/16 S11</p> <p> </p> <p>C</p> <p>1978</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 4° E., 101.5 lks. dist., mkd. CS 1/16 S11 BT.</p> <p style="padding-left: 40px;">An alligator juniper, 8 ins. diam., bears S. 86° W., 144 lks. dist., mkd. CS 1/16 S11 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the cor.</p> <p>Cor. is located 63 lks. E of a N-S fence.</p> <p>20.45 Fence, bears E and W.</p> <p>39.58 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E and W center line of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R22E</p> <p>C 1/4 S11</p> <p>1978</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 45° E., 40 lks. dist., mkd. C 1/4 S11 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 16° W., 14 lks. dist., mkd. C 1/4 S11 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W of the cor.</p> <p>40.60 Fence, bears E and W.</p> <p>79.09 The 1/4 sec. cor. of secs. 2 and 11.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 11 and 12.</p> <p>S. 89°43' W., on the E and W center line of sec. 11.</p>

Subdivision of Sec. 11, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	Over rolling land, through dense timber.
.60	Fence, bears S. 30° E. and N. 30° W.
3.20	Track road, bears S. 20° E. and N. 20° W.
40.35	The center 1/4 sec. cor. of sec. 11.
60.60	Fence cor., bears North, 100 lks. dist.; fences extend N and E.
80.38	The 1/4 sec. cor. of secs. 10 and 11.
<hr/> Subdivision of Sec. 12, T. 9 N., R. 22 E., Gila and Salt River Meridian, Arizona <hr/>	
	From the 1/4 sec. cor. of secs. 12 and 13.
	N. 1°14' E., on the N and S center line of sec. 12.
	Over rolling land, through dense timber.
9.93	Point for the center S-S 1/64 sec. cor. of sec. 12, falls on a volcanic boulder, 7 x 3 x 2 ft. above ground.
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole in the boulder, with top mkd.
	S12 C-S-S 1/64 1978
	from which
	A ponderosa pine, 10 ins. diam., bears N. 2° E., 85 lks. dist., mkd. C-S-S 1/64 S12 BT.
	An oak, 8 ins. diam., bears N. 50° W., 13 lks. dist., mkd. C-S-S 1/64 S12 BT.
	Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, E of the cor. The boulder prevented building the mound W of the cor.
19.86	Point for the center S 1/16 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T9N R22E C S 1/16 S12 C 1978
	from which
	An alligator juniper, 11 ins. diam., bears S. 28° E., 37 lks. dist., mkd. CS 1/16 S12 BT.
	An alligator juniper, 7 ins. diam., bears S. 31° W., 28 lks. dist., mkd. CS 1/16 S12 BT.

Subdivision of Sec. 12, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W of the corner.</p>
35.80	Track road, bears N. 65° E. and S. 65° W.
39.72	<p>Point for the center 1/4 sec. cor. of sec. 12, at intersection with the E and W center line of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E C 1/4 S12 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 32° E., 5.5 lks. dist., mkd. C 1/4 S12 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 74° W., 26.5 lks. dist., mkd. C 1/4 S12 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W of the cor.</p>
46.90	Fence, bears N. 75° E. and S. 75° W.
77.43	The 1/4 sec. cor. of secs. 1 and 12.
	<hr/> <p>From the 1/4 sec. cor. of secs. 7 and 12, on the E. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 3 ins. above ground, with brass cap mkd. as described in the official record of the 1967 resurvey, from which</p> <p style="padding-left: 40px;">A ponderosa pine, 25 ins. diam., mkd. in 1967, bears N. 82 1/4° E., 188 lks. dist., mkd. 1/4 S7 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 26 ins. diam., mkd. in 1967, bears S. 18 1/2° W., 54 lks. dist., mkd. 1/4 S12 BT.</p> <p style="padding-left: 40px;">A white oak, 16 ins. diam., mkd. in 1883, bears N. 77° W., 51 lks. dist., mkd. with a healed blaze.</p> <p>A mound of stone, 2 ft. base, 10 ins. high, is W of the cor.</p> <p>S. 87°48' W., on the E and W center line of sec. 12.</p> <p>Over rolling land through dense timber.</p>
26.75	Fence, bears N and S.
33.00	Track road, bears NE and SW.
37.89	The center 1/4 sec. cor. of sec. 12.
57.33	<p>Point for the center W 1/16 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Subdivision of Sec. 12, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	T9N R22E W 1/16 C-----C S12 1978
	from which
	A ponderosa pine, 13 ins. diam., bears N. 20° E., 59 lks. dist., mkd. CW 1/16 S12 BT.
	A ponderosa pine, 9 ins. diam., bears S. 89° E., 13 lks. dist., mkd. CW 1/16 S12 BT.
69.40	Fence, bears N. 25° E. and S. 25° W.
76.77	The 1/4 sec. cor. of secs. 11 and 12.
SW 1/4, Sec. 12 -----	
	From the point for the W 1/16 sec. cor. of secs. 12 and 13.
	N. 1°09' E., along the N. and S. center line of the SW 1/4, sec. 12.
	Over gently rolling land, through open grass land.
9.50	Fence, bears S. 60° E. and N. 60° W.
9.70	Irrigation ditch, flows N. 60° W.
12.00	Track road, bears S. 80° E. and N. 80° W.
	Enter dense timber, edge bears S. 80° E. and N. 80° W.
19.82	Point for the SW 1/16 sec. cor. of sec. 12, at intersection with the E and W center line of the SW 1/4 of sec. 12.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	T9N R22E SW 1/16 S12 1978
	from which
	An alligator juniper, 5 ins. diam., bears N. 39° W., 39 lks. dist., mkd. XBT.
	A pinyon pine, 8 ins. diam., bears N. 1 1/2° W., 68.5 lks. dist., mkd. SW 1/16 S12 BT.
24.60	Track road, bears S. 20° E. and N. 20° W.
27.00	Same track road, bears N. 25° E. and S. 25° W.
29.73	Point for the center N-SW 1/64 sec. cor. of sec. 12.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	12 C-N-SW 1/64 1978

Subdivision of Sec. 12, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>from which</p> <p>An alligator juniper, 6 ins. diam., bears N. 48 1/2° E., 26.5 lks. dist., mkd. C-N-SW 1/64 S12 BT.</p> <p>An alligator juniper, 10 ins. diam., bears S. 32 1/2° W., 75.5 lks. dist., mkd. C-N-SW 1/64 S12 BT.</p> <p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>	
	39.64	<p>The CW 1/16 sec. cor. of sec. 12.</p> <hr/> <p>From the center S 1/16 sec. cor. of sec. 12.</p> <p>S. 87°55' W., on the E. and W. center line of the SW 1/4 of sec. 12.</p> <p>Over rolling land, through dense timber.</p>	
	9.70	<p>Point for the center E-SW 1/64 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">S12 C-E-SW 1/64 1978</p>	
	16.30	<p>from which</p> <p>An alligator juniper, 17 ins. diam., bears N. 63° E., 77 lks. dist. mkd. C-E-SW 1/64 S12 BT.</p> <p>Track road, bears S. 55° E. and N. 55° W.</p>	
	19.40	<p>The SW 1/16 sec. cor. of sec. 12.</p>	
	38.80	<p>The S 1/16 sec. cor. of secs. 11 and 12.</p> <hr/> <p>From the center E-SW 1/64 sec. cor. of sec. 12.</p> <p>N. 1°11'30" E., on the N and S center line of the NE 1/4 SW 1/4 of sec. 12.</p> <p>Over rolling land, through dense timber.</p>	
	7.90	<p>Track road, bears N. 50° E. and S. 50° W.</p>	
	9.92	<p>Point for the NE-SW 1/64 sec. cor. of sec. 12.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S12 NE-SW 1/64 1978</p>	

Subdivision of Sec. 12, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>An alligator juniper, 10 ins. diam., bears S. 88° E., 11.5 lks. dist., mkd. NE-SW 1/64 S12 BT.</p> <p>A ponderosa pine, 13 ins. diam., bears S. 34° E., 93 lks. dist., mkd. NE-SW 1/64 S12 BT.</p> <p>Raise a mound of stone, 2 1/2 base, 1 1/2 ft. high, W. of the cor.</p> <p>S. 87°52' W., on the E. and W. center line of the NE 1/4 SW 1/4 of sec. 12.</p> <p>Over rolling land, through dense timber.</p>
6.60	Track road, bears SE and NW.
8.50	Same track road, bears NE and SW.
9.71	The center N-SW 1/64 sec. cor. of sec. 12.
	<hr/> <p>From the center S-S 1/64 sec. cor. of sec. 12.</p> <p>S. 87°58' W., on the E and W center line of the SE 1/4 SW 1/4 of sec. 12.</p> <p>Over rolling land, through dense timber.</p>
9.69	Point for the SE-SW 1/64 sec. cor. of sec. 12.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S12 SE-SW 1/64 1978</p>
	<p>from which</p> <p>An alligator juniper, 7 ins. diam., bears N. 66 1/2° E., 29 lks. dist., mkd. SE-SW 1/64 S12 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of the cor.</p> <p>N. 1°11'30" E., on the N and S center line of the SE 1/4 SW 1/4 of sec. 12.</p> <p>Over rolling land, through dense timber.</p>
9.92	The center E-SW 1/64 sec. cor. of sec. 12.
	<hr/> <p>Subdivision of Sec. 14, T. 9 N., R. 22 E., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of sec. 14 and 23.</p> <p>N. 0°23' E., on the N and S center line of sec. 14.</p> <p>Over rolling land, through medium timber.</p>

Subdivision of Sec. 14, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
10.00	Show Low Creek, 30 lks. wide, course N. 80° W.	
19.78	Point for the center S 1/16 sec. cor. of sec. 14.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 17 ins.	
	in the ground to solid rock, and in a mound of stone, 4	
	ft. base, to top, with brass cap mkd.	
	<div style="text-align: center;"> T9N R22E C S 1/16 S14 C 1978 </div>	
	from which	
	A fence cor. bears N. 25° E., 75 lks. dist., fences	
	extend N and W.	
	An alligator juniper, 4 ins. diam., bears	
	N. 77 1/4° W., 168 lks. dist., mkd. X at breast	
	height and BT at the base.	
	An alligator juniper, 12 ins. diam., bears	
	N. 41 1/2° W., 160 lks. dist., mkd.	
	CS 1/16 S14 BT.	
36.20	Show Low Creek, 50 lks. wide, course S. 80° E.	
39.56	True point for the center 1/4 sec. cor. of sec. 14,	
	at intersection with the E and W center line of sec. 14,	
	falls in Show Low Creek, not monumented.	
39.80	Show Low Creek, 80 lks. wide, course N. 50° W.	
40.56	Point selected for the witness center 1/4 sec. cor. of	
	sec. 14.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins.	
	in the ground, with brass cap mkd.	
	<div style="text-align: center;"> W C T9N R22E C 1/4 S14 1978 </div>	
	from which	
	A volcanic boulder, 7 x 5 x 2 ft. above water, bears	
	S. 8 1/2° E., 84 lks. dist., mkd. XBO on top.	
	A volcanic boulder, 5 x 5 x 5 ft. above ground,	
	bears N. 71 1/2° W., 72.5 lks. dist., mkd. XBO on	
	the NE face.	
	Raise a mound of stone, 3 ft. base, 1 ft. high, W. of	
	the cor.	
	Cor. is located 23 lks. W. of a N-S fence.	
57.10	Track road, bears S. 35° E. and N. 35° W.	
57.80	Fence, bears E and W.	
63.90	Power line, bears S. 25° E. and N. 25° W.	

Subdivision of Sec. 14, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
64.90	Power line and track road, bear S. 25° E. and N. 25° W.
78.95	The 1/4 sec. cor. of secs. 11 and 14.
<hr/>	
From the 1/4 sec. cor. of secs. 13 and 14.	
S. 89°50' W., on the E and W center line of sec. 14.	
Over level land, along a graded cinder road.	
20.00	Fence, bears N and S, enter rolling land covered with medium timber.
23.30	Power line, bears S. 30° E. and N. 30° W.
38.40	Show Low Creek, 60 lks. wide, course N. 80° W.
39.72	The true point for the center 1/4 sec. cor. of sec. 14.
79.20	Cinder road, bears N and S, curving E.
79.60	The 1/4 sec. cor. of secs. 14 and 15.
<hr/>	
Subdivision of Sec. 15, T. 9 N., R. 22 E., Gila and Salt River Meridian, Arizona	
<hr/>	
From the 1/4 sec. cor. of secs. 15 and 22.	
N. 0°20' E., on the N and S center line of sec. 15.	
Over gently rolling land, through medium timber.	
19.53	Point for the center S 1/16 sec. cor. of sec. 15, not monumented.
39.06	Point for the center 1/4 sec. cor. of sec. 15, at intersection with the E and W center line of sec. 15.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground to solid rock, and in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.	
<p style="text-align: center;">T9N R22E C 1/4 S15 1978</p>	
from which	
<p style="text-align: center;">A ponderosa pine, 7 ins. diam., bears N. 35° E., 17 lks. dist., mkd. C 1/4 S15 BT.</p>	
<p style="text-align: center;">A ponderosa pine, 9 ins. diam., bears N. 30° W., 35 lks. dist., mkd. X at breast height and BT at the base.</p>	
50.80	Show Low Creek, 50 lks. wide, flows N. 60° W.
57.40	Power line bears N. 65° E. and S. 65° W.
58.84	Point for the center N 1/16 sec. cor. of sec. 15.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	

Subdivision of Sec. 15, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T9N R22E C N 1/16 S15 C 1978</p> <p>from which</p> <p>An alligator juniper, 6 ins. diam., bears N. 33° E., 33.5 lks. dist., mkd. CN 1/16 S15 BT.</p> <p>An alligator juniper, 5 ins. diam., bears N. 41° W., 19 lks. dist., mkd. CN 1/16 S15 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.</p>	
78.62	The 1/4 sec. cor. of secs. 10 and 15.	
	<hr/> <p>From the 1/4 sec. cor. of secs. 14 and 15.</p> <p>S. 89°50' W., on the E and W center line of sec. 15.</p> <p>Over rolling land, through dense timber.</p>	
40.22	The center 1/4 sec. cor. of sec. 15.	
60.24	<p>The center W 1/16 sec. cor. of sec. 15, monumented with a re-bar 12 ins. long, 5/8 in. diam., projecting 3 ins. above ground. This monument was set in 1974 by George Matkin, Registered Civil Engineer No. 5047 in Arizona, and a record of his survey No. 6454 is on file at Matkin Engineering in Show Low, Arizona.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground over an X chiseled in solid rock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R22E W 1/16 C _____ C S15 1978</p> <p>from which</p> <p>The NW cor. of a frame house, 44 x 38 ft., bears N. 64 1/2° E., 61.5 lks. dist., the long side bears South.</p> <p>An alligator juniper, 12 ins. diam., bears S. 77° W., 48.5 lks. dist., mkd. C-W 1/16 S15 BT.</p> <p>An alligator juniper, 9 ins. diam., bears N. 33° W., 79.5 lks. dist., mkd. C-W 1/16 S15 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>S. 89°50' W., beginning new measurement.</p>	
19.10	Show Low Lake Road, asphalt surface, bears N. 35° E. and S. 35° W.	

Subdivision of Sec. 15, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
20.08	The 1/4 sec. cor. of secs. 15 and 16.
<hr/> SW 1/4, Sec. 15 <hr/>	
	From the point for the W 1/16 sec. cor. of secs. 15 and 22.
	N. 0°22' E., on the N and S center line of the SW 1/4 of sec. 15.
	Along graded gravel road.
.25	Power line, bears E. and W.
11.00	State highway No. 260, asphalt surfaced, bears SE and NW.
12.70	Power line and fence, bears SE and NW; enter pasture.
19.48	Point for the SW 1/16 sec. cor. of sec. 15, at intersection with the E and W center line of the SW 1/4 of sec. 15.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T9N R22E SW 1/16 S15 1978
	from which
	A fence cor., bears N. 49° E., 47.5 lks. dist., with fences extending E, W, and irregularly N.
	A ponderosa pine, 4 ins. diam., bears N. 77° W., 212 lks. dist., mkd. X at breast height and BT at the base.
	A ponderosa pine, 8 ins. diam., bears N. 19° W., 136 lks. dist., mkd. SW 1/16 S15 BT.
	Deposit broken glass at base of iron post.
	Cor. is located 32 lks., S of telephone and fence lines, bearing E and W.
	Cor. is 60 lks. N of the W edge of a dike.
21.70	Cinder driveway, bears E. and W.
24.85	The NW cor. of a house, 44 x 20.7 ft., bears East, .5 lk. dist., the long side bears S. 35° E.
38.95	The center W 1/16 sec. cor. of sec. 15.
<hr/>	
	From the point for the center S 1/16 sec. cor. of sec. 15.
	West, on the E and W center line of the SW 1/4 of sec. 15.
	Over gently rolling land, through medium timber.
20.04	The SW 1/16 sec. cor. of sec. 15.

Subdivision of Sec. 15, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
27.00	Power line and fence, bears SE and NW.
28.40	State Highway No. 260, asphalt surfaced, bears SE and NW.
29.80	Fence, bears SE and NW.
40.13	The S 1/16 sec. cor. of secs. 15 and 16.
<hr/> NW 1/4, Sec. 15 <hr/>	
<p>From the center W 1/16 sec. cor. of sec. 15.</p>	
<p>N. 0°05' E., on the N and S center line of the NW 1/4 of sec. 15.</p>	
<p>Over nearly level land, through dense timber.</p>	
9.80	Show Low Lake Road, asphalt surfaced, bears W and E, curving N.
10.22	<p>The center S NW 1/64 sec. cor. of sec. 15, monumented with a re-bar, 3/4 in. diam., projecting 4 ins. above ground, set in concrete alongside a railroad rail, projecting 2 1/2 ft. above ground. This position was shown to me by a land owner residing in the SW 1/4 SW 1/4 NW 1/4, has been used for road right of ways and is accepted as the cor. position. It is impractical to re-monument this position, from which the following cor. accessories</p>
<p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 4 ins. in the ground to solid rock and in a mound of stone, 4 ft. base, to top, for a reference monument, bears N. 57° E., 151.5 lks. dist., with brass cap mkd. C-S-NW 1/64 S15 RM 100 FT. 1978 and an arrow pointing to the cor.</p>	
<p style="padding-left: 40px;">An alligator juniper, 5 ins. diam., bears S. 58° E., 170.5 lks. dist., mkd. C-S-NW 1/64 S15 BT.</p>	
<hr/> <p>N. 0°44' E., beginning new measurement.</p>	
<p>On the W right of way of Show Low Lake road.</p>	
4.965	<p>A re-bar, 5/8 in. diam., projecting 4 ins. above a concrete base, with a brass tag attached mkd. 5047. A railroad rail projecting 3 ft. above ground is set alongside. This position was established in 1956 by Maddock & Associates Engineer, Inc. and is shown on Show Low Estates subdivision plat as the SE cor. N 1/4, SW 1/4, NW 1/4, sec. 15, (SE cor. of lot 20). This plat is on file at the Transamerica Title Company in Show Low, Arizona.</p>
9.25	Show Low Lake road, asphalt surfaced, bears W an E, curving S.

Subdivision of Sec. 15, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS

9.87

The NW 1/16 sec. cor. of sec. 15 monumented with a re-bar, 15 ins. long, 3/4 in. diam., set flush with the shoulder of Show Low Lake Road. This position was established in 1956 by Maddock & Associates Engineer, Inc. and is shown on Show Low Estates subdivision plat as the SE cor., NW 1/4, NW 1/4, sec. 15. This plat is on file at the Transamerica Title company in Show Low Arizona.

At the cor. point

Set an iron post, 14 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T9N R22E
NW 1/16 S15
1978

from which

An alligator juniper, 10 ins. diam., bears
N. 12° E., 6.5 lks. dist., mkd. NW 1/16 S15 BT.

A ponderosa pine, 9 ins. diam., bears
S. 60° E., 110.5 lks. dist., mkd. NW 1/16 S15 BT.

Reset re-bar alongside the iron post.

N. 0°24' E., beginning new measurement.

Over rolling land, through medium timber.

19.56

The W 1/16 sec. cor. of secs. 10 and 15.

From the center N 1/16 sec. cor. of sec. 15.

N. 89°16' W., on the E and W center line of the NW 1/4 of sec. 15.

Over rolling land, through dense timber.

11.50

Show Low Creek, course irregularly N. (Scaled)

19.99

The NW 1/16 sec. cor. of sec. 15.

S. 89°07' W., beginning new measurement.

On the N right of way of Show Low Lake road.

5.01

The center E-W-NW 1/256 sec. cor. of sec. 15, monumented with a re-bar, 15 ins. long, 3/4 ins. diam., set flush with the ground, alongside an open end pipe, 18 ins. long 3/4 in. diam. This position was established in 1956 by Maddock & Associates Engineers Inc. and is shown on Show Low Estates subdivision plat as the SE cor., W 3/4, NW 1/4, NW 1/4, sec. 15. (SE cor. of lot 19) This plat is on file at the Transamerica Title Company in Show Low, Arizona.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.

S15
C-E-W-NW
1/256
1978

Subdivision of Sec. 15, T. 9 N., R. 22 E.,
Gila and Salt River Meridian, Arizona

CHAINS

from which

A fence cor. bears N. 2° E., 15.3 lks. dist.; fences extend N and E.

An alligator juniper, 10 ins. diam., bears N. 52° E., 38.5 lks. dist., mkd. C-E-W NW 1/256 S15 BT.

Raise a mound of stone 2 1/2 ft. base, 2 1/2 ft. high N of the cor.

Cor. is located 33 lks. N of Show Low Lake Road, asphalt surfaced, bears E and W.

S. 89°17' W., beginning new measurement.

- | | |
|-------|--|
| 3.70 | Road, asphalt surfaced, bears N and S. |
| 11.20 | Road, asphalt surfaced, bears N and S. |
| 15.02 | The point for the N 1/16 sec. cor. of secs. 15 and 16. |

GENERAL DESCRIPTION

The area surveyed within T. 9 N., R. 22 E., varies from rolling to nearly level. The elevation ranges from about 6,500 to 7,000 ft. above sea level. The soil is a stony clay loam. The vegetation consists of pine, juniper and oak timber in the higher elevations with a good cover of native grasses in the open areas. Drainage being generally west and north, is furnished by Porter Creek which enters the Township at the corner of secs. 7, 12, 13 and 18, on the east boundary, meanders through sec. 13 and half way through section 14 to the confluence of Billy Creek, where the name changes to Show Low Creek, which exits on the north boundary of section 3.

Access is provided by State Highway No. 260, which passes through the SW 1/4 of section 15 from which numerous graded and track roads extend.

Scott Reservoir is located in section 13 and Show Low Lake is located in section 10, both are used for irrigation and fishing.

Homes are located on patented land in sections 10, 12, 14 and 15.

There was no evidence of mineral deposits or mining activity.

An average number of readings throughout the area surveyed gives a mean magnetic declination of 14° E., with a range of 5° in local attraction.

CHAINS

CERTIFICATE OF SURVEY

SUPERVISORY

(I) ~~(We)~~ Harry K. Smith, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 23rd day of June, 1978, ~~(I)~~ ~~(We)~~ and Supplemental Special Instructions dated June 5, 1979, have dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines and a portion of the subdivision in section 13, and surveyed subdivisions in certain sections of Township 9 North, Range 22 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(XX)~~ and under (my) ~~(XX)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

9-26-79
(Date)

Harry K. Smith
SUPERVISORY (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines and a portion of the subdivision in section 13, and the survey of subdivisions in certain sections of T. 9 N., R. 22 E., of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor,
having been critically examined and found correct, are hereby approved.

DEC 11 1979
(Date)

J. Voorhes
(Chief, Division of Cadastral Survey)
Chief, Cadastral Survey Examination and Approval Staff

~~CERTIFICATE OF TRANSCRIPT~~

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) 680-840-626