

Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH, EAST AND WEST BOUNDARIES

A PORTION OF THE SUBDIVISIONAL LINES

AND

A PORTION OF THE SUBDIVISION LINES (WITHIN SECTION 31)

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES

WITHIN A NUMBER OF SECTIONS

AND

THE SURVEY OF TRACTS 37, 38, 39, 40, AND 41

TOWNSHIP 7 SOUTH, RANGE 15 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

JAMES P. SCOTT

CADASTRAL SURVEYOR

RAY HARPIN

CADASTRAL SURVEYOR

Under special instructions dated OCTOBER 14, 1969, approved OCTOBER 27, 1969,

AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED NOVEMBER 20, 1969, APPROVED

NOVEMBER 21, 1969, which provided for the surveys included under ~~US Survey~~ Group

Number 517, and assignment instructions dated OCTOBER 14, 1969.

Survey commenced OCTOBER 28, 1969

Survey completed FEBRUARY 6, 1970

114

BOOK 5 100

INDEX DIAGRAM

Township 7 South, Range 15 West,

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24 5
		23	20	15	11
30	29 22	28 19	27 14	26 9	25 3
26	25	21	18	14	8
7 24					
31	32	33 16	34 12	35	36
			2		

- Subdivision of section 25 pg. 29
- Subdivision of section 26 pg. 31
- Subdivision of section 27 pg. 33
- Subdivision of section 28 pg. 35
- Subdivision of section 29 pg. 38
- Dependent Resurvey of the
subdivision lines, section 31 pg. 40
- Subdivision of section 34 pg. 41
- Survey of Tract 37. pg. 43
- Survey of Tract 38. pg. 45
- Survey of Tract 39. pg. 46
- Survey of Tract 40. pg. 48
- Survey of Tract 41. pg. 51

Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south, east, and west boundaries of the township, a portion of the subdivisional lines, and a portion of the subdivision lines (within section 31); the survey of a portion of the subdivision lines within a number of sections, and the survey of Tracts 37, 38, 39, 40, and 41, Township 7 South, Range 15 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The township exterior boundaries and subdivisional lines were surveyed by T. F. White, U. S. Deputy Surveyor, in 1877, as shown upon the official plat approved 30th July 1877. A portion of the south boundary was dependently resurveyed by Francis E. Joy, in 1934, as described in the official record of the north boundary of Township 8 South, Range 15 West, and shown upon the official plat for that survey approved February 23, 1935, and accepted April 2, 1935. A portion of the west boundary and a portion of the subdivisional lines were dependently resurveyed, and a portion of the subdivision lines within sections 19 and 31 were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953, as shown upon the official plat, examined and approved by the Bureau of Reclamation, Washington, D. C., March 17, 1955, and was accepted by the Bureau of Land Management, Cadastral Engineering Staff Officer, March 17, 1955.

The dependent resurvey and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 Edition, and the Special Instruction dated October 14, 1969, and Supplemental Special Instructions dated November 20, 1969.

The direction of all lines of these surveys were determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains and reduced to horizontal equivalents.

Prior to the restoration of any corner, all necessary lines of the original survey were retraced and a diligent search was made for any evidence of the original corner monuments and calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The data furnished with the special instructions give the geographic position of the corner of sections 25, 30, 31, and 36 on the east boundary of the township, as: Latitude $32^{\circ} 46.9' N.$, and Longitude $113^{\circ} 44.8' W.$ The mean magnetic declination is 14° East.

Dependent Resurvey of a Portion
of the South Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Survey Executed by
Francis E. Joy, in 1934

The cor. of secs. 2, 3, 34, and 35 (on the south boundary of the township), Tps. 7 and 8 S., R. 15 W., which is monumented with an iron post, 2 ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with regulation (G.L.O.) brass cap mkd.

T7S R15W
S 34 | S 35
S 3 | S 2
T8S

1934

S. 89° 53' W., between Tps. 7 and 8 S., through R. 15 W., and between secs. 3 and 34.

Descend over gently rolling land, through scattering paloverde, mesquite, and tesota trees; undergrowth, young trees and brush.

20.01 The point for the east 1/16 sec. cor. of secs. 3 and 34.

Set an iron post, 28 ins. long, 2½ ins. in diam., 22 ins. in the ground, with brass cap mkd.

E 1/16 $\frac{S 34}{S 3}$

1970

36.00 Wash, 10 lks. wide, 25 ft. deep, drains northwest.

40.02 The true point for the 1/4 sec. cor. of secs. 3 and 34 is determined at proportionate distance from the hereinafter described witness corner.

This true corner point is located within the above wash, drains southwest.

41.53 The witness 1/4 sec. cor. of secs. 3 and 34 is monumented with an iron post, 1-inch in diam., firmly set, projecting 12 ins. above the surface of the ground, with regulation (G.L.O.) brass cap mkd.

1/4 $\frac{W C}{S 34}$
S 3 →

1934

Dependent Resurvey of a Portion
of the South Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

S. 89° 53' W., beginning new measurement.

- 18.77 The point for the west 1/16 sec. cor. of secs. 3 and 34.
Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

$$W \frac{1}{16} \frac{S \ 34}{S \ 3}$$

1970

- 39.05 The cor. of secs. 3, 4, 33, and 34, is monumented with an iron post, 2 ins. in diam., firmly set, projecting 10 ins. above the surface of the ground, with regulation (G.L.O.) brass cap mkd.

$$\begin{array}{c} T7S \ R15E \\ S \ 33 \ | \ S \ 34 \\ \hline S \ 4 \ | \ S \ 3 \\ T8S \end{array}$$

1934

substantiated by:

A mound of stone, 3 ft. base, 1 ft. high, west of the corner.

Discontinue the dependent resurvey of the township line at this corner.

Dependent Resurvey of a Portion
of the East Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
T. F. White, U. S. Deputy Surveyor, in 1877

The cor. of secs. 25, 30, 31, and 36, Tps. 7 S., Rs. 14 and 15 W., which is marked with an iron pipe, of undetermined length, 2 ins. in diam., with brass cap 12 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
T7S
R15W
S 25, S 30
S 36 S 31
R14W

1952

Dependent Resurvey of a Portion
of the East Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

from which

An electric transmission line pole, bears N. 50° 15' E., 68 lks. distant.

The northeasterly corner of a concrete lateral, bears S. 62° 30' W., 98 lks. distant.

A Bureau of Reclamation bench mark, with a regulation brass tablet seated on top of the south wall of a concrete lateral, bears N. 63° 16' W., 102 lks. distant, marked ELEV. 319.25 FT.

N. 0° 06' E., through Tps. 7 S., between Rs. 14 and 15 W., and between secs. 25 and 30.

Over nearly level land, through dense French tamarisk.

20.07 The point for the south 1/16 sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.

S 1/16

S 25 | S 30

1969

36.50 The left bank of the Gila River (a dry wash), course southwest.

40.14 The point for the 1/4 sec. cor. of secs. 25 and 30 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.

T7S
R15W R14W
1/4

S 25 | S 30

1969


44.00 The right bank of the Gila River.

47.85 The point for Angle Point No. 6, Tract 37, Tp. 7 S., R. 15 W.

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the East Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona


CHAINS



1969

71.49 The point for Angle Point No. 1, Tract 37, Tp. 7 S.,
R. 15 W.

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins.
in the ground, with brass cap mkd.




1969

79.49 A concrete lateral, bears east and west, flows west.

80.28 The cor. of secs. 19, 24, 25, and 30 is marked with a
wood stake, 23 ins. long, 3 ins. in diam., set 13 ins. in
the ground, and is accepted as the best available evi-
dence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins.
in the ground, with brass cap mkd.



1969

Deposit the wood stake corner marker alongside the iron
post.

from which

A Bureau of Reclamation bench mark, with a regu-
lation brass tablet seated on top of the north wall
of a concrete lateral, bears S. 61° 40' W., 96 lks.
distant, mkd. ELEV. 319.98 FT.

N. 0° 01' W., between secs. 19 and 24

Over nearly level land, along a north and south roadway.

Dependent Resurvey of a Portion
of the East Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

20.025 The point for the south 1/16 sec. cor. of secs. 19 and 24. I did not monument this corner point.

40.05 The point for the 1/4 sec. cor. of secs. 19 and 24 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., 24 ins. in the ground, with brass cap mkd.

T7S
R15W R14W
1/4
S 24 | S 19

1969

from which

An electric transmission line pole, bears S. 20° 45' E., 121 lks. distant.

A cross (+) chiseled on a concrete lateral, bears S. 82° 10' W., 79 lks. distant.

80.10 The cor. of secs. 13, 18, 19, and 24 is marked with an iron pipe, 2 ins. in diam., with brass cap 4 ins. below the surface of the road, mkd.

T7S
R15W R14W
S 13 | S 18
S 24 | S 19

1912

substantiated by:

A cross (+) chiseled on a concrete wall of a lateral, bears S. 60° 03' W., 62.0 ft. distant, mkd. RP + 62.0.

A cross (+) chiseled on a concrete wall of a lateral, bears N. 58° 20' W., 62.0 ft. distant, mkd. RP + 62.0.

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

Discontinue the dependent resurvey of the range line at this corner.

Dependent Resurvey of a Portion
of the West Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Survey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation in 1953

The north 1/16 sec. cor. of secs. 31 and 36 (on the west boundary of the township), Tps. 7 S., Rs. 15 and 16 W., which is marked with an iron pipe, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
N 1/16

S 36 | S 31

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. I did not remonument this corner.

N. 0° 04' W., through Tps. 7 S., between Rs. 15 and 16 W., and between secs. 31 and 36.

Over nearly level land, through areas of dense to scattering French tamarisk.

4.94 The point for Angle Point No. 3, Tract 41, Tp. 7 S., R. 15 W.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S
R16W R15W
| TR 41
| AP 3

S 36 | S 31

1970

Continue on the west boundary of the township, and on line 3 - 2, Tract 41, Tp. 7 S., R. 15 W.

20.09 The cor. of secs. 25, 30, 31, and 36 is marked with an iron pipe, 2 ins. in diam., with brass cap 12 ins. below the surface of a roadway, mkd.

BUREAU OF RECLAMATION

R16W R15W

S 25 | S 30

S 36 | S 31

T7S

1949

Dependent Resurvey of a Portion
of the West Boundary
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. I did not remonument this corner.

There are no suitable accessories nor locations available for reference monuments.

This corner is designated to function for Angle Point No. 2, Tract 41, Tp. 7 S., R. 15 W.

Discontinue the dependent resurvey of the range line at this corner.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
T. F. White, U. S. Deputy Surveyor, in 1877

From the corner of secs. 25, 30, 31, and 36 on the east boundary of the township, heretofore described.

S. 89° 51' W., between secs. 25 and 36.

Over nearly level land.

40.01 The 1/4 sec. cor. of secs. 25 and 36 is marked with an iron pipe, 36 ins. long, 1-inch in diam., with the top 7 ins. below the surface of the roadway, and is accepted as the best available evidence of the position of the corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 9 ins. below the surface of the roadway, mkd.

T7S R15W
1/4 $\frac{S 25}{S 36}$

1969

Deposit the iron pipe corner marker alongside the iron post.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

from which

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 51° 15' E., 44.2 ft. dist., with brass cap mkd. RM T7S R15W S25 44.2 FT. 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears N. 55° 05' W., 48.9 ft. dist., with brass cap mkd. RM T7S R15W S25 48.9 FT. 1969, and an arrow pointing to the corner.

S. 89° 51' W., beginning new measurement.

40.02 The cor. of secs. 25, 26, 35, and 36 is marked with an iron pipe, of undetermined length, 2 ins. in diam., with the top 12 ins. below the surface of the road, and is accepted as the best available evidence of the position of the corner. This corner was not remonumented.

This corner is located at the intersection of roads, bearing north and south, and east and west.

N. 0° 11' E., between secs. 25 and 26

Over nearly level land, along the center line of Avenue 51 East.

40.09 The 1/4 sec. cor. of secs. 25 and 26 is marked with an iron pipe, 2 ins. in diam., with brass cap 9 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

1/4

S 26 | S 25

1952

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

N. 0° 11' E., beginning new measurement

14.31 The point for Angle Point No. 4, Tract 37, and Cor. No. 4, Lot 1, within section 26.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T7S R15W	
L 1	TR 37
C 4	AP 4

S 26	S 25

1969

from which

An iron post, 28 ins. long, 2½ ins. in diam., set 24 ins. in the ground, for a reference monument, bears S. 89° 27' E., 33 ft. distant, with brass cap mkd.

RM	
T7S R15W	
TR 37	
←	33 FT

S 25

1969

20.06 The point for the north 1/16 sec. cor. of secs. 25 and 26.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 10 ins. below the surface of the road, mkd.

N 1/16	
S 26	S 25

1969

from which

An iron post, 28 ins. long, 2½ ins. in diam., set 22 ins. in the ground, for a reference monument, bears S. 43° 30' W., 56.4 ft. dist., with brass cap mkd. RM T7S R15W S26 56.4 FT. 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2½ ins. in diam., set 21 ins. in the ground, for a reference monument, bears N. 34° 40' W., 69.5 ft. dist., with brass cap mkd. RM T7S R15W S26 69.5 FT. 1969, and an arrow pointing to the corner.

This corner is designated to function for Cor. No. 1, Lot 1, section 26.

29.47 The point for Angle Point No. 3, Tract 37.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 9 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

T7S R15W
S 26 | S 25

AP 3
TR 37

1969

from which

An iron post, 28 ins. long, 2½ ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 89° 27' E., 33 ft. distant, with brass cap mkd.

RM
T7S R15W
S 25
← 33 FT
TR 37

1969

40.12 The cor. of secs. 23, 24, 25, and 26 is marked with an iron pipe, 2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
T7S R15W
S 23 | S 24
S 26 | S 25

1951

substantiated by:

An electric transmission line pole, bears S. 48° 10' W., 40.5 ft. distant, mkd. 40.5 FT.

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

From the cor. of secs. 19, 24, 25, and 30 on the east boundary of the township, heretofore described.

S. 89° 48' W., between secs. 24 and 25.

Over nearly level land, along an east and west roadway.

19.98 The point for the east 1/16 sec. cor. of secs. 24 and 25. I did not monument this corner point.

39.96 The 1/4 sec. cor. of secs. 24 and 25 is marked with an iron pipe, 2 ins. in diam., with brass cap 5 ins. below the surface of the roadway, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

$$1/4 \frac{S 24}{S 25}$$

1954

substantiated by:

The northwest corner of a concrete lateral, bears
S. 4° 30' W., 46.0 ft. distant, mkd. 46.0'.

The above corner marker is accepted as the best available
evidence of the position of the original corner. This
corner was not remonumented.

from which

An iron post, 28 ins. long, 2½ ins. in diam., set
24 ins. in the ground, for a reference monument,
bears S. 60° 25' E., 86.4 ft. dist., with brass cap
mkd. RM T7S R15W S25 86.4 FT. 1969, and an arrow
pointing to the corner.

S. 89° 48' W., beginning new measurement.

19.97 The point for the west 1/16 sec. cor. of secs. 24 and 25.
I did not monument this corner point.

39.94 The corner of secs. 23, 24, 25, and 26, heretofore
described.

Discontinue the regular order of survey at this corner.

From the corner of secs. 2, 3, 34, and 35 on the south
boundary of the township, heretofore described.

N. 0° 28' W., between secs. 34 and 35.

Ascend approximately 600 ft. over broken southwest
slope.

20.03 The point for the south 1/16 sec. cor. of secs. 34 and
35. This corner point is located within a deep wash,
drains southwest; an unsafe location for a monument.

21.02 Set an iron post, 28 ins. long, 2½ ins. in diam., over a
cross (+) chiseled on bedrock, and in a mound of stone,
3 ft. base, to the top, for the witness south 1/16 sec.
cor. of secs. 34 and 35, with brass cap mkd.

W C
S 1/16
S 34 | S 35
↓

1970

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS	
27.50	Broken ridgespur, slopes west, descend over broken northwest slope.
39.90	Set an iron post, 28 ins. long, 2½ ins. in diam., over a cross (+) chiseled on bedrock, and in a mound of stone, 3 ft. base, to the top, for the witness 1/4 sec. cor. of secs. 34 and 35, with brass cap mkd.
	<p style="text-align: center;">W C T7S R15W 1/4 ▲ S 34 S 35 1970</p>
40.06	The true point for the 1/4 sec. cor. of secs. 34 and 35, is determined at porportionate distance; there is no evidence of the original corner. This true corner point is located on a very steep northwest slope; an unsafe location for a monument.
59.87	Set an iron post, 28 ins. long, 2½ ins. in diam., over a cross (+) chiseled on bedrock, and in a mound of stone, 3 ft. base, to the top, for the witness north 1/16 sec. cor. of secs. 34 and 35, with brass cap mkd.
	<p style="text-align: center;">W C N 1/16 ▲ S 34 S 35 1970</p>
60.09	The true point for the north 1/16 sec. cor. of secs. 34 and 35. This true corner point is located on a steep north slope; an unsafe location for a monument.
61.40	Base of descent, bears northwest and southeast; thence, descend over north slope, through paloverde trees and undergrowth of young trees, brush, and creosote brush.
71.60	Lateral, bears northwest and southeast; thence, over nearly level land.
80.12	The corner of secs. 26, 27, 34, and 35 is marked with a steel rod, 30 ins. long, 3/4-inch in diam., with the top 9 ins. below the surface of the road,
	<p>substantiated by:</p> <p style="padding-left: 40px;">A cross (+) chiseled on a concrete lateral, bears S. 51° 55' W., 59 ft. distant, mkd. RP + 59'.</p> <p style="padding-left: 40px;">A cross (+) chiseled on a concrete lateral, bears N. 47° 10' W., 61 ft. distant, mkd. RP + 61'.</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T7S R15W
S 27 | S 26
S 34 | S 35

1969

Deposit the steel rod corner marker alongside the iron post.

From the corner of secs. 25, 26, 35, and 36, heretofore described.

S. 89° 49' W., between secs. 26 and 35.

Over nearly level land, along an east and west road.

40.00

The 1/4 sec. cor. of secs. 26 and 35 is marked with an iron pipe, of undetermined length, 1-inch in diam., with the top 7 ins. below the surface of the road, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., over the above corner marker, with brass cap 6 ins. below the surface of the road, mkd.

T7S R15W
1/4 S 26
S 35

1969

from which

A water well, bears N. 40° 55' E., 57 lks. distant.

An electric transmission line pole, bears N. 43° 00' W., 58 lks. distant.

S. 89° 51' W., beginning new measurement.

40.00

The cor. of secs. 26, 27, 34, and 35, heretofore described.

N. 0° 01' E., between secs. 26 and 27.

Over nearly level land, along a north and south road.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

40.02 The point for the 1/4 sec. cor. of secs. 26 and 27 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 9 ins. below the surface of the road, mkd.

T7S R15W
1/4

S 27|S 26

1969

from which

The northeast corner of a concrete lateral, bears S. 80° 10' W., 71 lks. distant.

An U. S. Bureau of Reclamation bench mark bears N. 82° 10' W., 74 lks. distant, and is marked with a brass tablet seated in concrete, near the end of a concrete lateral, mkd. 313.25 FT.

A water level test well, an iron pipe, 1½ ins. in diam., bears N. 65° 45' W., 57 lks. distant.

80.04 The cor. of secs. 22, 23, 26, and 27 is marked with an iron pipe, 2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

T7S R15W
S 22|S 23
S 27|S 26

1940

substantiated by:

A cross (+) chiseled on the concrete base of a water well, bears S. 61° 10' W., 62 lks. distant.

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

There are no other suitable accessories nor locations available for reference monuments.

From the corner of secs. 23, 24, 25, and 26, heretofore described.

S. 89° 43' W., between secs. 23 and 26.

Over nearly level land.

20.01 The point for the east 1/16 sec. cor. of secs. 23 and 26. I did not monument this corner point.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

40.02

The 1/4 sec. cor. of secs. 23 and 26 is marked with an iron pipe, 2 ins. in diam., with brass cap 9 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

$$1/4 \quad \frac{S \ 23}{S \ 26}$$

1952

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

There are no suitable accessories nor locations available for reference monuments.

S. 89° 43' W., beginning new measurement.

40.12

The corner of secs. 22, 23, 26, and 27, heretofore described.

Discontinue the regular order of survey at this corner.

From the corner of secs. 3, 4, 33, and 34 on the south boundary of the township, heretofore described.

N. 0° 05' W., between secs. 33 and 34.

Over rolling land that generally slopes west, through scattering mesquite and paloverde trees, and undergrowth of young trees, brush, creosote brush, and cacti.

20.01

The south 1/16 sec. cor. of secs. 33 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

S 1/16

S 33 | S 34

1950

The above corner marker is accepted as the position of the corner. This corner was not remonumented.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

N. 0° 05' W., beginning new measurement.

- 20.02 The 1/4 sec. cor. of secs. 33 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

1/4

S 33 | S 34

1948

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

N. 0° 05' W., beginning new measurement.

- 14.50 Road, bears northeast and southwest, ascend over southwest slope.
- 20.02 The point for the north 1/16 sec. cor. of secs. 33 and 34.
- Set an iron post, 28 ins. long, 2½ ins. in diam., 15 ins. in the ground, and in a mound of stone, 2½ ft. base, to the top, with brass cap mkd.

N 1/16

S 33 | S 34

1970

- 21.40 Top of ascent (knoll), descend over north slope.
- 24.70 Base of descent, bears east and west; thence, over nearly level land.
- 33.25 Road, bears northeast and southwest.
- 33.85 The right bank of the Mohawk Canal, flows N. 31° E.
- 34.65 The left bank of the canal.
- 35.15 Road, bears N. 31° E., and S. 31° W.
- 40.04 The cor. of secs. 27, 28, 33, and 34 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

T7S R15W

S 28 | S 27

S 33 | S 34

1941

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

From the corner of secs. 26, 27, 34, and 35, heretofore described.

S. 89° 50' W., between secs. 27 and 34.

17.00 Leave road, road bears to the northwest.

17.80 Lateral, bears northwest and southeast; thence, over rolling land that generally slopes north.

20.01 The east 1/16 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 30 ins. long, 1-inch in diam., firmly set, 17 ins. in the ground, with brass cap mkd.

BUREAU OF RECLAMATION

E 1/16

S 27

S 34

1950

The above corner marker is accepted as the position for the corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

E 1/16 S 27

S 34

1970

Deposit the iron pipe corner marker alongside the iron post.

S. 89° 50' W., beginning new measurement.

20.01 The 1/4 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

1/4

S 27

S 34

1950


The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS	
	S. 89° 50' W., beginning new measurement.
20.01	The point for the west 1/16 sec. cor. of secs. 27 and 34.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.
	$W \frac{1}{16} \begin{array}{l} S \ 27 \\ S \ 34 \end{array}$
	1970
20.50	Roadway, bears northeast and southwest.
22.90	The right bank of a wide (floodway) wash, drains northeast.
35.70	The left bank of the (floodway) wash.
36.10	The right bank of the Mohawk Canal, flows on curve to the northeast.
37.10	The left bank of the canal.
40.02	The cor. of secs. 27, 28, 33, and 34, heretofore described.
	N. 0° 04' W., between secs. 27 and 28.
	Over nearly level land.
20.13	The south 1/16 sec. cor. of secs. 27 and 28 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.
	BUREAU OF RECLAMATION
	S 1/16
	S 28 S 27
	1950
	The above corner marker is accepted as the position of the corner. This corner was not remonumented.
	N. 0° 05' W., beginning new measurement.
3.71	The point for Angle Point No. 3, Tract 38, and Angle Point No. 10, Tract 39.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS



1970

- 5.00 Road, bears N. 30° W. and S. 30° E.
- 7.40 Road, bears east and west.
- 20.11 The point for the 1/4 sec. cor. of secs. 27 and 28 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
1/4

S 28 | S 27

1970

- 60.33 This corner is designated to function for Angle Point No. 2, Tract 38, and Angle Point No. 11, Tract 39.
- The cor. of secs. 21, 22, 27, and 28 is marked with a steel bar, of undetermined length, 1-inch in diam., with the top 7 ins. below the surface of the road.

substantiated by:

A cross (+) chiseled on a concrete watergate of a lateral, bears N. 27° 20' W., 81 lks. distant.

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

From the corner of secs. 22, 23, 26, and 27, heretofore described.

N. 89° 52' W., between secs. 22 and 27

Over nearly level land, through areas of dense to scattering mesquite, French tamarisk, and brush.

- 40.08 The 1/4 sec. cor. of secs. 22 and 27 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, and is accepted as the best available evidence of the original corner. This corner was not remonumented.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

- N. 89° 51' W., beginning new measurement
- 40.09 The cor. of secs. 21, 22, 27, and 28, heretofore described.
- Discontinue the regular order of survey at this corner.
-
- From the corner of secs. 27, 28, 33, and 34, heretofore described.
- N. 89° 48' W., between secs. 28 and 33.
- Over nearly level land, through areas of scattering mesquite, French tamarisk, and brush.
- 40.20 The 1/4 sec. cor. of secs. 28 and 33 is marked with an iron pipe, 2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.
- BUREAU OF RECLAMATION
1/4 $\frac{S\ 28}{S\ 33}$
1950
- The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.
-
- N. 89° 49' W., beginning new measurement.
- 20.08 The point for the west 1/16 sec. cor. of secs. 28 and 33. I did not monument this corner point.
- 40.16 The cor. of secs. 28, 29, 32, and 33 is marked with an iron pipe, 30 ins. long, 2 ins. in diam., with brass cap 24 ins. below the surface of the roadway, mkd.
- BUREAU OF RECLAMATION
T7S R15W
 $\frac{S\ 29\ |S\ 28}{S\ 32\ |S\ 33}$
1953
- The above corner marker is accepted as the best available evidence of the position of the original corner.
- At the corner point
- Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the roadway, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

T7S R15W
S 29 | S 28
S 32 | S 33

1970

Deposit the iron pipe corner marker alongside the iron post.

N. 0° 03' W., between secs. 28 and 29.

Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees; undergrowth young trees, brush, creosote brush, and cacti.

3.33 The point for Angle Point No. 5, Tract 39, and Angle Point No. 8, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
TR 40 | TR 39
AP 8 | AP 5

S 29 | S 28

1970

18.52 The point for Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
S 29 | S 28

AP 1 | AP 4
TR 40 | TR 39

1970

20.00 The point for the south 1/16 sec. cor. of secs. 28 and 29. I did not monument this corner point.

40.00 The 1/4 sec. cor. of secs 28 and 29 is marked with a steel rod, of undetermined length, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., over the above corner marker, 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

T7S R15W
1/4

S 29 | S 28

1970

N. 0° 03' W., beginning new measurement.

40.11

The cor. of secs. 20, 21, 28, and 29 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

T7S R15W

S 20 | S 21

S 29 | S 28

1952

substantiated by:

A cross (+) chiseled on a concrete watergate of a lateral, bears N. 30° 10' E., 53 ft. distant, mkd. + 53'.

A cross (+) chiseled on a concrete watergate of a lateral, bears N. 30° 00' W., 53 ft. distant, mkd. + 53'.

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

From the corner of secs. 21, 22, 27, and 28, heretofore described.

S. 89° 56' W., between secs. 21 and 28.

Over nearly level land, along an east and west road.

40.15

The point for the 1/4 sec. cor. of secs. 21 and 28 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T7S R15W
1/4 S 21
S 28

1970

from which

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

An electric transmission line pole, bears S. 83° 40' E., 369 lks. distant.

An electric transmission line pole, bears S. 83° 10' W., 276 lks. distant.

80.30

The cor. of secs. 20, 21, 28, and 29, heretofore described.

Discontinue the regular order of survey at this corner.

Restoring the Survey Executed by
Albin H. Wadin, Engineer,
Bureau of Reclamation, in 1953

The north 1/16 sec. cor. of secs. 31 and 32 is marked with an iron pipe, 1-inch in diam., with brass cap 4 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

N

1/16

S 31 | S 32

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. I did not remonument this corner.

There are no suitable accessories nor locations available for reference monuments.

N. 1° 22' W., between secs. 31 and 32

6.42

The point for Angle Point No. 5, Tract 41

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

T7S R15W

TR 41 |

AP 5 |

S 31 | S 32

1970

from which

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins. long, 2½ ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 85° 50' W., 33 ft. distant, with brass cap mkd.

R M
T7S R15W
TR 41
33 FT
S 31 >

1970

There are no suitable accessories nor locations available for other reference monuments.

20.06 The cor. of secs. 29, 30, 31, and 32 is marked with an iron pipe, 2 ins. in diam., with brass cap 13 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

T7S R15W
S 30 S 29
S 31 S 32

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. I did not remonument this corner.

There are no suitable accessories nor locations available for reference monuments.

This corner is designated to function for Angle Point No. 1, Tract 41.

Restoring the Survey Executed by
T. F. White, U. S. Deputy Surveyor, in 1877

From the corner of secs. 28, 29, 32, and 33, heretofore described.

S. 89° 42' W., between secs. 29 and 32.

Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.

20.41 The point for the east 1/16 sec. cor. of secs. 29 and 32. I did not monument this corner point.

27.12 The point for Angle Point No. 6, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T7S R15W TR 40 <u>AP 6 S 29</u> S 32</p> <p style="text-align: center;">1970</p>	
40.82	<p>The point for the 1/4 sec. cor. of secs. 29 and 32 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 7 ins. below the surface of the roadway, mkd.</p> <p style="text-align: center;">T7S R15W 1/4 <u>S 29</u> S 32</p> <p style="text-align: center;">1970</p>	
	<p>There are no suitable accessories nor locations available for reference monuments.</p> <p>This corner is designated to function for Angle Point No. 5, Tract 40.</p>	
61.23	<p>The west 1/16 sec. cor. of secs. 29 and 32 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 <u>S 29</u> S 32</p> <p style="text-align: center;">1950</p> <p>The above corner marker is accepted as the position for the corner. This corner was not remonumented.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer Bureau of Reclamation, in 1953</p> <hr/> <p>From the corner of secs. 29, 30, 31, and 32, which is designated to function for Angle Point No. 1, Tract 41, heretofore described.</p> <p>S. 89° 58' W., between secs. 30 and 31.</p> <p>Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

- 11.39 The point for Angle Point No. 2, lot 5 and Angle Point No. 1, lot 6 of sec. 31 is determined at proportionate distance; there is no evidence of the original corner.
- MEMORANDUM
- The above lot corner was originally established by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. The area of lots 5, 6, 7, 8, 9, and 10, and the NW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 31 have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots 15, 16, 17, and 18, and Tract 41 are described in this survey.
- From the above corner point a diligent search was made for any evidence of Angle Point No. 3, lot 5 and Angle Point No. 6, lot 6, and Angle Point No. 4, lot 5 and Angle Point No. 5, lot 6 of sec. 31, and none was found.
- 12.71 Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. in diam., 23 ins. in the ground, for the witness point of section 30 and Tract 41, with brass cap mkd.
- W P
T7S R15W
S 30
TR 41
- 1970
- 19.73 The east 1/16 sec. cor. of secs. 30 and 31 is marked with an iron pipe, 30 ins. long, 1-inch in diam., set 17 ins. in the ground, with brass cap mkd.
- BUREAU OF RECLAMATION
E 1/16 $\frac{S 30}{S 31}$
- 1949
- The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953.
- At the corner point
- Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. in diam., 21 ins. in the ground, with brass cap mkd.
- T7S R15W
E 1/16 $\frac{S 30}{S 31}$
- 1970
- Deposit the iron pipe corner marker alongside the iron post.
-
- S. 89° 58' W., beginning new measurement.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS		
19.73	<p>The 1/4 sec. cor. of secs. 30 and 31 is marked with an iron pipe, 30 ins. long, 2½ ins. in diam., firmly set 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION 1/4 $\frac{S\ 30}{S\ 31}$ 1949</p>	
	<p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R15W 1/4 $\frac{S\ 30}{S\ 31}$ 1970</p>	
	<p>Deposit the iron pipe corner marker alongside the iron post.</p>	
	<p style="text-align: center;">_____</p>	
	<p>S. 89° 58' W., beginning new measurement</p>	
16.70	<p>The point for Angle Point No. 2, lot 7 and Angle Point No. 1, lot 8 of sec. 31 is determined at proportionate distance; there is no evidence of the original corner.</p>	
	<p style="text-align: center;">MEMORANDUM</p>	
	<p>The above lot corner was originally established by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. The area of lots 5, 6, 7, 8, 9, and 10, and the NW¼ of the NE¼ of sec. 31 have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots 15, 16, 17, and 18, and Tract 41 are described in this survey.</p>	
	<p>From the above corner point a diligent search was made for any evidence of Angle Point No. 3, lot 7 and Angle Point No. 5, lot 8, and Angle Point No. 4, lot 7 and Angle Point No. 4, lot 8 of sec. 31, and none was found.</p>	
19.73	<p>The point for the west 1/16 sec. cor. of secs. 30 and 31 is determined at proportionate distance; there is no evidence of the original corner.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">W 1/16 $\frac{S\ 30}{S\ 31}$ 1970</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

38.03 The cor. of secs. 25, 30, 31, and 36 on the west boundary of the township, which is designated to function for Angle Point No. 2, Tract 41, Tp. 7 S., R. 15 W., heretofore described.

Discontinue the dependent resurvey of the subdivisional lines of the township at this corner.

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

Thence, in section 25.

From the 1/4 sec. cor. of secs. 25 and 36, heretofore described.

N. 0° 08' E., on the north and south center line of sec. 25.

Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.

40.11 Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 25.

Set an iron post, 28 ins. long, 2½ ins. in diam., 21 ins. in the ground, with brass cap mkd.

T7S R15W
C 1/4
S 25

1969

53.90 Intersect line 4 - 5, Tract 37.

The point for the closing corner of sec. 25.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T7S R15W
TR 37
C
L 6 | L 7
S | 25
CC
C

1969

From this closing corner, Angle Point No. 5, Tract 37, hereinafter described, bears S. 89° 27' E., 20.08 chs. distant.

Thence, on a blank line across Tract 37.

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
69.05	Intersect line 2 - 3, Tract 37.	
	The point for the closing corner of sec. 25.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	T7S R15W C CC S 25 L 3 L 2 C TR 37 1969	
	From this closing corner, Angle Point No. 2, Tract 37, hereinafter described, bears S. 89° 27' E., 20.19 chs. distant.	
80.23	The 1/4 sec. cor. of secs. 24 and 25, heretofore described.	
	From the 1/4 sec. cor. of secs. 25 and 30 on the east boundary of the township, heretofore described.	
	S. 89° 49' W., on the east and west center line of sec. 25.	
	Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.	
19.99	The point for the center-east 1/16 sec. cor. of sec. 25. I did not monument this corner point.	
39.98	Intersect the north and south center line, the center 1/4 sec. cor. of sec. 25, heretofore described.	
59.97	The point for the center-west 1/16 sec. cor. of sec. 25. I did not monument this corner point.	
79.96	The 1/4 sec. cor. of secs. 25 and 26, heretofore described.	
	From the point for the center-east 1/16 sec. cor. of sec. 25, heretofore described.	
	N. 0° 07' E., on the north and south center line of the northeast 1/4 of sec. 25.	
	Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.	
13.54	Intersect line 4 - 5, Tract 37.	

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The point for the closing corner of sec. 25. I did not monument this corner point. From this point for the closing corner, Angle Point No. 5, Tract 37, hereinafter described, bears S. 89° 27' E., 0.09 chs. distant.</p> <p>Thence, on a blank line across Tract 37.</p>
28.69	<p>Intersect line 2 - 3, Tract 37.</p> <p>The point for the closing corner of sec. 25. I did not monument this corner point. From this point for the closing corner, Angle Point No. 2, Tract 37, hereinafter described, bears S. 89° 27' E., 0.21 chs. distant.</p>
40.13	<p>The point for the east 1/16 sec. cor. of secs. 24 and 25, heretofore described.</p> <hr/> <p>From the point for the center-west 1/16 sec. cor. of sec. 25, heretofore described.</p> <p>N. 0° 10' E., on the north and south center line of the northwest 1/4 of sec. 25.</p> <p>Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.</p>
14.05	<p>Intersect line 4 - 5, Tract 37.</p> <p>The point for the closing corner of sec. 25. I did not monument this corner point. From this point for the closing corner, Angle Point No. 4, Tract 37, heretofore described, bears N. 89° 27' W., 19.98 chs. distant.</p> <p>Thence, on a blank line across Tract 37.</p>
29.21	<p>Intersect line 2 - 3, Tract 37.</p> <p>The point for the closing corner of sec. 25. I did not monument this corner point. From this point for the closing corner, Angle Point No. 3, Tract 37, heretofore described, bears N. 89° 27' W., 19.97 chs. distant.</p>
40.12	<p>The point for the west 1/16 sec. cor. of secs. 24 and 25, heretofore described.</p> <hr/> <p>Thence, in section 26</p> <p>From the 1/4 sec. cor. of secs. 26 and 35, heretofore described.</p> <p>N. 0° 06' E., on the north and south center line of sec. 26.</p> <p>Over nearly level land.</p>
27.15	<p>Concrete lateral, bears S. 74° E. and N. 74° W.</p>
40.07	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T7S R15W C 1/4 S 26</p> <p style="text-align: center;">1969</p>	
54.91	<p>The point for Cor. No. 3, Lot 1, sec. 26.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R15W L 1 C 3 _____ S 26</p> <p style="text-align: center;">1969</p>	
60.10	<p>The point for the center-north 1/16 sec. cor. of sec. 26.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">C N 1/16 S 26</p> <p style="text-align: center;">1969</p>	
	<p>This corner is designated to function for Cor. No. 2, Lot 1, sec. 26.</p>	
80.13	<p>The 1/4 sec. cor. of secs. 23 and 26, heretofore described.</p>	
	<hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, heretofore described.</p>	
	<p>S. 89° 47' W., on the east and west center line of sec. 26.</p>	
	<p>Over nearly level land, through areas of dense to scattering French tamarisk, mesquite, and paloverde trees.</p>	
20.03	<p>The point for the center-east 1/16 sec. cor. of sec. 26. I did not monument this corner point.</p>	
40.06	<p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 26, heretofore described.</p>	
80.12	<p>The 1/4 sec. cor. of secs. 26 and 27, heretofore described.</p>	
	<hr/> <p>From the point for the center-east 1/16 sec. cor. of sec. 26, heretofore described.</p>	
	<p>N. 0° 09' E., on the north and south center line of the northeast 1/4 of sec. 26.</p>	
	<p>Over nearly level land.</p>	

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS	
14.58	<p>Intersect line 3 - 4, Lot 1, sec. 26.</p> <p>The point for the closing corner of sec. 26. I did not monument this corner point. From this point for the closing corner, Cor. No. 4, Lot 1, sec. 26, which is identical with Angle Point No. 4, Tract 37, heretofore described, bears S. 89° 27' E., 20.02 chs. distant.</p>
20.05	<p>Intersect the east and west center line of the northeast 1/4, the point for the northeast 1/16 sec. cor. of sec. 26. I did not monument this corner point.</p>
40.10	<p>The point for the east 1/16 sec. cor. of secs. 23 and 26, heretofore described.</p> <hr/> <p>From the north 1/16 sec. cor. of secs. 25 and 26, which is designated to function for Cor. No. 1, Lot 1, sec. 26, heretofore described.</p> <p>S. 89° 45' W., on the east and west center line of the northeast 1/4, and on line 1 - 2, Lot 1, sec. 26.</p>
20.02	<p>Intersect the north and south center line of the northeast 1/4, the point for the northeast 1/16 sec. cor. of sec. 26, heretofore described.</p>
40.04	<p>Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 26, which is designated to function for Cor. No. 2, Lot 1, sec. 26, heretofore described.</p> <hr/> <p>From Cor. No. 3, Lot 1, sec. 26, heretofore described.</p> <p>S. 89° 27' E., on line 3 - 4, Lot 1, sec. 26.</p>
20.02	<p>Intersect the north and south center line of the northeast 1/4, the point for the closing corner of sec. 26, heretofore described.</p>
40.04	<p>Cor. No. 4, Lot 1, sec. 26, this corner is identical with Angle Point No. 4, Tract 37, heretofore described.</p> <hr/> <p>Thence, in section 27</p> <p>From the 1/4 sec. cor. of secs. 27 and 34, heretofore described.</p> <p>N. 0° 02' W., on the north and south center line of sec. 27.</p>
20.06	<p>The point for the center-south 1/16 sec. cor. of sec. 27. I did not monument this corner point.</p>
40.12	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T7S R15W C 1/4 S 27 1969</p>	
80.24	<p>The 1/4 sec. cor. of secs. 22 and 27, heretofore described.</p>	
40.06	<p>From the 1/4 sec. cor. of secs. 26 and 27, heretofore described.</p>	
60.09	<p>WEST, on the east and west center line of sec. 27.</p>	
40.06	<p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 27, heretofore described.</p>	
60.09	<p>The point for the center-west 1/16 sec. cor. of sec. 27. I did not monument this corner point.</p>	
64.14	<p>The point for Angle Point No. 1, Tract 38.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R15W S 27 <hr style="width: 50px; margin: auto;"/> AP 1 TR 38</p>	
	<p style="text-align: center;">1970</p>	
80.12	<p>The 1/4 sec. cor. of secs. 27 and 28, which is designated to function for Angle Point No. 2, Tract 38, and Angle Point No. 11, Tract 39, heretofore described.</p>	
20.09	<p>From the west 1/16 sec. cor. of secs. 27 and 34, heretofore described.</p>	
	<p>N. 0° 03' W., on the north and south center line of the southwest 1/4 of sec. 27.</p>	
20.09	<p>Intersect the east and west center line of the southwest 1/4, the point for the southwest 1/16 sec. cor. of sec. 27. I did not monument this corner point.</p>	
40.18	<p>Intersect the east and west center line, the point for the center-west 1/16 sec. cor. of sec. 27, heretofore described.</p>	
20.02	<p>From the point for the center-south 1/16 sec. cor. of sec. 27, heretofore described.</p>	
	<p>S. 89° 56' W., on the east and west center line of southwest 1/4 of sec. 27.</p>	
20.02	<p>Intersect the north and south center line of the southeast 1/4, the point for the southwest 1/16 sec. cor. of sec. 27, heretofore described.</p>	

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
40.04	<p>The south 1/16 sec. cor. of secs. 27 and 28, heretofore described.</p>	
6.37	<p>Thence, in section 28.</p> <p>From the 1/4 sec. cor. of secs. 28 and 33, heretofore described.</p> <p>N. 0° 03' W., on the north and south center line of sec. 28.</p> <p>Intersect the arc of a curve, hereinafter described.</p> <p>The point for Angle Point No. 7, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div data-bbox="857 1016 1024 1276" style="text-align: center;"> <p>T7S R15W</p> <p>TR 39 </p> <p>AP 7 </p> <p>—/— </p> <p>L 6 </p> <p>S 28</p> <p>1970</p> </div>	
20.06	<p>The point for the center-south 1/16 sec. cor. of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div data-bbox="906 1473 980 1634" style="text-align: center;"> <p>C S</p> <p>1/16</p> <p>S 28</p> <p>1970</p> </div> <p>This corner is designated to function for Angle Point No. 8, Tract 39.</p> <p>Thence, on a blank line across Tract 39.</p>	
21.59	<p>Intersect line 2 - 3, Tract 39, on the arc of a curve, hereinafter described.</p> <p>The point for the closing corner of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div data-bbox="889 2083 1036 2378" style="text-align: center;"> <p>T7S R15W</p> <p>S 28</p> <p>C C</p> <p>L 3 L 2</p> <p>—/— </p> <p>TR 39</p> <p>1970</p> </div>	
40.12	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 28.</p>	

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R15W C 1/4 S 28</p> <p style="text-align: center;">1970</p>	
80.28	<p>The 1/4 sec. cor. of secs. 21 and 28, heretofore described.</p>	
	<p>From the 1/4 sec. cor. of secs. 27 and 28, which is designated to function for Angle Point No. 2, Tract 38, and Angle Point No. 11, Tract 39, heretofore described.</p>	
	<p>WEST, on the east and west center line of sec. 28.</p>	
5.00	<p>The point for Angle Point No. 1, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R15W S 28 L 1 / AP 1 TR 39</p> <p style="text-align: center;">1970</p>	
20.10	<p>The point for the center-east 1/16 sec. cor. of sec. 28. I did not monument this corner point.</p>	
40.20	<p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 28, heretofore described.</p>	
60.28	<p>The point for the center-west 1/16 sec. cor. of sec. 28. I did not monument this corner point.</p>	
80.36	<p>The 1/4 sec. cor. of secs. 28 and 29, heretofore described.</p>	
	<p>From the point for the west 1/16 sec. cor. of secs. 28 and 33, heretofore described.</p> <p>N. 0° 03' W., on the north and south center line of the southwest 1/4 of sec. 28.</p>	
4.85	<p>Intersect line 5 - 6, Tract 39.</p> <p>The point for the closing corner of sec. 28. I did not monument this corner point. From this point for the closing corner, Angle Point No. 5, Tract 39, and Angle Point No. 8,, Tract 40, heretofore described, bears S. 85° 52' W., 20.12 chs. distant.</p> <p>Thence, on a blank line across Tract 39.</p>	

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS	
20.03	<p>Intersect line 3 - 4, Tract 39.</p> <p>The point for the closing corner of sec. 28. I did not monument this corner point. From this point for the closing corner, Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40, heretofore described, bears S. 85° 52' W., 20.12 chs. distant.</p>
40.06	<p>Intersect the east and west center line, the point for the center-west 1/16 sec. cor. of sec. 28, heretofore described.</p> <hr/> <p>From the point for the center-east 1/16 sec. cor. of sec. 28, heretofore described.</p> <p>S. 0° 04' E., (this bearing is determined of the mean bearing between the east boundary of the section and the north and south center line of the section), on the north and south center line of the southeast 1/4 of sec. 28.</p>
12.25	<p>Intersect line 2 - 3, Tract 39, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 28. I did not monument this corner point.</p> <p>Discontinue the survey of this subdivision line at this corner point.</p> <hr/> <p>From the south 1/16 sec. cor. of secs. 27 and 28, heretofore described.</p> <p>N. 89° 54' W., on the east and west center line of the southeast 1/4 of sec. 28.</p>
4.48	<p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 9, Tract 39.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T7S R15W TR 39 AP 9 L 5 S 28</p> </div> <p style="text-align: center; margin-top: 10px;">1970</p>
40.20	<p>Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 28, which is designated to function for Angle Point No. 8, Tract 39, heretofore described.</p> <hr/>

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS


Thence, in section 29

From the 1/4 sec. cor. of secs. 29 and 32, which is designated to function for Angle Point No. 5, Tract 40, heretofore described.

N. 0° 23' E., on the north and south center line of sec. 29.

12.22 The point for Angle Point No. 4, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1970

19.99 The point for the center-south 1/16 sec. cor. of sec. 29. I did not monument this corner point.

39.98 The center 1/4 sec. cor. of sec. 29, which is marked with a steel rod, 5/8-inch in diam., firmly set, projecting 5 ins. above the surface of the ground. This corner marker is accepted as the position of the corner. This corner was not remonumented.

N. 0° 23' E., beginning new measurement.


40.04 The point for the 1/4 sec. cor. of secs. 20 and 29 is determined from ties established by the Bureau of Reclamation, as:

A cross (+) chiseled on a concrete lateral, bears N. 0° 23' E., 36.0 ft. distant, mkd. + RP 36.00'.

A cross (+) chiseled on a concrete lateral, bears S. 0° 23' W., 28.0 ft. distant, mkd. + RP 28.00'.

The above corner point is accepted as the best available evidence of the position of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.



1970

This corner is located within an east and west road.

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 28 and 29, heretofore described.</p> <p>S. 89° 44' W., on the east and west center line of sec. 29.</p>
20.25	The point for the center-east 1/16 sec. cor. of sec. 29. I did not monument this corner point.
40.50	Intersect the center 1/4 sec. cor. of sec. 29, heretofore described.
	<hr/> <p>From the point for the east 1/16 sec. cor. of secs. 29 and 32, heretofore described.</p> <p>N. 0° 10' E., on the north and south center line of the southeast 1/4 of sec. 29.</p>
1.27	Intersect line 6 - 7, Tract 40, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 29. I did not monument this point for the closing corner.
	Thence, on a blank line across Tract 40.
16.64	Intersect line 2 - 3, Tract 40, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 29. I did not monument this point for the closing corner.
20.00	Intersect the east and west center line of the southeast 1/4, the point for the southeast 1/16 sec. cor. of sec. 29. I did not monument this corner point.
40.00	Intersect the east and west center line, the point for the center-west 1/16 sec. cor. of sec. 29, heretofore described.
	<hr/> <p>From the point for the south 1/16 sec. cor. of secs. 28 and 29, heretofore described.</p> <p>S. 89° 43' W., on the east and west center line of the southeast 1/4 of sec. 29.</p>
20.33	Intersect the north and south center line of the southeast 1/4, the point for the southeast 1/16 sec. cor. of sec. 29, heretofore described.
40.66	Intersect the north and south center line, the point for the center-south 1/16 sec. cor. of sec. 29, heretofore described.

Dependent Resurvey of a Portion of the
 Subdivision Lines within Section 31
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Survey Executed by
 Albin H. Wadin, Engineer
 Bureau of Reclamation, in 1953

The center-north 1/16 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 10 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

C N
 1/16
 S 31

1953

N. 0° 44' W., on the north and south center line of sec. 31.

4.73 Intersect line 3 - 4, Tract 41.

The point for the closing corner of sec. 31.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T7S R15W	
TR 41	
L 17	L 16
CC	
S 31	

1970

From this closing corner, Angle Point No. 3, Tract 41, heretofore described, bears N. 89° 43' W., 38.20 chs. distant.

Thence, on a blank line across Tract 41.

20.08 The 1/4 sec. cor. of secs. 30 and 31, heretofore described.

The northeast 1/16 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap mkd.

NE 1/16
 S 31

1953

MEMORANDUM

The above corner was originally established by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1953. The area of lots 5, 6, 7, 8, 9, and 10, and the NW¼ of the NE¼ of sec. 31 have remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of lots 15, 16, 17, and 18, and Tract 41 are described in this survey.

Dependent Resurvey of a Portion of the
Subdivision Lines within Section 31
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From the above corner point a diligent search was made for any evidence of Angle Point No. 5, lot 5 and Angle Point No. 4, lot 6 of sec. 31, and none was found.</p>	
	<p>N. 1° 03' W., on the north and south center line of the northeast 1/4 of sec. 31.</p>	
4.69	<p>Intersect line 4 - 5, Tract 41, on the arc of a curve, hereinafter described. The point for the closing corner of sec. 31. I did not monument this point for the closing corner.</p> <p>Thence, on a blank line across Tract 41.</p>	
20.07	<p>The east 1/16 sec. cor. of secs. 30 and 31, heretofore described.</p>	
	<p>The northwest 1/16 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 6 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 31 1953</p>	
	<p>N. 0° 25' W., on the north and south center line of the northwest 1/4 of sec. 31</p>	
4.84	<p>Intersect line 3 - 4, Tract 41.</p> <p>The point for the closing corner of sec. 31. I did not monument this corner point. From this point for the closing corner, Angle Point No. 3, Tract 41, heretofore described, bears N. 89° 43' W., 18.39 chs. distant.</p> <p>Thence, on a blank line across Tract 41.</p>	
20.08	<p>The west 1/16 sec. cor. of secs. 30 and 31, heretofore described.</p>	
	<p>Thence, in section 34.</p> <p>From the true point for the 1/4 sec. cor. of secs. 3 and 34 on the south boundary of the township, heretofore described.</p> <p>N. 0° 30' W., on the north and south center line of the sec. 34.</p>	
20.03	<p>The point for the center-south 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the
 Subdivision Lines within Section 31
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">C S 1/16 S 34</p> <p style="text-align: center;">1970</p>	
40.06	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 11 ins. in the ground, and in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R15W C 1/4 S 34</p> <p style="text-align: center;">1970</p>	
60.09	<p>The point for the center-north 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 5 ins. in the ground, and in a mound of stone, 3½ ft. base, to the top, with brass cap mkd.</p>	
	<p style="text-align: center;">C N 1/16 S 34</p> <p style="text-align: center;">1970</p>	
80.12	<p>The 1/4 sec. cor. of secs. 27 and 34, heretofore described.</p>	
	<p>From the true point for the 1/4 sec. cor. of secs. 34 and 35, heretofore described.</p> <p>S. 89° 52' W., on the east and west center line of sec. 34.</p>	
19.99	<p>The point for the center-east 1/16 sec. cor. of sec. 34. This true corner point is located on a steep broken west slope; an unsafe location for a monument.</p>	
26.59	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, for the witness center-east 1/16 sec. cor. of sec. 34, with brass cap mkd.</p>	
	<p style="text-align: center;">W C C E 1/16 S 34</p> <p style="text-align: center;">→</p> <p style="text-align: center;">1970</p>	
39.98	<p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 34, heretofore described.</p>	


Dependent Resurvey of a Portion of the
Subdivision Lines within Section 31
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS	
60.16	<p>The point for the center-west 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to the top, with brass cap mkd.</p> <p style="text-align: center;">C W 1/16 S 34 1970</p>
80.34	<p>The 1/4 sec. cor. of secs. 33 and 34, heretofore described.</p>
<hr/> <p>Survey of Tracts 37, 38, 39, 40, and 41 Township 7 South, Range 15 West Gila and Salt River Meridian, Arizona</p> <hr/>	
<p>Thence, with the survey of Tract 37.</p> <p>Beginning at Angle Point No. 1, Tract 37, on the east boundary of Tp. 7 S., R. 15 E., heretofore described.</p> <p>Thence, on line 1 - 2, Tract 37, along the arc of a curve, curve data:</p> <p>Radius 68.29 chs. distant. Length of arc 20.04 chs. distant. Length of chord 19.97 chs. distant, and bears S. 82° 08' W.</p> <p>At the end of arc of the curve, the point for Angle Point No. 2, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
<p>T7S R15W S 25 — AP 2 TR 37 1969</p>	
0.21	<p>N. 89° 27' W., on line 2 - 3, Tract 37</p> <p>Intersect the north and south center line of the northeast 1/4, the point for the closing corner of sec. 25, heretofore described.</p>

Survey of Tracts 37, 38, 39, 40, and 41
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
20.19	Intersect the north and south center line, the closing corner of sec. 25, heretofore described.	
40.16	Intersect the north and south center line of the northwest 1/4, the point for the closing corner of sec. 25, heretofore described.	
60.13	Angle Point No. 3, Tract 37, heretofore described.	

	S. 0° 11' W., on line 3 - 4 (west boundary), Tract 37, and along the east boundary of sec. 26.	
9.41	The north 1/16 sec. cor. of secs. 25 and 26, which is designated to function for Cor. No. 1, Lot 1, sec. 26, heretofore described.	
	Continue with the above course and measurement (the west boundary) of Tract 37, identical with line 1 - 4, Lot 1, sec. 26.	
15.16	Angle Point No. 4, Tract 37, which is identical with Cor. No. 4, Lot 1, sec. 26, heretofore described.	

	S. 89° 27' E., on line 4 - 5 (south boundary), Tract 37.	
19.98	Intersect the north and south center line of the northwest 1/4, the point for the closing corner. of sec. 25, heretofore described.	
39.96	Intersect the north and south center line, the closing corner of sec. 25, heretofore described.	
59.95	Intersect the north and south center line of the northeast 1/4, the point for the closing corner of sec. 25, heretofore described.	
60.04	The point for Angle Point No. 5, Tract 37.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p>T7S R15W TR 37 AP 5</p>  <p>L 8 S 25</p> <p>1969</p>	

	Thence, on line 5 - 6, Tract 37, along the arc of a curve, curve data:	

Survey of Tracts 37, 38, 39, 40, and 41
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

	CHAINS	
		<p>Radius 38.46 chs. distant. Length of arc 20.96 chs. distant. Length of chord 20.70 chs. distant, and bears S. 73° 50 E.</p> <p>At the end of arc of the curve, Angle Point No. 6, Tract 37 (on the east boundary of the township), heretofore described.</p> <hr/> <p>N. 0° 06' E., on line 6 - 1 (the east boundary), Tract 37, and along the east boundary of the township.</p>
	23.64	<p>Angle Point No. 1, Tract 37, and the place of beginning.</p> <hr/> <p>Thence, with the survey of Tract 38.</p> <p>Beginning at Angle Point No. 1, Tract 38, on the east and west center line of sec. 27, heretofore described.</p> <p>WEST, on line 1 - 2 (north boundary), Tract 38, and on the east and west center line of sec. 27.</p>
	15.98	<p>The 1/4 sec. cor. of secs. 27 and 28, which is designated to function for Angle Point No. 2, Tract 38, and Angle Point No. 11, Tract 39, heretofore described.</p> <hr/> <p>S. 0° 05' E., on line 2 - 3 (west boundary), Tract 38, identical with line 11 - 10 (east boundary), Tract 39.</p>
	16.40	<p>Angle Point No. 3, Tract 38, which is identical with Angle Point No. 10, Tract 39, heretofore described.</p> <hr/> <p>Thence, on line 3 - 4 (southeastern boundary), Tract 38, along the arc of a curve, curve data:</p> <p>Radius 68.44 chs. distant. Length of arc 5.07 chs. distant. Length of chord 5.06 chs. distant, and bears N. 45° 51' E.</p> <p>At the end of arc of the curve, the point for Angle Point No. 4, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of Tracts 37, 38, 39, 40, and 41
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

T7S R15W
TR 38
AP 4
L 1
S 27

1970

N. 43° 44' E., on line 4 - 1, Tract 38.

17.82 Angle Point No. 1, Tract 38, and the place of beginning.

Thence, with the survey of Tract 39.

Beginning at Angle Point No. 1, Tract 39 on the east and west center line of sec. 28, heretofore described.

S. 43° 44' W., on line 1 - 2, Tract 39.

3.33 The point for Angle Point No. 2, Tract 39.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
S 28
L 1
AP 2
TR 39

1970

Thence, on line 2 - 3, Tract 39, along the arc of a curve, curve data:

Radius 53.29 chs. distant.

Length of arc 39.18 chs. distant.

Length of chord 38.37 chs. distant, and bears S. 64° 46' W.

At 16.20 chs. distant on the arc of the curve. Intersect the north and south center line of the southeast quarter of sec. 28, the point for the closing corner of sec. 28, heretofore described.

At 37.52 chs. distant on the arc of the curve. Intersect the north and south center line, the closing corner of sec. 28, heretofore described.

At the end of arc of the curve, the point for Angle Point No. 3, Tract 39.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of Tracts 37, 38, 39, 40, and 41
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS

T7S R15W
 S 28
 L 3
 AP 3
 TR 39

1970

- S. 85° 52' W., on line 3 - 4, Tract 39.
- 18.47 Intersect the north and south center line of the southwest 1/4 of sec. 28, the point for the closing corner of sec. 28, heretofore described.
- 38.59 Angle Point No. 4, Tract 39, which is identical with Angle Point No. 1, Tract 40, heretofore described.
- S. 0° 03' E., on line 4 - 5 (west boundary), Tract 39, identical with line 1 - 8 (east boundary), Tract 40.
- 15.19 Angle Point No. 5, Tract 39, which is identical with Angle Point No. 8, Tract 40, heretofore described.
- N. 85° 52' W., on line 5 - 6 (southern boundary) Tract 39.
- 20.12 Intersect the north and south center line of the southwest 1/4 of sec. 28, the point for the closing corner of sec. 28, heretofore described.
- 39.67 The point for Angle Point No. 6, Tract 39.
- Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
 TR 39
 AP 6
 L 6
 S 28

1970

Thence, on line 6 - 7, Tract 39, along the arc of a curve, curve data:

Radius 68.44 chs. distant.
 Length of arc 0.58 chs. distant.
 Length of chord 0.58 chs. distant, and bears N. 85° 25' E.

Survey of Tracts 37, 38, 39, 40, and 41
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>At the end of arc of the curve, Angle Point No. 7, Tract 39, heretofore described.</p> <hr/>	
13.69	<p>N. 0° 03' W., on line 7 - 8, Tract 39, and on the north and south center line of sec. 28.</p>	
13.69	<p>The center-south 1/16 sec. cor. of sec. 28, which is designated to function for Angle Point No. 8, Tract 39, heretofore described.</p> <hr/>	
35.72	<p>S. 89° 54' E., on line 8 - 9, Tract 39, and on the east and west center line of the southeast 1/4 of sec. 28.</p>	
35.72	<p>Angle Point No. 9, Tract 39, heretofore described.</p> <hr/>	
	<p>Thence, on line 9 - 10, Tract 39, along the arc of a curve, curve data:</p>	
	<p>Radius 68.44 chs. distant. Length of arc 5.82 chs. distant. Length of chord 5.81 chs. distant, and bears N. 50° 23' E.</p>	
	<p>At the end of the curve, Angle Point No. 10, Tract 39, which is identical with Angle Point No. 3, Tract 38, heretofore described.</p> <hr/>	
16.40	<p>N. 0° 05' W., on line 10-11 (the east boundary), Tract 39, identical with line 3 - 2 (west boundary,) Tract 38.</p>	
16.40	<p>The 1/4 sec. cor. of secs. 27 and 28, which is designated to function for Angle Point No. 11, Tract 39, and Angle Point No. 2, Tract 38, heretofore described.</p> <hr/>	
5.00	<p>WEST, on line 11 - 1, Tract 39, and on the east and west center line of sec. 28.</p>	
5.00	<p>Angle Point No. 1, Tract 39, and place of beginning.</p> <hr/>	
	<p>Thence, with the survey of Tract 40.</p>	
	<p>Beginning at Angle Point No. 1, Tract 40, which is identical with Angle Point No. 4, Tract 39, heretofore described.</p>	

Survey of Tracts 37, 38, 39, 40, and 41
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS

S. 85° 52' W., on line 1 - 2 (northern boundary), Tract 40.

7.49 The point for Angle Point No. 2, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
S 29
L 1
AP 2
TR 40
1970

Thence, on line 2 - 3, Tract 40, along the arc of a curve, curve data:

Radius 159.97 chs. distant.

Length of arc 33.28 chs. distant.

Length of chord 33.22 chs. distant, and bears S. 79° 54' W.

At 12.96 chs. distant on the arc of the curve. Intersect the north and south center line of the southeast quarter of sec. 29, the point for the closing corner of sec. 29, heretofore described.

At the end of arc of the curve, the point for Angle Point No. 3, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T7S R15W
S 29
L 2
AP 3
TR 40
1970

S. 73° 57' W., on line 3 - 4, Tract 40

0.57 Angle Point No. 4, Tract 40, heretofore described.

S. 0° 23' W., on line 4 - 5 (west boundary), Tract 40, and on the north and south center line of sec. 29.

Survey of Tracts 37, 38, 39, 40, and 41
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS	
12.22	<p>The 1/4 sec. cor. of secs. 29 and 32, which is designated to function for Angle Point No. 5, Tract 40, heretofore described.</p> <hr/>
13.70	<p>N. 89° 42' E., on line 5 - 6 (southern boundary), Tract 40, and along the north boundary of section 32.</p> <p>Angle Point No. 6, Tract 40, heretofore described.</p> <hr/> <p>Thence, on line 6 - 7, Tract 40, along the arc of a curve, curve data:</p> <p>Radius 144.82 chs. distant. Length of arc 20.97 chs. distant. Length of chord 20.95 chs. distant, and bears N. 81° 43' E.</p> <p>At 6.84 chs. distant on the arc of the curve. Intersect the north and south center line of the southeast quarter of sec. 29, the point for the closing corner of sec. 29, heretofore described.</p> <p>At the end of arc of the curve, the point for Angle Point No. 7, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R15W TR 40 AP 7 L 3 S 29</p> <p>1970</p> </div> <hr/>
6.41	<p>N. 85° 52' E., on line 7 - 8, Tract 40.</p> <p>Angle Point No. 8, Tract 40, which is identical with Angle Point No. 5, Tract 39, heretofore described.</p> <hr/>
15.19	<p>N. 0° 03' W., on line 8 - 1 (east boundary), Tract 40, identical with line 5 - 4 (west boundary), Tract 39.</p> <p>Angle Point No. 1, Tract 40, which is identical with Angle Point No. 4, Tract 39, heretofore described, and the place of beginning.</p> <hr/>

Survey of Tracts 37, 38, 39, 40, and 41
Township 7 South, Range 15 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Thence, with the survey of Tract 41</p> <p>Beginning at the corner of secs. 29, 30, 31, and 32, which is designated to function for Angle Point No. 1, Tract 41, heretofore described.</p> <p>S. 89° 58' W., on line 1 - 2 (north boundry), Tract 41, and along the south boundary of sec. 30.</p>
12.71	The witness point of section 30 and Tract 41, heretofore described.
19.73	The east 1/16 sec. cor. of secs. 30 an 31, heretofore described.

	S. 89° 58' W., beginning new measurement.
19.73	The 1/4 sec. cor. of secs. 30 and 31, heretofore described.

	S. 89° 58' W., beginning new measurment.
19.73	The west 1/16 sec. cor. of secs. 30 and 31, heretofore described.
38.03	The cor. of secs. 25, 30, 31, and 36 on the west boundary of the township, which is designated to function for Angle Point No. 2, Tract 41, Tp. 7 S., R. 15 W., heretofore described.

	S. 0° 04' E., on line 2 - 3 (west boundary), Tract 41, and along the west boundary of the township.
15.15	Angle Point No. 3, Tract 41, heretofore described.

	S. 89° 43' E., on line 3 - 4 (south boundary), Tract 41.
18.39	Intersect the north and south center line of the north-west 1/4, the point for the closing corner of sec. 31, heretofore described.
38.20	Intersect the north and south center line, the closing corner of sec. 31, heretofore described.
53.00	The point for Angle Point No. 4, Tract 41
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

Survey of Tracts 37, 38, 39, 40, and 41
 Township 7 South, Range 15 West
 Gila and Salt River Meridian, Arizona

CHAINS

T7S R15W
 TR 41
 AP 4

 L 16
 S 31

 1970

Thence, on line 4 - 5, Tract 41, along the arc of a curve, curve data:

Radius 159.09 chs. distant.
 Length of arc 24.88 chs. distant.
 Length of chord 24.86 chs. distant, and bears N. 85° 48' E.

At 5.02 chs. distant on the arc of the curve. Intersect the north and south center line of the northeast quarter, the point for the closing corner of sec. 31, heretofore described.

At the end of arc of the curve, Angle Point No. 5, Tract 41, heretofore described.

N. 1° 22' W., on line 5 - 1 (east boundary), Tract 41, and along the west boundary of sec. 32.

13.64

The cor. of secs. 29, 30, 31, and 32, which is designated to function for Angle Point No. 1, Tract 41, heretofore described, and the place of beginning.

GENERAL DESCRIPTION

The land embraced by this survey is primarily sandy desert land, from nearly level to rolling, with the exception of section 34 which is rough and broken. Timber consists of mesquite, paloverde, tesota and French tamarisk trees; undergrowth, young trees, creosote (shrub) brush, and cacti.

The major water shed course is the dry bed of the Gila River which meanders through the area in a westerly direction. No water was noted in the river during this survey.

Irrigated farms are being developed in and near the area of this survey with many canals and laterals which are constructed of concrete. Improved roads have been constructed along certain section lines.

Game birds, coyotes, and rodents abound throughout the vicinity.

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Marvin T. Koppang	Cadastral Surveyor
Douglas A. Cody	Surveying Technician
Stephen Jaramillo	Surveying Aid
Manuel G. Jaramillo	Surveying Aid
Ernest F. Hurtado	Surveying Aid
Dale E. Phillips	Surveying Aid
Fordner VanFleet, Jr.	Surveying Aid
Kermit L. Duke	Surveying Aid
Norman Q. Hull	Surveying Aid

CERTIFICATE OF SURVEY

(X)(We), James P. Scott and Ray Harpin, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of October, 1969, (X)(We) have dependently resurveyed a portion of the south, east, and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision lines (within section 31); the survey of a portion of the subdivision lines within a number of sections, and the survey of Tracts 37, 38, 39, 40, and 41, Township 7 South, Range 15 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (X)(X) (us) and under (X)(X) (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 1, 1971 (Date) James P. Scott (Cadastral Surveyor)
May 23, 1977 (Date) Ray Harpin (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Washington, D.C.
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south, east, and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision lines (within section 31); the survey of a portion of the subdivision lines within a number of sections, and the survey of Tracts 37, 38, 39, 40, and 41, Township 7 South, Range 15 West, of the Gila and Salt River Meridian, Arizona

executed by James P. Scott and Ray Harpin, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

JAN 28 1980 0861 82 NVC (Date) J. Voster (Chief, Division of Cadastral Survey) Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date) (Chief, Division of Cadastral Survey) GPO 849-626