

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE
 DEPENDENT RESURVEY OF A PORTION OF THE
 EAST AND NORTH BOUNDARIES
 AND
 A PORTION OF THE SUBDIVISIONAL LINES
 THE SURVEY OF A PORTION OF THE SUBDIVISION LINES
 WITHIN SECTIONS 1 AND 11
 AND
 THE SURVEY OF TRACT NO. 37,
 TOWNSHIP 11 SOUTH, RANGE 25 WEST

Of the GILA AND SALT RIVER Meridian,
 In the State of ARIZONA

EXECUTED BY

RAY HARPIN CADASTRAL SURVEYOR

Under special instructions dated JANUARY 7, 1972, approved JANUARY 20, 1972,

_____, which provided for the surveys included under ~~U.S. Survey~~/Group
 Number 543, and assignment instructions dated JANUARY 7, 1972.

Survey commenced MARCH 2, 1972

Survey completed MAY 9, 1973

1A

BOOK 5107

INDEX DIAGRAM

Township 11 SOUTH, Range 25 WEST

6	5	4	3	2 8 9	1 1 4
7	8	9	10	11 6	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Survey of the subdivision lines within section 1 . . . p. 9.

Survey of the subdivision lines within section 11 . . . p. 23.

Survey of Tract No. 37 . . . p. 31.

1B

Township 11 South Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the east and north boundaries and a portion of the subdivisional lines; the survey of a portion of the subdivision lines within sections 1 and 11; and the survey of Tract No. 37, Township 11 South, Range 25 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The north boundary of the township was originally surveyed by Theodore F. White, U. S. Deputy Surveyor, in 1874. The east boundary and the subdivisional lines were surveyed by William H. Elliott, U. S. Deputy Surveyor, in 1905, as shown upon the official plat examined and approved May 12, 1909. A portion of the north boundary, and a portion of the subdivisional lines were dependently resurveyed; a portion of the south boundary was retraced by Robert C. Yundt, Cadastral Surveyor, in 1959 as shown upon the official plat accepted December 23, 1960. A portion of the subdivisional lines were dependently resurveyed by James W. Gilbery, (Engineer) Bureau of Reclamation, in 1963 and 1964, as described in the official field-note record and shown upon the plat of San Luis Townsite, Addition No. 1 and Lot No. 9, within section 12, accepted January 5, 1965.

The dependent resurvey and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 Edition, and the Special Instructions dated January 7, 1972.

The direction of all lines of these surveys were determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains.

The geographic position of the southeast corner of fractional section 11, determined by scaling from a U. S. Geological Survey Quadrangle Map, 7½ minute series Gadsden Arizona, 1965, is as follows: Latitude 32° 29.2' N. and Longitude 114° 47.1' W. The mean magnetic declination is 14° East.

Dependent Resurvey of a Portion of the East Boundary
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
William H. Elliott, U. S. Deputy Surveyor, in 1905

The corner of secs. 1, 6, 7, and 12, Tps. 11 S., Rs. 24 and 25 W. is marked with an iron pipe, 2 ins. in diam., with brass cap 7 ins. below the surface of the roadway, mkd.

Dependent Resurvey of a Portion of the East Boundary
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	BUREAU OF RECLAMATION T11S R25S R24W $\frac{S\ 1\ S\ 6}{S\ 12\ S\ 7}$ 191 The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented. <hr style="width: 20%; margin: auto;"/> N. 0° 29.5' W., through Tps. 11 S., between Rs. 24 and 25 W., and between secs. 1 and 6 Over nearly level land.
19.855	The point for the south 1/16 sec. cor. of secs. 1 and 6 Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> S 1/16 S 1 S 6 1972 </div>
20.20	Bench, bears east and west, descend over rolling north slope.
22.95	The left bank of the East Main Canal, course S. 83° 15' W.
23.60	The right bank of the East Main Canal; Thence, over nearly level land.
39.71	The 1/4 sec. cor. of secs. 1 and 6 is marked with an iron pipe, of undetermined length, 1-inch in diam., with the top 33 ins. below the surface of the ground, and an iron pipe, 25 ins. long, 1-inch in diam., set above the corner marker. The above corner marker is accepted as the best available evidence of the position of the original corner. At the corner point Set an iron post, 28 ins. long, 2½ ins. in diam., over the above corner marker, with brass cap 5 ins. below the surface of the ground, mkd. <div style="text-align: center;"> T11S R25W R24W 1/4 S 1 S 6 1972 </div> Deposit the iron pipe alongside the iron post.

Dependent Resurvey of a Portion of the East Boundary
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

There are no suitable accessories nor locations available for reference monuments.

N. 0° 26.5' W., beginning new measurement

20.145 The point for the north 1/16 sec. cor. of secs. 1 and 6

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

N 1/16

S 1|S 6

1972

40.29 The corner of Tps. 10 and 11 S., Rs. 24 and 25 W., which is marked with an iron pipe, 3 ins. in diam., with brass cap 24 ins. below the surface of the road, mkd.

S 36|S 31
 S 1|S 6

substantiated by

A cross (+) chiseled on a concrete headwall of a lateral, bears S. 16° 10' E., 31 ft. distant, mkd. 31' +

A cross (+) chiseled on a concrete headwall of a lateral, bears S. 38° 50' W., 37 ft. distant, mkd. 37' +

The above corner is set and witnessed as described in the official field-note record of the dependent resurvey of a portion of the south boundary of Tp. 10 S., R. 24 W., executed concurrently with this group.

Dependent Resurvey of a Portion of the North Boundary
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
 Theodore F. White, U S. Deputy Surveyor, in 1874

S. 89° 36' W., between Tps. 10 and 11 S., through R. 25 W. and between secs. 1 and 36

19.755 The point for the east 1/16 sec. cor. of secs. 1 and 36

Dependent Resurvey of a Portion of the North Boundary
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.

E 1/16 $\frac{S\ 36}{S\ 1}$

1972

There are no suitable accessories nor locations available for reference monuments.

39.51 The 1/4 sec. cor. of secs. 1 and 36 is marked with an iron pipe, 1-inch in diam., with brass cap 11 ins. below the surface of a roadway, mkd.

BUREAU OF RECLAMATION

1/4 $\frac{S\ 36}{S\ 1}$

1969

The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.

Discontinue the dependent resurvey of the township line at this corner.

Dependent Resurvey of a Portion of the
 Subdivisional Lines
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
 William H. Elliott, U. S. Deputy Surveyor, in 1905

From the corner of secs. 1, 6, 7, and 12 on the east boundary of the township, heretofore described.

S. 89° 34.5' W., between secs. 1 and 12

Over nearly level land, along an east and west roadway.

19.895 The point for the east 1/16 sec. cor. of secs. 1 and 12

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the roadway, mkd.

E 1/16 $\frac{S\ 1}{S\ 12}$

1972

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>There are no suitable accessories nor location available for reference monuments.</p>
39.79	<p>The 1/4 sec. cor. of secs. 1 and 12 is marked with an iron pipe, 1-inch in diam., with brass cap 7 ins. below the surface of the roadway, mkd.</p>
	$1/4 \frac{S 1}{S 12}$
	<p>19</p>
	<p>The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p>
	<hr/> <p style="text-align: center;">Restoring the Survey Executed by James W. Gilbery (Engineer) Bureau of Reclamation in 1963 and 1964</p> <hr/>
	<p>S. 89° 46.5' W., beginning new measurement</p>
0.49	<p>Intersect an iron pipe, 1-inch in diam., with brass cap 8 ins. below the surface of the roadway, mkd.</p>
	<p style="text-align: center;">BUREAU OF RECLAMATION P O S L</p>
	<p style="text-align: center;">1963</p>
20.07	<p>The west 1/16 sec. cor. of secs. 1 and 12 is marked with an unmarked Bureau of Reclamation brass cap set 7 ins. below the surface of the roadway, and is accepted as the position for the corner. I marked the above brass cap, as:</p>
	$W 1/16 \frac{S 1}{S 12}$
	<p style="text-align: center;">1972</p>
	<p>S. 89° 46.5' W., beginning new measurement</p>
5.015	<p>The point for the E-W-W 1/256 sec. cor. of secs. 1 and 12</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 9 ins. below the surface of the roadway, mkd.</p>
	<p style="text-align: center;">S 1 E W W 1/256 S 12</p>
	<p style="text-align: center;">1972</p>
6.20	<p>Center line of U. S. Highway No. 95, bears N. 21° 40' W. and S. 21° 40' E.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
7.01	Intersect a brass tablet, 2 ins. in diam., seated on a concrete form, 6 ins. square, with the top flush with the surface of the ground, mkd. ARIZONA HIGHWAY DEPT. ELEV STA 128.87 33 + 86.6 1938.
10.03	The west-west 1/64 sec. cor. of secs. 1 and 12 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.
BUREAU OF RECLAMATION T11S R25W W W 1/64 1963	
The above corner marker was reestablished and described by James W. Gilbery, (Engineer) Bureau of Reclamation in the dependent resurvey of a portion of the subdivisional lines (between secs. 1 and 12) of this fractional township. I did not remonument this corner.	
<hr style="width: 20%; margin: auto;"/> S. 89° 46.5' W., beginning new measurement	
Descend over west slope	
5.60	The left bank of the East Main Canal, course S. 8° E.
6.20	The right bank of the East Main Canal.
7.76	The witness section corner of secs. 1, 2, 11, and 12, which is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.
W C T11S R25W S 2 S 1 ← S 11 S 12 1959	
The above witness corner was established and described in the official field-note record of the dependent resurvey of a portion of the subdivisional lines within this township by Robert C. Yundt, Cadastral Surveyor, in 1959.	
9.25	The left bank of the Main Drain canal, course south.
10.03	The true point for the corner of secs. 1, 2, 11 and 12, which is determined at proportionate distance. Discontinue the regular order of survey at this corner.
<hr style="width: 20%; margin: auto;"/> S. 0° 26' E., between secs. 11 and 12	


Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	Along the bed of the Main Drain canal.
9.10	The left bank of the Main Drain canal, course on curve to the southwest; thence, over nearly level land.
20.04	The point for the north 1/16 sec. cor. of secs. 11 and 12 Set an iron post, 28 ins. long, 2½ ins. in diam., 26 ins. in the ground, with brass cap mkd. N 1/16 S 11 S 12 1972
32.61	Intersect the northern right-of-way of the Yuma Valley Levee. The point for the corner of lots 14 and 22 of section 11. I did not monument this corner point.
35.83	Intersect the center-line of the Yuma Valley Levee. The point for the corner of lots 21 and 22 of section 11. I did not monument this corner point.
39.05	Intersect the southern right-of-way of the Yuma Valley Levee. The point for the corner of lots 21 and 23 of section 11. I did not monument this corner point.
40.08	The 1/4 sec. cor. of secs. 11 and 12 is monumented with an iron post, 2½ ins. in diam., with brass cap 3 ins. below the surface of the ground, mkd. T11S R25W 1/4 S 11 S 12 1959
	S. 0° 26' E., beginning new measurement
2.45	The point for the corner of lots 8 and 13 of section 11 is determined at proportionate distance; there is no evidence of the original corner. This corner point is designated to function for the corner of lots 8 and 23 of section 11. Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd. T11S R25W S 11 S 12 LOT 23 / LOT 8 1972

Dependent Resurvey of a Portion of the Subdivisional Lines
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS

- 3.33 Intersect a chain link fence, 10 ft. high, bears parallel to the southern boundary of this fractional township.
- 3.41 The closing corner of secs. 11 and 12 on the international boundary; which is monumented with an iron post, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.




From the true point for the corner of secs. 1, 2, 11 and 12, heretofore described

N. 0° 05.5' W., between secs. 1 and 2

Along the bed of the Main Drain canal.


- 8.00 The left bank of the Main Drain canal, course on curve to the south; thence, over nearly level land.
- 20.00 The point for the south 1/16 sec. cor. of secs. 1 and 2
Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.



20.60 The left bank of the Main Drain canal, course S. 27° W.

24.80 The right bank of the Main Drain canal.

40.00 The 1/4 sec. cor. of secs. 1 and 2 is marked with an iron pipe, 1-inch in diam., with brass cap 5 ins. below the surface of the road, and set in a cast iron pipe, 10 ins. in diam., with the top flush with the surface of the road. The above brass cap is marked.



The above corner marker was accepted and described in the official field-note record of the dependent resurvey of a portion of the subdivisional lines within this township by Robert C. Yundt, Cadastral Surveyor, in 1959.

Dependent Resurvey of a Portion of the Subdivisional Lines
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the true point for the corner of secs. 1, 2, 11, and 12, heretofore described.</p> <p>S. 89° 42.5' W., between secs. 2 and 11</p> <p>Along the bed of the Main Drain canal.</p>
0.20	The right bank of the Main Drain canal; thence, over nearly level land, along an east and west roadway.
20.035	The point for the east 1/16 sec. cor. of secs. 2 and 11. I did not monument this corner point.
40.07	<p>The 1/4 sec. cor. of secs. 2 and 11 is marked with a "PK" nail, seated in the surface of a concrete bridge, which is over a concrete lined lateral. This corner point is accepted as the best available evidence of the position of the corner as reestablished by Robert C. Yundt, Cadastral Surveyor, in 1959. I did not remonument this corner.</p> <p>The water within the above lateral flows south.</p> <p>Discontinue the dependent resurvey of the township at this corner.</p> <hr/> <p style="text-align: center;">Survey of a Portion of the Subdivision Lines Within Sections 1 and 11 Township 11 South, Range 25 West Gila and Salt River Meridian, Arizona</p> <hr/> <p>Thence, in section 1</p> <p>From the 1/4 sec. cor. of secs. 1 and 12, heretofore described.</p> <p>N. 0° 16' W., on the north and south center line of sec. 1</p>
19.96	<p>The point for the center-south 1/16 sec. cor. of sec. 1</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C S 1/16 S 1 1972</p>
39.92	Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 1

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.
	T11S R25W C 1/4 S 1 1972
49.942	The point for the C-S-N 1/64 sec. cor. of sec. 1
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.
	C S N 1/64 S 1 1972
59.964	The point for the center-north 1/16 sec. cor. of sec. 1. I did not monument this corner point.
80.008	The 1/4 sec. cor. of secs. 1 and 36 on the north boundary of the township, heretofore described.
	From the 1/4 sec. cor. of secs. 1 and 6 on the east boundary of the township, heretofore described. S. 89° 53.5' W., on the east and west center line of sec. 1
19.825	The point for the center-east 1/16 sec. cor. of sec. 1. I did not monument this corner point.
24.51	The right bank of the East Main Canal, course on curve to the northwest.
24.781	The point for the C-E-W-E 1/256 sec. cor. of sec. 1. I did not monument this corner point.
25.26	The left bank of the East Main Canal.
26.041	The point for the corner of lots 3 and 4 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.
	T11S R25W S 1 C ————— C LOT 3 LOT 4 1972

Survey of a Portion of the Subdivision Lines
Within Sections 1 and 11
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona



CHAINS	
	A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the west side of the corner.
	Ascend over rolling northeast slope
26.70	Bench, bears northwest and southeast; thence, over nearly level land.
29.738	The point for the C-W-E 1/64 sec. cor. of sec. 1
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.
	C W E 1/64 S 1 1972
39.65	Intersect the north and south center line, the center 1/4 sec. cor. of sec. 1, heretofore described.
59.66	The center-west 1/16 sec. cor. of sec. 1 is marked with an iron pipe, of undetermined length, 1-inch in diam., with the top flush with the surface of the ground, and is accepted as the position of the corner. I did not monument this corner.

	S. 89° 53.5' W., beginning new measurement.
1.95	The left bank of the East Main Canal, course S. 16° W.
2.60	The right bank of the East Main Canal.
20.015	The 1/4 sec. cor. of secs. 1 and 2, heretofore described.

	From the point for the center-east 1/16 sec. cor. of sec. 1, heretofore described.
	N. 0° 21' W., on the north and south center line of the northeast quarter of sec. 1
20.095	Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 1. The adjacent landowners did not grant permission to monument this corner point or to establish a witness corner, thereto.
40.19	The east 1/16 sec. cor. of secs. 1 and 36 on the north boundary of the township, heretofore described.

	From the north 1/16 sec. cor. of secs. 1 and 6 on the east boundary of the township, heretofore described.

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>S. 89° 45' W., on the east and west center line of the northeast quarter of sec. 1</p>	
19.79	<p>Intersect the north and south center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 1, heretofore described.</p>	
39.58	<p>Intersect the north and south center line, the point for the center-north 1/16 sec. cor. of sec. 1, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p>	
	<p>From the C-W-E 1/64 sec. cor. of sec. 1, heretofore described.</p>	
	<p>N. 0° 18.5' W., on the north and south center line of the SW¼ of the NE¼ of sec. 1</p>	
5.40	<p>Bench, bears northwest and southeast; thence, descend over northeast slope.</p>	
7.50	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, for the witness SW-NE 1/64 sec. cor. of sec. 1, with brass cap mkd.</p>	
	<div style="text-align: center;">  <p>W/C SW NE 1/64 S 1</p> </div> <p>1972</p>	
	<p>This witness corner is located at the base of descent, bears northwest and southeast; thence, over nearly level land,</p>	
8.035	<p>The point for the cor. of lots 1 and 2 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>	
	<div style="text-align: center;">  <p>T11S R25W S 1 LOT 1 LOT 2</p> </div> <p>1973</p>	
	<p>A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the north side of the corner.</p>	
8.99	<p>The left bank of the East Main Canal, course N. 30° 45' W.</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

10.035 The calculated position, the true point for the SW-NE 1/64 sec. cor. of sec. 1. This true corner point is located within the bed of the East Main Canal, an unsafe location for a monument.

Discontinue the regular order of survey at this corner point.


Thence,

S. 89° 49' W., on the east and west center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of section 1

0.60 The left bank of the East Main Canal, course on curve to the northwest.

1.18 The point for the corner of lots 1 and 2 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. in diam., 25 ins. in the ground, with brass cap mkd.



A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the east side of the corner.

Thence, ascend over rolling northeast slope.

2.10 Bench, bears northwest and southeast; thence, over nearly level land.

9.905 Intersect the north and south center line, the C-S-N 1/64 sec. cor. of sec. 1, heretofore described.

From the corner of lots 1 and 2 of section 1, and is located on the north and south center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of section 1, heretofore described.

N. 30° 45' W., between lots 1 and 2 of section 1

2.325 The corner of lots 1 and 2 of section 1, and is located on the east and west center line of the SW $\frac{1}{4}$ of the NE $\frac{1}{4}$ of sec. 1, heretofore described.

From the west 1/16 sec. cor. of secs. 1 and 12, heretofore described.

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 0° 11' W., on the north and south center line of the southwest quarter of section 1.</p>
19.975	<p>Intersect the east and west center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 1</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">SW 1/16 S 1 1972</p>
34.96	<p>The point for the C-N-N-SW 1/256 sec. cor. of section 1</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">C N N SW 1/256 S 1 1972</p>
37.80	<p>Bench, bears northeast and southwest; thence, descend over rolling northwest slope.</p>
39.955	<p>The center-west 1/16 sec. cor. of sec. 1, heretofore described.</p>
	<p>From the center-south 1/16 sec. cor. of sec. 1, heretofore described.</p>
	<p>S. 89° 50' W., on the east and west center line of the southwest quarter of section 1.</p>
	<p>Descend over west to northwest slope.</p>
20.04	<p>Intersect the north and south center line of the southwest quarter, the southwest 1/16 sec. cor. of sec. 1, heretofore described.</p>
30.06	<p>The point for the C-W-SW 1/64 sec. cor. of sec. 1</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">C W SW 1/64 S 1 1972</p>
	<p>A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the west side of the corner.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
31.52	<p>The point for the corner of lots 8 and 9 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R25W</p> <p>S 1</p> <hr style="width: 100px; margin: 0 auto;"/> <p>LOT 8 \ LOT 9</p> <p style="margin-left: 100px;">/</p> <p>1973</p> </div> <p>A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the west side of the corner.</p>
32.01	The left bank of the East Main Canal, course S. 7° 20' W.
32.82	The right bank of the East Main Canal.
34.10	The center line of U. S. Highway No. 95, bears N. 20° 15' W. and S. 20° 15' E.
35.075	<p>The point for the C-W-W-SW 1/256 sec. cor. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C W W SW 1/256</p> <p>S 1</p> <p>1972</p> </div>
40.085	The south 1/16 sec. cor. of secs. 1 and 2, heretofore described.
10.88	<p>From the C-W-SW 1/64 sec. cor. of sec. 1, heretofore described.</p> <p>N. 0° 08' W., on the north and south center line of the NW¼ of the SW¼ of sec. 1</p> <p>The point for the corner of lots 6 and 7 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11S R25W</p> <p>S 1</p> <p>LOT 7</p> <p style="margin-left: 100px;">/</p> <p>LOT 6</p> <p>1973</p> </div>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the south side of the corner.
11.77	The left bank of the East Main Canal, course S. 35° 04' W.
12.89	The right bank of the East Main Canal.
14.99	The calculated position, the point for the C-N-NW-SW 1/256 sec. cor. of sec. 1
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">C N NW SW 1/256 S 1</p>
	<p style="text-align: center;">1972</p>
	A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the southwest side of the corner.
	Discontinue the regular order of survey at this corner.
	Thence,
	N. 89° 52.5' E., on the east and west center line of the NE¼-NW¼-SW¼ of sec. 1.
1.56	The right bank of the East Main Canal, course S. 35° 04' W.
2.28	The left bank of the East Main Canal.
2.90	The point for the corner of lots 6 and 7 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, wiht brass cap mkd.
	<p style="text-align: center;">T11S R25W S 1 ----- LOT 7 / LOT 6</p>
	<p style="text-align: center;">1973</p>
	A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the east side of the corner.
10.01	Intersect the north and south center line of the southwest quarter, the C-N-N-SW 1/256 sec. cor. of sec. 1, heretofore described.

Survey of a Portion of the Subdivision Lines
Within Sections 1 and 11
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the corner of lots 6 and 7 of section 1, and is located on the north and south center line of the NW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of section 1, heretofore described.</p> <p>N. 35° 04' E., between lots 6 and 7 of section 1</p>
5.03	<p>The corner of lots 6 and 7 of section 1, and is located on the east and west center line of the NE$\frac{1}{4}$-NW$\frac{1}{4}$-SW$\frac{1}{4}$ of sec. 1, heretofore described.</p>
	<p>From the west-west 1/64 sec. cor. of secs. 1 and 12, heretofore described</p> <p>N. 0° 08' W., on the north and south center line of the SW$\frac{1}{4}$ of the SW$\frac{1}{4}$ of sec. 1</p>
5.00	<p>The point for the C-S-SW-SW 1/256 sec. cor. of sec. 1; this corner point is located on the north edge of a clay-brick wall, 3 ft. high. I did not monument this corner point.</p> <p>from which</p> <p style="padding-left: 40px;">The east end of the above clay-brick wall, bears N. 89° 47.5' E., 105 lks. distant.</p> <p style="padding-left: 40px;">The west end of the same clay-brick wall, bears S. 89° 47.5' W., 90 lks. distant.</p>
9.72	<p>The center line of U. S. Highway No. 95, bears S. 21° 30' E. and N. 21° 30' W.</p>
19.99	<p>Intersect the east and west center line of the southwest quarter, the C-W-SW 1/64 sec. cor. of sec. 1, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p>
	<p>From point for the C-S-SW-SW 1/256 sec. cor. of sec. 1, heretofore described.</p> <p>S. 89° 47.5' W., on the east and west center line of the SW$\frac{1}{4}$-SW$\frac{1}{4}$-SW$\frac{1}{4}$ of sec. 1</p>
5.015	<p>The calculated position, the point for the SW-SW-SW 1/256 sec. cor. of sec. 1. This corner point is marked with a concrete form, 7 ins. square, firmly set, with the top flush with the surface of the ground, the center is marked with a drill hold, 1$\frac{1}{4}$-inch in diam. I accept this local marker as the position for the corner and did not remonument.</p> <p>I set a railroad track rail, 5 ft. long, 3 ft. in the ground, along the north side of the corner.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS


Discontinue the regular order of survey at this corner.

Thence,

N. 0° 06.7' W., on the north and south center line of the W $\frac{1}{2}$ of the SW $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 1.

2.165 The point for the corner of lots 8 and 9 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1973

A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the south side of the corner.

14.995 Intersect the east and west center line of the southwest quarter, the C-W-W-SW 1/256 sec. cor. of sec. 1, heretofore described.

From the corner of lots 8 and 9 of sec. 1, and is located on the north and south center line of the W $\frac{1}{2}$ of the SW $\frac{1}{4}$ of the SW $\frac{1}{4}$ of sec. 1, heretofore described.

N. 22° 12' E., between lots 8 and 9 of section 1.

2.635 The point for an Angle Point of lots 8 and 9 of sec. 1.

Set a railroad track rail, 5 ft. long, 3 ft. in the ground for the corner monument.

N. 5° 43' E., continue between lots 8 and 9 of sec. 1.

6.30 The point for an Angle Point of lots 8 and 9 of sec. 1.

Set an railroad track rail, 5 ft. long, 3 ft. in the ground for the corner monument.

Survey of a Portion of the Subdivision Lines
Within Sections 1 and 11
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 43° 41' E., continue between lots 8 and 9 of sec. 1.
1.00	The center line of U. S. Highway No. 95, bears S. 20° 15' E. and N. 20° 15' W.
3.11	The point for an Angle Point of lots 8 and 9 of sec. 1. Set a railroad track rail, 5 ft. long, 3 ft. in the ground for the corner monument. <hr/>
	N. 7° 20' W., continue between lots 8 and 9 of sec. 1.
1.90	Intersect the east and west center line of the southwest quarter. The corner of lots 8 and 9 of sec. 1, heretofore described. <hr/>
	From the E-W-W 1/256 sec. cor. of secs. 1 and 12, heretofore described.
	N. 0° 09.5' W., of the north and south center line of the SE $\frac{1}{4}$ -SW $\frac{1}{4}$ -SW $\frac{1}{4}$ of sec. 1.
4.995	The calculated position, the point for the SE-SW-SW 1/256 sec. cor. of sec. 1. Set an iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. in diam., 25 ins. in the ground, with brass cap mkd. SE SW SW 1/256 S 1 1972 Discontinue the regular order of survey at this corner. <hr/>
	Thence,
	S. 89° 47.5' W., on the east and west center line of the SE $\frac{1}{4}$ -SW $\frac{1}{4}$ -SW $\frac{1}{4}$ of sec. 1
5.015	The point for the C-S-SW-SW 1/256 sec. cor. of sec. 1, heretofore described. <hr/>
	From the east 1/16 sec. cor. of secs. 1 and 12, heretofore described
	N. 0° 23' W., on the north and south center line of the southeast quarter of sec. 1

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona


CHAINS	
19.905	<p>Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">SE 1/16 S 1 1972</p>
30.20	<p>Bench, bears southeast and northwest; thence, descend over rolling northeast slope.</p>
31.23	<p>The point for the corner of lots 3 and 5 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11S R25W S 1 LOT 5 LOT 3 1973</p> <p>A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the south side of the corner.</p> <p>This corner is located at the base of descent, bears northwest and southeast; thence, over nearly level land.</p>
32.11	<p>The left bank of the East Main Canal, course N. 31° 50' W.</p>
33.45	<p>The right bank of the East Main Canal.</p>
34.835	<p>The point for the C-N-N-SE 1/256 sec. cor. of sec. 1.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N N SE 1/256 S 1 1972</p> <p>A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the west side of the corner.</p>
39.81	<p>Intersect the east and west center line, the point for the center-east 1/16 sec. cor. of sec. 1, heretofore described.</p>

Survey of a Portion of the Subdivision Lines
Within Sections 1 and 11
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the south 1/16 sec. cor. of secs. 1 and 6 on the east boundary of the township, heretofore described.</p> <p>S. 89° 51' W., on the east and west center line of the southeast quarter of sec. 1</p>
19.86	Intersect the north and south center line of the southeast quarter, the southeast 1/16 sec. cor. of sec. 1, heretofore described.
29.79	<p>The point for the C-W-SE 1/64 sec. cor. of sec. 1</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C W SE 1/64 S 1 1972</p>
39.72	<p>Intersect the north and south center line, the center-south 1/16 sec. cor. of sec. 1, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the C-W-SE 1/64 sec. cor. of sec. 1, heretofore described.</p> <p>N. 0° 19' W., on the north and south center line of the NW¼ of the SE¼ of sec. 1</p>
19.93	<p>Intersect the east and west center line, the C-W-E 1/64 sec. cor. of sec. 1, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the C-N-N-SE 1/256 sec. cor. of sec. 1, heretofore described.</p> <p>S. 89° 51' W., on the east and west center line of the NE¼-NW¼-SE¼ of sec. 1</p>
0.76	The right bank of the east Main Canal, course N. 31° 50' W.
1.70	The left bank of the East Main Canal; thence, ascend over rolling northeast slope.
2.215	<p>The point for the corner of lots 3 and 5 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS




1973

4.00 Bench (top of ascent), bears northwest and southeast; thence, over nearly level land.

4.96 The calculated position, the point for the NE-NW-SE 1/256 sec. cor. of sec. 1

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1972

Discontinue the regular order of survey at this corner.


Thence,

N. 0° 21' W., on the north and south center line of the NE¼-NW¼-SE¼ of sec. 1

1.15 Bench, bears northwest and southeast; thence, descend over rolling northeast slope.

2.47 The point for the corner of lots 3 and 4 of section 1, which is determined at 55 ft. distance perpendicular to the center line of the East Main Canal.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1973

A railroad track rail, 5 ft. long, set 3 ft. in the ground, along the north side of the corner.

4.13 The left bank of the East Main Canal, course on curve to the northwest.

4.98 Intersect the east and west center line, the point for the C-E-W-E 1/256 sec. cor. of sec. 1, heretofore described.

Survey of a Portion of the Subdivision Lines
Within Sections 1 and 11
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS	
2.815	<p>From the corner of lots 3 and 4 of section 1, and is located on the north and south center line of the NE$\frac{1}{4}$-NW$\frac{1}{4}$-SE$\frac{1}{4}$ of section 1, heretofore described.</p> <p>N. 26° 57' W., between lots 3 and 4 of section 1</p> <p>Intersect the east and west center line, the corner of lots 3 and 4 of section 1, heretofore described.</p>
4.24	<p>From the corner of lots 3 and 5 of section 1, and is located on the north and south center line of southeast quarter of section 1, heretofore described.</p> <p>N. 31° 52' W., between lots 3 and 5 of section 1</p> <p>The corner of lots 3 and 5 of section 1, is located on the east and west center line of the NE$\frac{1}{4}$-NW$\frac{1}{4}$-SE$\frac{1}{4}$ of section 1, heretofore described.</p>
13.75	<p>Thence, in section 11</p> <p>From the 1/4 sec. cor. of secs. 2 and 11, heretofore described.</p> <p>S. 0° 39' E., on the north and south center line of section 11</p> <p>Along the center line of a concrete lined lateral</p> <p>At this point on line the lateral turns to the east.</p>
14.75	<p>The center line of the Yuma Valley Levee, bears on a curve to the northwest and southeast.</p>
16.40	<p>The center line of a concrete lined lateral, bears S. 59° 30' E. and N. 59° 30' W.</p>
20.045	<p>The point for the center-north 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 15 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">C N 1/16 S 11</p> <p style="text-align: center;">1972</p>
28.80	<p>There are no suitable accessories nor locations available for reference monuments.</p> <p>The corner of lots 3, 6, 7, and 12 of section 11 is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 3 ins. above the surface of the ground, with regulation brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

T11S R25W
 S | 11
 3 | 12

 6 | 7

1959

The above corner was established and the monument was described in the official field-note record of the re-tracement of the boundary between the United States and Mexico by Robert C. Yundt, Cadastral Surveyor, in 1959. I designated lot No. 12 of sec. 11 of the 1959 survey as lot No. 19 of sec. 11 of this survey and re-marked the above brass cap, as follows:

T11S R25W
 S | 11
 3 | 19

 6 | 7

1972

1959

29.68 Intersect a chain link fence, 10 ft. high, bears parallel to the southern boundary of this fractional section.

29.76 Intersect the closing corner of this subdivision line with the southern boundary of this fractional section. Which is monumented with an iron post, 2½ ins. in diam., firmly set, projecting 3 ins. above the surface of the ground, with regulation brass cap mkd.

T11S R25W
 C C
 C
 S | 11

 C

MEX

1959

The above corner was established and the monument was described in the official field-note record of the re-tracement of the boundary between the United States and Mexico by Robert C. Yundt, Cadastral Surveyor, in 1959.

From the point for the east 1/16 sec. cor. of secs. 2 and 11, heretofore described.

S. 0° 32.5' E., on the north and south center line of the northeast quarter of sec. 11

Over nearly level land.

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
20.045	<p>Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 15 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">NE 1/16 S 11 1972</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>
23.925	<p>Intersect the northern right-of-way of the Yuma Valley Levee. The point for the corner of lots 15, 16, 17, and 20 of sec. 11. I did not monument this corner point.</p>
27.47	<p>Intersect the center-line of the Yuma Valley Levee. The point for the corner of lots 17, 18, 20, and 21 of sec. 11. I did not monument this corner point.</p>
31.015	<p>Intersect the southern right-of-way of the Yuma Valley Levee. The point for the corner of lots 18, 19, 21, and 25 of sec. 11. I did not monument this corner point.</p>
35.665	<p>Intersect the northern boundary of the International Boundary Reserve. Which is determined at 60 ft. distance perpendicular to the south boundary of this fractional section. The point for the corner of lots 7, 8, 19, and 25 of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11S R25W S 11 LOT 19 LOT 25 <hr style="width: 50%; margin: auto;"/>LOT 7 LOT 8 1972</p>
36.55	<p>Intersect a chain link fence, 10 ft. high, bears parallel to the southern boundary of this fractional section.</p>
36.625	<p>Intersect the south boundary of fractional section 11. The point for the closing corner of this subdivision line with the south boundary of fractional section 11. I did not monument this corner point.</p> <p>From this corner point the closing corner of secs. 11 and 12, heretofore described, bears S. 71° 22' E., 21.17 chs. distant.</p> <p>From this same corner point the closing corner of the north and south center line of section 11, heretofore described, bears N. 71° 22' W., 21.17 chs. distant.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the north 1/16 sec. cor. of secs. 11 and 12, heretofore described.</p>
	<p>S. 89° 42.5' W., on the east and west center line of the northeast quarter of sec. 11</p>
	<p>Over nearly level land.</p>
<p>1.37</p>	<p>The point for Angle Point No. 4, Tract 37.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T11S R25W S 11 <hr style="width: 50%; margin: 0 auto;"/> AP 4 / TR 37 / 1972</p> </div>
<p>3.13</p>	<p>The left bank of the Main Drain canal, course S. 16° W.</p>
<p>4.72</p>	<p>The right bank of the Main Drain canal.</p>
<p>5.80</p>	<p>The point for Angle Point No. 5, Tract 37.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>
	<div style="text-align: center;"> <p>T11S R25W S 11 <hr style="width: 50%; margin: 0 auto;"/> / AP 5 / TR 37 1972</p> </div>
<p>20.035</p>	<p>Intersect the north and south center line of the northeast quarter, the northeast 1/16 sec. cor. of sec. 11, heretofore described.</p>
<p>26.45</p>	<p>Intersect the northern right-of-way of the Yuma Valley Levee. The point for the corner of lots 16 and 17 of section 11. I did not monument this corner point.</p>
<p>32.31</p>	<p>Intersect the center-line of the Yuma Valley Levee. The point for the corner of lots 17 and 18 of section 11. I did not monument this corner point.</p>
<p>38.17</p>	<p>Intersect the southern right-of-way of the Yuma Valley Levee. The point for the corner of lots 18 and 19 of section 11. I did not monument this corner point.</p>
<p>40.07</p>	<p>Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 11, heretofore described.</p>
	<p>Discontinue the regular order of survey at this corner.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>From the point for the corner of lots 15, 16, 17, and 20 of sec. 11, and is located on the north and south center line of the northeast quarter of sec. 11, heretofore described.</p> <p>N. 59° 10.3' W., between lots 16 and 17 of sec. 11</p>	
	7.51	<p>Intersect the east and west center line of the northeast quarter, the point for the corner of lots 16 and 17 of sec. 11, heretofore described.</p>	
		<p>From the point for the corner of lots 17, 18, 20, and 21 of sec. 11, and is located on the north and south center line of the northeast quarter of sec. 11, heretofore described.</p> <p>N. 59° 10.3' W., between lots 17 and 18 of sec. 11</p>	
	14.375	<p>Intersect the east and west center line of the northeast quarter, the point for the corner of lots 17 and 18 of sec. 11, heretofore described.</p>	
		<p>From the point for the corner of lots 18, 19, 21, and 25 of sec. 11, and is located on the north and south center line of the northeast quarter of sec. 11, heretofore described.</p> <p>N. 59° 10.3' W., between lots 18 and 19 of sec. 11</p>	
	21.235	<p>Intersect the east and west center line of the northeast quarter, the point for the corner of lots 18 and 19 of sec. 11, heretofore described.</p>	
		<p>From the corner of lots 8 and 23 of section 11, and is located on the section line between secs. 11 and 12, heretofore described.</p> <p>N. 71° 22' W., between lots 8 and 23 of section 11</p>	
	16.54	<p>The point for the corner of lots 8, 23, and 24 of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>	
		<p style="text-align: center;">T11S R25W S 11 LOT 24 LOT 23 LOT 8 1972</p>	

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona


CHAINS	
	<p>Thence, continuing course and measurement between lots 8 and 24 of section 11.</p>
19.89	<p>The point for the corner of lots 8, 24, and 25 of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p> <div data-bbox="711 682 956 903" style="text-align: center;"> <p>T11S R25W S 11</p> <p>LOT 25 LOT 24 LOT 8</p> <p>1972</p> </div>
21.17	<p>Thence, continuing course and measurement between lots 8 and 25 of section 11.</p> <p>Intersect the north and south center line of the north-east quarter, the corner of lots 7, 8, 19, and 25 of sec. 11, heretofore described.</p>
2.765	<p>From the point for the corner of lots 14 and 22 of sec. 11, and is located on the section line between secs. 11 and 12, heretofore described.</p> <p>N. 70° 40.5' W., between lots 14 and 22 of sec. 11</p> <p>Intersect line 1 - 2, Tract 37, the point for the corner of lots 14 and 22 of sec. 11. I did not monument this corner point.</p>
0.27	<p>The point for the corner of lots 15 and 20 of sec. 11 is determined at the point of intersection of the northern right-of-way of the Yuma Valley Levee and (the herein-after described) line 7 - 8 of Tract 37. I did not monument this corner point.</p> <p>N. 70° 40.5' W., between lots 15 and 20 of sec 11</p> <p>The point for an Angle Point of lots 15 and 20 of section 11. I did not monument this corner point.</p> <hr style="width: 20%; margin: 10px auto;"/>
7.315	<p>N. 59° 10.3' W.,</p> <p>Intersect the north and south center line of the north-east quarter, the point for the corner of lots 15, 16, 17, and 20 of sec. 11, heretofore described.</p>

Survey of a Portion of the Subdivision Lines
Within Sections 1 and 11
Township 11 South, Range 25 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the point for the corner of lots 21 and 22 of sec. 11, and is located on the section line between secs. 11 and 12, heretofore described.</p> <p>N. 70° 40.5' W., between lots 21 and 22 of sec. 11</p>
3.33	<p>The point for Angle Point No. 1, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 9 ins. below the surface of the road, mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>T11S R25W TR 37 / AP 1 / S 11</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1972</p> </div> <p>From this corner the southeast corner of a concrete constructed pump house, 44 by 61.5 ft. (longside bears parallel to line 1 - 8, Tract 37), bears N. 65° 53' W., 5.30 chs. distant.</p> <p>Thence, continuing course and measurement, and continue along the northern boundary of lot 21 and on line 1 - 8 of Tract 37.</p>
16.01	<p>The point for Angle Point No. 8, Tract 37, identical with the southern corner of lots 20, and an Angle Point on the northern boundary of lot 21 of sec. 11; which is marked with a brass tablet seated in concrete, with the top 7 ins. below the surface of the road, mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>BUREAU OF RECLAMATION PI S+2 1234+92.33</p> <hr style="width: 50%; margin: 0 auto;"/> <p>1952</p> </div> <p>N. 59° 10.3' W., between lots 20 and 21 of sec. 11</p>
5.775	<p>Intersect the north and south center line of the north-east quarter, the corner of lots 17, 18, 20, and 21 of sec. 11, heretofore described.</p>
10.80	<p>From the point for the corner of lots 21 and 23 of sec. 11, and is located on the section line between secs. 11 and 12, heretofore described.</p> <p>N. 70° 40.5' W., between lots 21 and 23 of sec. 11</p> <p>The point for the corner of lots 21, 23, and 24 of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona


CHAINS



Thence, continuing course and measurement between lots 21 and 24 of section 11.

14.10 The point for the corner of lots 21, 24, and 25 of sec. 11.

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



Thence, continuing course and measurement between lots 21 and 25 of section 11.

17.40 The point for an Angle Point of lots 21 and 25 of section 11. I did not monument this corner point.

N. 59° 10.3' W.,

4.24 Intersect the north and south center line of the northeast quarter, the corner of lots 18, 19, 21, and 25 of sec. 11, heretofore described.

From the corner of lots 23 and 24 of sec. 11, and is located on the northern boundary of lot 8 of sec. 11, heretofore described.

N. 72° 00' E., between lots 23 and 24 of section 11

5.73 The corner of lots 23 and 24 of sec. 11, and is located on the southern boundary of lot 21 of sec. 11, heretofore described.

From the corner of lots 24 and 25 of sec. 11, and is located on the northern boundary of lot 8 of sec. 11, heretofore described.

N. 72° 00' E., between lots 24 and 25 of section 11

Survey of a Portion of the Subdivision Lines
 Within Sections 1 and 11
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

5.79 The corner of lots 24 and 25 of sec. 11, and is located on the southern boundary of lot 21 of sec. 11, heretofore described.

Survey of Tract 37
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

From Angle Point No. 1, Tract 37, and is located on the northern boundary of lot 21 of section 11, heretofore described.

N. 9° 29.5' E., on line 1 - 2 of Tract 37, identical with the western boundary of lot 22 of section 11

3.075 The point for the corner of lots 14 and 22, heretofore described.

Continue on line 1 - 2 of Tract 37, and along the western boundary of lot 14 of section 11.

4.33 The point for Angle Point No. 2 of Tract 37

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T11S R25W
 AP 2
 TR 37 } S 11

1972

N. 4° 27' W., on line 2 - 3 of Tract 37, identical with the western boundary of lot 14 of section 11

3.69 The point for Angle Point No. 3 of Tract 37

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T11S R25W
 AP 3
 TR 37 } S 11

1972

N. 10° 23' E., on line 3 - 4 of Tract 37, identical with the western boundary of lot 14 of section 11

Survey of Tract 37
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

6.845 Intersect the east and west center line of the northeast quarter of section 11, Angle Point No. 4 of Tract 37, heretofore described.



S. 89° 42.5' W., on line 4 - 5 of Tract 37, identical with the east and west center line of the northeast quarter of section 11.

1.76 The left bank of the Main Drain canal, course S. 16° W.

3.35 The right bank of the Main Drain canal.


4.43 Angle Point No. 5 of Tract 37, heretofore described.



S. 24° 43.5' W., on line 5 - 6 of Tract 37, identical with the eastern boundary of lot 15 of section 11.

7.105 The point for Angle Point No. 6 of Tract 37

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.




1972



N. 80° 41.5' W., on the line 6 - 7 of Tract 37, identical with the southern boundary of lot 15 of section 11

3.63 The point for Angle Point No. 7 of Tract 37

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.



1972



S. 30° 01' W., on line 7 - 8 of Tract 37, identical with the southern boundary of lot 15 of section 11.

2.22 Intersect the northern right-of-way of the Yuma Valley Levee. The point for the corner of lots 15 and 20 of section 11, heretofore described.

Survey of Tract 37
 Township 11 South, Range 25 West
 Gila and Salt River Meridian, Arizona

CHAINS

Continue on line 7 - 8 of Tract 37, and along the eastern boundary of lot 20 of section 11.

5.31 Intersect the center-line of the Yuma Valley Levee. Angle Point No. 8 of Tract 37, identical with the southern corner of lot 20 and an Angle Point on the northern boundary of lot 21 of section 11, heretofore described.

S. 70° 40.5' E., on line 8 - 1 of Tract 37, identical with the northern boundary of lot 21 of section 11.

12.68 Angle Point No. 1 of Tract 37, heretofore described, and the place of beginning.

GENERAL DESCRIPTION

The land area within these surveys is nearly level. The soil consists of sandy clay loam, and for the most part the area is under cultivation, except for the federally controlled lands which are undeveloped; with mesquite trees and creosote brush (shrub) growth.

Improvements located throughout the area, are: U. S. Highway No. 95 (traverses across section 1), state, county, and farm roads; the East Main Canal meanders through the area, generally along the toe of a well-defined bench, numerous canals and laterals for irrigation and/or drainage purposes.

CHAINS

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Glenn F. Goodson	Cadastral Surveyor
Everett E. Gorgen	Surveying Aid
Henry X. Frank	Surveying Aid
Caleb C. Costin	Surveying Aid
Jerome A. McKay	Surveying Aid
Bruce C. McDonald	Surveying Aid
Victor S. Templeton	Surveying Aid

CERTIFICATE OF SURVEY

(I) (Wφ), Ray Harpin , HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 7th day of January , 19 72 , (I) (Wφ) have dependently resurveyed a portion of the east and north boundaries and a portion of the subdivisional lines; surveyed a portion of the subdivision lines within sections 1 and 11; and surveyed Tract No. 37, Township 11 South, Range West,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by (me), (us) and under (my) (of) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 28, 1978 (Date)

Ray Harpin (Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Washington, D.C. Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the east and north boundaries and a portion of the subdivisional lines; the survey of a portion of the subdivision lines within sections 1 and 11; and the survey of Tract No. 37, Township 11 South, Range 25 West, of the Gila and Salt River Meridian, Arizona.

executed by Ray Harpin, Cadastral Surveyor

having been critically examined and found correct, are hereby approved.

JAN 21 1980 (Date)

J. Jorke (Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626