

Form 9180-6
(March 1977)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE DEPENDENT RESURVEY OF THE

5TH GUIDE MERIDIAN EAST

THROUGH TOWNSHIP 14 NORTH, BETWEEN RANGES 20 AND 21 EAST

A

PORTION OF THE EAST BOUNDARY

AND

SUBDIVISIONAL LINES

TOWNSHIP 14 NORTH, RANGE 21 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

PAUL L. REEVES

Cadastral Surveyor

Under special instructions dated NOVEMBER 14, 19 78, approved NOVEMBER 14, 1978,

_____, which provided for the surveys included under U.S. Survey/Group
Number 607, and assignment instructions dated NOVEMBER 14, 19 78.

Survey commenced NOVEMBER 16, 19 78

Survey completed JUNE 6, 19 79

1A

BOOK 5 111

INDEX DIAGRAM

Township 14 NORTH, Range 21 EAST

4 6 34	34 5 33	28 4 27	22 8 21	2	1	
3 7 32	33 8 32	27 9 26	21 10 20	15 11 15	12	
3 18 31	31 17 31	26 16 26	15 20	14 14 14	9 13 9	
3 19 30	30 20 29	25 21 25	19 22 18	13 23 13	8 24 8	6
2 30 29	29 29 29	24 28 23	18 27 17	12 26 11	7 25	6
1 31	28 32	23 33	16 34	10 35	36	5

Township 14 North, Range 21 East,
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of the 5th Guide Meridian East, through Township 14 North, between Ranges 20 and 21 East, a portion of the east boundary and subdivisional lines, Township 14 North, Range 21 East.

The east boundary was surveyed in 1875 by C. B. Foster and resurveyed in 1882 by A. P. Johnson. The south boundary was surveyed by John L. Harris in 1879 and resurveyed by Henry Meyrick in 1883. The west five miles of the south boundary was resurveyed by Sidney E. Blout in 1920-21. The west boundary (the 5th Guide Meridian East) was surveyed by M. N. Grant in 1883. The north boundary and subdivisional lines were surveyed by Henry Meyrick in 1883. The north boundary was resurveyed by Boyd S. Owens and Kenneth D. Herman in 1966.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instruction for Group No. 607, Arizona dated November 14, 1978.

The directions of lines refer to the true meridian as determined by angular deflections from triangulation stations projected by fore and backsights.

Survey was made with a wild T-16 Theodolite, a Hewlett Packard Model 3805A and A Zeiss SM4.

Prior to restoration of any corners, the lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Identified corners were remonumented in their original positions; lost corners were reestablished at proportionate positions based on the original record but not until exhausting every reasonable possibility of finding direct evidence for the control of each corner. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the southeast corner of the Tp., as scaled from the U.S. Geological Survey Quadrangle Map "Snowflake, Arizona," prepared in 1970, is as follows:

Latitude 34°33.4' N. Longitude 110°02.7' W.

The mean magnetic declination is 13°30' E.

Dependent Resurvey of
the 5th Guide Meridian East through T. 14 N.,
bet. Rs. 20 and 21 E., Gila & Salt River Mer., Ariz.

(Restoring the 1883 survey by M. N. Grant)

From the cor. of Tps. 13 and 14 N., Rs. 20 and 21 E., monumented with an iron post, 3 ins. diam., projecting 14 ins. above the ground, with brass cap mkd.

T14N
R20E R21E
S36|S31
S 1|S 6
T13N
1921

Dependent Resurvey of
the 5th Guide Meridian East through T. 14 N.,
bet. Rs. 20 and 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>The original 1883 cedar post, 6 ins. diam., projecting 24 ins. above the ground alongside the iron post, mkd. TXIIIN RX.</p>
	<p>Cor. is located in a fence line, bears N. 20° E. and S. N. 1°26' E., bet. secs. 31 and 36.</p>
	<p>Over gently rolling land, through scattered juniper.</p>
40.17	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
	<p>Fence line, bears S. 78° E. and N. 78° W.</p>
80.34	<p>The cor. of secs. 25, 30, 31 and 36, monumented with spike nail at a fence cor., fences extend N., S. and W. At this point found the original juniper post, 3 ins. diam., 4 ft. long lying loose at the fence cor. blazed on 2 sides, no marks visible. This point was established by the Arizona Public Service Co. and is accepted as a careful and faithful reestablishment of the position of the original cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R20E R21E <u>S25 S30</u> <u>S36 S31</u> 1978</p>
	<p>Deposit the spike inside the iron post and set the wooden post alongside.</p>
	<p>N. 0°43' W., bet. secs. 25 and 30.</p>
	<p>Over gently rolling land, through widely scattered juniper along a fence line.</p>
40.42	<p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
80.84	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a spike nail at a fence cor., fences extend N., S., E. and W. This point was established by the Arizona Public Service Co. and is accepted as a careful and faithful reestablishment of the position of the original cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R20E R21E <u>S24 S19</u> <u>S25 S30</u> 1978</p>
	<p>Deposit spike inside iron post.</p>

Dependent Resurvey of
the 5th Guide Meridian East through T. 14 N.,
bet. Rs. 20 and 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>N. 0°38' W., bet. secs. 19 and 24.</p> <p>Over gently rolling land, through scattered juniper along a fence line.</p> <p>40.38 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>80.76 The cor. of secs. 13, 18, 19 and 24, monumented with a spike nail at a fence cor., fences extend N., E. and S. This point was established by the Arizona Public Service Co. and is accepted as a careful and faithful re-establishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R20E R21E <u>S13 S18</u> <u>S24 S19</u> 1978</p> <p>Deposit the spike at base of iron post.</p>	
	<p>N. 0°46' W., bet. secs. 13 and 18.</p> <p>Over gently rolling land, through scattered juniper along a fence line.</p> <p>40.91 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>81.82 The cor. of secs. 7, 12, 13 and 18, monumented with a spike nail at a fence cor., fences extend E., S. and W. This point was established by the Arizona Public Service Co. and is accepted as a careful and faithful reestablishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R20E R21E <u>S12 S 7</u> <u>S13 S18</u> 1978</p> <p>Deposit the spike at base of iron post.</p>	
	<p>N. 0°35' E., bet. secs. 7 and 12.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>40.40 The 1/4 sec. cor. of secs. 7 and 12, monumented with a cedar post, 3 ins. diam., projecting 5 ft. above the ground, blazed on W. side, no marks visible with a 3/8 in. reinforcement rod set alongside the wooden post.</p> <p>At the cor. point</p>	

Dependent Resurvey of
the 5th Guide Meridian East through T. 14 N.,
bet. Rs. 20 and 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R20E R21E $\frac{1}{4}$ S12 S 7 1978</p>
	<p>Deposit the reinforcement rod and wooden post alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 1°13' W., beginning new measurement.</p>
<p>40.33</p>	<p>The cor. of secs. 1, 6, 7 and 12, monumented with the remains of a cedar post, 4 ins. diam., firmly set, no marks visible.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R20E R21E <u>S 1 S 6</u> S12 S 7 1978</p>
	<p>Bury the cedar post alongside the iron post.</p>
	<p>Raise a mound of stone, 4 ft. base, 2 1/2 ft. high, W. of the cor.</p>
	<p style="text-align: center;">_____</p> <p>N. 0°27' W., bet. secs. 1 and 6.</p>
	<p>Over gently rolling land, through scattered cedar.</p>
<p>28.90</p>	<p>Track road, bears S. 87° E. and N. 87° W.</p>
<p>30.10</p>	<p>High voltage power line, bears S. 87° E. and N. 87° W.</p>
<p>40.19</p>	<p>The 1/4 sec. cor. of secs. 1 and 6, monumented with a cedar post, 4 ins. diam., 5 ft. long, loosely set, no marks visible.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R20E R21E $\frac{1}{4}$ S 1 S 6 1978</p>
	<p>Deposit the cedar post alongside the iron post.</p>
	<p>Set a steel fence post alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 1°29' E., beginning new measurement.</p>

Dependent Resurvey of
the 5th Guide Meridian East through T. 14 N.,
bet. Rs. 20 and 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
40.07	<p>The cor. of Tps. 14 and 15 N., Rs. 20 and 21 E., monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R20E R21E S36 S31 S 1 S 6 T14N 1966</p> <p>Cor. is located in an E. and W. fence line.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the E. Bdy., T. 14 N., R. 21 E., Gila and Salt River Mer., Arizona</p> <hr/> <p style="text-align: center;">(Restoring the 1882 resurvey by A. P. Johnson)</p> <p>Beginning at the cor. of Tps. 13 and 14 N., Rs. 21 and 22 E., monumented with a 1 in. open end pipe, projecting 6 ins. above the ground, with a wooden post, 3 ins. diam., 3 ft. long, wired to a fence cor. above the local iron pipe, mkd. XIV and other illegible scribe marks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E R22E S36 S31 S 1 S 6 R21E R22E T13N 1979</p> <p>Deposit iron pipe and set wooden post alongside the iron post.</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears S. 56° E., 270.5 lks. dist. mkd. T13N R22E S6 BT.</p> <p style="padding-left: 40px;">A juniper, 3 ins. diam., bears S. 3 1/2° W., 265 lks. dist. mkd. X BT at base.</p> <p>Cor. is located 1 lk. W. of a fence cor. fences extend N., E. and W. and 45 lks. N. of a track road, bears SE and W.</p> <p>N. 0°50' W., bet. secs. 31 and 36.</p> <p>Over gently rolling land, through scattered juniper along a fence line.</p>
40.57	<p>Point for the 1/4 sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
80.99	<p>Point for the cor. of secs. 25, 30, 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p>

Dependent Resurvey of a Portion of the E. Bdy.,
T. 14 N., R. 21 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E R22E <u>S25 S30</u> <u>S36 S31</u> 1979</p> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 13 lks. W. of fence line, bears S. and N. 3° W.</p>
40.62	<p>N. 0°50' W., bet. secs. 25 and 30.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 30, at proportionate dist., there is no remaining evidence of the original cor., not monumented.</p>
81.06	<p>The cor. of secs. 19, 24, 25 and 30, monumented with a 1 1/4 in. open end pipe 24 ins. long, projecting 8 ins. above the ground in a scattered mound of stone. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E R22E <u>S24 S19</u> <u>S25 S30</u> 1979</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears S. 31° W., 141.5 lks. dist., mkd. X BT at base.</p> <p>Deposit the iron pipe inside the iron post.</p> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 1 1/2 ft. base, 1 ft. high, W. of the cor.</p> <p>Cor. is located 352 lks. W. of a fence cor., fences extend N., E and W., cor. is also located 352 lks. E. of a fence cor., fences extend E., S. and W.</p>
40.22	<p>N. 0°51' W., bet. secs. 19 and 24.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>The 1/4 sec. cor. of secs. 19 and 24, monumented with a 3/4 in. open end pipe, projecting 6 ins. above the ground, with a scattered mound of stone N. of cor.</p>

Dependent Resurvey of a Portion of the E. Bdy.,
T. 14 N., R. 21 E., Gila and Salt River Mer., Arizona

CHAINS

Cor. is located 20 lks. E. of a N. and S. abandoned fence line and 20 lks. S. of a abandoned E. and W. road. This position is harmoniously related to existing original cors., and is accepted as the best available evidence of the original corner position, not remonumented.

N. 0°50' W., beginning new measurement.

40.19 The cor. of secs. 13, 18, 19 and 24, monumented with a sandstone, 32 x 16 x 6 ins. in a mound of stone, 2 ft. base, 1 ft. high on a solid base of rock, mkd. with 3 grooves on N. and 3 grooves on S., with a 1/4 in. rebar set alongside, from which an original bearing tree

A juniper, 8 ins. diam., bears N. 20° W.,
31 lks. dist., mkd. TXVIIIN RXXIE SXIII.
(Record N. 48° W., 20 lks. dist.)

At the cor. point

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole in bedrock, with top mkd.

T14N
R21E R22E
S13|S18
S24|S19
1979

from which

A juniper, 8 ins. diam., bears N. 64° E.,
78.5 lks. dist., mkd. T14N R22E S18 BT.

A sandstone outcropping 5 x 3 1/2 x 1 ft. above ground, bears S. 24° E., 53.5 lks. dist., mkd. X B0.

Raise a mound of stone, 3 1/2 ft. base, 3 1/2 ft. high W. of the cor.

Bury the original stone and rebar in the mound of stone.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

(Restoring the 1883 survey by Henry Meyrick)

From the cor. of secs. 25, 26, 35 and 36, monumented with a sandstone, 24 x 16 x 3 ins., projecting 20 ins. above the ground in a scattered mound of stone, mkd. with a faint cross on top.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T14N R21E
S26|S25
S35|S36
1979

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
40.06	<p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 218 lks. N. of an E. and W. fence line.</p> <p>N. 2°18' W., bet. secs. 25 and 26.</p> <p>Over gently rolling land, through railed juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S26 S25 1979</p>
80.12	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of the cor.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S23 S24 S26 S25 1979</p>
39.47	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>From this point a 3/8 in. reinforcement rod, bears S. 72°44' E., 166.7 lks. dist., projecting 3 ins. above the ground in a mound of stone, 1 1/2 ft. base, origin unknown.</p> <hr/> <p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., heretofore described.</p> <p>S. 86°09' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
78.95	<p>The cor. of secs. 23, 24, 25 and 26.</p>
40.06	<p>N. 2°20' E., bet. secs. 23 and 24.</p> <p>Over rolling land, through scattered juniper.</p> <p>The 1/4 sec. cor. of secs. 23 and 24, monumented with a sandstone, 10 x 8 x 3 ins., loosely set in a mound of stone, 2 ft. base, 1 ft. high, no marks visible.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

	CHAINS		
		<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S23 S24 1979</p> <p>Deposit the stone alongside the iron post.</p> <p>Deposit broken glass at base, of iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 3°35' W., beginning new measurement.</p>	
40.70		<p>Point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S14 S13 S23 S24 1979</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of the cor.</p> <p>From this point a 3/4 in. reinforcement rod, bears S. 69°47' E., 209.7 lks. dist., projecting 10 ins. above the ground in a mound of stone 1 1/2 ft. base, origin unknown.</p>	
		<p>From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of Tp., heretofore described.</p> <p>S. 86°19' W., bet. secs. 13 and 24.</p> <p>Over gently rolling land, through light juniper timber.</p>	
39.32		<p>Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>	
78.65		<p>The cor. of secs. 13, 14, 23 and 24.</p>	
		<p>N. 0°09' W., bet. secs. 13 and 14.</p> <p>Over gently rolling land, through widely scattered juniper.</p>	
40.62		<p>Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
81.24	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S14 S13 1979</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>The cor. of secs. 11, 12, 13 and 14, monumented with the remains of a 4 x 4 ins. wooden post, 36 ins. long, lying loose in a scattered mound of stone, no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S11 S12 S14 S13 1979</p> <p>Deposit the wooden post alongside and broken glass at base of the iron post.</p>	
40.36	<p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S34 S35 S 3 S 2 1920</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 9 ins. diam., bears N. 25 3/4° W., 318 lks. dist., mkd. T14N R21E S34 BT.</p> <p>A fence cor., bears N. 41° E., 62 lks. dist., fences extend N. and E.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T14N R21E S34 S35 S 3 S 2 T13N R21E 1979 1920</p> <p>N. 0°13' W., bet. secs. 34 and 35.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S34 S35 1979</p> <p>Set a juniper post, 3 ins. diam., 6 ft. long, alongside the iron post.</p> <p>Cor. is located 30 lks. W. of a N. and S. track road.</p> <p>From this point a $\frac{3}{4}$ in. reinforcement rod, bears S. $89^{\circ}18'$ E., 16.3 lks. dist., projecting 3 ins. above the ground, with steel fence post alongside.</p>	
80.72	<p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 15 ins. long, 2 $\frac{1}{2}$ ins. diam., 10 ins. below surface of a N. and S. graded gravel road, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S27 S26 S34 S35 1979</p> <p>Deposit broken glass at base of iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45° E., 75.8 lks. dist., mkd. T14N R21E RM 50 FT. S26 1979 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 $\frac{1}{2}$ ins. diam., set 21 ins. in the ground for a reference monument, bears S. 45° W., 113.6 lks. dist., mkd. T14N R21E RM 75 FT. S34 1979 and an arrow pointing to the cor.</p> <p>A fence cor., bears S. 28° W., 82.5 lks. dist., fences extend N. and W.</p> <p>From this point a local cor., bears N. $86^{\circ}43'$ E., 33.3 lks. dist., monumented with a $\frac{5}{8}$ in. reinforcement rod, projecting 2 ins. above the ground, with aluminum cap attached and mkd. 5047. Steel fence post alongside. This cor. was established by improper procedure and is unacceptable.</p>	
16.50	<p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>S. $89^{\circ}02'$ W., bet. secs. 26 and 35.</p> <p>Over rolling land, through medium juniper.</p> <p>Highway No. 77, bears S. 5° E. and N. 5° W.</p>	
40.88	<p>The $\frac{1}{4}$ sec. cor. of secs. 26 and 35, monumented with a sandstone, 22 x 10 x 8 ins., projecting 21 ins. above the ground in a mound of stone, 2 $\frac{1}{2}$ ft. base, 1 ft. high, mkd. $\frac{1}{4}$ on the N. face.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., over a cross chisled in bedrock, mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E $\frac{1}{4}$ $\frac{S26}{S35}$ 1979</p> <p>Deposit the mkd. stone in the mound of stone.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 88°41' W. beginning new measurement.</p>	
39.81	<p>The cor. of secs. 26, 27, 34 and 35.</p>	
	<p>N. 1°16' W., bet. secs. 26 and 27.</p> <p>Over gently rolling land, through railed area.</p>	
40.36	<p>Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E $\frac{1}{4}$ S27 S26 1979</p> <p>Deposit broken glass at base of iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is located 43.5 lks. W. of a N. and S. fence line and 69 lks. W. of a N. and S. track road.</p>	
80.72	<p>Point for the cor. of secs. 22, 23, 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S22 S23 S27 S26 1979</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 190 lks. S. of a track road, bears SE and NW.</p> <p>From this point a local cor. bears S. 88°14' E., 123.3 lks. dist., monumented with a 5/8 in. reinforcement rod, projecting 5 ins. above the ground, with aluminum cap attached and mkd. 5047. This cor. was established by improper procedure and is unacceptable.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	From the cor. of secs. 23, 24, 25 and 26.	
	N. 89°21' W., bet. secs. 23 and 26.	
	Over gently rolling land, through railed juniper.	
25.30	Highway No. 77, bears S. 7° E. and N. 7° W.	
39.62	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T14N R21E $\frac{1}{4}$ $\frac{S23}{S26}$ 1979	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of the cor.	
	Cor. is located 120 lks. W. of a N. and S. track road.	
79.25	The cor. of secs. 22, 23, 26 and 27.	
	N. 0°05' W., bet. secs. 22 and 23.	
	Over rolling land, through railed juniper.	
40.36	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor. This point falls in a wash, where it is impracticable to monument.	
40.56	Point selected for the witness cor. to the 1/4 sec. cor. of secs. 22 and 23.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	W C T14N R21E $\frac{1}{4}$ S22 S23 ↓ 1979	
	from which	
	A juniper, 12 ins. diam., bears N. 71° E., 161 lks. dist., mkd. X BT at base.	
	A juniper, 6 ins. diam., bears S. 88° W., 186 lks. dist., mkd. X BT at base.	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.	
	Cor. is located on the N. edge of a wash, 20 lks. wide, 3 ft. deep, drains N. 70° E.	
57.10	Fence line, bears N. 80° E. and S. 80° W.	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
80.72	<p>The cor. of secs. 14, 15, 22 and 23, monumented with a sandstone, 20 x 18 x 4 ins., loosely set, mkd. with 3 grooves on S. face and 2 grooves on E. face, with a wooden post, 4 x 9 x 36 ins. long, lying loose alongside the stone and a steel fence post set alongside.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S15 S14 S22 S23 1979</p> <p>Deposit the mkd. stone and wooden post alongside the iron post.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p>
38.20	<p>From the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°18' W., bet. secs. 14 and 23.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>Highway No. 77, bears S. 6° E. and N. 6° W.</p>
39.22	<p>Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S14 S23 1979</p> <p>Cor. is located in a fence line, bears S. 6° E. and N. 6° W.</p>
78.44	<p>The cor. of secs. 14, 15, 22 and 23.</p> <p>N. 0°58' W., bet. secs. 14 and 15.</p> <p>Over rolling land, through railed juniper.</p>
40.10	<p>Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S15 S14 1979</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>from which</p> <p>A well casing, 8 ins. diam., projecting 12 ins. above the ground, bears N. 46° W., 147 lks. dist.</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>From this point a local cor., bears S. 88°59' E., 33.7 lks. dist., monumented with a 5/8 in. reinforcement rod set flush with ground, with aluminum cap attached and mkd. 5047. Steel fence post projecting 3 ft. above the ground alongside the local cor. This cor. was established by improper procedure and is unacceptable.</p> <p>80.20 Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S10 S11 S15 S14 1979</p> <p>Cor. is located 22 lks. N. of an E. and W. gravel road.</p> <p>From this point a local cor., bears S. 88°42' E., 57.4 lks. dist., monumented with a 5/8 in. reinforcement rod set flush with ground in mound of stone, 1 1/2 ft. base, 6 ins. high, with aluminum cap attached and mkd. 5047. Steel fence post projecting 3 ft. above the ground alongside the local cor. This cor. was established by improper procedure and is unacceptable.</p>
	<p>From the cor. of secs. 11, 12, 13 and 14.</p> <p>S. 89°56' W., bet. secs. 11 and 14.</p> <p>Over rolling land, through medium juniper.</p> <p>39.78 Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S11 S14 1979</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N. of the cor.</p>
	<p>51.10 Highway No. 77, bears S. 7° E. and N. 7° W.</p>
	<p>79.56 The cor. of secs. 10, 11, 14 and 15.</p> <hr/> <p>N. 0°34' E., bet. secs. 10 and 11.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	Over rolling land, through scattered juniper.
40.09	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S10 S11 1979</p>
80.18	The cor. of secs. 2, 3, 10 and 11, monumented with a sandstone, 21 x 12 x 5 ins., set in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. with 4 grooves on S. face, 1 groove on E. face and a cross on top.
	At the cor. point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., over a cross chiseled in bedrock, mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T14N R21E <u>S 3 S 2</u> S10 S11 1979</p>
	Deposit the mkd. stone in the mound of stone.
	From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of Tp., monumented with an iron post, 2 ins. diam., projecting 16 ins. above the ground, with brass cap mkd.
	<p style="text-align: center;">T14N R21E <u>S33 S34</u> S 4 S 3 T13N 1920</p>
	from which
	A juniper stump, 10 ins. diam., bears N. 55° E., 246 lks. dist., no marks visible.
	A juniper stump, 10 ins. diam., bears S. 66° E., 292 lks. dist., no marks visible.
	A juniper snag, 8 ins. diam., bears S. 42° W., 298 lks. dist., marks visible 3N R21.
	A juniper, 10 ins. diam., bears N. 43 3/4° W., 535 lks. dist., mkd. T14N R21 S.
	Cor. is located 3 lks. N. of a fence cor., fences extend S. and W.
	From this point triangulation station First Knoll, bears S. 60°49' W., 15.465 chs. dist., monumented with a brass tablet, mkd. First Knoll 1932, set in a sandstone out cropping.
	N. 0°20' W., bet. secs. 33 and 34.

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>Over gently rolling land, through scattered juniper.</p> <p>40.56 Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S33 S34 1979</p>	
	<p>81.12 Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S28 S27 S33 S34 1979</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point a local cor., bears N. 89°23' E., 27.8 lks. dist., monumented with a 3/8 in. reinforcement rod projecting 4 ins. above the ground, with aluminum cap attached and mkd. 5047. This cor. was established by improper procedure and is unacceptable.</p>	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°54' W., bet. secs. 27 and 34.</p> <p>Through S. edge of a pig farm.</p> <p>40.15 Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1 S27 4 S34 1979</p> <p>from which</p> <p style="text-align: center;">A juniper, 11 ins. diam., bears S. 31 1/2° E., 313.5 lks. dist., mkd. 1/4 S34 BT.</p> <p>Deposit broken glass at base of iron post.</p> <p>Cor. is located 59 lks. W. of a fence cor., fences extend N., W. and S. 117.5 lks., thence E.</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>From this point a local cor., bears S. 89°27' E., 31 lks. dist., monumented with a 5/8 in. reinforcement rod projecting 4 ins. above the ground, with aluminum cap attached and mkd. 5047. This cor. was established by improper procedure and is unacceptable.</p> <p>Continue measurement over gently rolling land, through railed juniper.</p>
80.30	<p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°29' W., bet. secs. 27 and 28.</p> <p>Over rolling land, through railed juniper.</p>
37.50	<p>Five mile draw, 50 lks. wide, drains NE, thence through medium juniper.</p>
40.56	<p>The 1/4 sec. cor. of secs. 27 and 28, monumented with a sandstone, 25 x 19 x 6 ins., loosely set in a scattered mound of stone, mkd. 1/4 on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 3 ins. in the ground over a cross chisled in bedrock in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S28 S27 1978</p> <p>Deposit the mkd. stone in the mound.</p> <hr/> <p>N. 0°18' W., beginning new measurement.</p>
40.18	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a sandstone, 52 x 28 x 6 ins., loosely set in a scattered mound of stone, mkd. with 3 notches on S. and 3 notches on E.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S21 S22 S28 S27 1978</p> <p>Deposit the mkd. stone in base of mound.</p> <p>Cor. is located 415 lks. N. of draw, 30 lks. wide, drains N. 55° E.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°56' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land, through railed juniper.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
17.30	Enter medium juniper.	
39.54	Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, in a drill hole in a sandstone out cropping, with top mkd.	
	$\begin{array}{r} T14N R21E \\ \frac{1}{4} \frac{S22}{S27} \\ 1979 \end{array}$	
	from which	
	An X BO on a sandstone out cropping, bears N. 64° E., 33.8 lks. dist.	
	An X BO on a sandstone out cropping, 5 x 3 x 1 1/2 ft., bears N. 46° W., 20.2 lks. dist.	
	Raise a mound of stone, 3 ft. base, 3 ft. high, NW of the cor., only place practical.	
	Cor. is located 100 lks. W. of a wash, drains N. 60° E.	
79.08	The cor. of secs. 21, 22, 27 and 28.	
	N. 0°33' W. bet. secs. 21 and 22.	
	Over gently rolling land, through railed juniper.	
34.30	Fence line, bears N. 85° E. and S. 85° W.	
40.18	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	$\begin{array}{r} T14N R21E \\ \frac{1}{4} \\ S21 S22 \\ 1979 \end{array}$	
	Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of the cor.	
80.36	The cor. of secs. 15, 16, 21 and 22, monumented with a sandstone, 30 x 18 x 4 ins., firmly set in a scattered mound of stone, mkd. with 3 notches on S. and 3 notches on E.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground in a mound of stone, 4 ft. base, to top, with brass cap mkd.	
	$\begin{array}{r} T14N R21E \\ S16 S15 \\ S21 S22 \\ 1978 \end{array}$	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>Deposit the mkd. stone in the mound.</p>	
	<p>Set a steel fence post alongside the cor.</p>	
	<hr/> <p>From the cor. of secs. 14, 15, 22 and 23.</p>	
	<p>S. 89°17' W., bet. secs. 15 and 22.</p>	
	<p>Over rolling land, through scattered juniper.</p>	
39.99	<p>The 1/4 sec. cor. of secs. 15 and 22, monumented with a sandstone, 17 x 14 x 3 ins., set in a mound of stone, 2 ft. base, 6 ins. high, illegible marks.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T14N R21E</p>	
	<p style="text-align: center;">$\frac{1}{4}$ S15</p>	
	<p style="text-align: center;">$\frac{1}{4}$ S22</p>	
	<p style="text-align: center;">1979</p>	
	<p>Deposit the stone alongside the iron post.</p>	
	<hr/> <p>N. 89°57' W., beginning new measurement.</p>	
39.76	<p>The cor. of secs. 15, 16, 21 and 22.</p>	
	<hr/> <p>From the cor. of secs. 10, 11, 14 and 15.</p>	
	<p>N. 89°42' W., bet. secs. 10 and 15.</p>	
	<p>Over gently rolling land, through scattered juniper, along N. side of gravel road.</p>	
39.71	<p>Point for the 1/4 sec. cor. of secs. 10 and 15, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T14N R21E</p>	
	<p style="text-align: center;">$\frac{1}{4}$ S10</p>	
	<p style="text-align: center;">$\frac{1}{4}$ S15</p>	
	<p style="text-align: center;">1979</p>	
	<p>Cor. is located 18 lks. N. of an E. and W. gravel road.</p>	
79.42	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a 3/8 in. reinforcement rod, 12 ins. long, projecting 3 ins. above the ground, with the remains of a wooden post, 4 x 4 x 36 ins. long alongside, no marks visible and a steel fence post alongside. This monument was set by Arizona Public Service Co. and is accepted as a careful and faithful perpetuation of the position of the original cor.</p>	
	<p>At the cor. point</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

	CHAINS		
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S 9 S10 S16 S15 1979</p> <p>Deposit the wooden post and reinforcement rod alongside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of the cor.</p>	
		<p>N. 0°10' E., bet. secs. 9 and 10.</p> <p>Over rolling land, through scattered juniper.</p>	
	40.01	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E $\frac{1}{4}$ S 9 S10 1979</p> <p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of the cor.</p>	
	80.02	<p>The cor. of secs. 3, 4, 9 and 10, monumented with a 3/8 in. reinforcement rod, 14 ins. long, projecting 4 ins. above the ground, with the remains of a wooden post, 4 x 4 x 32 ins. long alongside, no marks visible and a steel fence post alongside. This monument was set by Arizona Public Service Co. and is accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S 4 S 3 S 9 S10 1979</p> <p>Deposit the reinforcement rod and wooden post alongside the iron post.</p>	
		<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°49' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through scattered juniper.</p>	
	39.97	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S 3 $\frac{1}{4}$ S10 1979</p>
	<p>from which</p>
	<p style="text-align: center;">A juniper, 7 ins. diam., bears S. 47 1/2° E., 72.5 lks. dist., mkd. 1/4 S10 BT.</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of the cor.</p>
79.94	<p>The cor. of secs. 3, 4, 9 and 10.</p>
	<p>N. 1°50' W., bet. secs. 3 and 4.</p>
	<p>Over rolling land through scattered juniper.</p>
21.50	<p>High voltage power line, bears N. 87° E. and S. 87° W.</p>
22.60	<p>Track road, bears N. 87° E. and S. 87° W.</p>
23.50	<p>High voltage power line, bears N. 87° E. and S. 87° W., thence through medium juniper.</p>
39.48	<p>The 1/4 sec. cor. of secs. 3 and 4, monumented with a sandstone, 14 x 11 x 3 ins., projecting 11 ins. above the ground, mkd. 1/4 on W. face with a 3/8 in. reinforcement rod, 16 ins. long, projecting 10 ins. above ground alongside the cor. and a mound of stone, 3 ft. base, 1 1/2 ft. high N. of the cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 13 ins. in the ground in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S 4 S 3 1979</p>
	<p>Deposit the mkd. stone and reinforcement rod alongside the iron post.</p>
	<p style="text-align: center;">_____</p> <p>N. 4°18' W., beginning new measurement.</p>
39.40	<p>Fence line, bears E. and W.</p>
43.72	<p>The cor. of secs. 3, 4, 33 and 34 on the N. bdy. of Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 14 ins. above the ground in a mound of stone 2 1/2 ft. base, 1 ft. high, with a wooden post, 4 ins. diam., projecting 3 ft. above the ground alongside, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p style="text-align: center;">T15N R21E <u>S33 S34</u> S 4 S 3 T14N 1966</p> <hr/> <p>From the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of Tp., monumented with an iron post, 2 ins. diam., projecting 36 ins. above the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E <u>S32 S33</u> S 5 S 4 T13N 1920</p> <p>Cor. is located 2.5 lks. W. of a fence cor., fences extend N., E. and S. and 45 lks. W. of a N. and S. power line.</p> <p>N. 0°02' W., bet. secs. 32 and 33.</p> <p>Over gently rolling land, through scattered juniper along fence and power line.</p>	
40.50	Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
81.00	<p>The cor. of secs. 28, 29, 32 and 33, monumented with a 1/4 in. reinforcement rod 15 ins. long projecting 2 ins. above the ground, perpetuated in 1969 by the Arizona Public Service Co., and accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E <u>S29 S28</u> <u>S32 S33</u> 1979</p> <p>Deposit the reinforcement rod inside the iron post.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located in a N. and S. fence line and 45 lks. W. of a N. and S. power line.</p> <hr/> <p>From the cor. of secs. 27, 28, 33 and 34.</p> <p>S. 89°52' W., bet. secs. 28 and 33.</p> <p>Over rolling land, through scattered juniper.</p>	
40.03	Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor.	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4} \frac{S28}{S33}$ 1979</p>
80.06	<p>The cor. of secs. 28, 29, 32 and 33.</p>
	<p>N. 0°08' E., bet. secs. 28 and 29.</p>
	<p>Over gently rolling land, through scattered juniper, along a N. and S. fence and power line.</p>
41.15	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist., found the remains of a wooden post, 4 x 4 x 36 ins. long, lying loose.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S29 S28 1979</p>
	<p>Deposit the remains of wooden post alongside iron post.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of the cor.</p>
	<p>Cor. is located 2 lks. W. of a N. and S. fence line and 43 lks. W. of a N. and S. power line.</p>
	<p>From this point a sandstone, 12 x 10 x 4 ins., bears N. 2°05' E., 121 lks. dist., mkd. SW cor. SW 1/4 NW 1/4, origin unknown.</p>
82.30	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a 1 in. open end pipe, 30 ins. long projecting 10 ins. above the ground in a scattered mound of stone, perpetuated in 1969 by the Arizona Public Service Co., and accepted as a careful and faithful perpetuation of the position of the original cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{S20 S21}{S29 S28}$ 1979</p>
	<p>Deposit the open end pipe inside the iron post.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>Cor. is located 3 lks. N. of a fence cor., fences extend N., N. 75° E. and W.; 15 lks. S. of a track road, bears irregularly E. and W. and 45 lks. W. of a N. and S. power line.</p>	
39.66	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 89°01' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 21 and 28, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., on bedrock in a mound of stone, 4 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E $\frac{1}{4}$ $\frac{S21}{S28}$ 1979</p>	
79.31	<p>The cor. of secs. 20, 21, 28 and 29.</p> <p>N. 0°54' W., bet. secs. 20 and 21.</p> <p>Over rolling land, through scattered juniper along a power line.</p>	
40.41	<p>Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E $\frac{1}{4}$ S20 S21 1979</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 45 lks. W. of a N. and S. power line.</p>	
80.82	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a 3/4 in. open end pipe, 24 ins. long, projecting 6 ins. above the ground in a scattered mound of stone, perpetuated in 1969 by the Arizona Public Service Co., and accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E $\frac{S17 S16}{S20 S21}$ 1979</p>	

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>Deposit the open end pipe inside the iron post.</p> <p>Rebuild the mound of stone, 2 1/2 ft. base, 1 ft. high, W. of the cor.</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 45 lks. W. of a N. and S. power line.</p>
<p>39.90</p> <p>79.80</p>	<p>From the cor. of secs. 15, 16, 21 and 22.</p> <p>N. 88°42' W., bet. secs. 16 and 21.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>The cor. of secs. 16, 17, 20 and 21.</p>
<p>40.31</p> <p>80.62</p>	<p>N. 1°09' W., bet. secs. 16 and 17.</p> <p>Over rolling land, through scattered juniper along a power line.</p> <p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>The cor. of secs. 8, 9, 16 and 17, monumented with a 1 in. open end pipe, 30 ins. long projecting 10 ins. above the ground in a scattered mound of stone, perpetuated in 1969 by the Arizona Public Service Co., and accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;"> T14N R21E S 8 S 9 S17 S16 1979 </p> <p>Deposit the open end pipe alongside the iron post.</p> <p>Set a steel fence post alongside the iron post.</p> <p>Cor. is located 18 lks. W. of a track road, bears S. 10° E. and N. 10° W. and 45 lks. W. of a N. and S. power line.</p>
<p>40.18</p>	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°01' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
80.36	The cor. of secs. 8, 9, 16 and 17.
	<p>North, bet. secs. 8 and 9.</p> <p>Over rolling land, through scattered juniper.</p>
40.30	<p>Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S 8 S 9 1979</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>
80.60	<p>The cor. of secs. 4, 5, 8 and 9, monumented with a 3/4 in. reinforcement rod, 15 ins. long, projecting 3 ins. above the ground in a scattered mound of stone, with a steel fence post alongside, perpetuated in 1969 by the Arizona Public Service Co., and accepted as a careful and faithful perpetuation of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S 5 S 4 S 8 S 9 1979</p>
40.30	<p>Deposit the reinforcement rod alongside the iron post.</p> <p>Rebuild mound of stone, 2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 46 lks. W. of a power line, bears N. 5° E. and S. 5° W.</p> <hr/> <p>From the cor. of secs. 3, 4, 9 and 10.</p> <p>N. 88°37' W., bet. secs. 4 and 9.</p> <p>Over rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p style="text-align: center;">T14N R21E $\frac{1}{4} \frac{S}{S} \frac{4}{9}$ 1979</p>
80.60	<p>The cor. of secs. 4, 5, 8 and 9.</p>
	<p>N. 2°09' W., bet. secs. 4 and 5.</p>
	<p>Over rolling land, through scattered juniper.</p>
21.50	<p>High voltage power line, bears E. and W.</p>
22.40	<p>Track road, bears E. and W.</p>
23.30	<p>High voltage power line, bears E. and W.</p>
40.32	<p>Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S 5 S 4 1979</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p>
	<p>Cor. is located 380 lks. W. of a power line, bears N. 5° E. and S. 5° W.</p>
78.50	<p>Fence line, bears E. and W.</p>
80.44	<p>The cor. of secs. 4, 5, 32 and 33 on the N. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T15N R21E $\frac{S32}{S} \frac{S33}{S} \frac{4}{5}$ T14N 1969</p>
	<p>From the cor. of secs. 5, 6, 31 and 32 on the S. bdy. of Tp., monumented with an iron post, 2 ins. diam., projecting 18 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{S31}{S} \frac{S32}{S} \frac{5}{5}$ T13N 1920</p>
	<p>N. 0°33' E., bet. secs. 31 and 32.</p>
	<p>Over rolling land, through medium juniper.</p>
40.50	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
81.00	Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
	<p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°57' W., bet. secs. 29 and 32.</p> <p>Over rolling land, through scattered juniper.</p>
39.91	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
44.80	Apache railroad, bears S. 12° E. and N. 12° W.
79.83	The point for the cor. of secs. 29, 30, 31 and 32.
	<p>S. 89°16' W., bet. secs. 30 and 31.</p> <p>Over rolling land, through scattered juniper.</p>
39.86	Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
79.42	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of the Tp., heretofore described.
	<p>From the point for the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°34' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through scattered juniper.</p>
40.50	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
81.00	<p>Point for the cor. of secs. 19, 20, 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S19 S20 S30 S29 1979</p> <p>Cor. is located 2 lks. S. of a fence line, bears W. and E. 73 lks. to a fence cor., fences extend N., E. and W.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°01' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through scattered juniper.</p>
40.42	Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S20 $\frac{1}{4}$ S29 1979</p>
	<p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of the cor.</p>
	<p>Cor. is located 20 lks. N. of an E. and W. fence line and 58 lks. S. of a track road, bears S. 75° E. curving E. and N. 75° W.</p>
50.30	<p>Apache railroad, bears N. and S.</p>
80.84	<p>The cor. of secs. 19, 20, 29 and 30.</p>
	<p>S. 89°09' W., bet. secs. 19 and 30.</p>
	<p>Over rolling land, through scattered juniper.</p>
40.28	<p>Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
79.61	<p>The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of the Tp. heretofore described.</p>
	<p>From the cor. of secs. 19, 20, 29 and 30.</p>
	<p>N. 0°42' W., bet. secs. 19 and 20.</p>
	<p>Over rolling land, through scattered juniper.</p>
40.50	<p>Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E $\frac{1}{4}$ S19 S20 1979</p>
	<p>Cor. is located 20 lks. W. of a N. and S. fence line.</p>
81.00	<p>Point for the cor. of secs. 17, 18, 19 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T14N R21E S18 S17 S19 S20 1979</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of the cor.</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS								
	<p>Fence cor., bears S. 49° E., 81 lks. dist., fences extend N., S. and W.</p> <p>Cor. is located in a track road, bears irregularly E. and W.</p> <p>From this point a local cor., bears N. 57°21' E., 77.7 lks. dist., monumented with a 3/8 in. reinforcement rod projecting 2 ins. above the ground, with aluminum cap attached and mkd. 5047. This cor. was established by improper procedure, and is unacceptable.</p>							
<p>37.00</p> <p>40.27</p>	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. 89°08' W., bet. secs. 17 and 20.</p> <p>Over rolling land, through scattered juniper.</p> <p>Apache railroad, bears N. 25° E. and S. 25° W.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R21E</p> <table style="margin-left: auto; margin-right: auto;"> <tr> <td style="padding: 0 5px;">1</td> <td style="padding: 0 5px;">S17</td> </tr> <tr> <td style="padding: 0 5px;">4</td> <td style="padding: 0 5px;">S20</td> </tr> <tr> <td colspan="2" style="padding: 0 5px;">1979</td> </tr> </table> </div> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of the cor..</p> <p>From this point a local cor., bears N. 55°45' E., 36.4 lks. dist.; monumented with a 3/8 in. reinforcement rod projecting 6 ins. above the ground, with aluminum cap attached and mkd. 5047. This cor. was established by improper procedure, and is unacceptable.</p>	1	S17	4	S20	1979		
1	S17							
4	S20							
1979								
<p>80.54</p> <p>40.31</p>	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>S. 88°58' W., bet. secs. 18 and 19.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 18 and 19, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>							
<p>79.51</p> <p>40.50</p>	<p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°49' W., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>							

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS		
81.00	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a 3/8 in. reinforcement rod, 16 ins. long, projecting 3 ins. above the ground, with aluminum cap attached and mkd. 5047, and a 4 x 4 ins. wooden post, 3 ft. long, lying loose alongside local cor., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R21E S 7 S 8 ----- S18 S17 1979</p> </div> <p>Deposit the reinforcement rod inside the iron post and the wooden post alongside.</p> <p>Cor. is located at a fence cor., fences extend E. and W., abandoned N. 3° E. and S. 3° W.; cor. is also located 162 lks. W. of a new fence cor., fences extend N., S. and W.</p>	
	<p>From the cor. of secs. 8, 9, 16 and 17.</p>	
	<p>S. 89°24' W., bet. secs. 8 and 17.</p>	
	<p>Over gently rolling land, through scattered juniper.</p>	
40.03	<p>The 1/4 sec. cor. of secs. 8 and 17, monumented with a 5/8 in. reinforcement rod, 16 ins. long, projecting 4 ins. above the ground, with aluminum cap attached and mkd. 5047, and a steel fence post alongside, re-established in 1970 by George Matkin, Registered Engineer, and accepted as a careful and faithful re-establishment of the position of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T14N R21E 1 S 8 4 S17 1979</p> </div> <p>Deposit the reinforcement rod inside the iron post.</p>	
	<p>S. 89°24' W., beginning new measurement.</p>	
31.20	<p>Apache railroad, bears S. 3° E. and N. 6° W.</p>	
40.03	<p>The cor. of secs. 7, 8, 17 and 18.</p>	
	<p>S. 89°33' W., bet. secs. 7 and 18.</p>	
	<p>Over gently rolling land, through scattered juniper.</p>	
40.34	<p>Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>	

Dependent Resurvey of a Portion of the Subdivisional
Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
79.42	The cor. of secs. 7, 12, 13 and 18 on the W. bdy. of Tp., heretofore described.
40.24	<p>From the cor. of secs. 7, 8, 17 and 18.</p> <p>N. 0°38' W., bet. secs. 7 and 8.</p> <p>Over gently rolling land, through scattered juniper.</p> <p>Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1/4 S 7 S 8 1979</p> <p>Set a juniper post alongside the iron post.</p> <p>Cor. is located 42 lks. W. of a N. and S. fence line.</p>
80.48	<p>Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E S 6 S 5 S 7 S 8 1979</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of the cor.</p> <p>Cor. is located 11 lks. W. of a N. and S. fence line.</p>
9.90	Track road, bears S. 10° E. and N. 10° W.
40.46	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R21E 1 S 5 4 S 8 1979</p>

Dependent Resurvey of a Portion of the Subdivisional Lines, T. 14 N., R. 21 E., Gila & Salt River Mer., Ariz.

CHAINS	
	Cor. is located 240 lks. S. of track road, bears E. and W.
77.70	Apache railroad, bears S. 7° E. and N. 7° W.
80.93	The cor. of secs. 5, 6, 7 and 8.
	S. 89°43' W., bet. secs. 6 and 7.
	Over gently rolling land, through scattered juniper.
40.41	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
78.98	The cor. of secs. 1, 6, 7 and 12 on the W. bdy. of the Tp., heretofore described.
	From the cor. of secs. 5, 6, 7 and 8.
	N. 0°49' W., bet. secs. 5 and 6.
	Over gently rolling open land.
24.50	High voltage power line, bears E. and W.
40.24	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
80.61	The cor. of secs. 5, 6, 31 and 32 on the N. bdy. of Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 24 ins. above the ground in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.
	<p style="text-align: center;">T15N R21E S31 S32 S 6 S 5 T14N 1966</p>
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The SE cor. of this Tp. is located 3 miles north of Snowflake, Arizona. The general elevation ranges from 5,500 to 5,850 feet above sea level. The soil is a shallow sandy loam.</p> <p>Silver Creek flows in a northerly direction through the east side of the Tp.</p> <p>Access is by way of Highway No. 77, which crosses the eastern portion of the township in a northerly direction. There are several unimproved or lightly gravelled roads throughout the township. The Apache railroad crosses the western portion of the township in a northerly direction.</p> <p>The vegetation consist of sage brush, creosote, cactus and juniper of which a major portion has been railed.</p> <p>There is no evidence of mining activity or minerals.</p>

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Technician
John J. Bulinski	Survey Aid
Bill Anderson	Survey Aid
Dan Simpson	Survey Aid
Bruce Babcock	Survey Aid
Duane Ferneau	Survey Aid

CERTIFICATE OF SURVEY

(I) (~~We~~), Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of November, 19 78, (I) (~~We~~) have resurveyed the 5th Guide Meridian East, through Township 14 North, between Ranges 20 and 21 East, and a portion of the east boundary and subdivisional lines, Township 14 North, Range 21 East,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), (~~us~~) and under (my) (~~our~~) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

February 4, 1980 (Date) Paul L. Reeves (Cadastral Surveyor)

(Date) (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT Denver, Colorado

The foregoing field notes of the resurvey of the 5th Guide Meridian East, through Township 14 North, between Ranges 20 and 21 East, and a portion of the east boundary and subdivisional lines, Township 14 North, Range 21 East,

executed by Paul L. Reeves, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

FEB 20 1980 (Date) [Signature] (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in T. 14 N., R. 21 E., G&SRM., is a true copy of the original field notes.

(Date) (Chief, Cadastral Survey Examination and Approval Staff)