

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

NORTH, SOUTH AND WEST BOUNDARIES

AND

SUBDIVISIONAL LINES

AND A

SURVEY OF SUBDIVISIONS IN SECTIONS

6, 8, 17, 18, 20, 21, 22, 27, 29 AND 30

OF

TOWNSHIP 4 SOUTH, RANGE 4 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

Paul L. REEVES

CADASTRAL SURVEYOR

Under special instructions dated JANUARY 6, 1978, approved JANUARY 9, 1978,

_____, which provided for the surveys included under U.S. Survey/Group
Number 601, and assignment instructions dated JANUARY 9, 1978.

Survey commenced JANUARY 10, 1978

Survey completed MARCH 15, 1978

PA

BOOK 5 112

INDEX DIAGRAM

Township 4 South, Range 4 West

10	9	9	8		
7	48	37	31	24	18
6	46	36	30	23	17
5	43	35	29	22	15
19	20	34	28	21	14
30	39	32	26	20	12
31	32	32	25	19	11
5	4	4	3	2	1

- Subdivision Sec. 6 page 49
- Subdivision Sec. 8 page 50
- Subdivision Sec. 17 page 51
- Subdivision Sec. 18 page 51
- Subdivision Sec. 20 page 52
- Subdivision Sec. 21 page 54
- Subdivision Sec. 22 page 55
- Subdivision Sec. 27 page 56
- Subdivision Sec. 29 page 57
- Subdivision Sec. 30 page 59

Township 4 South, Range 4 West,
Gila and Salt River Meridian, Arizona

CHAINS

The east boundary, the north boundary, a portion of the south and west boundaries and a portion of the subdivisional lines were surveyed by Solomon W. Foreman in 1871. A portion of the south boundary and a portion of the subdivisional lines were surveyed and a portion of the subdivisional lines were resurveyed by William M. Breakenridge in 1890. The east and north boundaries were resurveyed by Benjamin J. Kinsey and Karl L. Siebecker in 1930 and 31. A portion of the south and west boundaries and a portion of the subdivisional lines were surveyed, a portion of the south boundary and a portion of the subdivisional lines were resurveyed by Karl L. Siebecker in 1931. A portion of the south boundary was resurveyed by Ty White and Claude F. Warner in 1941-43. The east boundary was resurveyed by Horace M. Muscott in 1938.

The following field notes are those of the dependent resurvey of portions of the north, south and west boundaries and subdivisional lines and the survey of subdivisions in sections 6, 8, 17, 18, 20, 21, 22, 27, 29 and 30, Township 4 South, Range 4 West, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 601, Arizona, dated January 6, 1978.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of the township, as scaled from U.S. Geological Survey Quadrangle Map, "Cotton Center SE, Arizona," prepared in 1973 is as follows:

Latitude 33°01.7' N. Longitude 112°36.8' W.

The mean magnetic declination is 13°30' E.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona

(Restoring the 1871 survey by Solomon W. Foreman)

Beginning at the cor. of Tps. 4 and 5 S., Rs. 3 and 4 W., monumented with an iron post, 3 ins. diam., projecting 8 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of the S. Bdy.,
T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T4S R4W R3W <u>S36 S31</u> S 1 S 6 T5S 1938</p> <p>From which the 1938 bearing trees</p> <p style="padding-left: 40px;">An ironwood, 12 ins. diam., bears N. 13° E., 632 lks. dist., mkd. T4S R3W S31 BT.</p> <p style="padding-left: 40px;">An ironwood, 10 ins. diam., bears N. 74 1/2° W., 392 lks. dist., mkd. T4S R4W S36 BT.</p> <p>N. 89°56' W., bet. secs. 1 and 36.</p> <p>Over gently rolling land, through scattered palo verde, ironwood, mesquite, creosote and cacti.</p>	
39.71	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4S R4W 1/4 <u>S36</u> S 1 T5S 1978</p> <p>from which</p> <p style="padding-left: 40px;">An ironwood, 12 ins. diam., bears N. 31 1/2° E., 59 lks. dist., mkd. 1/4 S36 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 35 lks. S. of a wash, 20 lks. wide, 2 ft. deep, drains N. 80° W.</p>	
79.42	<p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Cor. point falls in the W. edge of a wash, 25 lks. wide, 3 ft. deep, drains NW, curving westerly, impracticable to monument.</p>	
.10	<p>N. 89°56' W., bet. secs. 2 and 35.</p> <p>Over gently rolling land, through scattered mesquite, palo verde, ironwood, creosote and cacti.</p> <p>Point selected for the witness cor. of secs. 1, 2, 35 and 36.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the S. Bdy.,
T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona

CHAINS		
	W C T4S R4W S35 S36 S 2 S 1 → T5S 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.	
14.50	Power line, bears N. 5° E. and S. 5° W.	
39.71	Point for the 1/4 sec. cor. of secs. 2 and 35, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T4S R4W 1/4 <u>S35</u> S 2 T5S 1978	
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.	
74.10	Fence line, bears N. 10° E. and S. 10° W.	
76.00	Highway No. 85, bears N. 10° E. and S. 10° W.	
77.20	Fence line, bears N. 10° E. and S. 10° W.	
79.42	Point for the cor. of secs. 2, 3, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T4S R4W S34 S35 S 3 S 2 T5S 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.	
	N. 89°56' W., bet. secs. 3 and 34.	
	Over gently rolling land, through scattered mesquite, palo verde, ironwood, creosote and cacti.	
31.70	Gila Bend Canal, flows S. 5° W., thence along a graded road between cultivated fields.	
39.71	Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
44.20	Power line, bears N. 20° E. and S. 20° W.	

Dependent Resurvey of a Portion of the S. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
79.42	<p>Point for the cor. of secs. 3, 4, 33 and 34, determined longitudinally by the center of Old Highway No. 80, bears N. and S. and latitudinally on line between found cors.</p> <p>Set a P.K. nail flush with surface of paved road.</p> <p>from which</p> <p style="padding-left: 40px;">A bench mark, bears S. 89° 47' W., 81 lks. dist., monumented with a brass tablet, 4 ins. diam., set in a concrete base 12 x 12 ins., mkd. U.S. Coast and Geodetic Survey E 361 1967.</p> <p style="padding-left: 40px;">An iron peg, 1 in. diam., bears S. 1°14' W., 42 lks. dist., set flush with surface of Old Highway No. 80.</p> <p>The cor. of secs. 3, 4, 33 and 34 is located at intersection of Old Highway No. 80, bears N. and S. and graded road, bears E. and W.</p>
	<p>N. 89°56' W., bet. secs. 4 and 33.</p> <p>Along a graded road, between cultivated fields.</p>
.80	<p>Power line, bears N. and S.</p>
40.35	<p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
57.00	<p>Graded road ends.</p>
57.20	<p>Fence line, bears N. and S., thence over river bottom land, through dense undergrowth.</p>
80.70	<p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
	<p>N. 89°56' W., bet. secs. 5 and 32.</p> <p>Over river bottom land, through dense undergrowth.</p>
40.35	<p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented. Leave dense undergrowth, bears N. and S., thence along track road between cultivated fields.</p>
80.70	<p>The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., 3 ins. below surface of E. and W. track road, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R4W S31 S32 S 6 S 5 T5S 1931</p>
	<p>Cor. is located 30 lks. N. of a concrete lined irrigation ditch, flows East.</p>

Dependent Resurvey of a Portion of the S. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	<p>(Restoring the 1931 resurvey by Karl L. Siebecker)</p> <hr/> <p>N. 89°43' W., bet. secs. 6 and 31.</p> <p>Along a track road, between cultivated fields.</p> <p>27.90 Intersection of track roads, extending E., S. 10° E. and N. 10° W., thence over rolling land, through medium undergrowth and scattered timber.</p> <p>39.91 The 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., projecting 24 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S31</u> S 6 1931</p> <p>from which</p> <p style="text-align: center;">A fallen ironwood, 12 ins. diam., bears S. 11 1/2° W., 164 lks. dist., mkd. 1/4 S6 BT.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T4S R4W 1/4 <u>S31</u> S 6 T5S 1978 1931</p> <p>From which a new bearing tree</p> <p style="text-align: center;">An ironwood, 16 ins. diam., bears S. 12° W., 163 lks. dist., mkd. 1/4 S6 BT.</p> <p>Cor. is located in N. and S. fence line.</p> <hr/> <p style="text-align: center;">Dependent Resurvey of a Portion of the W. Bdy., T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona</p> <hr/> <p style="text-align: center;">(Restoring the 1931 survey by Karl L. Siebecker)</p> <hr/> <p>From the cor. of secs. 18 and 19 only, monumented with an iron post, 2 ins. diam., projecting 24 ins. above the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S18 S19 1931</p> <p>from which</p> <p style="text-align: center;">A dead palo verde, 4 ins. diam., bears N. 73 3/4° E., 42 lks. dist., no marks visible.</p>

Dependent Resurvey of a Portion of the W. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
39.74	<p>A palo verde, 5 ins. diam., bears S. 72° E., 172 lks. dist., no marks visible.</p> <p>N. 0°15' E., along the W. bdy. of sec. 18.</p> <p>Over rugged mountainous land, through scattered palo verde and cacti.</p> <p>The 1/4 sec. cor. of sec. 18, monumented with an iron post, 1 in. diam., projecting 30 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;"> 1/4 S18 1931</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T4S 1/4 S18 R4W 1978 1931</p> <hr/> <p style="text-align: center;">(Restoring the 1871 survey by Solomon W. Foreman)</p> <hr/> <p>From the cor. of secs. 7 and 18, monumented with an iron post, 2 ins. diam., projecting 36 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S 7 S18 1931</p> <p>from which</p> <p style="margin-left: 40px;">An XBO on W. face of cliff, bears S. 84 1/4° E., 54 lks. dist.</p> <p style="margin-left: 40px;">An XBO on NE face of a cliff, bears N. 89 1/4° W., 36 lks. dist.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T4S S 7 S18 R4W 1978 1931</p>	
39.93	<p>N. 0°01' E., along the W. bdy. sec. 7.</p> <p>Over rugged mountainous land, through scattered palo verde and cacti.</p> <p>Point for the 1/4 sec. cor. of sec. 7 only, at proportionate dist.; there is no remaining evidence of the original cor.</p>	

Dependent Resurvey of a Portion of the W. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

	CHAINS		
		<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T4S 1/4 S 7 R4W 1978</p> <p>Cor. is located 10 lks. N. of a draw, drains easterly curving northeasterly.</p>	
	79.86	<p>Point for the cor. of secs. 6 and 7 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S S 6 S 7 R4W 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located 15 lks. S. of a track road, bears E. and W.</p> <p>From this point, a re-bar of unknown origin, 3/8 in. diam., projecting 3 ins. above ground, bears N. 85°19' E., 108 lks. dist., encircled by a mound of stone, 3 ft. base, 8 ins. high.</p> <p>From this same point the NW cor. of a trailer house in place, 48.5 x 10 ft., bears S. 88°16' E., 4.215 chs. dist. long side bears E. and W.</p>	
		<p>N. 0°01' E., along the W. bdy. of sec. 6.</p> <p>Over rolling land, through medium palo verde, ironwood and creosote.</p>	
	20.055	<p>From this point on line, a re-bar of unknown origin, 3/8 in. diam., projecting 4 ins. above ground, bears East, 109.5 lks. dist., with a steel fence post alongside.</p>	
	39.93	<p>Point for the 1/4 sec. cor. of sec. 6 only, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S 1/4 S 6 R4W 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>	

Dependent Resurvey of a Portion of the W. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS

Cor. is located 70 lks. N. of a draw, drains E.

From this point a re-bar of unknown origin, 3/8 in. diam., projecting 4 ins. above ground, bears N. 87°01' E., 111.5 lks. dist., set in a mound of stone, 2 ft. base, 8 ins. high.

79.86

The cor. of Tps. 3 and 4 S., Rs. 4 and 5 W., monumented with an iron post, 3 ins. diam., projecting 9 ins. above the ground, in a mound of stone, 3 ft. base, to top and a mound of stone, 4 ft. base, 1 ft. high S., with brass cap mkd.

T3S
R5W|R4W
S36|S31
S 1 | S 6
T4S
1931

from which

An ironwood, 13 ins. diam., bears S. 37 3/4° E.,
183 lks. dist., mkd. T4S R4W S6 BT.

An ironwood, 20 ins. diam., bears S. 44 1/2° W.,
114 lks. dist., mkd. T4S R5W S1 BT.

An ironwood, 15 ins. diam., bears N. 38° W.,
110 lks. dist., mkd. T3S R5W S31 BT.
(Record T3S R5W S36).

Dependent Resurvey of a Portion of the N. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

(Restoring the 1930-31 resurvey by Benjamin J. Kinsey
and Karl L. Siebecker.)

From the 1/4 sec. cor. of secs. 3 and 34, monumented with an iron post, 1 in. diam., flush with surface of ground, with brass cap mkd.

1/4 S34
S 3
1931

from which

An ironwood, 10 ins. diam., bears N. 13° W.,
334 lks. dist., mkd. T3S R4W S34 BT. (Record
330 lks.)

Cor. is located 15 lks. N. of an E. and W. track road and
42 lks. N. of an E. and W. power line.

Remark the brass cap to read

T3S R4W
1/4 S34
S 3
T4S
1978
1931

Dependent Resurvey of a Portion of the N. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
<p>39.80</p> <p>40.00</p>	<p>N. 89°33' W., bet. secs. 3 and 34.</p> <p>Over nearly level land, through medium mesquite along a track road.</p> <p>Track road ends.</p> <p>True point for the cor. of secs. 3, 4, 33 and 34, at proportionate dist., falls in the Gila Bend Canal where it cannot be monumented, canal flows S. 5° W., curving southerly.</p>
<p>2.90</p>	<p>N. 89°33' W., bet. secs. 4 and 33.</p> <p>Over nearly level land, through scattered mesquite.</p> <p>The witness cor. of secs. 3, 4, 33 and 34, monumented with an iron post, 2 ins. diam., projecting 14 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3S R4W</p> <p><u>S33 S34</u> WC</p> <p>S 4 S 3</p> <p>T4S</p> <p>1931</p> </div> <p>from which</p> <p style="padding-left: 40px;">A mesquite stump, 12 ins. diam., bears S. 69° W., 81 lks. dist., no marks visible.</p>
<p>2.10</p> <p>37.13</p> <p>77.16</p>	<p>N. 89°42' W., beginning new measurement.</p> <p>Old Highway No. 80, bears S. 15° E. and N. 15° W., thence over cultivated land.</p> <p>Point for the 1/4 sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <p>Point for the cor. of secs. 4, 5, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
<p>41.55</p>	<p>S. 89°21' W., bet. secs. 5 and 32.</p> <p>Over cultivated land.</p> <p>Point for the 1/4 sec. cor. of secs. 5 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T3S R4W</p> <p>1/4 <u>S32</u></p> <p>S 5</p> <p>T4S</p> <p>1978</p> </div> <p>Set a steel fence post alongside the cor.</p>

Dependent Resurvey of a Portion of the N. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
47.50	Fence line, bears S. 5° E. and N. 5° W.	
49.00	Enter river bottom land, through dense salt cedar, bears N. and S.	
81.00	Leave river bottom land.	
83.10	The cor. of secs. 5, 6, 31 and 32, monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.	
	<p style="text-align: center;">T3S R4W <u>S31 S32</u> S 6 S 5 T4S 1931</p>	
	Steel fence post alongside the cor.	
	From the 1/4 sec. cor. of secs. 6 and 31, monumented with an iron post, 1 in. diam., projecting 6 ins. above the ground, with brass cap mkd.	
	<p style="text-align: center;">1/4 <u>S31</u> S 6 1931</p>	
	from which	
	<p style="text-align: center;">A mesquite stump, bears S. 40 1/2° W., 58 lks. dist., no marks visible.</p>	
	<p style="text-align: center;">A stump hole, bears N. 62° E., 217 lks. dist.</p>	
	Steel fence post alongside the cor.	
	Cor. is located 20 lks. S. of an E. and W. track road and 37 lks. S. of an E. and W. fence line.	
	S. 89°49' W., bet. sec. 6 and 31.	
	Over gently rolling land, through medium mesquite, palo verde, ironwood and creosote, along a track road.	
12.40	Intersection of roads, extending East, S. 25° E. and N. 25° W.	
20.02	Point for the W 1/16 sec. cor. of secs. 6 and 31.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T3S R4W W 1/16 <u>S31</u> S 6 T4S 1978</p>	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	

Dependent Resurvey of a Portion of the N. Bdy.,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
38.89	The cor. of Tps. 3 and 4 S., Rs. 4 and 5 W., heretofore described.
	Dependent Resurvey of a Portion of Subdivisional Lines, T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona
	(Restoring the 1871 survey by Solomon W. Foreman)
	From the true point for the cor. of secs. 1, 2, 35 and 36 on the S. bdy. of the Tp., heretofore described.
	N. 0°19' W., bet. secs. 35 and 36.
	Over gently rolling land, through scattered mesquite, ironwood, palo verde and medium creosote.
40.01	Point for the 1/4 sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor. The cor. falls in a wash, 30 lks. wide, 3 ft. deep, drains S. 75° W., impracticable to monument.
40.61	Point selected for the witness 1/4 sec. cor. of secs. 35 and 36.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	W C T4S R4W 1/4 S35 S36 ↓ 1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
80.02	Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T4S R4W S26 S25 S35 S36 1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	Cor. is located on the N. edge of a small wash, drains S. 75° W.
	From the cor. of secs. 25, 30, 31 and 36 on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T4S R4W R3W <u>S30 S25</u> <u>S31 S36</u> 1938</p> <p>from which</p> <p>An ironwood, 10 ins. diam., bears N. 54 1/2° E., 399 lks. dist., mkd. T4S R3W S30 BT.</p> <p>An ironwood, 14 ins. diam., bears S. 21 1/2° E., 322 lks. dist., mkd. T4S R3W S31 BT. (Record 326 lks.)</p> <p>An ironwood, 12 ins. diam., bears S. 57° W., 434 lks. dist., mkd. T4S R4W S36 BT.</p> <p>An ironwood, 10 ins. diam., bears N. 1 1/4° W., 717 lks. dist., mkd. T4S R4W S25 BT. (Record 723 lks.)</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T4S R4W R3W <u>S25 S30</u> <u>S36 S31</u> 1978 1938</p> <p>N. 89°55' W., bet. secs. 25 and 36.</p> <p>Over gently rolling land, through scattered ironwood, palo verde and medium creosote.</p>	
39.63	<p>Point for the 1/4 sec. cor. of secs. 25 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S25</u> S36 1978</p>	
79.26	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>The cor. of secs. 25, 26, 35 and 36.</p> <hr/> <p>N. 0°39' W., bet. secs. 25 and 26.</p> <p>Over rolling land, through scattered ironwood, palo verde and medium creosote.</p>	
40.01	<p>Point for the 1/4 sec. cor. of secs. 25 and 26, at proportionate dist., there is no remaining evidence of the original cor.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S26 S25 1978</p>	
80.02	<p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 23, 24, 25 and 26, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S23 S24 S26 S25 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, W. of cor.</p>	
39.77	<p>From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W R3W S24 S19 S25 S30 1938</p> <p>from which</p> <p style="padding-left: 40px;">An ironwood, 14 ins. diam., bears N. 38 1/2° E., 381 lks. dist., mkd. T4S R3W S19 BT. (Record N. 35 1/2° E.)</p> <p style="padding-left: 40px;">An ironwood, 4 ins. diam., bears N. 7° W., 227 lks. dist., mkd. T4S R4W S24 BT. (Record N. 11° W.)</p> <p>Mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Cor. is located 255 lks. S. of a fence line, bears S. 80° E. and N. 80° W.</p> <p>N. 89°53' W., bet. secs. 24 and 25.</p> <p>Over rolling land, through scattered ironwood, palo verde and creosote.</p> <p>Point for the 1/4 sec. cor. of secs. 24 and 25, at proportionate dist.; there is no remaining evidence of the original cor.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4 <u>S24</u>
	S25
	1978
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.
79.55	The cor. of secs. 23, 24, 25 and 26.
	N. 0°31' W., bet. secs. 23 and 24.
	Over gently rolling land, through scattered ironwood, palo verde and medium creosote.
9.70	Fence line, bears S. 85° E. and N. 85° W.
40.01	Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4
	S23 S24
	1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
44.60	Track road, bears N. 80° E. and S. 80° W.
65.30	Track road, bears N. 70° E. and S. 70° W.
79.82	Point selected for the witness cor. of secs. 13, 14, 23 and 24.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	W C
	T4S R4W
	↑
	S14 S13
	S23 S24
	1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
80.02	True point for the cor. of secs. 13, 14, 23 and 24, at proportionate dist.; there is no remaining evidence of the original cor. The cor. falls on the S. edge of a wash, 50 lks. wide, 12 ft. deep, drains NW from East, impracticable to monument.
	From the cor. of secs. 13, 18, 19 and 24 on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	T4S R4W R3W S13 S18 S24 S19 1938	
	from which An ironwood, 10 ins. diam., bears N. 70° E., 318 lks. dist., mkd. T4S R3W S18 BT. (Record N. 67 1/2° E.) A palo verde, 6 ins. diam., bears S. 29° E., 207 lks. dist., bark scribed T4S R3W S19 BT. (Record S. 31° E.) An ironwood, 10 ins. diam., bears S. 35° W., 566 lks. dist., mkd. T4S R4W S24 BT. A fallen palo verde, 6 ins. diam., bears N. 88° W., 279 lks. dist., no marks visible. Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor. Add the marks 1978 to the brass cap. N. 89°53' W., bet. secs. 13 and 24. Over rolling land, through scattered ironwood, palo verde and medium creosote.	
39.83	Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T4S R4W 1/4 <u>S13</u> S24 1978	
79.66	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor. True point for the cor. of secs. 13, 14, 23 and 24.	
	N. 0°46' W., bet. secs. 13 and 14. Over rolling land, through scattered ironwood, palo verde and medium creosote.	
1.20	Wash, 20 lks. wide, 3 ft. deep, drains S. 75° W.	
35.90	Wash, 20 lks. wide, 3 ft. deep, drains S. 75° W.	
40.01	Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T4S R4W 1/4 S14 S13 1978</p>
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
80.02	Point for the cor. of secs. 11, 12, 13 and 14, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 in. diam, 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T4S R4W S11 S12 S14 S13 1978</p>
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
<hr/>	
From the cor. of secs. 7, 12, 13 and 18 on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.	
<p style="text-align: center;">T4S R4W R3W S12 S 7 S13 S18 1938</p>	
from which	
<p style="padding-left: 40px;">A fallen palo verde, 6 ins. diam., bears N. 28° E., 330 lks. dist., no marks visible. (Record N. 24 1/2° E., 333 lks.)</p>	
<p style="padding-left: 40px;">A palo verde, 8 ins. diam., bears S. 50° E., 231 lks. dist., bark scribed T4S R3W S18 BT. (Record S. 53 3/4° E.)</p>	
<p style="padding-left: 40px;">A palo verde, 7 ins. diam., bears S. 59° W., 257 lks. dist., bark scribed T4S R4W S13 BT. (Record 259 lks.)</p>	
<p style="padding-left: 40px;">An ironwood, 7 ins. diam., bears N. 44° W., 246 lks. dist., mkd. T4S R4W S12 BT.</p>	
N. 89°50' W., bet. secs. 12 and 13.	
Over rolling land, through scattered ironwood, palo verde and medium creosote.	
34.00	Wash, 100 lks. wide, 4 ft. deep, drains southerly.
40.06	Point for the 1/4 sec. cor. of secs. 12 and 13, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S12</u> S13 1978</p>	
80.12	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>The cor. of secs. 11, 12, 13 and 14.</p>	
40.01	<p>N. 0°19' W., bet. secs. 11 and 12.</p> <p>Over rolling land, through scattered ironwood, palo verde and medium creosote.</p> <p>Point for the 1/4 sec. cor. of secs. 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S11 S12 1978</p>	
80.02	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 1, 2, 11 and 12, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W <u>S 2 S 1</u> S11 S12 1978</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>From the cor. of secs. 1, 6, 7 and 12 on the E. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 14 ins. above the ground, in a mound of stone, 2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W R3W <u>S 1 S 6</u> S12 S 7 1938</p>	
	<p>Mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 89°47' W., bet. secs. 1 and 12.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	Over rolling land, through scattered ironwood, palo verde and medium creosote.
39.98	Point for the 1/4 sec. cor. of secs. 1 and 12, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4 <u>S 1</u>
	S12
	1978
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.
74.80	Wash, 100 lks. wide, 3 ft. deep, drains S. 35° W.
79.96	The cor. of secs. 1, 2, 11 and 12.
	N. 0°28' W., bet. secs. 1 and 2.
	Over rolling land, through scattered ironwood, palo verde and medium creosote.
40.01	Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4
	S 2 S 1
	1978
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
80.02	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 9 ins. above the ground, with brass cap mkd.
	T3S R4W
	<u>S35 S36</u>
	S 2 S 1
	T4S
	1931
	From which
	A palo verde, 8 ins. diam., bears N. 31 1/2° E., 160 lks. dist., mkd. with illegible bark scribing. (Record N. 28° E.)
	A palo verde, 9 ins. diam., bears S. 55° E., 180 lks. dist., bark scribed T4S R4W S1 BT.
	A palo verde, 15 ins. diam., bears S. 57° W., 185 lks. dist., bark scribed T4S R4W BT. (Record S. 60° W.)

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S. R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>An ironwood, 10 ins. diam., bears N. 75° W., 199 lks. dist., mkd. T3S R4W S35 BT.</p> <hr/> <p>From the cor. of secs. 2, 3, 34 and 35 on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°04' W., bet. secs. 34 and 35.</p> <p>Over gently rolling land, through scattered ironwood, palo verde and medium creosote.</p>	
40.22	<p>Point for the 1/4 sec. cor. of secs. 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S34 S35 1978</p>	
80.44	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Point for the cor. of secs. 26, 27, 34 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S27 S26 S34 S35 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 25, 26, 35 and 36.</p> <p>N. 89°38' W., bet. secs. 26 and 35.</p> <p>Over rolling land, through scattered ironwood, palo verde and medium creosote.</p>	
14.40	<p>Power line, bears N. 2° E. and S. 2° W.</p>	
39.53	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S26 S35 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
57.00	Fence line, bears N. 10° E. and S. 10° W.
58.90	Highway No. 85, bears N. 10° E. and S. 10° W.
60.10	Fence line, bears N. 10° E. and S. 10° W.
79.06	The cor. of secs. 26, 27, 34 and 35.
	N. 1°06' W., bet. secs. 26 and 27.
	Over gently rolling land, through scattered ironwood, palo verde and medium creosote.
40.22	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4
	S27 S26
	1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
80.44	The cor. of secs. 22, 23, 26 and 27, monumented with a wooden post, 3 ins. diam., 24 ins. long, in a mound of earth, with 4 faint pits.
	At the cor. point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T4S R4W
	S22 S23
	S27 S26
	1978
	Deposit the wooden post alongside the cor.
	Cor. is located 58 lks. E. of a N. and S. fence line.
	From the cor. of secs. 23, 24, 25 and 26.
	N. 89°20' W., bet. secs. 23 and 26.
	Over rolling land, through scattered ironwood, palo verde and medium creosote.
12.90	Power line, bears N. and S.
39.85	Point for the 1/4 sec. cor. of secs. 23 and 26, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S23</u> S26 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>	
57.00	Fence line, bears S. 5° E. and N. 5° W.	
58.40	Highway No. 85, bears S. 5° E. and N. 5° W.	
60.00	Fence line, bears S. 5° E. and N. 5° W.	
79.70	The cor. of secs. 22, 23, 26 and 27.	
	<hr/> <p>N. 0°19' W., bet. secs. 22 and 23.</p> <p>Over rolling land, through scattered ironwood, palo verde and medium creosote.</p>	
30.70	Fence line, bears S. 70° E. and N. 70° W.	
39.91	Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S22 S23 1978</p>	
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of cor.</p> <p>Cor. is located 30 lks. E. of an abandoned N. and S. fence line.</p>	
79.82	Point for the cor. of secs. 14, 15, 22 and 23, at proportionate dist.; there is no remaining evidence of the original cor.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S15 S14 S22 S23 1978</p>	
	<p>Set a steel fence post alongside cor.</p> <hr/> <p>From the true point for the cor. of secs. 13, 14, 23 and 24.</p> <p>N. 89°29' W., bet. secs. 14 and 23.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	Over rolling land, through scattered ironwood, palo verde and medium creosote.
12.00	Power line, bears N. 2° E. and S. 2° W.
39.71	Point for the 1/4 sec. cor. of secs. 14 and 23, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4 <u>S14</u>
	S23
	1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.
64.90	Fence line, bears S. 5° E. and N. 5° W.
66.40	Highway No. 85, bears S. 5° E. and N. 5° W.
67.90	Fence line, bears S. 5° E. and N. 5° W.
79.42	The cor. of secs. 14, 15, 22 and 23.
	N. 1°24' W., bet. secs. 14 and 15.
	Over gently rolling land, through scattered ironwood, palo verde and medium creosote.
39.92	Point for the 1/4 sec. cor. of secs. 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4
	S15 S14
	1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	From this point a 3/4 inch. reinforcement rod of unknown origin, projecting 1 inch above the ground, bears N. 89°E., 122.5 lks. dist.
79.84	Point for the cor. of secs. 10, 11, 14 and 15, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R4W
	S10 S11
	S15 S14
	1978

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, W. of cor.	
	From the cor. of secs. 11, 12, 13 and 14.	
	N. 89°37' W., bet. secs. 11 and 14.	
	Over rolling land, through scattered ironwood, palo verde and medium creosote.	
5.90	Track road, bears S. 20° E. and N. 20° W.	
10.80	Power line, bears S. 5° E. and N. 5° W.	
40.13	Point for the 1/4 sec. cor. of secs. 11 and 14, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T4S R4W 1/4 <u>S11</u> S14 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
71.70	Fence line, bears S. 5° E. and N. 5° W.	
72.50	Highway No. 85, bears S. 5° E. and N. 5° W.	
73.60	Fence line, bears S. 5° E. and N. 5° W.	
80.26	The cor. of secs. 10, 11, 14 and 15.	
	N. 0°24' E., bet. secs. 10 and 11.	
	Over rolling land, through medium creosote.	
39.91	Point for the 1/4 sec. cor. of secs. 10 and 11, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T4S R4W 1/4 S10 S11 1978	
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.	
	From this point a 3/4 in. reinforcement rod of unknown origin projecting 1/2 in. above ground, bears N. 30° W., 36.6 lks. dist.	
	Cor. is located 233 lks. W. of a fence line, bears S. 2° E. and N. 2° W. and 347 lks. W. of Highway No. 85, bears S. 2° E. and N. 2° W.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
79.82	<p>The cor. of secs. 2, 3, 10 and 11, monumented with an iron pipe, 1 1/4 ins. diam., in a hand hole 10 ins. diam., 18 lks. W. of center of Highway No. 85, bears N. 0°30' W., and S. 5° E. Accepted as the best available evidence of the original cor. position.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears N. 52°54' E., 266.4 lks. dist., with brass cap mkd. T4S R4W S2 RM 175.8 FT. 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 33°36' W., 193.9 lks. dist., with brass cap mkd. T4S R4W S2 RM 128 FT. 1978 and an arrow pointing to the cor.</p>
	<p>From the cor. of secs. 1, 2, 11 and 12.</p> <p>N. 89°45' W., bet. secs. 2 and 11.</p>
	<p>Over gently rolling land, through scattered ironwood, palo verde and medium creosote.</p>
10.30	<p>Power line, bears S. 5° E. and N. 5° W.</p>
33.10	<p>Track road, bears S. 20° E. and N. 20° W.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S 2</u> S11 1978</p>
	<p>Raise a mound of stone, 3 1/2 ft. base, 2 1/2 ft. high, N. of cor.</p>
80.04	<p>The cor. of secs. 2, 3, 10 and 11.</p>
	<p>N. 0°28' W., bet. secs. 2 and 3.</p> <p>Along Highway No. 85.</p>
39.97	<p>Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a railroad spike in center of Highway No. 85, bears S. 0°30' E. and N. 0°30' W., with railroad spike mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S 3 S 2 1978</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 55°25' E., 230.8 lks. dist., mkd. T4S R4W 1/4 S2 RM 152.3 FT. 1978 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears S. 55°25' W., 143.6 lks. dist., mkd. T4S R4W 1/4 S3 RM 94.8 FT. 1978 and an arrow pointing to the cor.</p>	
80.08	<p>The cor. of secs. 2, 3, 34 and 35, monumented with an iron post, 2 ins. diam., in a hand hole 10 ins. diam., in center of Highway No. 85, bears S. 0°30' E. and N. 0°30' W., with brass cap mkd.</p> <p style="text-align: center;">T3S R4W S34 S35 S 3 S 2 T4S 1931</p> <p>Add the marks 1978 to the brass cap</p> <p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 58°49' E., 211.7 lks. dist., mkd. T3S R4W S35 RM 139.7 FT. 1978 and an arrow pointing to the cor.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 42°53' E., 275.3 lks. dist., mkd. T4S R4W S2 RM 181.7 FT. 1978 and an arrow pointing to the cor.</p>	
	<p>From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the Tp., heretofore described.</p> <p>N. 0°04' W., bet. secs. 33 and 34.</p> <p>Along Old Highway No. 80, bet. cultivated fields.</p>	
40.20	<p>Point for the 1/4 sec. cor. of secs. 33 and 34, at proportionate dist; there is no remaining evidence of the original cor., not monumented.</p>	
80.40	<p>The cor. of secs. 27, 28, 33 and 34, monumented with an open end iron pipe 1 in. diam., flush with surface of Old Highway No. 80, this position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position, not remonumented.</p>	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>N. 89°58' W., bet. secs. 27 and 34.</p> <p>Over gently rolling land, through dense ironwood, palo verde and creosote.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

<p>CHAINS</p> <p>12.40</p> <p>13.40</p> <p>39.70</p> <p>59.555</p> <p>79.41</p> <p>39.78</p>	<p>Leave dense undergrowth, edge bears S. 10° E. and N. 10° W.</p> <p>Gila Bend Canal, flows S. 10° E.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S27</u> S34 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 60 lks. N. of a track road, bears E. and W.</p> <p>Point for the W 1/16 sec. cor. of secs. 27 and 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below surface of edge of cultivated field, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W W 1/16 <u>S27</u> S34 1978</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears N. 69 1/2° E., 170 lks. dist., mkd. T4S R4W W 1/16 S27 RM 112.2 FT. 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An X on a concrete lined irrigation ditch, bears S. 57° E., 118 lks. dist., ditch bears N. 2° E. and S. 2° W.</p> <p>Cor. is located 135 lks. N. 70° W., from a track road intersection, roads extend N., E., S. and W.</p> <p>The cor. of secs. 27, 28, 33 and 34.</p> <hr/> <p>N. 0°11' W., bet. secs. 27 and 28.</p> <p>Along Old Highway No. 80, bet. cultivated fields.</p> <p>Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
--	---

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

<p>CHAINS 79.56</p> <p>11.30</p> <p>39.05</p> <p>57.875</p>	<p>The cor. of secs. 21, 22, 27 and 28, monumented with a cotton picker spindle gear, flush with surface of center of Old Highway No. 80, bears N. and S. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position, not remonumented.</p> <p>From this point a bench mark, bears S. 32°23' W., 134.6 lks. dist., monumented with a brass tablet 4 ins. diam., set in a concrete base 12 x 12 ins., mkd. U.S. Coast and Geodetic Survey G361 1967.</p> <hr/> <p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>S. 89°25' W., bet. secs. 22 and 27.</p> <p>Over gently rolling land, through medium ironwood, palo verde and creosote.</p> <p>Gila Bend Canal, flows S. 10° E.</p> <p>Point for the 1/4 sec. cor. of secs. 22 and 27, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S22</u> S27 1978</p> <p>from which</p> <p style="text-align: center;">An ironwood, 15 ins. diam., bears N. 34° W., 174 lks. dist., mkd. 1/4 S22 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 185 lks. S. of a track road, bears N. 75° E. and S. 77° W. and 230 lks. N. of a power line, bears E. and W.</p> <p>Point selected for the witness W 1/16 sec. cor. of secs. 22 and 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T4S R4W W 1/16 ← <u>S22</u> S27 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 75 lks. N. of a track road, bears irregularly E. and W. and 145 lks. N. of a power line, bears E. and W.</p>	
---	--	--

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS 58.575	True point for the W 1/16 sec. cor. of secs. 22 and 27 falls in a wash, 25 lks. wide, 5 ft. deep, drains W. from NE, impracticable to monument.
78.10	The cor. of secs. 21, 22, 27 and 28.
	N. 1°32' W., bet. secs. 21 and 22. Along Old Highway No. 80 and power line.
40.13	Point for the 1/4 sec. cor. of secs. 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
80.26	Point for the cor. of secs. 15, 16, 21 and 22, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
	From the cor. of secs. 14, 15, 22 and 23. S. 89°24' W., bet. secs. 15 and 22. Over gently rolling land, through medium ironwood, palo verde and creosote.
5.20	Gila Bend Canal, flows S. 15° E.
39.78	The 1/4 sec. cor. of secs. 15 and 22, monumented with an iron post, 1 in. diam., projecting 12 ins. above the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd. 1/4 $\frac{S15}{S22}$ 1931 from which An ironwood, 15 ins. diam., bears S. 18 1/4° E., 489 lks. dist., mkd. 1/4 S22 BT. Add the marks T4S R4W 1978 to the brass cap. Cor. is located 99 lks. N. of power line, bears S. 85°E. and N. 85° W. N. 89°58' W., beginning new measurement.
19.995	Point for the W 1/16 sec. cor. of secs. 15 and 22. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T4S R4W W 1/16 $\frac{S15}{S22}$ 1978 Set a steel fence post alongside cor. Cor. is located 39 lks. N. of an E. and W. power line and 95 lks. W. of a N. and S. fence line.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
39.40	Old Highway No. 80, bears N. and S.
39.99	The point for the cor. of secs. 15, 16, 21 and 22.
	<p>N. 2°00' W., bet. secs. 15 and 16.</p> <p>Along Old Highway No. 80 and power line.</p>
40.14	Point for the 1/4 sec. cor. of secs. 15 and 16, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
80.28	<p>The cor. of secs. 9, 10, 15 and 16, monumented with a granite stone 15 x 12 x 8 ins., 30 ins. below surface of Pierpoint Road, mkd. with 2 notches on N., 3 notches on E., 4 notches on S and 3 notches on W. edges. Also found a decayed re-bar 3/4 in. diam., 20 ins. long under mkd. stone. This position is harmoniously related to identified original cors., and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below surface of road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R4W S 9 S10 S16 S15 1978</p> </div> <p>from which</p> <p>An X on a concrete abutment, bears S. 53° W., 37.5 lks. dist.</p> <p>A bench mark, bears S. 66 1/2° W., 78 lks. dist., mkd. U.S. Coast and Geodetic Survey J361 1967.</p> <p>An X on a concrete abutment, bears N. 52° W., 39.3 lks. dist.</p> <p>Cor. is located 46 lks. W. of intersection of roads, Old Highway No. 80, bears S. 2° E. and N. 5° W., Pierpoint Road extends west. Cor. is also located 24 lks. E. of a power line, bears S. 2° E. and N. 5° W.</p> <p>Deposit the mkd. stone and re-bar alongside the cor.</p> <p>NOTE: A thorough search was made for the cor. monument and 4 witness corners set in 1931, none of which could be found.</p>
40.05	<p>From the cor. of secs. 10, 11, 14 and 15.</p> <p>S. 89°03' W., bet. secs. 10 and 15.</p> <p>Over rolling land, through medium ironwood, palo verde and creosote.</p> <p>The 1/4 sec. cor. of secs. 10 and 15, monumented with the remains of a wooden stake, 3 ins. diam, 15 ins. long, from which an original bearing tree</p> <p>A dead ironwood, 16 ins. diam., bears N. 8° W., 86 lks. dist., no visible marks.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4S R4W 1/4 <u>S10</u> S15 1978</p>	
	<p>Deposit the wooden stake alongside cor.</p>	
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	
	<p>N. 89°00' W., beginning new measurement.</p>	
12.50	<p>Gila Bend Canal, flows S. 10° E.</p>	
40.55	<p>The cor. of secs. 9, 10, 15 and 16.</p>	
	<p>N. 0°19' E., bet. secs. 9 and 10.</p>	
	<p>Over gently rolling land, through scattered mesquite and medium creosote.</p>	
40.39	<p>Point for the 1/4 sec. cor. of secs. 9 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T4S R4W 1/4 S 9 S10 1978</p>	
	<p>Raise a mound of stone, 4 ft. base, 2 ft. high, W. of cor.</p>	
43.60	<p>Power line, bears E. and W.</p>	
80.78	<p>The cor. of secs. 3, 4, 9 and 10, determined at record course and distance from an original bearing tree</p>	
	<p style="padding-left: 40px;">An ironwood, 14 ins. diam., bears S. 61° E., 77 lks. dist., mkd. with illegible scribe marks.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. below surface of road borrow pit, with brass cap mkd.</p>	
	<p style="text-align: center;">T4S R4W S 4 S 3 S 9 S10 1978</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, for a reference monument, bears N. 68° E., 149.4 lks. dist., mkd. T4S R4W S3 RM 98.6 FT. 1978 and an arrow pointing to the cor.</p> <p>A power pole, bears S. 6° E., 79.5 lks. dist.</p> <p>Cor. is located 50 lks. E. of center of Old Highway No. 80, bears N. 4° E. curving northerly and S. 4° W. curving southerly.</p>	
	<p>From the cor. of secs. 2, 3, 10 and 11.</p> <p>N. 89°17' W., bet. secs. 3 and 10.</p> <p>Over rolling land, through medium ironwood, palo verde, mesquite and creosote.</p>	
1.00	Fence line, bears S. 5° E. and N. 5° W.	
39.96	<p>Point for the 1/4 sec. cor. of secs. 3 and 10, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S 3 S10 1978</p>	
64.00	<p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.</p> <p>Gila Bend Canal, flows S. 20° E.</p>	
79.92	The cor. of secs. 3, 4, 9 and 10.	
39.78	<p>N. 0°30' W., bet. secs. 3 and 4.</p> <p>Along Old Highway No. 80.</p> <p>Point for the 1/4 sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set a railroad spike flush with surface of Old Highway No. 80, mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S 4 S 3 1978</p>	
	<p>from which</p> <p>A power pole, bears N. 69° E., 65.8 lks. dist.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	<p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 56° E., 92.7 lks. dist., mkd. T4S R4W 1/4 S3 RM 61.2 FT. 1978 and an arrow pointing to the cor.</p>
	<p>Set a steel fence post alongside R.M.</p>
	<p>A power pole, bears N. 71° W., 82.3 lks. dist.</p>
	<p>Cor. is located 7 lks. E. of center of Old Highway No. 80, bears N. and S. and 80 lks. E. of a N. and S. power line.</p>
66.00	<p>Gila Bend Canal, flows S. 15° E. as scaled from U.S. Geological Survey Quadrangle Map, "Cotton Center, Ariz." prepared in 1973.</p>
79.56	<p>True point for the cor. of secs. 3, 4, 33 and 34, on the N bdy. of the Tp.</p>
40.02	<p>From the point for the cor. of secs. 4, 5, 32 and 33 on the S. bdy. of the Tp.</p>
	<p>N. 1°01' E., bet. secs. 32 and 33.</p>
	<p>Over river bottom land, through dense salt cedar.</p>
40.02	<p>Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
79.90	<p>Graded gravel road, bears E. and W.</p>
80.04	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
	<p>From this point a reinforcement rod of unknown origin, 3/4 in. diam., set 15 ins. below N. edge of graded gravel road, bears N. 83°10' E., 85 lks. dist.</p>
	<p>From the cor. of secs. 27, 28, 33 and 34.</p>
	<p>S. 89°48' W., bet. secs. 28 and 33.</p>
	<p>Along a graded gravel road.</p>
.80	<p>Power line, bears N. and S.</p>
39.58	<p>Point for the 1/4 sec. cor. of secs. 28 and 33, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
67.70	<p>Cattle guard in fence line, bears N. 5° E. and S. 5° W.</p>
79.17	<p>Point for the cor. of secs. 28, 29, 32 and 33.</p>
	<p>N. 3°20' W., bet. secs. 28 and 29.</p>
	<p>Over river bottom land, through dense salt cedar.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
40.08	Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist. falls in a slough, impracticable to monument; there is no remaining evidence of the original cor.	
40.68	<p>Point selected for the witness 1/4 sec. cor. of secs. 28 and 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T4S R4W 1/4 S29 S28 ↓ 1978</p> <p>Set a steel fence post alongside the cor.</p> <p>Cor. is located on a small dirt dike 8 ft. high, bears E. and W.</p>	
80.16	<p>Point for the cor. of secs. 20, 21, 28 and 29, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S20 S21 S29 S28 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 50 lks. W. of a cultivated field, bears N. and S.</p>	
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>N. 88°39' W., bet. secs. 21 and 28.</p> <p>Over level cultivated land.</p>	
43.57	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with an iron post, 1 in. diam., projecting 2 ins. above ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S21</u> S28 1931</p> <p>Add the marks T4S R4W 1978 to the brass cap.</p> <p>Cor. is located 9 lks. N. of a concrete lined canal, bears E. and W., also located under a N. and S. power line.</p> <p style="text-align: center;">S. 88°48' W., beginning new measurement.</p> <p>Over cultivated land.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
40.00	The cor. of secs. 20, 21, 28 and 29.
	N. 0°55' E., bet. secs. 20 and 21.
	Over cultivated land.
20.01	Point for the S 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. below cultivated field, with brass cap mkd.
	T4S R4W
	S 1/16
	S20 S21
	1978
	from which
	An X on a concreted lined irrigation ditch, bears
	N. 30° E. 101.3 lks. dist.
	An X on the same irrigation ditch, bears
	N. 3° W., 91.3 lks. dist.
	Cor. is located 160 lks. S. 65° E. of the cor. of field, bears E. and S.
20.90	Concrete lined irrigation ditch, bears E. and W., thence over nearly level open land.
40.02	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T4S R4W
	1/4
	S20 S21
	1978
	Set a steel fence post alongside cor.
40.80	Fence line, bears E. and W., thence over river bottom land, through medium salt cedar and scattered mesquite.
60.03	Point for the N 1/16 sec. cor. of secs. 20 and 21.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T4S R4W
	N 1/16
	S20 S21
	1978
	Set a steel fence post, alongside cor.
	Cor. is located 215 lks. E. of left bank of Gila River, bears N. 10° E. and S. 10° W.
80.04	Point for the cor. of secs. 16, 17, 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S17 S16 S20 S21 1978</p> <p>Set a steel fence post, alongside cor.</p>
	<hr/> <p>From the point for the cor. of secs. 15, 16, 21 and 22. S. 89°59' W., bet. secs. 16 and 21.</p> <p>Over cultivated land, along a track road.</p>
.17	Power line, bears S. 2° E. and N. 2° W.
40.05	Point for the 1/4 sec. cor. of secs. 16 and 21, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
49.50	Leave cultivated land.
50.00	Track road, bears N. 3° W. and S. 3° E., curving East.
51.00	Enter river bottom land, through dense undergrowth.
60.075	Point for the W 1/16 sec. cor. of secs. 16 and 21.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W W 1/16 S16 S21 1978</p> <p>Set a steel fence post alongside cor.</p>
61.70	Fence line, bears N. and S.
80.10	The cor. of secs. 16, 17, 20 and 21.
	<hr/> <p>N. 3°07' W., bet. secs. 16 and 17.</p> <p>Over river bottom land, through medium salt cedar and mesquite.</p>
40.07	Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S17 S16 1978</p> <p>Set a steel fence post alongside cor.</p>
79.73	Power line, bears E. and W.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
80.14	<p>The cor. of secs. 8, 9, 16 and 17, monumented with an iron pipe, 1 1/2 ins. diam., 36 ins. long, 4 ins. below center of surface of Pierpoint Road. This cor. was established by the Maricopa County Engineers and is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set a cut off iron post, 14 ins. long, 2 1/2 ins. diam., 12 ins. below surface of Pierpont Road, with brass cap mkd.</p> <div style="text-align: center;"> <p>T4S R4W S 8 S 9 S17 S16 1978</p> </div> <p>Reset the local cor. alongside iron post.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears S. 45° W., 75.8 lks. dist., mkd. T4S R4W S17 RM 50 FT. 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears N. 45° W., 75.8 lks. dist., mkd. T4S R4W S8 RM 50 FT. 1978 and an arrow pointing to the cor.</p> <p>Set a steel fence post alongside R.M.</p> <p>Cor. is located N. 65° W., 128 lks. dist. from a fence cor., fences extend N., E. and W.</p>	
	<p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>S. 89°52' W., bet. secs. 9 and 16.</p> <p>Along Pierpoint Road.</p>	
40.83	<p>The 1/4 sec. cor. of secs. 9 and 16, monumented with an iron pipe, 1 1/2 ins. diam., 4 ins. below Pierpoint Road. This cor. was established by the Maricopa County Engineers and is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position, not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°52' W., beginning new measurement.</p>	
40.82	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 0°15' E., bet. secs. 8 and 9.</p> <p>Over nearly level land, through medium salt cedar and mesquite.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
40.23	Point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T4S R4W 1/4 S 8 S 9 1978	
	Set a steel fence post alongside cor.	
40.40	Track road, bears E. and W., thence over cultivated land.	
80.46	Point for the cor. of secs. 4, 5, 8, and 9, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
	<hr/> From the cor. of secs. 3, 4, 9 and 10. S. 89°39' W., bet. secs. 4 and 9. Along a track road, bet. cultivated fields.	
1.10	Power line, bears N. 2° E. and S. 2° W.	
40.87	Point for the 1/4 sec. cor. of secs. 4 and 9, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
81.74	Point for the cor. secs. 4, 5, 8 and 9.	
	<hr/> N. 0°41' E., bet. secs. 4 and 5. Over cultivated land.	
40.24	Point for the 1/4 sec. cor. of secs. 4 and 5, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
80.48	Point for the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.	
	<hr/> From the point for the cor. of secs. 28, 29, 32 and 33. N. 89°58' W., bet. secs. 29 and 32. Along a graded gravel road.	
9.70	Gila River, 150 lks. wide, flows S. 35° W.	
39.61	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
	From this point a 1 in. open end pipe of unknown origin, 6 ins. below surface of N. edge of graded gravel road, bears N. 82°33' E., 38.6 lks. dist.	
79.22	The cor. of secs. 29, 30, 31 and 32, monumented with an iron post, 2 ins. diam., flush with ground, with brass cap mkd.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T4S R4W S30 S29 S31 S32 1931</p> <p>Railroad tie alongside cor.</p> <p>Cor. is located 25 lks. N. of E. and W. graded gravel road and 50 lks. N. of an E. and W. power line.</p> <hr/> <p style="text-align: center;">(Restoring the 1931 resurvey by Karl L. Siebecker)</p> <hr/> <p>N. 89°59' W., bet. secs. 30 and 31.</p> <p>Along N. edge of graded gravel road.</p>
10.80	Intersection of roads extending N. 30° E., E., S. 30° W. and N. 35° W. curving N.
11.24	Point for the 1/16 80 sec. cor. of sec. 30 only.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. below N. edge of road, with brass cap mkd.
	<p>T4S R4W 1/16 <u>S30</u> 80 1978</p>
	from which
	<p>A power pole, bears S. 29° W., 55.5 lks. dist.</p> <p>The SE. cor. of a wood frame building, 16 x 10 ft., bears S. 89 1/2° W., 344 lks. dist., long side bears N. 10° E. and S. 10° W.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground for a reference monument, bears N. 57° W., 119.8 lks. dist., mkd. T4S R4W 1/16 80 S30 79.1 FT. 1978 and an arrow pointing to the cor.</p>
	Set a steel fence post alongside R.M.
31.22	Point for the E 1/16 sec. cor. of sec. 30 only, not monumented.
39.92	The 1/4 sec. cor. of sec. 31 only, monumented with an iron post, 1 in. diam., projecting 15 ins. above the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.
	<p>1/4 _____ S31 1931</p>
	from which
	<p>An ironwood, 7 ins. diam., bears S. 34° E., 160 lks. dist., mkd. 1/4 S31 BT. (Record S. 36 3/4° E.)</p> <p>A palo verde, 6 ins. diam., bears S. 16° W., 127 lks. dist., mkd. 1/4 S31 BT. (Record S. 14 1/2° W., 125 lks. dist.)</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Cor. is located at a fence cor., fences extend E. and S.</p> <hr/> <p>S. 89°57' W., beginning new measurement.</p>	
11.28	<p>The 1/4 sec. cor. of sec. 30 only, monumented with an iron post, 1 in. diam., projecting 14 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">1/4 S30 1931</p> <p>from which</p> <p style="padding-left: 40px;">A dead palo verde, 8 ins. diam., bears N. 51° E., 123 lks. dist., no visible marks. (Record N. 52 3/4° E., 120 lks. dist.)</p> <p>Add the marks T4S R4W 1978 to the brass cap</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 3°51' W., bet. secs. 29 and 30.</p> <p>Over cultivated land.</p>	
13.20	<p>Leave cultivated land, bears N. 30° E. and S. 30° W., thence over rolling land, through scattered ironwood, palo verde and creosote.</p>	
20.065	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W S 1/16 S30 S29 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located 90 lks. N. of a fence cor.; fences extend N. 4° W. and S. 40° W.</p>	
40.13	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with an iron post, 1 in. diam., projecting 14 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">1/4 S30 S29 1931</p> <p>from which</p> <p style="padding-left: 40px;">An ironwood, 9 ins. diam., bears S. 68 3/4° E., 252 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">Stump hole, bears S. 8 1/2° W., 66 lks. dist. (Found bearing tree bulldozed out of position mkd. 1/4 S30 BT.)</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	<p>Cor. is located 2 lks. W. of fence cor., fences extend E. and S. 4° E.</p>
	<p style="text-align: center;">_____</p> <p>N. 3°52' W. beginning new measurement.</p>
20.035	<p>Point for the N 1/16 sec. cor. of secs. 29 and 30, not monumented.</p>
40.07	<p>The cor. of secs. 19, 20, 29 and 30, monumented with an iron post, 2 ins. diam., projecting 15 ins. above the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R4W S19 S20 S30 S29 1931</p>
	<p>from which</p> <p style="padding-left: 40px;">An ironwood, 12 ins. diam., bears N. 19° E., 182.5 lks. dist. mkd. T4S R4W S20 BT. (Record 204 lks. dist.)</p>
	<p>Mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
	<p style="text-align: center;">(Restoring the 1871 survey by Solomon W. Foreman)</p> <p style="text-align: center;">_____</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p>
	<p>S. 89°59' W., bet. secs. 20 and 29.</p>
	<p>Over river bottom land, through medium salt cedar and mesquite.</p>
38.50	<p>Leave river bottom land.</p>
39.60	<p>Track road, bears N. 20° E. and S. 20° W.</p>
39.99	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with a local iron pipe, 1 in. diam., projecting 2 ins. above the ground, in a mound of stone 3 ft. base, 1 ft. high. This is accepted as the best available evidence of the original cor. position.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R4W 1/4 S20 S29 1978</p>
	<p>Reset the local cor. alongside iron post.</p>
	<p>Rebuild the mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>From this point a 2 in. iron pipe, projecting 15 ins. above the ground, bears N. 4°17' E., 622 lks. dist., mkd. USCE PP12-6 J&G 1953, with mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>N. 89°56' W., beginning new measurement.</p> <p>Over mountainous land, through scattered ironwood, palo verde and medium creosote.</p>	
19.985	<p>The W 1/16 sec. cor. of secs. 20 and 29, monumented with an open end iron pipe, 1 in. diam., projecting 3 ins. above the ground, in a mound of stone, 4 ft. base, 1 ft. high.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground over the local cor., with brass cap mkd.</p> <p style="text-align: center;">T4S R4W W 1/16 <u>S20</u> S29 1978</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located on a steep N. slope.</p> <hr/> <p>N. 89°55' W., beginning new measurement.</p>	
19.975	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°59' W., bet. secs. 17 and 20.</p> <p>Over river bottom land, through medium salt cedar.</p>	
15.00	<p>Leave river bottom, thence over gentle rolling land.</p>	
19.995	<p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W E 1/16 <u>S17</u> S20 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Fence cor. bears S. 88° W., 56 lks. dist., fences extend W. and N. 20° E., curving N.</p>	
39.99	<p>Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	<p style="text-align: center;">T4S R4W 1/4 <u>S17</u> S20 1978</p>
	<p>Set a steel fence post alongside cor.</p> <p>Cor. is located 19 lks. S. of an E. and W. fence line.</p> <p>From this point an iron pipe of unknown origin, 1 in. diam., projecting 12 ins. above ground, bears N. 82°11' E., 47.7 lks. dist.</p>
59.985	<p>Point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R4W W 1/16 <u>S17</u> S20 1978</p>
	<p>Set a steel fence post alongside cor.</p> <p>Cor. is located 14 lks. S. of a E. and W. fence line.</p> <p>From this point an open end pipe of unknown origin, 1 in. diam., projecting 5 ins. above ground, bears N. 17°27' W., 3.7 lks. dist.</p>
68.50	<p>Track road, bears S. 60° E. and N. 60° W., thence over rolling land, through scattered ironwood and palo verde.</p>
79.98	<p>The cor. of secs. 17, 18, 19 and 20, monumented with an iron post, 2 ins. diam., projecting 30 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T4S R4W <u>S18 S17</u> <u>S19 S20</u> 1931</p>
	<p>from which</p> <p>A dead palo verde, 5 ins. diam., bears N. 20 1/2° E., 35 lks. dist., no marks visible. (Record 33 lks. dist.)</p> <p>A dead palo verde, 4 ins. diam., bears S. 19 3/4° E., 80 lks. dist., no marks visible.</p> <p>A dead palo verde, 5 ins. diam., bears S. 18 3/4° W., 79 lks. dist., no marks visible.</p> <p>A dead palo verde, 4 ins. diam., bears N. 47 1/4° W., 44 lks. dist., no marks visible.</p>
	<p style="text-align: center;">(Restoring the 1931 survey by Karl L. Siebecker)</p> <hr style="width: 20%; margin: auto;"/>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

	CHAINS		
		<p>S. 89°57' W., bet. secs. 18 and 19.</p> <p>Over rugged mountainous land, through scattered palo verde and ironwood.</p>	
	21.52	<p>Point for the E 1/16 sec. cor. of sec. 18 only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.</p>	
		<p>T4S R4W E 1/16 S18 1978</p>	
	43.04	<p>The 1/4 sec. cor. of sec. 18 only, monumented with an iron post, 1 in. diam., projecting 24 ins. above the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p>	
		<p>1/4 S18 1931</p>	
		<p>from which</p> <p>The stumphole of a fallen palo verde, 6 ins. diam., bears N. 65° E., 65 lks. dist., no marks visible. (Record 68 lks. dist.)</p> <p>A palo verde, 5 ins. diam., bears N. 52 1/2° W., 53 lks. dist., bark scribed 1/4 S18 BT.</p> <p>Add the marks T4S R4W 1978 to the brass cap.</p>	
		<p>_____</p>	
		<p>N. 89°51' W., beginning new measurement.</p>	
	4.02	<p>The 1/4 sec. cor. of sec. 19 only, monumented with an iron post, 1 in. diam., projecting 24 ins. above the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p>	
		<p>1/4 S19 1931</p>	
		<p>from which</p> <p>A dead palo verde, 5 ins. diam., bears S. 81 3/4° E., 61 lks. dist., no marks visible.</p> <p>A dead palo verde, 5 ins. diam., bears S. 21 1/2° W., 93 lks. dist., no marks visible.</p> <p>Add the marks T4S R4W 1978 to the brass cap.</p>	
		<p>_____</p>	
		<p>S. 89°52' W., beginning new measurement.</p>	
	39.70	<p>The cor. of secs. 18 and 19 only, on the W. bdy. of the Tp., heretofore described.</p>	
		<p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 4°14' W., bet. secs. 17 and 18.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	Over rolling land, through scattered palo verde and ironwood.	
5.50	Track road, bears S. 85° E. and NW., curving northerly, as scaled from U.S. Geological Quadrangle Map, "Cotton Center, Ariz." prepared in 1973, thence over cultivated land.	
39.60	Track road, bears E. and W.	
40.07	Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; found original cor. lying loose, which is a broken iron post, 1 in. diam., 16 ins. long, with brass cap mkd.	
	1/4 S18 S17 1931	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T4S R4W 1/4 S18 S17 1978	
	Reset the original cor. inside the iron post.	
	Set a steel fence post alongside cor.	
	Cor. is located 3 lks. N. of an E. and W. power line and 17 lks. N. of a concrete lined irrigation ditch, flows E.	
80.14	The cor. of secs. 7, 8, 17 and 18, monumented with an iron post, 2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.	
	T4S R4W S 7 S 8 S18 S17 1931	
	(Restoring the 1871 survey by Solomon W. Foreman)	
	<hr/> From the cor. of secs. 8, 9, 16 and 17.	
	S. 89°57' W., bet. secs. 8 and 17.	
	Along Pierpoint Road.	
12.40	Gila River, 150 lks. wide, flows S. 10° E.	
40.78	The 1/4 sec. cor. of secs. 8 and 17, monumented with an iron pipe, 1 1/2 ins. diam., projecting 3 ins. above the ground, in a mound of stone, 4 ft. base, 1 ft. high. This cor. was established by the Maricopa County Engineers and is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position. At the cor. point	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground over local cor., with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 S 8 S17 1978</p> <p>from which</p> <p style="text-align: center;">An X on the E. end of a concrete abutment, bears N. 58° W., 19.6 lks. dist.</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>Cor. is located 30 lks. S. of Pierpoint Road, bears S. 85° E., curving E. and S. 85° W., curving W. and 40 lks. N. of an E. and W. power line.</p> <p style="text-align: center;">_____</p> <p>S. 89°57' W., beginning new measurement.</p> <p>Continue along S. edge of Pierpoint Road.</p>	40.78
	<p style="text-align: center;">The cor. of secs. 7, 8, 17 and 18.</p> <p style="text-align: center;">(Restoring the 1931 resurvey by Karl L. Siebecker)</p> <p style="text-align: center;">_____</p> <p>From the 1/4 sec. cor. of secs. 7 and 18, monumented with an iron post, 1 in. diam., projecting 24 ins. above the ground, with mound of stone, 4 ft. base, 1 ft. high, N. of cor., brass cap mkd.</p> <p style="text-align: center;">1/4 S 7 S18 1931</p> <p>from which</p> <p style="text-align: center;">An iron wood, 9 ins. diam., bears N. 51 1/2° E., 132 lks. dist., mkd. 1/4 S7 BT. (Record N. 53 3/4° E.)</p> <p style="text-align: center;">A dead palo verde, 8 ins. diam., bears S. 41 1/2° E., 105 lks. dist., no marks visible. (Record S. 43 1/2° E.)</p> <p>Rebuild mound of stone around cor., 5 ft. base, to top.</p> <p>Cor. is located in an E. and W. fence line.</p> <p>Add the marks T4S R4W 1978 to the brass cap.</p> <p>S. 89°46' W., bet. secs. 7 and 18.</p> <p>Over rugged mountainous land, through scattered ironwood and palo verde.</p>	39.95
	<p style="text-align: center;">The cor. of secs. 7 and 18 only, on the W. bdy. of the Tp., heretofore described.</p> <p style="text-align: center;">(Restoring the 1871 survey by Solomon W. Foreman)</p> <p style="text-align: center;">_____</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	From the cor. of secs. 7, 8, 17 and 18.
	N. 0°11' E., bet. secs. 7 and 8.
.40	Pierpoint Road, bears E. and W., thence over cultivated land.
39.99	Point for the 1/4 sec. cor. of secs. 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. below surface of a track road on an E. and W. dirt dike, with brass cap mkd.
	T4S R4W 1/4 S 7 S 8 1978
	from which
	An iron post, 28 ins. long, 2 1/2 ins. diam., set 21 ins. in the ground for a reference monument, bears N. 58 1/2° W., 54.2 lks. dist., mkd. T4S R4W 1/4 S7 RM 35.8 FT. 1978 and an arrow pointing to the cor.
	Set a steel fence post alongside R.M.
40.50	Begin along a drainage ditch, through dense salt cedar.
79.40	Track road on dirt dike, bears E. and W.
79.63	Point selected for the witness cor. of secs. 5, 6, 7 and 8.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	W C T4S R4W ↑ S 6 S 5 S 7 S 8 1978
	Set a steel fence post alongside cor.
	From this point an open end pipe of unknown origin, 1 1/2 ins. diam., projecting 4 ins. above ground, bears N. 70°09' W., 60 lks. dist.
79.98	True point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor.
	Cor. point falls on the W. edge of a wash, 5 lks. wide, 2 ft. deep, drains southerly, impracticable to monument.
	From the point for the cor. of secs. 4, 5, 8 and 9.
	S. 89°37' W., bet. secs. 5 and 8.
	Over cultivated land.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

<p>CHAINS 20.415</p>	<p>Point for the E 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 15 ins. below surface of cultivated field, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W E 1/16 <u>S 5</u> S 8 1978</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 41 1/2° E., 97.1 lks. dist., mkd. T4S R4W E 1/16 S8 RM 64.1 FT. 1978 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 22 ins. in the ground for a reference monument, bears S. 46° W., 106.7 lks. dist., mkd. T4S R4W E 1/16 S8 RM 70.4 FT. 1978 and an arrow pointing to the cor.</p> <p>Both reference monuments are located in an E. and W. fence line.</p> <p>The E 1/16 sec. cor. is located in a cultivated field, 40 lks. N. of an E. and W. track road.</p>	
<p>36.90</p>	<p>Fence line, bears N. and S., thence over river bottom land, through medium creosote.</p>	
<p>40.83</p>	<p>Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, over a steel fence post driven in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W 1/4 <u>S 5</u> S 8 1978</p> <p>Set a steel fence post alongside cor.</p>	
<p>61.245</p>	<p>Point for the W 1/16 sec. cor. of secs. 5 and 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, over a steel fence post driven in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W W 1/16 <u>S 5</u> S 8 1978</p> <p>Set a steel fence post alongside cor.</p>	
<p>73.00</p>	<p>Leave Gila River bottom land.</p>	
<p>81.66</p>	<p>True point for the cor. of secs. 5, 6, 7 and 8.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
	S. 89°43' W., bet. secs. 6 and 7.
	Over nearly level land, through scattered iron wood, palo verde and medium creosote.
39.20	Graded road, bears N. and S.
39.50	Power line, bears N. and S.
40.87	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T4S R4W 1/4 S 6 S 7 1978</p>
	Set a steel fence post alongside cor.
	Cor. is located 15 lks. S. of an E. and W. graded road.
	From this point a re-bar of unknown origin, 3/8 in. diam., projecting 3 ins. above ground, bears S. 83°01' E., 26.3 lks. dist.
	From this same point the NW cor. of a trailer house in place, 12 x 56 ft., bears S. 0°29' W. 36.085 chs. dist., long side bears N. 42° E. and S. 42° W.
80.97	The cor. of secs. 6 and 7 only, on the W. bdy. of the Tp., heretofore described.
	From the true point for the cor. of secs. 5, 6, 7 and 8.
	N. 0°20' W., bet. secs. 5 and 6.
	Over nearly level land, along a drainage ditch, through dense salt cedar.
39.99	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T4S R4W 1/4 S 6 S 5 1978</p>
	Set a steel fence post alongside cor.
	Cor. is located 30 lks. W. of a drainage ditch, drains southerly.
	From this point an open end pipe of unknown origin, 2 ins. diam., projecting 30 ins. above ground, bears S. 74°51' W., 28.7 lks. dist.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 4 S., R. 4 W., Gila & Salt River Meridian, Arizona

CHAINS	
80.08	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., heretofore described.
	Subdivision of Section 6, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 6 and 7. N. 0°51' W., along the N. and S. center line of sec. 6. Over gently rolling land, through scattered ironwood, palo verde, mesquite and medium creosote.
39.96	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 6.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R4W C 1/4 S 6 1978
	Set a steel fence post alongside cor.
	Cor. is located 145 lks. W. of graded gravel road, bears S. 7° E. and N. 7° W.
	From this point a re-bar of unknown origin, 3/8 in. diam., projecting 2 ins. above ground, bears S. 87° E., 12.6 lks. dist.
50.50	Graded gravel road, bears S. 5° E. and N. 5° W.
79.80	The 1/4 sec. cor. of secs. 6 and 31, on the N. bdy. of the Tp., heretofore described.
	From the 1/4 sec. cor. of secs. 5 and 6. S. 89°41' W., along the E. and W. center line of sec. 6. Over gently rolling land, through scattered ironwood, palo verde, mesquite and medium creosote.
41.20	The C 1/4 sec. cor. of sec. 6.
61.43	Point for the C-W 1/16 sec. cor. of sec. 6.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	T4S R4W W 1/16 C———C S 6 1978
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, N. of cor.
80.70	The 1/4 sec. cor. of sec. 6 only, on the W. bdy. of the Tp., heretofore described.

Subdivision of Section 8, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
	Subdivision of Section 8, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 8 and 17. N. 0°13' E., along the N. and S. center line of sec. 8. Over river bottom land, through medium salt cedar.
40.11	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground over a steel fence post driven in ground, with brass cap mkd. <div style="text-align: center;"> T4S R4W C 1/4 S 8 1978 </div> Set a steel fence post alongside cor.
80.22	The 1/4 sec. cor. of secs. 5 and 8.
	From the 1/4 sec. cor. of secs. 8 and 9. S. 89°47' W., along the E. and W. center line of sec. 8. Over river bottom land, through medium salt cedar and mesquite.
20.40	Point for the C-E 1/16 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground over a steel fence post driven in the ground, with brass cap mkd. <div style="text-align: center;"> T4S R4W E 1/16 C ————— C S 8 1978 </div> Set a steel fence post alongside cor.
40.80	The C 1/4 sec. cor. of sec. 8.
51.20	Gila River, 2 chs. wide, drains southerly.
61.205	Point for the C-W 1/16 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> T4S R4W W 1/16 C ————— C S 8 1978 </div> Set a steel fence post alongside cor.

Subdivision of Section 8, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
81.61	<p>The 1/4 sec. cor. of secs. 7 and 8.</p> <hr/> <p style="text-align: center;">Subdivision of Section 17, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 17 and 20. N. 3°41' W., along the N. and S. center line of sec. 17. Over nearly level open land.</p>
40.07	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W C 1/4 S17 1978</p> <p>Set a steel fence post alongside cor. Cor. is located 8 lks. S. of a concrete lined irrigation ditch, 5 lks. wide, flows E.</p>
80.15	<p>The 1/4 sec. cor. of secs. 8 and 17.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 16 and 17. S. 89°59' W., along the E. and W. center line of sec. 17. Over river bottom land, through medium salt cedar.</p>
16.90	Gila River, 150 lks. wide, flows southerly.
20.19	<p>Point for the C-E 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W E 1/16 C—C S17 1978</p> <p>Set a steel fence post alongside cor.</p>
22.90	Fence line, bears S. 10° E. and N. 10° W., thence over nearly level open land.
40.38	The C 1/4 sec. cor. of sec. 17.
80.77	<p>The 1/4 sec. cor. of secs. 17 and 18.</p> <hr/> <p style="text-align: center;">Subdivision of Section 18, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona</p> <hr/> <p>From the 1/4 sec. cor. of sec. 18 only. N. 2°39' W., along the N. and S. center line of sec. 18.</p>

Subdivision of Section 18, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS		
	Over mountainous land, through scattered palo verde and ironwood.	
39.87	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 18.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 6 ft. base, to top, with brass cap mkd.	
	T4S R4W C 1/4 S18 1978	
79.92	The 1/4 sec. cor. of secs. 7 and 18.	
	<hr/> From the 1/4 sec. cor. of secs. 17 and 18. S. 89°46' W., along the E. and W. center line of sec. 18. Over nearly level open land.	
16.30	Track road, bears S. 10° E. and N. 5° W., as scaled from U.S. Geological Quadrangle Map, "Cotton Center, Ariz." prepared in 1973. Thence over mountainous land, through scattered ironwood and palo verde.	
20.965	Point for the C-E 1/16 sec. cor. of sec. 18.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T4S R4W E 1/16 C—C S18 1978	
	Fence cor. bears S. 88° E., 115 lks. dist., fences extend N., S. and E.	
41.93	The C 1/4 sec. cor. of sec. 18.	
83.64	The 1/4 sec. cor. of sec. 18 only, on the W bdy. of the Tp., heretofore described.	
	Subdivision of Section 20, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona	
	<hr/> From the 1/4 sec. cor. of secs. 20 and 29. N. 0°55' E., along the N. and S. center line of sec. 20.	
	Over gently rolling land, through scattered mesquite, palo verde, salt cedar and creosote.	
7.90	Track road, bears S. 35° E. curving southerly and N. 35° W.	
19.995	Point for the C-S 1/16 sec. cor. of sec. 20.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	

Subdivision of Section 20, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

	CHAINS		
		<p>T4S R4W C S 1/16 S20 C 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
	39.99	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
		<p>T4S R4W C 1/4 S20 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
	80.05	<p>The 1/4 sec. cor. of secs. 17 and 20.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 20 and 21.</p> <p>S. 89°59' W., along the E. and W. center line of sec. 20.</p> <p>Over nearly level open land.</p>	
	13.00	<p>Enter river bottom land, through medium salt cedar.</p>	
	16.00	<p>Gila river, 100 lks. wide, flows S. 15° W.</p>	
	19.995	<p>Point for the C-E 1/16 sec. cor. of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
		<p>T4S R4W E 1/16 C ——— C S20 1978</p> <p>Set a steel fence post alongside cor.</p>	
	39.99	<p>The C 1/4 sec. cor. of sec. 20.</p>	
	54.80	<p>Track road, bears N. 20° E. and S. 20° W.</p>	
	59.975	<p>Point for the C-W 1/16 sec. cor. of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
		<p>T4S R4W W 1/16 C ——— C S20 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p>	

Subdivision of Section 20, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	<p>From this point an open end iron pipe, 1 in. diam., projecting 3 ins. above ground, bears S. 6° W., 5 lks. dist., set in a mound of stone, 2 ft. base, 6 ins. high.</p>
79.96	<p>The 1/4 sec. cor. of secs. 19 and 20.</p>
<p>Subdivision of Section 21, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona</p>	
<p>From the 1/4 sec. cor. of secs. 21 and 28.</p>	
<p>N. 0°59' E., along the N. and S. center line of sec. 21.</p>	
<p>Over cultivated land.</p>	
39.14	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 21, not monumented.</p>
59.175	<p>Point for the C-N 1/16 sec. cor. of sec. 21, not monumented.</p>
79.21	<p>Point for the 1/4 sec. cor. of secs. 16 and 21.</p>
<p>From the point for the 1/4 sec. cor. of secs. 21 and 22.</p>	
<p>N. 89°56' W., along the E. and W. center line of sec. 21.</p>	
<p>Over cultivated land.</p>	
41.81	<p>The point for the C 1/4 sec. cor. of sec. 21.</p>
42.80	<p>Track road, bears N. and S., thence over nearly level land, through medium salt cedar and mesquite.</p>
61.82	<p>Point for the C-W 1/16 sec. cor. of sec. 21, not monumented.</p>
62.70	<p>Fence line, bears S. and N., 30 lks. dist. to fence cor., fences extend N., S. and W.</p>
81.83	<p>The 1/4 sec. cor. of secs. 20 and 21.</p>
<p>NW 1/4, Section 21</p> <hr style="width: 20%; margin: auto;"/>	
<p>From the point for the C-W 1/16 sec. cor. of sec. 21.</p>	
<p>N. 0°57' E., along the N. and S. center line of the NW 1/4, sec. 21.</p>	
<p>Over nearly level land, through medium mesquite.</p>	
20.02	<p>Point for the NW 1/16 sec. cor. at intersection with the E. and W. center line of the NW 1/4, sec. 21.</p>
<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>	
<p>T4S R4W NW 1/16 S21 1978</p>	

Subdivision of Section 21, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

	CHAINS	
		Set a steel fence post alongside cor.
		Cor. is located 118 lks. E. of a N. and S. fence line.
40.04		The W 1/16 sec. cor. of secs. 16 and 21.
		From the point for the C-N 1/16 sec. cor. of sec. 21.
		N. 89°59' W., along the E. and W. center line of the NW 1/4, sec. 21.
		Over nearly level land, through medium mesquite and salt cedar.
20.015		The NW 1/16 sec. cor. of sec. 21.
40.03		The N 1/16 sec. cor. of secs. 20 and 21.
Subdivision of Section 22, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona		
		From the 1/4 sec. cor. of secs. 22 and 27.
		N. 0°53' W., along the N. and S. center line of sec. 22.
		Over gently rolling land, through scattered mesquite, ironwood and medium creosote.
40.01		Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 22.
		Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
		T4S R4W C 1/4 S22 1978
		Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
43.50		Track road, bears S. 85° E. and N. 85° W., as scaled from U.S. Geological Quadrangle Map, "Cotton Center, Ariz." prepared in 1973.
63.20		Track road, bears S. 70° E. and S. 70° W., as scaled from U.S. Geological Quadrangle Map, "Cotton Center, Ariz." prepared in 1973.
79.80		The 1/4 sec. cor. of secs. 15 and 22.
		From the 1/4 sec. cor. of secs. 22 and 23.
		S. 89°34' W., along the E. and W. center line of sec. 22.
		Over gently rolling land, through medium ironwood, palo verde and creosote.
8.40		Gila Bend Canal, flows S. 5° W.
39.41		The C 1/4 sec. cor. of sec. 22.
59.175		Point for the C-W 1/16 sec. cor. of sec. 22.

Subdivision of Section 22, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W W 1/16 C-----C S22 1978</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 25 lks. N. of a track road, bears N. 85° E. curving NE and S. 85° W. curving SW.</p> <p>78.15 Old Highway No. 80, bears N. and S.</p> <p>78.94 The point for the 1/4 sec. cor. of secs. 21 and 22.</p>
<hr/> <p>Subdivision of Section 27, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°39' W., along the N. and S. center line of sec. 27.</p> <p>Over gently rolling land, through scattered mesquite, palo verde, ironwood and medium creosote.</p> <p>38.50 Power line bears E. and W.</p> <p>40.00 Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W C 1/4 S27 1978</p> <p>Set a steel fence post alongside cor.</p> <p>80.00 The 1/4 sec. cor. of secs. 22 and 27.</p>
	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>S. 89°43' W., along the E. and W. center line of sec. 27.</p> <p>Over gently rolling land, through scattered palo verde, ironwood and medium creosote.</p> <p>9.30 Gila Bend Canal, flows S. 15° E.</p> <p>39.38 The C 1/4 sec. cor. of sec. 27.</p> <p>59.07 Point for the C-W 1/16 sec. cor. of sec. 27.</p>

Subdivision of Section 27, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W W 1/16 C-----C S27 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 117 lks. N. of an E. and W. power line, 270 lks. N. of a cultivated field, edge bears E. and W. and 156 lks. W. of the N. end of a track road extending southerly only.</p>	
78.70	Old Highway No. 80, bears N. and S.	
78.76	The point for the 1/4 sec. cor. of secs. 27 and 28.	
<hr/> <p>Subdivision of Section 29, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona</p> <hr/>		
	<p>From the point for the 1/4 sec. cor. of secs. 29 and 32. N. 3°36' W., along the N. and S. center line of sec. 29.</p> <p>Over nearly level land, through scattered mesquite, palo verde and creosote.</p>	
40.10	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W C 1/4 S29 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located 21 lks. W. of a N. and S. fence line.</p> <p>From this point an open end iron pipe of unknown origin, 1 in. diam., projecting 2 ins. above ground, bears N. 75°30' E., 22 lks. dist.</p>	
60.125	<p>Point for the C-N 1/16 sec. cor. of sec. 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W C N 1/16 S29 C 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>From this point a fence cor., bears N. 83° E., 11.5 lks. dist., fences extend E., S. and W.</p>	

Subdivision of Section 29, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
80.15	The 1/4 sec. cor. of secs. 20 and 29.
	From the true point for the 1/4 sec. cor. of secs. 28 and 29.
	N. 89°56' W., along the E. and W. center line of sec. 29.
	Over river bottom land, through medium salt cedar and mesquite.
36.00	Leave river bottom land, enter gently rolling land, through scattered mesquite, ironwood, palo verde, and medium creosote.
39.80	The C 1/4 sec. cor. of sec. 29.
58.20	Track road, bears NE., curving northerly and S. 35° W., curving southerly.
59.685	Point for the C-W 1/16 sec. cor. of sec. 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T4S R4W
	W 1/16
	C-----C
	S29
	1978
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.
	From this point a re-bar of unknown origin, 3/8 in. diam., projecting 4 ins. above ground, bears N. 76°30' E., 10.5 lks. dist.
79.57	The 1/4 sec. cor. of secs. 29 and 30.
	NW 1/4, Section 29
	From the C-W 1/16 sec. cor. of sec. 29.
	N. 3°44' W., along the N. and S. center line of the NW 1/4, sec. 29.
	Over rolling land, through scattered mesquite, palo verde and medium creosote.
6.00	Fence line, bears N. 40° E. and S. 40° W.
20.035	Point for the NW 1/16 sec. cor. at intersection with the E. and W. center line of the NW 1/4, sec. 29.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.
	T4S R4W
	NW 1/16 S29
	1978

Subdivision of Section 29, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
40.07	<p>The W 1/16 sec. cor. of secs. 20 and 29.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 29.</p> <p>N. 89°56' W., along the E. and W. center line of the NW 1/4, sec. 29.</p> <p>Over rolling land, through scattered palo verde and medium creosote.</p> <p>7.30 Track road, bears N. 10° E. and S. 10° W.</p> <p>7.40 Fence cor., fences extend E. and W. 250 lks., thence S. 10° W., 100 lks., thence S. 40° W.</p> <p>19.935 The NW 1/16 sec. cor. of sec. 29.</p> <p>39.87 The point for the N 1/16 sec. cor. of secs. 29 and 30.</p>
<hr/> <p>Subdivision of Sec. 30, T. 4 S., R. 4 W., Gila and Salt River Meridian, Arizona</p> <hr/>	
20.01	<p>From the 1/4 sec. cor. of sec. 30 only.</p> <p>N. 0°03'30" E., along the N. and S. center line of sec. 30.</p> <p>Over rolling land, through scattered palo verde, ironwood and medium creosote.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 30, not monumented.</p>
40.02	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T4S R4W C 1/4 S30 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
80.02	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with an iron post, 1 in. diam., projecting 36 ins. above the ground, in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">1/4 <u>S19</u> S30 1931</p> <p>Add the marks T4S R4W 1978 to the brass cap.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>S. 89°59'30" W., along the E. and W. center line of sec. 30.</p>

Subdivision of Section 30, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
	Over rolling land, through scattered mesquite, ironwood, palo verde and medium creosote.
8.48	Point for the C 1/16 80 sec. cor. of sec. 30, not monumented.
28.48	Point for the C-E 1/16 sec. cor. of sec. 30, not monumented.
48.48	The C 1/4 sec. cor. of sec. 30.
88.40	The 1/4 sec. cor. of sec. 30 only, on the W. bdy. of the Tp., monumented with an iron post, 1 in. diam., projecting 10 ins. above the ground, in a mound of stone, 1 1/2 ft. base, to top, with brass cap mkd.
	<div style="text-align: center;"> 1/4 S30 1931 </div>
	from which
	<div style="text-align: center;"> An ironwood, 8 ins. diam., bears S. 48 1/4° E., 230 lks. dist., mkd. 1/4 S30 BT. </div>
	Add the marks T4S R4W 1978 to the brass cap.
<hr/> SE 1/4, Section 30	
	From the point for the E 1/16 sec. cor. of sec. 30 only.
	N. 0°05' E., along the N. and S. center line of the SE 1/4, sec. 30.
	Over rolling land, through scattered ironwood, palo verde, mesquite and medium creosote.
20.01	Point for the SE 1/16 sec. cor. at intersection with the E. and W. center line of the SE 1/4, sec. 30, not monumented.
40.02	The point for the C-E 1/16 sec. cor. of sec. 30.
	From the S 1/16 sec. cor. of secs. 29 and 30.
	S. 89°59'30" W., along the E. and W. center line of the SE 1/4, sec. 30.
	Over rolling land, through scattered ironwood, mesquite, palo verde and medium creosote.
9.86	Point for the S 1/16 80 sec. cor. of sec. 30.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> T4S R4W 1/16 S ——— 80 S30 1978 </div>

Subdivision of Section 30, T. 4 S., R. 4 W.,
Gila & Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p>
29.85	<p>The point for the SE 1/16 sec. cor. of sec. 30.</p>
49.84	<p>The point for the C-S 1/16 sec. cor. of sec. 30.</p>
	<hr/> <p>From the E 1/16 80 sec. cor. of sec. 30 only.</p>
	<p>N. 0°06' E., along the E 1/16 80 line, sec. 30.</p>
	<p>Over rolling land, through scattered palo verde and medium creosote.</p>
20.015	<p>The S 1/16 80 sec. cor. of sec. 30.</p>
40.03	<p>The point for the C 1/16 80 sec. cor. of sec. 30.</p>
	<hr/> <p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 10 miles north of Gila Bend, Arizona. The general elevation ranges from about 650 to 2100 feet above sea level. The soil is a sandy loam.</p> <p>The Gila River flows in a southerly direction through the west portion of the township; bottom land is rich, silty clay loam of which most is under cultivation.</p> <p>Access is by way of Old Highway No. 80, which crosses the center portion of the township in a north and south direction and New Highway No. 85 (formerly No. 80) crosses the east portion of township in a north and south direction. There are several unimproved or lightly gravelled roads throughout the township.</p> <p>The vegetation consist of salt cedar and mesquite along the Gila River. The remainder of the township consist of creosote, ironwood, palo verde and cactus.</p> <p>There is no evidence of mining activity or minerals.</p>

CHAINS

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Technician
Richard H. Bancroft	Survey Aid
Duane R. Ferneau	Survey Aid
Jay D. Lytle	Survey Aid
Dirk L. Peterson	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~We~~, Paul L. Reeves Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 6th day of January, 19 78, (I) ~~We~~ have dependently resurveyed portions of the north, south and west boundaries and subdivisional lines and surveyed subdivisions in sections 6, 8, 17, 18, 20, 21, 22, 27, 29 and 30, Township 4 South, Range 4 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~us~~ and under (my) ~~our~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

March 30, 1979
(Date)

Paul L. Reeves
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
Denver, Colorado

The foregoing field notes of the dependent resurvey of portions of the north, south and west boundaries and subdivisional lines and survey of subdivisions in sections 6, 8, 17, 18, 20, 21, 22, 27, 29 and 30, Township 4 South, Range 4 West, Gila and Salt River Meridian, Arizona.

executed by Paul L. Reeves, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 10 1980
(Date)

J. Voorhees
(Chief, Division of Cadastral Survey)

Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in, is a true copy of the original field notes.

(Date)

(Chief, Division of Cadastral Survey) GPO 849-626