

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

SOUTH AND WEST BOUNDARIES

AND

SUBDIVISIONAL LINES

AND

A SURVEY OF SUBDIVISIONS IN SECTIONS

27, 29, 30, 31 AND 32

TOWNSHIP 11 NORTH, RANGE 20 EAST

Of the GILA AND SALT RIVER Meridian,
In the State of ARIZONA

EXECUTED BY

HARRY K. SMITH

SUPERVISORY CADASTRAL SURVEYOR

PAUL L. REEVES

SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated APRIL 18, 1978, approved APRIL 20, 1978,

_____, which provided for the surveys included under U.S. Survey/Group
Number 603, and assignment instructions dated APRIL 18, 1978.
AND JUNE 9, 1978

Survey commenced MAY 3, 1978

Survey completed JUNE 23, 1978

1A

BOOK 5 114

INDEX DIAGRAM

Township 11 North, Range 20 East

6	5	4	3	2	1
7	8	9	10	11	12
18 27	17	16	15	14	13
19 24	26 20 23	21 18	13 22 13	23	24
7 30 21	22 29 20	17 28 16	12 27 11	8 26	25
4 31	19 32 1	14 33	10 34	35	36

- Subdivision of sec. 27 .. p. 28
- Subdivision of sec. 29 p. 29
- Subdivision of sec. 30 p. 31
- Subdivision of sec. 31 p. 34
- Subdivision of sec. 32 p. 38

T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS

A portion of the north and east boundaries were surveyed by John L. Harris in 1879. The south boundary, a portion of the east boundary and the subdivisional lines were surveyed by A. E. Shoemaker in 1883. A portion of the north boundary was surveyed by M. N. Grant in 1883. The west boundary was surveyed by H. A. Coe in 1883. The south boundary was resurveyed by Sidney E. Blout in 1915. A portion of the east boundary was resurveyed by Benjamin J. Kinsey and Sidney E. Blout in 1921. The west boundary was resurveyed by Roger F. Wilson in 1936.

The following field notes are those of the dependent resurvey of a portion of the south and west boundaries, subdivisional lines and a survey of subdivisions in Sections 27, 29, 30, 31 and 32, Township 11 North, Range 20 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973 and the Special Instructions for Group No. 603, dated April 18, 1978.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record.

Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the south-east corner of section 27, as scaled from U. S. Geological Survey Quadrangle Map, "Pinedale, Arizona", prepared in 1970, is as follows:

Latitude $34^{\circ}18.9'$ N. Longitude $110^{\circ}11.7'$ W.

The mean magnetic declination is $13^{\circ}30'$ E.

Dependent Resurvey of a Portion of the South Bdy.,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

(Restoring the 1915 resurvey by Sidney E. Blout)

Beginning at the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 3 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.

T11N
S32|S33
R20E S 5|S 4
T10N
1915

from which

A fallen pine, 24 ins. diam., bears N. $32\ 1/2^{\circ}$ E.,
86 lks. dist., mkd. T11N R20E S33 BT.

Dependent Resurvey of a Portion of South Bdy.,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS

A ponderosa pine, 24 ins. diam., bears S. 10° E.,
137 lks. dist., healed blaze.

A stump hole, bears S. 33 1/4° W., 170 lks. dist.

A decayed stump, bears N. 49° W., 260 lks. dist.,
mkd. BT.

from which a new BT

A ponderosa pine, 8 ins. diam., bears N. 18 1/2° E.,
97 lks. dist., mkd. T11N R20E S33 BT.

Cor. is located 3 lks. S. of a fence cor., fences extend
N. and W.

Remark the brass cap to read

T11N R20E
S32|S33
S 5|S 4
T10N
1978
1915

N. 89°56' W., bet. secs. 5 and 32.

Over gently rolling land, through dense ponderosa pine,
scattered cedar and juniper.

40.03 The 1/4 sec. cor. of sec. 5 only, T. 10 N., R. 20 E., de-
termined at record bearing and dist. from an original be-
aring tree

A ponderosa pine stump, 30 ins. diam., bears
S. 60 3/4° E., 104 lks. dist., mkd. BT.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, with brass cap mkd.

T11N R20E

1/4 S 5
T10N R20E
1978

from which a new BT

A ponderosa pine, 9 ins. diam., bears S. 8° W.,
104.5 lks. dist., mkd. 1/4 S5 BT.

Cor. is located 1 link N. of an E. and W. fence line.

N. 89°56' W., beginning new measurement.

.15 The 1/4 sec. cor. of sec. 32 only, T. 11 N., R. 20 E.,
monumented with an iron post, 1 inch diam., projecting 8
ins. above the ground, with brass cap mkd.

1/4|
S32|
1915

Dependent Resurvey of a Portion of South Bdy.,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>Cor. is located 1 lk. N. of an E. and W. fence line.</p> <p>Remark the brass cap to read</p> $\begin{array}{r} T11N R20E \\ \frac{1}{4} S32 \\ \hline T10N R20E \\ 1978 \\ 1915 \end{array}$ <p>N. 89°59' W., beginning new measurement.</p>	
1.70	Graded road, bears N. and S.	
12.50	Power line, bears NE and W.	
20.00	Power line, bears E. and S.	
20.10	Point for the W 1/16 sec. cor. of sec. 32 only, T. 11 N., R. 20 E., not monumented.	
39.70	Track road, bears S. 5° E. and N. 5° W.	
39.88	<p>The cor. of secs. 5 and 6 only, T. 10 N., R. 20 E., monumented with an iron post, 3 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.</p> $\begin{array}{r} T11N \\ R20E \frac{S31 S32}{S 6 S 5} \\ T10N \\ 1915 \end{array}$ <p>from which</p> <p>A cedar stump, 26 ins. diam., bears S. 33 1/2° E., 106 lks. dist., no marks. (Record S. 31° E.)</p> <p>A cedar, 20 ins. diam., bears S. 57° W., 30 lks. dist., mkd. T10N R20E S6 BT. (Record S. 54 3/4° W.)</p> <p>Remark the brass cap to read</p> $\begin{array}{r} T11N R20E \\ S32 \\ \hline S 6 S 5 \\ T10N R20E \\ 1978 \\ 1915 \end{array}$ <p>N. 89°59' W., beginning new measurement.</p>	
.32	The cor. of secs. 31 and 32 only, T. 11 N., R. 20 E., monumented with an iron post, 3 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.	

Dependent Resurvey of a Portion of South Bdy.,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS

T11N
R20E $\frac{S31|S32}{S 6|S 5}$
T10N
1915

from which

A cedar, 15 ins. diam., bears N. 46° E., 133 lks.
dist., mkd. T11N R20E S32 BT.
(Record N. 43 1/4° E.)

A cedar, 20 ins. diam., bears S. 22° E., 17 lks.
dist., mkd. T10N R20E S BT.
(Record S. 65 1/4° E.)

An oak, 12 ins. diam., bears S. 60° W., 153 lks.
dist., healed blaze. (Record S. 57° W.)

A cedar, 16 ins. diam., bears N. 36° E., 41 lks.
dist., mkd. T11N R20E S31 BT.
(Record N. 40 1/4° W.)

Fence cor. bears S. 55° E., 9 lks. dist., fences extend
N., E. and W.

Remark the brass cap to read

T11N R20E
|
 $\frac{S31|S32}{S 6}$
T10N R20E
1978
1915

Dependent Resurvey of a Portion of the West Boundary,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

(Restoring the 1936 resurvey by Roger F. Wilson)

From the cor. of secs. 1, 6, 31 and 36, Tps. 10 and
11 N., Rs. 19 and 20 E., monumented with an iron post,
3 ins. diam., projecting 8 ins. above the ground, with
brass cap mkd.

T11N
R19E R20E
 $\frac{S36|S31}{S 1|S 6}$
T10N
1936

from which 1883 bearing trees

An oak stump, bears N. 48 1/2° E., 37 lks. dist.,
illegible scribe marks.

A ponderosa pine, 20 ins. diam., bears S. 51° E.,
47 lks. dist., partly healed blaze.

An oak 20 ins. diam., bears S. 56° W., 42 lks.
dist., healed blaze.

Dependent Resurvey of a Portion of West Boundary,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 30 ins. diam., bears N. 59 1/2° W., 181 lks. dist., mkd. T11N R19E S36 BT.</p> <p>from which 1936 bearing tree</p> <p>A juniper, 30 ins. diam., bears N. 42° E., 87 lks. dist., mkd. T11N R20E S31 BT.</p> <p>from which a new bearing tree</p> <p>A ponderosa pine, 16 ins. diam., bears S. 38° W., 33.5 lks. dist., mkd. T10N R19E S1 BT.</p> <p>Cor. is located 15 lks. W. of a fence cor., fences extend N., E. and W.</p> <p>Add the marks 1978 to the brass cap.</p> <p>N. 0°11' W., bet. secs. 31 and 36.</p> <p>Over rolling land, through dense ponderosa pine, scattered oak, cedar and juniper.</p>
20.01	Point for the S 1/16 sec. cor. of secs. 31 and 36, not monumented.
35.02	Point for the N-N-S 1/256 sec. cor. of secs. 31 and 36.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 9 ins. below surface of a track road, with brass cap mkd.</p> <p style="text-align: center;">T11N N-N-S 1/256 R19E R20E S36 S31 1978</p> <p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears N. 79° E., 26 lks. dist., mkd. N-N-S 1/256 S31 BT.</p> <p>A ponderosa pine, 15 ins. diam., bears S. 41 1/2° W., 16 lks. dist., mkd. N-N-S 1/256 S36 BT.</p> <p>Cor. is located 2 lks. W. of center of a N. and S. track road and 29 lks. W. of a N. and S. fence line.</p> <p>Fence cor., bears S. 82° W., 9 lks. dist., fences extend N. and S. 60° W.</p>
37.90	Wash, 40 lks. wide, 5 ft. deep, drains NE from W.
39.00	Track road, bears E. and W.
40.02	The 1/4 sec. cor. of secs. 31 and 36, monumented with an iron post, 1 in. diam., projecting 10 ins. above the ground, with brass cap mkd.

Dependent Resurvey of a Portion of West Boundary,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S36 S31 1936</p> <p>from which</p> <p style="padding-left: 40px;">The stump hole of a pine stump, 20 ins. diam., bears S. 46 1/2° E., 122 lks. dist., stump mkd. 1/4 S31 BT.</p> <p style="padding-left: 40px;">The remains of a pine stump, bears N. 40 1/2° W., 73 lks. dist., no marks visible.</p> <p>from which a new bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 35° E., 80.5 lks. dist., mkd. 1/4 S31 BT.</p> <p>Remark the brass cap to read</p> <p style="text-align: center;">T11N R19E R20E 1/4 S36 S31 1978 1936</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°11' W., beginning new measurement.</p> <p>Over mountainous land, through dense ponderosa pine, scattered oak, cedar and juniper.</p>	
10.04	<p>Point for the S-N 1/64 sec. cor. of secs. 31 and 36.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N S-N 1/64 R19E R20E S36 S31 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 30° E., 21 lks. dist., mkd. S-N 1/64 S31 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 40° W., 46.5 lks. dist., mkd. S-N 1/64 S36 BT.</p> <p>Cor. is located 25 lks. E. of a N. and S. fence line.</p>	
20.08	<p>Point for the N 1/16 sec. cor. of secs. 31 and 36, not monumented.</p>	
40.16	<p>The cor. of secs. 25, 30, 31 and 36, monumented with an iron post, 2 ins. diam., projecting 10 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R19E R20E S25 S30 S36 S31 1936</p> <p>from which the 1883 bearing trees</p>	

Dependent Resurvey of a Portion of West Boundary,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>A pine stump, 30 ins. diam., bears S. 81° E., 32 lks. dist., mkd. T11N R20E S31 BT.</p> <p>A ponderosa pine, 20 ins. diam., bears S. 57° W., 69 lks. dist., mkd. T11N R19E S36 BT.</p> <p>A juniper, 20 ins. diam., bears N. 32° W., 23 lks. dist., mkd. T11N R19E S25 BT.</p> <p>from which a 1936 bearing tree</p> <p>An oak snag, 10 ins. diam., bears N. 30 1/2° E., 80 lks., dist., mkd. T11N R20E S30 BT.</p>	
39.54	<p>N. 0°32' W., bet. secs. 25 and 30.</p> <p>Over mountainous land, through dense ponderosa pine, medium pinyon, cedar, oak and juniper.</p> <p>The 1/4 sec. cor. of secs. 25 and 30, monumented with an iron post, 1 in. diam., projecting 15 ins. above the ground in a mound of stone, 2 ft. base, 1 ft. high, with brass cap mkd.</p> <p style="text-align: center;">1/4 S25 S30 1936</p> <p>from which an 1883 bearing tree</p> <p>The remains of a fallen pine, bears S. 81 1/2° W., 69 lks. dist., marks visible 1/4 S.</p> <p>from which 1936 bearing trees</p> <p>A cedar, 8 ins. diam., bears S. 83 1/2° E., 22 lks. dist., mkd. S30 BT.</p> <p>A cedar, 28 ins. diam., bears N. 11° W., 16 lks. dist., mkd. 1/4 S25 BT.</p>	
20.14	<p>N. 0°53' W., beginning new measurement.</p> <p>Over gently rolling land, through dense ponderosa pine, cedar, pinyon, oak and juniper.</p> <p>The N 1/16 sec. cor. of secs. 25 and 30, monumented with a reinforcement rod, 1/2 in. diam., 18 ins. long, projecting 1 in. above the ground, with a tag attached and mkd. L.S. 1640. This cor. was established by Hanen H. Williams, L.S. 1640, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R19E R20E N 1/16 S25 S30 1978</p>	

Dependent Resurvey of a Portion of West Boundary,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS

from which

A ponderosa pine, 6 ins. diam., bears S. 75° E.,
7 lks. dist., mkd. N 1/16 S30 BT.

A ponderosa pine, 10 ins. diam., bears
S. 49 1/2° W., 27.5 lks. dist., mkd.
N 1/16 S25 BT.

Deposit the local cor. alongside iron post.

Cor. is located 14 lks. S. of an E. and W. track road.

Fence cor. bears S. 73° E., 37 lks. dist., fences extend
N., E., S. and W.

N. 0°53' W., beginning new measurement.

20.13 The cor. of secs. 19, 24, 25 and 30, monumented with an
iron post, 2 ins. diam., flush with ground, with brass
cap mkd.

T11N
R19E R20E
S24|S19
S25|S30
1936

from which

The remains of a pine stump, bears S. 49 3/4° E.,
323 lks. dist., no marks visible.

An oak stump, 12 ins. diam., bears S. 26 1/4° W.,
403 lks. dist., no marks visible.

Center of well, 3 ft. diam., bears N. 84 3/4° W.,
345 lks. dist.

Cor. is located 38 lks. E. of a graded gravel road, bears
S. 32° E. and N. 32° W.

From this point a reinforcement rod 3/4 in. diam.,
projecting 2 ins. above a 1 ft. diam. concrete base,
bears S. 89°36' W., 86.5 lks. dist., with tag attached
and mkd. L.S. 1640.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

(Restoring the 1883 survey by A. E. Shoemaker)

From the cor. of secs. 26, 27, 34 and 35, monumented with
the remains of a wooden post, 20 x 5 x 3 ins. in a mound
of stone, 2 ft. base, 6 ins. high, with illegible scribe
marks, from which an original bearing tree

A fallen pine, 11 ins. diam., bears N. 45° E.,
46 lks. dist., mkd. T11N R20E S26 BT.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins.
in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of Subdivisional Lines
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T11N R20E $\frac{S27 S26}{S34 S35}$ 1978</p> <p>from which new bearing trees</p> <p>A ponderosa pine, 6 ins. diam., bears N. 19° E., 79 lks. dist., mkd. T11N R20E S26 BT.</p> <p>A cedar, 9 ins. diam., bears S. 32° E., 81.5 lks. dist., mkd. T11N R20E S35 BT.</p> <p>A pinyon, 6 ins. diam., bears S. 34° W., 154 lks. dist., mkd. T11N R20E S34 BT.</p> <p>A cedar, 18 ins. diam., bears N. 28° W., 68.5 lks. dist., mkd. T11N R20E S27 BT.</p> <p>Deposit the wooden post alongside cor.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 7 lks. NE of a fence cor., fences extend E., S. and W.</p> <p>N. 0°39' W., bet. secs. 26 and 27.</p> <p>Over rolling land, through dense ponderosa pine, cedar, pinyon and scattered oak and juniper.</p>	
36.10	Track road, bears N. 85° E. and S. 85° W.	
39.80	Point for the 1/4 sec. cor. of secs. 26 and 27, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T11N R20E $\frac{1}{4}$ $\frac{S27 S26}{1978}$</p>	
79.60	The cor. of secs. 22, 23, 26 and 27, monumented with a fallen pine, 8 ins. diam., mkd. T11N S23 on one side, R20E S26 on one side, S27 on one side and S22 on one side, from which an original bearing tree	
	A cedar, 20 ins. diam., bears S. 42° E., 88 lks. dist., mkd. T11N R20E S26 BT.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T11N R20E $\frac{S22 S23}{S27 S26}$ 1978</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>from which new bearing trees</p> <p>A cedar, 14 ins. diam., bears S. 35° W., 126 lks. dist., mkd. T11N R20E S27 BT.</p> <p>A cedar, 15 ins. diam., bears N. 61 1/2° W., 164 lks. dist., mkd. T11N R20E S22 BT.</p> <p>Cor. is located 9 lks. E. of a fence cor., fences extend N. and E.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34, determined from original bearing trees</p> <p>A pine stump, 24 ins. diam., bears S. 46° E., 34 lks. dist., no marks visible. (Record S. 50° E.)</p> <p>A ponderosa pine, 32 ins. diam., bears N. 74° W., 94 lks. dist., healed blaze, open blaze enough to read 1/4 S.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S33 S34 1978</p> <p>from which new bearing tree</p> <p>A cedar, 5 ins. diam., bears S. 69° E., 18 lks. dist., mkd. 1/4 S34 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>North, bet. secs. 33 and 34.</p> <p>Over rolling land, through dense ponderosa pine and scattered cedar.</p>
10.20	Fence line, bears S. 70° E. and N. 70° W.
11.70	Highway No. 260, bears S. 70° E. and N. 70° W.
12.90	Fence line, bears S. 70° E. and N. 70° W.
40.38	<p>Point for the cor. of secs. 27, 28, 33 and 34, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E S28 S27 S33 S34 1978</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 10 ins. diam., bears S. 63° E., 75.5 lks. dist., mkd. T11N R20E S34 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears S. 48° W., 31.5 lks. dist., mkd. T11N R20E S33 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 68° W., 61 lks. dist., mkd. T11N R20E S28 BT.</p> <p>Cor. is located at the E. edge of a track road, bears SE and NW.</p> <p>Fence cor. bears N. 61° W., 50.5 lks. dist., fences extend N. and W.</p>	
	<p>From the cor. of secs. 26, 27, 34 and 35.</p> <p>S. 89°58' W., bet. secs. 27 and 34.</p> <p>Over rolling land, through dense cedar, medium ponderosa pine, pinyon, scattered oak and juniper along a fence line.</p>	
40.24	<p>The 1/4 sec. cor. of secs. 27 and 34, monumented with a sandstone, 18 x 11 x 7 ins. in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on N. face.</p> <p>from which</p> <p>The stump hole of a fallen cedar, 26 ins. diam., bears S. 52° W., 67 lks. dist., mkd. 1/4 S BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S27 4 S34 1978</p> <p>from which new bearing trees</p> <p>A juniper, 6 ins. diam., bears N. 53 1/2° E., 45.5 lks. dist., mkd. 1/4 S27 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 10 1/2° W., 131.5 lks. dist., mkd. 1/4 S34 BT.</p> <p>Deposit the mkd. stone alongside cor.</p> <p>Rebuild mound of stone, 2 ft. base, 6 ins. high, N. of cor.</p> <p>Cor. is located at a fence cor., fences extend N., E. and W.</p>	
16.80	<p>N. 89°36' W., beginning new measurement.</p> <p>Telephone line, bears N. 30° E. and S. 30° W.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
40.30	The cor. of secs. 27, 28, 33 and 34.
	N. 0°55' W., bet. secs. 27 and 28.
	Over rolling land, through dense ponderosa pine, cedar and scattered juniper, along a fence line.
36.50	Power line, bears S. 70° E. and N. 70° W.
40.38	The 1/4 sec. cor. of secs. 27 and 28, determined from remains of original bearing tree
	A pine stump, bears S. 10° E., 60 lks. dist., found remains of tree bulldozed away from stump, open blaze enough to read 1/4 S.
	At the cor. point
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T11N R20E $\frac{1}{4}$ S28 S27 1978
	from which new bearing trees
	A ponderosa pine, 15 ins. diam., bears N. 35 1/2° E., 56 lks. dist., mkd . 1/4 S27 BT.
	A ponderosa pine, 14 ins. diam., bears N. 71 1/2° W., 40 lks. dist., mkd. 1/4 S28 BT.
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
	Cor. is located 12 lks. W. of a N. and S. fence line and 10 lks. E. of abandoned N. and S. fence line.
	N. 0°03' E., beginning new measurement.
14.20	Abandoned railroad grade, bears N. 10° E., curving northerly and SW (scaled).
21.70	Leave dense timber, thence through scattered ponderosa pine and cedar.
37.40	Graded road, bears W. and SE., curving southerly.
39.71	Point for the cor. of secs. 21, 22, 27 and 28, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T11N R20E $\frac{S21 S22}{S28 S27}$ 1978
	from which an unrecorded bearing tree

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>A pine snag, 30 ins. diam., bears S. 22° E., 118 lks. dist., mkd. T11N R20E S27 BT.</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears N. 66° E., 148 lks. dist., mkd. T11N R20E S22 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 50° E., 135 lks. dist., mkd. T11N R20E S27 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears S. 78° W., 115 lks. dist., mkd. T11N R20E S28 BT.</p> <p>A ponderosa pine, 10 ins. diam., bears N. 67° W., 121 lks. dist., mkd. T11N R20E S21 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 23 lks. W. of a N. and S. fence line, 43 lks. E. of a graded gravel road, bears N. 5° E., curving northerly and S. 15° W., curving SW.</p>	
40.26	<p>From the cor. of secs. 22, 23, 26 and 27.</p> <p>N. 89°48' W., bet. secs. 22 and 27.</p> <p>Over rolling land, through dense ponderosa pine, cedar, pinyon, scattered oak and juniper.</p> <p>The 1/4 sec. cor. of secs. 22 and 27, monumented with a mound of stone, 2 ft. base, 6 ins. high in an abandoned E. and W. fence line.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S22 1/4 S27 1978</p> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S. 36° W., 18.5 lks. dist., mkd. 1/4 S27 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears N. 44 1/2° W., 39 lks. dist., mkd. 1/4 S22 BT.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p>	
39.89	<p>N. 89°05' W., beginning new measurement.</p> <p>The cor. of secs. 21, 22, 27 and 28.</p> <hr/> <p>N. 4°08' W., bet. secs. 21 and 22.</p> <p>Over rolling land, through dense ponderosa pine and cedar.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
20.00	Graded gravel road, bears N. 30° E. and S. 30° W., curving southerly. (scaled)
39.81	<p>The 1/4 sec. cor. of secs. 21 and 22, monumented with a sandstone, 16 x 12 x 10 ins., in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. 1/4 on W. face, from which original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 20 ins. diam., bears N. 81° E., 66 lks. dist., mkd. 1/4 S BT over healed blaze.</p> <p style="padding-left: 40px;">The remains of a decayed pine, bears N. 70° W., 208 lks. dist., mkd. 1/4 S.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S21 S22 1978</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 60 1/2° E., 34.5 lks. dist., mkd. 1/4 S22 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 72° W., 22.5 lks. dist., mkd. 1/4 S21 BT.</p> <p>Deposit the mkd. stone alongside the cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the Tp.
	North, bet. secs. 32 and 33.
	Over rolling land, through dense ponderosa pine, scattered oak and cedar, along a fence line.
4.00	Power line, bears N., S. 40° E. and N. 85° W.
20.15	<p>Point for the S 1/16 sec. cor. of secs. 32 and 33.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E S 1/16 S32 S33 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 53° E., 120 lks. dist., mkd. S 1/16 S33 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 21° W., 51 lks. dist., mkd. S 1/16 S32 BT.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Fence cor., bears N. 30° W., 26.5 lks. dist., fences extend N., S. and W.</p> <p>Cor. is located, 18 lks. W. of a N. and S. power line.</p> <p>From this point a 3/4 in. reinforcement rod, bears S. 57°52' W., 46 lks. dist. This cor. was established by George O. Matkin, Registered Civil Engineer No. 5047 without reference to the 1/4 sec. cor. of secs. 32 and 33, which was recovered in this survey and is therefor rejected.</p>	
40.30	<p>The 1/4 sec. cor. of secs. 32 and 33, determined from original bearing tree</p> <p style="padding-left: 40px;">A ponderosa pine, 32 ins. diam., bears S. 41° W., 90 lks. dist. mkd. 1/4 S BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S32 S33 1978</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 5 ins. diam., bears N. 64° E., 77 lks. dist., mkd. 1/4 S33 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 75° W., 66 lks. dist., mkd. 1/4 S32 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 8 lks. NE of a fence cor. fences extend N., S. and W.</p> <p style="text-align: center;">_____</p> <p>N. 1°18' W., beginning new measurement.</p>	
20.00	Point for the N 1/16 sec. cor. of secs. 32 and 33, falls in a wash, 50 lks. wide, 3 ft. deep, drains easterly, not monumented.	
24.30	Fence line, bears S. 80° E. and N. 80° W.	
25.80	Highway No. 260, bears S. 80° E. and N. 80° W.	
27.30	Fence line, bears S. 80° E. and N. 80° W.	
40.00	<p>Point for the cor. of secs. 28, 29, 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
	T11N R20E $\frac{S29 S28}{S32 S33}$ 1978
	from which A ponderosa pine, 7 ins. diam., bears N. 58° E., 62 lks. dist., mkd. T11N R20E S28 BT. A ponderosa pine, 9 ins. diam., bears S. 67° E., 163 lks. dist., mkd. T11N R20E S33 BT. A ponderosa pine, 6 ins. diam., bears S. 24° W., 97 lks. dist., mkd. T11N R20E S32 BT. Cor. is located 56 lks. W. of a N. and S. fence line.
	<hr/> From the cor. of secs. 27, 28, 33 and 34. S. 89°44' W., bet. secs. 28 and 33. Over rolling land, through dense ponderosa pine and scattered cedar.
14.00	Wash, 30 lks. wide, 6 ft. deep, drains NW.
14.90	Track road, bears SE and NW.
23.60	Leave dense timber, edge bears N. and S., thence through medium timber.
30.20	Track road, bears N. 5° E. and S. 5° W., curving SW.
38.40	Enter dense timber, edge bears N. and S.
40.40	The 1/4 sec. cor. of secs. 28 and 33, monumented with a sandstone, 20 x 12 x 7 ins., firmly set in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. 1/4 on S. face, from which remains of original bearing trees A ponderosa pine stump, 30 ins. diam., bears N. 72° E., 136 lks. dist., no marks visible. (Record 139 lks. dist.) A pine stump, 36 ins. diam., bears S. 59° W., 94 lks. dist., mkd. BT.
	At the cor. point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T11N R20E $\frac{1}{4} \frac{S28}{S33}$ 1978
	from which A ponderosa pine, 7 ins. diam., bears N. 32 1/2° E., 25 lks. dist., mkd. 1/4 S28 BT. A ponderosa pine, 16 ins. diam., bears S. 50° W., 26 lks. dist., mkd. 1/4 S33 BT.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Deposit the mkd. stone alongside the cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <hr/> <p>S. 89°46' W., beginning new measurement.</p>	
4.50	Wash, 2 chs. wide, 3 ft. deep drains N. 30° E.	
11.40	Power line and abandoned railroad bed, bears N. 30° E. and S. 30° W.	
41.03	The cor. of secs. 28, 29, 32 and 33.	
	<hr/> <p>N. 1°29' W., bet. secs. 28 and 29.</p> <p>Over rolling land, through dense ponderosa pine, scattered cedar, juniper and oak.</p>	
21.30	Graded gravel road, bears N. 85° E., curving NE and S. 85° W., curving west.	
40.00	<p>Point for the 1/4 sec. cor. of secs. 28 and 29, at proportionate dist. The original cor. monument, a sandstone, 15 x 12 x 10 ins., mkd. 1/4 on one face, was found lying loose N. 55°06' E., 218 lks. dist.; there is no remaining evidence of the original cor. position.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 19 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S29 S28 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 28° E., 20 lks. dist., mkd. 1/4 S28 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 19° E., 16 lks. dist., mkd. 1/4 S28 BT.</p>	
	<p>Deposit the mkd. stone alongside the cor.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 109 lks. W. of a N. and S. fence line.</p>	
60.00	<p>Point for the N 1/16 sec. cor. of secs. 28 and 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E N 1/16 S29 S28 1978</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>from which</p> <p>A pinyon, 6 ins. diam., bears S. 77° E., 72 lks. dist., mkd. N 1/16 S28 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 25 lks. W. of a N. and S. fence line.</p>
80.00	<p>The cor. of secs. 20, 21, 28 and 29, monumented with a sandstone, 24 x 10 x 4 ins. in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. with 4 grooves on E. face and 2 grooves on S. face, from which original bearing trees</p> <p>A ponderosa pine, 24 ins. diam., bears N. 12° E., 94 lks. dist., illegible scribe marks. (Record N. 10° E. 100 lks. dist.)</p> <p>A ponderosa pine stump, 36 ins. diam., bears S. 42° E., 268 lks. dist., illegible scribe marks.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R20E <u>S20 S21</u> <u>S29 S28</u> 1978</p> </div> <p>from which new bearing trees</p> <p>A ponderosa pine, 8 ins. diam., bears S. 41 1/2° E., 133 lks. dist., mkd. T11N R20E S28 BT.</p> <p>A ponderosa pine, 7 ins. diam., bears N. 31° W., 15.5 lks. dist., mkd. T11N R20E S20 BT.</p> <p>Deposit the mkd. stone alongside cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 53 lks. E. of a N. and S. fence line and 50 lks. S. of a wash, 30 lks. wide, 2 ft. deep, drains S. 80° E.</p>
	<p>From the cor. of secs. 21, 22, 27 and 28.</p> <p>S. 89°12' W., bet. secs. 21 and 28.</p> <p>Over rolling land, through dense ponderosa pine and cedar.</p>
4.80	<p>Abandoned railroad grade, bears S. 10° E. and N. 10° W.</p>
40.08	<p>The 1/4 sec. cor. of secs. 21 and 28, monumented with a sandstone, 26 x 18 x 8 ins. in a mound of stone, 2 1/2 ft. base, 1 ft. high, mkd. 1/4 on N. face.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 4 ins. in the ground in mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E $\frac{1}{4} \frac{S21}{S28}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 40° W., 33 lks. dist., mkd. 1/4 S28 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 15, W., 49 lks. dist., mkd. 1/4 S21 BT.</p> <p>Deposit mkd. stone in mound of stone around cor.</p> <p>Cor. is located 13 lks. S. of an E. and W. abandoned fence line.</p> <p style="text-align: center;">—————</p> <p>N. 89°55' W., beginning new measurement.</p>
40.40	Wash, 30 lks. wide, 2 ft. deep, drains S. 80° E.
42.77	The cor. of secs. 20, 21, 28 and 29.
	<p>From the cor. of secs. 31 and 32 only, on the S. bdy. of the Tp.</p> <p>N. 1°40' W., bet. secs. 31 and 32.</p> <p>Over gently rolling land, along a graded road.</p>
19.99	Point for the S 1/16 sec. cor. of secs. 31 and 32, not monumented.
39.98	The 1/4 sec. cor. of secs. 31 and 32, monumented with a local iron pipe, 1 in. diam., projecting 3 ins. above the ground. This position is harmoniously related with other identified original cors. in the area, and is accepted as the best available evidence of the original cor. position, not remonumented.
	<p style="text-align: center;">—————</p> <p>N. 1°38' W., beginning new measurement.</p>
.60	Graded road, bears W. and E. 45 lks. dist. to a N. and S. graded road.
12.20	Wash, drains NE (scaled). Thence over rolling land through dense ponderosa pine, cedar and juniper.
19.63	The N 1/16 sec. cor. of secs. 31 and 32, monumented with a re-bar, 14 ins. long, 5/8 in. diam., projecting 3 ins. above ground, with a metal tag attached mkd. 5047. This monument was set by George O. Matkin, Registered Civil Engineer No. 5047 in Arizona and is accepted as a careful and faithful determination of the position of the cor. A copy of this survey is on file at Matkin Engineering in Show Low, Arizona.
	At the cor. point

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E N 1/16 S31 S32 1978</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 9 ins. diam., bears N. 7 1/2° W., 35.5 lks. dist., mkd. N 1/16 S31 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Reset the re-bar alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 1°38' W., beginning new measurement.</p>
19.63	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an iron pipe, 3 ins. diam., projecting 8 ins. above the ground in a mound of stone, 2 ft. base, 6 ins. high, with brass cap mkd.</p> <p style="text-align: center;">LS 5704 T11N R20E S30 S29 S31 S32 1966</p> <p>from which original bearing trees</p> <p style="padding-left: 40px;">A cedar, 24 ins. diam., bears N. 20° E., 113 lks. dist., mkd. T11N R20E S29 BT.</p> <p style="padding-left: 40px;">A fallen cedar, 16 ins. diam., bears S. 60° W., 107 lks. dist., mkd. T11N R20E S31 BT.</p> <p>from which new bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 4 ins. diam., bears S. 60° W., 156 lks. dist., mkd. X at breast height and BT at base.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 79° W., 117.5 lks. dist., mkd. T11N R20E S30 BT.</p> <p>Cor. is located 5 lks. SE of a fence cor., fences extend N. and W.</p>
20.43	<hr/> <p>From the cor. of secs. 28, 29, 32 and 33.</p> <p>S. 89°17' W., bet. secs. 29 and 32.</p> <p>Over gently rolling open land.</p> <p>Point for the E 1/16 sec. cor. of secs. 29 and 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS		
	T11N R20E E 1/16 $\frac{S29}{S32}$ 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
23.50	Fence line, bears N. and S.	
31.50	Fence line bears S. 60° E. and N. 60° W.	
34.50	Highway No. 260, bears S. 60° E. and N. 60° W.	
37.40	Fence line, bears S. 60° E. and N. 60° W.	
40.86	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
41.00	Power line, bears N. and S.	
65.70	Paved road, bears N. and S.	
66.20	Telephone line, bears N. and S., thence through dense ponderosa pine, cedar, scattered juniper and oak.	
81.71	The cor. of secs. 29, 30, 31 and 32.	
	S. 89°58' W., bet. secs. 30 and 31. Over rolling land, through dense ponderosa pine, cedar, juniper and scattered oak along a fence line.	
39.71	The 1/4 sec. cor. of secs. 30 and 31, monumented with a sandstone, 12 x 8 x 4 ins. in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on S. face, from which original bearing tree A pine stump, 20 ins. diam., bears N. 42° E., 28 lks. dist., mkd. BT. At the cor. point Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T11N R20E $\frac{1}{4}$ $\frac{S30}{S31}$ 1978	
	From which new bearing trees A ponderosa pine, 9 ins. diam., bears N. 11 1/2° E., 24 lks. dist., mkd. 1/4 S30 BT. A ponderosa pine, 6 ins. diam., bears S. 47° W., 12.5 lks. dist., mkd. 1/4 S31 BT. Deposit mkd. stone alongside cor. Rebuild mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Cor. is located in an E. and W. fence line.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°01' W., beginning new measurement.</p>	
18.69	Point for the W 1/16 sec. cor. of secs. 30 and 31, not monumented.	
36.18	The cor. of secs. 25, 30, 31 and 36 on the W. bdy. of Tp., heretofore described.	
	<hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p> <p>N. 0°18' W., bet. secs. 29 and 30.</p> <p>Over rolling land, through medium ponderosa pine, cedar and juniper.</p>	
21.30	Abandoned Highway No. 160, bears S. 80° E. and N. 80° W.	
27.30	Telephone line, bears S. 75° E. and N. 75° W.	
38.10	Fence line, bears SE and NW.	
38.70	Highway No. 260, bears SE and NW.	
40.04	Point for the 1/4 sec. cor. of secs. 29 and 30, at proportionate dist.; there is no remaining evidence of the original cor.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S30 S29 1978</p> <p>from which</p> <p style="margin-left: 40px;">A brass tablet set in a concrete base, 14 ins. diam., bears N. 0°01' E., 62 lks. dist. mkd. Arizona Highway Dept. Sta. 1112 x 56.84 Elev. P.O.T. 6406.43 1974.</p> <p>A state highway cor., bears N. 27°36' W., 142 lks. dist., monumented with a sandstone, 16 x 8 x 4 ins. firmly set projecting 6 ins. above ground, mkd. X 16 M, from which a cedar, 16 ins. diam., bears S. 70° E., 515 lks. dist., mkd. X 16 M BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p>	
40.60	Fence line, bears SE and NW.	
60.06	Point for the N 1/16 sec. cor. of secs. 29 and 30.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E N 1/16 S30 S29 1978</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A cedar, 4 ins. diam., bears N. 24 1/2° E., 128 lks. dist., mkd. X at breast height and BT at base.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 11 lks. E. of a N. and S. fence line.</p> <p>From this point a local cor., monumented with a 3/4 in. reinforcement rod, projecting 2 ins. above the ground in a mound of stone 1 ft. base 6 ins. high, with tag attached and mkd. L.S. 1640, bears S. 5°56' W., 42.5 lks. dist. The position of this cor. is not harmoniously related to identified orig. cors. and is not accepted.</p>	
62.10	Power line, bears S. 80° E. and N. 80° W.	
66.60	Wash, 30 lks. wide, 2 ft. deep, drains easterly.	
80.08	<p>The cor. of secs. 19, 20, 29 and 30 monumented with a 1 in. steel rod, projecting 5 ins. above the ground, with tag attached and mkd. Flour 120, from which an original bearing tree</p> <p>A cedar, 32 ins. diam., bears N. 64° E., 196 lks. dist., mkd. T11N R20E S20 BT.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E S19 S20 S30 S29 1978</p> <p>From which new bearing tree</p> <p>A ponderosa pine, 6 ins. diam., bears S. 44 1/2° E., 90.5 lks. dist., mkd. T11N R20E S29 BT.</p> <p>Deposit the steel rod alongside the cor.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>S. 89°34' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through medium ponderosa pine and scattered cedar.</p>	
3.80	Wash, 30 lks. wide, 2 ft. deep, drains N. 80° E., curving easterly.	
4.20	Track road, bears N. 5° E., curving Northwesterly and S. 5° W., thence along a fence line.	
20.09	<p>Point for the E 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T11N R20E E 1/16 $\frac{S20}{S29}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 80° W., 74.5 lks. dist., mkd. E 1/16 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 37° W., 57.5 lks. dist., mkd. E 1/16 S20 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 6.5 lks. N. of an E. and W. fence line.</p>
40.18	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with a sandstone, 16 x 12 x 10 ins. in a mound of stone, 2 ft. base, 1 ft. high, mkd. 1/4 on one side.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E $\frac{1}{4}$ $\frac{S20}{S29}$ 1978</p> <p>from which</p> <p style="padding-left: 40px;">A cedar, 14 ins. diam., bears S. 47° W., 45 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 79° W., 88 lks. dist., mkd. 1/4 S20 BT.</p> <p>Deposit the mkd. stone alongside the cor.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 5 lks. N. of a fence cor., fences extend E., S. and W.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89°05' W., beginning new measurement.</p>
39.91	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>N. 89°17' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through medium cedar and ponderosa pine.</p>
38.78	<p>The 1/4 sec. cor. of secs. 19 and 30, monumented with a 3/4 in. reinforcement rod, projecting 2 ins. above the ground, with two tags attached and mkd. Flour 185 and L.S. 1640. Origin of monument unknown.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS

This position is harmoniously related to existing original cors., has long been recognized as the cor. by adjacent landowners, and is accepted as the best available evidence of the original cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T11N R20E

$\frac{1}{4} \frac{S19}{S30}$

1978

from which

A ponderosa pine, 7 ins. diam., bears S. 46° W., 24 lks. dist., mkd. 1/4 S30 BT.

A power pole, bears N. 5° E., 121 lks. dist., power lines extend N. 50° E. and S.

Deposit the local cor. alongside iron post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.

Cor. is located at the cor. of fences extending NW and E.

N. 89°19' W., beginning new measurement.

10.20 Highway No. 260, bears S. 50° E. and N. 50° W.

19.405 Point for the W 1/16 sec. cor. of secs. 19 and 30.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.

T11N R20E

W 1/16 $\frac{S19}{S30}$

1978

from which

A ponderosa pine, 13 ins. diam., bears S. 37° E., 119.5 lks. dist., mkd. W 1/16 S30 BT.

Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.

Cor. is located 11 lks. S. of a wash, 5 lks. wide, 5 ft. deep, drains easterly and 22 lks. S. of a fence cor., fences extend N. and W.

From this point a local cor. bears S. 85°00' E., 18.5 lks. dist., monumented with a 1/2 in. reinforcement rod flush with 1 1/2 ft. base, of concrete, with tag attached and mkd. L.S. 1640. The position of this cor. is not harmoniously related to identified original cors. and is not accepted.

37.65 The cor. of secs. 19, 24, 25 and 30 on the W. bdy. of Tp., heretofore described.

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°38' E., bet. secs. 19 and 20.</p> <p>Over rolling land, through dense ponderosa pine, cedar, scattered oak and juniper.</p> <p>39.90 The 1/4 sec. cor. of secs. 19 and 20, monumented with a sandstone, 10 x 10 x 3 ins. in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on W. face, with a local cor. alongside monumented with a 1/2 in. reinforcement rod, with tag attached and mkd. L.S. 1640.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E 1/4 S19 S20 1978</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 10 ins. diam., bears N. 12° E., 94 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A cedar, 10 ins. diam., bears S. 70° E., 73 lks. dist., mkd. XBT.</p> <p>Deposit the mkd. stone and local reinforcement rod alongside cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°36' E., beginning new measurement.</p>
39.87	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a sandstone, 11 x 10 x 8 ins. in a mound of stone, 2 ft. base, 6 ins. high, mkd. with 5 grooves on one side and 3 grooves on another side, with a local cor. alongside, monumented with a 1/4 in. reinforcement rod, projecting 2 ins. above the ground, tag attached and mkd. L.S. 1640, from which original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears N. 73° E., 48 lks. dist., healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears S. 70° W., 46 lks. dist., healed blaze.</p> <p style="padding-left: 40px;">A ponderosa pine, 24 ins. diam., bears N. 18° W., 24 lks. dist., healed blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E S18 S17 S19 S20 1978</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 16 ins. diam., bears S. 6° E., 64 lks. dist., mkd. T11N R20E S20 BT.</p> <p>Deposit the mkd. stone and reinforcement rod alongside the cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p> <hr/> <p>N. 88°45' W., bet. secs. 18 and 19.</p> <p>Over rolling land, through dense ponderosa pine, cedar, juniper and oak.</p> <p>40.29 The 1/4 sec. cor. of secs. 18 and 19, monumented with a 1/2 in. reinforcement rod, projecting 4 ins. above ground in a mound of stone, 2 1/2 ft. base, 1 ft. high, with tag attached and mkd. L.S. 1640.</p> <p>This cor. was monumented by Hanen H. Williams, L.S. 1640 and is accepted as a careful and faithful perpetuation of the original cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd</p> <p style="text-align: center;">T11N R20E 1 S18 4 S19 1978</p> <p>from which</p> <p>A cedar, 15 ins. diam., bears N. 81° W., 121 lks. dist., mkd. 1/4 S18 BT.</p> <p>Deposit the reinforcement rod alongside cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 ft. high, N. of cor.</p> <p>Cor. is located 24 lks. S. of an E. and W. fence line.</p> <hr/> <p>N. 89°41' W., beginning new measurement.</p>	
39.43	<p>The cor. of secs. 13, 18, 19 and 24 on the W. bdy of the Tp., monumented with an iron post, 2 ins. diam., project- ing 12 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R19E R20E S13 S18 S24 S19 1936</p> <p>from which 1883 bearing trees</p> <p>A juniper, 15 ins. diam., bears S. 19° W., 39 lks. dist., mkd. T11N R19E S24 BT.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 11 N., R. 20 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A juniper, 16 ins. diam., bears N. 20° W., 23 lks. dist., mkd. T11N R19E S13 BT. (Record N. 25° W.)</p> <p>from which 1936 bearing trees</p> <p>A cedar, 15 ins. diam., bears N. 58 1/2° E., 77 lks. dist., mkd. T11N R20E S18 BT.</p> <p>An oak, 6 ins. diam., bears S. 31° E., 35 lks. dist., mkd. BT.</p> <p>Cor. is located 3 lks. E. of a fence cor., fences extend W. and N. 22 lks. dist. to a fence cor., fences extend E. and S.</p>
	<p>Subdivision of Section 27, T. 11 N., R. 20 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of secs. 27 and 34.</p> <p>N. 0°39'30" W., along the N. and S. center line of sec. 27.</p> <p>Over rolling land, through dense ponderosa pine, pinyon, cedar and juniper, along a fence line.</p>
26.00	Leave timber, edge bears E. and W.
40.25	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E C 1/4 S27 1978</p>
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N. 26° E., 47 lks. dist., mkd. C 1/4 S27 BT.</p> <p>A ponderosapine, 10 ins. diam., bears N. 67° W., 68.5 lks. dist., mkd. C 1/4 S27 BT.</p> <p>Raise a mound of stone, 2 ft. base, 2 ft. high, W. of cor.</p> <p>Fence cor. bears S. 2° W., 32.5 lks. dist., fences extend S. and W.</p>
40.35	Track road, bears E. and W., thence enter dense timber.
79.74	The 1/4 sec. cor. of secs. 22 and 27.
	<p>From the 1/4 sec. cor. of secs. 26 and 27.</p> <p>N. 89°23' W., along the E. and W. center line of sec. 27.</p> <p>Over rolling land, through dense ponderosa pine, cedar, scattered pinyon, juniper and oak.</p>
17.00	Track road, bears ESE and WNW. (Scaled)

Subdivision of Section 27, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
40.25	The C 1/4 sec. cor. of sec. 27, thence through medium timber along a fence line.
47.20	Track road, bears N. and S.
80.72	The 1/4 sec. cor. of secs. 27 and 28.
Subdivision of Section 29, T. 11 N., R. 20 E., Gila and Salt River Meridian, Arizona	
From the point for the 1/4 sec. cor. of secs. 29 and 32. N. 0°59' W., along the N. and S. center line of sec. 29. Over rolling open land, along a power line.	
3.20	Highway No. 260, bears S. 50° E. and N. 50° W.
20.30	Graded gravel road, bears E. and W. (scaled).
40.01	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 29.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
T11N R20E C 1/4 S29 1978	
from which	
A power pole, bears N. 60° E., 57 lks. dist., power line, bears N. and S.	
Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.	
Cor. is located 52 lks. W. of abandoned N. and S. fence line.	
47.90	Power line, bears N. 55° W. and S. 55° E. approximately 60 lks. dist., thence S.
60.105	Point for the C-N 1/16 sec. cor. of sec. 29.
Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
T11N R20E C N 1/16 S29 C 1978	
from which	
A ponderosa pine, 9 ins. diam., bears N. 40 1/2° E., 61 lks. dist., mkd. C-N 1/16 S29 BT.	

Subdivision of Section 29, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>
	<p>Fence cor. bears N. 64° E., 89 lks. dist., fences extend E., W. and abandoned S. from this same point another fence cor., bears N. 45° W., 72 lks. dist., fences extend N., E. and W.</p>
60.50	<p>Enter dense ponderosa pine and cedar, edge bears E. and W.</p>
80.20	<p>The 1/4 sec. cor. of secs. 20 and 29.</p>
	<p>From the 1/4 sec. cor. of secs. 28 and 29.</p>
	<p>S. 89°18' W., along the E. and W. center line of sec. 29.</p>
	<p>Over rolling land, through medium ponderosa pine and scattered cedar.</p>
20.265	<p>Point for the C-E 1/16 sec. cor. of sec. 29, not monumented.</p>
27.50	<p>Leave dense timber, edge, bears NE and SW, thence through scattered ponderosa pine and cedar.</p>
30.00	<p>Track road, bears NE and SW. (Scaled)</p>
40.53	<p>The C 1/4 sec. cor. of sec. 29.</p>
40.60	<p>Enter medium timber, edge bears N. and S.</p>
80.91	<p>The 1/4 sec. cor. of secs. 29 and 30.</p>
	<p style="text-align: center;">NE 1/4, Section 29</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the point for the C-E 1/16 sec. cor. of sec. 29.</p>
	<p>N. 1°12' W., along the N. and S. center line of the NE 1/4, sec. 29.</p>
	<p>Over rolling land, through medium ponderosa pine and cedar.</p>
12.80	<p>Track road, bears NE and SW.</p>
20.045	<p>Point for the NE 1/16 sec. cor. at intersection with the E. and W. center line of the NE 1/4, sec. 29.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R20E NE 1/16 S29 1978</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 29 1/2° W., 161 lks. dist., mkd. NE 1/16 S29 BT.</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>

Subdivision of Section 29, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	Cor. is located 36 lks. S. of abandoned E. and W. fence line.	
20.40	Enter dense timber, edge bears E. and W.	
40.09	The E 1/16 sec. cor. of secs. 20 and 29.	
	<p style="text-align: center;">_____</p> From the N 1/16 sec. cor. of secs. 28 and 29. S. 89°26' W., along the E. and W. center line of the NE 1/4, sec. 29. Over rolling land, through medium cedar and ponderosa pine.	
15.00	Track road, bears NE and SW (scaled).	
20.175	The NE 1/16 sec. cor. of sec. 29.	
40.35	The C-N 1/16 sec. cor. of sec. 29.	
	Subdivision of Section 30, T. 11 N., R. 20 E., Gila and Salt River Meridian, Arizona	
	From the 1/4 sec. cor. of secs. 30 and 31. N. 0°23' E., along the N. and S. center line of sec. 30. Over rolling land, through dense ponderosa pine, scattered oak, cedar and juniper.	
32.80	Abandoned Highway No. 160, bears SE and NW.	
38.80	Telephone line, bears S. 70° E. and N. 70° W.	
40.44	Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 30.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.	
	T11N R20E C 1/4 S30 1978	
	from which	
	A pinyon, 8 ins. diam., bears S. 63 1/2° E., 101 lks. dist., mkd. C 1/4 S30 BT.	
	A ponderosa pine, 8 ins. diam., bears S. 22 1/2° W., 87 lks. dist., mkd. C 1/4 S30 BT.	
	Cor. is located 20 lks. S. of an E. and W. fence line.	
	From this point a 3/8 in. reinforcement rod, projecting 2 ins. above the ground, bears N. 49° W., 62 lks. dist.	
	This monument may have been set by Hanen H. Williams, L.S. 1640, however, it is poorly related to other cors. in this sec. and is not accepted as the C 1/4 sec. cor.	

Subdivision of Section 30, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
60.53	<p>The C-N 1/16 sec. cor. of sec. 30, monumented with a 5/8 in. reinforcement rod, projecting 3 ins. above the ground, with tag attached and mkd. L.S. 1640.</p> <p>This cor. was established by Hanen H. Williams, L.S. 1640, and is accepted as a careful and faithful determination of the position of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R20E</p> <p>C</p> <p> </p> <p>N 1/16 S30</p> <p> </p> <p>C</p> <p>1978</p> </div> <p>from which</p> <p style="padding-left: 40px;">A cedar, 6 ins. diam., bears S. 38° W., 53 lks. dist., mkd. C-N 1/16 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 70° W., 72 lks. dist., mkd. C-N 1/16 S30 BT.</p> <p>Deposit the reinforcement rod alongside the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°23' E., beginning new measurement.</p>
11.70	Highway No. 260, bears S. 50° E. and N. 50° W.
20.07	The 1/4 sec. cor. of secs. 19 and 30.
<hr/> <p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89°27' W., along the E. and W. center line of sec. 30.</p> <p>Over gently rolling land, through dense ponderosa pine, cedar and juniper.</p>	
2.00	Highway No. 260, bears SE and NW.
39.24	The C 1/4 sec. cor. of sec. 30.
51.30	Abandoned Highway No. 160, bears SE and NW. (scaled).
58.22	Point for the C-W 1/16 sec. cor. of sec. 30, not monumented.
76.02	The 1/4 sec. cor. of secs. 25 and 30 on the W. bdy. of Tp., heretofore described.
<hr/> <div style="text-align: center;"> <p>NW 1/4, Section 30</p> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>From the point for the C-W 1/16 sec. cor. of sec. 30.</p> <p>N. 0°14' W., along the N. and S. center line of the NW 1/4, sec. 30.</p>	

Subdivision of Section 30, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	Over gently rolling land, through dense ponderosa pine, cedar, pinyon and juniper.	
4.00	Abandoned Highway No. 160, bears SE and NW. (scaled).	
20.115	The NW 1/16 sec. cor. of sec. 30, monumented with a 5/8 in. reinforcement rod, projecting 1 in. above a concrete base. The origin of this monument is unknown, however it is accepted as a careful and faithful determination of the position of the cor.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T11N R20E NW 1/16 S30 1978	
	from which	
	A ponderosa pine, 9 ins. diam., bears S. 29° E., 117 lks. dist., mkd. NW 1/16 S30 BT.	
	A pinyon, 5 ins. diam., bears S. 21° W., 71 lks. dist., mkd. NW 1/16 S30 BT.	
	Deposit the reinforcement rod alongside cor.	
	Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.	
	Cor. is located 33 lks. N. of an irregularly E. and W. track road and 43 lks. S. of an E. and W. fence line.	

	N. 0°12' W., beginning new measurement.	
10.80	Power line, bears S. 82° E. and N. 82° W.	
20.095	The W 1/16 sec. cor. of secs. 19 and 30.	

	From the C-N 1/16 sec. cor. of sec. 30.	
	N. 89°22' W., along the E. and W. center line of the NW 1/4, sec. 30.	
	Over gently rolling land, through medium ponderosa pine, cedar, pinyon and juniper.	
16.90	Track road, bears N. and S., curving westerly.	
19.19	The NW 1/16 sec. cor. of sec. 30.	

	N. 89°24' W., beginning new measurement.	
11.00	Abandoned Highway No. 160, bears SE and NW. (scaled)	

Subdivision of Section 30, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
18.02	<p>The N 1/16 sec. cor. of secs. 25 and 30 on the W. bdy. of the Tp., heretofore described.</p>
	<p>Subdivision of Section 31, T. 11 N., R. 20 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of sec. 31 only on the S. bdy. of the Tp., monumented with a sandstone, 15 x 12 x 6 ins., firmly set, projecting 3 ins. above the ground, mkd. 1/4 on the N. face, from which an 1883 bearing tree</p>
	<p>An oak, 12 ins. diam., bears S. 23° E., 46 lks. dist., mkd. 1/4 S. (Record S. 65 1/2° E.)</p>
	<p>from which a 1936 bearing tree</p>
	<p>An oak, 18 ins. diam., bears N. 67, E., 67 lks. dist., mkd. 1/4 S31 BT.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R20E 1/4 S31 T10N 1978</p>
	<p>from which new bearing trees</p>
	<p>A ponderosa pine, 12 ins. diam., bears N. 20° E., 36 lks. dist., mkd. 1/4 S31 BT.</p>
	<p>A ponderosa pine, 12 ins. diam., bears N. 46° W., 35.5 lks. dist., mkd. XBT.</p>
	<p>Deposit the mkd. stone alongside the cor.</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>
	<p>Cor. is located 12 lks. N. of an E. and W. fence line.</p>
	<p>N. 1°30' W., along the N. and S. center line of sec. 31.</p>
	<p>Over gently rolling land, through medium ponderosa pine, cedar and scattered oak.</p>
40.04	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 31, not monumented.</p>
41.00	<p>Graded road, bears E. and W. (scaled)</p>
49.81	<p>Point for the C-S-N 1/64 sec. cor. of sec. 31.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S31 C-S-N 1/64 1978</p>

Subdivision of Section 31, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears N. 77° W., 69 lks. dist. mkd. XBT.</p> <p>A ponderosa pine, 13 ins. diam.; bears N. 41° W., 40.5 lks. dist., mkd. C-S-N 1/64 S31 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>From this point a 3/4 in. reinforcement rod, projecting 5 ins. above the ground, with aluminum cap attached, no marks, origin unknown, bears N. 74°40' E., 178.5 lks. dist.</p>	
59.58	<p>Point for the C-N 1/16 sec. cor. of sec. 31.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R20E</p> <p>C</p> <p> </p> <p>N 1/16 S31</p> <p> </p> <p>C</p> <p>1978</p> </div>	
79.12	<p>from which</p> <p>A pinyon, 4 ins. diam., bears N. 71 1/2° E., 28.5 lks. dist., mkd. X at breast height and BT at base.</p> <p>A pinyon, 10 ins. diam., bears S. 83° W., 34.5 lks. dist., mkd. C-N 1/16 S31 BT.</p> <p>Cor. is located 40 lks. S. of a spur, slopes S. 80° E.</p> <p>The 1/4 sec. cor. of secs. 30 and 31.</p>	
39.81	<p>From the 1/4 sec. cor. of secs. 31 and 32.</p> <p>N. 89°47' W., along the E. and W. center line of sec. 31.</p> <p>Over gently rolling land, alongside graded road, through medium ponderosa pine and oak.</p>	
49.26	<p>The point for the C 1/4 sec. cor. of sec. 31.</p>	
	<p>Point for the C-E-W 1/64 sec. cor. of sec. 31.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S31</p> <p>C-E-W</p> <p>1/64</p> <p>1978</p> </div>	
	<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears N. 56, W., 129.5 lks. dist., mkd. C-E-W 1/64 S31 BT.</p>	

Subdivision of Section 31, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 33 lks. S. of an E. and W. fence line and 58 lks. S. of an E. and W. road.</p> <p>From this point a 3/4 in. reinforcement rod, projecting 5 ins. above the ground, with aluminum cap attached, no marks, origin unknown, bears N. 81°55' E., 161 lks. dist.</p> <p>58.71 Point for the C-W 1/16 sec. cor. of sec. 31.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E W 1/16 C _____ C S31 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 48° E., 133 lks. dist., mkd. C-W 1/16 S31 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 52° W., 155.5 lks. dist., mkd. C-W 1/16 S31 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, N. of cor.</p> <p>Cor. is located 10 lks. S. of an E. and W. fence line and 52 lks. S. of an E. and W. graded road.</p> <p>76.15 The 1/4 sec. cor. of secs. 31 and 36 on the W. bdy. of the Tp., heretofore described.</p>
	<p style="text-align: center;">NW 1/4, Section 31</p> <hr style="width: 20%; margin: auto;"/> <p>From the C-W 1/16 sec. cor. of sec. 31.</p> <p>N. 1°06' W., along the N. and S. center line of the NW 1/4, sec. 31.</p> <p>Over rolling land, through dense ponderosa pine, juniper and oak.</p> <p>9.905 Point for the C-S-NW 1/64 sec. cor. of sec. 31, not monumented.</p> <p>19.81 Point for the NW 1/16 sec. cor. at intersection with the E. and W. center line of the NW 1/4, sec. 31.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E NW 1/16 S31 1978</p> <p>from which</p> <p style="padding-left: 40px;">A pinyon, 5 ins. diam., bears S. 84° E., 66 lks. dist., mkd. NW 1/16 S31 BT.</p>

Subdivision of Section 31, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
<p>39.64</p>	<p>A pinyon, 6 ins. diam., bears N. 27° W., 19 lks. dist., mkd. NW 1/16 S31 BT.</p> <p>The point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <hr/> <p>From the C-N 1/16 sec. cor. of sec. 31.</p> <p>N. 88°53' W., along the E. and W. center line of the NW 1/4, sec. 31.</p> <p>Over rolling land, through dense ponderosa pine, pinyon, cedar, scattered juniper and oak.</p>
<p>9.39</p>	<p>Point for the C-E-NW 1/64 sec. cor. of sec. 31, not monumented.</p>
<p>18.78</p>	<p>The NW 1/16 sec. cor. of sec. 31.</p>
<p>36.25</p>	<p>The point for the N 1/16 sec. cor. of secs. 31 and 36 on the W. bdy. of the Tp., heretofore described.</p>
	<p style="text-align: center;">SE 1/4 of NW 1/4, Section 31</p> <hr/>
	<p>From the C-E-W 1/64 sec. cor. of sec. 31.</p> <p>N. 1°18' W., along the N. and S. center line of the SE 1/4 of the NW 1/4, sec. 31.</p> <p>Over gently rolling land, through dense ponderosa pine, juniper, scattered oak and cedar.</p>
<p>9.84</p>	<p>Point for the SE-NW 1/64 sec. cor. at intersection with the E. and W. center line of the SE 1/4 of the NW 1/4, sec. 31.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S31 SE-NW 1/64 1978</p>
	<p>from which</p>
	<p>A ponderosa pine, 7 ins. diam., bears N. 10° W., 18 lks. dist., mkd. SE-NW 1/64 S31 BT.</p>
	<p>A ponderosa pine, 7 ins. diam., bears S. 48 1/2° W., 28.5 lks. dist., mkd. SE-NW 1/64 S31 BT.</p>
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>
	<p>From this point a 3/4 in. reinforcement rod, projecting 6 ins. above the ground, with aluminum cap attached, no marks, origin unknown, bears S. 89°51' E., 156.5 lks. dist.</p>
<p>19.68</p>	<p>The point for the C-E-NW 1/64 sec. cor. of sec. 31.</p> <hr/>
	<p>From the C-S-N 1/64 sec. cor. of sec. 31.</p>

Subdivision of Section 31, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 89°20' W., along the E. and W. center line of the SE 1/4 of the NW 1/4, sec. 31.</p> <p>Over gently rolling land, through dense ponderosa pine, juniper, scattered oak and cedar.</p> <p>9.42 The SE-NW 1/64 sec. cor. of sec. 31.</p> <p>18.84 The point for the C-S-NW 1/64 sec. cor. of sec. 31.</p>
	<p style="text-align: center;">Subdivision of Section 32, T. 11 N., R. 20 E., Gila and Salt River Meridian, Arizona</p>
	<p>From the 1/4 sec. cor. of sec. 32 only on the S. bdy. of the Tp.</p> <p>N. 1°10' W., along the N. and S. center line of sec. 32.</p> <p>Over gently rolling land, through dense ponderosa pine, cedar, juniper and oak.</p> <p>20.06 Point for the C-S 1/16 sec. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R20E</p> <p>C</p> <p> </p> <p>S 1/16 S32</p> <p> </p> <p>C</p> <p>1978</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 34° W., 122 lks. dist., mkd. C-S 1/16 S32 BT.</p> <p>Set a steel fence post alongside the cor.</p> <p>A fence cor. bears N. 50° E., 29.5 lks. dist., fences extend E., S. and W.</p> <p>From this point a bumper jack, projecting 12 ins. above the ground, origin unknown, bears S. 72°24' E., 21.5 lks. dist.</p>
30.09	Point for the C-N-S 1/64 sec. cor. of sec. 32, not monumented.
36.40	Track road, bears N. 70° E. curving easterly and S. 70° W.
40.08	Fence line, bears E. and W.
40.12	<p>Point for the C 1/4 sec. cor. at intersection with the E. and W. center line of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R20E</p> <p>C 1/4 S32</p> <p>1978</p> </div>

Subdivision of Section 32, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>from which</p> <p>A ponderosa pine, 9 ins. diam., bears N. 57° E., 21 lks. dist., mkd. C 1/4 S32 BT.</p> <p>A ponderosa pine, 5 ins. diam., bears S. 30° E., 22 lks. dist., mkd. C 1/4 S32 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>50.70 Power line, bears E. and W.</p> <p>59.50 Fence line, bears E. and W., thence through scattered timber.</p> <p>59.935 Point for the C-N 1/16 sec. cor. of sec. 32.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T11N R20E</p> <p>C</p> <p> </p> <p>N 1/16 S32</p> <p> </p> <p>C</p> <p>1978</p> </div> <p>from which</p> <p>A ponderosa pine, 6 ins. diam., bears S. 11° E., 96.5 lks. dist., mkd. C-N 1/16 S32 BT.</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located 57 lks. E. of a N. and S. power line.</p> <p>69.00 Leave scattered timber edge bears E. and W., thence over open grass land.</p> <p>79.75 The point for the 1/4 sec. cor. of secs. 29 and 32.</p>
	<hr/> <p>From the 1/4 sec. cor. of secs. 32 and 33.</p> <p>S. 89°47' W., along the E. and W. center line of sec. 32.</p> <p>Over rolling land, through dense ponderosa pine, cedar and juniper, along a fence line.</p> <p>20.50 Point for the C-E 1/16 sec. cor. of sec. 32, not monumented.</p> <p>41.00 The C 1/4 sec. cor. of sec. 32.</p> <p>51.135 Point for the C-E-W 1/64 sec. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S32</p> <p>C-E-W</p> <p>1/64</p> <p>1978</p> </div>

Subdivision of Section 32, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S. 34 1/2° W., 47 lks. dist., mkd. C-E-W 1/64 S32 BT.</p> <p>Cor. is located 3 lks. N. of an E. and W. fence line.</p>	
56.20	<p>Point for the C-W-E-W 1/256 sec. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S32 C-W-E-W 1/256 1978</p>	
	<p>from which</p> <p>A ponderosa pine, 13 ins. diam., bears S. 20° E., 134.5 lks. dist., mkd. C-W-E-W 1/256 S32 BT.</p> <p>Fence cor., bears S. 25° W., 5 lks. dist., fences extend E., S. and W.</p> <p>NE fence cor. around Pinedale Cemetery, bears S. 3° W., 56.5 lks. dist.</p>	
61.265	<p>Point for the C-W 1/16 sec. cor. of sec. 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E S32 C———C W 1/16 1978</p>	
	<p>from which</p> <p>A cedar, 24 ins. diam., bears S. 53° E., 67 lks. dist., mkd. C-W 1/16 S32 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 41 lks. S. of an irregular E. and W. fence line.</p> <p>NW fence cor. around Pinedale Cemetery, bears S. 77°25' E., 263 lks. dist.</p> <p>From this point a wooden hub 1 x 2 ins., projecting 6 ins. above the ground in a mound of stone, 2 ft. base, 6 ins. high, origin unknown, bears N. 81°11' E., 183 lks. dist.</p>	
81.53	<p>The 1/4 sec. cor. of secs. 31 and 32.</p> <hr/> <p style="text-align: center;">NE 1/4, Section 32</p> <hr/> <p>From the point for the C-E 1/16 sec. cor. of sec. 32.</p>	

Subdivision of Section 32, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>N. 1°15' W., along the N. and S. center line of the NE 1/4, sec. 32.</p> <p>Over rolling land, through dense ponderosa pine, scattered cedar and juniper.</p>	
6.90	Power line, bears S. 75° E. and N. 75° W.	
19.91	<p>Point for the NE 1/16 sec. cor. at intersection with the E. and W. center line of the NE 1/4, sec. 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 6 ins. in the ground in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T11N R20E NE 1/16 S32 1978</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 47° E., 35.5 lks. dist., mkd. NE 1/16 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 15° E., 75.5 lks. dist., mkd. XBT.</p> <p>Cor. is located 38 lks. E. of a N. and S. fence line.</p>	
20.00	Enter a wash, 100 lks. wide, drains SE, from north.	
24.80	Leave wash, drains S. from W.	
30.70	Fence line, bears S. 65° E. and N. 65° W.	
32.30	Highway No. 260, bears S. 65° E. and N. 65° W.	
33.90	Fence line, bears S. 65° E. and N. 65° W., thence over open land.	
39.82	The E 1/16 sec. cor. of secs. 29 and 32.	
	<hr style="width: 20%; margin: 0 auto;"/> <p>From the point for the N 1/16 sec. cor. of secs. 32 and 33.</p> <p>S. 89°31'30" W., along the E. and W. center line of the NE 1/4, sec. 32.</p> <p>Over nearly level land, through dense ponderosa pine,</p>	
19.00	Wash, 100 lks. wide, drains SE, curving easterly.	
20.48	The NE 1/16 sec. cor. of sec. 32.	
20.80	Leave dense timber, edge bears N. and S., thence through scattered timber.	
40.95	The C-N 1/16 sec. cor. of sec. 32.	
	<hr style="width: 20%; margin: 0 auto;"/> <p style="text-align: center;">SW 1/4, Section 32</p> <hr style="width: 20%; margin: 0 auto;"/> <p>From the point for the W 1/16 sec. cor. of sec. 32 only on the S. bdy. of the Tp.</p>	

Subdivision of Section 32, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>N. 1°24' W., along the N. and S. center line of the SW 1/4, sec. 32.</p>
	<p>Over gently rolling land, through scattered oak, cedar, juniper and ponderosa pine.</p>
20.02	<p>Point for the SW 1/16 sec. cor. at intersection with the E. and W. center line of the SW 1/4, sec. 32.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 28 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T11N R20E SW 1/16 S32 1978</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 83° E., 108 lks. dist., mkd. SW 1/16 S32 BT.</p>
	<p>Cor. is located 28.5 lks. S. of an E. and W. fence line.</p>
	<p>From this point the NW corner of a stucco house, bears N. 89°01' E., 11.18 chs. dist., long side, bears N. and S.</p>
25.00	<p>Paved road, bears SE and NW (scaled)</p>
30.03	<p>Point for the C-N-SW 1/64 sec. cor. of sec. 32, not monumented.</p>
35.035	<p>Point for the C-N-N-SW 1/256 sec. cor. of sec. 32.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S32 C-N-N-SW 1/256 1978</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A cedar, 6 ins. diam., bears N. 77° E., 44 lks. dist., mkd. C-N-N-SW 1/256 S32 BT.</p>
	<p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p>
	<p>SW fence cor. around Pinedale Cemetery, bears N. 51°57' E., 315 lks. dist.</p>
40.04	<p>The C-W 1/16 sec. cor. of sec. 32.</p>
	<p style="text-align: center;">_____</p>
	<p>From the C-S 1/16 sec. cor. of sec. 32.</p>
	<p>S. 89°53' W., along the E. and W. center line of the SW 1/4, Sec. 32.</p>
	<p>Over rolling land, through medium ponderosa pine.</p>
10.09	<p>Point for the C-E-SW 1/64 sec. cor. of sec. 32, not monumented.</p>
14.00	<p>Graded gravel road, bears S. 30° E. and N. 30° W.</p>

Subdivision of Section 32, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
20.18	The SW 1/16 sec. cor. of sec. 32.
40.36	The point for the S 1/16 sec. cor. of secs. 31 and 32.
	<hr/> From the point for the C-E-SW 1/64 sec. cor. of sec. 32.
	N. 1°17' W., along the N. and S. center line of the NE 1/4 of the SW 1/4, sec. 32.
	Over rolling land, through dense ponderosa pine.
10.02	Point for the NE-SW 1/64 sec. cor. at intersection with the E. and W. center line of the NE 1/4, of the SW 1/4, sec. 32, not monumented.
15.03	Point for the C-N-NE-SW 1/256 sec. cor. of sec. 32.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> S32 C-N-NE-SW 1/256 1978 </div>
	from which
	<div style="text-align: center;"> A ponderosa pine, 6 ins. diam., bears S. 33 1/2° E., 56 lks. dist., mkd. C-N-NE-SW 1/256 S32 BT. </div>
20.04	The C-E-W 1/64 sec. cor. of sec. 32
	<hr/> From the point for the C-N-S 1/64 sec. cor. of sec. 32.
	S. 89°50' W., along the E. and W. center line of the NE 1/4 of the SW 1/4, sec. 32.
	Over rolling land, through dense ponderosa pine.
10.11	The point for the NE-SW 1/64 sec. cor. of sec. 32.
15.165	Point for the C-W-NE-SW 1/256 sec. cor. of sec. 32, not monumented.
20.22	The point for the C-N-SW 1/64 sec. cor. of sec. 32.
	<hr/> From the point for the C-W-NE-SW 1/256 sec. cor. of sec. 32.
	N. 1°20'30" W., along the N. and S. center line of the NW 1/4 of the NE 1/4 of the SW 1/4, sec. 32.
5.005	Point for the NW-NE-SW 1/256 sec. cor. at intersection with the E. and W. center line of the NW 1/4 of the NE 1/4 of the SW 1/4, sec. 32.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> S32 NW-NE-SW 1/256 1978 </div>

Subdivision of Section 32, T. 11 N., R. 20 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>from which</p> <p>A ponderosa pine, 5 ins. diam., bears S. 1 1/2° E., 74.5 lks. dist., mkd. NW-NE-SW 1/256 S32 BT.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>SE fence cor. around, Pinedale Cemetery, bears N. 3° W., 60 lks. dist., fences extend N., S. 30° E. and W.</p> <p>From this point a reinforcement rod 1/2 in. diam., projecting 1 in. above the ground, bears S. 25° E., 11 lks. dist., origin unknown.</p>	
10.01	<p>The C-W-E-W 1/256 sec. cor. of sec. 32.</p> <hr/> <p>From the C-N-NE-SW 1/256 sec. cor. of sec. 32.</p> <p>S. 89°48' W., along the E. and W. center line of the NW 1/4 of the NE 1/4 of the SW 1/4, sec. 32.</p>	
5.06	<p>The NW-NE-SW 1/256 sec. cor. of sec. 32.</p>	
10.12	<p>The C-N-N-SW 1/256 sec. cor. of sec. 32.</p>	
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located in the Pinedale, Arizona vicinity. The general elevation ranges from about 6300 to 6750 ft. above sea level. The soil is a clay loam.</p> <p>Access is by way of U. S. Highway No. 260 which crosses the south-west corner of the township in a SE and NW direction. There are several unimproved or lightly gravelled roads throughtout the township.</p> <p>The vegetation consists of ponderosa pine, cedar, pinyon, juniper and oak.</p> <p>There is no evidence of mining activity or minerals.</p>	

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Technician
John J. Bulinski	Survey Aid
Jay D. Lytle	Survey Aid
William J. Anderson	Survey Aid
Daniel L. Simpson	Survey Aid

CERTIFICATE OF SURVEY

Cadastral
 (We), Harry K. Smith, and Paul L. Reeves, Supervisory Surveyors, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 18th day
 of April, 19 78, (We) have dependently resurveyed a portion of
 the south and west boundaries, subdivisional lines, and surveyed subdivi-
 sions in sections 27, 29, 30, 31 and 32, Township 11 North, Range 20 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), (us) and under (my)
 (our) direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

September 17, 1979
 (Date) Harry K. Smith
 Supervisory (Cadastral Surveyor)

September 17, 1979
 (Date) Paul L. Reeves
 Supervisory (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Washington, D.C.
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south and
 west boundaries, subdivisional lines and a survey of subdivisions in sections
 27, 29, 30, 31 and 32, Township 11 North, Range 20 East, Gila and Salt River
 Meridian, Arizona

executed by Harry K. Smith and Paul L. Reeves, Supervisory Cadastral Surveyors
 having been critically examined and found correct, are hereby approved.

JAN 29 1980
 (Date) J. Voorhees
 (Chief, Division of Cadastral Survey)
 Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 , is a true copy of the original field notes.