

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

NORTH AND WEST BOUNDARIES

AND

SUBDIVISIONAL LINES

AND

A SURVEY OF SUBDIVISIONS IN SECTIONS

5, 7, 8, 9, 18, 20 AND 30,

TOWNSHIP 7 SOUTH, RANGE 25 EAST

GILA AND SALT RIVER

Of the _____ Meridian,
ARIZONA

In the State of _____

EXECUTED BY

PAUL L. REEVES

CADASTRAL SURVEYOR

Under special instructions dated FEBRUARY 15, 1978, approved FEBRUARY 15, 1978

_____, which provided for the surveys included under U.S. Survey/Group
Number 602, and assignment instructions dated FEBRUARY 16, 1978

Survey commenced MARCH 16, 1978
Survey completed APRIL 20, 1978

1A

BOOK 5 115

INDEX DIAGRAM

Township 7 South, Range 25 East,

	3					
6	22 5	10 4	8	2	1	
21	20	9				
2 7	19 8	8 9	5 10	11	12	
19	18	8				
1 18	17 17	7 16	15	14	13	
17	16					
19	15 20	6 21	22	23	24	
15	14					
30	13 29	28	27	26	25	
12	12					
31	11 32	33	34	35	36	

- Subdivision of Sec. 5 ----- page 22
- Subdivision of Sec. 7 ----- page 24
- Subdivision of Sec. 8 ----- page 26
- Subdivision of Sec. 9 ----- page 28
- Subdivision of Sec. 18 ----- page 29
- Subdivision of Sec. 20 ----- page 31
- Subdivision of Sec. 30 ----- page 33

Township 7 South, Range 25 East,
Gila and Salt River Meridian, Arizona

CHAINS

The boundaries and subdivisional lines were surveyed in 1875 by Theodore F. White. A portion of the north and west boundaries were retraced in 1916 by A. B. Rich. A portion of the north and east boundaries and the boundaries of section 1 were resurveyed and section 1 was subdivided in 1966 by Paul G. Bauer and Robert R. Johnson. The west boundary was resurveyed in 1967 by Kenneth D. Herman. A portion of the north boundary was resurveyed in 1964-70 by Leonard W. Murphy and Paul G. Bauer. A portion of the north boundary was resurveyed in 1976-77 by Paul L. Reeves.

The following field notes are those of the dependent resurvey of a portion of the north and west boundaries, subdivisional lines and a survey of subdivisions in sections 5, 7, 8, 9, 18, 20 and 30, Township 7 South, Range 25 East, Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 602, Arizona dated February 15, 1978.

The direction of the lines of this survey was determined by altitude observations on the sun and refer to the true meridian.

Prior to restoration of any corners, all necessary lines of the original survey were retraced and diligent search was made for any evidence of the original monuments and other calls of the official record. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

The geographic position of the southeast corner of section 20, as scaled from U. S. Geological Survey Quadrangle Map, "Thatcher, Arizona", prepared in 1960, is as follows:

Latitude 32°48.1' N. Longitude 109°48.0' W.

The mean magnetic declination is 13°30' E.

Dependent Resurvey of a Portion of West Bdy.,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

(Restoring the 1967 resurvey by Kenneth D. Herman)

Beginning at the S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.

T7S
R24E R25E
S 1/16
S13|S18
1967

Mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.

N. 0°03' E., bet. secs. 13 and 18.

Dependent Resurvey of a Portion of West Bdy.,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
	Over gently rolling land, through medium creosote.
11.60	Graded road, bears NE and SW curving southerly.
20.11	Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
32.80	Power line, bears N. 55° E. and S. 55° W.
37.70	Graded roads extend N., E. and SW.
60.33	The cor. of secs. 7, 12, 13 and 18, monumented with an iron post, 2 1/2 ins. diam., flush with ground, with brass cap mkd.
	<p style="text-align: center;">T7S R24E R25E S12 S 7 S13 S18 1967</p> <p>Cor. is located 4 lks. W. of fence cor.; fences extend N. and E. 25 lks., thence S.; also 50 lks. W. of a N. and S. graded road.</p>
	N. 0°02' E., bet. secs. 7 and 12.
	Over gently rolling land, along W. side of graded road.
39.64	Point for the 1/4 sec. cor. of secs. 7 and 12, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
79.72	The cor. of secs. 1, 6, 7 and 12, monumented with an iron post, 2 1/2 ins. diam., 18 ins. below surface of W. edge of a N. and S. graded road, with brass cap mkd.
	<p style="text-align: center;">T7S R24E R25E S 1 S 6 S12 S 7 1967</p>
	<p>from which</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., projecting 6 ins. above the ground, bears S. 60° W., 32.6 lks. dist., mkd. T7S R24E S12 RM 21.5 FT. 1967 and an arrow pointing to the cor.</p> <p style="padding-left: 40px;">An iron post, 2 1/2 ins. diam., projecting 4 ins. above the ground, bears N. 30° W., 55.3 lks. dist., mkd. T7S R24E S1 RM 36.5 FT. 1967 and an arrow pointing to the cor.</p> <p>Reference monuments are located in a N. and S. fence line.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of North Bdy., T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona</p>
	<p style="text-align: center;">(Restoring the 1964-70 resurvey by Leonard W. Murphy and Paul G. Bauer)</p>

Dependent Resurvey of a Portion of North Bdy.,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>From the cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp., reestablished in 1974 by Jerry Carl Williams, L.S. 9090 and recorded in Graham County, and accepted as a careful and faithful reestablishment of the position of the original cor., monumented with an iron post, 2 ins. diam., 6 ins. below surface of road, with aluminum cap mkd.</p> <p style="text-align: center;">Woodruff Engineering T6S R25E <u>32 33</u> 5 4 T7S R25E 1974 L.S. 9090</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. diam., set 14 ins. in the ground in a mound of stone, 3 ft. base, to top, for a reference monument, bears S. 30° W., 167.5 lks. dist., mkd. T7S R25E S5 RM 110.6 FT. 1978 and an arrow pointing to cor.</p> <p>Cor. is located in a N. and S. graded road, 50 lks. N. of intersection of roads extending N., S. and W., and 49 lks. W. of fence cor., fences extend N., E. and S.</p> <p>N. 89°52' W., bet. secs. 5 and 32.</p> <p>Over gently rolling land, through medium creosote, along the N. edge of a graded gravel road.</p>
19.94	<p>Point for the E 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E E 1/16 <u>S32</u> S 5 T7S 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 55 lks. N. of center of an E. and W. graded gravel road.</p>
38.70	<p>Graded road, bears S. 55° E. and N. 55° W., curving NE.</p>
38.90	<p>Power line, bears S. 55° E. and N. 55° W.</p>
39.88	<p>The 1/4 sec. cor. of secs. 5 and 32, monumented with an iron post, 2 1/2 ins. diam., projecting 3 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">T6S R25E <u>1 S32</u> 4 S 5 T7S 1964</p> <p>Set a steel fence post alongside cor.</p>

Dependent Resurvey of a Portion of North Bdy.,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Add the marks 1978 to the brass cap.</p> <p>Cor. is located 50 lks. N. of center of an E. and W. graded gravel road.</p>
	<p>N. 89°52' W., beginning new measurement.</p>
9.10	<p>Telephone line, bears S. 55° E. and N. 55° W., for approximately 150 lks., thence N. 75° W.</p>
19.94	<p>Point for the W 1/16 sec. cor. of secs. 5 and 32.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R25E W 1/16 $\frac{S32}{S 5}$ T7S 1978</p>
	<p>Set a steel fence post alongside cor.</p>
	<p>From this point a fence cor., bears S. 51° W., 61 lks. dist.; fences extend S. and W. around a land fill.</p>
	<p>Cor. is located 2 chs. N. of graded gravel road, bears N. 85° E. and S. 80° W.</p>
39.88	<p>Point for the cor. of secs. 5, 6, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R25E $\frac{S31 S32}{S 6 S 5}$ T7S 1978</p>
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p>
	<p>From this point a fence cor., bears S. 29° E., 10 lks. dist., fences extend N., E. and S.</p>
	<p>From this same point the cor. of Tps. 6 and 7 S., Rs. 24 and 25 E., bears N. 89°52' W., 77.92 chs. dist., monumented with an iron post, 2 1/2 ins. diam., 8 ins. below surface of N. and S. graded gravel road, with brass cap mkd.</p>
	<p style="text-align: center;">T6S R24E R25E $\frac{S36 S31}{S 1 S 6}$ T7S 1967</p>
	<p>from which</p>

Dependent Resurvey of a Portion of North Bdy.,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

	CHAINS		
		<p>An iron post, 2 1/2 ins. diam., projecting 2 ins. above the ground, bears N. 45° E., 74 lks. dist., mkd. T6S R25E S31 RM 48.84 FT. 1967 and an arrow pointing to the cor.</p> <p>An iron post, 2 1/2 ins. diam., projecting 7 ins. above the ground, bears S. 45° E., 74 lks. dist., mkd. T7S R25E S6 RM 48.84 FT. 1967 and an arrow pointing to the cor.</p> <p>Cor. is located 12 lks. W. of center of N. and S. graded gravel road.</p> <p>Reference monuments are located in a N. and S. fence line.</p> <p>The control line was fully retraced, and no evidence of the intervening cor. was found.</p> <hr/> <p>Dependent Resurvey of a Portion of Subdivisional Lines, T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona</p> <hr/> <p>(Restoring the 1875 survey by Theodore F. White)</p> <p>From the cor. of secs. 9, 10, 15 and 16, monumented with a spike nail in a mound of stone, 2 1/2 ft. base, 1 ft. high, from which an original bearing tree</p> <p>A mesquite snag, bears N. 49 1/2° E., 197 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E S 9 S10 S16 S15 1978</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 6 lks. S. of an E. and W. fence line.</p> <p>N. 0°12' E., bet. secs. 9 and 10.</p> <p>Over rolling land, through scattered mesquite and medium creosote.</p>	
	39.81	<p>The 1/4 sec. cor. of secs. 9 and 10, monumented with an angle iron, 18 ins. long, lying loose in a mound of stone, 2 ft. base, 6 ins. high, from which original bearing trees</p> <p>A tesote stump, bears N. 6 1/2° W., 213 lks. dist., no marks visible.</p> <p>A mesquite stump, bears N. 78° W., 98 lks. dist., no marks visible.</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E 1/4 S 9 S10 1978</p> <p>Deposit the angle iron alongside cor.</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°18' W., beginning new measurement.</p> <p>19.775 Point for the N 1/16 sec. cor. of secs. 9 and 10, not monumented.</p> <p>32.70 Telephone line, bears S. 55° E. and N. 55° W.</p> <p>39.55 True point for the cor. of secs. 3, 4, 9 and 10, determined at record bearing and dist. from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A mesquite snag, bears N. 34 1/2° E., 95 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite snag, bears S. 38 1/2° W., 68 lks. dist., no marks visible.</p> <p>The cor. point falls in a wash, 50 lks. wide, 10 ft. deep, draining N. 5' E., where it is impractical to set a monument.</p> <p>From this point a local witness cor., bears S. 89°51' E., 50 lks. dist., monumented with an iron pipe, 2 1/2 ins. diam., projecting 30 ins. above the ground, with cap mkd.</p> <p style="text-align: center;">WC 4 3 ← 9 10 33 ft. W.</p>
	<p>From the cor. of secs. 20, 21, 28 and 29, monumented with a mound of stone, 2 1/2 ft. base, 1 ft. high, from which the remains of original bearing trees</p> <p style="padding-left: 40px;">A mesquite snag, bears S. 67° E., 56 lks. dist., no marks visible. (Record S. 69° E.)</p> <p style="padding-left: 40px;">A mesquite snag, bears S. 17° W., 55 lks. dist., no marks visible. (Record S. 21° W.)</p> <p style="padding-left: 40px;">A mesquite snag, bears S. 54 1/2° W., 84 lks. dist., no marks visible.</p> <p style="padding-left: 40px;">A mesquite snag, bears N. 3 1/2° W., 39 lks. dist., no marks visible.</p> <p>At the cor. point</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E S20 S21 S29 S28 1978</p>	
	<p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <p>N. 0°21' W., bet. secs. 20 and 21.</p> <p>Over rolling land, through medium mesquite and creosote.</p>	
38.40	Graded road, bears NE and SW.	
39.95	Point for the 1/4 sec. cor. of secs. 20 and 21, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
77.90	Fence line, bears E. and W.	
78.60	Point selected for the witness cor. of secs. 16, 17, 20 and 21.	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T7S R25E S17↑S16 S20 S21 1978</p>	
78.90	<p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Enter washed area.</p>	
79.90	<p>True point for the cor. of secs. 16, 17, 20 and 21, determined at record bearing and dist. from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A mesquite 10 ins. diam., bears N. 78 3/4° E., 241 lks. dist., open blaze, no marks visible.</p> <p style="padding-left: 40px;">A mesquite snag, bears N. 31 3/4° E., 179 lks. dist., no marks visible.</p> <p>This point falls in a wash, 20 lks. wide, 3 ft. deep, draining northerly from S. 25° W., where it is impractical to set a monument.</p>	
40.02	<p>N. 0°20' E., bet. secs. 16 and 17.</p> <p>Over rolling land, through scattered mesquite, creosote and cactus.</p> <p>The 1/4 sec. cor. of secs. 16 and 17, monumented with a granite stone, 16 x 10 x 8 ins., firmly set, projecting 6 ins. above the ground, mkd. 1/4 on S. face.</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E $\frac{1}{4}$ S17 S16 1978</p> <p>Deposit mkd. stone alongside cor.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located 153 lks. E. of a N. and S. fence line.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0°05' E., beginning new measurement.</p>
33.20	<p>Fence line, bears S. 80° E. and N. 80° W., 130 lks. to a fence cor., fences extend S. 80° E., S. and N. 80° W.</p>
39.68	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a quartz stone, 12 x 7 x 7 ins. firmly set, projecting 5 ins. above the ground, with 2 notches visible on the E. edge.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E <u>S 8 S 9</u> S17 S16 1978</p> <p>Deposit mkd. stone alongside cor.</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p> <hr/> <p>From the cor. of secs. 9, 10, 15 and 16.</p> <p>N. 89°55' W., bet. secs. 9 and 16.</p> <p>Over rolling land, through scattered mesquite, creosote and cactus, along a fence line.</p>
35.40	<p>Fence cor., fences extend E. and SW.</p>
39.75	<p>Point for the 1/4 sec. cor. of secs. 9 and 16, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p>
79.50	<p>The cor. of secs. 8, 9, 16 and 17.</p> <hr/> <p>N. 0°11' W., bet. secs. 8 and 9.</p> <p>Over rolling land through scattered mesquite and medium creosote.</p>
39.34	<p>Point selected for the witness 1/4 sec. cor. of secs. 8 and 9.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W C T7S R25E $\frac{1}{4}$ ↑ S 8 S 9 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 250 lks. E. of a N. and S. fence line.</p>	
39.74	<p>True point for the 1/4 sec. cor. of secs. 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor. This point falls in the E. edge of a wash, 50 lks. wide, 6 ft. deep, drains N. 20° E. curving N., impractical to monument.</p>	
52.60	<p>Wash, 50 lks. wide, 3 ft. deep, drains N. from S. 15° W.</p>	
59.61	<p>Point for the N 1/16 sec. cor. of secs. 8 and 9, falls in a wash, 50 lks. wide, 3 ft. deep, drains northerly, no monument set.</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 12 ins. diam., bears N. 54 1/2° E., 124 lks. dist., mkd. N 1/16 S9 BT.</p> <p style="padding-left: 40px;">A mesquite, 10 ins. diam., bears N. 79° W., 48 lks. dist., mkd. N 1/16 S8 BT.</p> <p>Cor. point is located 136 lks. E. of a N. and S. fence line.</p>	
67.00	<p>Leave wash, thence along W. edge of same wash.</p>	
79.48	<p>Point for the cor. of secs. 4, 5, 8 and 9, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E S 5 S 4 S 8 S 9 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 70 lks. E. of a N. and S. fence line.</p> <hr/> <p>From the true point for the cor. of secs. 3, 4, 9 and 10. N. 89°51' W., bet. secs. 4 and 9.</p> <p>Over rolling land, through scattered mesquite and medium creosote.</p>	
11.50	<p>Telephone line, bears S. 55° E. and N. 55° W.</p>	
19.915	<p>Point for the E 1/16 sec. cor. of secs. 4 and 9.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E E 1/16 $\frac{S}{S}$ $\frac{4}{9}$ 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>	
22.40	<p>Track road, bears N. 35° E., curving easterly and S. 35° W., curving southerly.</p>	
39.83	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented with a scattered mound of stone, from which the remains of original bearing trees</p>	
	<p style="padding-left: 40px;">A mesquite snag, bears S. 7 1/4° W., 24 lks. dist., no marks visible.</p>	
	<p style="padding-left: 40px;">A mesquite snag, bears N. 19 1/2° W., 28 lks. dist., no marks visible.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E $\frac{1}{4}$ $\frac{S}{S}$ $\frac{4}{9}$ 1978</p>	
	<p>Set a steel fence post alongside cor.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>N. 89°50' W., beginning new measurement.</p>	
39.83	<p>The cor. of secs. 4, 5, 8 and 9.</p> <hr style="width: 50%; margin: 10px auto;"/>	
	<p>N. 0°09' W., bet. secs. 4 and 5.</p> <p>Over gently rolling land through scattered mesquite and medium creosote.</p>	
19.87	<p>Point for the S 1/16 sec. cor. of secs. 4 and 5.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E S 1/16 S 5 S 4 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
	<p>Cor. is located 36 lks. E. of a N. and S. fence line.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
39.74	<p>The 1/4 sec. cor. of secs. 4 and 5, monumented with an angle iron, 18 ins. long, projecting 6 ins. above the ground, in a mound of stone, 2 ft. base, 6 ins. high. This position is harmoniously related with other identified original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E 1/4 S 5 S 4 1978</p> <p>Deposit the angle iron alongside cor.</p> <p>Rebuild mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>Cor. is located in a N. and S. fence line and 25 lks. E. of a N. and S. track road.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°11' E., beginning new measurement.</p>	
5.70	Faint trail road, bears N. 65° E. and S. 65° W., called for in the original 1875 survey.	
6.50	Telephone line, bears S. 53° E. and N. 53° W.	
10.10	Power line bears S. 53° E. and N. 53° W.	
19.60	Intersection of graded roads extending N., E., SW and a track road extending S.	
39.99	<p>The cor. of secs. 4, 5, 32 and 33, on the N. bdy. of the Tp.</p> <hr style="width: 60%; margin: 10px auto;"/> <p>From the 1/4 sec. cor. of secs. 31 and 32, monumented with a granite stone, 18 x 15 x 9 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on S. face, with mound of stone, 3 ft. base, 2 ft. high, N. of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E 1/4 S31 S32 1978</p> <p>Deposit the mkd. stone alongside the cor.</p> <p>North, bet. secs. 31 and 32.</p> <p>Over rolling land, through medium creosote.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS 39.75	<p>Point for the cor. of secs. 29, 30, 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 29 and 32, monumented with a granite stone, 16 x 12 x 8 ins., firmly set, projecting 8 ins. above ground, mkd. 1/4 on S. face, with mound of stone, 3 ft. base, 1 ft. high, W. of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R25E</p> <p>$\frac{1}{4}$ <u>S29</u></p> <p>4 S32</p> <p>1978</p> </div> <p>Deposit mkd. stone alongside cor.</p> <p>N. 89°21' W., bet. secs. 29 and 32.</p> <p>Over rolling land, through medium mesquite and creosote.</p>
6.00	<p>Wash, 50 lks. wide, 2 ft. deep, drains northerly.</p>
10.00	<p>Track road, bears irregularly N. and S., as scaled from U. S. Geological Quadrangle Map, "Thatcher, Arizona", prepared in 1960.</p>
39.94	<p>The point for the cor. of secs. 29, 30, 31 and 32.</p> <hr/> <p>S. 89°38' W., bet. secs. 30 and 31.</p> <p>Over rolling land, through medium mesquite and creosote.</p>
18.40	<p>Graded road, bears N. 50° E. and S. 50° W.</p>
39.95	<p>The 1/4 sec. cor. of secs. 30 and 31, monumented with a granite stone, 16 x 10 x 8 ins., firmly set, projecting 10 ins. above the ground, mkd. 1/4 on E. face, with mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R25E</p> <p>$\frac{1}{4}$ <u>S30</u></p> <p>4 S31</p> <p>1978</p> </div> <p>Deposit mkd. stone alongside cor.</p> <p>Cor. is located 3 lks. NW of fence cor., fences extend N. and S. 65° W.</p> <hr/> <p>N. 89°48' W., beginning new measurement.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
38.84	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 20 ins. above the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R24E R25E S25 S30 S36 S31 1967</p>	
	<p>from which the remains of the original bearing trees</p>	
	<p style="padding-left: 40px;">A mesquite stump, 8 ins. diam., bears N. 87 3/4° W., 217 lks. dist., no marks visible.</p>	
	<p style="padding-left: 40px;">A mesquite stump, 7 ins. diam., bears N. 35 1/2° W., 164 lks. dist., no marks visible.</p>	
	<hr/>	
	<p>From the point for the cor. of secs. 29, 30, 31 and 32.</p>	
	<p>N. 0°03' W., bet. secs. 29 and 30.</p>	
	<p>Over rolling land, through medium mesquite and creosote.</p>	
20.00	<p>Graded road, bears N. 40° E. and S. 40° W.</p>	
39.75	<p>The 1/4 sec. cor. of secs. 29 and 30, monumented with a granite stone, 20 x 10 x 8 ins., firmly set, projecting 8 ins. above the ground, mkd. 1/4 on S. face, with mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 10 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E 1/4 S30 S29 1978</p>	
	<p>Deposit mkd. stone alongside cor.</p>	
	<hr/>	
	<p>N. 0°03' E., beginning new measurement.</p>	
3.00	<p>Fence cor., fences extend N. 35° E. and N. 87° W.</p>	
20.06	<p>Point for the N 1/16 sec. cor. of secs. 29 and 30.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E N 1/16 S30 S29 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
40.12	<p>The cor. of secs. 19, 20, 29 and 30, monumented with a mound of stone, 2 ft. base, 1 ft. high. This position is harmoniously related to existing original cors. and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E S19 S20 S30 S29 1978</p>
	<p>From the cor. of secs. 20, 21, 28 and 29.</p> <p>N. 89°49' W., bet. secs. 20 and 29.</p> <p>Over rolling land, through medium mesquite and creosote.</p>
31.90	<p>Graded road, bears N. 35° E. and S. 35° W.</p>
39.82	<p>The 1/4 sec. cor. of secs. 20 and 29, monumented with a mound of stone, 1 1/2 ft. base, 6 ins. high, from which an original bearing tree</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears S. 65° W., 24 lks. dist., no marks visible. (Record S. 65° E.)</p> <p>At the cor. point</p> <p>Set an iron post, 2 ins. long, 2 1/2 ins. diam., 12 ins. in the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E 1 S20 4 S29 1978</p>
	<p>Cor. is located at the S. edge of a wash, 10 lks. wide, 3 ft. deep, drains easterly.</p>
	<p style="text-align: center;">—————</p> <p>N. 89°39' W., beginning new measurement.</p>
15.30	<p>Fence line, bears N. 35° E. and S. 35° W.</p>
19.955	<p>Point for the W 1/16 sec. cor. of secs. 20 and 29.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E W 1/16 S20 S29 1978</p>
	<p>Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 30 lks. S. of a wash, 15 lks. wide, 3 ft. deep, drains N. 70° E.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

	<p>CHAINS 39.91</p>	<p>The cor. of secs. 19, 20, 29 and 30.</p> <hr/> <p>S. 89°59' W., bet. secs. 19 and 30.</p> <p>Over rolling land, through medium mesquite and creosote.</p> <p>40.33 Point for the 1/4 sec. cor. of secs. 19 and 30, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E $\frac{1}{4}$ S19 S30 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.</p> <p>78.73 The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 20 ins. above the ground, in a mound of stone, 3 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E S24 S19 S25 S30 1967</p> <hr/> <p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 0°19' E., bet. secs. 19 and 20.</p> <p>Over rolling land, through scattered mesquite and medium creosote.</p> <p>19.82 Point for the S 1/16 sec. cor. of secs. 19 and 20, not monumented.</p> <p>39.64 The 1/4 sec. cor. of secs. 19 and 20, monumented with a mound of stone, 2 1/2 ft. base, 1 ft. high. This position is harmoniously related to existing original cors. and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E $\frac{1}{4}$ S19 S20 1978</p> <p>Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p> <hr/> <p>N. 1°07' W., beginning new measurement.</p> <p>39.55 Fence line, bears E. and W.</p>
--	-------------------------	--

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
40.08	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a mound of stone, 2 ft. base, 1 ft. high. This position is harmoniously related to existing original cors. and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E S18 S17 S19 S20 1978</p> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
	<p>From the true point for the cor. of secs. 16, 17, 20 and 21.</p> <p>N. 89°53' W., bet. secs. 17 and 20.</p> <p>Over gently rolling land, through scattered mesquite and medium creosote.</p>
2.70	<p>Fence line, bears N. and S. 38 lks. to fence cor., fences extend N., W. and S. 120 lks. to another cor., fences extend N., E. and S. 35° W.</p>
19.97	<p>Point for the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E E 1/16 S17 S20 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 40 lks. N. of an E. and W. fence line.</p>
36.80	<p>Descend from mesa, bears N. 15° E. and S. 15° W.</p>
39.94	<p>The 1/4 sec. cor. of secs. 17 and 20, monumented with a granite stone, 20 x 15 x 10 ins., firmly set, projecting 12 ins. above the ground, mkd. 1/4 on the E. face, with mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, and in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E 1/4 S17 S20 1978</p> <p>Deposit mkd. stone alongside cor.</p>

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS						
	<p>Cor. is located 44 lks. N. of an E. and W. fence line.</p> <hr/> <p>N. 89°51' W., beginning new measurement.</p>					
.90	End of descent.					
39.89	<p>The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. 89°55' W., bet. secs. 18 and 19.</p> <p>Over rolling land, through scattered mesquite and medium creosote.</p>					
39.83	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with a mound of stone, 2 ft. base, 1 ft. high, from which remains of original bearing trees</p> <p style="padding-left: 40px;">A mesquite stump, bears N. 49 3/4° E., 87 lks. dist., no marks visible. (Record 85 lks. dist.)</p> <p style="padding-left: 40px;">A mesquite snag, bears S. 78° W., 73 lks. dist., no marks visible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7S R25E</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding: 0 5px;">1</td><td style="padding: 0 5px;">S18</td></tr> <tr><td style="padding: 0 5px;">4</td><td style="padding: 0 5px;">S19</td></tr> </table> <p>1978</p> </div> <p>Rebuild mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 59 lks. N. of E. and W. fence line.</p> <hr/> <p>S. 89°13' W., beginning new measurement.</p>	1	S18	4	S19	
1	S18					
4	S19					
38.28	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 8 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T7S</p> <p>R24E R25E</p> <table style="margin-left: auto; margin-right: auto;"> <tr><td style="padding: 0 5px;">S13</td><td style="padding: 0 5px;">S18</td></tr> <tr><td style="padding: 0 5px;">S24</td><td style="padding: 0 5px;">S19</td></tr> </table> <p>1967</p> </div> <p>Mound of stone, 2 ft. base, 1 1/2 ft. high, W. of cor.</p> <p>Cor. is located at cor. of fences extending E. and S.</p> <hr/> <p>From the cor. of secs. 17, 18, 19 and 20.</p> <p>N. 0°10' E., bet. secs. 17 and 18.</p> <p>Over gently rolling land, through medium mesquite and creosote.</p>	S13	S18	S24	S19	
S13	S18					
S24	S19					

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
39.60	<p>Point for the 1/4 sec. cor. of secs. 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E 1/4 S18 S17 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
59.40	<p>Point for the N 1/16 sec. cor. of secs. 17 and 18.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E N 1/16 S18 S17 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
78.10	<p>Track road, bears N. 25° E. and S. 25° W.</p>	
79.20	<p>Point for the cor. of secs. 7, 8, 17 and 18, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E S 7 S 8 S18 S17 1978</p>	
	<p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
	<hr/> <p>From the cor. of secs. 8, 9, 16 and 17.</p>	
	<p>S. 89°47' W., bet. secs. 8 and 17.</p>	
	<p>Over gently rolling land, through medium mesquite and creosote.</p>	
4.50	<p>Fence line, bears N. and S.</p>	
39.92	<p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T7S R25E 1/4 S 8 S17 1978</p>	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
59.88	Point for the W 1/16 sec. cor. of secs. 8 and 17. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T7S R25E W 1/16 $\frac{S\ 8}{S17}$ 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
79.00	Track road, bears N. 25° E. and S. 25° W.	
79.84	The cor. of secs. 7, 8, 17 and 18.	
	N. 89°27' W., bet. secs. 7 and 18. Over gently rolling land, through scattered mesquite and medium creosote.	
19.965	Point for the E 1/16 sec. cor. of secs. 7 and 18. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T7S R25E E 1/16 $\frac{S\ 7}{S18}$ 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
30.80	Graded road, bears N. 35° E. and S. 35° W.	
39.93	Point for the 1/4 sec. cor. of secs. 7 and 18, at proportionate dist.; there is no remaining evidence of the original cor. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd. T7S R25E $\frac{1}{4}$ $\frac{S\ 7}{S18}$ 1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
77.50	Power line, bears N. and S.	
78.28	The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp.	
	From the cor. of secs. 7, 8, 17 and 18. N. 0°35' W., bet. secs. 7 and 8.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
	Over nearly level land, through medium mesquite and creosote.	
19.80	Point for the S 1/16 sec. cor. of secs. 7 and 8, not monumented.	
21.20	Graded road, bears E. and W.	
39.60	The 1/4 sec. cor. of secs. 7 and 8, monumented with a granite stone, 18 x 16 x 9 ins., firmly set, and mkd. 1/4 on N. face.	
	At the cor. point	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T7S R25E 1/4 S 7 S 8 1978	
	Deposit the marked stone alongside cor.	
	Cor. is located 75 lks. N. of a faint trail, bears N. 80° E. and S. 80° W., called for in the original 1875 survey.	

	N. 0°25' E., beginning new measurement.	
2.00	Intersection of track roads, extending N., SE and W.	
2.20	Fence line, bears E. and W.	
20.00	Point for the N 1/16 sec. cor. of secs. 7 and 8.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 18 ins. in the ground, with brass cap mkd.	
	T7S R25E N 1/16 S 7 S 8 1978	
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.	
	Cor. is located 25 lks. W. of a track road, bears N. 25° E. and S. 25° W. and 40 lks. E. of a track road, bears N. and S.	
40.00	Point for the cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
	From the cor. of secs. 4, 5, 8 and 9.	
	S. 89°52' W., bet. secs. 5 and 8.	
	Over gently rolling land, through scattered mesquite and creosote.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS		
19.915	Point for the E 1/16 sec. cor. of secs. 5 and 8.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T7S R25E	
	E 1/16 $\frac{S\ 5}{S\ 8}$	
	1978	
	Set a mesquite post, 6 ft. long, 4 ins. diam., 2 ft. in the ground alongside the cor.	
39.83	Point for the 1/4 sec. cor. of secs. 5 and 8, at proportionate dist.; there is no remaining evidence of the original cor.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T7S R25E	
	$\frac{1\ S\ 5}{4\ S\ 8}$	
	1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
44.00	Graded road, bears N. 10° E. and S. 10° W.	
59.75	Point for the W 1/16 sec. cor. of secs. 5 and 8.	
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.	
	T7S R25E	
	W 1/16 $\frac{S\ 5}{S\ 8}$	
	1978	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.	
65.80	Track road, bears NE and SW (scaled).	
79.67	The point for the cor. of secs. 5, 6, 7 and 8.	
	N. 89°21' W., bet. secs. 6 and 7.	
	Over nearly level land, through medium mesquite and creosote.	
34.70	Track road, bears N. and S.	
39.76	Fence line, bears N. and S.	
39.80	Point for the 1/4 sec. cor. of secs. 6 and 7, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.	
41.50	Wash, 40 lks. wide, 4 ft. deep, drains NE.	

Dependent Resurvey of a Portion of Subdivisional Lines,
T. 7 S., R. 25 E., Gila & Salt River Mer., Arizona

CHAINS	
77.30	Power line, bears N. and S.
78.11	The cor. of secs. 1, 6, 7 and 12, on the W. bdy. of the Tp.
	From the point for the cor. of secs. 5, 6, 7 and 8.
	N. 0°04' W., bet. secs. 5 and 6.
	Over nearly level land, through medium mesquite and creosote.
40.00	Point for the 1/4 sec. cor. of secs. 5 and 6, at proportionate dist.; there is no remaining evidence of the original cor., not monumented.
60.00	Point for the N 1/16 sec. cor. of secs. 5 and 6.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.
	T7S R25E N 1/16 S 6 S 5 1978
	Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.
	From this point, a fence cor., bears S. 64° E., 43 lks. dist.; fences extend N., E. and S., around a land fill.
80.09	The cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp.
	Subdivision of Section 5, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona
	From the 1/4 sec. cor. of secs. 5 and 8.
	N. 0°02' W., along the N. and S. center line of sec. 5.
	Over gently rolling land, through medium creosote.
19.93	Point for the C-S 1/16 sec. cor. of sec. 5.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
	T7S R25E C S 1/16 S 5 C 1978
	Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.
	Cor. is located 33 lks. W. of a graded road, bears N. 35° E. and S. 20° W.
39.86	Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 5.

Subdivision of Section 5, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S 5 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 1/2 ft. high, W. of cor.</p>
59.87	Point for the C-N 1/16 sec. cor. of sec. 5, not monumented.
73.80	Telephone line, bears S. 55° E. and N. 55° W.
79.89	The 1/4 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.
	<hr/> <p>From the 1/4 sec. cor. of secs. 4 and 5.</p> <p>N. 89°56'30" W., along the E. and W. center line of sec. 5.</p> <p>Over gently rolling land, through scattered mesquite and dense creosote.</p>
17.00	Graded road, bears N. 40° E. and S. 40° W.
19.87	Point for the C-E 1/16 sec. cor. of sec. 5.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E E 1/16 C ————— C S 5 1978</p> <p>Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, N. of cor.</p>
39.74	The C 1/4 sec. cor. of sec. 5.
51.40	Track road, bears N. 30° E. and S. 30° W.
59.67	Point for the C-W 1/16 sec. cor. of sec. 5.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E W 1/16 C ————— C S 5 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 1/2 ft. high, N. of cor.</p>
79.60	The point for the 1/4 sec. cor. of secs. 5 and 6.
	<hr/> <p style="text-align: center;">NW 1/4, Section 5</p> <hr/>

Subdivision of Section 5, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
<p>20.01</p>	<p>From the C-W 1/16 sec. cor. of sec. 5.</p> <p>N. 0°04' W., along the N. and S. center line of the NW 1/4, sec. 5.</p> <p>Over gently rolling land, through scattered creosote, sage brush and mesquite.</p> <p>Point for the NW 1/16 sec. cor., at intersection with the E. and W. center line of the NW 1/4, sec. 5.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 2 1/2 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E NW 1/16 S 5 1978</p> <p>From this point a fence cor., bears S. 70° W., 94 lks. dist., fences extend N. and W. around a land fill.</p>
<p>40.06</p>	<p>The W 1/16 sec. cor. of secs. 5 and 32, on the N. bdy. of the Tp.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the point for the C-N 1/16 sec. cor. of sec. 5.</p> <p>N. 89°57'30" W., along the E. and W. center line of the NW 1/4, sec. 5.</p> <p>Over nearly level land, through scattered creosote, sage brush and mesquite.</p>
<p>3.50</p>	<p>Track road, bears N. and S.</p>
<p>19.94</p>	<p>The NW 1/16 sec. cor. of sec. 5.</p>
<p>39.87</p>	<p>The N 1/16 sec. cor. of secs. 5 and 6.</p>
<p>Subdivision of Section 7, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona</p>	
<p>19.81</p>	<p>From the 1/4 sec. cor. of secs. 7 and 18.</p> <p>N. 0°00'30" W., along the N. and S. center line of sec. 7.</p> <p>Over nearly level land, through medium creosote, sage brush and mesquite.</p> <p>Point for the C-S 1/16 sec. cor. of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C S 1/16 S 7 C 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 ft. high, W. of cor.</p>

Subdivision of Section 7, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Deposit broken glass at base of cor.</p> <p>Cor. is located 22 lks. W. of an abandoned N. and S. fence line.</p>	
39.62	<p>Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S 7 1978</p> <p>Set a wooden post alongside cor.</p> <p>Cor. is located 48 lks. N. of an E. and W. track road, 15 lks. W. of an abandoned N. and S. fence line, and 137 lks. S. of an E. and W. fence line.</p>	
79.67	<p>The point for the 1/4 sec. cor. of secs. 6 and 7.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 7 and 8.</p> <p>N. 89°24'30" W., along the E. and W. center line of sec. 7.</p> <p>Over gently rolling land, through medium creosote, sage brush and mesquite.</p>	
19.76	<p>Point for the C-E 1/16 sec. cor. of sec. 7, not monumented.</p>	
39.52	<p>The C 1/4 sec. cor. of sec. 7.</p>	
77.10	<p>Power line bears N. and S.</p>	
77.70	<p>Graded road, bears N. and S.</p>	
77.85	<p>The point for the 1/4 sec. cor. of secs. 7 and 12, on the W. bdy. of the Tp.</p> <hr/> <p style="text-align: center;">SE 1/4, Section 7</p> <hr/> <p>From the E 1/16 sec. cor. of secs. 7 and 18.</p> <p>N. 0°17' W., along the N. and S. center line of the SE 1/4, sec. 7.</p> <p>Over nearly level land, through scattered creosote, sage brush and mesquite.</p>	
13.80	<p>Graded road, bears N. 35° E. and S. 35° W.</p>	
19.80	<p>Point for the SE 1/16 sec. cor., at intersection with the E. and W. center line of SE 1/4, sec. 7.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E SE 1/16 S 7 1978</p>	

Subdivision of Section 7, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.
39.60	<p>The point for the C-E 1/16 sec. cor. of sec. 7.</p> <hr/> <p>From the point for the S 1/16 sec. cor. of secs. 7 and 8. N. 89°25'30" W., along the E. and W. center line of the SE 1/4, sec. 7.</p> <p>Over gently rolling land, through medium creosote, mesquite and scattered sage brush.</p>
10.30	Graded road, bears NE curving easterly and SW.
19.855	The SE 1/16 sec. cor. of sec. 7.
39.71	The C-S 1/16 sec. cor. of sec. 7.
Subdivision of Section 8, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona	
39.66	<p>From the 1/4 sec. cor. of secs. 8 and 17. N. 0°07'30" W., along the N. and S. center line of sec. 8.</p> <p>Over gently rolling land, through dense creosote and scattered mesquite.</p> <p>Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S 8 1978</p> <p>from which</p> <p style="padding-left: 40px;">A mesquite, 6 ins. diam., bears N. 65° W., 54 lks. dist., mkd. C 1/4 S8 BT.</p>
41.50	Fence line, bears E. and W.
59.60	Point for the C-N 1/16 sec. cor. of sec. 8, not monumented.
79.54	The 1/4 sec. cor. of secs. 5 and 8.
From the true point for the 1/4 sec. cor. of secs. 8 and 9.	
19.94	<p>S. 89°41' W., along the E. and W. center line of sec. 8.</p> <p>Over gently rolling land, through scattered mesquite and dense creosote.</p> <p>Point for the C-E 1/16 sec. cor. of sec. 8.</p>

Subdivision of Section 8, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E E 1/16 C-----C S 8 1978</p> <p>Set a steel fence post alongside cor.</p> <p>Cor. is located 178 lks. S. of an E. and W. fence line.</p>
39.88	The C 1/4 sec. cor. of sec. 8.
55.10	Graded road, bears N. 25° E. and S. 25° W.
59.99	Point for the C-W 1/16 sec. cor. of sec. 8.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E W 1/16 C-----C S 8 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p> <p>Cor. is located 210 lks. S. of an E. and W. fence line.</p>
78.10	Track road, bears N. 60° W. and S. 60° E. approximately 2 chs., thence southerly.
80.10	The 1/4 sec. cor. of secs. 7 and 8.
	<hr/> <p>NW 1/4, Section 8</p> <hr/>
	<p>From the C-W 1/16 sec. cor. of sec. 8.</p> <p>N. 0°08'30" E., along the N. and S. center line of the NW 1/4, sec. 8.</p> <p>Over nearly level land, through scattered mesquite and dense creosote.</p>
19.97	Point for the NW 1/16 sec. cor., at intersection with the E. and W. center line of the NW 1/4, sec. 8.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E NW 1/16 S 8 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>
39.94	The W 1/16 sec. cor. of secs. 5 and 8.
	<hr/> <p>From the point for the C-N 1/16 sec. cor. of sec. 8.</p>

Subdivision of Section 8, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>S. 89°46' W., along the E. and W. center line of the NW 1/4, sec. 8.</p> <p>Over gently rolling land, through scattered mesquite and medium creosote.</p> <p>8.50 Graded road, bears N. 15° E. and S. 15° W.</p> <p>20.01 The NW 1/16 sec. cor. of sec. 8.</p> <p>40.03 The N 1/16 sec. cor. of secs. 7 and 8.</p>
<p>Subdivision of Section 9, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona</p>	
	<p>From the point for the 1/4 sec. cor. of secs. 9 and 16.</p> <p>N. 0°07' W., along the N. and S. center line of sec. 9.</p> <p>Over dry bed of Allen Reservoir, through medium salt cedar and mesquite.</p> <p>12.40 Dirt dike, bears E. and W., thence over gently rolling land, through medium creosote, sage brush and mesquite.</p> <p>39.77 Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S 9 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>59.59 Point for the C-N 1/16 sec. cor. of sec. 9.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C N 1/16 S 9 C 1978</p> <p>Raise a mound of stone, 2 ft. base, 1 ft. high, W. of cor.</p> <p>79.41 The 1/4 sec. cor. of secs. 4 and 9.</p>
	<p>From the 1/4 sec. cor. of secs. 9 and 10.</p> <p>N. 89°59' W., along the E. and W. center line of sec. 9.</p> <p>Over gently rolling land, through scattered mesquite and dense creosote.</p> <p>19.98 Point for the C-E 1/16 sec. cor. of sec. 9, not monumented.</p>

Subdivision of Section 9, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
26.80	Track road, bears N. 20° E. and S. 20° W.
39.96	The C 1/4 sec. cor. of sec. 9.
79.74	The true point for the 1/4 sec. cor. of secs. 8 and 9.
NE 1/4, Section 9	

From the point for the C-E 1/16 sec. cor. of sec. 9.	
N. 0°13' W., along the N. and S. center line of the NE 1/4, sec. 9.	
Over gently rolling land, through scattered mesquite and medium creosote.	
19.80	Point for the NE 1/16 sec. cor., at intersection with the E. and W. center line of the NE 1/4, sec. 9. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.
T7S R25E NE 1/16 S 9 1978	
Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.	
39.60	The E 1/16 sec. cor. of secs. 4 and 9.

From the point for the N 1/16 sec. cor. of secs. 9 and 10.	
N. 89°55' W., along the E. and W. center line of the NE 1/4, sec. 9.	
Over gently rolling land, through scattered mesquite and medium creosote.	
19.95	The NE 1/16 sec. cor. of sec. 9.
26.00	Track road, bears N. and S. (scaled)
39.89	The C-N 1/16 sec. cor. of sec. 9.
Subdivision of Section 18, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona	

From the 1/4 sec. cor. of secs. 18 and 19.	
N. 0°05'30" E., along the N. and S. center line of sec. 18.	
Over gently rolling land, through medium mesquite and dense creosote.	
39.60	Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 18.

Subdivision of Section 18, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S18 1978</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.</p>
58.60	Track road, bears S. 30° E. and N. 30° W.
59.56	Point for the C-N 1/16 sec. cor. of sec. 18, not monumented.
66.50	Graded road, bears N. 40° E. and S. 55° W. curving westerly.
79.52	The 1/4 sec. cor. of secs. 7 and 18.
	<hr/> <p>From the 1/4 sec. cor. of secs. 17 and 18.</p> <p>N. 89°55' W., along the E. and W. center line of sec. 18.</p> <p>Over rolling land, through medium mesquite and creosote.</p>
19.94	<p>Point for the C-E 1/16 sec. cor. of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E E 1/16 C ————— C S18 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, N. of cor.</p>
39.40	Enter washed area, bears N. 15° E. and S. 15° W.
39.88	The C 1/4 sec. cor. of sec. 18.
42.90	Leave washed area, bears N. 15° E. and S. 15° W., thence through medium creosote.
73.00	Graded road, bears N. 20° E. and S. 20° W.
78.17	The point for the 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.
	<hr/> <p style="text-align: center;">NE 1/4, Section 18</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 18.</p> <p>N. 0°08' E., along the N. and S. center line of the NE 1/4, sec. 18.</p> <p>Over rolling land, through scattered mesquite and medium creosote.</p>
19.88	<p>Poi E. the NE 1/16 sec. cor., at intersection with the center line of the NE 1/4, sec. 18.</p>

BOOK 5115

Subdivision of Section 18, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E NE 1/16 S18 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
39.76	<p>The E 1/16 sec. cor. of secs. 7 and 18.</p> <hr/> <p>From the N 1/16 sec. cor. of secs. 17 and 18.</p> <p>N. 89°40'30" W., along the E. and W. center line of the NE 1/4, sec. 18.</p> <p>Over gently rolling land, through medium mesquite and creosote.</p>	
3.40	Track road, bears N. 5° E. and S. 5° W.	
19.95	The NE 1/16 sec. cor. of sec. 18.	
39.90	The point for the C-N 1/16 sec. cor. of sec. 18.	
	<p>Subdivision of Section 20, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona</p> <hr/>	
	<p>From the 1/4 sec. cor. of secs. 20 and 29.</p> <p>N. 0°24' W., along the N. and S. center line of sec. 20.</p> <p>Over gently rolling land, through medium creosote and mesquite.</p>	
19.94	<p>Point for the C-S 1/16 sec. cor. of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C S 1/16 S20 C 1978</p> <p>Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, W. of cor.</p>	
22.90	Fence line, bears N. 35° E. and S. 35° W.	
39.88	<p>Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 8 ins. in the ground, in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S20 1978</p>	
67.50	Track road, bears N. 30° E. and S. 30° W.	

Subdivision of Section 20, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
69.90	Descend from mesa, edge bears NE and SW.
79.85	The 1/4 sec. cor. of secs. 17 and 20.
<hr/>	
	From the point for the 1/4 sec. cor. of secs. 20 and 21. N. 89°57' W., along the E. and W. center line of sec. 20. Over gently rolling land, through medium creosote and mesquite.
19.925	Point for the C-E 1/16 sec. cor. of sec. 20. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.
	T7S R25E E 1/16 C-----C S20 1978
28.30	Fence line, bears N. 35° E. and S. 35° W.
39.85	The C 1/4 sec. cor. of sec. 20.
57.00	Track road, bears N. 25° E. and S. 25° W.
59.30	Descend from mesa, edge bears N. 25° E. and S. 25° W.
59.555	Point for the C-W 1/16 sec. cor. of sec. 20, not monumented.
62.60	End of descent, thence over rolling land.
79.26	The 1/4 sec. cor. of secs. 19 and 20.
<hr/>	
	SW 1/4, Section 20 <hr style="width: 20%; margin: auto;"/>
	From the W 1/16 sec. cor. of secs. 20 and 29. N. 0°03' W., along the N. and S. center line of the SW 1/4, sec. 20. Over rolling land, through scattered mesquite and medium creosote.
19.88	Point for the SW 1/16 sec. cor., at intersection with the E. and W. center line of the SW 1/4, sec. 20. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T7S R25E SW 1/16 S20 1978
	Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.
34.00	Track road, bears N. 30° E. and S. 30° W.
39.75	The point for the C-W 1/16 sec. cor. of sec. 20.

Subdivision of Section 20, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>From the C-S 1/16 sec. cor. of sec. 20.</p> <p>N. 89°50' W., along the E. and W. center line of the SW 1/4, sec. 20.</p> <p>Over gently rolling land, through medium mesquite and creosote.</p>
2.20	Fence line, bears N. 35° E. and S. 35° W.
19.83	The SW 1/16 sec. cor. of sec. 20.
31.00	Track road, bears N. 30° E. and S. 30° W.
31.20	Descend from mesa, edge bears N. 30° E. and S. 30° W.
34.20	End of descent, thence over rolling land.
39.66	The point for the S 1/16 sec. cor. of secs. 19 and 20.
<p>Subdivision of Section 30, T. 7 S., R. 25 E., Gila and Salt River Meridian, Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°18' W., along the N. and S. center line of sec. 30.</p> <p>Over gently rolling land, through medium creosote and mesquite.</p>
40.04	<p>Point for the C 1/4 sec. cor., at intersection with the E. and W. center line of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C 1/4 S30 1978</p> <p>Raise a mound of stone, 3 1/2 ft. base, 2 ft. high, W. of cor.</p> <p>Cor. is located 95 lks. W. of a N. and S. fence line.</p>
47.90	Fence line, bears W. and E., 130 lks. to a fence cor., from which fences extend E., S. and W.
60.075	<p>Point for the C-N 1/16 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T7S R25E C N 1/16 S30 C 1978</p>
80.11	The 1/4 sec. cor. of secs. 19 and 30.

Subdivision of Section 30, T. 7 S., R. 25 E.,
Gila and Salt River Meridian, Arizona

CHAINS	<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 89°56' W., along the E. and W. center line of sec. 30.</p> <p>Over gently rolling land, through dense mesquite and creosote.</p> <p>40.09 The C 1/4 sec. cor. of sec. 30.</p> <p>78.75 The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp., monumented with an iron post, 2 1/2 ins. diam., projecting 10 ins. above the ground, mound of stone 3 ft. base, 2 ft. high, W. of cor., with brass cap mkd.</p> <p style="text-align: center;">T7S R24E R25E 1/4 S25 S30 1967</p>
	<p>GENERAL DESCRIPTION</p> <p>The land encompassed in this survey is located about 2 miles southwest of Thatcher, Arizona. The general elevation ranges from about 2940 to 3600 ft. above sea level. The soil is a sandy, rocky loam.</p> <p>Access is by way of U. S. Highway No. 70 which crosses the north-east corner of the township in a SE and NW direction, paralleled by the Southern Pacific Railroad. There are several unimproved or lightly gravelled roads throughout the township.</p> <p>The vegetation consists of mesquite, creosote, sage brush and cacti.</p> <p>There is no evidence of mining activity or minerals.</p>

Form 9180-8
(March 1969)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
John P. Bennett III	Surveying Technician
Duane R. Ferneau	Survey Aid
Jay D. Lytle	Survey Aid
John J. Bulinski	Survey Aid

CERTIFICATE OF SURVEY

(I) ~~(We)~~, Paul L. Reeves, Cadastral Surveyor, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 15th day of February, 1978, (I) ~~(We)~~ have dependently resurveyed a portion of the north and west boundaries, subdivisional lines and surveyed subdivisions in sections 5, 7, 8, 9, 18, 20 and 30, Township 7 South, Range 25 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

6-04-79 (Date) Paul L. Reeves (Cadastral Surveyor)
 _____ (Date) _____ (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
~~Washington, D.C.~~
 Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north and west boundaries, subdivisional lines and a survey of subdivisions in sections 5, 7, 8, 9, 18, 20 and 30, Township 7 South, Range 25 East, Gila and Salt River Meridian, Arizona

executed by Paul L. Reeves, Cadastral Surveyor having been critically examined and found correct, are hereby approved.

MAR 28 1980 (Date) Gary S. Speight (Chief, Division of Cadastral Survey)
 Acting Chief, Cadastral Survey Examination and Approval Staff

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

_____ (Date) _____ (Chief, Division of Cadastral Survey) GPO 849-626