

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES

AND

A PORTION OF THE SUBDIVISION LINES WITHIN SECTIONS 13, 14, AND 22

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES

WITHIN SECTIONS 13, 14, 19, 20, 21, AND 28,

AND

THE METES-AND-BOUNDS SURVEY OF TRACTS 40 THROUGH 43,

TOWNSHIP 8 SOUTH, RANGE 17 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

RAY HARPIN

CADASTRAL SURVEYOR

DOUGLAS A. CODY

CADASTRAL SURVEYOR

Under special instructions dated OCTOBER 14, 19 69, approved OCTOBER 27, 1969,
SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED NOVEMBER 20, 1969, APPROVED NOVEMBER 21,
1969, AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED SEPTEMBER 5, 1979, APPROVED
SEPTEMBER 13, 1979, which provided for the surveys included under ~~XXXXXX~~ Group
Number 517, and assignment instructions dated OCTOBER 14, 19 69.

Survey commenced NOVEMBER 12, 19 69

Survey completed SEPTEMBER 21, 19 79

1A

BOOK 5 1 1 9

INDEX DIAGRAM

Township 8 SOUTH, Range 17 WEST

6	5	4	3	2	1
7	8	9	10	11	12
18	17	16	15	14	13
24	23	20	14	9	2
22	20 19	21 12	22 6	23	24
30	29 16	28 10	27	26	25
		15			
31	32	33	34	35	36

Dependent Resurvey of Subdivision Lines

- Section 13 . . . p. 25
- Section 14 . . . p. 32
- Section 22 . . . p. 28

Metes-and-Bounds Survey of Parcels within

- Section 14 . . . p. 34
- Section 20 . . . p. 38
- Section 21 . . . p. 44

Survey of Subdivision Lines

- Section 13 . . . p. 33
- Section 19 . . . p. 35
- Section 20 . . . p. 36
- Section 21 . . . p. 40
- Section 28 . . . p. 47

Metes-and-Bounds Survey

- Tract 40 . . . p. 49
- Tract 41 . . . p. 51
- Tract 42 . . . p. 53
- Tract 43 . . . p. 55

Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision lines within secs. 13, 14, and 22 inclusive; the survey of a portion of the subdivision lines within a number of sections, and the metes-and-bounds survey of Tracts 40 through 43 inclusive, Township 8 South, Range 17 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The exterior boundaries and subdivisional lines of this township were surveyed by John L. Harris, U. S. Deputy Surveyor, in 1878, as shown upon the official plat examined and approved April 1, 1878. A portion of the subdivisional lines were dependently resurveyed; a portion of the subdivision lines within sections 13 and 22 were surveyed, and the metes-and-bounds survey of Tracts 37, 38, and 39 were surveyed by Clark Gumm, Cadastral Engineer, in 1952, as shown upon the official plat accepted July 7, 1952. A portion of the subdivisional lines were dependently resurveyed; a portion of the subdivision lines within a number of sections were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952, as shown upon the official plat, examined and approved by the Bureau of Reclamation, Washington, D. C. July 17, 1953, and was accepted by the Chief, Branch of Surveys, Bureau of Land Management, July 17, 1953. A portion of the subdivision lines were dependently resurveyed; a portion of the subdivision lines within section 29 were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Bureau of Reclamation, Washington, D. C., November 5, 1956, and was accepted by the Chief, Branch of Surveys, Bureau of Land Management, November 5, 1956. A portion of the subdivisional lines were dependently resurveyed; a portion of the subdivision lines within section 19 were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Bureau of Reclamation, Washington, D. C., November 5, 1956, and was accepted by the Chief, Branch of Surveys, Bureau of Land Management, November 5, 1956.

These dependent resurveys and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 and 1973 Editions, and the Special Instructions dated October 14, 1969, and Supplemental Special Instructions dated November 20, 1969, and Supplemental Special Instructions dated September 5, 1979.

The direction of all lines of these surveys were determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Directions are expressed in chains.

Prior to the restoration of any corner, all necessary lines of the original survey were retraced and a diligent search was made for any evidence of the original corner monuments and calls of the official record. Identified corners were remonumented in their original positions. Lost corners were reestablished at proportionate positions, but not until exhausting every reasonable possibility of finding direct evidence of the control of each corner.

Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

The geographic position of the corner of secs. 27, 28, 33, and 34, determined by scaling from a U. S. Geological Survey Quadrangle Map, 7 1/2 minute series "Wellton Mesa, Arizona, 1965", is as follows: Latitude 32° 41.6' N., and Longitude 114° 00.2' W. The mean magnetic declination is 14° East.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
John L. Harris, U. S. Deputy Surveyor
in 1878

The 1/4 sec. cor. of secs. 13 and 24 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

1/4 $\frac{S\ 13}{S\ 24}$

1949

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

S. 89° 11' W., between secs. 13 and 24

Over nearly level land.

19.915 The point for the west 1/16 sec. cor. of secs. 13 and 24. I did not monument this corner point.

38.22 Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 5, Tract 40.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W
TR 40 /
 $\frac{AP\ 5\ / \ S\ 13}{S\ 24}$

1975

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS								
39.83	<p>The corner of secs. 13, 14, 23, and 24 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">S 24</td> </tr> </table> 1949 </p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952.</p>	S 14	S 13	S 23	S 24			
S 14	S 13							
S 23	S 24							
20.00	<p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer Bureau of Reclamation, in 1952</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 26.7' W., between secs. 13 and 14</p> <p>The south 1/16 sec. cor. of secs. 13 and 14 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION S 1/16 <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> </table> 1950 </p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952.</p>	S 14	S 13					
S 14	S 13							
8.76	<p>N. 0° 26.7' W., beginning new measurement</p> <p>The point for Angle Point No. 3, Tract 40</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R17W <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">S 13</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">AP 3</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;"></td> <td style="padding: 0 5px;">TR 40</td> </tr> </table> 1970 </p>	S 14	S 13		AP 3		TR 40	
S 14	S 13							
	AP 3							
	TR 40							

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

20.005 The point for the 1/4 sec. cor. of secs. 13 and 14 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W
1/4
S 14 | S 13

1970

In the 1952 survey this corner was designated to function for Angle Point No. 3, Tract 37. The area of Tract 37, and lot No. 1 within section 13 has remained vacant (United States ownership). The description, Tract No. 37 and lot No. 1 within section 13, and the corners controlling the position of this Tract and lot are voided by this survey. New descriptions of Tract 40, and lots 2 through 6 inclusive within section 13 are described in this survey.

Restoring the Survey Executed by
Clark Gumm, Cadastral Engineer
in 1952

N. 0° 26.7' W., beginning new measurement

20.005 The north 1/16 sec. cor. of secs. 13 and 14 is marked with an iron pipe, 1-inch in diam., with brass cap 11 ins. below the surface of the ground, mkd.

BUREAU OF RECLAMATION
N 1/16
S 14 | S 13

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952. In that survey this corner was designated to function for Angle Point No. 2, Tract 37. The area of Tract 37, and lot No. 1 within section 13 has remained vacant (United States ownership). The description, Tract No. 37 and lot No. 1 within section 13, and the corners controlling the position of this Tract and lot are voided by this survey. New descriptions of Tract 40, and lots 2 through 6 inclusive within section 13 are described in this survey.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>N. 0° 26.7' W., beginning new measurement</p> <p>20.00 The corner of secs. 11, 12, 13, and 14 is marked with an iron pipe, 2 ins. in diam., with brass cap 19 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION S 11 S 12 ----- S 14 S 13</p> <p style="text-align: center;">1941</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A cross (+) chiseled on concrete headwall, near the north end of a lateral, bears S. 52° 45' W., 58 ft. distant, mkd. + R P 58.</p> <p style="padding-left: 40px;">A cross (+) chiseled on concrete headwall, near the south end of a lateral, bears N. 53° 45' W., 58 ft. distant, mkd. + R P 58.</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952.</p> <p>Discontinue the regular order of survey at this corner.</p>	
	<p>The 1/4 sec. cor. of secs. 12 and 13 is marked with an iron pipe, with brass cap missing, 36 ins. long, 1-inch in diam., with the top flush with the surface of the ground; this corner marker is accepted as the best available evidence of the position of the corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R17W S 12 1/4 ----- S 13</p> <p style="text-align: center;">1970</p> <p>Deposit the iron pipe corner marker alongside the iron post.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>S. 89° 12' W., between secs. 12 and 13</p> <p>Over nearly level land.</p> <p>39.955 The corner of secs. 11, 12, 13, and 14, heretofore described.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

Discontinue the regular order of survey at this corner.

Restoring the Survey Executed by
John L. Harris, U. S. Deputy Surveyor
in 1878

The corner of secs. 22, 23, 26, and 27 is marked with an iron pipe, 2 ins. in diam., with brass cap 19 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

S 22	S 23
S 27	S 26

1941

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

This corner is located near the intersection of roads, bearing north - south and east - west.

N. 0° 47' E., between secs. 22 and 23

Over nearly level land, along a north and south road.

39.96

The 1/4 sec. cor. of secs. 22 and 23 is marked with an iron pipe, with brass cap missing, 36 ins. long, 1-inch in diam., with the top 3 ins. below the surface of the road. This corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952. In that survey this corner was designated to function for Angle Point No. 7, Tract 39. The area of Tract 39, and lots 1 and 2 within section 22 has remained vacant (United States ownership). The description, Tract No. 39 and lots 1 and 2 within section 22, and the corners controlling the position of this Tract and these lots are voided by this survey. New descriptions of Tract 41, and lots 5 through 13 inclusive within section 22 are described in this survey.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S R17W
1/4

S 22 | S 23

1970

Deposit the iron pipe corner marker alongside the iron post.

from which

An iron post 28 ins. long, 2½ ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 46° 45' W., 44 ft. distant, with brass cap mkd. RM T8S R17W S 22 44 FT 1970, and an arrow pointing to the corner.

There are no suitable accessories nor locations available for other reference monuments.

Restoring the Survey Executed by
Clark Gumm, Cadastral Engineer
in 1952

N. 0° 47.7' E., beginning new measurement

3.69 Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 10, Tract 41.

Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., with brass cap, 1½ ins. in diam., flush with the surface of the road, mkd.

T8S R17W
TR 41 |
AP 10 |
S 22 | S 23

1975

18.89 Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 1, Tract 41

Set a copper-coated steel stake, 30 ins. long, 1/2-inch in diam., with brass cap, 1½ ins. in diam., flush with the surface of the road, mkd.

T8S R17W
S 22 | S 23
AP 1 |
TR 41 |


1975

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

19.985 The point for the north 1/16 sec. cor. of secs. 22 and 23 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.




1970

There are no suitable accessories nor locations available for reference monuments.

In the 1952 survey this corner was designated to function for Angle Point No. 1, Tract 39. The area of Tract 39, and lots 1 and 2 within section 22 has remained vacant (United States ownership). The description, Tract No. 39 and lots 1 and 2 within section 22, and the corners controlling the position of this Tract and these lots are voided by this survey. New descriptions of Tract 41, and lots 5 through 13 inclusive within section 22 are described in this survey.

32.17 The point for Angle Point No. 9, Tract 38 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.



1970

There are no suitable accessories nor locations available for reference monuments.

39.97 The corner of secs. 14, 15, 22, and 23 is marked with the remains of an iron pipe, with brass cap missing, 30 ins. long, 2 ins. in diam., with the top, 9 ins. below the surface of the road. This corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952. In that survey this corner was designated to function for Angle Point No. 1, Tract 38.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S R17W
S 15 | S 14
S 22 | S 23

1970

Deposit the iron pipe corner marker inside the iron post.
This corner is located on the center line of a north and south road.

Restoring the Survey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation, in 1952

From the corner of secs. 13, 14, 23, and 24, heretofore described.

S. 89° 16' W., between secs. 14 and 23

Over nearly level land.

17.97 Intersect the arc of a curve, hereinafter described, the point for Corner No. 4, Parcel A of section 14.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W
S 14
PAR B / PAR A
COR 4
S 23

1975

19.76 The east 1/16 sec. cor. of secs. 14 and 23 is marked with an iron pipe, 1-inch in diam., with brass cap flush with the surface of the ground, mkd.

BUREAU OF RECLAMATION
E 1/16
S 14
S 23

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952.

Discontinue the regular order of survey at this corner.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

Restoring The Survey Executed by
John L. Harris, U. S. Deputy Surveyor
in 1878

The corner of secs. 27, 28, 33, and 34 is marked with an iron pipe, 1-inch in diam., with the brass cap 12 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
T8S R17W
S 28 | S 27
S 33 | S 34

1941

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

This corner is located on the center line of a north and south road.

N. 0° 16' W., between secs. 27 and 28

Over nearly level land, along the center line of a north and south roadway.

20.08 The south 1/16 sec. cor. of secs. 27 and 28 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, mkd.

BUREAU OF RECLAMATION
S 1/16
S 28 | S 27

1950

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 0° 16' W., beginning new measurement

2.70 The right bank of the Mohawk Canal, flows S. 88° E.

3.60 The left bank of the Mohawk Canal.

20.08 The 1/4 sec. cor. of secs. 27 and 28 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set, with brass cap flush with the surface of the ground, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

1/4
S 28 | S 27

1941

The above corner marker is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W

1/4
S 28 | S 27

1970

Deposit the iron pipe corner marker alongside the iron post.

N. 0° 16' W., beginning new measurement

20.08 The north 1/16 sec. cor. of secs. 27 and 28 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

N 1/16
S 28 | S 27

1950

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 0° 16' W., beginning new measurement

20.08 The corner of secs. 21, 22, 27, and 28 is marked with an iron pipe, 2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

S 21	S 22
S 28	S 27

1941

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952.

This corner is located on the center line of an east and west road.

Discontinue the regular order of survey at this corner.

Restoring the Survey Executed by
Clark Gumm, Cadastral Engineer
in 1952

NORTH, between secs. 21 and 22

Over rolling land.

19.93 The south 1/16 sec. cor. of secs. 21 and 22 is marked with a wood post, 17 ins. long, 2 x 3 ins., firmly set 11 ins. in the ground, mkd. S 22 on the east, C 1949 on the south; and is accepted as the position of the corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

S 1/16	
S 21	S 22

1970

Deposit the wood post corner marker alongside the iron post.

NORTH, beginning new measurement

2.12 Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 5, Tract 41 and Angle Point No. 7, Tract 42.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W TR 42 TR 41 AP 7 AP 5</p> <hr style="width: 100%; border: 0.5px solid black;"/> <p>S 21 S 22</p> <p>1975</p> </div>	
17.29		<p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 4, Tract 41 and Angle Point No. 1, Tract 42.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W S 21 S 22</p> <hr style="width: 100%; border: 0.5px solid black;"/> <p>AP 1 AP 4 TR 42 TR 41</p> <p>1975</p> </div>	
19.94		<p>The 1/4 sec. cor. of secs. 21 and 22 is marked with an iron pipe, 1-inch in diam., firmly set projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION 1/4 S 21 S 22</p> <p>1949</p> </div> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952.</p> <div style="text-align: center; border-top: 1px solid black; border-bottom: 1px solid black; padding: 10px;"> <p>Restoring the Survey Executed by Albin H. Wadin, Engineer Bureau of Reclamation, in 1952</p> </div>	
19.94		<p>NORTH, beginning new measurement</p> <p>The north 1/16 sec. cor. of secs. 21 and 22 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

N 1/16

S 21 | S 22

1952

NORTH, beginning new measurement

19.94 The corner of secs. 15, 16, 21, and 22 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

S 16		S 15
S 21		S 22

1941

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952.

Restoring the Survey Executed by
Clark Gumm, Cadastral Engineer
in 1952

From the corner of secs. 14, 15, 22, and 23, heretofore described.

S. 89° 24' W., between secs. 15 and 22

Over nearly level land

20.33 The point for the east 1/16 sec. cor. of secs. 15 and 22 is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.

40.66 The 1/4 sec. cor. of secs. 15 and 22 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S R17W 1/4 $\frac{S\ 15}{S\ 22}$ 1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> <p>This corner is located on the center line of an east and west road.</p>	
60.99	<p>The point for the west 1/16 sec. cor. of secs. 15 and 22 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 15}{S\ 22}$ 1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> <p>This corner is located on the center line of an east and west road.</p>	
	<hr/> <p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer Bureau of Reclamation, in 1952</p> <hr/> <p>S. 89° 24' W., beginning new measurement</p> <p>20.33 The corner of secs. 15, 16, 21, and 22, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p style="text-align: center;">Restoring the Survey Executed by John L. Harris, U. S. Deputy Surveyor in 1878</p> <hr/> <p>From the corner of secs. 27, 28, 33, and 34, heretofore described.</p> <p>S. 89° 34' W., between secs. 28 and 33</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	Over nearly level land	
20.18	The east 1/16 sec. cor. of secs. 28 and 33 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 15 ins. above the surface of the ground, with brass cap mkd.	
	BUREAU OF RECLAMATION E 1/16 $\frac{S\ 28}{S\ 33}$	
	1950	
	The above corner marker is accepted as the position of the corner. I did not remonument this corner.	
	<hr style="width: 20%; margin: auto;"/> S. 89° 34' W., beginning new measurement	
19.00	The right bank of the Mohawk Canal, flows N. 43° E.	
19.90	The left bank of the Mohawk Canal.	
20.19	The point for the 1/4 sec. cor. of secs. 28 and 33 is determined at proportionate distance; there is no evidence of the original corner.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.	
	T8S R17W 1/4 $\frac{S\ 28}{S\ 33}$	
	1972	
	There are no suitable accessories nor locations available for reference monuments.	
60.57	The corner of secs. 28, 29, 32, and 33 is marked with a steel rod, of undetermined length, 1-inch in diam., with the top 1-inch below the surface of roads; and is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.	
	This corner is located at the intersect of roads, bearing north and south, and west.	
	N. 0° 16' W., between secs. 28 and 29	
	Over nearly level land, along the center line of Avenue 36 East.	
40.47	The 1/4 sec. cor. of secs. 28 and 29 is marked with an iron pipe, 2 ins. in diam., with brass cap 7 ins. below the surface of the road, and is sat in a covered cast-iron survey monument pot, 10 ins. in diam. The above brass cap is marked.	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

1/4
S 29 | S 28

1941

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

This corner is located 10 ft. east of the center line of a north and south road.

From this corner the U. S. Geological Survey Triangulation Station "Antelope" bears N. 57° 49' E., 35.54 chs. distant, and is marked with a regulation brass tablet, 3 1/4 ins. in diam., seated on a stone-in-place, 3 ft. above ground level, mkd. ANTELOPE 1925.

Restoring the Survey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation, in 1952

N. 0° 16' W., beginning new measurement

5.00 Avenue 36 East curves to the northeast; thence, descend over rolling northwest slope.

20.235 The north 1/16 sec. cor. of secs. 28 and 29 is marked with an iron pipe, 1-inch in diam., with brass cap flush with the surface of the ground, mkd.

BUREAU OF RECLAMATION

N 1/16
S 29 | S 28

1950

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952.

N. 0° 16' W., beginning new measurement

17.10 The center line of the Southern Pacific Railroad, bears N. 47° 22' E. and S. 47° 22' W.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
20.245	<p>The corner of secs. 20, 21, 28, and 29 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION $\frac{S\ 20\ S\ 21}{S\ 29\ S\ 28}$</p>	
	<p style="text-align: center;">1941</p>	
	<p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1952.</p>	
	<p style="text-align: center;">Restoring the Survey Executed by John L. Harris, U. S. Deputy Surveyor in 1878</p>	
	<p>From the corner of secs. 21, 22, 27, and 28, heretofore described.</p>	
	<p>S. 89° 59' W., between secs. 21 and 28</p>	
	<p>Over nearly level land.</p>	
20.20	<p>The point for the east 1/16 sec. cor. of secs. 21 and 28</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">E 1/16 $\frac{S\ 21}{S\ 28}$</p>	
	<p style="text-align: center;">1972</p>	
25.00	<p>Base of Antelope Hill, bears north and south; thence, ascend 580 ft. over broken east slope.</p>	
40.40	<p>The 1/4 sec. cor. of secs. 21 and 28 is marked with an iron pipe, 1-inch in diam., firmly set in a mound of stone, 4 ft. base, 2 ft. high, with brass cap mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION $\frac{1/4\ S\ 21}{S\ 28}$</p>	
	<p style="text-align: center;">1941</p>	
	<p>The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	S. 89° 59' W., beginning new measurement	
1.60	Ridge of Antelope Hill, bears north and south, descend 670 ft. over broken west slope.	
18.60	Base of descent, bears north and south; thence, over nearly level land.	
25.50	Road, bears N. 24° E. and S. 24° W.	
36.95	The center line of the Southern Pacific Railroad, bears N. 47° 22' E., and S. 47° 22' W.	
40.40	The corner of secs. 20, 21, 28, and 29, heretofore described.	
	<hr/>	
	N. 0° 49' E., between secs. 20 and 21	
3.15	Roads, bearing N. 30° E. and S. 30° W., and North; thence, along the center line of the above road.	
39.66	The point for the 1/4 sec. cor. of secs. 20 and 21 is determined at proportionate distance; there is no evidence of the original corner. Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.	
	T8S R17W 1/4 S 20 S 21 1970	
51.29	Intersect the arc of a curve, hereinafter, described, the point for Corner No. 1, Parcel B of sec. 20 and Corner No. 3, Parcel A and Corner No. 3, Parcel B of sec. 21. Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.	
	T8S R17W S 20 S 21 PAR A COR 3 COR 1 COR 3 PAR B PAR B 1975	
59.49	The point for the north 1/16 sec. cor. of secs. 20 and 21. I did not monument this corner point.	
74.363	The point for the N - N - N 1/256 sec. cor. of secs. 20 and 21.	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p>	
	<p style="text-align: center;">N N N 1/256</p> <p style="text-align: center;">S 20 S 21</p>	
	<p style="text-align: center;">1970</p>	
79.32	<p>The corner of secs. 16, 17, 20, and 21 is marked with the remains of an iron pipe, 36 ins. long, 2 ins. in diam., with brass cap, 8 ins. below the surface of the road, mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION T8S R17W</p> <p style="text-align: center;">S 17 S 16 ----- S 20 S 21</p>	
	<p style="text-align: center;">1941</p>	
	<p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p>	
	<p>At the corner point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap 11 ins. below the surface of the road, mkd.</p>	
	<p style="text-align: center;">T8S R17W S 17 S 16 ----- S 20 S 21</p>	
	<p style="text-align: center;">1970</p>	
	<p>Deposit the iron pipe corner marker alongside the iron post.</p>	
	<p>There are no suitable accessories nor locations available for reference monuments.</p>	
	<p>From the corner of secs. 15, 16, 21, and 22, heretofore described.</p>	
	<p>S. 89° 43' W., between secs. 16 and 21</p>	
	<p>Over nearly level land.</p>	
3.50	<p>Enter and continue along the center line of 7th Street, from the southeast.</p>	
19.93	<p>The point for the east 1/16 sec. cor. of secs. 16 and 21. I did not monument this corner point.</p>	
23.25	<p>Road, bears N. 26° 30' E. and S. 26° 30' W.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
25.45	The center line of the Southern Pacific Railroad, bears N. 26° 39' E. and S. 26° 39' W.	
39.86	The 1/4 sec. cor. of secs. 16 and 21 is marked with an iron pipe, 1-inch in diam., set in a concrete pipe, 6 ins. in diam., with brass cap flush with the surface of the ground, mkd.	
	$1/4 \frac{S 16}{S 21}$	
	1941	
	The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.	
	<hr style="width: 20%; margin: auto;"/>	
	S. 89° 43' W., beginning new measurement	
19.93	The west 1/16 sec. cor. of secs. 16 and 21 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set, 23 ins. in the ground, with brass cap mkd.	
	BUREAU OF RECLAMATION W 1/16 $\frac{S 16}{S 21}$	
	1950	
	The above corner marker is accepted as the position of the corner.	
	At the corner point	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.	
	W 1/16 $\frac{S 16}{S 21}$	
	1970	
	Deposit the iron pipe corner marker alongside the iron post.	
	<hr style="width: 20%; margin: auto;"/>	
	S. 89° 43' W., beginning new measurement	
19.93	The corner of secs. 16, 17, 20, and 21, heretofore described.	
	Discontinue the regular order of survey at this corner.	
	<hr style="width: 20%; margin: auto;"/>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Survey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

The 1/4 sec. cor. of secs. 19 and 20 is marked with the remains of a wood post, 10 ins. long, approximately 4 ins. square, with the top 7 ins. below the surface of the ground; substantiated by a wood hub, 10 ins. long, 2 ins. square, set over the above corner marker; and is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.

T8S R17W
1/4
S 19 | S 20

1970

Deposit the corner marker and wood hub alongside the iron post.

N. 0° 33' E., between secs. 19 and 20

Over nearly level land.

20.24 The point for the north 1/16 sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.


N 1/16
S 19 | S 20

1970

35.42 The point for Angle Point No. 5, Tract 43 and Corner No. 3, Lot 7 of sec. 19.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S R17W L 7 TR 43 C 3 AP 5</p>  <p style="text-align: center;">1970</p>	
<p>40.48</p>	<p>The corner of secs. 17, 18, 19, and 20 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 7 ins. above the surface of the ground, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R17W <u>S 18 S 17</u> <u>S 19 S 20</u></p> <p style="text-align: center;">1950</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954.</p>	
	<p style="text-align: center;">Restoring the Survey Executed by John L. Harris, U. S. Deputy Surveyor in 1878</p> <hr/> <p>From the corner of secs. 16, 17, 20, and 21, heretofore described.</p> <p>S. 89° 56' W., between secs. 17 and 20</p> <p>Over nearly level land.</p> <p>20.285 The point for the east 1/16 sec. cor. of secs. 17 and 20. I did not monument this corner point.</p> <p>40.57 The 1/4 sec. cor. of secs. 17 and 20 is marked with the remains of an iron pipe, 17 ins. long, 1-inch in diam., with the top 7 ins. below the surface of the ground; and is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R17W 1/4 <u>S 17</u> S 20</p> <p style="text-align: center;">1970</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	Deposit the iron pipe corner marker inside the iron post.	
	<hr/> <p>S. 89° 56' W., beginning new measurement</p>	
18.92	The point for Angle Point No. 3, Tract 43	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<div style="text-align: center;"> <p>T8S R17W S 17 AP 3 / S 20 TR 43</p> </div>	
	1970	
20.24	The west 1/16 sec. cor. of secs. 17 and 20 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.	
	<div style="text-align: center;"> <p>BUREAU OF RECLAMATION W 1/16 S 17 S 20</p> </div>	
	1950	
	The above corner marker is accepted as the position of the corner. I did not remonument this corner.	
	<hr/> <p>S. 89° 56' W., beginning new measurement</p>	
20.22	The corner of secs. 17, 18, 19, and 20, heretofore described.	
	<div style="text-align: center;"> <p>Restoring the Survey Executed by Albin H. Wadin, Engineer Bureau of Reclamation, in 1954</p> </div>	
	<hr/> <p>S. 89° 52' W., between secs. 18 and 19</p>	
	Over nearly level land.	
8.815	The point for Corner No. 2, lot 7 of section 19	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W
S 18
L 8 / C 2
L 7
S 19

1970

20.345 The east 1/16 sec. cor. of secs. 18 and 19 is marked with a iron pipe, 1-inch in diam., firmly set, projecting 15 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

E 1/16

S 18

S 19

1949

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954.

Discontinue the dependent resurvey of the subdivisional lines at this corner.

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
Clark Gumm, Cadastral Engineer
in 1952

Thence, in section 13

The center 1/4 sec. cor. of sec. 13 is marked with a wood post, 40 ins. long, 3 ins. by 4 ins. with the top 11 ins. below the surface of the ground, scribed S 13 on the north and 1/4 on the south. This corner maker was accepted and described in the official field-note record of the survey by Clark Gumm, Cadastral Engineer, in 1952.

At the corner point

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S R17W C 1/4 S 13 1970</p>	
	<p>Deposit the wood post corner marker alongside the iron post.</p> <hr style="width: 20%; margin: 10px auto;"/>	
	<p>N. 0° 20.5' W., on the north and south center line of sec. 13.</p>	
<p>20.00</p>	<p>The point for the center-north 1/16 sec. cor. of sec. 13, which is located within the center of a concrete lined lateral, bears east and west. I did not monument this corner point.</p>	
<p>20.135</p>	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, for the witness center-north 1/16 sec. cor. of sec. 13, with brass cap mkd.</p>	
	<p style="text-align: center;">C N 1/16 S 13 ↓ W C 1970</p>	
<p>40.00</p>	<p>The 1/4 sec. cor. of secs. 12 and 13, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/>	
	<p>From the center 1/4 sec. cor. of sec. 13, heretofore described.</p> <p>S. 89° 10.5' W., on the east and west center line of sec. 13.</p>	
<p>17.15</p>	<p>Intersect line 6 - 1, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T8S R17W TR 40 C / L 2 / L 5 / S 13 1970</p>	

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>From this point of intersection Angle Point No. 1, Tract 40, hereinafter described, bears N. 26° 23' E., 22.49 chs. distant.</p> <p>Continue on the east and west center line of sec. 13 and on a blank line across Tract 40</p>	
19.95	The point for the center-west 1/16 sec. cor. of sec. 13. I did not monument this corner point.	
34.19	<p>Intersect line 2 - 3, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W L 3 C — C TR 40 L 4 S 13</p> </div> <p>1970</p>	
	<p>From this point of intersection Angle Point No. 2, Tract 40, hereinafter described, bears N. 26° 23' E., 22.49 chs. distant.</p> <p>Continue on the east and west center line of sec. 13.</p>	
35.46	<p>The point for Angle Point No. 4, Tract 37 is determined at proportionate distance; there is no evidence of the original corner. The above Angle Point was established by Clark Gumm, Cadastral Engineer, in 1952. The area of Tract 37, and lot No. 1 within section 13 has remained vacant (United States ownership). The description, Tract No. 37 and lot No. 1 within section 13, and the corners controlling the position of this Tract and this lot are voided by this survey. New descriptions of Tract 40, and lots 2 through 6 inclusive within section 13 are described in this survey.</p> <p>From the above corner point a diligent search was made for any evidence of Angle Points Nos. 5 and 6, Tract 37, and none was found.</p>	
39.89	<p>The 1/4 sec. cor. of secs. 13 and 14, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the true point for the center-north 1/16 sec. cor. of sec. 13, heretofore described.</p> <p>S. 89° 10.5' W., on the east and west center line of the northwest quarter of sec. 13</p>	

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Over nearly level land, along the center line of a lateral.</p>	
0.35	<p>Leave the above lateral, bears to the northwest.</p>	
0.55	<p>Lateral, bears northwest and southeast; thence, continue over nearly level land.</p>	
7.03	<p>The point for Angle Point No. 1, Tract 40.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;"> T8S R17W S 13 AP 1 / L 2 TR 40 1970 </p>	
24.07	<p>The point for Angle Point No. 2, Tract 40</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;"> T8S R17W S 13 AP 2 TR 40 1970 </p>	
25.12	<p>Angle Point No. 1, Tract 37 is marked with an iron pipe, 36 ins. long, 1-inch in diam., loosely set 22 ins. in the ground, with brass cap mkd. BUREAU OF RECLAMATION T8S R17W S 13 AP 1 TR 37 1952.</p>	
	<p>The above corner was established by Clark Gumm, Cadastral Engineer, in 1952. I destroyed this corner. The area of Tract No. 37 and lot 1, section 13 have remained vacant (United States ownership). The description, Tract No. 37 and lot 1, section 13 and the corners controlling the position of the above tract and lot are voided by this survey. New descriptions (hereinafter described) of Tract 40, and lots 2 through 6 inclusive within section 13 are described in this survey.</p>	
39.92	<p>The north 1/16 sec. cor. of secs. 13 and 14, heretofore described.</p>	
	<p>Thence, in section 22</p>	
	<p>The 1/4 sec. cor. of secs. 22 and 27 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p>	



Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>BUREAU OF RECLAMATION</p> <p>1/4 $\frac{S\ 22}{S\ 27}$</p> <p>1941</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Clark Gumm, Cadastral Engineer, in 1952.</p> <hr/> <p>N. 0° 24.8' E., on the north and south center line of sec. 22.</p> <p>Over nearly level land, along the center line of a concrete lined lateral.</p>
19.953	The point for the center-south 1/16 sec. cor. of sec. 22. I did not monument this corner point.
26.50	End of lateral; on top of a bench, bearing east and southwest; thence, descend over steep north slope.
29.00	Base of descent; thence, over nearly level bottom land.
30.375	The point for Angle Point No. 7, Tract 41.
	Set an iron post, 28 ins. long, 2½ ins. in diam., 25 ins. in the ground, with brass cap mkd.
	<p>T8S R17W</p> <p style="margin-left: 100px;">C</p> <p style="margin-left: 80px;">TR 41 S 22</p> <p style="margin-left: 80px;">AP 7 </p> <p style="margin-left: 100px;">C</p> <p>1975</p>
39.905	The center 1/4 sec. cor. of sec. 22 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.
	<p>BUREAU OF RECLAMATION</p> <p>C 1/4</p> <p>S 22</p> <p>1949</p> <p>The above corner marker was accepted and described in the official field-note record of the survey by Clark Gumm, Cadastral Engineer, in 1952.</p> <p>This corner is designated to function for Angle Point No. 8, Tract 41.</p> <hr/> <p>N. 0° 24.8' E., beginning new measurement</p>

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Continue on the north and south center line of sec. 22, and on a blank line across (hereinafter described) Tract 41.</p>
7.08	<p>Intersect line 2 - 3, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W</p> <p>C</p> <p>S 22</p> <p>—/—</p> <p>C</p> <p>TR 41</p> <p>1975</p> </div> <p>From this point of intersection Angle Point No. 2, Tract 41, hereinafter described, bears N. 66° 13.5' E., 13.055 chs. distant.</p> <p>Continue on the north and south center line of sec. 22.</p>
14.555	<p>Angle Point No. 3, Tract 39 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 28 ins. in the ground, with brass cap mkd. BUREAU OF RECLAMATION T8S R17W S 22 AP 3 TR 39 1952.</p> <p>The above corner was established by Clark Gumm, Cadastral Engineer, in 1952. I destroyed this corner. The area of Tract No. 39 and lots 1 and 2 within section 22 has remained vacant (United States ownership). The description, Tract No. 39, and lots Nos. 1 and 2 within section 22, and the corners controlling the position of this tract and these lots are voided by this survey. New descriptions of Tract 41 and lots 5 through 13 inclusive within section 22 are described in this survey.</p> <p>From the above corner point a diligent search was made for any evidence of Angle Points Nos. 2 and 4, Tract 39, and none was found.</p>
19.953	<p>The point for the center-north 1/16 sec. cor. of sec. 22. I did not monument this corner point.</p>
35.21	<p>The point for Angle Point No. 5, Tract 38 is determined at record course and record distance; there is no evidence of the original corner. I did not monument this corner point.</p> <p>Continue on the north and south center line of sec. 22, and on a blank line across Tract 38.</p>
39.905	<p>The 1/4 sec. cor. of secs. 15 and 22, heretofore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 22 and 23, heretofore described.</p> <p>S. 89° 27.8' W., on the east and west center line of sec. 22.</p>

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
17.94	<p>Intersect the arc of a curve, hereinafter described. The point for Angle Point No. 9, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W TR 41 AP 9  S 22</p> <p>1975</p> </div> <p>Continue on the east and west center line of sec. 22.</p>	
20.19	<p>The point for the center-east 1/16 sec. cor. of sec. 22. I did not monument this corner point.</p>	
40.38	<p>The center 1/4 sec. cor. of sec. 22, which is designated to function for Angle Point No. 8, Tract 41, heretofore described.</p> <hr style="width: 30%; margin: 10px auto;"/> <p>S. 89° 27.8' W., beginning new measurement</p> <p>Continue on the east and west center line of sec. 22, and on a blank line across (hereinafter described) Tract 41.</p>	
17.63	<p>Intersect the arc of a curve, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W S 22 C  C TR 41</p> <p>1975</p> </div> <p>Continue on the east and west center line of sec. 22.</p>	
20.19	<p>The center-west 1/16 sec. cor. of sec. 22 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION C W 1/16 S 22</p> <p>1952</p> </div> <p>The above corner was established by Clark Gumm, Cadastral Engineer, in 1952. In that survey this corner was designated to function for Angle Point No. 6, Tract 39. The area of Tract 39, and lots 1 and 2 within section 22 has remained vacant (United States ownership). The description, Tract No. 39 and lots 1 and 2 within section 22, and the corners controlling the position of this tract and these lots are voided by this survey. New descriptions of Tract 41, and lots 5 through 13 inclusive within section 22 are described in this survey.</p> <hr style="width: 30%; margin: 10px auto;"/>	

Dependent Resurvey of a Portion
of the Subdivision Lines
Within Sections 13 and 22
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

S. 89° 27.8' W., beginning new measurement

20.19 The 1/4 sec. cor. of secs. 21 and 22, heretofore described.

Dependent Resurvey of a Portion
of the Subdivision Lines Within Section 14
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona


Restoring the Survey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation, in 1952

From the east 1/16 sec. cor. of secs. 14 and 23, heretofore described.

N. 0° 34.7' W., on the north and south center line of the southeast quarter of sec. 14

2.59 Angle Point No. 3, lot 1 and Angle Point No. 3, lot 2 of sec. 14 is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 30 ins. in the ground, with brass cap mkd.

BUREAU OF RECLAMATION




1952

The area of lots 1 and 2 of section 14 having been acquired (United States ownership). The description and lot No. 1 within section 14 are voided by this survey. New descriptions of Parcels A and B within section 14 are described in this survey.

At the corner point, which is designated to function for a corner of Parcel B. of section 14.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.



1975

Dependent Resurvey of a Portion
of the Subdivision Lines Within Section 14
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS

Deposit the iron pipe corner marker alongside the iron post.


Discontinue the dependent resurvey of this subdivision line at this corner.

From the south 1/16 sec. cor. of secs. 13 and 14, heretofore described.

S. 89° 17' W., on the east and west center line of the southeast quarter of sec. 14.

4.44 The point for Corner No. 2, Parcel A and a corner of Parcel B of section 14

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.



1975

8.54 Angle Point No. 2, lot 1 and Angle Point No. 1, lot 2 of sec. 14 is marked with an iron pipe, with brass cap missing, 1-inch in diam., with the top 15 ins. below the surface of the ground. I did not remonument this corner.

The area of lots 1 and 2 of section 14 having been acquired (United States ownership). The descriptions and lot No. 1 within section 14 are voided by this survey. New descriptions of Parcels A and B within section 14 are described in this survey. This Corner is designated to function for a corner of Parcel B of section 14.

This corner is located at the intersection of roads, bearing north and west.

Discontinue the dependent resurvey of this subdivision line at this corner.

The Survey of a Portion of the Subdivision Lines
Within Sections 13, 14, 19, 20, 21, and 28
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

Thence, in section 13

From the 1/4 sec. cor. of secs. 13 and 24, heretofore described.

N. 0° 21' W., on the north and south center line of sec. 13.

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS

20.00 The point for the center-south 1/16 sec. cor. of sec. 13
 Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins.
 in the ground, with brass cap mkd.

C S
 1/16
 S 13

1970

40.00 The center 1/4 sec. cor. of sec. 13, heretofore de-
 scribed.

The Metes-and-Bounds Survey of Parcel A
 Within Section 14
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

Beginning at the South 1/16 sec. cor. of secs. 13 and 14,
 heretofore described, which is designated to function for
 Corner No. 1, Parcel A of sec. 14.

S. 89° 17' W., on line 1 - 2, Parcel A of sec. 14, which
 is identical with the east and west center line of the
 southeast quarter of sec. 14.

4.44 Corner No. 2, Parcel A which is identical with a corner
 of Parcel B of sec. 14, heretofore described.

S. 26° 23' W., on line 2 - 3, Parcel A, which is iden-
 tical with the eastern boundary of Parcel B of sec. 14.

3.95 The point for Corner No. 3, Parcel A which is identical
 with a corner of Parcel B of sec. 14

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins.
 in the ground, with brass cap mkd.

T8S R17W
 S 14
 PAR B / PAR A
 COR 3

1975

Thence, on line 3 - 4, Parcel A which is identical with
 the eastern boundary of Parcel B of sec. 14, along the
 arc of a curve, curve data:



The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Chord bears S. 34° 56' W. Chord length 20.29 chs. distant Radius 68.18 chs. distant Length of arc 20.36 chs. distant</p> <p>At the end of the arc of the curve, Corner No. 4, Parcel A, which is identical with a corner of Parcel B of sec. 14, heretofore described.</p> <hr/> <p>N. 89° 16' E., on line 4 - 5, Parcel A of sec. 14, which is identical with the section line between secs. 14 and 23.</p>	
	17.97	<p>The corner of secs. 13, 14, 23, and 24, heretofore described, which is designated to function for Corner No. 5, Parcel A of sec. 14.</p> <hr/> <p>N. 0° 26.7' E., on line 5 - 1, Parcel A of sec. 14, which is identical with the section line between secs. 13 and 14.</p>	
	20.00	<p>The south 1/16 sec. cor. of secs. 13 and 14, which is designated to function for Corner No. 1, Parcel A of sec. 14, and the place of beginning.</p> <hr/> <p>Thence, with the Metes-and-Bounds Survey of lot 7 within section 19.</p> <p>From the corner of secs. 17, 18, 19, and 20, heretofore described; which is designated to function for Corner No. 1 of lot 7 of sec. 19.</p> <p>S. 89° 52' W., on line 1 - 2, lot 7 of section 19, which is identical with the section line between secs. 18 and 19.</p>	
	8.815	<p>Corner No. 2, lot 7 which is identical with a corner of lot 8 of sec. 19, heretofore described.</p> <hr/> <p>S. 60° 08' E., on line 2 - 3, lot 7, which is identical with the northeast boundary of lot 8 of section 19.</p>	
	10.11	<p>Corner No. 3, lot 7 which is identical with a corner of lot 8 of sec. 19, and is identical with Angle Point No. 5, Tract 43, heretofore described.</p> <hr/> <p>N. 0° 33' E., on line 3 - 1, lot 7 of section 19, which is identical with the section line between secs. 19 and 20.</p>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS	
5.06	<p>The corner of secs. 17, 18, 19, and 20, which is designated to function for Corner No. 1, lot 7 of sec. 19, and the place of beginning.</p>
	<p>Thence, in section 20</p>
	<p>The 1/4 sec. cor. of secs. 20 and 29 is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">BUREAU OF RECLAMATION 1/4 <u>S 20</u> S 29 1952</p>
	<p>substantiated by:</p>
	<p>A cross (+) chiseled on a concrete headwall of a lateral, bears N. 0° 20' E., 44 lks. distant.</p>
	<p>A cross (+) chiseled on a concrete headwall of a lateral, bears S. 0° 50' W., 45 lks. distant.</p>
	<p>The above corner was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954.</p>
	<p>N. 0° 38' E., on the north and south center line of sec. 20</p>
39.47	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T8S R17W C 1/4 S 20 1970</p>
51.40	<p>Intersect line 6 - 7, Tract 43, on the arc of a curve, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T8S R17W TR 43 C S 20 C 1970</p>

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
68.73	<p>Continue on the north and south center line of sec. 20, and on a blank line across (hereinafter described) Tract 43.</p> <p>Intersect line 2 - 3, Tract 43</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W</p> <p>C</p> <p>S 20</p>  <p>C</p> <p>TR 43</p> <p>1970</p> </div>	
79.54	<p>The 1/4 sec. cor. of secs. 17 and 20, heretofore described.</p>	
13.52	<p>From the 1/4 sec. cor. of secs. 20 and 21, heretofore described; which is designated to function for Corner No. 5, Parcel B of sec. 20.</p> <p>S. 89° 22' W., on the east and west center line of sec. 20</p> <p>Intersect the arc of a curve, hereinafter described, the point for Corner No. 4, Parcel B of sec. 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W</p> <p>S 20</p> <p>PAR B</p> <p>COR 4</p>  <p>C</p> <p>1970</p> </div>	
20.22	<p>Continue on the east and west center line of sec. 20.</p> <p>The point for the center-east 1/16 sec. cor. of sec. 20</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>C E 1/16</p> <p>S 20</p> <p>1970</p> </div>	
40.44	<p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 20, heretofore described.</p>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS

80.88 The 1/4 sec. cor. of secs. 19 and 20, heretofore described.

From the center-east 1/16 sec. cor. of sec. 20, heretofore described.

N. 0° 43.5' E., on the north and south center line of the northeast quarter of sec. 20.

2.43 Intersect the arc of a curve, hereinafter described, the point for Corner No. 3, Parcel B of sec. 20 and Angle Point No. 7, Tract 43.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W	
TR 43	PAR B
AP 7	COR 3
S 20	

1970

18.67 Intersect the arc of a curve, hereinafter described, the point for Corner No. 2, Parcel B of sec. 20 and Angle Point No. 1, Tract 43.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W	
S 20	
PAR A	
AP 1	
TR 43	COR 2
PAR B	

1970

39.86 The point for the east 1/16 sec. cor. of secs. 17 and 20, heretofore described.



The Metes-and-Bounds Survey of Parcel B
 Within Section 20
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

From Corner No. 1, Parcel B of sec. 20, which is identical with Corner No. 3, Parcel B of sec. 21, heretofore described.



The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Thence, on line 1 - 2, Parcel B, which is identical with the southern boundary of Parcel A of section 20; along the arc of a curve, curve data:</p> <p>Chord bears N. 71° 19' W. Chord length 21.27 chs. distant Radius 143.94 chs. distant Length of arc 21.29 chs. distant</p> <p>At the end of the arc of the curve, Corner No. 2, Parcel B, of sec. 20, which is identical with Angle Point No. 1, Tract 43, heretofore described.</p> <hr/> <p>S. 0° 43.5' W., on line 2 - 3, Parcel B of sec. 20, which is identical with line 1 - 7, Tract 43, and is identical with the north and south center line of the northeast quarter of sec. 20.</p>	
	16.24	<p>Corner No. 3 of sec. 20, which is identical with Angle Point No. 7, Tract 43, heretofore described.</p> <hr/> <p>Thence, on line 3 - 4, Parcel B, which is identical with the northern boundary of Parcel C of sec. 20; along the arc of a curve, curve data:</p> <p>Chord bears S. 70° 33' E. Chord length 7.07 chs. distant Radius 159.09 chs. distant Length of arc 7.075 chs. distant</p> <p>At the end of the arc of the curve, Corner No. 4, Parcel B of sec. 20, heretofore described.</p> <hr/> <p>N. 89° 22' E., on line 4 - 5, Parcel B, which is identical with the east and west center line of sec. 20.</p>	
	13.52	<p>The 1/4 sec. cor. of secs. 20 and 21, heretofore described, which is designated to function for Corner No. 5, Parcel B of sec. 20.</p> <hr/> <p>N. 0° 49' E., on line 5 - 1, Parcel B of sec. 20, which is identical with the section line between secs. 20 and 21.</p>	
	11.63	<p>Corner No. 1, Parcel B of sec. 20, which is identical with Corner No. 3, Parcel B of sec. 21, and the place of beginning.</p> <hr/>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	Thence, in section 21	
	From the 1/4 sec. cor. of secs. 21 and 28, heretofore described.	
	N. 0° 24' E., on the north and south center line of sec. 21.	
19.88	The point for the center-south 1/16 sec. cor. of sec. 21. I did not monument this corner point.	
28.37	The point for Corner No. 3, Parcel C of section 21.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
		
	1975	
39.76	Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 21.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
		
	1970	
59.645	The point for the center-north 1/16 sec. cor. of sec. 21. I did not monument this corner point.	
79.53	The 1/4 sec. cor. of secs. 16 and 21, heretofore described.	
	From the 1/4 sec. cor. of secs. 21 and 22, heretofore described.	
	S. 89° 53' W., on the east and west center line of sec. 21.	
18.04	Intersect line 2 - 3, Tract 42.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	 <p>T8S R17W S 21 C ————— C TR 42</p>	
	1975	
	Continue on the east and west center line of sec. 21, and on a blank line across (hereinafter described) Tract 42.	
20.07	The point for the center-east 1/16 sec. cor. of sec. 21. Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p>C E 1/16 S 21</p>	
	1970	
40.14	Intersect the north and south center line, the center 1/4 sec. cor. of sec. 21, heretofore described.	
42.50	Road, bears N. 26° 40' E. and S. 26° 40' W.	
45.40	The center line of the Southern Pacific Railroad, bears N. 26° 40' E. and S. 26° 40' W.	
60.215	The point for the center-west 1/16 sec. cor. of sec. 21. This corner point is located within a floodway channel of the Gila River, where it is impracticable to establish a permanent monument. A witness corner is hereinafter described.	
80.29	The 1/4 sec. cor. of secs. 20 and 21, heretofore described.	
	From the center-east 1/16 sec. cor. of sec. 21, heretofore described. N. 0° 12' E., on the north and south center line of the northeast quarter of sec. 21.	
0.37	The point for Angle Point No. 3, Tract 42. Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	 <p>T8S R17W E S 21 AP 3 TR 42 E</p>	
	1975	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
19.915	Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 21.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	NE 1/16 S 21	
	1970	
39.83	The point for the east 1/16 sec. cor. of secs. 16 and 21, heretofore described.	
	From the north 1/16 sec. cor. of secs. 21 and 22, heretofore described.	
	S. 89° 48' W., on the east and west center-line of the northeast quarter of sec. 21.	
20.00	Intersect the north and south center line of the northeast quarter, the northeast 1/16 sec. cor. of sec. 21, heretofore described.	
40.00	Intersect the north and south center line, the point for the center-north 1/16 sec. cor. of sec. 21, heretofore described.	
	From the true point for the center-west 1/16 sec. cor. of sec. 21, heretofore described.	
	N. 0° 37' E., on the north and south center line of the northwest quarter of section 21.	
0.46	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, for the witness center-west 1/16 sec. cor. of sec. 21, with brass cap mkd.	
	C W 1/16 S 21 ↓ W C	
	1970	
7.60	The point for Corner No. 5, Parcel A and Corner No. 1, Parcel B of sec. 21.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	


The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>T8S R17W</p> <p>W</p> <p>S 21</p> <p>PAR A </p> <p>COR 5 </p> <p>--- </p> <p>COR 1 </p> <p>PAR B </p> <p>W</p> <p>1975</p>	
19.86	Intersect the east and west center line of the northwest quarter, the point for the northwest 1/16 sec. cor. of sec. 21. I did not monument this corner point.	
34.755	<p>The point for the C-N-N-NW 1/256 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long. 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.</p> <p style="text-align: center;">S 21 C N N NW 1/256</p> <p style="text-align: center;">1975</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
39.72	The west 1/16 sec. cor. of secs. 16 and 21, heretofore described.	
20.00	<p>From the point for the center-north 1/16 sec. cor. of sec. 21, heretofore described.</p> <p>S. 89° 48' W., on the east and west center line of the northwest quarter of sec. 21.</p> <p>Intersect the north and south center line of the northwest quarter, the point for the northwest 1/16 sec. cor. of sec. 21, heretofore described.</p>	
40.00	<p>The north 1/16 sec. cor. of secs. 20 and 21, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p>	
19.905	<p>From the east 1/16 sec. cor. of secs. 21 and 28, heretofore described.</p> <p>N. 0° 12' E., on the north and south center line of the southeast quarter of sec. 21.</p> <p>Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 21.</p>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	Set an iron post, 28 ins. long 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">SE 1/16 S 21 1970</p>	
24.795	The point for Corner No. 4, Parcel C of sec. 21 and Angle Point No. 5, Tract 42.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T8S R17W PAR C TR 42 COR 4 AP 5 ----- S 21 1975</p>	
39.80	Intersect the east and west center line, the center-east 1/16 sec. cor. of sec. 21, heretofore described.	
	From the south 1/16 sec. cor. of secs. 21 and 22, heretofore described.	
	S. 89° 56' W., on the east and west center line of the southeast quarter of sec. 21	
20.14	Intersect the north and south center line of the southeast quarter, the southeast 1/16 sec. cor. of sec. 21, heretofore described.	
40.28	Intersect the north and south center line, the point for the center-south 1/16 sec. cor. of sec. 21, heretofore described.	
	<p style="text-align: center;">The Metes-and-Bounds Survey of Parcels A, B, and C Within Section 21 Township 8 South, Range 17 West Gila and Salt River Meridian, Arizona</p> <hr style="width: 20%; margin: auto;"/>	
	Thence, with the survey of Parcel A of section 21	
	From the C-N-N-NW 1/256 sec. cor. of sec. 21, heretofore described, which is designated to function for Corner No. 1, Parcel A of sec. 21.	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>S. 89° 44' W., on line 1 - 2, Parcel A, which is identical with the east and west center line of the north half of the NW$\frac{1}{4}$ of the NW$\frac{1}{4}$ of sec. 21.</p>	
	19.95	<p>The N-N-N 1/256 sec. cor. of secs. 20 and 21, heretofore described, which is designated to function for Corner No. 2, Parcel A of sec. 21.</p> <hr/>	
		<p>S. 0° 49' W., on line 2 - 3, Parcel A of sec. 21, which is identical with the section line between secs. 20 and 21.</p>	
	14.873	<p>The north 1/16 sec. cor. of secs. 20 and 21, heretofore described.</p>	
	23.073	<p>Corner No. 3, Parcel A, which is identical with Corner No. 3, Parcel B of sec. 21, and Corner No. 1, Parcel B of sec. 20, heretofore described.</p> <hr/>	
		<p>S. 77° 43' E., on line 3 - 4, Parcel A, which is identical with line 3 - 2, Parcel B of sec. 21.</p>	
	10.90	<p>The point for Corner No. 4, Parcel A and Corner No. 2, Parcel B of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2$\frac{1}{2}$ ins. in diam., with brass cap 7 ins. below the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>T8S R17W S 21 PARCEL A COR 4  COR 2 PARCEL B</p> </div> <p>1975</p>	
		<p>There are no suitable accessories nor locations available for reference monuments.</p> <hr/>	
		<p>S. 79° 53' E., on line 4 - 5, Parcel A, which is identical with line 2 - 1, Parcel B of sec. 21.</p>	
	9.49	<p>Intersect the north and south center line of the northwest quarter, Corner No. 5, Parcel A, which is identical with Corner No. 1, Parcel B of sec. 21, heretofore described.</p> <hr/>	
		<p>N. 0° 37' E., on line 5 - 1, Parcel A, which is identical with the north and south center line of the northwest quarter of sec. 21.</p>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS	
12.26	The point for the northwest 1/16 sec. cor. of sec. 21, heretofore described.
27.155	The C-N-N-NW 1/256 sec. cor. of sec. 21, which is designated to function for Corner No. 1, Parcel A of sec. 21 and the place of beginning.
<hr/>	
Thence, with the survey of Parcel B of section 21	
From Corner No. 1, Parcel B, which is identical with Corner No. 5, Parcel A of sec. 21, heretofore described.	
N. 79° 53' W., on line 1 - 2, Parcel B, which is identical with line 5 - 4, Parcel A of sec. 21.	
9.49	Corner No. 2, Parcel B, which is identical with Corner No. 4, Parcel A of sec. 21, heretofore described.
<hr/>	
N. 77° 43' W., on line 2 - 3, Parcel B, which is identical with line 4 - 3, Parcel A of sec. 21.	
10.90	Corner No. 3, Parcel B, which is identical with Corner No. 3, Parcel A of sec. 21 and Corner No. 1, Parcel B of sec. 20, heretofore described.
<hr/>	
S. 0° 49' W., on line 3 - 4, Parcel B of sec. 21, which is identical with line 1 - 5, Parcel B of sec. 20, and is identical with the section line between secs. 20 and 21.	
11.63	The 1/4 sec. cor. of secs. 20 and 21, which is designated to function for Corner No. 4, Parcel B of sec. 21, and Corner No. 5, Parcel B of sec. 20, heretofore described.
<hr/>	
N. 89° 53' E., on line 4 - 5, Parcel B, which is identical with the east and west center line of sec. 21.	
20.075	The true point for the center-west 1/16 sec. cor. of sec. 21, heretofore described, which is designated to function for Corner No. 5, Parcel B of sec. 21.
<hr/>	
N. 0° 37' E., on line 5 - 1, Parcel B, which is identical with the north and south center line of the northwest quarter of sec. 21.	
0.46	The witness center-west 1/16 sec. cor. of sec. 21, heretofore described.
7.60	Corner No. 1, Parcel B, which is identical with Corner No. 5, Parcel A of sec. 21, and the place of beginning.

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Thence, with the survey of Parcel C of section 21</p> <p>From the center-east 1/16 sec. cor. of secs. 21, heretofore described, which is designated to function for Corner No. 1, Parcel C of sec. 21.</p> <p>S. 89° 53' W., on line 1 - 2, Parcel C, which is identical with the east and west center line of sec. 21.</p>	
	20.07	<p>The center 1/4 sec. cor. of sec. 21, heretofore described, which is designated to function for Corner No. 2, Parcel C of sec. 21.</p> <hr/> <p>S. 0° 24' W., on line 2 - 3, Parcel C, which is identical with the north and south center line of sec. 21.</p>	
	11.39	<p>Corner No. 3, Parcel C of sec. 21, heretofore described.</p> <hr/> <p>S. 79° 53' E., on line 3 - 4, Parcel C, which is identical with the northern boundary of Parcel D of sec. 21.</p>	
	20.41	<p>Intersect the north and south center line of the southeast quarter, Corner No. 4, Parcel C of sec. 21 which is identical with Angle Point No. 5, Tract 43, heretofore described.</p> <hr/> <p>N. 0° 12' E., on line 4 - 1, Parcel C, which is identical with the north and south center line of the southeast quarter of sec. 21.</p>	
	15.005	<p>The center-east 1/16 sec. cor. of sec. 21, which is designated to function for Corner No. 1, Parcel C of sec. 21, and the place of beginning.</p> <hr/> <p>Thence, in section 28</p> <p>From the 1/4 sec. cor. of secs. 28 and 33, heretofore described.</p> <p>N. 0° 16' W., on the north and south center line of sec. 28.</p>	
	40.32	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 11 ins. in the ground, and in a mound of stone, 4 ft. base, to the top, with brass cap mkd.</p>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S R17W C 1/4 S 28 1972</p>	
60.475	<p>The point for the center-north 1/16 sec. cor. of sec. 28</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., over a cross(+) chiseled on bedrock (a stone in place), and in a mound of stone, 4 ft. base, to the top, with brass cap mkd.</p>	
80.63	<p style="text-align: center;">C N 1/16 S 28 1972</p> <p>The 1/4 sec. cor. of secs. 21 and 28, heretofore described.</p>	
20.195	<p>From the 1/4 sec. cor. of sec. 27 and 28, heretofore described.</p> <p>S. 89° 47' W., on the east and west center line of sec. 28.</p>	
40.39	<p>The point for the center-east 1/16 sec. cor. of sec. 28.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., with brass cap flush with the surface of the ground, mkd.</p> <p style="text-align: center;">C E 1/16 S 28 1972</p>	
80.78	<p>There are no suitable accessories nor locations available for reference monuments.</p> <p>Intersect the north and south center line, the center 1/4 sec. cor. of sec. 28, heretofore described.</p> <p>The 1/4 sec. cor. of secs. 28 and 29, heretofore described.</p>	
20.115	<p>From the center-east 1/16 sec. cor. of sec. 28, heretofore described.</p> <p>N. 0° 16' W., on the north and south center line of the northeast quarter of sec. 28.</p> <p>Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 28.</p>	

The Survey of a Portion of the Subdivision Lines
 Within Sections 13, 14, 19, 20, 21, and 28
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona


CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NE 1/16 S 28</p> <p style="text-align: center;">1972</p>
40.23	The east 1/16 sec. cor. of secs. 21 and 28, heretofore described.
	<p>From the north 1/16 sec. cor. of secs. 27 and 28, heretofore described.</p> <p>S. 89° 53.5' W., on the east and west center line of the northeast quarter of sec. 28.</p>
20.195	Intersect the north and south center line of the northeast quarter, the northeast 1/16 sec. cor. of sec. 28, heretofore described.
40.39	Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 28, heretofore described.
	Discontinue the regular order of survey at this corner.
	<p>S. 89° 53.5' W., on the east and west center line of the northwest quarter of sec. 28.</p>
40.40	The north 1/16 sec. cor. of secs. 28 and 29, heretofore described.
	<p style="text-align: center;">The Metes-and-Bounds Survey Tracts 40 through 43 inclusive Township 8 South, Range 17 West Gila and Salt River Meridian, Arizona</p>
	<p>Thence, with the survey of Tract 40</p> <p>Beginning at Angle Point No. 1, Tract 40, which is located on the east and west center line of the northwest quarter of sec. 13, heretofore described.</p> <p>S. 89° 10.5' W., on line 1 - 2, Tract 40, which is identical with the east and west center line of the northwest quarter of sec. 13.</p>
17.04	Angle Point No. 2, Tract 40, heretofore described.

The Metes-and-Bounds Survey
 Tracts 40 through 43 inclusive
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	S. 26° 23' W., on line 2 - 3, Tract 40	
22.49	Intersect the east and west center line of sec. 13, heretofore described.	
35.14	Angle Point No. 3, Tract 40, heretofore described.	



	S. 0° 26.7' E., on line 3 - 4, Tract 40, which is identical with the section line between sec. 13 and 14.	
8.76	The south 1/16 sec. cor. of secs. 13 and 14, which is designated to function for Corner No. 1, Parcel A of section 14, heretofore described.	
	Thence, continue on line 3 - 4, Tract 40, which is identical with line 1 - 5, Parcel A of section 14.	
28.76	The corner of secs. 13, 14, 23, and 24, heretofore described, which is designated to function for Angle Point No. 4, Tract 40, and is identical with Corner No. 5, Parcel A of section 14.	

	N. 89° 11' E., on line 4 - 5, Tract 40, which is identical with the section line between secs. 13 and 24.	
1.61	Angle Point No. 5, Tract 40, heretofore described.	

	Thence, on line 5 - 6, Tract 40, along the arc of a curve, curve data:	
	Chord bears N. 30° 13' E.	
	Chord length 11.16 chs. distant	
	Radius 83.33 chs. distant	
	Length of arc 11.17 chs. distant	
	At the end of the arc of the curve, the point for Angle Point No. 6, Tract 40.	
	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p>T8S R17W</p>  <p>1975</p>	

	N. 26° 23' E., on line 6 - 1, Tract 40.	
34.23	Intersect the east and west center line of sec. 13, heretofore described.	

The Metes-and-Bounds Survey
Tracts 40 through 43 inclusive
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

	CHAINS	
	56.72	<p>Intersect the east and west center line of the northwest quarter of sec. 13, Angle Point No. 1, Tract 40, and the place of beginning.</p> <hr/> <p>Thence, with the survey of Tract 41</p> <p>Beginning at Angle Point No. 1, Tract 41, which is located on the section line between secs. 22 and 23, heretofore described.</p> <p>Thence, on line 1 - 2, Tract 41, along the arc of a curve, curve data:</p> <p>Chord bears S. 76° 24.5' W. Chord length 29.465 chs. distant Radius 83.33 chs. distant Length of arc 29.62 chs. distant</p> <p>At the end of the arc of the curve, the point for Angle Point No. 2, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W S 22</p>  <p>AP 2 TR 41</p> <p>1975</p> </div> <hr/> <p>S. 66° 13.5' W., on line 2 - 3, Tract 41</p>
	13.055	Intersect the north and south center line of sec. 22, heretofore described.
	23.935	<p>The point for Angle Point No. 3, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R17W S 22</p>  <p>AP 3 TR 41</p> <p>1975</p> </div> <hr/> <p>Thence, on line 3 - 4, Tract 41, along the arc of a curve, curve data:</p>

The Metes-and-Bounds Survey
 Tracts 40 through 43 inclusive
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS

Chord bears S. 79° 22.5' W.
 Chord length 31.01 chs. distant
 Radius 68.18 chs. distant
 Length of arc 31.28 chs. distant

At 8.24 chs. distant on the arc of the curve. Intersect the east and west center line of sec. 22, heretofore described.

At the end of the arc of the curve, Angle Point No. 4, Tract 41, which is identical with Angle Point No. 1, Tract 42, heretofore described.

SOUTH, on line 4 - 5, Tract 41, which is identical with line 1 - 7, Tract 42, and on the section line between sections 21 and 22.

15.17 Angle Point No. 5, Tract 41, which is identical with Angle Point No. 7, Tract 42, heretofore described.

Thence, on line 5 - 6, Tract 41, along the arc of a curve, curve data:

Chord bears N. 79° 08.5' E.
 Chord length 37.245 chs. distant
 Radius 83.33 chs. distant
 Length of arc 37.565 chs. distant

At the end of the arc of the curve, the point for Angle Point No. 6, Tract 41.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W
 TR 41
 AP 6

—+—
 S 22

1975

N. 66° 13.5' E., on line 6 - 7, Tract 41.

4.075 Intersect the north and south center line of sec. 22. Angle Point No. 7, Tract 41, heretofore described.

The Metes-and-Bounds Survey
 Tracts 40 through 43 inclusive
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
9.53	<p>N. 0° 24.8' E., on line 7 - 8, Tract 41, which is identical with the north and south center line of sec. 22.</p> <p>The center 1/4 sec. cor. of sec. 22, heretofore described, which is designated to function for Angle Point No. 8, Tract 41.</p> <hr/>	
22.44	<p>N. 89° 27.8' E., on line 8 - 9, Tract 41, which is identical with the east and west center line of sec. 22.</p> <p>Angle Point No. 9, Tract 41, heretofore described.</p> <hr/> <p>Thence, on line 9 - 10, Tract 41, along the arc of a curve, curve data:</p> <p>Chord bears N. 77° 54' E. Chord length 18.40 chs. distant Radius 68.18 chs. distant Length of arc 18.46 chs. distant</p> <p>At the end of the arc of the curve, Angle Point No. 10, Tract 41, heretofore described.</p> <hr/> <p>N. 0° 47.7' E., on line 10 - 1, Tract 41, which is identical with the section line between secs. 22 and 23.</p>	
15.20	<p>Angle Point No. 1, Tract 41, and the place of beginning.</p> <hr/> <p>Thence, with the survey of Tract 42</p> <p>Beginning at Angle Point No. 1, Tract 42, which is identical with Angle Point No. 4, Tract 41, heretofore described.</p> <p>Thence, on line 1 - 2, Tract 42, along the arc of a curve, curve data:</p> <p>Chord bears N. 83° 41' W. Chord length 9.04 chs. distant Radius 68.18 chs. distant Length of arc 9.05 chs. distant</p> <p>At the end of the arc of the curve, the point for Angle Point No. 2, Tract 42. This corner point is located within a floodway channel of the Gila River, where it is impracticable to establish a permanent monument. A witness corner is hereinafter described.</p> <hr/>	

The Metes-and-Bounds Survey
Tracts 40 through 43 inclusive
Township 8 South, Range 17 West
Gila and Salt River Meridian, Arizona

CHAINS		
	N. 79° 53' W., on line 2 - 3, Tract 42.	
1.46	Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, for the witness Angle Point No. 2, Tract 42, with brass cap mkd.	
	<p style="text-align: center;">W C T8S R17W S 21 → AP 2 TR 42</p> <p style="text-align: center;">1975</p>	
9.20	Intersect the east and west center line of sec. 21, heretofore described.	
11.26	Intersect the north and south center line of sec. 21, Angle Point No. 3, Tract 42, heretofore described.	
	<hr style="width: 30%; margin: auto;"/> <p>S. 0° 12' W., on line 3 - 4, Tract 42, which is identical with the north and south center line of the northeast quarter of sec. 21.</p>	
0.37	The center-east 1/16 sec. cor. of sec. 21, heretofore described, which is designated to function for Angle Point No. 4, Tract 42, and is identical with Corner No. 1, Parcel C of sec. 21.	
	<hr style="width: 30%; margin: auto;"/> <p>S. 0° 12' W., on line 4 - 5, Tract 42, which is identical with line 1 - 4, Parcel C, and is identical with the north and south center line of the southeast quarter of sec. 21.</p>	
15.005	Angle Point No. 5, Tract 42, which is identical with Corner No. 4, Parcel C of sec. 21, heretofore described.	
	<hr style="width: 30%; margin: auto;"/> <p>S. 79° 53' E., on line 5 - 6, Tract 42.</p>	
8.61	The point for Angle Point No. 6, Tract 42. Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T8S R17W TR 42 AP 6 + S 21</p> <p style="text-align: center;">1975</p> <hr style="width: 30%; margin: auto;"/>	

The Metes-and-Bounds Survey
 Tracts 40 through 43 inclusive
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS

Thence, on line 6 - 7, Tract 42, along the arc of a curve, curve data:

Chord bears S. 83° 55' E.
 Chord length 11.715 chs. distant
 Radius 83.33 chs. distant
 Length of arc 11.725 chs. distant

At the end of the arc of the curve, Angle Point No. 7, Tract 42, which is identical with Angle Point No. 5, Tract 41, heretofore described.

NORTH, on line 7 - 1, Tract 42, which is identical with line 5 - 4, Tract 41, and on the section line between secs. 21 and 22.

15.17 Angle Point No. 1, Tract 42, which is identical with Angle Point No. 4, Tract 41, and the place of beginning.

Thence, with the survey of Tract 43

Beginning at Angle Point No. 1, Tract 43, which is identical with Corner No. 2, Parcel B of sec. 20, heretofore described.

Thence, on line 1 - 2, Tract 43, along the arc of a curve, curve data:

Chord bears N. 63° 36' W.
 Chord length 17.42 chs. distant
 Radius 143.94 chs. distant
 Length of arc 17.43 chs. distant

At the end of the arc of the curve, the point for Angle Point No. 2, Tract 43.

Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R17W
 S 20
 AP 2
 TR 43


1970

N. 60° 08' W., on line 2 - 3, Tract 43.

5.23 Intersect the north and south center line of sec. 20, heretofore described.

26.915 Angle Point No. 3, Tract 43, heretofore described.

The Metes-and-Bounds Survey
 Tracts 40 through 43 inclusive
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p>S. 89° 56' W., on line 3 - 4, Tract 43, which is identical with the section line between sections 17 and 20.</p>	
1.32	<p>The west 1/16 sec. cor. of secs. 17 and 20, heretofore described.</p>	
21.54	<p>The corner of secs. 17, 18, 19, and 20, heretofore described, which is designated to function for Angle Point No. 4, Tract 43 and Corner No. 1, Lot 7 of sec. 19.</p>	
	<hr/>	
	<p>S. 0° 33' W., on line 4 - 5, Tract 43, which is identical with line 1 - 3, lot 7 of sec. 19, and on the section line between secs. 19 and 20.</p>	
5.06	<p>Angle Point No. 5, Tract 43, which is identical with Corner No. 3, lot 7 of sec. 19, heretofore described.</p>	
	<hr/>	
	<p>S. 60° 08' E., on line 5 - 6, Tract 43.</p>	
43.10	<p>The point for Angle Point No. 6, Tract 43. Set an iron post, 28 ins. long, 2½ ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T8S R17W TR 43 AP 6  S 20</p>	
	<p style="text-align: center;">1970</p>	
	<hr/>	
	<p>Thence, on line 6 - 7, Tract 43, along the arc of a curve, curve data:</p>	
	<p>Chord bears S. 64° 42.5' E. Chord length 25.375 chs. distant Radius 159.09 chs. distant Length of arc 25.40 chs. distant</p>	
	<p>At 3.23 chs. distant on the arc of the curve. Intersect the north and south center line of sec. 20, heretofore described.</p>	
	<p>At the end of the arc of the curve, intersect the north and south center line of the northeast quarter of sec. 20, Angle Point No. 7, Tract 43, which is identical with Corner No. 3, Parcel B of secs. 20, heretofore described.</p>	
	<hr/>	

The Metes-and-Bounds Survey
 Tracts 40 through 43 inclusive
 Township 8 South, Range 17 West
 Gila and Salt River Meridian, Arizona

	CHAINS		
	16.24	<p>N. 0° 43.5' E., on line 7 - 1, Tract 43, which is identical with line 2 - 3, Parcel B of sec. 20, and on the north and south center line of the northeast quarter of section 20.</p> <p>Angle Point No. 1, Tract 43, which is identical with Corner No. 2, Parcel B of sec. 20, and the place of beginning.</p>	
		<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The land area within these surveys are nearly level to gently rolling; with the exception of Antelope Hill which is located in the southern portion of section 21 and the northern portion of section 28. The soil consists of sandy clay loam; the land area is under cultivation, with the exception of the federally controlled lands, which are undeveloped; with French tamarisk and mesquite trees, and creosote brush (shrub).</p> <p>Improvements located throughout the area are: The Southern Pacific Railroad, the Mohawk Canal and the Mohawk Main Cannel, numerous canals and laterals for irrigation and/or drainage purposes; Yuma County and farm roads.</p>	

CHAINS		
--------	--	--

Form 9600-11
(August 1979)UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
Marvin T. Koppang	Cadastral Surveyor
James P. Scott	Cadastral Surveyor
Stephen Jaramillo	Surveying Aid
Manuel G. Jaramillo	Surveying Aid
Ernest E. Hurtado	Surveying Aid
Dale E. Phillips	Surveying Aid
Fordner Van Fleet, Jr.	Surveying Aid
Kermit L. Duke	Surveying Aid
Norman Q. Hull	Surveying Aid
Terry L. Behrendt	Surveying Aid
Jerold L. Peterson	Surveying Aid
Lewis J. Scheeler	Surveying Aid
Eric A. Werner	Surveying Aid

CERTIFICATE OF SURVEY

~~XX~~(We), Ray Harpin and Douglas A. Cody, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day

of October, 1969, ~~XXXXXX~~ Supplemental Special Instructions dated November 20, 1969, and Supplemental Special Instructions dated September 5, 1979, we have dependently resurveyed a portion of the subdivisional lines and a portion of the subdivision lines within sections 13, 14, and 22 inclusive; surveyed a portion of the subdivision lines within a number of sections, and the metes-and-bounds survey of Tracts 40 through 43 inclusive, Township 8 South, Range 17 West,

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~XXXX~~ (us) and under ~~XXXX~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

November 15, 1979 (Date) [Signature: Ray Harpin] (Cadastral Surveyor)
November 15, 1979 (Date) [Signature: Douglas A. Cody] (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the subdivisional lines and a portion of the subdivision lines within sections 13, 14, and 22 inclusive; the survey of a portion of the subdivision lines within a number of sections, and the metes-and-bounds survey of Tracts 40 through 43 inclusive, Township 8 South, Range 17 West, of the Gila and Salt River Meridian, Arizona

executed by Ray Harpin and Douglas A. Cody, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

MAY 1 1980 (Date) [Signature: J. Voorhes] (Chief, Cadastral Survey Examination and Approval Staff)

~~CERTIFICATE OF TRANSCRIPT~~
~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in is a true copy of the original field notes.~~
~~(Date) (Chief, Cadastral Survey Examination and Approval Staff)~~