

# FIELD NOTES

1

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE

NORTH BOUNDARY OF TOWNSHIP 14 NORTH, RANGE 15 EAST

AND THE

DEPENDENT RESURVEY OF A PORTION OF THE

NORTH BOUNDARY AND SUBDIVISIONAL LINES

AND THE

SURVEY OF SUBDIVISIONS IN SECTION 2

TOWNSHIP 14 NORTH, RANGE 14 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

HARRY K. SMITH,

CADASTRAL SURVEYOR

Under special instructions dated SEPTEMBER 16, 19 76, approved SEPT. 21, 1976,

\_\_\_\_\_, which provided for the surveys included under U.S. Survey/Group  
Number 590, and assignment instructions dated SEPTEMBER 30, 1976.

Survey commenced JUNE 11, 19 79

Survey completed JUNE 22, 19 79

# INDEX DIAGRAM

Township 14 NORTH, Range 14 EAST

3 Range  
15 East

6	5	4	6 3	4 2 8	3 1 7	1
7	8	9	10	11	12	
18	17	16	15	14	13	
19	20	21	22	23	24	
30	29	28	27	26	25	
31	32	33	34	35	36	

Dependent Resurvey, Tps. 14 N., Rs. 14 and 15 E.,  
Gila and Salt River Mer., Arizona

## CHAINS

The north boundary of Township 14 North, Range 15 East, of the Gila and Salt River Meridian, Arizona, was surveyed in 1893 by Philip Contzen.

The boundaries and subdivisional lines of Township 14 North, Range 14 East, of the Gila and Salt River Meridian, Arizona, were surveyed in 1893 by Philip Contzen.

The following field notes describe the dependent resurvey of a portion of the north boundary of Township 14 North, Range 15 East, the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines and the survey of subdivisions in section 2, Township 14 North, Range 14 East, of the Gila and Salt River Meridian, Arizona.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 590, Arizona, dated September 16, 1976.

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined by direct solar observations and refer to the true meridian. Distances were measured electronically with a Zeiss SM-4 instrument.

The geographic position of the corner of secs. 5, 6, 31 and 32, on the north boundary of Township 14 North, Range 15 East, as scaled from the U.S. Geological Survey Quadrangle Map, CHEVELON BUTTE, ARIZ., prepared in 1970, is as follows:

Latitude 34°38.2' N. Longitude 110°47.2' W.

The mean magnetic declination is 13°30' E.

---

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 14 N., R. 15 E., Gila and Salt River Mer., Arizona

---

(Restoring the 1893 survey executed by Philip Contzen)

---

Beginning at the cor. of secs. 5, 6, 31 and 32, on the N. bdy. of the Tp., monumented with an iron post, 2½ ins. diam., set in a mound of stone, 3½ ft. base, 28 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonumentation notes by Paul L. Reeves, Cadastral Surveyor, from which the remains of the original bearing trees

A cedar stump, 16 ins. diam., bears N. 16° E.,  
36 lks. dist.; no visible marks.

A stumphole, bears S. 65° E., 116 lks. dist.;  
a pinyon, 8 ins. diam., lying alongside is mkd.  
T14N R15E S5 BT.

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 14 N., R. 15 E., Gila and Salt River Mer., Arizona

CHAINS	
40.01	<p>A pinyon, 10 ins. diam., bears S. 27° W., 43 lks. dist., mkd. with a healed blaze.</p> <p>A pinyon, 14 ins. diam., bears N. 7° W., 88 lks. dist., mkd. T15N R15E S31 BT.</p> <p>From this point a fence cor., bears N. 4° W., 39 lks. dist.; fences extend N., E. and W.</p> <p>S. 89°44' W., bet. secs. 6 and 31.</p> <p>Over gently rolling land, through medium timber.</p> <p>The 1/4 sec. cor. of secs. 6 and 31, monumented with a limestone, 32 x 10 x 6 ins., loosely set, mkd. 1/4 on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R15E 1/4 S31 4 S 6 T14N 1979</p> <p>from which</p> <p>A juniper, 4 ins. diam., bears S. 61½° E., 208.5 lks. dist., mkd. X BT at the base.</p> <p>A juniper, 4 ins. diam., bears S. 32° W., 90 lks. dist., mkd. X BT at the base.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Cor. is 82 lks. S. of an E-W fence.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 88°50' W., beginning new measurement.</p>
45.56	<p>The cor. of Tps. 14 and 15 N., Rs. 14 and 15 E., monu- mented with a sandstone, 18 x 12 x 10 ins., set flush with the ground, mkd. with an X on top, from which</p> <p>A large charred juniper stump, bears N. 28° E., 169 lks. dist. The stump is so badly burned that it is impossible to see any scribe marks or determine the diam.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R14E R15E S36 S31 S 1 S 6 T14N 1979</p> <p>from which</p> <p>A pinyon, 8 ins. diam., bears N. 80° E., 215.5 lks. dist., mkd. T15N R15E S31 BT.</p>

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 14 N., R. 15 E., Gila and Salt River Mer., Arizona

## CHAINS

A juniper, 4 ins. diam., bears N. 31° W.,  
34 lks. dist., mkd. X BT at the base.

Deposit the mkd. stone alongside the iron post.

Cor. is located S. 48° W., 12 lks. dist., from an  
abandoned concrete cattleguard.

Cor. is in an E-W fence and 5 lks. W. of an abandoned  
fence extending S.

Cor. is also 3.00 chs. S. of a gravel road, bears E.  
and W.

From this point the 1/4 sec. cor. of secs. 31 and 36,  
Tps. 15 N., Rs. 14 and 15 E., bears N. 0°05' W., 40.01  
chs. dist., monumented with a limestone, 20 x 18 x 6  
ins., firmly set in a mound of stone, 2 ft. base, 1 ft.  
high, mkd. 1/4 on the W. face from which the remains of  
the original bearing trees

A stumphole, bears N. 23° E., 249 lks. dist.;  
a pinyon, 9 ins. diam., lying alongside is mkd.  
1/4.

A juniper limb, 14 ins. diam., bears S. 34° W.,  
46 lks. dist., mkd. 1/4 S. (The trunk of this  
tree bears S. 31½° W., which is record)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in  
the ground, with brass cap mkd.

T15N  
1/4  
R14E|R15E  
S36|S31  
|  
1979

from which

A juniper, 12 ins. diam., bears S. 89½° E.,  
93.5 lks. dist., mkd. 1/4 S31 BT.

A pinyon, 6 ins. diam., bears N. 68° W.,  
134.5 lks. dist., mkd. 1/4 S36 BT.

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of  
the cor.

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 14 N., R. 14 E., Gila and Salt River Mer., Arizona

(Restoring the 1893 survey executed by Philip Contzen)

From the cor. of Tps. 14 and 15 N., Rs. 14 and 15 E.,  
previously described.

N. 89°38' W., bet. secs. 1 and 36.

Over gently rolling land which has been railed.

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 14 N., R. 14 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Along the S. side of an E-W fence.</p>	
.20	<p>Track road, bears NE and SW, curving W.</p>	
39.58	<p>Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R14E  <math>\frac{1}{4} \frac{S36}{S1}</math>                      T14N                      1979</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 4 ins. diam., bears N. 10° E., 90 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A juniper, 12 ins. diam., bears N. 61° W., 96 lks. dist., mkd. 1/4 S36 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1 ft. high, N. of the cor.</p> <p>Cor. is 13 lks. S. of an E-W fence.</p>	
79.16	<p>The point for the cor. of secs. 1, 2, 35 and 36, determined at record bearing and dist., from the remains of the original bearing trees</p> <p style="padding-left: 40px;">A stumphole, bears S. 83° W., 39 lks. dist., a pinyon, 6 ins. diam., lying alongside is mkd. T14N R14E S2 BT.</p> <p style="padding-left: 40px;">A stumphole, bears N. 49° W., 163 lks. dist., a pinyon, 4 ins. diam., lying alongside is mkd. with a blaze and definite scribe marks which are illegible.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T15N R14E  <math>\frac{S35 S36}{S2 S1}</math>                      T14N                      1979</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 8 ins. diam., bears N. 46° E., 105.5 lks. dist., mkd. T15N R14E S36 BT.</p> <p style="padding-left: 40px;">A pinyon, 8 ins. diam., bears N. 27° W., 104.5 lks. dist., mkd. T15N R14E S35 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>Cor. is 45.5 lks. S. of an E-W fence.</p>	
	<p>N. 88°50' W., bet. secs. 2 and 35.</p>	

CHAINS		
	<p>Over nearly level land, which has been railed.</p> <p>Along the S. side of an E-W fence.</p> <p>39.88 The 1/4 sec. cor. of secs. 2 and 35, monumented with a mound of stone, 2 ft. base, 10 ins. high, verified by an original bearing tree</p> <p style="padding-left: 40px;">A juniper limb, 5 ins. diam., bears N. 9° E., 72 lks. dist., mkd. 1/4 S BT.</p> <p>At the center of the mound</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R14E     1  S35     4  S  2     T14N     1979</p> <p>from which</p> <p style="padding-left: 40px;">A juniper, 6 ins. diam., bears N. 26° E., 48 lks. dist., mkd. 1/4 S35 BT.</p> <p style="padding-left: 40px;">A pinyon, 24 ins. diam., bears S. 78° W., 171 lks. dist., mkd. 1/4 S2 BT.</p> <p>The original cor., a limestone 14 x 12 x 4 ins., mkd. 1/4 on one face was found lying loose on the ground and was deposited in the mound alongside the iron post.</p> <p>The cor. is located 19 lks. S. of an E-W fence and 130 lks. N. of a graded road, bears E. and W.</p> <p style="text-align: center;">_____</p> <p>N. 89°32' W., beginning new measurement.</p> <p>39.54 The point for the cor. of secs. 2, 3, 34 and 35, determined at record distances from the only remaining original bearing trees</p> <p style="padding-left: 40px;">A juniper limb, 13 ins. diam., bears N. 31° E., 109 lks. dist., mkd. T14N R15 E S35. (Record bearing N. 36° E.)</p> <p style="padding-left: 40px;">A juniper limb, 8 ins. diam., bears S. 8° W., 69 lks. dist., mkd. 14E S3 BT. (Record bearing S. 5½° W.) The top portion of the limb has been cut off.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T15N R14E     S34 S35     S  3 S  2     T14N     1979</p>	

Dependent Resurvey of a Portion of the N. Bdy.,  
T. 14 N., R. 14 E., Gila and Salt River Mer., Arizona

## CHAINS

from which

A juniper, 6 ins. diam., bears N. 29° E.,  
85.5 lks. dist., mkd. T15N R14E S35 BT.

A fence cor., bears S. 58° E., 37 lks. dist.;  
fences extend N and E.

A juniper, 6 ins. diam., bears N. 77° W.,  
22 lks. dist., mkd. T15N R14E S34 BT.

Deposit broken brown glass at the base of the iron post.

N. 89°31' W., bet. secs. 3 and 34.

Over gently rolling land, through medium to scattering  
timber.

This line was resurveyed as a control line and the 1/4  
sec. cor. of secs. 3 and 34 remonumented prior to finding  
the original evidence at the cor. of secs. 2, 3, 34 and  
35.

39.79

The 1/4 sec. cor. of secs. 3 and 34, monumented with a  
limestone, 12 x 12 x 3 ins., firmly set 6 ins. in the  
ground, mkd. 1/4 on the N. face, with a mound of stone,  
1 ft. base, 6 ins. high, N. of the cor., from which the  
remains of the original bearing trees

A stump hole, bears N. 55° E., 24 lks. dist.;  
a pinyon, 7 ins. diam., lying alongside is mkd.  
1/4 S BT.

A stump hole, bears S. 73° W., 22 lks. dist.;  
a pinyon, 6 ins. diam., lying alongside is mkd.  
1/4 S BT. (Record bearing N. 73° W.)

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in  
the ground to solid rock, and in a mound of stone, 3 ft.  
base, to top, with brass cap mkd.

T15N R14E

$\frac{1}{4}$   $\frac{S34}{S3}$

T14N

1979

from which

A pinyon, 9 ins. diam., bears N. 13° E.,  
72 lks. dist., mkd. 1/4 S34 BT.

A juniper, 9 ins. diam., bears S. 65° E.,  
13.5 lks. dist., mkd. 1/4 S3 BT.

Deposit the mkd. stone alongside the iron post.

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 14 E., Gila & Salt River Mer., Ariz.

(Restoring the 1893 survey executed by Philip Contzen)



Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 14 E., Gila & Salt River Mer., Ariz.

CHAINS		
	<p>From the cor. of secs. 1, 2, 11 and 12, monumented with a limestone in place, 14 x 12 x 12 ins., projecting 3 ins. above ground, mkd. with 1 groove on the E. and 5 grooves on the S., all marks were on top of the stone, from which the remains of the original bearing trees</p> <p>A stumphole, bears N. 18° E., 72 lks. dist.; a pinyon, 10 ins. diam., lying alongside is mkd. T14N R14E S1 BT.</p> <p>A stumphole, bears S. 28° E., 59 lks. dist.; a pinyon, 8 ins. diam., lying alongside is mkd. T14 with other illegible scribe marks.</p> <p>A stumphole, bears S. 2½° W., 78 lks. dist.; a badly decayed pine lying alongside is mkd. with a blaze and illegible scribe marks.</p> <p>A pine, 14 ins. diam., bears N. 53½° W., 45 lks. dist.; mkd. with a healed blaze.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T14N R14E S 2 S 1 S11 S12 1979</p> <p>from which</p> <p>A juniper, 7 ins. diam., bears N. 61½° E., 73.5 lks. dist., mkd. T14N R14E S1 BT.</p> <p>A juniper, 11 ins. diam., bears S. 66° E., 48.5 lks. dist., mkd. T14N R14E S12 BT.</p> <p>A pinyon, 7 ins. diam., bears S. 31° W., 129 lks. dist., mkd. T14N R14E S11 BT.</p> <p>Deposit the mkd. stone in the mound alongside the iron post.</p> <p>N. 1°38' E., bet. secs. 1 and 2.</p> <p>Over rugged land, through medium timber.</p> <p>20.30 West Chevelon Canyon, drains NE. (1893 Record)</p> <p>32.00 Enter gently rolling railed area, edge bears E. and W.</p> <p>40.21 Point for the 1/4 sec. cor. of secs. 1 and 2, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R14E 1/4 S 2 S 1 1979</p> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of the cor.</p>	

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 14 E., Gila & Salt River Mer., Ariz.

CHAINS	
40.90	Old track road, bears N. 75° E. and S. 75° W.
42.90	Track road, bears NE and SW.
80.68	The cor. of secs. 1, 2, 35 and 36, on the N. bdy. of the Tp., heretofore described.
<hr/>	
From the cor. of secs. 1, 2, 11 and 12.	
N. 88°16' W., bet. secs. 2 and 11.	
Over rugged terrain, through scattering timber. (Topography omitted).	
36.70	Fence, bears S. 6° E. and N. 6° W.
38.44	Point for the 1/4 sec. cor. of secs. 2 and 11, at proportionate dist.; there is no remaining evidence of the original cor.
Set an iron post, 28 ins. long, 2½ ins. diam., 12 ins. in the ground to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.	
T14N R14E $\frac{1}{4}$ S 2 S11 1979	
from which	
A fence cor., bears N. 33¾° E., 265 lks. dist.; fences extend N., S. 6° E. and N. 33° W.	
A juniper, 10 ins. diam., bears S. 39° E., 11 lks. dist., mkd. 1/4 S11 BT.	
A pinyon, 8 ins. diam., bears N. 82° W., 25 lks. dist., mkd. 1/4 S2 BT.	
76.88	The cor. of secs. 2, 3, 10 and 11, monumented with an iron post, 2½ ins. diam., set in a mound of stone, 3 ft. base, 18 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonumentation notes by Paul L. Reeves, Cadastral Surveyor, from which
A fence cor., bears N. 64½° E., 4 lks. dist.; fences extend N. and easterly.	
A pinyon, 14 ins. diam., mkd. in 1893, bears S. 18 1/4° E., 89 lks. dist., with scribe marks visible through a partially healed blaze.	
A stump hole, bears N. 63½° W., 74 lks. dist.; a pinyon, 8 ins. diam., mkd. in 1893, lying alongside is mkd. R14E S3 BT.	
A juniper, 10 ins. diam., mkd. in 1975, bears N. 64¾° W., 88.5 lks. dist., mkd. T14N R14E S3 BT. (Record dist. 87 lks.)	
<hr/>	
N. 0°16' W., bet. secs. 2 and 3.	
Over rolling land, through medium timber.	

Dependent Resurvey of a Portion of the Subdivisional  
Lines, T. 14 N., R. 14 E., Gila & Salt River Mer., Ariz.

CHAINS		
16.80	Graded gravel road, bears N. 50° E. and S. 50° W.	
19.20	Fence, bears N. 60° E. and S. 60° W.	
39.71	<p>The 1/4 sec. cor. of secs. 2 and 3, monumented with an iron post, 2½ ins. diam., set in a mound of stone, 2 ft. base, 16 ins. high, to top, with brass cap mkd. as described in the official record of the 1975 remonumentation notes by Paul L. Reeves, Cadastral Surveyor, from which</p> <p>A juniper, 5 ins. diam., mkd. in 1975, bears N. 60° E., 31 lks. dist., mkd. 1/4 S2 BT.</p> <p>A stumphole, bears N. 19½° E., 22 lks. dist.; a pinyon, 10 ins. diam., mkd. in 1893, lying alongside is mkd. 1/4 S BT.</p> <p>A stumphole, bears S. 37½° W., 35 lks. dist.; a pinyon, 8 ins. diam., mkd. in 1893, lying alongside is mkd. 1/4 S BT.</p> <p>A juniper, 7 ins. diam., mkd. in 1975, bears S. 89½° W., 26 lks. dist., mkd. 1/4 S3 BT.</p> <hr/> <p>N. 0°08' W., beginning new measurement.</p>	
39.75	The cor. of secs. 2, 3, 34 and 35, on the N. bdy. of the Tp., heretofore described.	
	<p>Subdivision of Section 2, T. 14 N., R. 14 E., Gila and Salt River Mer., Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 2 and 11.</p> <p>N. 0°36' E., on the N. and S. center line of sec. 2.</p> <p>Over rolling land, through a railed area. (Topography omitted)</p>	
39.96	<p>Point for the center 1/4 sec. cor. of sec. 2, at intersection with the E. and W. center line of sec. 2.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T14N R14E C 1/4 S 2 1979</p> <p>from which</p> <p>A fence cor., bears N. 16° E., 55.5 lks. dist.; fences extend S. and W.</p> <p>A pinyon, 12 ins. diam., bears N. 70° E., 67.5 lks. dist., mkd. C 1/4 S2 BT.</p> <p>A pinyon, 10 ins. diam., bears S. 84° E., 66.5 lks. dist., mkd. X BT at the base.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>	

CHAINS	
80.30	The 1/4 sec. cor. of secs. 2 and 35, on the N. bdy. of the Tp., heretofore described.
	<p>From the 1/4 sec. cor. of secs. 1 and 2.</p> <p>N. 88°38' W., on the E. and W. center line of sec. 2.</p> <p>Over gently rolling land, through railed area.</p>
33.00	Enter medium to dense timber, edge bears N. 15° E. and S. 15° W.
39.00	Fence, bears N. and S.
39.16	The center 1/4 sec. cor. of sec. 2.
78.20	The 1/4 sec. cor. of secs. 2 and 3.
	<p style="text-align: center;">GENERAL DESCRIPTION</p> <p>The area encompassed in this survey is located about nineteen miles northwest of Heber, Arizona. The land is rolling and is extremely rough and steep along the West Chevelon Canyon which traverses through the southern tip of section 2. Elevations range from about 6,200 to 6,500 feet above sea level.</p> <p>Dirt and gravel roads provide access north of the West Chevelon Canyon.</p> <p>Much of the area has been railed and is now covered with native grasses and thinly scattering juniper and pinyon. The undisturbed areas are covered with thick stands of juniper and pinyon.</p> <p>The Babbitt Winter Ranch is located in the SW 1/4 of section 2. The area is used for livestock grazing.</p> <p>There is no evidence of minerals or mining activities in the area.</p> <p>The mean magnetic declination is 13°30' E., with a range of 4°00' in local attraction.</p>



14

CERTIFICATE OF SURVEY

(I) ~~(We)~~ Harry K. Smith, Cadastral Surveyor, HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 16th day of September, 1976 (I) ~~(We)~~ have dependently resurveyed a portion of the North boundary of Township 14 North, Range 15 East, dependently resurveyed a portion of the North boundary and a portion of the subdivisional lines and surveyed subdivisions in section 2 of Township 14 North, Range 14 East

of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by (me), ~~(us)~~ and under (my) ~~(our)~~ direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 19, 1980  
(Date)

*Harry K. Smith*  
(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north boundary of T. 14 N., R. 15 E., the dependent resurvey of a portion of the north boundary and a portion of the subdivisional lines and the survey of subdivisions in section 2 of T. 14 N., R. 14 E., of the Gila and Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

FEB 25 1981  
(Date)

*D. Voorhees*  
(Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in \_\_\_\_\_ is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)