

FIELD NOTES

OF THE

 CORRECTIVE DEPENDENT RESURVEY

 OF A PORTION OF

 THE SUBDIVISIONAL LINES

 AND

 THE SUBDIVISION OF

 SECTION 4

 TOWNSHIP 9 NORTH, RANGE 25 EAST

Of the _____ GILA AND SALT RIVER _____ Meridian,
 In the State of _____ ARIZONA _____

EXECUTED BY

JERRY L. WAHL _____ SUPERVISORY CADASTRAL SURVEYOR

Under special instructions dated _____ MAY 3 _____, 19 73, approved _____ MAY 8, 1973 _____,
 AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED JUNE 14, 1973, MARCH 3, 1977, AND
 JULY 15, 1980, AND RESPECTIVELY APPROVED JUNE 14, 1973, MARCH 9, 1977, AND
 NOVEMBER 20, 1980 _____, which provided for the surveys included under ~~XXXXXX~~ Group
 Number _____ 558 _____, and assignment instructions dated _____ JULY 15 _____, 19 80.

Survey commenced _____ JULY 15 _____, 19 80
 Survey completed _____ AUGUST 15 _____, 19 80

INDEX DIAGRAM

Township 9 NORTH, Range 25 EAST,

6	5	6 4	2 3	2	1
7	8	3 9	10	11	12
18	17	16	15	14	13
19	20	21	22	23	24
30	29	28	27	26	25
31	32	33	34	35	36

Subdivision of section 4 . . . pp. 7 - 9

T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

The following field notes describe the corrective dependent resurvey of a portion of the subdivisional lines and of the subdivision of section 4, Township 9 North, Range 25 East of the Gila and Salt River Meridian, Arizona.

The subdivisional lines were originally surveyed by A. P. Johnson, in 1882. In 1896, Chas. E. Perkins received Contract 40 providing for the survey of those portions of the subdivisional lines necessary for the proper closing of the public land surveys in this and several other townships on the north boundary of the White River Indian Reservation. Perkins' surveys involved extensive retracements of the subdivisional lines of the townships involved. The National Archive records reveal that portions of Perkins' surveys were examined by Chas. V. Sheldon, in 1896, and also by Sidney E. Blout, in 1909. As a result of the field examinations conducted of Perkins' survey work under Contract 40 it was rejected. In 1915, Blout resurveyed portions of the subdivisional lines restoring a portion of the Johnson survey, destroying such evidence of the Perkins' survey as was found. An unrecorded survey of a portion of the subdivisional lines and a partial subdivision of section 4, was performed by Michael Paige Wier, Arizona Registered Land Surveyor No. 7247, in July 1970. A dependent resurvey of a portion of the north boundary and subdivisional lines with the subdivision of certain sections was executed by Gilbert V. Olson in 1973. Olson's notes were approved and plat accepted June 5, 1975. In 1979, Ronald S. Stoll, Arizona Registered Land Surveyor No. 11758, of Lowry & Associates, (under contract with the U.S. Forest Service), retraced portions of the subdivisional lines and executed a survey of the subdivision of sections 4 and 9. The Stoll survey is recorded in the Apache County Courthouse, St. Johns, Arizona. This survey purportedly found errors on the south and west section lines of section 4 that would affect the subdivision of the section. The investigative retracement performed prior to the corrective resurvey confirmed that the purported errors did exist.

This corrective resurvey and survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions dated May 3, 1973, the Supplemental Special Instructions dated June 14, 1973, the Supplemental Special Instructions dated March 3, 1977, and the Supplemental Special Instructions dated July 15, 1980, for Group 558, Arizona.

The directions of the lines were determined by direct solar, stellar and Polaris observations. They refer to the true meridian. The lines were carried by conventional traverse methods and the bearings verified by additional observations at various points throughout this survey. The horizontal and vertical angles were determined by using the mean value of repetitive angles measured with a Wild T-16 theodolite. The distances were determined with a Hewlett-Packard 3805 E.D.M. and a steel tape, and reduced to the horizontal equivalents throughout this survey.

T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

Preliminary to the corrective resurvey, the lines of the official surveys were retraced and diligent search was made for all corners and other calls of the record. Certain positions could be accepted as perpetuations of the original corner location, or acceptable determinations by local surveys. Identified corners were remonumented in their original positions. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of sections 3, 4, 9, and 10, as scaled from U. S. Geological Survey quadrangle map "BOUNDARY BUTTE, ARIZ.," 1968, 7 1/2 minute series, is:

Latitude 34° 11.9' N., Longitude 109° 41.4' W.

The observed mean magnetic declination is 12 1/2° E.

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

Restoring the survey executed by A. P. Johnson
in 1882, and correcting the resurvey by
Gilbert V. Olson in 1973

From the cor. of secs. 3, 4, 9, and 10, as reestablished from the remains of the original bearing trees by Daniel M. Wier, Arizona R.L.S. No. 1476, and is accepted as a careful and faithful reestablishment of the original cor. position, monumented with an iron pipe, 1 1/2 ins. diam., to which a brass washer mkd. L.S. 1476 is attached, firmly set, projecting 15 ins. above ground in a mound of stone, 3 ft. base to top, with brass cap, 3 ins. diam., mkd.

CARLOCK
SECTIONS
4|3
9|10
T9N R25E
G&SRB&M

from which the remains of the original bearing trees

A pine stump, 28 ins. diam., bears S. 20° 40' E., 168 1/2 lks. dist., with evidence of healed blaze. (Record, S. 21° E., 167 lks.)

A rotted pine stump, 28 ins. diam., bears S. 81° 39' W., 159 lks. dist. (Record, S. 75° E., 158 lks.) James E. Muth, Arizona R.L.S. No. 13014, U.S.F.S. surveyor and a local landowner, indicated that at a time previous to the decomposition of this stump that scribe marks were visible.

from which

The cor. of fences extending N. 10° E. and S. 80° E., bears N. 68 1/2° E., 22 lks. dist.

N. 0° 21' W., bet. secs. 3 and 4.

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS		
	<p>Over nearly level open land, bet. dirt farm road and fence.</p> <p>40.20 The 1/4 sec. cor. of secs. 3 and 4, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 22 ins. above ground, in a supporting mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E 1/4 S 4 S 3</p> <p style="text-align: center;">1973</p> <p>from which a bearing tree not of original record</p> <p>A pine, 26 ins. diam., bears S. 28° 09' W., 94 1/2 lks. dist. with visible scribe marks 1/4 S BT on open blaze. (1973 Record, S. 35° W., 94 lks.)</p> <p>from which the 1973 bearing tree</p> <p>A pine, 8 ins. diam., bears S. 45 1/4° E., 32 lks. dist., with overgrown blaze. (Record, S. 38 1/4° E.)</p> <p>from which</p> <p>A brass tablet, 4 ins. diam., cemented in lava rock outcrop, bears S. 27° 46' W., 86.6 lks. dist., mkd. "U. S. Dept. of Agriculture Forest Service GILESPIE."</p> <p>A basalt stone of unknown origin, 18 x 8 x 5 ins., loosely set in scattered old mound of stone, bears S. 83° 12' W., 253 1/2 lks. dist., dimly mkd. 1/4 on W. face, projecting 12 ins. above ground, with 3/4 ins. iron pipe in-place alongside. This point was indicated on the unrecorded survey plat, dated July 1970, prepared by Michael Paige Wier, Arizona R.L.S. No. 7247, as the E 1/4 sec. cor. of sec. 4.</p> <p>Added the marks 1980 to the cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 7° 38' W., beginning new measurement.</p> <p>Continue over nearly level land, through occasional scattered pine.</p>	
40.07	<p>The cor. of secs. 3, 4, 33, and 34, monumented with an iron post, 2 1/2 ins. diam., with brass cap mkd. as described in the field note records of the corrective dependent resurvey of a portion of the S. bdy., T. 10 N., R. 25 E., executed concurrently under this same group.</p> <hr style="width: 80%; margin: 10px auto;"/> <p>From the cor. of secs. 3, 4, 9, and 10.</p> <p>S. 89° 29' W., bet. secs. 4 and 9.</p> <p>Over gradually rising land, through moderate pine timber.</p>	

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

19.975

The E 1/16 sec. cor. of secs. 4 and 9, established by Ronald S. Stoll, Arizona R.L.S. 11758, as recorded in the Apache County Courthouse, St. Johns, Arizona, and is accepted as a careful and faithful determination of the cor. position, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 16 ins. above ground,, in a supporting mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.

U.S. DEPARTMENT OF AGRICULTURE
UNLAWFUL TO DISTRUB

T9N R25E

E

1/16

S 4

S 9

1979

LS11758

CADASTRAL SURVEY
FOREST SERVICE

From this point, the E 1/16 sec. cor. of secs. 4 and 9, erroneously established by Olson in 1973, bears S. 88° 50' E., 46.4 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd. as described in the 1973 resurvey. I removed the iron post and defaced the 1973 bearing tree to the SW.

from which the 1973 NE bearing tree

A pine, 10 ins. diam., now bears N. 86° 35' E., 66 1/2 lks. dist., with overgrown blaze.

from which 1979 bearing trees mkd. by Stoll

A pine, 16 ins. diam., bears S. 82° E., 3 1/2 lks. dist., mkd. X BT on open blaze and 2 ins. metal disc nailed in blaze.

A pine, 16 ins. diam., bears S. 45 1/4° W., 20 1/2 lks. dist., mkd. X BT on open blaze and 2 ins. metal disc nailed in blaze.

A pine, 14 ins. diam., bears N. 53 3/4° W., 34 1/2 lks. dist., mkd. X BT on open blaze and 2 ins. metal disc nailed in blaze.

from which

An iron pipe, 3/4 ins. diam., firmly set, projecting 3 ins. above ground, bears N. 20 1/2° E., 9 lks. dist. established by Michael Paige Wier, Arizona R.L.S. No. 7247, as shown on the unrecorded plat of survey dated July 1970.

Cor. falls 12 lks. W. of old fence line extending N. and S.

S. 89° 29' W., beginning new measurement.

Continue over nearly level land through moderate pine timber.

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS		
19.975	<p>The 1/4 sec. cor. of secs. 4 and 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, and a mound of stone, 3 ft. base, 2 ft. high, N. of the post, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E 1/4 $\frac{S\ 4}{S\ 9}$ 1973</p> <p>from which the original bearing tree</p> <p>An oak, 24 ins. diam., bears S. 73 3/4° W., 33 1/2 lks. dist., with fragmentary scribe marks "S B" visible on partially overgrown blaze. (Record: S. 72° W., 33 lks.) (1973 record: S. 31° W., 34 lks.)</p> <p>from which new bearing trees</p> <p>A pine, 8 ins. diam., bears S. 53° E., 22 1/2 lks. dist., mkd. 1/4 S9 BT.</p> <p>A pine, 10 ins. diam., bears N. 2 3/4° W., 20 lks. dist., mkd. 1/4 S4 BT.</p> <p>from which</p> <p>An angle iron of unknown origin, 3/4 x 3/4 in., bears N. 50° W., 38.0 lks. dist., firmly set, projecting 5 ins. above ground, painted orange.</p> <p>Add the marks 1980 to the cap.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 19' W., beginning new measurement.</p> <p>Ascend slightly through moderate pine, juniper and oak timber.</p>	
29.80	<p>Single pole transmission line, bears N. 32° E. and S. 32° W.</p>	
36.10	<p>The cor. of secs. 4, 5, 8, an 9, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 8 ins. above ground, in a mound of stone, 4 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R25E S 5 S 4 S 8 S 9 1973</p> <p>from which the original bearing trees</p> <p>A pine snag, 24 ins. diam., bears N. 19° E., 142 1/2 lks. dist., mkd. T9N R25E S4 BT visible on partially overgrown blaze. (Record: N. 14° E., 42 lks.) (1973 Record, N. 14° E., 143 lks.)</p> <p>A pine stump, 20 ins. diam., bears S. 66 1/4° E., 119 lks. dist., with cut tree alongside with visible marks S9 BT on rotted wood fragment. (Record: S. 66° E., 117 lks.)</p>	

8

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

The root hole of a fallen pine, 30 ins. diam., bears S. 12° W., 102 lks. dist., with overgrown blaze. (Record, 100 lks.) (1973 Record, S. 11 1/2° W., 100 lks.)

A pine snag, 24 ins. diam., bears N. 16 3/4° W., 89 lks. dist., marks 1/4 S5 BT visible on open blaze. (Record, N. 17° W., 87 lks.)

from which the 1973 bearing trees

A pine, 6 ins. diam., bears N. 34 1/4° E., 27 lks. dist., with visible scribe marks T9N R25E S4 BT. (Record, N. 35 3/4° E.)

A pine, 8 ins. diam., bears S. 42 1/2° E., 31 1/2 lks. dist., with visible scribe marks T9N R25E S9 BT. (Record, S. 42 1/4° E., 31 lks)

A pine, 6 ins. diam., bears S. 74° W., 19 lks. dist., with visible scribe marks T9N R25E S8 BT. (Record, S. 79 1/4° W.)

A pine, 6 ins. diam., bears N. 28 3/4° W., 23 1/2 lks. dist., with visible scribe marks T9N R25E S5 BT. (Record, N. 28° W., 23 lks)

Add the marks 1980 to the cap.

N. 6° 46' W., bet. secs. 4 and 5.

Over nearly level land, through thick pine timber.

39.50 Descend into prominent wash, drains NE.

40.17 The 1/4 sec. cor. of secs. 4 and 5, reestablished by Ronald S. Stoll, Arizona R.L.S. No. 11758, as recorded in the Apache County Courthouse, St. Johns, Arizona, and is accepted as a careful reestablishment of the original cor. position, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground in a supporting mound of stone, 3 1/2 ft. base to top, with aluminum cap mkd.

U.S. DEPT OF AGRICULTURE
UNLAWFUL TO DISTRUB
T9N R25E
1/4
S 5 | S 4

1979
LS 11758
CADASTRAL SURVEY
FOREST SERVICE

From this point, the 1/4 sec. cor. of secs. 4 and 5, erroneously established by Olson in 1973, bears N. 8° 09' W., 30.6 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 20 ins. above ground, in supporting mound of stone, 3 1/2 ft. base to top, with brass cap mkd. as described in the 1973 resurvey. I removed the iron post.

from which the 1973 bearing trees

Corrective Dependent Resurvey of a Portion of the
Subdivisional Lines
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A pine, 12 ins. diam., now bears N. 62° E., 36 1/2 lks. dist., with visible scribe marks 1/4 S4 BT on partially overgrown blaze and 2 in. metal disc nailed in blaze.</p> <p>A pine, 18 ins. diam., now bears N. 14 1/4° W., 107 1/2 lks. dist., with visible scribe marks 1/4 S5 BT on partially overgrown blaze</p>
	<p>N. 6° 46' W., beginning new measurement.</p>
	<p>Ascend northwesterly bank of wash.</p>
3.33	<p>Top of hill, descend gradual N. slope, through moderate pine and oak timber.</p>
22.43	<p>Gravel road, 25 lks. wide, bears NE and SW.</p>
	<p>Ascend along E. slope.</p>
40.47	<p>The cor. of secs. 4, 5, 32, and 33, monumented with an iron post, 2 1/2 ins. diam., with brass cap mkd. as described in the field notes of the corrective dependent resurvey of a portion of the S. bdy. of T. 10 N., R. 25 E., executed concurrently under this same group.</p>
<p>Corrective Dependent Resurvey of the Subdivision of Section 4 T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p>
	<p>N. 3° 54' W., on the N. and S. center line of sec. 4.</p>
	<p>Over gently rolling land, through thick pine, oak, and juniper timber.</p>
40.52	<p>The center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line, established by Ronald S. Stoll, Arizona R.L.S. NO. 11758, as recorded in the Apache County Courthouse, St. Johns, Arizona, and is accepted as a careful establishment of the cor. position, monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, in a supporting mound of stone, 4 ft. base to top, with aluminum cap mkd.</p>
<p>U.S. DEPT OF AGRICULTURE UNLAWFUL TO DISTURB T9N R25E C 1/4 S 4 1979 LS11758 CADASTRAL SURVEY FOREST SERVICE</p>	
	<p>From this point, the center 1/4 sec. cor. of sec. 4, erroneously established by Olson in 1973, bears N. 71° 37' E., 46.6 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 22 ins. above ground, in supporting mound of stone, 3 1/2 ft. base to top, with brass cap mkd. as described in the 1973 resurvey. I removed the iron post and defaced the NW bearing tree.</p>

Corrective Dependent Resurvey of the
Subdivision of Section 4
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>from which the 1973 NE bearing tree</p> <p>A pine, 12 ins. diam., now bears N. 63 1/4° E., 61 lks. dist., mkd. C 1/4 S4 BT on partially overgrown blaze.</p> <p>from which the 1979 bearing trees mkd. by Stoll</p> <p>A pine, 14 ins. diam., bears N. 44° E., 44 1/2 lks. dist., mkd. X BT on open blaze and 2 in. metal disc nailed in blaze.</p> <p>A pine, 18 ins. diam., bears S. 63 1/2° E., 57 1/2 lks. dist., mkd. X BT on open blaze and 2 in. metal disc nailed in blaze.</p> <p>from which</p> <p>A power pole, bears N. 76° 13' W., 122.4 lks. dist., with number 146 on E. side.</p> <hr/> <p>N. 3° 54' W., beginning new measurement.</p>
1.98	Single pole transmission line bears N. 32° E. and S. 32° W.
38.57	Fence line extends E. and W.
39.21	The 1/4 sec. cor. of secs. 4 and 33, monumented with an iron post, 2 1/2 ins. diam., with brass cap, mkd. and described in the field note record of a corrective dependent resurvey of a portion of the S. bdy. of T. 10 N., R. 25 E., executed concurrently under this same group.
	<hr/> <p>From the 1/4 sec. cor. of secs. 3 and 4.</p> <p>S. 89° 51' W., on the E. and W. center line of sec. 4.</p> <p>Over nearly level open land.</p>
10.00	Ascend E. slope through thick pine and oak timber.
20.40	Fence line extends N. and S.
21.22	<p>The C-E 1/16 sec. cor. of sec. 4, established by Ronald S. Stoll, Arizona R.L.S. NO. 11758, and is accepted as a careful and faithful establishment of the cor. position, mkd. with a cross (+) chiseled on rock.</p> <p>From this point, the C-E 1/16 sec. cor. of sec. 4, erroneously established by Olson in 1973, bears N. 70° 39' E., 23.7 lks. dist., monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 18 ins. above ground, in supporting mound of stone, 3 ft. base to top, with brass cap mkd. as described in the 1973 resurvey. I removed the iron post and defaced the NW bearing trees.</p> <p>from which the 1973 NE bearing tree</p> <p>A pine, 6 ins. diam., now bears N. 79 1/2° E., 34 1/2 lks. dist., mkd. X BT on open blaze.</p> <p>from which the 1979 bearing trees mkd. by Stoll</p>

Corrective Dependent Resurvey of the
Subdivision of Section 4
T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A pine, 8 ins. diam., bears S. 27° W., 62 1/2 lks. dist., mkd. X BT on open blaze and 2 in. metal disc nailed in blaze.</p> <p>A pine, 6 ins. diam., bears N. 64 1/4° W., 22 1/2 lks. dist., mkd. X BT on open blaze and 2 in. metal disc nailed in blaze.</p> <p>At the corner point</p> <p>Set a brass tablet, 3 1/4 ins. diam., 3 1/2 in. stem, cemented in drill hole at center of the cross (+), with top mkd.</p> <div style="text-align: center;"> $\begin{array}{c} \text{E } 1/16 \\ \text{C} \text{-----} \text{C} \\ \text{S } 4 \\ 1980 \end{array}$ </div> <hr/> <p>S. 89° 51' W., beginning new measurement.</p> <p>Descend gradual W. slope, through moderate pine, oak, and juniper timber.</p>
21.22	<p>The center 1/4 sec. cor. of sec. 4.</p> <hr/> <p>S. 89° 51' W., beginning new measurement.</p>
1.76	<p>Single pole transmission line, bears N. 32° E. and S. 32° W.</p>
38.06	<p>The 1/4 sec. cor. of secs. 4 and 5.</p> <hr/> <p>From the C-E 1/16 sec. cor. of sec. 4.</p> <p>N. 5° 48.6' W., along the N. and S. center line of the NE 1/4 of sec. 4.</p>
39.59	<p>The E 1/16 sec. cor. of secs. 4, T. 9 N., R. 25 E., and 33, T. 10 N., R. 25 E., monumented with an iron post, 2 1/2 ins. diam., with brass cap mkd. as described in the field note record of a corrective dependent resurvey of T. 10 N., R. 25 E., executed concurrently under this same group.</p> <hr/> <p>From the E 1/16 cor. of secs. 4 and 9.</p> <p>N. 2° 08.1' W., along the N. and S. center line of the SE 1/4 of sec. 4.</p>
40.34	<p>The C-E 1/16 sec. cor. of sec. 4.</p> <hr/>

T. 9 N., R. 25 E., Gila and Salt River Mer., Arizona

CHAINS

GENERAL DESCRIPTION

The land encompassed in this corrective survey is located about 3 1/2 miles south of the small town of Vernon, Arizona, which is approximately 27 miles west of Springerville, Arizona, along U. S. Highway No. 60, and is in the foothills sloping generally to the north, with several prominent drainages. The terrain is predominately covered with scattered to dense stands of pine, juniper and oak. Much of the terrain is covered with outcrops of malpais lava rock. There is an occupied ranch residence located in the southeast quarter of section 4.

Access is by way of country road from Vernon which traverses through the northwest 1/4 of section 4, and a ranch road which provides access to the north and east boundaries of section 4.

The predominant use is cattle ranching. Some wood cutting is evident in the westerly portion of section 4.

CERTIFICATE OF SURVEY

(I) ~~XXXX~~ Jerry L. Wahl, HEREBY
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 3rd day
 of May, 1973, ~~XXXXXXXXXX~~ and Supplemental Special Instructions
 dated June 14, 1973, March 3, 1977 and July 15, 1980, (I) have corrected
 the dependent resurvey of a portion of the subdivisional lines and the
 subdivision of section 4, Township 9 North, Range 25 East,

of the Gila and Salt River Meridian, in the State of Arizona, which
 are represented in the foregoing field notes as having been executed by (me), ~~XXX~~ and under (my)
~~XXXX~~ direction; and that said survey has been made in strict conformity with said special instruc-
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in
 specific manner described in the foregoing field notes.

May 6, 1981
 (Date)

Jerry L. Wahl
 Supervisory (Cadastral Surveyor)

 (Date)

 (Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
 Denver, Colorado

The foregoing field notes of the corrective dependent resurvey of a portion of
 the subdivisional lines and the subdivision of section 4, Township 9 North,
 Range 25 East, of the Gila and Salt River Meridian, Arizona

executed by Jerry L. Wahl, Supervisory Cadastral Surveyor
 having been critically examined and found correct, are hereby approved.

JUN 30 1981
 (Date)

Ray S. Spaight
 ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in
 _____, is a true copy of the original field notes.

 (Date)

 (Chief, Cadastral Survey Examination and Approval Staff)