

Form 9600-9  
(December 1979)  
(formerly 9180-6)

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

ORIGINAL

BOOK 5134

PAGE 1

# FIELD NOTES

OF THE DEPENDENT RESURVEY OF

A PORTION OF THE SOUTH BOUNDARY (SECOND STANDARD PARALLEL NORTH),

A PORTION OF THE WEST BOUNDARY

A PORTION OF THE SUBDIVISIONAL LINES

AND THE SURVEY OF SUBDIVISIONS IN SECTIONS 17, 18, 19, 20 AND 30,

TOWNSHIP 9 NORTH, RANGE 27 EAST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

## EXECUTED BY

HARRY K. SMITH,

CADASTRAL SURVEYOR

Under special instructions dated AUGUST 2, 1979, approved AUGUST 2, 1979,

, which provided for the surveys included under U.S. Survey/Group  
Number 613, and assignment instructions dated AUGUST 2, 1979.

Survey commenced AUGUST 10, 1979

Survey completed OCTOBER 4, 1979

# INDEX DIAGRAM

Township 9 North, Range 27 East

6	5	4	3	2	1
7	8	9	10	11	12
25	25				
18	24 17	11 16	15	14	13
21	21				
4	19 20	10 21	22	23	24
18	17				
30	15 29	9 28	27	26	25
14	13	8			
31	12 32	7 33	34	35	36
	1				

Subdivision of Sec. 17	-----	Page 26
" " " 18	-----	" 27
" " " 19	-----	" 30
" " " 20	-----	" 40
" " " 30	-----	" 41

T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona

## CHAINS

The history of surveys of Township 9 North, Range 27 East, Gila and Salt River Meridian, Arizona, is as follows:

The south boundary (Second Standard Parallel North) and the west boundary were surveyed in 1875 by C. Burton Foster, U.S. Deputy Surveyor, and resurveyed in 1882 by A.P. Johnson, Deputy Surveyor, who at the same time subdivided the township. The west boundary was resurveyed in 1937 by Roger F. Wilson, Surveyor. The south boundary (Second Standard Parallel North) was resurveyed in 1940 by Ty White, Surveyor, Claude F. Warner, Transitman and Frank Motoh, Public Land Surveyor. Green's Peak Hideaway Subdivision located within section 19, was surveyed in 1961 by C.H. Robertson, Registered Land Surveyor No. 772 in the State of Arizona.

The following field notes describe the dependent resurvey of a portion of the south boundary (Second Standard Parallel North), a portion of the west boundary, a portion of the subdivisional lines and the survey of subdivisions in secs. 17, 18, 19, 20 and 30 of the township.

The survey was executed in accordance with specifications set forth in the Manual of Surveying Instructions, 1973, the Special Instructions for Group No. 613, Arizona, dated August 2, 1979, and Instruction Memorandum No. 79-441.

Preliminary to the resurvey the lines of prior surveys and resurveys were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The directions of lines were determined from United States Coast and Geodetic triangulation station GREEN dated 1936 and refer to the true meridian. Measurements were made with a Zeiss SM-4 electronic instrument.

The geographic position of the standard corner of sections 32 and 33 on the south boundary of the township determined by a tie to the United States Coast and Geodetic triangulation station "GREEN" dated 1936, is as follows:

Latitude  $34^{\circ}07'31.1''$  N. Longitude  $109^{\circ}29'51.8''$  W.

The mean magnetic declination is  $14^{\circ}$  E.

Dependent Resurvey of a Portion of the S. Bdy.  
(Second Standard Parallel North), T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

(Restoring the 1940 resurvey by Ty White, Claude F. Warner and Frank Motoh)

4

Dependent Resurvey of a Portion of the S. Bdy.  
(Second Standard Parallel North), T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Beginning at the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set in a mound of stone, 3½ ft. base, 18 ins. high, to top, with brass cap mkd. as described in the official record of the 1940 resurvey from which the remains of the bearing trees mkd. in 1882.</p>	
	<p>A ponderosa pine, 32 ins. diam., bears N. 57¼° E., 24 lks. dist., mkd. T9N R27E S33 SC BT.</p>	
	<p>A ponderosa pine stump, 29 ins. diam., bears S. 20°E., 43 lks. dist.</p>	
	<p>A ponderosa pine, 16 ins. diam., bears S. 69½° W., 20.5 lks. dist., mkd. with an open blaze. (Record bearing and dist. S. 66° W., 19 lks.)</p>	
	<p>A stumphole, bears N. 29½° W., 20 lks. dist., a ponderosa pine, 10 ins. diam., lying alongside is mkd. T9N R27E S32 SC BT.</p>	
	<p>And a new bearing tree</p>	
	<p>A ponderosa pine, 8 ins. diam., bears N. 35½° W., 52.5 lks. dist., mkd. T9N R27E S32 SC BT.</p>	
	<p>Add the marks 1979 to the brass cap.</p>	
	<p>The cor. is N. 52½° E., 10 lks. dist. from a fence cor.; fences extend N, E, SW and W.</p>	
	<p>S. 89°45' W., on the S. bdy. of sec. 32.</p>	
	<p>Over rolling land, through medium timber.</p>	
<p>20.70</p>	<p>Graded road, bears SE and NW.</p>	
<p>40.11</p>	<p>The standard 1/4 sec. cor. of sec. 32, monumented with an iron post, 1 in. diam., projecting 6 ins. above ground with brass cap mkd. as described in the official record of the 1940 resurvey from which the bearing trees mkd. in 1940.</p>	
	<p>A ponderosa pine, 13 ins. diam., bears N. 32 1/4° E., 138 lks. dist., mkd. 1/4 S32 SC BT.</p>	
	<p>A ponderosa pine, 10 ins. diam., bears N. 37¼° W., 123 lks. dist., mkd. with a healed blaze.</p>	
<p>Dependent Resurvey of a Portion of the W. Bdy., T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona</p>		
<p>(Restoring the 1937 resurvey by Roger F. Wilson)</p>		
<p>From the cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., set in a mound of stone, 4 ft. base, 3 ft. high, to top, with brass cap mkd. as described in the official record of the 1937 resurvey, from which</p>		

Dependent Resurvey of a Portion of the W. Bdy.,  
T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona

## CHAINS

A fir, 13 ins. diam., mkd. in 1937, bears  
N.  $53\frac{1}{2}^{\circ}$  E., 67 lks. dist., mkd. with a healed  
blaze.

A white pine, 13 ins. diam., mkd. in 1937, bears  
S.  $56\frac{1}{2}^{\circ}$  E., 19 lks. dist., mkd. T9N R27E S31 BT.

A fir stump, 24 ins. diam., mkd. in 1882, bears  
S.  $42^{\circ}$  E., 50 lks. dist., no visible markings.

A fir stump, 24 ins. diam., mkd. in 1937, bears  
S.  $55^{\circ}$  W., 27 lks. dist., the fallen tree lying  
alongside is mkd. T9N R26E S36 BT.

A fir, 20 ins. diam., mkd. in 1937, bears N.  $73^{\circ}$  W.,  
47 lks. dist., bark scribed T9N R26E S25 BT.

A fir, 33 ins. diam., mkd. in 1882, bears N.  $45^{\circ}$  W.,  
15 lks. dist., mkd. with a healed blaze.

And a new bearing tree

A white pine, 9 ins. diam., bears S.  $80^{\circ}$  W.,  
30 lks. dist., mkd. T9N R26E S36 BT.

Add the marks 1979 to the brass cap.

N.  $3^{\circ}22'$  E., bet. secs. 25 and 30.

Over rolling land, through dense timber.

18.30 Fence, bears S.  $60^{\circ}$  E. and N.  $60^{\circ}$  W.

20.265 Point for the S  $1/16$  sec. cor. of secs. 25 and 30.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in  
the ground, with brass cap mkd.

T9N  
S  $1/16$   
R26E | R27E  
S25 | S30  
1979

from which

A fir, 7 ins. diam., bears S.  $21^{\circ}$  W., 148.5 lks.  
dist., mkd. S  $1/16$  S25 BT.

A ponderosa pine, 4 ins. diam., bears S.  $72\frac{1}{2}^{\circ}$  W.,  
107 lks. dist., mkd. X BT at the base.

Raise a mound of stone,  $2\frac{1}{2}$  ft. base,  $1\frac{1}{2}$  ft. high, W. of  
the cor.

Continue over gently rolling land, through scattering  
timber.

40.53 The  $1/4$  sec. cor. of secs. 25 and 30, monumented with an  
iron post, 1 in. diam., projecting 10 ins. above ground,  
with brass cap mkd. as described in the official record  
of the 1937 resurvey, from which

A pine stump, 16 ins. diam., mkd. in 1882, bears  
N.  $85^{\circ}$  E., 76 lks. dist., no visible marks.

6

Dependent Resurvey of a Portion of the W. Bdy.,  
T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona

## CHAINS

A ponderosa snag, 21 ins. diam., mkd. in 1937, bears  
S. 59° E., 229 lks. dist., mkd. 1/4 S30 BT.

A pine stump, 33 ins. diam., mkd. in 1882, bears  
S. 86° W., 108 lks. dist., mkd. with a healed  
blaze.

And new bearing trees

A ponderosa pine, 14 ins. diam., bears  
N. 86½° E., 9 lks. dist., mkd. 1/4 S30 BT.

A ponderosa pine, 12 ins. diam., bears  
N. 42 1/4° W., 121 lks. dist., mkd. 1/4 S25 BT.

Add the marks 1979 to the brass cap.

The cor. is in an E-W fence.

From the cor. of secs. 19, 24, 25 and 30, on the W. bdy.  
of the Tp., monumented with an iron post, 2 ins. diam.,  
projecting 4 ins. above a mound of stone, 3 ft. base, 18  
ins. high, with brass cap mkd. as described in the  
official record of the 1937 resurvey, from which

A ponderosa pine, 18 ins. diam., mkd. in 1937, bears  
N. 67° E., 44 lks. dist., mkd. T9N R27E S19 BT.

A ponderosa pine, 23 ins. diam., mkd. in 1882, bears  
N. 81½° E., 34 lks. dist., mkd. T9N R27E S19 BT.

A pine stump, 19 ins. diam., mkd. in 1937, bears  
S. 58° E., 258 lks. dist., mkd. BT.

A ponderosa pine snag, 26 ins. diam., mkd. in 1882,  
bears S. 62½° W., 51 lks. dist., mkd.  
T9N R26E S25 BT.

A ponderosa pine, 23 ins. diam., mkd. in 1882,  
bears N. 9 1/4° W., 83 lks. dist., mkd.  
T9N R26E S19 BT.

And new bearing trees

A ponderosa pine, 1 in. diam., bears S. 40° E.,  
18.5 lks. dist., mkd. T9N R27E S30 BT.

A ponderosa pine, 10 ins. diam., bears S. 42½° W.,  
66 lks. dist., mkd. T9N R26E S25 BT.

Add the marks 1979 to the brass cap.

The cor. is 18 lks. W. of a N-S fence.

N. 1°12' W., bet. secs. 19 and 24.

Over rolling land, through medium to dense timber.

20.08

Point for the S 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in  
the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the W. Bdy.,  
T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona

## CHAINS

T9N  
S 1/16  
R26E | R27E  
S24 | S19  
1979

from which

A ponderosa pine, 8 ins. diam., bears N. 76° E.,  
12.5 lks. dist., mkd. S 1/16 S19 BT.

A ponderosa pine, 8 ins. diam., bears S. 49° W.,  
68.5 lks. dist., mkd. S 1/16 S24 BT.

Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of  
the cor.

The cor. is 94 lks. W. of a N-S fence.

40.16 The 1/4 sec. cor. of secs. 19 and 24, monumented with an  
iron post, 1 in. diam., set in a mound of stone, 3 ft.  
base, 1 ft. high, to top, with brass cap mkd. as  
described in the official record of the 1937 resurvey,  
from which

A ponderosa pine, 23 ins. diam., mkd. in 1882, bears  
N. 67 1/4° E., 32 lks. dist., mkd. BT through a  
partially healed blaze. This same tree was  
remarked in 1937 and reads 1/4 S19 BT.

A pine stump, 20 ins. diam., mkd. in 1882, bears  
S. 66½° W., 90 lks. dist., no visible markings.

A ponderosa pine, 20 ins. diam., mkd. in 1937, bears  
N. 85¾° W., 173 lks. dist., mkd. 1/4 S24 BT.

And new bearing trees

A ponderosa pine, 14 ins. diam., bears S. 86° E.,  
46 lks. dist., mkd. 1/4 S19 BT.

A ponderosa pine, 7 ins. diam., bears S. 47½° W.,  
18 lks. dist., mkd. 1/4 S24 BT.

Add the marks 1979 to the brass cap.

The cor. is 6 lks. W. of a N-S fence.

N. 1°54' W., beginning new measurement.

20.035 Point for the N 1/16 sec. cor. of secs. 19 and 24, falls  
on a rock outcropping, 4 x 3 x 1½ ft. above ground.

Set a brass tablet, 3 1/4 ins. diam., 3½ in. stem, in a  
drill hole in the outcropping, with top mkd.

T9N  
N 1/16  
R26E | R27E  
S24 | S19  
1979

from which

A ponderosa pine, 12 ins. diam., bears N. 49° E.,  
28.5 lks. dist., mkd. N 1/16 S19 BT.

Dependent Resurvey of a Portion of the W. Bdy.,  
T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona

CHAINS	
	<p>A boulder, 8 x 6 x 5 ft. above ground, bears N. 56° W., 23 lks. dist., mkd. XBO on the E. face.</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of the cor.</p> <p>The cor. is 39 lks. W. of a N-S fence.</p>
25.00	Track road, bears N. 80° E. curving N. and westerly.
40.07	<p>The cor. of secs. 13, 18, 19 and 24, monumented with an iron post, 2 ins. diam., set in a mound of stone, 3½ ft. base, 18 ins. high, to top, with brass cap mkd. as described in the official record of the 1937 resurvey, from which</p> <p>A ponderosa pine, 22 ins. diam., mkd. in 1937, bears N. 52¼° E., 235 lks. dist., mkd. T9N R27E S18 BT.</p> <p>A pine stump, 27 ins. diam., mkd. in 1882, bears N. 81¼° E., 120 lks. dist., no visible markings.</p> <p>A pine stump, 27 ins. diam., mkd. in 1882, bears S. 3½° E., 114 lks. dist., mkd. BT; a tree lying alongside is mkd. T9N R27.</p> <p>A ponderosa pine snag, 24 ins. diam., mkd. in 1937, bears S. 41½° W., 92 lks. dist., mkd. T9N R26E S24 BT.</p> <p>A ponderosa pine, 16 ins. diam., mkd. in 1882, bears S. 59° W., 91 lks. dist., mkd. with a healed blaze.</p> <p>A ponderosa pine, 22 ins. diam., mkd. in 1882, bears N. 43 3/4° W., 82 lks. dist., mkd. T9N R26E S13 BT.</p> <p>And new bearing trees</p> <p>A ponderosa pine, 7 ins. diam., bears S. 15½° E., 31 lks. dist., mkd. T9N R27E S19 BT.</p> <p>A ponderosa pine, 6 ins. diam., bears S. 27° W., 48 lks. dist., mkd. T9N R26E S24 BT.</p> <p>Add the marks 1979 to the brass cap.</p> <p>The cor. is about 30 lks. E. of a N-S fence.</p>
20.08	<p>N. 1°12' W., bet. secs. 13 and 18.</p> <p>Over rolling land, through medium timber.</p> <p>Point for the S 1/16 sec. cor. of secs. 13 and 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N S 1/16 R26E   R27E S13   S18 1979</p>



Dependent Resurvey of a Portion of the W. Bdy.,  
T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona

CHAINS

from which

A ponderosa pine, 11 ins. diam., bears  
N. 4 1/4° E., 16.5 lks. dist., mkd.  
S 1/16 S18 BT.

A ponderosa pine, 10 ins. diam., bears  
S. 42 1/4° W., 15 lks. dist., mkd.  
S 1/16 S13 BT.

22.00 Aqueduct, bears N. 25° E. and S. 25° W.

40.16 The 1/4 sec. cor. of secs. 13 and 18, monumented with an iron post, 1 in. diam., projecting 8 ins. above ground, with brass cap mkd. as described in the official record of the 1937 resurvey, from which the bearing trees mkd. in 1937

A pine stump, 14 ins. diam., bears S. 14° E.,  
411 lks. dist., mkd. BT.

An alligator juniper, 32 ins. diam., bears  
N. 51 1/4° W., 472 lks. dist., mkd. 1/4 S13 BT.

And a new bearing tree

A ponderosa pine, 12 ins. diam., bears S. 70° E.,  
89.5 lks. dist., mkd. 1/4 S18 BT.

A mound of stone, 3 1/2 ft. base, 1 ft. high, is W. of the cor.

Add the marks 1979 to the brass cap.

---

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

---

(Restoring the 1882 survey executed by A.P. Johnson)

From the standard cor. of secs. 32 and 33, on the S. bdy. of the Tp., heretofore described.

N. 0°29' W., bet. secs. 32 and 33.

Over rolling land, through medium to dense timber.

Along a fence, bearing irregularly N. and S.

37.64 Point for the 1/4 sec. cor. of secs. 32 and 33, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

T9N R27E  
1/4  
S32 | S33  
1979

from which

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>A ponderosa pine, 8 ins. diam., bears S. 78° E., 57.5 lks. dist., mkd. 1/4 S33 BT.</p>	
	<p>A ponderosa pine, 16 ins. diam., bears S. 62° W., 81.5 lks. dist., mkd. 1/4 S32 BT.</p>	
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>	
38.60	<p>Draw drains easterly.</p>	
75.28	<p>The cor. of secs. 28, 29, 32 and 33, at intersection of fences extending N, E and S. This position is har- moniously related to identified original cors. and is accepted as the best available evidence of the original cor. position.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R27E S29   S28 S32   S33 1979</p>	
	<p>from which</p>	
	<p>A re-bar, of unknown origin, 3/8 in. diam., projecting 4 ins. above ground, bears S. 77° E., 97 lks. dist.</p>	
	<p>A ponderosa pine, 15 ins. diam., bears S. 78° W., 106.5 lks. dist., mkd. T9N R27E S32 BT.</p>	
	<p>An alligator juniper, 6 ins. diam., bears N. 32° W., 30.5 lks. dist., mkd. T9N R27E S29 BT.</p>	
	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of the cor.</p>	
	<p>From the 1/4 sec. cor. of secs. 28 and 33, monumented with a basalt stone, 18 x 11 x 5 ins., firmly set in a mound of stone, 2½ ft. base, 1 ft. high, mkd. 1/4 on the S. face.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R27E 1   S28 4   S33 1979</p>	
	<p>The cor. is 18 lks. N. of an E-W fence.</p>	
	<p>N. 89°58' W., bet. secs. 28 and 33.</p>	
	<p>Over gently rolling land, through scattering timber.</p>	

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
40.35	<p>Along the N. side of an E-W fence.</p> <p>The cor. of secs. 28, 29, 32 and 33.</p>	
40.07	<p>N. 0°37' W., bet. secs. 28 and 29.</p> <p>Over rolling land, through scattering timber.</p> <p>Along a N-S fence.</p> <p>The 1/4 sec. cor. of secs. 28 and 29, at intersection of fences extending N, E and S. This position is harmoniously related to identified original cors. and is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E 1/4 S29   S28 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 68° W., 59 lks. dist., mkd. 1/4 S29 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears N. 7° W., 126.5 lks. dist., mkd. X BT at the base.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, NW of the cor.</p> <p>The cor. is 10 lks. N. of a track road, bears E and W.</p>	
40.21	<p>N. 0°42' W., beginning new measurement.</p> <p>The cor. of secs. 20, 21, 28 and 29, monumented with a mound of stone, 2 ft. base, 1 ft. high, with a re-bar, 18 ins. long, ½ in. diam., set in the center of the mound. This is accepted as the best available evidence of the original cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 10 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E S20   S21 S29   S28 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 65° W., 82 lks. dist., mkd. T9N R27E S29 BT.</p> <p style="padding-left: 40px;">A re-bar, of unknown origin, ½ in. diam., projecting 2 ins. above ground, bears West, 3.7 lks. dist.</p>	

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>A ponderosa pine, 9 ins. diam., bears N. 25° W., 44 lks. dist., mkd. T9N R27E S20 BT.</p>
	<p>Reset the re-bar inside the iron post.</p>
	<p>From the cor. a fence cor., bears North, 7 lks. dist., from which fences extend N, E and S.</p>
	<p>N. 0°35' W., bet. secs. 20 and 21.</p>
	<p>Over gently rolling land, through scattering timber.</p>
	<p>Along a N-S fence.</p>
40.67	<p>The 1/4 sec. cor. of secs. 20 and 21, monumented with a volcanic stone, 18 x 17 x 10 ins., firmly set 7 ins. in the ground, mkd. 1/4 on the W. face, with a scattered mound of stone S. of the cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R27E</p>
	<p style="text-align: center;">1/4</p>
	<p style="text-align: center;">S20   S21</p>
	<p style="text-align: center;">1979</p>
	<p>from which</p>
	<p>A ponderosa pine, 5 ins. diam., bears S. 34 1/4° W., 265 lks. dist., mkd. X BT at the base.</p>
	<p>A ponderosa pine, 9 ins. diam., bears S. 74° W., 172 lks. dist., mkd. 1/4 S20 BT.</p>
	<p>A fence cor., bears West, 4 lks. dist.; fences extend S and W.</p>
	<p>Deposit the mkd. stone alongside the iron post.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of the cor.</p>
	<p>N. 0°31' W., beginning new measurement.</p>
41.09	<p>The cor. of secs. 16, 17, 20 and 21, monumented with a volcanic stone, 12 x 12 x 12 ins., firmly set 6 ins. in the ground, mkd. with 3 grooves on the S. and 4 grooves on the E. faces, with a scattered mound of stone, W. of the cor.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R27E</p>
	<p style="text-align: center;">S17   S16</p>
	<p style="text-align: center;">S20   S21</p>
	<p style="text-align: center;">1979</p>
	<p>from which</p>

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>U.S.C. &amp; G.S. Triangulation Station "Green" bears S. 48°02'38" W., 466.10 chs. dist., monumented with a standard disc, set in concrete, projecting 4 ins. above the ground, with top mkd. GREEN 1936.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>The cor. is in an E-W fence, 15 lks. W. of a track road which bears N. and S.</p>	
	<p>N. 0°57' W., bet. secs. 16 and 17.</p> <p>Over rolling open grassland.</p>	
43.26	<p>Point for the 1/4 sec. cor. of secs. 16 and 17, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E 1/4 S17 S16 1979</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, W. of the cor.</p>	
78.10	Fence, bears NE and SW.	
85.10	Wash, 30 lks. wide, 1 ft. deep, drains N. 70° E.	
86.52	<p>The cor. of secs. 8, 9, 16 and 17, monumented with a basalt stone, 18 x 15 x 8 ins., firmly set 8 ins. in the ground, and in a mound of stone, 2½ ft. base, 6 ins. high, mkd. with 4 grooves on the E. and S. faces.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E S 8   S 9 S17   S16 1979</p> <p>from which</p> <p style="padding-left: 40px;">A boulder, 4 x 3 x 1½ ft. above ground, bears S. 60½° W., 153 lks. dist., mkd. X BO on the E. face.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor.</p>	

14

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>The cor. is 52 lks. W. of a track road, bears N. 30° E., curving N. and S. 30° W., curving SE.</p> <hr/> <p>From the standard cor. of secs. 31 and 32, on the S. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 7 ins. above a scattered mound of stone, with brass cap mkd. as described in the official record of the 1940 resurvey, from which the bearing trees mkd. in 1940</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 20° E., 57 lks. dist., mkd. T9N R27E S32 SC BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 35° W., 47 lks. dist., mkd. T9N R27E S31 SC BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>N. 1°10' W., bet. secs. 31 and 32.</p> <p>Over rolling land, through dense timber.</p>	
2.00	Ridge, bears NE. and SW.	
37.49	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E 1/4 S31   S32 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 73° E., 95 lks. dist., mkd. 1/4 S32 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 62° W., 48.5 lks. dist., mkd. 1/4 S31 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p>	
63.00	Forest Service Road No. 118, graded, bears E and W.	
74.98	<p>The cor. of secs. 29, 30, 31 and 32, monumented with an unmkd. basalt stone, 18 x 16 x 4 ins., firmly set in a mound of stone, 2½ ft. base, 1 ft. high, from which the remains of the original bearing trees</p> <p style="padding-left: 40px;">A ponderosa pine, 16 ins. diam., bears N. 47° E., 72 lks. dist., mkd. with a healed blaze. (Record dist. 69 lks.)</p> <p style="padding-left: 40px;">A stump hole, bears S. 33½° W., 77 lks. dist., a partially burned ponderosa pine, 18 ins. diam., lying alongside is mkd. T1XN R.</p> <p style="padding-left: 40px;">A stumphole, bears N. 38° W., 69 lks. dist.</p> <p>At the cor. point</p>	

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T9N R27E  
S30|S29  
S31|S32  
1979

from which new bearing trees

A ponderosa pine, 12 ins. diam., bears  
N.  $63\frac{1}{4}^{\circ}$  E., 35 lks. dist., mkd.  
T9N R27E S29 BT.

A ponderosa pine, 9 ins. diam., bears  
S.  $36\frac{3}{4}^{\circ}$  E., 44 lks. dist., mkd.  
T9N R27E S32 BT.

A ponderosa pine, 8 ins. diam., bears  
S.  $64\frac{1}{2}^{\circ}$  W., 47.5 lks. dist., mkd.  
T9N R27E S31 BT.

A ponderosa pine, 10 ins. diam., bears  
N.  $20\frac{1}{2}^{\circ}$  W., 71.5 lks. dist., mkd.  
T9N R27E S30 BT.

Deposit the unmkd. stone alongside the iron post.

Raise a mound of stone,  $2\frac{1}{2}$  ft. base, 2 ft. high, W. of the cor.

From the cor. of secs. 28, 29, 32 and 33.

N.  $89^{\circ}59'$  W., bet. secs. 29 and 32.

Over rolling land, through medium to dense timber.

40.56 Point for the  $\frac{1}{4}$  sec. cor. of secs. 29 and 32, at proportionate dist.; there is no remaining evidence of the original cor. post. Both bearing trees were recovered, however, on the ground they are positioned too far apart to use the original record ties to reestablish the cor. point.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

T9N R27E  
 $\frac{1}{4}$  S29  
S32  
1979

From which the remains of the original bearing trees

A stumphole, bears S.  $36^{\circ}09'$  E., 75 lks. dist.;  
a ponderosa pine, 26 ins. diam., lying alongside  
is mkd.  $\frac{1}{4}$  S BT. (Record bearing and dist.  
S.  $86^{\circ}30'$  E., 100 lks.)

A pine stump, 22 ins. diam., bears S.  $54^{\circ}08'$  W.,  
169 lks. dist., mkd. BT. (Record bearing and  
dist. S.  $57^{\circ}$  W., 34 lks.)

And new bearing trees

16

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>A ponderosa pine, 7 ins. diam., bears S. 14½° W., 32.5 lks. dist., mkd. 1/4 S32 BT.</p>	
	<p>A ponderosa pine, 9 ins. diam., bears N. 33° W., 38.5 lks. dist., mkd. 1/4 S29 BT.</p>	
	<p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of the cor.</p>	
81.13	<p>The cor. of secs. 29, 30, 31 and 32.</p>	
	<p>N. 85°16' W., bet. secs. 30 and 31.</p>	
	<p>Over rolling land, through medium to dense timber.</p>	
9.40	<p>Forest Service Road No. 118, graded, bears S. 15° E. and N. 15° W.</p>	
19.374	<p>Point for the E 1/16 sec. cor. of secs. 30 and 31.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R27E E 1/16 <u>S30</u> S31 1979</p>	
	<p>from which</p>	
	<p>A ponderosa pine, 15 ins. diam., bears N. 34° E., 93 lks. dist., mkd. E 1/16 S30 BT.</p>	
	<p>A ponderosa pine, 10 ins. diam., bears S. 14° W., 31 lks. dist., mkd. E 1/16 S31 BT.</p>	
	<p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the cor.</p>	
32.85	<p>Logging road, bears SE and NW.</p>	
33.905	<p>Point for the W-W-E 1/256 sec. cor. of secs. 30 and 31.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 3½ ft. base, to top, with brass cap mkd.</p>	
	<p style="text-align: center;">S30 W-W-E 1/256 S31 1979</p>	
	<p>from which</p>	
	<p>A ponderosa pine, 8 ins. diam., bears N. 43° E., 43 lks. dist., mkd. W-W-E 1/256 S30 BT.</p>	
	<p>A ponderosa pine, 8 ins. diam., bears S. 33° E., 38 lks. dist., mkd. W-W-E 1/256 S31 BT.</p>	
38.748	<p>Point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no remaining evidence of the original cor.</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	



Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E., 17  
Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">T9N R27E <math>\frac{1}{4}</math> S30 S31 1979</p> <p>from which</p> <p>A ponderosa pine, 12 ins. diam., bears S. 60° E., 129 lks. dist., mkd. 1/4 S31 BT.</p> <p>A ponderosa pine, 17 ins. diam., bears S. 75° W., 17.5 lks. dist., mkd. 1/4 S31 BT.</p> <p>Raise a mound of stone, 3½ ft. base, 2½ ft. high, N. of the cor.</p>	
48.435	<p>Point for the E-W 1/64 sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S30 E-W 1/64 S31 1979</p> <p>from which</p> <p>A ponderosa pine, 8 ins. diam., bears S. 10° E., 82.5 lks. dist., mkd. X BT at the base.</p> <p>A ponderosa pine, 8 ins. diam., bears S. 64° W., 32.5 lks. dist., mkd. E-W 1/64 S31 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of the cor.</p> <p>The cor. is 70 lks. S. of a logging road, bears SE and NW.</p>	
58.122	<p>Point for the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E W 1/16 <math>\frac{S30}{S31}</math> 1979</p> <p>from which</p> <p>A ponderosa pine, 14 ins. diam., bears S. 62° E., 31 lks. dist., mkd. W 1/16 S31 BT.</p> <p>A ponderosa pine, 12 ins. diam., bears N. 26½° W., 95.5 lks. dist., mkd. W 1/16 S30 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p>	
77.884	<p>The cor. of secs. 25, 30, 31 and 36, on the W. bdy. of the Tp., heretofore described.</p> <hr/> <p>From the cor. of secs. 29, 30, 31 and 32.</p>	

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 1°22' W., bet. secs. 29 and 30.</p>
	<p>Over rolling land, through medium to dense timber.</p>
20.065	<p>Point for the S 1/16 sec. cor. of secs. 29 and 30.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R27E S 1/16 S30 S29 1979</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears N. 21° E., 28 lks. dist., mkd. S 1/16 S29 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 82° W., 81.5 lks. dist., mkd. S 1/16 S30 BT.</p>
	<p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of the cor.</p>
36.85	<p>Track road, bears S. 75° E. and N. 75° W.</p>
40.13	<p>The 1/4 sec. cor. of secs. 29 and 30, determined at record bearing and dist. from the remains of the original bearing trees</p>
	<p style="padding-left: 40px;">A ponderosa pine, 21 ins. diam., bears N. 46° E., 58 lks. dist., mkd. 1/4 S.</p>
	<p style="padding-left: 40px;">A stumphole, bears N. 39° W. 30 lks. dist.</p>
	<p>At the cor. point</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 3 ins. in the ground, to solid rock, and in a mound of stone, 4½ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R27E 1/4 S30 S29 1979</p>
	<p>from which new bearing trees</p>
	<p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 15¾° E., 49.5 lks. dist., mkd. 1/4 S29 BT.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears N. 57¾° W., 49 lks. dist., mkd. 1/4 S30 BT.</p>
	<p style="text-align: center;">—————</p>
	<p>N. 1°19' E., beginning new measurement.</p>
40.46	<p>The cor. of secs. 19, 20, 29 and 30, determined at record bearing and dist. from the remains of the original bearing trees</p>
	<p style="padding-left: 40px;">A pine stump, 34 ins. diam., bears S. 19° E., 106 lks. dist., mkd. 29; a pine 34 ins. diam., lying alongside is mkd. T9N R27E.</p>

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

19

## CHAINS

A ponderosa pine, 27 ins. diam., bears S. 63° W.,  
110 lks. dist., mkd. with a healed blaze. Scribe  
marks are now visible through a cut open blaze.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in  
the ground, to solid rock, and in a mound of stone, 4 ft.  
base, to top, with brass cap mkd.

T9N R27E	
S19	S20
S30	S29
1979	

from which new bearing trees

A ponderosa pine, 8 ins. diam., bears N. 66° E.,  
28 lks. dist., mkd. T9N R27E S20 BT.

A ponderosa pine, 8 ins. diam., bears S. 29° E.,  
18.5 lks. dist., mkd. T9N R27E S29 BT.

A ponderosa pine, 6 ins. diam., bears  
S. 45 1/4° W., 62.5 lks. dist., mkd.  
T9N R27E S30 BT.

A ponderosa pine, 8 ins. diam., bears N. 36½° W.,  
61.5 lks. dist., mkd. T9N R27E S19 BT.

From the cor. of secs. 20, 21 28 and 29.

S. 89°40' W., bet. secs. 20 and 29.

Over rolling land, through medium to dense timber.

40.46 The 1/4 sec. cor. of secs. 20 and 29, monumented with a  
basalt stone, 24 x 15 x 8 ins., firmly set 10 ins. in the  
ground, and in a mound of stone, 2½ ft. base, 6 ins.  
high, mkd. 1/4 on the N. face.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in  
the ground, with brass cap mkd.

T9N R27E	
1	S20
4	S29
1979	

from which

A ponderosa pine, 11 ins. diam., bears N. 53° E.,  
50 lks. dist., mkd. 1/4 S20 BT.

A ponderosa pine, 14 ins. diam., bears S. 79½° W.,  
52 lks. dist., mkd. 1/4 S29 BT.

Deposit the mkd. stone alongside the iron post.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, N. of  
the cor.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	N. 89°13' W., beginning new measurement.
39.77	The cor. of secs. 19, 20, 29 and 30.
	N. 85°50' W., bet. secs. 19 and 30.
	Over rolling land, through medium to dense timber.
19.42	Point for the E 1/16 sec. cor. of secs. 19 and 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T9N R27E E 1/16 <u>S19</u>           S30           1979</p>
	from which
	<p style="text-align: center;">A ponderosa pine, 7 ins. diam., bears North, 27.5 lks. dist., mkd. E 1/16 S19 BT.</p>
	<p style="text-align: center;">A ponderosa pine, 10 ins. diam., bears S. 14½° E., 23 lks. dist., mkd. E 1/16 S30 BT.</p>
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.
38.84	The 1/4 sec. cor. of secs. 19 and 30, monumented with a re-bar, 26 ins. long, 1 in. diam., projecting 11 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away Subdivision, a plat of which is on file at the Apache County Courthouse in Holbrook, Arizona. This point is accepted as the best available evidence of the original cor. position.
	At the cor. point
	Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
	<p style="text-align: center;">T9N R27E   1  <u>S19</u>   4  S30   1979</p>
	from which
	<p style="text-align: center;">A ponderosa pine, 9 ins. diam., bears N. 53½° E., 38 lks. dist., mkd. 1/4 S19 BT.</p>
	<p style="text-align: center;">A ponderosa pine, 9 ins. diam., bears S. 88° W., 32.5 lks. dist., mkd. 1/4 S30 BT.</p>
	Deposit the re-bar inside the iron post.
	Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.
	N. 84°37' W., beginning new measurement.
19.153	Point for the W 1/16 sec. cor. of secs. 19 and 30.

Dependent Resurvey of a Portion of the 21  
 Subdivisional Lines, T. 9 N., R. 27 E.,  
 Gila and Salt River Mer., Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E                      W 1/16 <u>S19</u>                      S30                      1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 16° E., 22 lks. dist., mkd. W 1/16 S19 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 45° E., 51 lks. dist., mkd. W 1/16 S30 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p>
31.30	Track road, bears N. 20° E. and S. 20° W.
38.21	The cor. of secs. 19, 24, 25 and 30, on the W. bdy. of the Tp., heretofore described.
	<p>From the cor. of secs. 19, 20, 29 and 30.</p> <p>N. 1°37' W., bet. secs. 19 and 20.</p> <p>Over rolling land, through medium to dense timber.</p>
19.92	<p>Point for the S 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., over an X chiseled in solid rock, and in a mound of stone, 5 ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E                      S 1/16                      S19 S20                      1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 46° E., 26 lks. dist., mkd. S 1/16 S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 64° W., 82 lks. dist., mkd. S 1/16 S19 BT.</p> <p>From this point the center of a dry stock pond, 2.50 chs. diam., bears S. 25° W., 375 lks. dist.</p>
34.00	Track road, bears E and W.
39.84	<p>The 1/4 sec. cor. of secs. 19 and 20, monumented with a basalt stone, 20 x 16 x 9 ins., firmly set 9 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on the W. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T9N R27E 1/4 S19 S20 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 17 ins. diam., bears S. 85° E., 57.5 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 18 ins. diam., bears S. 73° W., 88.5 lks. dist., mkd. 1/4 S19 BT.</p> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°25' W., beginning new measurement.</p>
20.27	<p>Point for the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 6 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R27E N 1/16 S19 S20 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 35° E., 38.5 lks. dist., mkd. N 1/16 S20 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 71° W., 90 lks. dist., mkd. N 1/16 S19 BT.</p>
40.54	<p>The cor. of secs. 17, 18, 19 and 20, monumented with a basalt stone, 22 x 9 x 8 ins., firmly set 12 ins. in the ground, mkd. with 4 grooves on the E. and 2 grooves on the S. faces, with a mound of stone, 2 ft. base, 8 ins. high, E. of the cor.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">T9N R27E S18 S17 S19 S20 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 55° E., 157.5 lks. dist., mkd. T9N R27E S20 BT.</p> <p style="padding-left: 40px;">A boulder, 5 x 5 x 4 ft. above ground, bears S. 20° W., 46 lks. dist., mkd. X BO on the NW top.</p>

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, W. of the cor.</p> <p>The cor. is in an E-W fence.</p>	
	<p>From the cor. of secs. 16, 17, 20 and 21.</p> <p>S. <math>89^{\circ}15'</math> W., bet. secs. 17 and 20.</p> <p>Over open rolling grassland.</p> <p>Alongside an E-W fence.</p> <p>40.42 Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 17 and 20, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 18 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E <math>\frac{1}{4}</math> <math>\frac{S17}{S20}</math> 1979</p> <p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, N. of the cor.</p> <p>From this point a fence cor., bears S. <math>84\frac{1}{2}^{\circ}</math> W., 71 lks. dist.; fences extend N, E, S and W.</p> <p>The cor. is 6.5 lks. N. of an E-W fence.</p>	
	<p>60.63 Point for the W <math>\frac{1}{16}</math> sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 4 ins. in the ground, to solid rock, and in a mound of stone, <math>4\frac{1}{2}</math> ft. base, to top, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E W <math>\frac{1}{16}</math> <math>\frac{S17}{S20}</math> 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. <math>61^{\circ}</math> E., 89 lks. dist., mkd. W <math>\frac{1}{16}</math> S17 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 13 ins. diam., bears S. <math>50^{\circ}</math> E., 116 lks. dist., mkd. W <math>\frac{1}{16}</math> S20 BT.</p> <p>The cor. is 21.5 lks. N. of an E-W fence.</p>	
	<p>80.84 The cor. of secs. 17, 18, 19 and 20.</p> <hr/> <p>N. <math>85^{\circ}08'</math> W., bet. secs. 18 and 19.</p> <p>Over rolling land, through medium timber.</p> <p>19.52 Point for the E <math>\frac{1}{16}</math> sec. cor. of secs. 18 and 19.</p>	

24

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R27E E 1/16 <math>\frac{S18}{S19}</math> 1979</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. <math>63^\circ</math> E., 112 lks. dist., mkd. X BT at the base.</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. <math>10^\circ</math> W., 150.5 lks. dist., mkd. E 1/16 S19 BT.</p>	
	<p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, N. of the cor.</p>	
	<p>The cor. is 50 lks. E. of a N-S fence.</p>	
39.04	<p>The 1/4 sec. cor. of secs. 18 and 19, monumented with a mound of stone, <math>2\frac{1}{2}</math> ft. base, 1 ft. high. This position is harmoniously related to existing subdivision cors. of Green's Peak Hide-Away, recorded in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, a copy of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the best available evidence of the original cor. position.</p>	
	<p>At the center of the mound.</p>	
	<p>Set an iron post, 28 ins. long, <math>2\frac{1}{2}</math> ins. diam., 21 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R27E <math>\frac{1}{4}</math> <math>\frac{S18}{S19}</math> 1979</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. <math>41\frac{1}{2}^\circ</math> W., 7 lks. dist., mkd. 1/4 S19 BT.</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. <math>48^\circ</math> W., 37 lks. dist., mkd. 1/4 S18 BT.</p>	
	<p>Raise a mound of stone, <math>2\frac{1}{2}</math> ft. base, 2 ft. high, N. of the cor.</p>	
	<p style="text-align: center;">_____</p> <p>N. <math>85^\circ 42'</math> W., beginning new measurement.</p>	
9.71	<p>The E-W 1/64 sec. cor. of secs. 18 and 19, monumented with a re-bar, 16 ins. long, <math>\frac{3}{8}</math> in. diam., projecting 8 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.</p>	
	<p>At the cor. point.</p>	



Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

## CHAINS

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 20 ins. in the ground, with brass cap mkd.

S18  
E-W 1/64  
S19  
1979

from which

A ponderosa pine, 12 ins. diam., bears N.  $87^\circ$  E.,  
118 lks. dist., mkd. E-W 1/64 S18 BT.

A ponderosa pine, 8 ins. diam., bears S.  $31^\circ$  E.,  
197.5 lks. dist., mkd. E-W 1/64 S19 BT.

Reset the re-bar alongside the iron post.

Raise a mound of stone, 3 ft. base,  $2\frac{1}{2}$  ft. high, N. of the cor.

---

N.  $85^\circ 41'$  W., beginning new measurement.

- 9.74 The W 1/16 sec. cor. of secs. 18 and 19, monumented with a re-bar, 16 ins. long,  $\frac{3}{8}$  in. diam., projecting 5 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, over the re-bar, with brass cap mkd.

T9N R27E  
W 1/16  $\frac{S18}{S19}$   
1979

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

---

N.  $85^\circ 40'$  W., beginning new measurement.

- 9.646 A re-bar,  $\frac{3}{8}$  in. diam., projecting 10 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Ariz. This point was improperly established and is not acceptable as the cor. position for the W-W 1/64 sec. cor. of sec. 18 and 19.

- 9.725 Point for the W-W 1/64 sec. cor. of secs. 18 and 19.

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., on solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS		
	<p style="text-align: center;">S18 W-W 1/64 S19 1979</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 44° W., 24 lks. dist., mkd. W W 1/64 S19 BT.</p>	
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 36° W., 12.5 lks. dist., mkd. W W 1/64 S18 BT.</p>	
<p>19.275</p>	<p>The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., heretofore described.</p>	
	<p>From the cor. of secs. 17, 18, 19 and 20.</p>	
	<p>N. 1°44' W., bet. secs. 17 and 18.</p>	
	<p>Over rolling open grassland.</p>	
<p>23.18</p>	<p>Point for the S 1/16 sec. cor. of secs. 18 and 19, not monumented.</p>	
<p>46.36</p>	<p>The 1/4 sec. cor. of secs. 17 and 18, monumented with a basalt stone, 18 x 8 x 4 ins., firmly set 4 ins. in the ground, and in scattered mound of stone, mkd. 1/4 on the W. face.</p>	
	<p>At the cor. point</p>	
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T9N R27E 1/4 S18 S17 1979</p>	
	<p>from which</p>	
	<p style="padding-left: 40px;">A boulder, 6 x 4 x 1½ ft. above ground, bears N. 85½° W., 76.5 lks. dist., mkd. XBO on top.</p>	
	<p>Deposit the mkd. stone alongside the iron post.</p>	
	<p>Raise a mound of stone, 3 ft. base, 1 ft. high, W. of the cor.</p>	
	<p>The cor. is in an E-W fence.</p>	
	<p style="text-align: center;">_____</p> <p>N. 0°22' W., beginning new measurement.</p>	
<p>40.00</p>	<p>Fence, bears E and W.</p>	
<p>40.31</p>	<p>The cor. of secs. 7, 8, 17 and 18, monumented with a volcanic stone, 18 x 12 x 6 ins., firmly set 10 ins. in the ground, and in a mound of stone, 2 ft. base, 6 ins. high, mkd. with 5 grooves on the E. and 4 grooves on the S. faces.</p>	

Dependent Resurvey of a Portion of the 27  
 Subdivisional Lines, T. 9 N., R. 27 E.,  
 Gila and Salt River Mer., Arizona

CHAINS					
	<p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R27E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 7</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S18</td> <td style="padding: 0 5px;">S17</td> </tr> </table> <p>1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p>	S 7	S 8	S18	S17
S 7	S 8				
S18	S17				
40.53	<p>From the cor. of secs. 8, 9, 16 and 17.</p> <p>S. 89°22' W., bet. secs. 8 and 17.</p> <p>Over open rolling grassland.</p> <p>Point for the 1/4 sec. cor. of secs. 8 and 17, at proportionate dist., there is no remaining evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R27E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1</td> <td style="padding: 0 5px;">S 8</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">4</td> <td style="padding: 0 5px;">S17</td> </tr> </table> <p>1979</p> </div> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p> <p>From this point a fence cor., bears S. 38° W., 92 lks. dist.; fences extend S. and W.</p>	1	S 8	4	S17
1	S 8				
4	S17				
81.07	<p>The cor. of secs. 7, 8, 17 and 18.</p>				
40.16	<p>S. 89°57' W., bet. secs. 7 and 18.</p> <p>Over gently rolling open grassland.</p> <p>Along, the N. side of an E-W fence.</p> <p>The 1/4 sec. cor. of secs. 7 and 18, monumented with a volcanic stone, 10 x 12 x 8 ins., loosely set in a mound of stone, 2 ft. base, 6 ins. high, mkd. 1/4 on the N. face.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R27E</p> <table style="margin: auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">1</td> <td style="padding: 0 5px;">S 7</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">4</td> <td style="padding: 0 5px;">S18</td> </tr> </table> <p>1979</p> </div> <p>Deposit the mkd. stone alongside the iron post.</p>	1	S 7	4	S18
1	S 7				
4	S18				

Dependent Resurvey of a Portion of the  
Subdivisional Lines, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p> <p>The cor. is 27 lks. N. of an E-W fence.</p>
	<p>S. 89°57' W., beginning new measurement.</p>
37.37	<p>The cor. of secs. 7, 12, 13 and 18, on the W. bdy. of the Tp., monumented with an iron post, 2 ins. diam., projecting 14 ins. above ground, with brass cap mkd. as described in the official record of the 1937 resurvey by Roger F. Wilson, Surveyor. A mound of stone, 3 ft. base, 1 ft. high, is W of the cor.</p> <p>The cor. is 12.5 lks. N. of an E-W fence.</p>
<p style="text-align: center;">Subdivision of section 17, T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona</p>	
	<p>From the 1/4 sec. cor. of secs. 17 and 20.</p> <p>N. 1°01' W., on the N. and S. center line of sec. 17.</p> <p>Over open rolling grassland.</p>
22.40	<p>Point for the center S 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E C S 1/16   S17 C 1979</p>
	<p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p> <p>The cor. is 48 lks. E. of a N-S fence.</p>
44.80	<p>Point for the center 1/4 sec. cor. of sec. 17, at intersection with the E. and W. center line of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E C 1/4 S17 1979</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.</p> <p>From this point a fence cor., bears N. 24° W., 52 lks. dist.; fences extend N, S and W.</p>
86.59	<p>The 1/4 sec. cor. of secs. 8 and 17.</p>
	<p>From the 1/4 sec. cor. of secs. 16 and 17.</p>

Subdivision of section 17, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 88°34' W., on the E. and W. center line of sec. 17.</p> <p>Over open rolling grassland.</p>
40.51	The center 1/4 sec. cor. of sec. 17.
61.03	<p>Point for the center W 1/16 sec. cor. of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 18 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p>
	<p>T9N R27E C <u>W 1/16</u> C S17 1979</p>
	The cor. is 24 lks. S. of an E-W fence.
81.55	The 1/4 sec. cor. of secs. 17 and 18.
	<p>SW 1/4, section 17</p> <hr/>
	<p>From the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>N. 1°23' W., on the N. and S. center line of the SW 1/4 of sec. 17.</p> <p>Over open rolling grassland.</p>
22.79	<p>Point for the SW 1/16 sec. cor. of sec. 17, at intersection with the E. and W. center line of the SW 1/4 of sec. 17.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p>
	<p>T9N R27E SW 1/16 S17 1979</p>
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
45.58	The center W 1/16 sec. cor. of sec. 17.
	<hr/>
	<p>From the center S 1/16 sec. cor. of sec. 17.</p> <p>N. 89°39' W., on the E. and W. center line of the SW 1/4 of sec. 17.</p> <p>Over open rolling grassland.</p>
20.365	The SW 1/16 sec. cor. of sec. 17.
40.73	The point for the S 1/16 sec. cor. of sec. 17 and 18.
	<p>Subdivision of section 18, T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona</p> <hr/>
	From the 1/4 sec. cor. of secs. 18 and 19.

Subdivision of section 18, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>N. 2°01' W., on the N. and S. center line of sec. 18. Over rolling land, through medium to scattering timber.</p>
<p>21.53</p>	<p>Point for the center S 1/16 sec. cor. of sec. 18. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R17E C S 1/16   S18 C 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 23° W., 99 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 15 ins. diam., bears S. 79° W., 150.5 lks. dist., mkd. C S 1/16 S18 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the cor.</p>
<p>43.06</p>	<p>Point for the center 1/4 sec. cor. of sec. 18, at intersection with the E. and W. center line of sec. 18. Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E C 1/4 S18 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears N. 73½° W., 208 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 18° W., 24 lks. dist., mkd. C 1/4 S18 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2 ft. high, W. of the cor.</p>
<p>43.58</p>	<p>Fence, bears S. 85° E. and N. 85° W.</p>
<p>83.33</p>	<p>The 1/4 sec. cor. of secs. 7 and 18.</p>
<p>39.01</p>	<p>From the 1/4 sec. cor. of secs. 17 and 18. N. 89°58' W., on the E. and W. center line of sec. 18. Over open rolling grassland.</p>
<p>44.00</p>	<p>The center 1/4 sec. cor. of sec. 18.</p>
<p>58.07</p>	<p>Enter scattering timber.</p>
<p>58.07</p>	<p>Point for the center W 1/16 sec. cor. of sec. 18. Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>

Subdivision of section 18, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p style="text-align: center;">T9N R27E C W 1/16 C S18 1979</p> <p>from which</p> <p>A ponderosa pine, 7 ins. diam., bears S. 53½° W., 26 lks. dist., mkd. C W 1/16 S18 BT.</p> <p>A ponderosa pine, 8 ins. diam., bears N. 38° W., 19 lks. dist., mkd. C W 1/16 S18 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, N. of the cor.</p> <p>The cor. is 75 lks. S. of a fence which bears S. 85° E. and N. 85° W.</p>
76.95	<p>The 1/4 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.</p>
	<p style="text-align: center;">SW 1/4, section 18</p> <hr style="width: 20%; margin: auto;"/>
20.805	<p>From the W 1/16 sec. cor. of secs. 18 and 19.</p> <p>N. 1°38' W., on the N. and S. center line of the SW 1/4 of sec. 18.</p> <p>Over rolling land, through scattering to medium timber.</p>
41.605	<p>Point for the SW 1/16 sec. cor. of sec. 18, at inter- section with the E. and W. center line of the SW 1/4 of sec. 18.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E SW 1/16 S18 1979</p> <p>from which</p> <p>A ponderosa pine, 4 ins. diam., bears S. 7½° E., 20 lks. dist., mkd. X BT at the base.</p> <p>A ponderosa pine, 9 ins. diam., bears N. 35° W., 94 lks. dist., mkd. SW 1/16 S18 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 2½ ft. high, W. of the cor.</p>
19.24	<p>The center W 1/16 sec. cor. of sec. 18.</p> <hr style="width: 20%; margin: auto;"/> <p>From the center S 1/16 sec. cor. of sec. 18.</p> <p>N. 87°48' W., on the E. and W. center line of the SW 1/4 of sec. 18.</p> <p>Over rolling land, through medium timber.</p>
	<p>The SW 1/16 sec. cor. of sec. 18.</p>

Subdivision of section 18, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
38.305	The S 1/16 sec. cor. of secs. 13 and 18, on the W. bdy. of the Tp.
Subdivision of section 19, T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona	
From the 1/4 sec. cor. of secs. 19 and 30.	
N. 1°06' W., on the N. and S. center line of sec. 19.	
Over rolling land, through medium to dense timber.	
20.21	Point for the center S 1/16 sec. cor. of sec. 19.  Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.
T9N R27E C S 1/16   S19 C 1979	
from which	
A ponderosa pine, 8 ins. diam., bears N. 41° E., 13.5 lks. dist., mkd. X BT at the base.	
A ponderosa pine, 6 ins. diam., bears S. 36° E., 14 lks. dist., mkd. C S 1/16 S19 BT.	
Raise a mound of stone, 3½ ft. base, 3 ft. high, W. of the cor.	
30.315	The center N-S 1/64 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 8 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.  At the cor. point  Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">                     S19                      C-N-S                      1/64                      1979                 </div> from which  A ponderosa pine, 17 ins. diam., bears S. 84° E., 16 lks. dist., mkd. C-N-S 1/64 S19 BT.  A ponderosa pine, 6 ins. diam., bears S. 50° W., 51 lks. dist., mkd. X BT at the base.  Reset the re-bar alongside the iron post.



Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

## CHAINS

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, W. of the cor.

---

N.  $1^{\circ}06'$  W., beginning new measurement.

10.095 The center  $1/4$  sec. cor. of sec. 19, monumented with a re-bar, 25 ins. long, 1 in. diam., projecting 10 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., over the re-bar, 10 ins. in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T9N R27E  
C  $1/4$  S19  
1979

---

N.  $1^{\circ}06'$  W., beginning new measurement.

20.233 The center N  $1/16$  sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long,  $3/8$  in. diam., projecting 6 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long,  $2\frac{1}{2}$  ins. diam., 21 ins. in the ground, with brass cap mkd.

T9N R27E  
C  
N  $1/16$  | S19  
C  
1979

from which

A ponderosa pine, 13 ins. diam., bears N.  $11\frac{1}{2}^{\circ}$  E.,  
93 lks. dist., mkd. X BT at the base.

A ponderosa pine, 12 ins. diam., bears N.  $76^{\circ}$  E.,  
77 lks. dist., mkd. C N  $1/16$  S19 BT.

Reset the re-bar alongside the iron post.

Raise a mound of stone,  $3\frac{1}{2}$  ft. base, 2 ft. high, W. of the cor.

---

N.  $1^{\circ}08'$  W., beginning new measurement.

Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

<p>CHAINS</p>	<p>10.13 The center N-N 1/64 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 7 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S19 C-N-N 1/64 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears S. 49° E., 11.5 lks. dist., mkd. C-N-N 1/64 S19 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears N. 46° W., 34 lks. dist., mkd. C-N-N 1/64 S19 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p style="text-align: center;">_____</p> <p>N. 1°08' W., beginning new measurement.</p> <p>10.122 The 1/4 sec. cor. of secs. 18 and 19.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 19 and 20.</p> <p>N. 84°57' W. on the E. and W. center line of sec. 19</p> <p>Over rolling land, through medium timber.</p> <p>19.27 The center E 1/16 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 3 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E E 1/16 C _____ C S19 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears N. 29° E., 63.5 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 52° E., 50 lks. dist., mkd. C-E 1/16 S19 BT.</p>
---------------	---

Subdivision of section 19, T. 9 N., R. 27 E.  
Gila and Salt River Mer., Arizona

CHAINS

Reset the re-bar alongside the iron post.

Raise a mound of stone, 3½ ft. base, 2 ft. high, E. of the cor., on federal land.

The cor. is 1 lk. W. of a N-S fence.

N. 84°57' W., beginning new measurement.


19.273 The center 1/4 sec. cor. of sec. 19.

N. 84°59' W., beginning new measurement.

19.193 The center W 1/16 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 3 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.



from which

A ponderosa pine, 8 ins. diam., bears N. 74° W., 14.5 lks. dist., mkd. CW 1/16 S19 BT.

A ponderosa pine, 8 ins. diam., bears N. 5° W., 43.5 lks. dist., mkd. X BT at the base.

Reset the re-bar alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.

N. 84°57' W., beginning new measurement.

19.04

The 1/4 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.

NE 1/4, section 19

From the center E 1/16 sec. cor. of sec. 19.

N. 0°45' W., on the N. and S. center line of the NE 1/4 of sec. 19.

Over rolling land, through medium to scattering timber.

Along a N-S fence.

CHAINS		
20.262	<p>The NE 1/16 sec. cor. of sec. 19, monumented with a re-bar, 12 ins. long, 3/8 in. diam., projecting 6 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.</p> <p>At the cor. point</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T9N R27E NE 1/16 S19 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 13° E., 63 lks. dist., mkd. X BT at the base.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 46½° E., 30 lks. dist., mkd. NE 1/16 S19 BT.</p> <p>Reset the re-bar alongside the iron post.</p> <p>Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of the cor.</p> <p>The cor. is 46 lks. W. of a fence, bears irregularly N. and S.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0°49' W., beginning new measurement.</p>	
20.255	<p>The E 1/16 sec. cor. of secs. 18 and 19.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the N 1/16 sec. cor. of secs. 19 and 20.</p> <p>N. 85°02' W., on the E. and W. center line of the NE 1/4 of sec. 19.</p> <p>Over gently rolling land, through medium to scattering timber.</p>	
19.383	<p>The NE 1/16 sec. cor. of sec. 19.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 85°04' W., beginning new measurement.</p>	
19.403	<p>The center N 1/16 sec. cor. of sec. 19.</p> <hr style="width: 20%; margin: 10px auto;"/> <p style="text-align: center;">SE 1/4, section 19</p> <hr style="width: 20%; margin: 10px auto;"/> <p>From the E 1/16 sec. cor. of secs. 19 and 30.</p> <p>N. 1°32' W., on the N. and S. center line of the SE 1/4 of sec. 19.</p> <p>Over rolling land, through medium to scattering timber.</p>	

Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

37

## CHAINS

- 20.075 Point for the SE 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SE 1/4 of sec. 19.
- Set an iron post, 28 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
- T9N R27E  
SE 1/16 S19  
1979
- from which
- A ponderosa pine, 8 ins. diam., bears N. 39° E.,  
28.5 lks. dist., mkd. X BT at the base.
- A ponderosa pine, 8 ins. diam., bears S. 10° W.,  
21 lks. dist., mkd. SE 1/16 S19 BT.
- Raise a mound of stone, 3 ft. base, 3 ft. high, W. of the cor.
- The cor. is 79 lks. W. of a N-S fence.
- 30.00 The center N-SE 1/64 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 10 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.
- At the cor. point
- Set an iron post, 28 ins. long, 2½ ins. diam., 5 ins. in the ground, to solid rock, and in a mound of stone, 4½ ft. base, to top, with brass cap mkd.
- S19  
C-N-SE  
1/64  
1979
- from which
- A ponderosa pine, 7 ins. diam., bears S. 37½° E.,  
62.5 lks. dist., mkd. CN SE 1/64 S19 BT.
- A ponderosa pine, 6 ins. diam., bears  
S. 42 1/4° W., 24 lks. dist., mkd. X BT at the  
base.
- Reset the re-bar alongside the iron post.
- The cor. is 2.5 lks. W. of a N-S fence.
- \_\_\_\_\_
- N. 0°54' W., beginning new measurement.
- 5.25 Track road, bears S. 80° E. and N. 80° W.
- 10.128 The center E 1/16 sec. cor. of sec. 19.
- \_\_\_\_\_

Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

## CHAINS

From the S 1/16 sec. cor. of secs. 19 and 20.

N. 85°22' W., on the E. and W. center line of the SE 1/4 of sec. 19.

Over rolling land, through medium timber.

7.50 Track road, bears S. 15° E. and N. 15° W.

19.40 The SE 1/16 sec. cor. of sec. 19.

38.69 The center S 1/16 sec. cor. of sec. 19.

SW 1/4, section 19

From the W 1/16 sec. cor. of secs. 19 and 30.

N. 1°11' W., on the N. and S. center line of the SW 1/4 of sec. 19.

Over rolling land, through medium timber.

20.145 Point for the SW 1/16 sec. cor. of sec. 19, at intersection with the E. and W. center line of the SW 1/4 of sec. 19.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T9N R27E  
SW 1/16 S19  
1979

from which

A ponderosa pine, 10 ins. diam., bears N. 64° E.,  
54 lks. dist., mkd. SW 1/16 S19 BT.

A ponderosa pine, 6 ins. diam., bears S. 50° W.,  
43 lks. dist., mkd. X BT at the base.

Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.

30.22 The center N-SW 1/64 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 3 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

S19  
C-N-SW  
1/64  
1979

from which

Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

## CHAINS

A ponderosa pine, 7 ins. diam., bears S. 42° E.,  
19.5 lks. dist., mkd. X BT at the base.

A ponderosa pine, 8 ins. diam., bears S. 46° W.,  
15.5 lks. dist., mkd. C N SW 1/64 S19 BT.

Reset the re-bar alongside the iron post.

Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of  
the cor.

N. 1°14' W., beginning new measurement.

10.062 The center W 1/16 sec. cor. of sec. 19.

From the center S 1/16 sec. cor. of sec. 19.

N. 84°48' W., on the E. and W. center line of the SW 1/4  
of sec. 19.

Over rolling land, through medium timber.

19.17 The SW 1/16 sec. cor. of sec. 19.

38.225 The S 1/16 sec. cor. of secs. 19 and 24, on the W. bdy.  
of the Tp.

NW 1/4, section 19

From the center W 1/16 sec. cor. of sec. 19.

N. 1°31' W., on the N. and S. center line of the NW 1/4  
of sec. 19.

20.134 The NW 1/16 sec. cor. of sec. 19, monumented with a  
re-bar, 16 ins. long, 3/8 in. diam., projecting 4 ins.  
above ground. This monument was set in 1961 by C.H.  
Robertson, Registered Land Surveyor No. 772, Arizona,  
while surveying the Green's Peak Hide-Away subdivision, a  
plat of which is on file at the Apache County courthouse  
in Holbrook, Arizona, and is accepted as the cor. posi-  
tion.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 19 ins. in  
the ground, with brass cap mkd.

T9N R27E  
NW 1/16 S19  
1979

from which

A ponderosa pine, 7 ins. diam., bears S. 11° W.,  
13 lks. dist., mkd. X BT at the base.

A ponderosa pine, 8 ins. diam., bears N. 76° W.,  
29.5 lks. dist., mkd. NW 1/16 S19 BT.

Reset the re-bar alongside the iron post.

Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

---

N. 1°31' W., beginning new measurement.

10.076 The center N-NW 1/64 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 5 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.

S19  
C-N-NW  
1/64  
1979

from which

A ponderosa pine, 7 ins. diam., bears S. 9½° W., 27.5 lks. dist., mkd. C-N-NW 1/64 S19 BT.

A ponderosa pine, 8 ins. diam., bears S. 81° W., 23.5 lks. dist., mkd. X BT at the base.

Reset the re-bar alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

The cor. is 12 lks. W. of a graded cindered road, bears N. and S.

---

N. 1°31' W., beginning new measurement.

10.072 The W 1/16 sec. cor. of secs. 18 and 19.

---

From the center N 1/16 sec. cor. of sec. 19.

N. 85°20' W., on the E. and W. center line of the NW 1/4 of sec. 19.

Over rolling land, through medium timber.

19.326 The NW 1/16 sec. cor. of sec. 19.

---

N. 85°17' W., beginning new measurement.

19.158 The N 1/16 sec. cor. of secs. 19 and 24, on the W. bdy. of the Tp.

---

From the center N-N 1/64 sec. cor. of sec. 19.



Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS

N. 85°34' W., on the E. and W. center line of the NE 1/4 of the NW 1/4 of sec. 19.

Over gently rolling land, through medium timber.

9.70 The NE-NW 1/64 sec. cor. of sec. 19, monumented with a re-bar, 16 ins. long, 3/8 in. diam., projecting 5 ins. above ground. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona, and is accepted as the cor. position.

At the cor. point

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

S19  
NE-NW  
1/64  
1979

from which

A ponderosa pine, 13 ins. diam., bears N. 39° E., 21.5 lks. dist., mkd. X BT at the base.

A ponderosa pine, 10 ins. diam., bears N. 88° E., 59.5 lks. dist., mkd. NE-NW 1/64 S19 BT.

Reset the re-bar alongside the iron post.

Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.

N. 1°12' W., on the N. and S. center line of the NE 1/4 of the NW 1/4 of sec. 19.

Over rolling land, through medium to scattering timber.

10.10 The E-W 1/64 sec. cor. of secs. 18 and 19.

From the center N-NW 1/64 sec. cor. of sec. 19.

N. 85°29' W., on the E. and W. center line of the NW 1/4 of the NW 1/4 of sec. 19.

Over nearly level land, through medium timber.

9.616 A re-bar, 3/8 in. diam., projecting 4 ins. above ground, bears South, .7 lk. dist. This monument was set in 1961 by C.H. Robertson, Registered Land Surveyor No. 772, Arizona, while surveying the Green's Peak Hide-Away subdivision, a plat of which is on file at the Apache County courthouse in Holbrook, Arizona. This point was improperly established and is not acceptable as the cor. position for the NW-NW 1/64 sec. cor. of sec. 19.

9.69 Point for the NW-NW 1/64 sec. cor. of sec. 19.

Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

Subdivision of section 19, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS

S19  
NW-NW  
1/64  
1979

from which

A ponderosa pine, 11 ins. diam., bears S. 79 $\frac{3}{4}$ ° E.,  
14 lks. dist., mkd. X BT at the base.

A ponderosa pine, 8 ins. diam., bears N. 53° W.,  
36 lks. dist., mkd. NW-NW 1/64 S19 BT.

N. 1°44' W., on the N. and S. center line of the NW 1/4  
of the NW 1/4 of sec. 19.

Over nearly level land, through medium timber.

10.046 The W-W 1/64 sec. cor. of secs. 18 and 19.

Subdivision of section 20, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

From the 1/4 sec. cor. of secs. 20 and 29.

N. 0°32' W., on the N. and S. center line of sec. 20.

Over rolling land, through medium to scattering timber.

40.64 Point for the center 1/4 sec. cor. of sec. 20, at inter-  
section with the E. and W. center line of sec. 20.

Set an iron post, 28 ins. long, 2 $\frac{1}{2}$  ins. diam., 21 ins. in  
the ground, with brass cap mkd.

T9N R27E  
C 1/4 S20  
1979

from which

A ponderosa pine, 11 ins. diam., bears S. 81° E.,  
90.5 lks. dist., mkd. C 1/4 S20 BT.

A fence cor., bears N. 46° W., 85 lks. dist.;  
fences extend N. and E.

A ponderosa pine, 11 ins. diam., bears N. 29 $\frac{1}{2}$ ° W.,  
48 lks. dist., mkd. C 1/4 S20 BT.

Raise a mound of stone, 3 ft. base, 2 $\frac{1}{2}$  ft. high, W. of  
the cor.

81.45 The 1/4 sec. cor. of secs. 17 and 20.

From the 1/4 sec. cor. of secs. 20 and 21.

S. 89°39' W., on the E. and W. center line of sec. 20.

Over rolling land, through scattering timber.

40.42 The center 1/4 sec. cor. of sec. 20.

Subdivision of section 20, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

<p>CHAINS 80.93</p>	<p>The 1/4 sec. cor. of secs. 19 and 20.</p> <hr/> <p style="text-align: center;">Subdivision of section 30, T. 9 N., R. 27 E., Gila and Salt River Mer., Arizona</p> <hr/> <p>From the 1/4 sec. cor. of secs. 30 and 31.</p> <p>N. 0°06.5' W., on the N. and S. center line of sec. 30.</p> <p>Over rolling land, through medium to scattering timber.</p> <p>1.50 Fence, bears S. 60° E. and N. 60° W.</p> <p>10.09 Point for the center S-S 1/64 sec. cor. of sec. 30, not monumented.</p> <p>20.18 Point for the center S 1/16 sec. cor. of sec. 30, not monumented.</p> <p>30.27 Point for the center N-S 1/64 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} C \\ N-S \ 1/64 \   \ S30 \\ C \\ 1979 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears East, 57 lks. dist., mkd. C-N-S 1/64 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 89° W., 17.5 lks. dist., mkd. C-N-S 1/64 S30 BT.</p> <p>Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.</p> <p>35.30 Fence, bears S. 80° E. and N. 80° W.</p> <p>40.36 Point for the center 1/4 sec. cor. of sec. 30, at intersection with the E. and W. center line of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 4 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <math display="block">\begin{array}{c} T9N \ R27E \\ C \ 1/4 \ S30 \\ 1979 \end{array}</math> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 14 ins. diam., bears N. 3° E., 3 lks. dist., mkd. C 1/4 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 48° W., 18.5 lks. dist., mkd. C 1/4 S30 BT.</p> <p>80.20 The 1/4 sec. cor. of secs. 19 and 30.</p>
-------------------------	--

Subdivision of section 30, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the 1/4 sec. cor. of secs. 29 and 30.</p> <p>N. 84°47.4' W., on the E. and W. center line of sec. 30.</p> <p>Over gently rolling land, through medium timber.</p>
8.30	Road, cindered, bears S. 55° E. and N. 55° W.
18.95	<p>Point for the center E 1/16 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R27E C E 1/16 C S30 1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 11 ins. diam., bears S. 10° E., 33.5 lks. dist., mkd. C E 1/16 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 9 ins. diam., bears N. 53° W., 24 lks. dist., mkd. C E 1/16 S30 BT.</p> <p>The cor. is 90 lks. W. of a graded road, bears S. 55° E. and N. 55° W.</p>
37.90	The center 1/4 sec. cor. of sec. 30.
56.178	<p>Point for the center W 1/16 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T9N R27E C W 1/16 C S30 1979</p> </div> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears S. 33° E., 31 lks. dist., mkd. C W 1/16 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 6 ins. diam., bears N. 55° W., 58.5 lks. dist., mkd. C W 1/16 S30 BT.</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, N. of the cor.</p>
74.593	The 1/4 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.
	<p>SE 1/4, section 30</p> <hr style="width: 20%; margin: auto;"/>
	<p>From the E 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 0°45' W., on the N. and S. center line of the SE 1/4 of sec. 30.</p> <p>Over rolling land, through medium to scattering timber.</p>

Subdivision of section 30, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
7.50	Forest Service Road No. 118, graded, bears E. and W.
16.30	Graded road, bears S. 70° E. and N. 70° W.
18.90	The center of a stock pond, 150 lks. diam., bears East, 30 lks. dist.
20.12	Point for the SE 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SE 1/4 of sec. 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	T9N R27E SE 1/16 S30 1979
	from which
	A ponderosa pine, 8 ins. diam., bears S. 35° E., 7 lks. dist., mkd. X BT at the base.
	A ponderosa pine, 8 ins. diam., bears S. 60° W., 16 lks. dist., mkd. SE 1/16 S30 BT.
	Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the cor.
23.40	Fence, bears N. 55° E. and S. 55° W.
30.18	Point for the center N-SE 1/64 sec. cor. of sec. 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	S30 C-N-SE 1/64 1979
	from which
	A ponderosa pine, 9 ins. diam., bears N. 69° E., 26.5 lks. dist., mkd. C N SE 1/64 S30 BT.
	A ponderosa pine, 14 ins. diam., bears S. 11° E., 83.5 lks. dist., mkd. C N SE 1/64 S30 BT.
	Raise a mound of stone, 2½ ft. base, 2 ft. high, W. of the cor.
36.25	Fence, bears E. and W.
40.24	The center E 1/16 sec. cor. of sec. 30.
	From the S 1/16 sec. cor. of secs. 29 and 30.
	N. 85°01.5' W., on the E. and W. center line of the SE 1/4 of sec. 30.
	Over rolling land, through medium to dense timber.
14.20	Graded road, bears N. 55° E. and S. 55° W.

Subdivision of section 30, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
19.16	The SE 1/16 sec. cor. of sec. 30.
23.10	Fence, bears N. 60° E. and S. 60° W.
28.74	Point for the center W-SE 1/64 sec. cor. of sec. 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	S30 C-W-SE 1/64 1979
	from which
	A ponderosa pine, 16 ins. diam., bears S. 58° E., 69 lks. dist., mkd. C W SE 1/64 S30 BT.
	A ponderosa pine, 8 ins. diam., bears S. 13° E., 80.5 lks. dist., mkd. C W SE 1/64 S30 BT.
	Raise a mound of stone, 3 ft. base, 2 ft. high, N. of the cor.
38.32	Point for the center S 1/16 sec. cor. of sec. 30.
	From the center W-SE 1/64 sec. cor. of sec. 30.
	S. 0°24.2' E., on the N. and S. center line of the SW 1/4 of the SE 1/4 of sec. 30.
	Over gently rolling land, through scattering timber.
10.076	Point for the SW-SE 1/64 sec. cor. of sec. 30.
	Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	S30 SW-SE 1/64 1979
	from which
	A ponderosa pine, 12 ins. diam., bears N. 36° E., 35.5 lks. dist., mkd. SW SE 1/64 S30 BT.
	A ponderosa pine, 13 ins. diam., bears S. 15½° W., 36 lks. dist., mkd. SW SE 1/64 S30 BT.
	Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
	The cor. is 65 lks. W. of a graded road, bears NE and SW.
	N. 85°08.8' W., on the E. and W. center line of the SW 1/4 of the SE 1/4 of sec. 30.
	Over gently rolling land, through medium to scattering timber.
1.90	Fence, bears N. 30° E. and S. 30° W.

Subdivision of section 30, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
4.816	<p>Point for the center W-SW-SE 1/256 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S30 C-W-SW-SE 1/256 1979</p> <p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
9.632	<p>Point for the center S-S 1/64 sec. cor. of sec. 30.</p>
<hr/> <p>SW 1/4, section 30</p> <hr/>	
10.11	<p>From the W 1/16 sec. cor. of secs. 30 and 31.</p> <p>N. 1°26.4' E., on the N. and S. center line of the SW 1/4 of sec. 30.</p> <p>Over rolling land, through dense to scattering timber.</p> <p>Point for the center S-SW 1/64 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S30 C-S-SW 1/64 1979</p> <p>from which</p> <p style="padding-left: 40px;">A ponderosa pine, 12 ins. diam., bears S. 72° E., 32.5 lks. dist., mkd. C S SW 1/64 S30 BT.</p> <p style="padding-left: 40px;">A ponderosa pine, 10 ins. diam., bears S. 10° W., 11 lks. dist., mkd. C S SW 1/64 S30 BT.</p>
12.90	<p>Fence, bears S. 80° E. and N. 80° W.</p>
20.22	<p>Point for the SW 1/16 sec. cor. of sec. 30, at intersection with the E. and W. center line of the SW 1/4 of sec. 30, not monumented.</p>
30.33	<p>Point for the center N-SW 1/64 sec. cor. of sec. 30.</p> <p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">S30 C-N-SW 1/64 1979</p> <p>Raise a mound of stone, 3 ft. base, 2½ ft. high, W. of the cor.</p>
39.10	<p>Fence, bears S. 65° E. and N. 65° W.</p>
40.44	<p>The center W 1/16 sec. cor. of sec. 30.</p> <hr/>

Subdivision of section 30, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS	
	<p>From the point for the center S 1/16 sec. cor. of sec. 30.</p>
	<p>N. 85°01.4' W. on the E. and W. center line of the SW 1/4 of sec. 30.</p>
	<p>Over gently rolling to rolling land, through scattering timber.</p>
18.824	<p>The point for the SW 1/16 sec. cor. of sec. 30.</p>
28.24	<p>Point for the center W-SW 1/64 sec. cor. of sec. 30.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.</p>
	<p style="text-align: center;">S30 C-W-SW 1/64 1979</p>
	<p>Raise a mound of stone, 2½ ft. base, 2 ft. high, N. of the cor.</p>
37.915	<p>The S 1/16 sec. cor. of secs. 25 and 30, on the W. bdy. of the Tp.</p>
	<p>From the E-W 1/64 sec. cor. of secs. 30 and 31.</p>
	<p>N. 0°40.2' E., on the N. and S. center line of the SE 1/4 of the SW 1/4 of sec. 30.</p>
	<p>Over rolling land, through dense to medium timber.</p>
10.10	<p>Point for the SE-SW 1/64 sec. cor. of sec. 30.</p>
	<p>Set an iron post, 28 ins. long, 2½ ins. diam., 8 ins. in the ground, to solid rock, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd.</p>
	<p style="text-align: center;">S30 SE-SW 1/64 1979</p>
	<p>from which</p>
	<p style="padding-left: 40px;">A ponderosa pine, 7 ins. diam., bears S. 25° W., 19 lks. dist., mkd. X BT at the base.</p>
	<p style="padding-left: 40px;">A ponderosa pine, 8 ins. diam., bears S. 88° W., 81 lks. dist., mkd. SE-SW 1/64 S30 BT.</p>
	<p>N. 85°09' W., on the E. and W. center line of the SE 1/4 of the SW 1/4 of sec. 30.</p>
	<p>Over rolling land, through dense timber.</p>
9.55	<p>The center S-SW 1/64 sec. cor. of sec. 30.</p>
	<p>N. 85°09' W., on the E. and W. center line of the SW 1/4 of the SW 1/4 of sec. 30.</p>



Subdivision of section 30, T. 9 N., R. 27 E.,  
Gila and Salt River Mer., Arizona

CHAINS

- 9.55 Point for the SW-SW 1/64 sec. cor. of sec. 30.
- Set an iron post, 28 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
- S30  
SW-SW  
1/64  
1979
- from which
- A fir, 13 ins. diam., bears S. 62° E., 58.5 lks. dist., mkd. SW-SW 1/64 S30 BT.
- A fir, 8 ins. diam., bears S. 14° W., 55.5 lks. dist., mkd. SW-SW 1/64 S30 BT.
- Raise a mound of stone, 2½ ft. base, 1½ ft. high, W. of the cor.
- 
- N. 2°14' E., on the N. and S. center line of the SW 1/4 of the SW 1/4 of sec. 30.
- Over rolling land, through dense timber.
- 5.00 Fence, bears S. 65° E. and N. 65° W.; enter scattering timber.
- 10.12 The center W-SW 1/64 sec. cor. of sec. 30.

GENERAL DESCRIPTION

The land encompassed in this survey is located about 13 miles west of Springerville, Arizona. Drainage in the area surveyed is generally north and east. Elevation ranges from about 7,900 feet above sea level to about 9,100 feet above sea level.

Access is by way of U.S. Forest Service roads numbers 117 and 118, from which track roads and logging roads extend.

Most of the rolling terrain in the higher elevations is covered with ponderosa pine, juniper, fir and aspen, the predominate species being ponderosa pine. Where the land is cleared of timber, there is a good cover of native grasses.

The area is primarily used for logging and grazing. There is no evidence of valuable minerals or mining activities.

Green's Peak Hide-Away, a subdivision on which several houses are located is situated on patented land in section 19. Several springs are located in section 18 and section 19 and in the SE 1/4 of section 30.

The average of a number of readings throughout the area surveyed gives a mean magnetic declination of 14° E., with a range of 4° in local attraction.

CHAINS



CERTIFICATE OF SURVEY

(I) ~~(W)~~, Harry K. Smith, Cadastral Surveyor, HEREBY  
 CERTIFY upon honor that, in pursuance of special instructions bearing date of the 2nd day  
 of August, 19 79, (I) ~~(W)~~ have dependently resurveyed a portion of  
 the south boundary (Second Standard Parallel North), a portion of the  
 west boundary, a portion of the subdivisional lines, and surveyed subdivi-  
 sions in sections 17, 18, 19, 20 and 30 of Township 9 North, Range 27  
 East,

of the Gila and Salt River Meridian, in the State of Arizona, which  
 are represented in the foregoing field notes as having been executed by (me), ~~(US)~~ and under (my)  
~~(SW)~~ direction; and that said survey has been made in strict conformity with said special instruc-  
 tions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in  
 specific manner described in the foregoing field notes.

September 24, 1980

(Date)

*Harry K. Smith*

(Cadastral Surveyor)

(Date)

(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT  
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south  
 boundary (Second Standard Parallel North), a portion of the west bound-  
 ary, a portion of the subdivisional lines and the survey of subdivisions  
 in sections 17, 18, 19, 20 and 30 of T. 9 N., R. 27 E., of the Gila and  
 Salt River Meridian, Arizona,

executed by Harry K. Smith, Cadastral Surveyor,

having been critically examined and found correct, are hereby approved.

JUL 06 1981

(Date)

*J. D. Underwood*  
(Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in  
 \_\_\_\_\_, is a true copy of the original field notes.

(Date)

(Chief, Cadastral Survey Examination and Approval Staff)