

R 5160

BOOK 5160 ;

FIELD NOTES

PAGE 1

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH AND WEST BOUNDARIES

A PORTION OF THE SUBDIVISIONAL LINES,

AND

A PORTION OF THE SUBDIVISION LINES WITHIN A NUMBER OF SECTIONS;

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES WITHIN A NUMBER OF SECTIONS,

THE METES-AND-BOUNDS SURVEY OF LOT 8 OF SECTION 35,

AND

THE METES-AND-BOUNDS SURVEY OF TRACTS 37 THROUGH 45 INCLUSIVE,

TOWNSHIP 8 SOUTH, RANGE 19 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

| | |
|------------------------|---------------------------|
| <u>RAY HARPIN</u> | <u>CADASTRAL SURVEYOR</u> |
| <u>DOUGLAS A. CODY</u> | <u>CADASTRAL SURVEYOR</u> |
| <u>PAUL J. FISHER</u> | <u>CADASTRAL SURVEYOR</u> |

Under special instructions dated OCTOBER 14, 19 69, approved OCTOBER 27, 1969,
 SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED NOVEMBER 20, 1969, APPROVED NOVEMBER 21,
 1969, SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED SEPTEMBER 5, 1979, APPROVED SEPTEMBER
 13, 1979 AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED OCTOBER 20, 1980, APPROVED
 OCTOBER 27, 1980, which provided for the surveys included under ~~XXXX SURVEY~~ Group
 Number 517, and assignment instructions dated OCTOBER 14, 1969
 AND OCTOBER 14, 1980

Survey commenced OCTOBER 27, 19 69
 Survey completed APRIL 6, 19 81

INDEX DIAGRAM

Township 8 SOUTH, Range 19 WEST,

| | | | | | |
|---------|-------|----------|-------|----------|----------|
| 6 | 5 | 4 | 3 | 2 | 1 |
| 7 | 8 | 9 | 10 | 11 | 12 |
| 18 | 17 | 16 | 15 | 14 | 13 |
| 19 | 20 | 21 | 22 | 23 28 | 24 16 |
| 30 | 29 | 28 | 27 21 | 26 14 | 25 |
| 30 | | 27 | 25 | 20 | 13 |
| 9 31 28 | 32 26 | 23 33 | 34 18 | 12 35 | 36 |
| 6 | | 3 | 2 | | |

Dependent Resurvey
of Subdivision Lines

Survey of Subdivision
Lines

Metes-and-Bounds
Survey of Tracts

Section 25 . . . p. 31
Section 26 . . . p. 38
Section 34 . . . p. 41
Section 35 . . . p. 44

Section 26 . . . p. 48
Section 31 . . . p. 49
Section 33 . . . p. 52
Section 34 . . . p. 54
Section 35 . . . p. 55

Tract 37 . . . p. 57
Tract 38 . . . p. 60
Tract 39 . . . p. 61
Tract 40 . . . p. 62
Tract 41 . . . p. 64
Tract 42 . . . p. 66
Tract 43 . . . p. 66
Tract 44 . . . p. 69
Tract 45 . . . p. 70

Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision lines within a number of sections; the survey of a portion of the subdivision lines within a number of sections, and the metes-and-bounds survey of lot 8 of section 35, and the metes-and-bounds survey of Tracts 37 through 45 inclusive, Township 8 South, Range 19 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The south boundary was surveyed by John F. Hesse, U. S. Deputy Surveyor, in 1910; the south boundary of section 31 was retraced, a portion of the east boundary was retraced, another portion was resurveyed, and another portion was surveyed; the west and north boundaries, and a portion of the subdivisional lines were surveyed by Sidney E. Blout, U. S. Surveyor, in 1912, as shown upon the official plat examined and approved July 27, 1914. A portion of the east boundary of section 25 and a portion of the subdivisional lines (the exterior boundaries of sections 25 and 26) were resurveyed and a portion of the subdivision lines within sections 25 and 26 were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Assistant Commissioner, Bureau of Reclamation, Washington, D. C., March 17, 1955; and was accepted by the Chief, Branch of Surveys, Bureau of Land Management, March 17, 1955. A portion of the south boundary of section 34 and a portion of the subdivisional lines (the exterior boundaries of sections 34 and 35) were surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Assistant Commissioner, Bureau of Reclamation, Washington, D. C., March 17, 1955; and was accepted by the Chief, Branch of Surveys, Bureau of Land Management, March 17, 1955. A supplemental plat of section 31, showing the amended lottings, lot 2 is designated lots 5 and 6, as shown upon the official plat, approved September 20, 1956. A portion of the east boundary of the township was dependently resurveyed as described in the official field-note record of the dependent resurvey of a portion of the west boundary of T. 8 S., R. 18 W., executed concurrently with this group.

These dependent resurveys and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 and 1973 Editions, and the Special Instructions dated October 14, 1969, for Group No. 517, Arizona, Supplemental Special Instructions dated November 20, 1969, Supplemental Special Instructions dated September 5, 1979, and Supplemental Special Instructions dated October 20, 1980.

The direction of all lines of these surveys were determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains, reduced to horizontal equivalents.

Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the south 1/4 sec. cor. of sec. 35 (on the south boundary of the township) is determined by scaling from a U. S. Geological Survey Quadrangle Map, 7 1/2 minute series "Wellton, Arizona, 1965", is as follows: Latitude 32° 40.7' N. and Longitude 114° 11.1' W. The mean magnetic declination is 14° E.

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

Restoring the Resurvey Executed
by Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

The corner of secs. 34 and 35 on the south boundary of the township, which is monumented with an iron post, 2 ins. in diam., with regulation General Land Office brass cap, 6 ins. below the surface of the road, mkd.

T8S R19W
S 34 | S 35

1910

substantiated by:

A cross (+) chiseled on a concrete headwall of a lateral, bears N. 59° 30' W., 56 ft. distant, mkd.
+ RP 56'

N. 89° 51' W., on the south boundary of the township, and on the south boundary of sec. 34.

Along the center line of an east and west road.

- 14.92 The point for Angle Point No. 4, lot 3 and Angle Point No. 6, lot 4 of sec. 34, is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner.
- 16.40 The point for the east 1/16 sec. cor. of sec. 3 on the north boundary of T. 9 S., R. 19 W., which is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner.

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

5

| CHAINS | | |
|--------|--|--|
| 20.06 | The point for the east 1/16 sec. cor. of sec. 34 on the south boundary of the township, which is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner. | |
| 36.47 | The north 1/4 sec. cor. of sec. 3, T. 9 S., R. 19 W., is marked with an iron pipe, 1-inch in diam., with brass cap 14 ins. below the surface of the road, mkd. | |
| | <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;"><u>1/4 S 3</u></p> <p style="text-align: center;">1949</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> | |
| 40.12 | The south 1/4 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., with brass cap 14 ins. below the surface of the road, mkd. | |
| | <p style="text-align: center;">BUREAU OF RECLAMATION</p> <p style="text-align: center;"><u>1/4 S 34</u></p> <p style="text-align: center;">1949</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Ablin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> | |
| | <p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 44° 55' E., 40.6 ft. distant, with brass cap mkd. RM T8S R19W S34 40.6 FT 1969, and an arrow pointing to the corner.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 30° 10' W., 32.9 ft. distant, with brass cap mkd. RM T8S R19W S34 32.9 FT 1969, and an arrow pointing to the corner.</p> <p>Discontinue the regular order of survey at this corner.</p> | |
| | <p style="text-align: center;">Restoring the Survey Executed by John F. Hesse, U. S. Surveyor, in 1910</p> <hr style="width: 20%; margin: auto;"/> <p>The point for the corner of secs. 33 and 34 on the south boundary of the township, which is determined from ties (distances only), established by the Bureau of Reclamation, as:</p> | |

6

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

A redwood post of undetermined length, 4 ins. square, scribed RP 33 FT, firmly set, projecting 20 ins. above the surface of the ground, bears SOUTH 33 ft. dist.

An electric transmission line pole, bears N. 19° 05' W., 30 ft. distant, scribed RP 30 FT.

The above corner point is accepted as a careful and faithful reestablishment of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T8S R19W
S 33 | S 34
S 4

T9S R19W

1969

There are no other suitable accessories nor locations available for reference monuments.

N. 89° 53' W., on the south boundary of sec. 33.

Over nearly level land, along the center line of an east and west road.

- 16.385 The east 1/16 sec. cor. of sec. 4 on the north boundary of T. 9 S., R. 19 W., which is marked with an iron pipe, 1-inch in diam., with brass cap 12 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

E 1/16 S 4

1949

The above corner marker was accepted and described in the official field-note record of the dependent resurvey of the north boundary of sec. 4, T. 9 S., R. 19 W., by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1956. I did not remonument this corner.

- 40.085 The point for the south 1/4 sec. cor. of sec. 33, is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

T8S R19W
1/4 S33

1969

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

7

CHAINS

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 59° 00' E., 55.4 ft. distant, with brass cap mkd. RM T8S R19W S33 55.4 FT 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 68° 25' W., 58.6 ft. distant, with brass cap mkd. RM T8S R19W S33 58.6 FT 1969, and an arrow pointing to the corner.

62.745 The point for Angle Point No. 3, Tract 45.

Set an aluminum rod, 48 ins. long, 5/8-inch diam., with aluminum cap 3 1/4 ins. diam., 7 ins. below the surface of the road, mkd.

T8S R19W
TR 45 |
AP 3 | S 33
S 4
T9S

1981

There are no suitable accessories nor locations available for reference monuments.

76.51 The closing corner of secs. 4 and 5, T. 9 S., R. 19 W., is monumented with an iron post 2 ins. in diam., with regulation General Land Office brass cap 8 ins. below the surface of the road, mkd.

T8S R19W
S 32 | S 33 CC
S 5 | S 4
T9S

1911

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 70° 00' E., 80.7 ft. distant, with brass cap mkd. RM T9S R19W S4 80.7 FT 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 42° 25' W., 39.8 ft. distant, with brass cap mkd. RM T9S R19W S5 39.8 FT 1969, and an arrow pointing to the corner.

80.17 The corner of secs. 32 and 33 is monumented with an iron post, 2 ins. in diam., with regulation General Land Office brass cap 15 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

8

CHAINS

T8S R19W
S 32 | S 33

1912

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 16° 15' E., 107.6 ft. distant, with brass cap mkd. RM T8S R19W S33 107.6 FT 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 71° 05' W., 85.3 ft. distant, with brass cap mkd. RM T8S R19W S32 85.3 FT 1969, and an arrow pointing to the corner.

Discontinue the regular order of survey at this corner.

The corner of secs. 31 and 32 on the south boundary of the township, which is marked with an iron pipe, 2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

T8S R19W
S 31 | S 32
T9S R19W

1941

The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.

from which

An iron post, 28 ins. long 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 59° 15' E., 53.4 ft. distant, with brass cap mkd. RM T8S R19W S32 53.4 FT 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 48° 00' W., 41.5 ft. distant, with brass cap mkd. RM T8S R19W S31 41.5 FT 1969, and an arrow pointing to the corner.

N. 89° 55.5' W., on the south boundary of sec. 31.

Over nearly level land, along the center line of an east and west road.

16.43

The point for Angle Point No. 10, Tract 37.

Set an iron post 28 ins. long, 2 1/2 ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S R19W
TR 37|S 31
AP 10|L 17
S 6
T9S

1969

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 0° 05' E., 33 ft. distant, with brass cap mkd. RM T8S R19W S31 33 FT 1969, and an arrow pointing to the corner.

There are no other suitable accessories nor locations available for reference monuments.

27.04 The point for Angle Point No. 9, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T8S R19W
S 31|TR 37
L 16|AP 9
S 6
T9S

1969

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 0° 04.5' E., 33 ft. distant, with brass cap mkd. RM T8S R19W TR 37 S31 33 FT 1969, and an arrow pointing to the corner.

There are no other suitable accessories nor locations available for reference monuments.

39.95 The south 1/4 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., with brass cap 17 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
1/4 S 31

1949

The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 66° 35' E., 74.9 ft. distant, with brass cap mkd. RM T8S R19W S31 74.9 FT 1969, and an arrow pointing to the corner.

10

Dependent Resurvey of a Portion
of the South Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 44° 40' W., 39.1 ft. distant, with brass cap mkd. RM T8S R19W S31 39.1 FT 1969, and an arrow pointing to the corner.

N. 89° 55.5' W., beginning new measurement

19.975 The west 1/16 sec. cor. of sec. 31 on the south boundary of the township, which is marked with an iron pipe, 1-inch in diam. with brass cap 3 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
W 1/16 S 31

1949

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 89° 55.5' W., beginning new measurement.

16.515 The corner of Tps. 8 and 9 S., Rs. 19 and 20 W., which is marked with an iron pipe, 2 ins. in diam., with brass cap 21 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

T8S
R20W|R19W
S 36|S 31
S 1|S 6
R20W|R19W
T9S

1941

The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 55° 45' E., 74 ft. distant, with brass cap mkd. RM T8S R19W S31 74 FT 1969, and an arrow pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 47° 50' W., 39.2 ft. distant, with brass cap mkd. RM T8S R20W S36 39.2 FT 1969, and an arrow pointing to the corner.

Dependent Resurvey of a Portion
of the West Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

11

CHAINS

Restoring the Survey Executed by
Sidney E. Blout, U. S. Surveyor, in 1912

N. 0° 01' E., through Tps. 8 S., between Rs. 19 and 20 W.

Over nearly level land, along the center line of a north
and south road.

17.04 The point for Angle Point No. 5, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with
brass cap 7 ins. below the surface of the road, mkd.

| | |
|------|-------|
| T8S | |
| R20W | R19W |
| | TR 37 |
| S 36 | AP 5 |
| | L 14 |
| | S 31 |

1969

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set
23 ins. in the ground, for a reference monument,
bears N. 87° 27.5' E., 33 ft. distant, with brass
cap mkd. RM T8S R19W TR 37 L14 S31 33 FT 1969, and
an arrow pointing to the cor.

20.01 The south 1/16 sec. cor. of secs. 31 and 36 is marked
with an iron pipe, 1-inch in diam., with brass cap 13
ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

| | |
|------|------|
| 1/16 | |
| S 36 | S 31 |
| | |

1958

The above corner point is accepted as a careful and
faithful determination of the position of the corner.

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set
23 ins. in the ground, for a reference monument,
bears N. 47° 15' E., 55.6 ft. distant, with brass
cap mkd. RM T8S R19W S 31 55.6 FT 1969, and an arrow
pointing to the corner.

An iron post, 28 ins. long, 2 1/2 ins. in diam., set
23 ins. in the ground, for a reference monument,
bears N. 51° 00' W., 60 ft. distant, with brass cap
mkd. RM T8S R20W S 36 60 FT 1969, and an arrow
pointing to the corner.

12

Dependent Resurvey of a Portion
of the West Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

N. 0° 01' E., beginning new measurement

12.195 The point for Angle Point No. 4, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

| | |
|------|-------|
| T8S | |
| R20W | R19W |
| | S 31 |
| S 36 | L 9 |
| | AP 4 |
| | TR 37 |

1969

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 87° 27.5' E., 33 ft. distant, with brass cap mkd. RM T8S R19W L9 S31 TR 37 33 FT 1969, and an arrow pointing to the cor.

20.01 The 1/4 sec. cor. of secs. 31 and 36 is marked with an iron pipe, 2 ins. in diam., with brass cap 40 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

| | |
|------|------|
| 1/4 | |
| | |
| S 36 | S 31 |

1969

The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., over the top of the above corner marker, with brass cap 12 ins. below the surface of the road, mkd.

| | |
|------|------|
| T8S | |
| R20W | R19W |
| | 1/4 |
| S 36 | S 31 |

1969

from which

Dependent Resurvey of a Portion
of the West Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

13

CHAINS

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 44° 30' E., 32.6 ft. distant, with brass cap mkd. RM T8S R19W S 31 32.6 FT 1969, and an arrow pointing to the corner.

There are no other suitable accessories nor locations available for reference monument.

N. 0° 01' E., beginning new measurement

9.135 The point for Angle Point No. 3, Tract 43.

Set an aluminum rod, 48 ins. long, 5/8-inch diam., with aluminum cap 3 1/4 ins. diam., 11 ins. below the surface of the road, mkd.

| | |
|------|-------|
| T8S | |
| R20W | R19W |
| | TR 43 |
| S 36 | AP 3 |
| | S 31 |

1981

There are no suitable accessories nor locations available for reference monuments.

20.01 The north 1/16 sec. cor. of secs. 31 and 36 is marked with an iron pipe, 1-inch in diam., with brass cap 9 ins. below the surface of the road, mkd.

| | |
|------|------|
| N | |
| 1/16 | |
| | |
| S 36 | S 31 |
| | |

1952

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 0° 01' E., beginning new measurement

20.01 The corner of secs. 25, 30, 31, and 36 is marked with an iron pipe, 1-inch in diam., with brass cap 5 ins. below the surface of the road, mkd.

| | | | |
|-----------------------|------|------|------|
| BUREAU OF RECLAMATION | | | |
| T8S | | | |
| R20W | R19W | | |
| | | S 25 | S 30 |
| | | S 36 | S 31 |

1959

The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.

14

Dependent Resurvey of a Portion
of the West Boundary
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 44° 40' E., 37.6 ft. distant, with brass cap mkd. RM T8S R19W S 31 37.6 FT 1969, and an arrow pointing to the corner.


An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 45° 00' W., 38.3 ft. distant, with brass cap mkd. RM T8S R20W S 36 38.3 FT 1969, and an arrow pointing to the corner.

Discontinue the dependent resurvey of the range line at this corner.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

Restoring the Survey Executed by
Sidney E. Blout, U. S. Surveyor in 1912

The 1/4 sec. cor. of secs. 35 and 36 is monumented with an iron post, 2 ins. in diam., with regulation General Land Office brass cap 9 ins. below the surface of the road, mkd.



1912

substantiated by:

A cross (+) chiseled on a concrete headwall of a lateral, bears S. 65° 55' W., 50 ft. distant, mkd. RP + 50.0'

A cross (+) chiseled on a concrete headwall of a lateral, bears N. 56° 00' W., 50 ft. distant, mkd. RP + 50.'

N. 0° 01' W., between secs. 35 and 36.

Over nearly level land, along the center line of a road.

19.985 The point for the north 1/16 sec. cor. of secs. 35 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

N 1/16
S 35 | S 36

1969

There are no suitable accessories nor locations available for reference monuments.

37.24 The point for Corner No. 6, lot 8 of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T8S R19W
L 8 |
C 6 |
L 9 |
S 35 | S 36

1969

There are no suitable accessories nor locations available for reference monuments.

39.97 The corner of secs. 25, 26, 35, and 36 is marked with an iron pipe, 2 ins. in diam., with brass cap 15 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
T8S R19W
S 26 | S 25
S 35 | S 36

1951

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954.

Discontinue the regular order of survey at this corner.

Restoring the Resurvey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

The 1/4 sec. cor. of secs. 25 and 36 is monumented with an iron post, 1-inch in diam., with regulation General Land Office brass cap 15 ins. below the surface of the road, mkd.

1/4 $\frac{S 25}{S 36}$

1912

16

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

WEST, between secs. 25 and 36.

Over nearly level land, along the center line of a road.

19.89 The point for the west 1/16 sec. cor. of secs. 25 and 36 is determined at proportionate distance; there is no evidence of the original corner. I did not remonument this corner point.

39.78 The corner of secs. 25, 26, 35 and 36, heretofore described.

N. 0° 03' W., between secs. 25 and 26.

Over nearly level land, along a north and south roadway.

19.975 The south 1/16 sec. cor. of secs. 25 and 26 is marked with an iron pipe, 1-inch in diam., with brass cap 5 ins. below the surface of the roadway, mkd.

BUREAU OF RECLAMATION

S 1/16
|
S 25 | S 26
|

1951

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 0° 03' W., beginning new measurement

2.575 The point for Angle Point No. 3, Tract 38 and Angle Point No. 5, Tract 39.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 39 | TR 38
AP 5 | AP 3
|
L 28
L 9 | S 25
S 26 |

1969

19.975 The 1/4 sec. cor. of secs. 25 and 26 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

17

CHAINS

BUREAU OF RECLAMATION

1/4
|
S 26 | S 25
|

1951

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation in 1954. I did not remonument this corner.

Restoring the Survey Executed by
Sidney E. Blout, U. S. Surveyor, in 1912

N. 0° 03' W., beginning new measurement

0.335 The point for Angle Point No. 2, Tract 38 and Angle Point No. 1, Tract 39.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
S 26 | S 25
L 3 | L 21
|
AP 2
AP 1 | TR 38
TR 39 |

1969

Ascend over rolling southeast slope.

19.98 The north 1/16 sec. cor. of secs. 25 and 26 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 15 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

N 1/16
|
S 26 | S 25
|

1951

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 0° 03' W., beginning new measurement

19.97 The corner of secs. 23, 24, 25, and 26 is monumented with an iron post, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S R19W
S 23 | S 24
S 26 | S 25

1912

Restoring the Resurvey Executed by
Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

From the corner of secs. 19, 24, 25 and 30, on the east boundary of the township, which is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 11 ins. above the surface of the ground; set, marked, and witnessed as described in the field-note record of the dependent resurvey of a portion of the west boundary of T. 8 S., R. 18 W., executed concurrently with this group.

S. 89° 34' W., between secs. 24 and 25.

Over nearly level land.

- 4.13 Angle Point No. 1, lot 5, which is identical with Angle Point No. 2, lot 6 of sec. 25, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

T8S R19W

S 24

AP 1 / AP 2
L 5 / L 6

S 25

1954

The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The description, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW 1/4 of the NW 1/4, and the south-half of the southwest quarter within sec. 25 are described in this survey.

I destroyed the above corner marker and from this same corner point a diligent search was made for any evidence of Angle Point No. 4, lot 5, which is identical with Angle Point No. 3, lot 6 of sec. 25, and none was found.

- 12.00 Leave bottom land, bears northeast and southwest; ascend along rolling south to southeast slope.

- 14.135 The point for Angle Point No. 1, Tract 38.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| | <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W S 24 ----- L 19 / AP 1 S 25 / TR 38</p> <p style="text-align: center;">1969</p> | |
| 19.425 | <p>The east 1/16 sec. cor. of secs. 24 and 25 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION E 1/16 S 24 ----- S 25</p> <p style="text-align: center;">1951</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr/> <p>S. 89° 34' W., beginning new measurement.</p> | |
| 19.895 | <p>The 1/4 sec. cor. of secs. 24 and 25 is monumented with an iron post, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> <p style="text-align: center;">1/4 S 24 ----- S 25</p> <p style="text-align: center;">1912</p> <hr/> <p style="text-align: center;">Restoring the Survey Executed by Sidney E. Blout, U. S. Surveyor, in 1912</p> <hr/> <p>N. 89° 51' W., beginning new measurement.</p> | |
| 19.985 | <p>The west 1/16 sec. cor. of secs. 24 and 25 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 S 24 ----- S 25</p> <p style="text-align: center;">1951</p> <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> | |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | N. 89° 51' W., beginning new measurement. |
| 19.98 | The corner of secs. 23, 24, 25, and 26, heretofore described. Discontinue the regular order of survey at this corner. |
| | <hr/> Restoring the Resurvey Executed by Albin H. Wadin, Engineer Bureau of Reclamation, in 1954 <hr/> |
| | From the corner of secs. 34 and 35 on the south boundary of the township, heretofore described. NORTH, between secs. 34 and 35. Over nearly level land. |
| 20.00 | The south 1/16 sec. cor. of secs. 34 and 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd. |
| | BUREAU OF RECLAMATION S 1/16 S 34 S 35 1951 |
| | The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner. |
| | <hr/> NORTH, beginning new measurement |
| 20.00 | The 1/4 sec. cor. of secs. 34 and 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd. |
| | BUREAU OF RECLAMATION 1/4 S 34 S 35 1951 |
| | The above corner was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner. |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| | <p>NORTH, beginning new measurement</p> | |
| 3.12 | <p>Angle Point No. 3, lot 6, which is identical with Angle Point No. 6, lot 7 of sec. 35, is marked with an iron pipe, 1-inch in diam., with brass cap missing, firmly set, projecting 8 ins. above the surface of the ground.</p> <p>The area of the north-half of the northeast quarter and the northwest quarter of sec. 35 is vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 40, and lots 8 through 14 inclusive within section 35 are described in this survey.</p> <p>I destroyed the above corner marker and from this same corner point a diligent search was made for any evidence of Angle Point No. 4, lot 6, which is identical with Angle Point No. 5, lot 7, and Angle Point No. 5, lot 6, which is identical with Angle Point No. 4, lot 7 of sec. 35, and none was found.</p> | |
| 19.63 | <p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 4, Tract 40, and Angle Point No. 8, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W TR 41 TR 40 AP 8 AP 4 ----- L 11 L 14 S 34 S 35</p> <p>1969</p> </div> | |
| 20.01 | <p>The north 1/16 sec. cor. of secs. 34 and 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION N 1/16 S 34 S 35 </p> <p>1954</p> </div> | |
| | <p>NORTH, beginning new measurement</p> | |
| 15.515 | <p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 3, Tract 40 and Angle Point No. 1, Tract. 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> | |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S R19W
S 34 | S 35
L 5 | L 12
AP 3
AP 1 | TR 40
TR 41 |

1969

- 19.99 The corner of secs. 26, 27, 34, and 35 is monumented with an iron post, 2 ins. in diam., firmly set, projecting 6 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

T8S R19W
S 27 | S 26
S 34 | S 35

1912

From the corner of secs. 25, 26, 35, and 36, heretofore described.

N. 89° 54.5' W., between secs. 26 and 35.

Over nearly level land.

- 20.065 The east 1/16 sec. cor. of secs. 26 and 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

E 1/16
S 26
S 35

1951

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 89° 54.5' W., beginning new measurement

- 16.845 The point for Angle Point No. 4, Tract 39, Angle Point No. 1, Tract 40, and Corner No. 2, lot 8 of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 39 / S 26
AP 4 / L 8
TR 40 / C 2
AP 1 / L 8
S 35

1969

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

20.055 The 1/4 sec. cor. of secs. 26 and 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

1/4
S 26
S 35

1951

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 89° 54.5' W., beginning new measurement

20.045 The west 1/16 sec. cor. of secs. 26 and 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 15 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

W 1/16
S 26
S 35

1951

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 89° 54.5' W., beginning new measurement.

8.42 The point for Angle Point No. 3, Tract 39 and Angle Point No. 2, Tract 40.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

| | | | |
|--|------|-------|--|
| | T8S | R19W | |
| | S 26 | TR 39 | |
| | L 7 | AP 3 | |
| | L 12 | AP 2 | |
| | S 35 | TR 40 | |

1969

20.055 The corner of secs. 26, 27, 34 and 35.

Restoring the Survey Executed by
Sidney E. Blout, U.S. Surveyor in 1912

N. 0° 01' W., between secs. 26 and 27.

Ascend over rolling southeast slope.


Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

20.00 The point for the south 1/16 sec. cor. of secs. 26 and 27. I did not monument this corner point.

40.00 The 1/4 sec. cor. of secs. 26 and 27 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION




1954

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 0° 03' W., beginning new measurement

1.50 The witness 1/4 sec. cor. of secs. 26 and 27 is monumented with an iron post, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.



1912


substantiated by:

A mound of stone, 4 ft. base, 1 1/2 ft. high, south-east of the corner.

N. 0° 03' W., beginning new measurement

18.50 The point for the north 1/16 sec. cor. of secs. 26 and 27.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



1969

38.50 The corner of secs. 22, 23, 26, and 27 is monumented with an iron post, 28 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| | <p style="text-align: center;">T8S R19W $\frac{S\ 22}{S\ 27} \frac{S\ 23}{S\ 26}$ 1912</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A mound of stone, 4 ft. base, 2 1/2 ft. high, south-east of the corner.</p> <hr/> <p>From the corner of secs. 23, 24, 25, and 26, heretofore described.</p> <p>N. 89° 47' W., between secs. 23 and 26.</p> <p>Ascend over rolling to broken southeast slope.</p> | |
| 40.05 | <p>The 1/4 sec. cor. of secs. 23 and 26 is monumented with an iron post, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> <p style="text-align: center;">$\frac{1}{4} \frac{S\ 23}{S\ 26}$ 1912</p> <hr/> <p>N. 89° 55' W., beginning new measurement</p> | |
| 6.65 | <p>Ridge spur, slopes southeast; continue over rolling to broken southeast slope.</p> | |
| 20.06 | <p>The point for the west 1/16 sec. cor. of secs. 23 and 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 17 ins. in the ground, and in a mound of stone, 2 ft. base, to the top, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S\ 23}{S\ 26}$ 1969</p> | |
| 40.12 | <p>The corner of secs. 22, 23, 26 and 27, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>The 1/4 sec. cor. of secs. 33 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 19 ins. above the surface of the ground, and in a low mound of stone, with brass cap mkd.</p> | |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

1/4

S 33 | S 34

1951

The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 0° 03' E., between secs. 33 and 34.

Over nearly level land.

9.01 The point for Angle Point No. 4, Tract 42.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W

TR 42 |

AP 4 | S 34

L 4 |

S 33 |

1969

19.99 The north 1/16 sec. cor of secs. 33 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

N 1/16

S 33 | S 34

1951

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 0° 03' E., beginning new measurement

4.234 The point for Angle Point No. 3, Tract 41 and Angle Point No. 1, Tract 42.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W

S 33 | S 34

L 1 | L 8

AP 1 | AP 3

TR 42 | TR 41

1969

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

27

| CHAINS | | |
|--------|--|--|
| | <p>Thence, ascend over south slope.</p> | |
| 20.01 | <p>The corner of secs. 27, 28, 33, and 34 is monumented with an iron post, 2 ins. in diam., firmly set, projecting 11 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> | |
| | <p style="text-align: center;">T8S R19W S 28 S 27 S 33 S 34</p> <p style="text-align: center;">1912</p> | |
| | <p>substantiated by:</p> <p style="padding-left: 40px;">A mound of stone, 3 ft. base, 2 ft. high, west of the corner.</p> | |
| | <hr/> <p>From the corner of secs. 26, 27, 34, and 35, heretofore described.</p> <p>N. 89° 53' W., between secs. 27 and 34.</p> <p>Over nearly level land.</p> | |
| 14.00 | <p>Leave botton land, ascend along rolling south slope.</p> | |
| 20.04 | <p>The east 1/16 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">BUREAU OF RECLAMATION E 1/16 S 27 S 34</p> <p style="text-align: center;">1951</p> <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> | |
| | <p style="text-align: center;">N. 89° 53' W., beginning new measurement</p> | |
| 20.03 | <p>The 1/4 sec. cor. of secs. 27 and 34, is monumented with an iron post, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> | |
| | <p style="text-align: center;">S 27 1/4 S 34</p> <p style="text-align: center;">1912</p> | |
| | <p>substantiated by:</p> <p style="padding-left: 40px;">A mound of stone, 2 ft. base, 1 1/2 ft. high, north of the corner.</p> | |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>N. 89° 53' W., beginning new measurement</p> |
| 20.07 | <p>The west 1/16 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 S 27 S 34</p> <p style="text-align: center;">1951</p> <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 89° 53' W., beginning new measurement</p> |
| 20.04 | <p>The corner of secs. 27, 28, 33, and 34, heretofore described.</p> <hr/> <p>From the corner of secs. 32 and 33 on the south boundary of the township, heretofore described.</p> <p>NORTH, between secs. 32 and 33.</p> <p>Over nearly level land, along the center line of a road.</p> |
| 16.09 | <p>The point for Angle Point No. 1, Tract 45.</p> <p>Set an aluminum rod, 48 ins. long, 5/8-inch diam., with aluminum cap 3 1/4 ins. diam., 7 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R19W S 32 S 33 AP 1 TR 45</p> <p style="text-align: center;">1981</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> |
| 20.02 | <p>The south 1/16 sec. cor. of secs. 32 and 33 is marked with an iron pipe, 1-inch in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION S 1/16 S 32 S 33</p> <p style="text-align: center;">1950</p> <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

29

| CHAINS | | |
|--------|---|--|
| | <p>NORTH, beginning new measurement</p> <p>20.01 The point for the 1/4 sec. cor. of secs. 32 and 33 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R19W 1/4 S 32 S 33 </p> <p>1969</p> </div> <p>from which</p> <p>An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 48° 25' E., 39.2 ft. distant, with brass cap mkd. RM T8S R19W S33 39.2 FT 1969, and an arrow pointing to the corner.</p> <p>An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 44° 55' W., 38.8 ft. distant, with brass cap mkd. RM T8S R19W S32 38.8 FT 1969, and an arrow pointing to the corner.</p> <p>60.03 The corner of secs. 28, 29, 32, and 33 is marked with an iron pipe, 2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION T8S R19W S 29 S 28 S 32 S 33</p> <p>1950</p> </div> <p>The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr/> <p>From the corner of secs. 27, 28, 33, and 34, heretofore described.</p> <p>N. 89° 51.5' W., between secs. 28 and 33.</p> <p>Over nearly level land.</p> <p>20.065 The east 1/16 sec. cor. of secs. 28 and 33 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 12 ins. above the surface of the ground, with brass cap mkd.</p> | |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

E 1/16

S 28

S 33

1952

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 89° 51.5' W., beginning new measurement

20.085 The 1/4 sec. cor. of secs. 28 and 33 is monumented with an iron post, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

S 28

1/4

S 33

1912

substantiated by:

A mound of stone, 3 ft. base, 1 ft. high, north of the corner.

Discontinue the regular order of survey at this corner.

From the corner of secs. 31 and 32 on the south boundary of the township, heretofore described.

N. 0° 02' W., between secs. 31 and 32.

Over nearly level land.

20.02 The south 1/16 sec. cor. of secs. 31 and 32 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

S 1/16

S 31 | S 32

1952

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 0° 02' W., beginning new measurement

20.02 The 1/4 sec. cor. of secs. 31 and 32 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| | <p style="text-align: center;">BUREAU OF RECLAMATION 1/4 S 31 S 32 1952</p> <p>The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 02' W., beginning new measurement</p> | |
| 19.62 | <p>The point for Angle Point No. 1 Tract 37.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W S 31 L 7 S 32 AP 1 TR 37 1969</p> | |
| 20.01 | <p>The north 1/16 sec. cor. of secs. 31 and 32 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION N 1/16 S 31 S 32 1952</p> <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 02' W., beginning new measurement</p> | |
| 0.375 | <p>The point for Angle Point No. 4, Tract 44.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 in in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 44 AP 4 S 32 S 31 1981</p> | |
| 1.95 | <p>Road, parallels the hereinafter described canal.</p> | |
| 2.25 | <p>Left bank of canal, flows northwest.</p> | |

32

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 2.80 | Right bank of canal. |
| 3.20 | Road, parallels the above canal. |
| 5.755 | <p>The point for Angle Point No. 14, Tract 43 and Angle Point No. 1, Tract 44.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> |
| 20.02 | <p style="text-align: center;">T8S R19W TR 43 AP 14 S 32 AP 1 TR 44 </p> <p style="text-align: center;">1981</p> <p>The corner of secs. 29, 30, 31, and 32 is marked with an iron pipe, 1-inch in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R19W S 30 S 29 S 31 S 32</p> <p style="text-align: center;">1959</p> <p>The above corner marker is accepted as a careful and faithful reestablishment of the position of the original corner.</p> <p>from which</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 42° 20' W., 39 ft. distant, with brass cap mkd. RM T8S R19W S 31 39 FT 1969, and an arrow pointing to the corner.</p> <p style="padding-left: 40px;">An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 39° 05' W., 59.1 ft. distant, with brass cap mkd. RM T8S R19W S30 59.1 FT 1969 and an arrow pointing to the corner.</p> <p>Discontinue the regular order of survey at this corner.</p> |
| 20.01 | <p>N. 89° 55' W., between secs. 30 and 31.</p> <p>Over nearly level land, along the center line of a road.</p> <p>The point for the east 1/16 sec. cor. of secs. 30 and 31, at proportionate dist.; there is no evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the ground, mkd.</p> |

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

33

| CHAINS | |
|--------|--|
| | <p style="text-align: center;">E 1/16 S 30 S 31</p> <p style="text-align: center;">1969</p> |
| 40.02 | <p>The point for the 1/4 sec. cor. of secs. 30 and 31, at proportionate distance; there is no evidence of the original corner.</p> |
| | <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.</p> |
| | <p style="text-align: center;">T8S R19W 1/4 S 30 S 31</p> <p style="text-align: center;">1969</p> |
| | <p>from which</p> |
| | <p>An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 71° 15' E., 88.2 ft. distant, with brass cap mkd. RM T8S R19W S31 88.2 FT 1969, and an arrow pointing to the corner.</p> |
| | <p>An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears S. 7° 00' W., 28.7 ft. distant, with brass cap mkd. RM T8S R19W S31 28.7 FT 1969, and an arrow pointing to the corner.</p> |
| 76.35 | <p>The corner of secs. 25, 30, 31, and 36 on the west boundary of the township.</p> |
| | <p>Discontinue the dependent resurvey of the subdivisional lines at this corner.</p> |
| | <p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivision Lines Within a Number of Sections Township 8 South, Range 19 West Gila and Salt River Meridian, Arizona</p> |
| | <p style="text-align: center;">Restoring the Survey Executed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954</p> |
| | <p>Thence, in section 25</p> |
| | <p>From the 1/4 sec. cor. of secs. 25 and 36, heretofore described.</p> |
| | <p>N. 0° 05' E., on the north and south center line of sec. 25.</p> |
| 20.025 | <p>The center-south 1/16 sec. cor. of sec. 25 is marked with an iron pipe, 1-inch in diam., with brass cap 3 ins. below the surface of the ground, mkd.</p> |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

C S
 1/16
 S 25

1954

N. 0° 05' E., beginning new measurement

17.90 The point for Angle Point No. 5, lot 15, which is identical with Angle Point No. 1, lot 16 of sec. 25, determined at proportionate distance; there is no evidence of the original cor.

The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The description, lot number (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.

From the above corner point, a diligent search was made for any evidence of Angle Point No. 4, lot 15, which is identical with Angle Point No. 2, lot 16 of section 25, and one was found.

20.01 The center 1/4 sec. cor. of sec. 25 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

C 1/4
 S 25

1954

N. 0° 05' E., beginning new measurement.

6.87 Intersect line 3 - 4, Tract 38, hereinafter described.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
 TR 38
 |
 L 23
 L 26 |
 S | 25

1969

From this intersection, Angle Point No. 3, Tract 38, heretofore described, bears S. 58° 38' W., 46.685 chs. dist.

Thence, on a blank line across Tract 38.

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

35

| CHAINS | | |
|--------|--|--|
| 11.95 | <p>Angle Point No. 3, lot 10, which is identical with Angle Point No. 4, lot 11 of sec. 25, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R19W AP 3 L 10 AP 4 L 11 S 25</p> <p style="text-align: center;">1954</p> <p>The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The description, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within sec. 25 are described in this survey. I destroyed the above corner marker.</p> | |
| 19.89 | <p>The center-north 1/16 sec. cor. of sec. 25 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C N 1/16 S 25</p> <p style="text-align: center;">1954</p> <hr/> <p>N. 0° 05' E., beginning new measurement.</p> | |
| 4.745 | <p>Intersect line 1 - 2, Tract 38, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W S 25 L 20 L 19 TR 38</p> <p style="text-align: center;">1969</p> <p>From this intersection, Angle Point No. 1, Tract 38, heretofore described, bears N. 58° 38' E., 29.53 chs. distant.</p> | |
| 19.93 | <p>The 1/4 sec. cor. of secs. 24 and 25, heretofore described.</p> | |

Dependent Resurvey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

From the 1/4 sec. cor. of secs. 25 and 30, on the east boundary of the township, which is monumented with an iron post, 1-inch in diam., with brass cap 11 ins. below the surface of the road, marked, and witnessed as described in the field-note record of the dependent resurvey of a portion of the west boundary of T. 8 S., R. 18 W., executed concurrently with this group.

S. 89° 57.5' W., on the east and west center line of sec. 25.

19.57 The point for the center-east 1/16 sec. cor. of sec. 25 is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.

30.89 The point for Angle Point No. 6, lot 11, which is identical with Angle Point No. 3, lot 12 of sec. 25, determined at proportionate distance; there is no evidence of the original cor.

The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The description, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.


From the above corner point a diligent search was made for any evidence of Angle Point No. 7, lot 11, which is identical with Angle Point No. 2, lot 12 of section 25, and none was found.

39.56 The center 1/4 sec. cor. of sec. 25, heretofore described.

S. 89° 55' W., beginning new measurement.

11.275 Intersect line 3 - 4, Tract 38, hereinafter described.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



1969

From this intersection, Angle Point No. 3, Tract 38, heretofore described, bears S. 58° 38' W., 33.47 chs. distant.

Thence, on a blank line across Tract 38.

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

37

| CHAINS | |
|--------|--|
| 19.93 | <p>The center-west 1/16 sec. cor. of sec. 25 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C W 1/16 S 25 1954</p> <hr style="width: 20%; margin: auto;"/> <p>S. 89° 55' W., beginning new measurement.</p> |
| 19.945 | <p>The 1/4 sec. cor. of secs. 25 and 26, heretofore described.</p> <hr/> <p>From the point for the center-east 1/16 sec. cor. of sec. 25, heretofore described.</p> <p>N. 0° 06' W., on the north and south center line the northeast quarter of sec. 25.</p> |
| 11.58 | <p>The point for Angle Point No. 8, lot 11, which is identical with Angle Point No. 1, lot 12, Angle Point No. 3, lot 13, and Angle Point No. 3, lot 14 of sec. 25, and is determined at proportionate distance; there is not evidence of the original cor.</p> <p>The area of section 25 has remained vacant (United States ownership), with the exception of the southeast quarter, which is patented (private ownership). The description, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.</p> |
| 19.04 | <p>Intersect line 3 - 4, Tract 38, hereinafter described.</p> <p>From this point of intersection, Angle Point No. 4, Tract 38, bears N. 58° 38' E., 22.765 chs. distant.</p> <p>Thence, on a blank line across Tract 38.</p> |
| 19.97 | <p>Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 25; there is no evidence of the original cor. I did not monument this corner point.</p> |
| 23.52 | <p>The point for Angle Point No. 3, lot 5, which is identical with Angle Point No. 4, lot 6, Angle Point No. 5, lot 8, and Angle Point No. 1, lot 9 of sec. 25, and is determined at proportionate distance; there is no evidence of the original cor.</p> |

Dependent Resurvey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The description, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.</p> |
| 36.73 | <p>Intersect line 1 - 2, Tract 38, hereinafter described.</p> <p>From this point of intersection, Angle Point No. 1, Tract 38, bears N. 58° 38' E., 6.195 chs. distant.</p> |
| 39.95 | <p>The east 1/16 sec. cor. of secs. 24 and 25, heretofore described.</p> |
| | <hr/> <p>From the north 1/16 sec. cor. of secs. 25 and 30 on the east boundary of the township, which is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, and marked as described in the field-note record of the dependent resurvey of a portion of the west boundary of T. 8 S., R. 18 W., executed concurrently with this group.</p> <p>S. 89° 44.5' W., on the east and west center line of the northeast quarter of sec. 25.</p> |
| 9.70 | <p>The point for Angle Point No. 6, lot 6, which is identical with Angle Point No. 2, lot 7, Angle Point No. 1, lot 13, and Angle Point No. 2, lot 14 of sec. 25, and is determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The description, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 and the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.</p> |
| 17.965 | <p>Intersect line 3 - 4, Tract 38, hereinafter described</p> <p>From this point of intersection, Angle Point No. 4, Tract 38, bears N. 58° 38' E., 20.97 chs. dist.</p> <p>Thence, on a blank line across Tract 38.</p> |
| 19.50 | <p>Intersect the north and south center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 25, heretofore described.</p> |
| 22.855 | <p>The point for Angle Point No. 4, lot 8, which is identical with Angle Point No. 2, lot 9, Angle Point No. 1, lot 10, and Angle Point No. 2, lot 11 of sec. 25, and is determined at proportionate distance; there is no evidence of the original cor.</p> |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

39

| CHAINS | | |
|--------|---|--|
| | <p>The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The descriptions, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.</p> <p>From the above corner, a diligent search was made for any evidence of Angle Point No. 4, lot 10, which is identical with Angle Point No. 3, lot 11 of sec. 25, none was found.</p> | |
| 39.425 | <p>The center-north 1/16 sec. cor. of sec. 25, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> | |
| | <p>From the point for the west 1/16 sec. cor. of secs. 25 and 36, heretofore described.</p> <p>N. 0° 01' E., on the north and south center line of the southwest quarter of sec. 25.</p> | |
| 20.00 | <p>The southwest 1/16 sec. cor. of sec. 25, is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">BUREAU OF RECLAMATION SW 1/16 S 25 1954</p> | |
| | <p>N. 0° 01' E., beginning new measurement.</p> | |
| 7.39 | <p>The point for Angle Point No. 3, lot 15, which is identical with Angle Point No. 3, lot 16, Angle Point No. 1, lot 17, and Angle Point No. 7, lot 18 of section 25, and is determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The descriptions, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey.</p> <p>From the above corner point, a diligent search was made for any evidence of Angle Point No. 2, lot 17, which is identical with Angle Point No. 6, lot 18 of sec. 25, and none was found.</p> | |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 14.72 | Intersect line 3 - 4, Tract 38, hereinafter described. From this point of intersection, Angle Point No. 3, Tract 38, bears S. 58° 38' W., 23.345 chs. distant. |
| 19.99 | The center-west 1/16 sec. cor. of sec. 25, heretofore described. |
| | From the center-south 1/16 sec. cor. of sec. 25, heretofore described. S. 89° 57' W., on the east and west center line of the southwest quarter of sec. 25. |
| 19.91 | The southwest 1/16 sec. cor. of sec. 25, heretofore described. S. 89° 57' W., beginning new measurement. |
| 16.87 | The point for Angle Point No. 4, lot 17, which is identical with Angle Point No. 4, lot 18 of sec. 25, and is determined at proportionate distance; there is no evidence of the original corner. The area of section 25 has remained vacant (United States ownership) with the exception of the southeast quarter, which is patented (private ownership). The descriptions, lot numbers (with the exception of the southeast quarter), and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 38, and lots 19 through 28 inclusive, the NW1/4 of the NW1/4, and the south-half of the southwest quarter within section 25 are described in this survey. From the above corner point, a diligent search was made for any evidence of Angle Point No. 3, lot 17, which is identical with Angle Point No. 5, lot 18 of sec. 25, and none was found. |
| 19.92 | The south 1/16 sec. cor. of secs. 25 and 26, heretofore described. Thence, in section 26 From the 1/4 sec. cor. of secs. 26 and 35, heretofore described. N. 0° 01.5' W., on the north and south center line of sec. 26, and on a blank line across Tract 39. |
| 15.78 | Intersect line 1 - 2, Tract 39, hereinafter described. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

41

| CHAINS | | |
|--------|---|--|
| | <p style="text-align: center;">T8S R19W S 26 L 6 L 5 /-----\ TR 39</p> <p style="text-align: center;">1969</p> <p>From this intersection, Angle Point No. 2, Tract 39, hereinafter described, bears S. 58° 38' W., 12.585 chs. distant.</p> | |
| 19.98 | <p>The center-south 1/16 sec. cor. of sec. 26 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C S 1/16 S 26</p> <p style="text-align: center;">1954</p> <hr/> <p>N. 0° 01.5' W., beginning new measurement</p> | |
| 19.99 | <p>The center 1/4 sec. cor. of sec. 26 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 15 ins. above the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C 1/4 S 26</p> <p style="text-align: center;">1954</p> <hr/> <p>N. 0° 01.5' W., beginning new measurement.</p> | |
| 20.02 | <p>The point for the center-north 1/16 sec. cor. of sec. 26. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W C N 1/16 S 26</p> <p style="text-align: center;">1969</p> | |
| 40.04 | <p>The 1/4 sec. cor. of secs. 23 and 26, heretofore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 25 and 26, heretofore described.</p> <p>N. 89° 53' W., on the east and west center line of sec. 26, and on a blank line across Tract 39.</p> | |
| 0.55 | <p>Intersect line 1 - 2, Tract 39, hereinafter described.</p> | |

42

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

| CHAINS | | |
|---------------|--|--|
| | <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam. 23 ins. in the ground, with brass cap mkd.</p> | |
| | <p style="text-align: center;">T8S R19W S 26 L 3 L 4 TR 39</p> <p style="text-align: center;">1969</p> | |
| | <p>From this intersection, Angle Point No. 1, Tract 39, heretofore described, bears N. 58° 38' E., 0.645 chs. distant.</p> | |
| <p>20.045</p> | <p>The center-east 1/16 sec. cor. of sec. 26 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C E 1/16 S 26</p> <p style="text-align: center;">1954</p> | |
| | <p>N. 89° 53' W., beginning new measurement.</p> | |
| <p>20.03</p> | <p>The center 1/4 sec. cor. of sec. 26, heretofore described.</p> | |
| | <p>N. 89° 53' W., beginning new measurement.</p> | |
| <p>10.03</p> | <p>The point for the C-E-W 1/64 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 17 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.</p> <p style="text-align: center;">C E W 1/64 S 26</p> <p style="text-align: center;">1969</p> | |
| <p>20.06</p> | <p>The point for the center-west 1/16 sec. cor. of sec. 26.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C W 1/16 S 26</p> <p style="text-align: center;">1969</p> | |
| <p>40.12</p> | <p>The 1/4 sec. cor. of secs. 26 and 27, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> | |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

43

| CHAINS | | |
|--------|---|--|
| | <p>From the east 1/16 sec. cor. of secs. 26 and 35, heretofore described.</p> <p>N. 0° 02.5' W., on the north and south center line of the southeast quarter of sec. 26.</p> | |
| 9.99 | <p>The point for Angle Point No. 3, lot 1, which is identical with Angle Point No. 2, lot 2 of sec. 26, determined at proportionate distance; there is no evidence of the original cor.</p> <p>The area of section 26 has remained vacant (United States ownership). The description, lot number and the above corners controlling the positions of lots 1 and 2, are voided by this survey. New descriptions of Tract 39, and lots 3 through 11 inclusive, within section 26 are described in this survey.</p> | |
| 10.295 | <p>Intersect line 4 - 5, Tract 39, hereinafter described. From this point of intersection, Angle Point No. 4, Tract 39, bears S. 58° 38' W., 19.725 chs. dist.</p> <p>Thence, on a blank line across Tract 39.</p> | |
| 19.98 | <p>The point for the southeast 1/16 sec. cor. of sec. 26, is determined at record distance; there is no evidence of the original corner. I did not monument this corner point.</p> | |
| 28.04 | <p>Intersect line 1 - 2, Tract 39, hereinafter described. From this point of intersection, Angle Point No. 1, Tract 39, bears N. 58° 38' E., 23.465 chs. distant.</p> | |
| 39.96 | <p>The center-east 1/16 sec. cor. of sec. 26, heretofore described.</p> <hr/> <p>Thence, in section 34</p> <p>From the south 1/4 sec. cor. of sec. 34, heretofore described.</p> <p>N. 0° 02' E., on the north and south center line of sec. 34.</p> | |
| 20.00 | <p>The center-south 1/16 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C S 1/16 S 34 1954</p> <hr/> <p>N. 0° 02' E., beginning new measurement.</p> | |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 20.01 | <p>The center 1/4 sec. cor. of sec. 34, is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C 1/4 S 34 1954</p> <hr style="width: 20%; margin: auto;"/> <p>N. 0° 02' E., beginning new measurement.</p> |
| 12.735 | <p>Intersect line 6 - 7, Tract 41, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 41 / L 9 L 10 S 34 1969</p> <p>From this intersection, Angle Point No. 7, Tract 41, hereinafter described, bears N. 84° 50.5' E., 8.75 chs. dist.</p> <p>Thence, on a blank line across Tract 41.</p> |
| 20.01 | <p>The point for the center-north 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 34 1969</p> |
| 27.95 | <p>Intersect line 2 - 3, Tract 41, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W S 34 L 7 L 6 / TR 41 1969</p> <p>From this intersection, Angle Point No. 2, Tract 41, hereinafter described, bears N. 84° 50.5' E., 7.375 chs. dist.</p> |
| 40.02 | <p>The 1/4 sec. cor. of secs. 27 and 34, heretofore described.</p> <hr style="width: 50%; margin: auto;"/> |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

45

CHAINS

From the 1/4 sec. cor. of secs. 34 and 35, heretofore described.

N. 89° 53' W., on the east and west center line of sec. 34.

- 7.81 Angle Point No. 2, lot 1, which is identical with Angle Point No. 1, lot 2 of sec. 34, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
 T8S R19W

AP 1 / AP 2
 L 2 / L 1
 S 34

1954

- 20.05 The center-east 1/16 sec. cor. of sec. 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

C E
 1/16
 S 34

1954

N. 89° 53' W., beginning new measurement.

- 20.06 The center 1/4 sec. cor. of sec. 34, heretofore described.

N. 89° 53' W., beginning new measurement.

- 20.07 The center-west 1/16 sec. cor. of sec. 34 is marked with an iron pipe, 10 ins. long, 1-inch in diam., firmly set 7 ins. in the ground, and is accepted as the positions of the corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

C W
 1/16
 S 34
 1969

Deposit the iron pipe corner marker inside the iron post.

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

46

| CHAINS | | |
|--------|---|--|
| | N. 89° 53' W., beginning new measurement. | |
| 20.05 | The 1/4 sec. cor. of secs. 33 and 34, heretofore described. | |
| | Thence, in section 35 | |
| | The south 1/4 sec. cor. of sec. 35, on the south boundary of the township, which is marked with an iron pipe, 1-inch in diam., with brass cap 7 ins. below the surface of the road, mkd. | |
| | BUREAU OF RECLAMATION | |
| | S C | |
| | <u>1/4 S 35</u> | |
| | 1949 | |
| | The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner. | |
| | from which | |
| | An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 56° 00' E., 48.2 ft. distant, with brass cap mkd. RM T8S R19W S35 48.2 FT 1969, and an arrow pointing to the corner. | |
| | An iron post 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears N. 54° 00' W., 46.8 ft. distant, with brass cap mkd. RM T8S R19W S35 46.8 FT 1969, and an arrow pointing to the corner. | |
| | N. 0° 02' W., on the north and south center line of sec. 35. | |
| 19.20 | Enter and continue along the center line of a lateral; at the intersection of laterals, bears east and west. | |
| 19.80 | Lateral bears west; continue along the center line of the above lateral. | |
| 40.00 | Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 35. This corner point is located on the center line of a north and south lateral; there is no evidence of the original corner. A witness corner is hereinafter described. | |
| 59.99 | The point for the C-N 1/16 sec. cor. of sec. 35, at proportionate dist.; there is no evidence of the original corner. This corner point is located on the center line of a north and south lateral, where it is impracticable to establish a permanent monument. | |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

47

CHAINS

From this cor. point, the point for the witness C-N 1/16 sec. cor. of sec. 35, bears East, 0.14 chs. dist.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

C N 1/16
 W C ←
 S 35
 1969

74.20 Leave lateral, bears N. 69° 00' E., thence, over nearly level land.

74.625 The point for Corner No. 4, lot 8 of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T8S R19W
 | L 8
 | C 4
 L 11 |
 | L 10
 S | 35
 1969

from which

A wheel shaft on a water gate, bears SOUTH, 1.43 chs. distant.

There are no other suitable accessory nor locations available for reference monuments.

The above corner is located within a roadway; roadway parallels (hereinafter described) line 4 - 5, lot 8 of sec. 35.

74.68 The point for Angle Point No. 5, lot 1, which is identical with Angle Point No. 1 lot 2 of sec. 35, determined at proportionate distance; there is no evidence of the original corner.

The area of the north-half of the northeast quarter and the northwest quarter has remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 40, and lots 8 through 14 inclusive within section 35 are described in this survey.

76.875 The point for Angle Point No. 7, Tract 40.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

48

CHAINS

T8S R19W
 TR 40 |
 AP 7 | L 8
 L 11 |
 S | 35

1969

78.02 The point for Angle Point No. 8, Tract 40, and Corner No. 3, lot 8 of sec. 35.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
 TR 40
 AP 8 |
 C 3
 L 8
 S 35

1969

Thence, on a blank line across Tract 40.

79.98 The 1/4 sec. cor. of secs. 26 and 35, heretofore described.

From the 1/4 sec. cor. of secs. 35 and 36, heretofore described.

N. 89° 55.5' W., on the east and west center line of sec. 35.

39.99 Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for the witness center 1/4 sec. cor. of sec. 35, with brass cap mkd.

T8S R19W
 W C ← C 1/4
 S 35

1969

40.13 Intersect the north and south center line, the true point for the center 1/4 sec. cor. of sec. 35, heretofore described.

60.19 The center-west 1/16 sec. cor. of sec. 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

C W
 1/16
 S 35

1954

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

49

| CHAINS | | |
|--------|---|--|
| 20.06 | <p>N. 89° 55.5' W., beginning new measurement.</p> <p>The 1/4 sec. cor. of secs. 34 and 35, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> | |
| 19.99 | <p>From the center-west 1/16 sec. cor. of sec. 35, heretofore described.</p> <p>N. 0° 01' W., on the north and south center line of the northwest quarter of sec. 35.</p> <p>The northwest 1/16 sec. cor. of sec. 35 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION NW 1/16 S 35 1954</p> | |
| 5.36 | <p>N. 0° 01' W., beginning new measurement.</p> <p>The point for Angle Point No. 3, lot 1, which is identical with Angle Point No. 3, lot 2, Angle Point No. 1, lot 3, and Angle Point No. 4, lot 4 of sec. 35, determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of the north-half of the northeast quarter and the northwest quarter has remained vacant (United States ownership). The description, lot numbers and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 40, and lots 8 through 14 inclusive within section 35 are described in this survey.</p> <p>From the above corner point, a diligent search was made for any evidence of Angle Point No. 4, lot 1, which is identical with Angle Point No. 2, lot 2 of sec. 35, and none was found.</p> | |
| 7.12 | <p>Intersect the arc of a curve, line 4 - 5, Tract 40, hereinafter described. From this point of intersection Angle Point No. 5, bears along the arc of the above curve 19.035 chs. distant.</p> <p>Thence, on a blank line across Tract 40.</p> | |
| 19.99 | <p>The west 1/16 sec. cor. of secs. 26 and 35, heretofore described.</p> | |

Dependent Resurvey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

50

CHAINS

From the true point for the center-north 1/16 sec. cor. of sec. 35, heretofore described.

N. 89° 55' W., on the east and west center line of the northwest quarter of sec. 35.

20.05 The northwest 1/16 sec. cor. of sec. 35, heretofore described.

N. 89° 55' W., beginning new measurement.

5.42 The point for Angle Point No. 2, lot 3, which is identical with Angle Point No. 3, lot 4, Angle Point No. 1, lot 6, and Angle Point No. 2, lot 7 of sec. 35, determined at proportionate distance; there is no evidence of the original corner.

The area of the north-half of the northeast quarter and the northwest quarter has remained vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions of Tract 40 and lots 8 through 14 inclusive within section 35 are described in this survey.

From the above corner point, a diligent search was made for any evidence of Angle Point No. 6, lot 6, which is identical with Angle Point No. 3, lot 7 of section 35, and none was found.

18.50 Intersect the arc of a curve, line 4 - 5, Tract 40, hereinafter described. From this point of intersection Angle Point No. 4, bears along the arc of the above curve 1.60 chs. distant.

20.06 The north 1/16 sec. cor. of secs. 34 and 35, heretofore described.

Discontinue the dependent resurvey of a portion of the subdivision lines at this corner.

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

Thence, in section 26

From the center-west 1/16 sec. cor. of sec. 26, heretofore described.

N. 0° 01' W., on the north and south center line of the northwest quarter of sec. 26.

20.02 Intersect the east and west center line of the northwest quarter, the point for the northwest 1/16 sec. cor. of sec. 26. This corner point is located within a wash, 10 lks. wide, drains to the southeast; where it is impracticable to establish a permanent monument.

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

51

| CHAINS | |
|--------|---|
| 21.02 | <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for the witness northwest 1/16 sec. cor. of sec. 26, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S ↓ 26 ↓ W C 1969</p> |
| 40.03 | <p>The west 1/16 sec. cor. of secs. 23 and 26, heretofore described.</p> <hr/> <p>From the center-north 1/16 sec. cor. of sec. 26, heretofore described.</p> <p>N. 89° 53.5' W., on the east and west center line of the northwest quarter of sec. 26.</p> |
| 10.03 | <p>The point for the C-E-NW 1/64 sec. cor. of sec. 26</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C E NW 1/64 S 26 1969</p> |
| 20.06 | <p>Intersect the north and south center line of the northwest quarter, the true point for the northwest 1/16 sec. cor. of sec. 26, heretofore described.</p> |
| 40.12 | <p>The north 1/16 sec. cor. of secs. 26 and 27, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the C-E-W 1/64 sec. cor. of sec. 26, heretofore described.</p> <p>N. 0° 01' W., on the north and south center line of the SE 1/4 of the NW 1/4 of sec. 26.</p> |
| 20.02 | <p>Intersect the east and west center line of the northwest quarter, the C-E-NW 1/64 sec. cor. of sec. 26, heretofore described.</p> <hr/> <p>Thence, in section 31</p> <p>From the south 1/4 sec. cor. of sec. 31, on the south boundary of the township, heretofore described.</p> |

52

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

N. $0^{\circ} 03.5'$ W., on the north and south center line of sec. 31.

19.915 Intersect the arc of a curve, line 6 - 7, Tract 37, hereinafter described.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 37

1969

From this intersection Angle Point No. 7, Tract 37, hereinafter described, bears along the arc of the above curve 1.80 chs. distant.

Thence, on a blank line across Tract 37.

35.505 Intersect the arc of a curve, line 2 - 3, Tract 37, hereinafter described.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
S|31

L 10 | L 11

TR 37

1969

From this intersection, Angle Point No. 3, Tract 37, hereinafter described, bears along the arc of the above curve 14.92 chs. distant.

40.03 The center 1/4 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
CENTER
SEC 31
T8S R19W

1953

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. $0^{\circ} 03.5'$ W., beginning new measurement.

11.42 Intersect line 7 - 8, Tract 43, no permanent monument established; from this point of intersection Angle Point No. 8, Tract 43 bears S. $76^{\circ} 18'$ E., 0.28 chs. distant.

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

53

CHAINS

20.02 The center-north 1/16 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

N 1/16

C

SEC 31

C

1953

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 0° 03.5' W., beginning new measurement.

20.025 The 1/4 sec. cor. of secs. 30 and 31, heretofore described.

From the 1/4 sec. cor of secs. 31 and 32, heretofore described.

N. 89° 54.5' W., on the east and west center line of sec. 31.

0.735 The point for Angle Point No. 14, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W

TR 37

AP 14

/ L 12

/ S 31

1969

Thence, on a blank line across Tract 37.

20.00 The center-east 1/16 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

E 1/16

C ————— C

SEC 31

1953

The above corner point is accepted as a careful and faithful determination of the position of the corner.

N. 89° 54.5' W., beginning new measurement.

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| 7.88 | <p>Intersect the arc of a curve, line 2 - 3, Tract 37, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W S 31 $\frac{L 8}{L 11 / TR 37}$ 1969</p> <p>From this intersection, Angle Point No. 2, Tract 37, hereinafter described, bears along the arc of the above curve 13.67 chs. distant.</p> |
| 19.99 | <p>The center 1/4 sec. cor. of sec. 31, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 54.5' W., beginning new measurement.</p> |
| 20.01 | <p>The center-west 1/16 sec. cor. of sec. 31 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 $\frac{C}{SEC 31}$ 1953</p> <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 54.5' W., beginning new measurement.</p> |
| 16.415 | <p>The 1/4 sec. cor. of secs. 31 and 36 on the west boundary of the township, heretofore described.</p> <hr style="width: 70%; margin: 10px auto;"/> <p>Thence, in section 33</p> <p>From the south 1/4 sec. cor. of sec. 33, on the south boundary of the township, heretofore described.</p> <p>N. 0° 01.5' E., on the north and south center line of sec. 33.</p> |
| 20.01 | <p>The center-south 1/16 sec. cor. of sec. 33 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION S 1/16 C SEC 33 C 1953</p> |

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona

55

| CHAINS | |
|--------|--|
| | <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 01.5' E., beginning new measurement.</p> |
| 20.005 | <p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 33.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W C 1/4 S 33</p> <p style="text-align: center;">1969</p> |
| 25.295 | <p>The point for Angle Point No. 3, Tract 42.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 42 AP 3 L 3 S 33</p> <p style="text-align: center;">1969</p> |
| 40.51 | <p>The point for Angle Point No. 2, Tract 42.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W S 33 L 2 AP 2 TR 42</p> <p style="text-align: center;">1969</p> |
| 60.04 | <p>The 1/4 sec. cor. of secs. 28 and 33, heretofore described.</p> <hr/> <p>From the 1/4 sec. cor. of secs. 33 and 34, heretofore described.</p> <p>N. 89° 53' W., on the east and west center line of sec. 33.</p> |
| 20.07 | <p>The center-east 1/16 sec. cor. of sec. 33 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.</p> |

56

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | <p>BUREAU OF RECLAMATION E 1/16 C ————— C SEC 33 1954</p> |
| | <p>The above corner point is accepted as a careful and faithful determination of the position of the corner.</p> <hr/> <p>N. 89° 53' W., beginning new measurement.</p> |
| 20.075 | Intersect the north and south center line, the center 1/4 sec. cor. of sec. 33, heretofore described. |
| 60.155 | The 1/4 sec. cor. of secs. 32 and 33, heretofore described. |
| | <hr/> <p>From the center-east 1/16 sec. cor. of sec. 33, heretofore described.</p> <p>N. 0° 02' E., on the north and south center line of the northeast quarter of sec. 33.</p> |
| 7.15 | Intersect line 3 - 4, Tract 42, hereinafter described. From this point of intersection Angle Point No. 3, Tract 42, bears S. 84° 50.5' W., 20.16 chs. distant. |
| | Thence, on a blank line across Tract 42. |
| 22.365 | Intersect line 1 - 2, Tract 42, hereinafter described. From this point of intersection Angle Point No. 1, Tract 42, bears N. 84° 50.5' E., 20.155 chs. distant. |
| 40.02 | The east 1/16 sec. cor. of secs. 28 and 33. heretofore described. |
| | Discontinue the regular order of survey at this corner. |
| | <hr/> <p>From the center-south 1/16 sec. cor. of sec. 33, heretofore described.</p> <p>N. 89° 53' W., on the east and west center line of the southwest quarter of sec. 33.</p> |
| 40.085 | The south 1/16 sec. cor. of secs. 32 and 33, heretofore described. |
| | <hr/> <p>Thence, in section 34.</p> <p>From the center-west 1/16 sec. cor. of sec. 34, heretofore described.</p> <p>N. 0° 03' E., on the north and south center line of the northwest quarter of sec. 34.</p> |

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 19 West
 Gila and Salt River Meridian, Arizona



57

| CHAINS | |
|--------|--|
| 10.865 | <p>The point for Angle Point No. 6, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 41 AP 6 L 9 S 34</p> <p style="text-align: center;">1969</p> |
| 20.00 | <p>Intersect the east and west center line of the northwest quarter, the point for the northwest 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">NW 1/16 S 34</p> <p style="text-align: center;">1969</p> |
| 26.075 | <p>Intersect line 2 - 3, Tract 41, hereinafter described. From this point of intersection Angle Point No. 3, Tract 41, bears S. 84° 50.5' W., 20.12 chs. distant.</p> |
| 40.00 | <p>The west 1/16 sec. cor. of secs. 27 and 34, heretofore described.</p> <hr/> <p>From the center-north 1/16 sec. cor. of sec. 34, heretofore described.</p> <p>N. 89° 53' W., on the east and west center line of the northwest quarter of sec. 34, on a blank line across Tract 41.</p> |
| 20.06 | <p>Intersect the north and south center line of the northwest quarter, the northwest 1/16 sec. cor. of sec. 34, heretofore described.</p> |
| 40.11 | <p>The north 1/16 sec. cor. of secs. 33 and 34, heretofore described.</p> <hr/> <p>Thence, with the metes-and-bounds survey of lot 8, section 35</p> <p>From the corner of secs. 25, 26, 35, and 36, heretofore described, which is designated to function for Corner No. 1, lot 8, section 35.</p> <p>N. 89° 54.5' W., on line 1 - 2, lot 8 of sec. 35, which is identical with the section line between secs. 26 and 35.</p> |

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| 20.065 | The east 1/16 sec. cor. of secs. 26 and 35, heretofore described. |
| 36.91 | Corner No. 2, lot 8 of sec. 35, which is identical with Angle Point No. 4, Tract 39, and Angle Point No. 1, Tract 40, heretofore described. |
| | _____ |
| | S. 58° 38' W., on line 2 - 3, lot 8 of sec. 35, which is identical with line 1 - 8, Tract 40. |
| 3.76 | Corner No. 3, lot 8 of sec. 35, which is identical with Angle Point No. 8, Tract 40, heretofore described. |
| | _____ |
| | S. 0° 02' E., on line 3 - 4, lot 8 of sec. 35, which is identical with line 8 - 7, Tract 40, and on the north and south center line of sec. 35. |
| 1.145 | Angle Point No. 7, Tract 40, heretofore described. |
| | Continue with course and measurement of line 3 - 4, lot 8 of sec. 35, which is identical with the north and south center line of sec. 35. |
| 3.395 | Corner No. 4, lot 8 of sec. 35, heretofore described. |
| | _____ |
| | N. 69° 02' E., on line 4 - 5, lot 8 of sec. 35. |
| 5.20 | The point for Corner No. 5, lot 8 of sec. 35. |
| | Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd. |
| | <p style="text-align: center;">T8S R19W S 35 L 8 / L 10 C 5</p> <p style="text-align: center;">1969</p> |
| | There are no suitable accessories nor locations available for reference monuments. |
| | _____ |
| | N. 88° 52' E., on line 5 - 6, lot 8 of sec. 35. |
| 35.28 | Corner No. 6, lot 8 of sec. 35, heretofore described. |
| | _____ |
| | N. 0° 01' W., on line 6 - 1, lot 8 of sec. 35, which is identical with the section line between secs. 35 and 36. |
| 2.73 | The corner of secs. 25, 26, 35, and 36, which is designated to function for Corner No. 1, lot 8 of sec. 35, and the place of beginning. |
| | _____ |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|--|
| | <p>Thence, with the survey of Tract 37</p> <p>Beginning at Angle Point No. 1, Tract 37, heretofore described, and is located on the section line between secs. 31 and 32.</p> <p>S. 52° 38' W., on line 1 - 2, Tract 37.</p> |
| 20.46 | <p>The point for Angle Point No. 2, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W S 31</p>  <p>AP 2 TR 37</p> <p>1969</p> </div> |
| | <p>Thence, on line 2 - 3, Tract 37, along the arc of a curve, curve data:</p> <p>Chord bears S. 70° 02.5' W. Chord length 40.875 chs. distant Radius 68.285 chs. distant Length of arc 41.51 chs. distant</p> <p>At 13.67 chs. distant on the arc of the curve. Intersect the east and west center line of sec. 31, heretofore described.</p> <p>At 26.59 chs. distant on the arc of the curve. Intersect the north and south center line of sec. 31, heretofore described.</p> <p>At the end of the arc of the curve. The point for Angle Point No. 3, Tract 37</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W S 31</p>  <p>AP 3 TR 37</p> <p>1969</p> </div> |
| | <p>S. 87° 27.5' W., on line 3 - 4 Tract 37.</p> |
| 21.735 | <p>Angle Point No. 4, Tract 37, heretofore described.</p> |
| | <p>S. 0° 01' W., on line 4 - 5, Tract 37, which is identical with the west boundary of the township.</p> |
| 12.195 | <p>The south 1/16 sec. cor. of secs. 31 and 36, heretofore described.</p> |

60

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

15.165 Angle Point No. 5, Tract 37, heretofore described.

N. 87° 27.5' E., on line 5 - 6, Tract 37.

22.41 The point for Angle Point No. 6, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W

TR 37

AP 6

S 31

1969

Thence, on line 6 - 7, Tract 37, along the arc of a curve, curve data:

Chord bears N. 81° 58' E.
Chord length 16.00 chs. distant
Radius 83.44 chs. distant
Length of arc 16.02 chs. distant

At 14.22 chs. distant on the arc of the curve. Intersect the north and south center line of sec. 31, heretofore described.

At the end of the arc of the curve. The point for Angle Point No. 7, Tract 37.

Set an iron post 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W

TR 37

AP 7

S 31

1969

Thence, on line 7 - 8, Tract 37, along the arc of a curve, curve data:

Chord bears S. 37° 14.5' E.
Chord length 18.45 chs. distant
Radius 15.22 chs. distant
Length of arc 19.825 chs. distant

At the end of the arc of the curve. The point for Angle Point No. 8, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

61

CHAINS

T8S R19W
TR 37
S 31 } AP 8
1969

S. $0^{\circ} 04.5'$ W., on line 8 - 9, Tract 37.

5.65 Angle Point No. 9, Tract 37, heretofore described.

S. $89^{\circ} 55.5'$ E., on line 9 - 10, Tract 37, which is identical with the south boundary of sec. 31.

10.61 Angle Point No. 10, Tract 37, heretofore described.

N. $0^{\circ} 04.5'$ E., on line 10 - 11, Tract 37.

5.65 The point for Angle Point No. 11, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 37 } AP 11 } S 31
1969

Thence, on line 11 - 12, Tract 37, along the arc of a curve, curve data:

Chord bears N. $23^{\circ} 48.5'$ W.
Chord length 20.91 chs. distant
Radius 25.825 chs. distant
Length of arc 21.53 chs. distant

At the end of the arc of the curve. The point for Angle Point No. 12, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 37 } AP 12 } S 31
1969

Thence, on line 12 - 13, Tract 37, along the arc of a curve, curve data:


Chord bears N. $59^{\circ} 42.5'$ E.
Chord length 20.575 chs. distant
Radius 83.44 chs. distant
Length of arc 20.63 chs. distant

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

CHAINS

At the end of the arc of the curve. The point for Angle Point No. 13, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



1969

N. 52° 38' E., on line 13 - 14, Tract 37.

7.985 Intersect the east and west center line of sec. 31, Angle Point No. 14, Tract 37, heretofore described.

S. 89° 54.5' E., on line 14 - 15, Tract 37, which is identical with the east and west center line of sec. 31.

0.735 The 1/4 sec. cor. of secs. 31 and 32, heretofore described, which is designated to function for Angle Point No. 15, Tract 37.

N. 0° 02' W., on line 15 - 1, Tract 37, which is identical with the section line between secs. 31 and 32.

19.62 Angle Point No. 1, Tract 37, and the place of beginning.

Thence, with the survey of Tract 38

Beginning at Angle Point No. 1, Tract 38, heretofore described.

S. 58° 38' W., on line 1 - 2, Tract 38.

6.195 Intersect the north and south center line of the northeast quarter of sec. 25, heretofore described.

29.53 Intersect the north and south center line of sec. 25, heretofore described.

76.265 Angle Point No. 2, Tract 38, which is identical with Angle Point No. 1, Tract 39, heretofore described.

S. 0° 03' E., on line 2 - 3, Tract 38, which is identical with line 1 - 5, Tract 39, and is identical with the section line between secs. 25 and 26.

0.335 The 1/4 sec. cor. of secs. 25 and 26, heretofore described.

17.735 Angle Point No. 3, Tract 38, which is identical with Angle Point No. 5, Tract 39, heretofore described.

N. 58° 38' E., on line 3 - 4, Tract 38.

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

63

| CHAINS | | |
|--------|---|--|
| 23.345 | Intersect the north and south center line of the southwest quarter of sec. 25, heretofore described. | |
| 33.47 | Intersect the east and west center line of sec. 25, heretofore described. | |
| 46.685 | Intersect the north and south center line of sec. 25, heretofore described. | |
| 70.085 | Intersect the north and south center line of the northeast quarter of sec. 25, heretofore described. | |
| 71.88 | Intersect the east and west center line of the northeast quarter of sec. 25, heretofore described. | |
| 92.85 | Angle Point No. 4, Tract 38, which is identical with Corner No. 4, Parcel A and Corner No. 3, Parcel B of sec. 30, T. 8 S., R. 18 W., and is monumented with an iron post, 2 1/2 ins. in diam., set and marked as described in the field-note record of the dependent resurvey of a portion of the west boundary of T. 8 S., R. 18 W., executed concurrently with this group. | |
| | <hr/> N. 0° 18.5' W., on line 4 - 5, Tract 38, which is identical with line 3 - 2, Parcel B of sec. 30, T. 8 S., R. 18 W., and is the east boundary of the township. | |
| 9.205 | The corner of secs. 19, 24, 25, and 30 on the east boundary of the township, heretofore described, which is designated to function for Angle Point No. 5, Tract 38, of this township, Corner No. 2, Parcel B of sec. 30 and Angle Point No. 5, Tract 43 of T. 8 S., R. 18 W. | |
| | <hr/> S. 89° 34' W., on line 5 - 1, Tract 38, which is identical with the section line between secs. 24 and 25. | |
| 14.135 | Angle Point No. 1, Tract 38, and the place of beginning. | |
| | <hr/> Thence, with the survey of Tract 39 Beginning at Angle Point No. 1, Tract 39, which is identical with Angle Point No. 2, Tract 38, heretofore described. S. 58° 38' W., on line 1 - 2, Tract 39. | |
| 0.645 | Intersect the east and west center line of sec. 26, heretofore described. | |
| 23.465 | Intersect the north and south center line of the southeast quarter of sec. 26, heretofore described. | |
| 46.925 | Intersect the north and south center line of sec. 26, heretofore described. | |
| 59.51 | The point for Angle Point No. 2, Tract 39 Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. | |

64

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|---|--|
| | <p>T8S R19W S 26 AP 2 TR 39 1969</p> | |
| | S. 62° 36' W., on line 2 - 3, Tract 39. | |
| 19.955 | Angle Point No. 3, Tract 39, which is identical with Angle Point No. 2, Tract 40, heretofore described. | |
| | S. 89° 54.5' E., on line 3 - 4, Tract 39, which is identical with line 2 - 1, Tract 40, and is identical with the section line between secs. 26 and 35. | |
| 8.42 | The west 1/16 sec. cor of secs. 26 and 35, heretofore described. | |
| 28.465 | The 1/4 sec. cor. of secs. 26 and 35, heretofore described. | |
| 31.675 | Angle Point No. 4, Tract 39, which is identical with Angle Point No. 1, Tract 40, and Corner No. 2, lot 8 of sec. 35, heretofore described. | |
| | N. 58° 38' E., on line 4 - 5, Tract 39. | |
| 19.725 | Intersect the north and south center line of the southeast quarter of sec. 26, heretofore described. | |
| 43.21 | Angle Point No. 5, Tract 39, which is identical with Angle Point No. 3, Tract 38, heretofore described. | |
| | N. 0° 03' W., on line 5 - 1, Tract 39, which is identical with line 3 - 2, Tract 38, and is identical with the section line between secs. 25 and 26. | |
| 17.40 | The 1/4 sec. cor of secs. 25 and 26, heretofore described. | |
| 17.735 | Angle Point No. 1, Tract 39, which is identical with Angle Point No. 2, Tract 38, and the place of beginning. | |
| | Thence, with the survey of Tract 40 | |
| | Beginning at Angle Point No. 1, Tract 40, which is identical with Angle Point No. 4, Tract 39 and Corner No. 2, lot 8 of sec. 35, heretofore described. | |
| | N. 89° 54.5' W., on line 1 - 2, Tract 40, which is identical with line 4 - 3, Tract 39, and is identical with the section line between secs. 26 and 35. | |
| 3.21 | The 1/4 sec. cor. of secs. 26 and 35, heretofore described. | |
| 23.255 | The west 1/16 sec. cor. of secs. 26 and 35, heretofore described. | |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona


65

| CHAINS | | |
|--------|---|--|
| 31.675 | <p>Angle Point No. 2, Tract 40, which is identical with Angle Point No. 3, Tract 39, heretofore described.</p> <hr/> <p>Thence, on line 2 - 3, Tract 40, along the arc of a curve, curve data:</p> <p>Chord bears S. 69° 03' W. Chord length 12.46 chs. distant Radius 144.155 chs. distant Length of arc 12.465 chs. distant</p> <p>At the end of the arc of the curve. Angle Point No. 3, Tract 40, which is identical with Angle Point No. 1, Tract 41, heretofore described.</p> <hr/> <p>SOUTH, on line 3 - 4, Tract 40, which is identical with line 1 - 8, Tract 41, and is identical with the section line between secs. 34 and 35.</p> | |
| 15.515 | <p>The north 1/16 sec. cor. of secs. 34 and 35, heretofore described.</p> | |
| 15.895 | <p>Angle Point No. 4, Tract 40, which is identical with Angle Point No. 8, Tract 41, heretofore described.</p> <hr/> <p>Thence, on line 4 - 5, Tract 40, along the arc of a curve, curve data:</p> <p>Chord bears N. 66° 04' E. Chord length 40.325 chs. distant Radius 159.31 chs. distant Length of arc 40.435 chs. distant</p> <p>At 1.60 chs. distant on the arc of the curve. Intersect the east and west center line of the northwest quarter of sec. 35, heretofore described.</p> <p>At 21.40 chs. distant on the arc of the curve. Intersect the north and south center line of the northwest quarter of sec. 35, heretofore described.</p> <p>At the end of the arc of the curve. The point for Angle Point No. 5, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins., in the ground with brass cap mkd.</p> <div data-bbox="852 1948 1047 2110" style="text-align: center;"> <p>T8S R19W TR 40 AP 5 X S 35 1969</p> <hr/> </div> <p>N. 58° 38' W., on line 5 - 6, Tract 40.</p> | |
| 1.61 | <p>The point for Angle Point No. 6, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> | |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

66

CHAINS



S. 89° 54.5' E., on line 6 - 7, Tract 40.

- 1.87 Intersect the north and south center line of sec. 35.
Angle Point No. 7, Tract 40, heretofore described.

N. 0° 02' W., on line 7 - 8, Tract 40, which is identical
with the north and south center line of sec. 35.

- 1.145 Angle Point No. 8, Tract 40, which is identical with
Corner No. 3, lot 8 of sec. 35, heretofore described.

N. 58° 38' E., on line 8 - 1, Tract 40, which is identi-
cal with line 3 - 2, lot 8 of sec. 35.

- 3.76 Angle Point No. 1, Tract 40, which is identical with
Angle Point No. 4, Tract 39 and Corner No. 2, lot 8 of
sec. 35, and the place of beginning.

Thence, with the survey of Tract 41


Beginning at Angle Point No. 1, Tract 41, which is iden-
tical with Angle Point No. 3, Tract 40, heretofore de-
scribed.

Thence, on line 1 - 2, Tract 41, along the arc of a
curve, curve data:

Chord bears S. 78° 10.5' W.
Chord length 33.435 chs. distant
Radius 144.155 chs. distant
Length of arc 33.51 chs. distant

At the end of the arc of the curve. The point for Angle
Point No. 2, Tract 41.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23
ins. in the ground, with brass cap mkd.



1969

S. 84° 50.5' W., on line 2 - 3, Tract 41

- 7.375 Intersect the north and south center line of sec. 34,
heretofore described.

- 27.53 Intersect the north and south center line of the north-
west quarter of sec. 34, heretofore described.

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

67

| CHAINS | |
|--------|---|
| 47.65 | <p>Angle Point No. 3, Tract 41, which is identical with Angle Point No. 1, Tract 42, heretofore described.</p> <hr/> <p>S. 0° 03' W., on line 3 - 4, Tract 41, which is identical with line 1 - 4, Tract 42, and is identical with the section line between secs. 33 and 34.</p> |
| 4.235 | <p>The north 1/16 sec. cor. of secs. 33 and 34, heretofore described, which is designated to function for Angle Point No. 4, Tract 41.</p> <hr/> <p>S. 89° 53' E., on line 4 - 5, Tract 41, which is identical with the east and west center line of the northwest quarter of sec. 34.</p> |
| 20.05 | <p>The northwest 1/16 sec. cor. of sec. 34, heretofore described, which is designated to function for Angle Point No. 5, Tract 41.</p> <hr/> <p>S. 0° 03' W., on line 5 - 6, Tract 41, which is identical with the north and south center line of the northwest quarter of sec. 34.</p> |
| 9.135 | <p>Angle Point No. 6, Tract 41, heretofore described.</p> <hr/> <p>N. 84° 50.5' E., on line 6 - 7, Tract 41.</p> |
| 20.15 | <p>Intersect the north and south center line of sec. 34, heretofore described.</p> |
| 28.90 | <p>The point for Angle Point No. 7, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W TR 41 AP 7 + S 34</p> </div> <p>1969</p> <hr/> <p>Thence, on line 7 - 8, Tract 41, along the arc of a curve, curve data:</p> <p>Chord bears N. 79° 05' E. Chord length 31.94 chs. distant Radius 159.31 chs. distant Length of arc 31.995 chs. distant</p> <p>At the end of the arc of the curve. Angle Point No. 8. Tract 41, which is identical with Angle Point No. 4, Tract 40, heretofore described.</p> <hr/> <p>NORTH, on line 8 - 1, Tract 41, which is identical with line 4 - 3, Tract 40, and is identical with the section line between secs. 34 and 35.</p> |
| 0.38 | <p>The north 1/16 sec. cor. of secs. 34 and 35, heretofore described.</p> |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|--|--|
| 15.895 | Angle Point No. 1, Tract 41, which is identical with Angle Point No. 3, Tract 40, and the place of beginning. | |
| | <p>Thence, with the survey of Tract 42</p> <p>Beginning at Angle Point No. 1, Tract 42, which is identical with Angle Point No. 3, Tract 41, heretofore described.</p> <p>S. 84° 50.5' W., on line 1 - 2, Tract 42.</p> | |
| 20.155 | Intersect the north and south center line of the northeast quarter of sec. 33, heretofore described. | |
| 40.32 | Intersect the north and south center line of sec. 33, Angle Point No. 2, Tract 42, heretofore described. | |
| | <p>S. 0° 01.5' W., on line 2 - 3, Tract 42, which is identical with the north and south center line of sec. 33.</p> | |
| 15.215 | Angle Point No. 3, Tract 42, heretofore described. | |
| 20.16 | Intersect the north and south center line of the northeast quarter of sec. 33, heretofore described. | |
| 40.315 | Angle Point No. 4, Tract 42, heretofore described. | |
| | <p>N. 0° 03' E., on line 4 - 1, Tract 42, which is identical with the section line between secs. 33 and 34.</p> | |
| 10.98 | <p>The north 1/16 sec. cor. of secs. 33 and 34, which is designated to function for Angle Point No. 4, Tract 41, heretofore described.</p> <p>Continue with course and measurement on line 4 - 1, Tract 42, which is identical with line 4 - 3, Tract 41.</p> | |
| 15.215 | Angle Point No. 1, Tract 42, which is identical with Angle Point No. 3, Tract 41, and the place of beginning. | |
| | <p>Thence, with the survey of Tract 43</p> <p>Beginning at the corner of secs. 29, 30, 31, and 32, which is designated to function for Angle Point No. 1, Tract 43.</p> <p>N. 89° 55' W., on line 1 - 2, Tract 43, which is identical with the section line between secs. 30 and 31.</p> | |
| 20.01 | The east 1/16 sec. cor. of secs. 30 and 31. | |
| 40.02 | The 1/4 sec. cor. of secs. 30 and 31. | |
| 76.35 | The cor. of secs. 25, 30, 31, and 36 on the west boundary of the township; which is designated to function for Angle Point No. 2, Tract 43. | |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | | |
|--------|---|--|
| | <p>S. 0° 01' W., on line 2 - 3, Tract 43, which is identical with the west boundary of the township.</p> | |
| 20.01 | The north 1/16 sec. cor. of secs. 31 and 36. | |
| 30.885 | <p>Angle Point No. 3, Tract 43.</p> <hr/> <p>N. 83° 40.5' E., on line 3 - 4, Tract 43.</p> | |
| 9.40 | <p>The point for Angle Point No. 4, Tract 43.</p> <p>Set an iron post 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 43 AP 4 S 31</p> <p style="text-align: center;">1981</p> <hr/> | |
| 12.425 | <p>N. 72° 25.5' E., on line 4 - 5, Tract 43.</p> <p>The point for Angle Point No. 5, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 43 AP 5 S 31</p> <p style="text-align: center;">1981</p> <hr/> | |
| 3.03 | <p>S. 87° 23.5' E., on line 5 - 6, Tract 43.</p> <p>The point for Angle Point No. 6, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 43 AP 6 S 31</p> <p style="text-align: center;">1981</p> <hr/> | |
| 5.305 | <p>S. 82° 06' E., on line 6 - 7, Tract 43.</p> <p>The point for Angle Point No. 7, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R19W TR 43 AP 7 S 31</p> <p style="text-align: center;">1981</p> <hr/> | |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

70

CHAINS

S. 76° 18' E., on line 7 - 8, Tract 43.

7.145 Intersect the north and south center line of sec. 31, heretofore described; from this point of intersection the center-north 1/16 sec. cor. of sec. 31 bears N. 0° 03.5' W., 8.60 chs. distant.

7.425 The point for Angle Point No. 8, Tract 43.

Set an iron post 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 43
AP 8

1981

S. 88° 34.5' E., on line 8 - 9, Tract 43.

1.365 The point for Angle Point No. 9, Tract 43.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 43
AP 9
S 31

1981

N. 67° 53.5' E., on line 9 - 10, Tract 43.

5.755 The point for Angle Point No. 10, Tract 43.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 43
AP 10
S 31

1981

N. 76° 53.5' E., on line 10 - 11, Tract 43.

6.29 The point for Angle Point No. 11, Tract 43.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R19W
TR 43
AP 11
S 31

1981


The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

71

| CHAINS | | |
|--------|---|--|
| | <p>N. 37° 24' E., on line 11 - 12, Tract 43.</p> | |
| 5.045 | <p>The point for Angle Point No. 12, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W TR 43 AP 12 S 31 / 1981</p> </div> | |
| | <p>N. 0° 02.5' W., on line 12 - 13, Tract 43</p> | |
| 1.435 | <p>The point for Angle Point No. 3, Tract 44</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W TR 44 AP 3 TR 43 S 31 1981</p> </div> | |
| | <p>Continue on line 12 - 13, Tract 43, which is now identical with line 3 - 2, Tract 44.</p> | |
| 6.815 | <p>The point for Angle Point No. 13, Tract 43 and Angle Point No. 2, Tract 44.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R19W AP 13 AP 2 TR 43 TR 44 1981</p> </div> | |
| | <p>S. 89° 54' E., on line 13 - 14, Tract 43, which is identical with line 2 - 1, Tract 44.</p> | |
| 23.805 | <p>Angle Point No. 14, Tract 43, which is identical with Angle Point No. 1, Tract 44.</p> | |
| | <p>N. 0° 02' W., on line 14 - 1, Tract 43, which is identical with the section line between secs. 31 and 32.</p> | |
| 14.265 | <p>The corner of secs. 29, 30, 31, and 32, which is designated to function for Angle Point No. 1, Tract 43, and the place of beginning.</p> | |
| | <p>Thence, with the survey of Tract 44</p> | |

72

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona

| CHAINS | |
|--------|---|
| | Beginning at Angle Point No. 1, Tract 44, which is identical with Angle Point No. 14, Tract 43. |
| | N. 89° 54' W., on line 1 - 2, Tract 44, which is identical with line 14 - 13, Tract 43. |
| 23.805 | Angle Point No. 2, Tract 44, which is identical with Angle Point No. 13, Tract 43. |
| | S. 0° 02.5' E., on line 2 - 3, Tract 44, which is identical with a portion of line 13 - 12, Tract 43. |
| 5.38 | Angle Point No. 3, Tract 44. |
| 23.805 | S. 89° 54' E., on line 3 - 4, Tract 44. |
| | Angle Point No. 4, Tract 44. |
| 5.38 | N. 0° 02' W., on line 4 - 1, Tract 44, which is identical with the section line between secs. 31 and 32. |
| | Angle Point No. 1, Tract 44, which is identical with Angle Point No. 14, Tract 43, and the place of beginning. |
| | Thence, with the survey of Tract 45 |
| | Beginning at Angle Point No. 1, Tract 45. |
| 16.09 | SOUTH, on line 1 - 2, Tract 45, which is identical with the section line between sections 32 and 33. |
| | The corner of secs. 32 and 33 on the south boundary of the township, which is designated to function for Angle Point No. 2, Tract 45. |
| 3.66 | S. 89° 53' E., on line 2 - 3, Tract 45, which is identical with the south boundary of the township. |
| | The closing corner of secs. 4 and 5, T. 9 S., R. 19 W., heretofore described. |
| 17.425 | Angle Point No. 3, Tract 45. |
| | NORTH, on line 3 - 4, Tract 45. |
| 15.08 | The point for Angle Point No. 4, Tract 45. |
| | Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd. |
| | <p style="text-align: center;">T8S R19W  AP 4 TR 45</p> |
| | 1981 |

The Metes-and-Bounds Survey of Tracts
37 through 45 inclusive
Township 8 South, Range 19 West
Gila and Salt River Meridian, Arizona


73

CHAINS

N. 53° 05' W., on line 4 - 5, Tract 45.

1.70 The point for Angle Point No. 5, Tract 45.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.



1981

N. 89° 53' W., on line 5 - 1, Tract 45.

16.06 Angle Point No. 1, Tract 45, and the place of beginning.

GENERAL DESCRIPTION

The land area within these surveys is nearly level with the exception of the northern portions of sections 25, 26, 33 and 34, which is rolling desert land. Drainage is southwest to west. The soil consists of sandy loam on the bottom land, sandy and rocky on the rolling land area. The land area is mostly under cultivation, with the exception of the federally controlled lands, which are undeveloped; with French tamarisk, mesquite, and paloverde trees; undergrowth young trees, cacti, arrowweed and creosote brush (shrub).

Improvements located throughout the area are: The Wellton-Mohawk Channel, Coyote Wash Channel (a controlled drainage canal), numerous canals and laterals for irrigation and/or drainage purposes; Yuma County and farm roads.

CHAINS

Form 9600-11
(August 1979)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS




| NAMES | CAPACITY |
|-----------------------|--------------------|
| Marvin T. Koppang | Cadastral Surveyor |
| Kermit L. Duke | Surveying Aid |
| Stephen Jaramillo | Surveying Aid |
| Manuel G. Jaramillo | Surveying Aid |
| Ernest E. Hurtado | Surveying Aid |
| Dale E. Phillips | Surveying Aid |
| Fordner VanFleet, Jr. | Surveying Aid |
| William A. Weiderman | Surveying Aid |
| George R. Vaughan | Surveying Aid |
| Thomas E. Casinger | Cadastral Surveyor |
| Regina R. Lefort | Cadastral Surveyor |
| Kevin J. Curtis | Surveying Aid |
| Barbara L. Heth | Surveying Aid |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |

CERTIFICATE OF SURVEY

~~XX~~ (We), Ray Harpin, Douglas A. Cody and Paul J. Fisher , HEREBY

CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of October , 1969 , ~~XXXXXX~~ Supplemental Special Instructions dated November 20, 1969, September 5, 1979 and October 20, 1980, (We) have dependently resurveyed a portion of the south and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision lines within a number of sections; surveyed a portion of the subdivision lines within a number of sections, the metes-and-bounds survey of lot 8 of section 35, and the metes-and-bounds survey of Tracts 37 through 45 inclusive, Township 8 South, Range 19 West,

of the Gila and Salt River Meridian, in the State of Arizona , which are represented in the foregoing field notes as having been executed by ~~XX~~, (us) and under ~~XXXX~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.


| | |
|---------------|--|
| June 30, 1981 |  |
| (Date) | (Cadastral Surveyor) |
| June 30, 1981 |  |
| (Date) | (Cadastral Surveyor) |
| June 30, 1981 |  |
| (Date) | (Cadastral Surveyor) |

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the south and west boundaries, a portion of the subdivisional lines, and a portion of the subdivision lines within a number of sections; the survey of a portion of the subdivision lines within a number of sections, the metes-and-bounds survey of lot 8 of section 35, and the metes-and-bounds survey of Tracts 37 through 45 inclusive, Township 8 South, Range 19 West, of the Gila and Salt River Meridian, Arizona

executed by Ray Harpin, Douglas A. Cody and Paul J. Fisher, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

| | |
|-------------|--|
| NOV 23 1981 |  |
| (Date) | ACTING (Chief, Cadastral Survey Examination and Approval Staff) |

CERTIFICATE OF TRANSCRIPT

~~I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.~~

| | |
|--------|--|
| | |
| (Date) | (Chief, Cadastral Survey Examination and Approval Staff) |