

R 5161

BOOK 5162

01

FIELD NOTES

OF THE

DEPENDENT RESURVEY OF A PORTION OF THE NORTH BOUNDARY,

A PORTION OF THE SUBDIVISIONAL LINES,

AND

A PORTION OF THE SUBDIVISION LINES

WITHIN A NUMBER OF SECTIONS;

THE SURVEY OF A PORTION OF THE SUBDIVISION LINES

WITHIN A NUMBER OF SECTIONS,

AND

THE METES-AND-BOUNDS SURVEY OF TRACTS 37 THROUGH 49 INCLUSIVE,

TOWNSHIP 8 SOUTH, RANGE 20 WEST

Of the GILA AND SALT RIVER Meridian,

In the State of ARIZONA

EXECUTED BY

RAY HARPIN

CADASTRAL SURVEYOR

DOUGLAS A. CODY

CADASTRAL SURVEYOR

PAUL J. FISHER

CADASTRAL SURVEYOR

Under special instructions dated OCTOBER 14, 19 69, approved OCTOBER 27, 1969,

SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED NOVEMBER 20, 1969, APPROVED NOVEMBER 21, 1969, SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED SEPTEMBER 5, 1979, APPROVED SEPTEMBER 13, 1979, AND SUPPLEMENTAL SPECIAL INSTRUCTIONS DATED OCTOBER 20, 1980, APPROVED OCTOBER 27, 1980

, which provided for the surveys included under ~~XXXX SURVEY~~ Group Number 517, and assignment instructions dated OCTOBER 14, 1969.

AND OCTOBER 14, 1980

Survey commenced FEBRUARY 26, 19 70

Survey completed MARCH 23, 19 81

INDEX DIAGRAM

Township 8 SOUTH, Range 20 WEST,
2

6 30 27	5 26	4	3	2	1
7 24	8 22	9	10	11	12
18	17 20	16	15	14	13
19	20 16	21 13 14	22 12	23	24
30	29	28 10	27 8	26 8	25
31	32	33	34 6	35 4	36

Dependent Resurvey
of Subdivision Lines

Section 6 . . . p. 32
 Section 17 . . . p. 40
 Section 21 . . . p. 42

Survey of Subdivision
Lines

Section 5 . . . p. 56
 Section 6 . . . p. 57
 Section 8 . . . p. 58
 Section 17 . . . p. 63
 Section 21 . . . p. 64
 Section 27 . . . p. 64
 Section 34 . . . p. 68

Metes-and-Bounds
Survey of Tracts

Tract 37 . . . p. 71
 Tract 38 . . . p. 73
 Tract 39 . . . p. 75
 Tract 40 . . . p. 76
 Tract 41 . . . p. 79
 Tract 42 . . . p. 81
 Tract 43 . . . p. 81
 Tract 44 . . . p. 84
 Tract 45 . . . p. 85
 Tract 46 . . . p. 87
 Tract 47 . . . p. 88
 Tract 48 . . . p. 90
 Tract 49 . . . p. 91

Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and a portion of the subdivision lines within a number of sections; the survey of a portion of the subdivision lines within a number of sections, and the metes-and-bounds survey of Tracts 37 through 49 inclusive, Township 8 South, Range 20 West, of the Gila and Salt River Meridian, Arizona.

History of Previous Surveys: The east boundary was originally surveyed by Sidney E. Blout, U. S. Surveyor, in 1912. A portion of the east and west boundaries were resurveyed, a portion of the west boundary, the south and north boundaries, and a portion of the subdivisional lines were surveyed by William B. Kimmel, U. S. Surveyor, in 1915 and 1916, as shown upon the official plat examined and approved, March, 20, 1918. A portion of the exterior boundaries of sections 6, 7, and 17 was dependently resurveyed and a portion of the subdivision lines within those sections was surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Assistant Commissioner, Bureau of Reclamation, Washington, D. C., March 17, 1955; and was accepted by the Cadastral Engineering Officer, Bureau of Land Management, March 17, 1955. A portion of the exterior boundaries of sections 20 and 21 was dependently resurveyed and a portion of the subdivision lines within those sections was surveyed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954, as shown upon the official plat, examined and approved by the Assistant Commissioner, Bureau of Reclamation, Washington, D. C., March 17, 1955; and was accepted by the Cadastral Engineering Officer, Bureau of Land Management, March 17, 1955. A portion of the west boundary was dependently resurveyed as the east boundary of Tp. 8 S., R. 21 W., executed by Phil D. Smith, Cadastral Surveyor, in 1957, and Paul G. Bauer, Surveying Technician, in 1962, as shown upon the official plat of the above township, accepted May 9, 1962. A portion of the west boundary of the township was dependently resurveyed as described in the official field-note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this group.

These dependent resurveys and surveys were executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947 and 1973 Editions, and the Special Instructions for Group No. 517, Arizona, dated October 14, 1969, the Supplemental Special Instructions dated November 20, 1969, and Supplemental Special Instructions dated September 5, 1979, and Supplemental Special Instructions dated October 20, 1980.

The direction of all lines of these surveys was determined from direct altitude observations on the sun for azimuth, and these directions refer to the true meridian. The lines were carried forward by normal transit traverse. Distances are expressed in chains, reduced to horizontal equivalents.

Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

Preliminary to the resurvey the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions; lost corners were restored and monumented at proportionate positions based on the original record. The retracement data were thoroughly verified and only the true line field notes are given herein.

The geographic position of the corner of secs. 1, 2, 35, and 36 on the south boundary of the township as determined by scaling from an U. S. Geological Survey Quadrangle Map, "Ligurta, Arizona, 1965", is as follows: Latitude 32° 40.7' N. and Longitude 114° 16.7' W. The mean magnetic declination is 14° East.

Dependent Resurvey of a Portion
of the North Boundary
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

Restoring the Resurvey Executed
by Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

The corner of secs. 5, 6, 31, and 32 is monumented with an iron post, 3 ins. in diam., with regulation General Land Office brass cap, 12 ins. below the surface of the road, mkd.

T7S R20W
S 31 | S 32
S 6 | S 5
T8S

1916

S. 89° 51.5' W., between Tps. 7 and 8 S., through R. 20 W., and between secs. 6 and 31.

19.935

The east 1/16 sec. cor. of secs. 6 and 31 is marked with an iron pipe, 1-inch in diam., with brass cap 7 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION
E 1/16
S 31
S 6

1954

S. 89° 51.5' W., beginning new measurement.

Dependent Resurvey of a Portion
of the North Boundary
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

05

CHAINS
19.935

The 1/4 sec. cor. of secs. 6 and 31 is marked with an iron pipe, 1-inch in diam., with brass cap 15 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

1/4
S 31
S 6

1949

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

S. 89° 51.5' W., beginning new measurement.

10.295

The closing corner of secs. 6 and 31 on the west boundary of the township, is marked with an iron pipe, 2 ins. in diam., with brass cap 20 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

T8S | T7S
S 1 | R20W
| S 31
| S 6
R21W | T8S

1939

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

This corner is located at the intersection of roads, bearing north and south, and east.

From this same corner, the east 1/4 sec. cor. of sec. 1, Tp. 8 S., R. 21 W., bears S. 0° 05' E., 2.00 chs. distant, and is marked with an iron pipe, 1-inch in diam., with brass cap 20 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

1/4 |
|
S 1 |
|

1952

The above corner marker was accepted and described in the official field-note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this group.

66

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p>Restoring the Survey Executed By William B. Kimmel, U. S. Surveyor in 1915 and 1916</p> <hr/> <p>The corner of secs. 1, 2, 35, and 36 on the south boundary of the township, which is monumented with an iron post, 3 ins. in diam., firmly set, projecting 15 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> <p style="text-align: center;"> T8S R20W S 35 S 36 S 2 S 1 T9S 1915 </p> <hr/> <p>N. 0° 01.5' W., between secs. 35 and 36.</p> <p>Over gently rolling land.</p>	
9.15	The south bank of the Wellton-Mohawk Canal, flows S. 61° 00' E.	
10.10	The north bank of the Wellton-Mohawk Canal.	
10.45	Road, bears parallel to the above canal.	
13.07	Point On Section Line station, marked with a concrete post, 4 ins. square, firmly set, projecting 6 ins. above the surface of the ground, with brass tablet, 3 1/4 ins. in diam., mkd.	
	<p>BUREAU OF RECLAMATION ROW POSL 649+51.44 1957</p>	
19.99	The south 1/16 sec. cor. of secs. 35 and 36 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.	
	<p>BUREAU OF RECLAMATION S 1/16 S 35 S 36 1952</p>	
	The above corner marker is accepted as the position of the corner. I did not remonument this corner.	
	<hr/> <p>N. 0° 01.5' W., beginning new measurement.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

07

CHAINS

7.47

The point for Angle Point No. 4, Tract 46.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W
TR 46 |
AP 4 |
S 35 | S 36

1970

19.99

The 1/4 sec. cor. of secs. 35 and 36 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
1/4
|
S 35 | S 36
|

1948

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

N. 0° 01.5' W., beginning new measurement.

3.20

The point for Angle Point No. 1, Tract 46.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W
S 35 |
AP 1 | S 36
TR 46 |

1970

19.98

The north 1/16 sec. cor. of secs. 35 and 36 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
N 1/16
S 35 | S 36

1952

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

08

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 0° 01.5' W., beginning new measurement.
19.99	<p>The point for the corner of secs. 25, 26, 35, and 36 is determined at the intersection of the center line of roads, bearing east and west, and north, and on the projection of the section line from the south. I accept this point as the best available evidence of the position of the original cor.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 26 S 25 S 35 S 36</p> </div> <p style="text-align: center;">1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>The corner of secs. 2, 3, 34, and 35 on the south boundary of the township, which is marked with a steel rod, of undetermined length, 1 1/2 ins. in diam., with the top flush with the surface of the ground, and is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.</p> <hr/> <p>N. 0° 02.5' E., between secs. 34 and 35.</p>
0.12	<p>The center line of the Southern Pacific Railroad, bears N. 41° 30' W. and S. 41° 30' E.</p> <p>Thence, over gently rolling land.</p>
20.10	<p>Enter and continue along the center line of a road from the southeast.</p>
40.01	<p>The point for the 1/4 sec. cor. of secs. 34 and 35 is determined at proportionate distance; there is no evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R20W 1/4 S 34 S 35 </p> </div> <p style="text-align: center;">1970</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

C9

CHAINS	
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
40.95	<p>The south bank of the Wellton-Mohawk Canal, flows S. 71° 40' E.</p>
41.95	<p>The north bank of the Wellton-Mohawk Canal.</p>
49.09	<p>The point for Angle Point No. 5, Tract 45.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">T8S R20W TR 45 AP 5 / S 35 S 34 </p>
	<p style="text-align: center;">1970</p>
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
49.405	<p>The point for Angle Point No. 3, Tract 46.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">T8S R20W TR 46 AP 3 TR 45 / S 35</p>
	<p style="text-align: center;">1970</p>
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
60.015	<p>The point for the north 1/16 sec. cor. of secs. 34 and 35.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">N 1/16 S 34 S 35</p>
	<p style="text-align: center;">1970</p>
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
65.115	<p>The point for Angle Point No. 2, Tract 46.</p>
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p>
	<p style="text-align: center;">T8S R20W S 34 S 35 / AP 2 TR 46</p>
	<p style="text-align: center;">1970</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>There are no suitable accessories nor locations available for reference monuments.</p>
80.02	<p>The corner of secs. 26, 27, 34, and 35 is marked with an iron pipe, 2 ins. in diam, with brass cap 15 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W <u>S 27 S 26</u> <u>S 34 S 35</u></p> <p style="text-align: center;">1948</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <hr/> <p>From the corner of secs. 25, 26, 35 and 36, heretofore described.</p> <p>N. 89° 55' W., between secs. 26 and 35.</p> <p>Over nearly level land, along the center line of a road.</p>
39.925	<p>The point for the 1/4 sec. cor. of secs. 26 and 35 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R20W 1/4 <u>S 26</u> S 35</p> <p style="text-align: center;">1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>
79.85	<p>The corner of secs. 26, 27, 34, and 35, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>S. 89° 58.5' W., between secs. 27 and 34.</p> <p>Over nearly level land, along the center line of a road.</p>
20.03	<p>The east 1/16 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 1-inch in diam., with brass cap 9 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION E 1/16 <u>S 27</u> S 34</p> <p style="text-align: center;">1950</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
10.605	<p>The above corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <hr/> <p>S. 89° 58.5' W., beginning new measurement.</p> <p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 5, Tract 44 and Angle Point No. 1, Tract 45.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R20W TR 44 / S 27 AP 5 / S 34 AP 1 / S 34 TR 45</p> </div> <p>1970</p>	
20.03	<p>The 1/4 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION 1/4 S 27 S 34</p> </div> <p>1950</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <hr/> <p>S. 89° 58.5' W., beginning new measurement.</p>	
10.76	<p>The point for Angle Point No. 4, Tract 44 and Angle Point No. 2, Tract 45.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W TR 44 / AP 4 S 27 / AP 2 S 34 / TR 45</p> </div> <p>1970</p>	
20.035	<p>The west 1/16 sec. cor. of secs. 27 and 34 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION W 1/16 S 27 S 34</p> </div> <p>1950</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The above corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 58.5' W., beginning new measurement.</p>
5.35	The north bank of the Wellton-Mohawk Canal, flows S. 60° 00' E.
6.85	The south bank of the Wellton-Mohawk Canal. Thence, over gently rolling land.
18.10	The center line of the Southern Pacific Railroad (northern track), bears on a curve southeast and northwest.
18.50	The center line of the Southern Pacific Railroad (southern track), parallels the above track.
20.03	<p>The corner of secs. 27, 28, 33, and 34 is marked with a wood stake, 17 ins. long, 2 ins. square, firmly set 10 ins. in the ground, in a mound of stone, 2 ft. base, 1 ft. high, and is accepted as the best available evidence of the position of the original corner. The original corner monument, an iron post, 36 ins. long, 2 ins. in diam., with regulation General Land Office brass cap marked for the above corner, was found lying on top of the above mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>T8S R20W</p> <p>S 28 S 27</p> <p>S 33 S 34</p> </div> <p style="text-align: center; margin: 10px 0;">1970</p> <p>Deposit the wood stake corner marker and the iron post monument alongside the iron post.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 0° 03' E., between secs. 27 and 28.</p> <p>Over gently rolling land.</p>
1.15	The center line of the Southern Pacific Railroad (southern track), bears on a curve southeast and northwest.
1.45	The center line of the Southern Pacific Railroad (northern track), parallels the above track.
7.25	The south bank of the Wellton-Mohawk Canal, flows S. 60° 00' E.
8.15	The north bank of the Wellton-Mohawk Canal.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

13

CHAINS		
11.38	Intersect an unmarked Bureau of Reclamation brass tablet, seated on top of a concrete post, 4 ins. in diam., firmly set, projecting 5 ins. above the surface of the ground.	
11.42	Intersect a Bureau of Reclamation brass tablet, seated on top of a concrete post, 4 ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, mkd.	
	<p style="text-align: center;">BUREAU OF RECLAMATION <u>ABOVE</u> <u>SEA</u> <u>DATUM</u> <u>FEET</u> 196.120 BM 12</p>	
19.965	The south 1/16 sec. cor. of secs. 27 and 28 is marked with an iron pipe, 1-inch in diam., with brass cap flush with the surface of the ground, mkd.	
	<p style="text-align: center;">BUREAU OF RECLAMATION S 1/16 S 28 S 27 1950</p> <p>The above corner marker is accepted as the position of the corner. This corner was not remonumented.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' E., beginning new measurement.</p>	
19.97	<p>The point for the 1/4 sec. cor. of secs. 27 and 28 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">T8S R20W 1/4 S 28 S 27 1970</p>	
59.91	<p>The corner of secs. 21, 22, 27, and 28 is marked with an iron pipe, 2 ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W <u>S 21</u> <u>S 22</u> <u>S 28</u> <u>S 27</u> 1954</p> <p>substantiated by:</p> <p style="margin-left: 40px;">A cross (+) chiseled on concrete headwall of a lateral, bears S. 36° 50' W., 59 ft. distant, mkd. + RP TO SEC. COR 59 FT.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

14

CHAINS

The above corner was reestablished and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

The corner of secs. 22, 23, 26, and 27 is marked with an iron pipe, 2 ins. in diam., with brass cap 13 ins. below the surface of the road, mkd.

BUREAU OF RECLAMATION

T8S R20W

S 22 | S 23

S 27 | S 26

1954

The above corner marker is accepted as the best available evidence of the position of the original corner. I did not remonument this corner.

S. 89° 52' W., between secs. 22 and 27.

Over nearly level land, along the center line of a road.

39.87

The point for the 1/4 sec. cor. of secs. 22 and 27 is determined at the intersection of the center line of roads, bearing east and west and north and south. This point of intersection is accepted as the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.

T8S R20W

1/4 $\frac{S\ 22}{S\ 27}$

1970

There are no suitable accessories nor locations available for reference monuments.

S. 89° 52' W., beginning new measurement.

40.12

The corner of secs. 21, 22, 27, and 28, heretofore described.

Restoring the Resurvey Executed
by Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
19.96	<p>N. 0° 04' W., between secs. 21 and 22.</p> <p>Over nearly level land, along the center line of a road.</p> <p>The south 1/16 sec. cor. of secs. 21 and 22 is marked with an iron pipe, 1-inch in diam., with brass cap 9 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION</p> <p>S 1/16</p> <p> </p> <p>S 21 S 22</p> <p> </p> <p>1954</p> </div> <hr style="width: 20%; margin: 10px auto;"/>
19.96	<p>NORTH, beginning new measurment.</p> <p>The point for the 1/4 sec. cor. of secs. 21 and 22 is determined latitudinally at proportionate dist. and longitudinally at the center line of a N and S road. There is no evidence of the original monument.</p> <p>Set an aluminum rod, 48 ins. long, 5/8-inch in diam., with aluminum cap, 3 1/4 ins. in diam., 16 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p>1/4</p> <p> </p> <p>S 21 S 22</p> <p> </p> <p>1981</p> </div>
32.20	<p>The point for Angle Point No. 5, Tract 48 and Angle Point No. 1, Tract 49.</p> <p>Set an aluminum rod, 48 ins. long, 5/8-inch in diam., with aluminum cap 3 1/4 ins. in diam., 16 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p>TR 48 </p> <p>AP 5 S 22</p> <p>AP 1 </p> <p>TR 49 </p> <p>1981</p> </div>
39.96	<p>The point for the north 1/16 sec. cor. of secs. 21 and 22</p> <p>Set an aluminum rod, 48 ins. long, 5/8-inch in diam., with aluminum cap 3 1/4 ins. in diam., 8 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>N 1/16</p> <p>S 21 S 22</p> <p>1981</p> </div>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
59.96	<p>The corner of secs. 15, 16, 21, and 22 is marked with an iron pipe, 2 ins. in diam., with brass cap 14 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION S 16 S 15 S 21 S 22</p> <p style="text-align: center;">19</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner. This corner was not remonumented.</p> <p>Discontinue the regular order of survey at this corner.</p>
8.835	<p>From the corner of secs. 21, 22, 27, and 28, heretofore described.</p> <p>S. 89° 58' W., between secs. 21 and 28.</p> <p>Over nearly level land, along the center line of a road.</p> <p>The point for Angle Point No. 10, Tract 43</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R20W TR 43 AP 10 S 21 S 28</p> <p style="text-align: center;">1970</p>
16.205	<p>The point for Angle Point No. 3, lot 19, which is identical with Angle Point No. 5, lot 20 of sec. 21, determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (privated ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.</p> <p>From the above corner point, a diligent search was made for any evidence of Angle Point No. 4, lot 19, which is identical with Angle Point No. 4, lot 20, and Angle Point No. 6, lot 17, which is identical with Angle Point No. 3, lot 18, Angle Point No. 1, lot 19, and Angle Point No. 3, lot 20 of sec. 21, and none was found.</p>
19.99	<p>The point for the east 1/16 sec. cor. of secs. 21 and 28 is determined at proportionate distance; there is no evidence of the original corner.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the road, mkd.</p> $E \ 1/16 \ \frac{S \ 21}{S \ 28}$ <p>1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>
27.85	<p>The point for Angle Point No. 4, lot 16, which is identical with Angle Point No. 4, lot 17 of sec. 21, determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48 and 49; lots 23 through 30 inclusive within section 21.</p> <p>The above corner point is to continue to function as Angle Point No. 4, lot 16 of sec. 21; whereas Angle Point No. 4, lot 17 is voided by this survey. The corner is designated to function for Angle Point No. 9, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., with brass cap 5 ins. below the surface of the road, mkd.</p> $\begin{array}{r} T8S \ R20W \\ S \ 21 \\ L \ 16 \ \backslash \ TR \ 43 \\ AP \ 4 \ \backslash \ AP \ 9 \\ \hline S \ 28 \end{array}$ <p>1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>
39.98	<p>The point for the 1/4 sec. cor. of secs. 21 and 28 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p> $\begin{array}{r} T8S \ R20W \\ 1/4 \ \frac{S \ 21}{S \ 28} \end{array}$ <p>1970</p>
56.10	<p>The northern bank of the Wellton-Mohawk Canal, flows S. 40° E.</p>
57.10	<p>The southern bank of the Wellton-Mohawk Canal. Thence, over gently rolling land.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

18

CHAINS	
59.97	<p>The west 1/16 sec. cor. of secs. 21 and 28 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 <u>S 21</u> S 28</p> <p style="text-align: center;">1952</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 58' W., beginning new measurement.</p>
6.30	The center line of the Southern Pacific Railroad (northern track), bears N. 52° 35' W. and S. 52° 35' E.
6.70	The center line of the Southern Pacific Railroad (southern track), parallels the above track.
19.975	<p>The corner of secs. 20, 21, 28 and 29 is monumented with an iron post, 2 ins. in diam., firmly set, projecting 5 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> <p style="text-align: center;">T8S R20W <u>S 20 S 21</u> <u>S 29 S 28</u></p> <p style="text-align: center;">1916</p> <p>substantiated by:</p> <p style="padding-left: 40px;">A low mound of stone, 3 ft. base, 1 ft. high, west of the corner.</p> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 0° 03.5' W., between secs. 20 and 21.</p> <p>Over gently rolling land.</p>
12.05	The center line of the Southern Pacific Railroad (southern track), bears N. 41° 40' W. and S. 41° 40' E.
12.35	The center line of the Southern Pacific Railroad (northern track), parallels the above track. Thence, over nearly level land.
20.00	The south 1/16 sec. cor. of secs. 20 and 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, and in a small mound of stone, 2 ft. base, to the top of the brass cap, with brass cap mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION

S 1/16

S 20 | S 21

1952

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 0° 03.5' W., beginning new measurement.

20.01

The 1/4 sec. cor. of secs. 20 and 21 is monumented with an iron post, 36 ins. long, 1-inch in diam., firmly set 26 ins. in the ground, with regulation General Land Office brass cap mkd.

1/4

S 20 | S 21

1916

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W

1/4

S 20 | S 21

1970

Deposit the iron post corner monument alongside the iron post.

Discontinue the regular order of survey at this corner.

From the corner of secs. 15, 16, 21, and 22, heretofore described.

N. 89° 53' W., between secs. 16 and 21.

Over nearly level land, along roadway.

20.00

The east 1/16 sec. cor. of secs. 16 and 21 is marked with an iron pipe, 36 ins. long, 1-inch in diam., with brass cap 5 ins. below the surface of the road, mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	BUREAU OF RECLAMATION E 1/16 <u>S 16</u> S 21 1954 At the corner point Set an aluminum rod, 48 ins. long, 5/8-inch in diam., with aluminum cap 3 1/4 ins. in diam., 7 ins. below the surface of the road, mkd.
	T8S R20E E 1/16 <u>S 16</u> S 21 1981 Deposit the iron pipe corner marker alongside the corner.
	<hr style="width: 20%; margin: auto;"/> <p>N. 89° 53' W., beginning new measurment.</p>
14.00	Leave roadway, roadway bears to the northwest; thence, over gently rolling land.
15.85	The point for Angle Point No. 2, Tract 48 Set an iron post, 28 ins. 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.
	T8S R20W <u>S 16</u> S 21 AP 2 TR 48 1981
20.00	The 1/4 sec. cor. of secs. 16 and 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.
	BUREAU OF RECLAMATION 1/4 <u>S 16</u> S 21 1952 The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.
	<hr style="width: 20%; margin: auto;"/> <p>N. 89° 55' W., beginning new measurment.</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
3.44	<p>Angle Point No. 2, lot, 1, which is identical with Angle Point No. 1, lot 2 of secs. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 28 ins. in the ground, with brass cap marked for the above corner.</p> <p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43 48, and 49; lots 23 through 30 inclusive within sec. 21. I destroyed the above corner marker.</p> <p>From the above corner a diligent search was made for any evidence of Angle Point No. 3, lot 1, which is identical with Angle Point No. 7, lot 2 of secs. 21, and none was found.</p> <p>Continue with course and measurment.</p>	
9.14	<p>The point for Angle Point No. 12, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p>S 16</p> <hr style="width: 50%; margin: 0 auto;"/> <p>AP 12 \ S 21</p> <p>TR 43 /</p> <p>1970</p> </div>	
20.00	<p>The west 1/16 sec. cor. of secs. 16 and 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION</p> <p>W 1/16</p> <p>S 16</p> <hr style="width: 50%; margin: 0 auto;"/> <p>S 21</p> <p>1954</p> </div> <hr style="width: 50%; margin: 10px auto;"/> <p>N. 89° 55' W., beginning new measurment.</p>	
1.52	<p>Angle Point No. 2, lot 4, which is identical with Angle Point No. 1, lot 5 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., with brass cap flush with the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION</p> <p>S 16</p> <hr style="width: 50%; margin: 0 auto;"/> <p>AP 1 \ AP 2</p> <p>L 5 \ L 4</p> <p>S 21</p> <p>1954</p> </div>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

The above corner is to continue to function as Angle Point No. 1, lot 5 of sec. 21; whereas Angle Point No. 2, lot 4 is voided by this survey. The corner is designated to function for Angle Point No. 1, Tract 43.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W	
S 16	

AP 1	AP 1
L 5	TR 43
S 21	

1970

Deposit the iron pipe corner marker alongside the iron post.

Discontinue the regular order of survey at this corner.

Restoring the Survey Executed
by William B. Kimmel, U. S. Surveyor
in 1915 and 1916

The south 1/16 sec. cor. of secs. 16 and 17 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 13 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION	
S 1/16	
S 17	S 16

1952

The above corner marker is accepted as the position of the corner. I did not remonument this corner.

N. 0° 03' W., between secs. 16 and 17.

Over nearly level land.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
0.08	<p>The point for Angle Point No. 4, Tract 42.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W TR 42 AP 4 S 16 / L 17 S 17 </p> <p>1970</p> </div>
19.975	<p>The point for the 1/4 sec. cor. of secs. 16 and 17 is determined at proportionate distance; there is no evidence of the original cor.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W 1/4 S 17 S 16 </p> <p>1970</p> </div>
59.925	<p>The corner of secs. 8, 9, 16, and 17 is marked with an iron pipe, 2 ins. in diam., with brass cap 31 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION T8S R20W S 8 S 9 S 17 S 16</p> </div> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam, over the top of the above corner marker, with brass cap 3 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 8 S 9 S 17 S 16</p> <p>1970</p> </div> <p>There are no suitable accessories nor locations available for reference monuments. This corner is located at the intersection of roads, bearing north and south, and east and west.</p> <p>Discontinue the regular order of survey at this corner.</p>

24

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

Restoring the resurvey Executed
by Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

The 1/4 sec. cor. of secs. 8 and 17 is monumented with an iron post, 1-inch in diam., with a regulation General Land Office brass cap 6 ins. below the surface of the road, mkd.

$$\frac{1/4}{\frac{S 8}{S 17}}$$

1916

substantiated by:

A cross (+) chiseled on concrete headwall of a lateral, bears NORTH, 28.6 ft. distant, mkd. + RP 28.6'.

A cross (+) chiseled on concrete headwall of a lateral, bears SOUTH, 30.4 ft. distant, mkd. + RP 30.4'.

N. 89° 57' W., between secs. 8 and 17.

Over nearly level land.

9.43 The point for Angle Point No. 1, Tract 41.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

$$\frac{T8S R20W}{\frac{S 8}{AP 1 \quad S 17}} \\ TR 41$$

1970

10.01 The point for the east-west 1/64 sec. cor. of secs. 8 and 17.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

$$E W 1/64 \quad \frac{S 8}{S 17}$$

1970

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

25

CHAINS	
13.495	<p>Angle Point No. 2, lot 1, which is identical with Angle Point No. 1, lot 2 of sec. 17, is marked with an iron pipe with brass cap missing, 36 ins. long, 1-inch in diam., firmly set 26 ins. in the ground. I destroyed this corner marker.</p> <p>The area of lots 1, 2, 4, and 11, and the southeast quarter of secs. 17 is vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions are of Tracts 41 and 42; lots 14 through 17 inclusive within section 17.</p> <p>Continue with course and measurement.</p>
20.02	<p>The west 1/16 sec. cor. of secs. 8 and 17 is marked with an iron pipe, 1-inch in diam, firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 <u>S 8</u> S 17</p> <p style="text-align: center;">1952</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 89° 57' W., beginning new measurement.</p>
7.31	<p>The point for Angle Point No. 4, Tract 40, which is identical with Angle Point No. 2, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R20W S 8 TR 40 <u>L 5 AP 4</u> S 17 AP 2 TR 41</p> <p style="text-align: center;">1970</p>
15.02	<p>Angle Point No. 2, lot 4, which is identical with Angle Point No. 1, lot 6 of sec. 17, is marked with an iron pipe, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION <u>S 8</u> AP 1 AP 2 L 6 L 4 S 17</p> <p style="text-align: center;">1954</p>

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

The area of lots 1, 2, 4, and 11, and the southeast quarter of sec. 17 is vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions are of Tracts 41 and 42; lots 14 and 17 inclusive within section 17.

The above corner is to continue to function as Angle Point No. 1, lot 6 of sec. 17; whereas Angle Point No. 2, lot 4 is voided by this survey. The corner is designated to function for the corner of lot 15. I changed the markings on the above brass cap, as follows:

S 8
AP 1 L 15
L 6
S 17
70
1954

N. 89° 57' W., beginning new measurement.

5.01 The corner of secs. 7, 8, 17, and 18 is marked with an iron pipe, 2 ins. in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
T8S R20W
S 7 S 8
S 18 S 17

1952

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

Discontinue the regular order of survey at this corner.

NORTH, between secs. 7 and 8.

Over nearly level land.

19.98 The point for the south 1/16 sec. cor. of secs. 7 and 8 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

S 1/16
S 7 S 8
1970

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

27

CHAINS	
20.05	<p>Angle Point No. 3, lot 12, which is identical with Angle Point No. 5, lot 13 of sec. 7, is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W AP 3 L 12 S 8 / AP 5 L 13 S 7 </p> <p style="text-align: center;">1954</p>
39.96	<p>The 1/4 sec. cor. of secs. 7 and 8 is marked with an iron pipe, 1-inch in diam., with brass cap flush with the surface of the ground, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION 1/4 S 7 S 8 </p> <p style="text-align: center;">1949</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>NORTH, beginning new measurement.</p>
19.995	<p>The point for the north 1/16 sec. cor. of secs. 7 and 8 is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p>
28.11	<p>The point for Angle Point No. 5, lot 5, which is identical with Angle Point No. 6, lot 6 of sec. 7, is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p>
39.99	<p>The corner of secs. 5, 6, 7, and 8 is marked with an iron pipe, 2 ins. in diam., with brass cap 6 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W S 6 S 5 S 7 S 8</p> <p style="text-align: center;">1949</p> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p>

28

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

Discontinue the regular order of survey at this corner.

Restoring the Survey Executed
by William B. Kimmel, U.S. Surveyor,
in 1915 and 1916

The 1/4 sec. cor. of secs. 5 and 8 is marked with an
iron pipe, 1-inch in diam., with brass cap 5 ins. below
the surface of the road, mkd.

BUREAU OF RECLAMATION

1/4
S 5
S 8

195

The above corner marker is accepted as the best avail-
able evidence of the position of the original corner. I
did not remonument this corner.

N. 89° 57' W., between secs. 5 and 8.

Over nearly level land, along the center line of a road.

19.99

The west 1/16 sec. cor. of secs. 5 and 8 is marked with
a steel rod, of undetermined length, 1-inch in diam.,
with the top 5 ins. below the surface of the road, and
is accepted as the position of the corner.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam.,
over the above corner marker, with brass cap 10 ins.
below the surface of the road, mkd.

W 1/16 $\frac{S 5}{S 8}$

1970

There are no suitable accessories nor locations avail-
able for reference monuments.

N. 89° 57' W., beginning new measurement.

2.495

The point for a 1/1024 sec. cor. of secs. 5 and 8.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam.,
with brass cap 10 ins. below the surface of the road,
mkd.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">S 5 1/1024 S 8 1970</p>	
4.325	<p>The point for Angle Point No. 6, Tract 38, which is identical with Angle Point No. 1, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R20W TR 38 S 5 AP 6 L 6 AP 1 L 1 TR 40 S 8 1970</p>	
19.48	<p>The point for Angle Point No. 5, Tract 38, which is identical with Angle Point No. 2, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R20W S 5 TR 38 L 7 AP 5 L 2 AP 2 S 8 TR 40 1970</p>	
19.975	<p>The corner of secs. 5, 6, 7, and 8, heretofore described.</p>	
	<hr/> <p style="text-align: center;">Restoring the Resurvey Executed by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954</p> <hr/> <p>N. 89° 57' W., between secs. 6 and 7.</p> <p>Over nearly level land.</p>	
9.86	<p>Angle Point No. 2, lot 5, which is identical with Angle Point No. 1, lot 6 of sec. 7, is marked with an iron pipe, 1-inch in diam., with brass cap 3 ins. below the surface of the roadway, mkd.</p>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W S 6 ----- AP 1 \ AP 2 L 6 \ L 5 S 7 1954</p>	
13.945	The point for Angle Point No. 5, Tract 47.	
	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.	
	<p style="text-align: center;">T8S R20W TR 47 AP 5 S 6 ----- S 7 1980</p>	
20.01	The east 1/16 sec. cor. of secs. 6 and 7 is marked with an iron pipe, 1-inch in diam., with brass cap 5 ins. below the surface of the roadway, mkd.	
	<p style="text-align: center;">BUREAU OF RECLAMATION E 1/16 $\frac{S 6}{S 7}$ 1954</p>	

	N. 89° 57' W., beginning new measurement.	
0.20	Leave roadway, roadway bears to the southwest.	
4.28	Angle Point No. 2, lot 8, which is identical with Angle Point No. 1, lot 9 of sec. 7, is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, mkd.	
	<p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W S 6 ----- AP 1 \ AP 2 L 9 \ L 8 S 7 1954</p>	
	Continue with course and measurement.	
7.75	The northern bank of the Wellton-Mohawk Canal, flows southeast.	
8.70	The southern bank of the Wellton-Mohawk Canal.	
19.99	The 1/4 sec. cor. of secs. 6 and 7 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 3 ins. above the surface of the ground, mkd.	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

31

CHAINS

BUREAU OF RECLAMATION

$$1/4 \frac{S 6}{S 7}$$

1941

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

Restoring the Survey Executed
by William B. Kimmel, U. S. Surveyor
in 1915 and 1916

N. 89° 57' W., beginning new measurment.

10.06

The closing corner of secs. 6 and 7 on the west boundary of the township, is monumented with an iron post, 2 ins. in diam., firmly set, projecting 9 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.

T8S	T8S	
R21W	S 6	CC
S 12	S 7	
	R20W	

1916

substantiated by:

A mound of stone, 4 ft. base, 2 1/2 ft. high, west of the corner.

From this corner, the east 1/4 sec. cor. of sec. 12, Tp. 8 S., R. 21 W., bears S. 0° 05' E., 1.74 chs. distant, and is monumented with an iron post, 2 1/2 ins. in diam., firmly set in a small mound of stone, projecting 9 ins. above the surface of the ground, with brass cap mkd.

T8S	
R21W	
1/4	
S 12	

1962

The above corner was remonumented by Paul G. Bauer, Surveying Technician, in 1962; as described in the official field-note record of the dependent resurvey of a portion of the east boundary and shown upon the official plat of Tp. 8 S., R. 21 W., accepted May 9, 1962.

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
17.64	<p>From the corner of secs. 5, 6, 7, and 8, heretofore described.</p> <p>N. 0° 01' W., between secs. 5 and 6.</p> <p>Over nearly level land.</p> <p>The point for Angle Point No. 10, Tract 37, which is identical with Angle Point No. 3, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p>TR 37 </p> <p>AP 10 TR 38</p> <p> AP 3</p> <p> </p> <p>L 18 </p> <p>S 6 L 7</p> <p> S 5</p> <p>1970</p> </div>	
20.05	<p>The south 1/16 sec. cor. of secs. 5 and 6 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 10 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION</p> <p>S 1/16</p> <p> </p> <p>S 6 S 5</p> <p> </p> <p>1952</p> </div> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/>	
20.05	<p>N. 0° 01' W., beginning new measurment.</p> <p>The 1/4 sec. cor. of secs. 5 and 6 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 5 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION</p> <p>1/4</p> <p> </p> <p>S 6 S 5</p> <p> </p> <p>1949</p> </div> <p>The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr style="width: 20%; margin: 10px auto;"/>	

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

Restoring the Resurvey Executed
by Albin H. Wadin, Engineer
Bureau of Reclamation, in 1954

N. 0° 01' W., beginning new measurement.

12.83 The point for Angle Point No. 1, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W
S 6 |
/ | S 5
AP 1 |
TR 37 |

1975

20.04 The north 1/16 sec. cor. of secs. 5 and 6 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION
N 1/16
|
S 6 | S 5
|

1952

The above corner marker was accepted and described in the official field-note record of the dependent resurvey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.

N. 0° 01' W., beginning new measurement.

5.085 The point for Angle Point No. 5, lot 7, which is identical with Angle Point No. 1, lot 8 of sec. 6, is determined at proportionate distance; there is no evidence of the original corner.

The area of lots 8, 10, and 12, the south-half of the northeast quarter, and the east-half of the southeast quarter of sec. 6, has remained vacant (United States ownership). The descriptions, the areas, and the above lot numbers are voided by this survey. New descriptions are of Tract 37 and 47; lots 13 through 18 inclusive within section 6.

The above corner is to continue to function as Angle Point No. 5, lot 7 of sec. 6; whereas Angle Point No. 1, lot 8, is voided by this survey. The corner is designated to function for a corner of lot 16 of sec. 6.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

34

Dependent Resurvey of a Portion
of the Subdivisional Lines
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
20.425	<p style="text-align: center;">T8S R20W S 6 L 7 S 5 <u>AP 5 </u> L 16 </p> <p style="text-align: center;">1970</p> <p>The corner of secs. 5, 6, 31, and 32 on the north boundary of the township, heretofore described.</p>	
	<p style="text-align: center;">Dependent Resurvey of a Portion of the Subdivision Lines within Sections 6, 17, and 21 Township 8 South, Range 20 West Gila and Salt River Meridian, Arizona</p>	
20.02	<p>Thence, in section 6</p> <p>From the 1/4 sec. cor. of secs. 6 and 7, heretofore described.</p> <p>N. 0° 04' E., on the north and south center line of sec. 6.</p>	
40.04	<p>The point for the center-south 1/16 sec. cor. of sec. 6. I did not monument this corner point.</p>	
40.04	<p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 6; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the roadway, mkd.</p>	
55.125	<p style="text-align: center;">T8S R20W C 1/4 S 6</p> <p style="text-align: center;">1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
55.125	<p>The point for Angle Point No. 1, Tract 47</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p>	
56.915	<p style="text-align: center;">T8S R20W S 6 AP 1 TR 47</p> <p style="text-align: center;">1980</p> <p>The point for Angle Point No. 9, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS		
	<p style="text-align: center;">T8S R20W TR 37 S 6 AP 9 L 4 L 13</p> <p style="text-align: center;">1970</p>	
60.045	<p>The center-north 1/16 sec. cor. of sec. 6 is marked with an iron pipe, 1-inch in diam., with brass cap 3 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION C N 1/16 S 6 C</p> <p style="text-align: center;">1953</p> <p>The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr style="width: 20%; margin: 20px auto;"/> <p>N. 0° 04' E., beginning new measurement.</p>	
9.03	<p>Angle Point No. 3, lot 9, which is identical with Angle Point No. 3, lot 10, Angle Point 4, lot 11, and Angle Point No. 1, lot 12, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W AP 4 AP 3 L 11 L 9 AP 1 AP 3 L 12 L 10 S 6</p> <p style="text-align: center;">1954</p> <p>The area of lots 8, 10, and 12, the south-half of the northeast quarter, and the east-half of the southeast quarter of sec. 6, has remained vacant (United States ownership). The descriptions, the areas, and the above lot numbers are voided by this survey. New descriptions are of Tracts 37 and 47, lots 13 through 18 inclusive within section 6.</p> <p>The above corner is to continue to function as Angle Point No. 3, lot 9 and Angle Point No. 4, lot 11 of sec. 6; whereas Angle Point No. 3, lot 10 and Angle Point No. 1, lot 12 are voided by this survey. The corner is designated to function for Angle Point No. 5, Tract 37.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

36

CHAINS		
20.40	<p style="text-align: center;">T8S R20W S 6 L 11 L 9 <u>AP 4 AP 3</u> AP 5 TR 37</p> <p style="text-align: center;">1970</p> <p>Deposit the iron pipe corner marker alongside the iron post.</p> <p>The 1/4 sec. cor. of secs. 6 and 31 on the north boundary of the township, heretofore described.</p>	
8.995	<p>From the 1/4 sec. cor. of secs. 5 and 6, heretofore described.</p> <p>S. 89° 58' W., on the east and west center line of sec. 6, and on a blank line across Tract 37.</p> <p>Intersect the arc of a curve, line 9 -10, Tract 37, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p>	
14.86	<p style="text-align: center;">T8S R20W S 6 TR 37 C-----C</p> <p style="text-align: center;">1970</p> <p>The point for Angle Point No. 7, Tract 47.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.</p>	
15.45	<p style="text-align: center;">T8S R20W AP 7 S 6 TR 47 </p> <p style="text-align: center;">1980</p> <p>Thence, on a blank line across Tract 47.</p>	
19.965	<p>Roads, bearing south and N. 20° W., and roadway bears west; thence, along the center line of the roadway.</p> <p>The point for the center-east 1/16 sec. cor. of sec. 6 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long 2 1/2 ins. in diam., with brass cap 5 ins. below the surface of the roadway, mkd.</p> <p style="text-align: center;">E 1/16 C-----C S 6</p> <p style="text-align: center;">1980</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

37

CHAINS		
39.93	Intersect the north and south center line, the center 1/4 sec. cor. of sec. 6, heretofore described.	
50.11	Intersect the west boundary of the township; the point for the west 1/4 sec. cor. of sec. 6 is determined at the point of intersection of the center line of the roadway, bears east, and the above west boundary. There is no evidence of the original corner monument.	
	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.	
	<p style="text-align: center;">T8S 1/4 S 6 R20W</p>	
	1970	
	There are no suitable accessories nor locations available for reference monuments.	
	From this corner, the corner of secs. 1 and 12, Tp. 8 S., R. 21 W., bears S. 0° 05' E., 1.745 chs. distant, and is monumented with an iron post, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, and is marked as described in the field note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this same group.	
	From the center-east 1/16 sec. cor. of sec. 6, heretofore described.	
	N. 0° 01.5' E., on the north and south center line of the northeast quarter of sec. 6.	
	Thence, on a blank line across Tract 47.	
4.655	The point for Angle Point No. 8, Tract 47.	
	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T8S R20W TR 47 AP 8 S 6</p>	
	1980	
7.97	The point for Angle Point No. 9, Tract 47.	
	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 22 ins. in the ground, with brass cap mkd.	
	<p style="text-align: center;">T8S R20W S 6 AP 9 TR 47 </p>	
	1980	

38

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS

10.045

Intersect the arc of a curve, line 9 - 10, Tract 37, hereinafter described. From this point of intersection, Angle Point No. 9, Tract 37, bears along the arc of the above curve 21.295 chs. distant.

Thence, on a blank line across Tract 37.

20.015

Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 6; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

NE 1/16 S 6

1975

26.145

Angle Point No. 3, lot 7, which is identical with Angle Point No. 3, lot 8, Angle Point No. 5, lot 9, and Angle Point No. 1, lot 10, is marked with an iron pipe, with brass cap missing, 33 ins. long, firmly set 30 ins. in the ground, and is accepted as the best available evidence of the position of the corner.

The area of lots 8, 10, and 12, the south-half of the northeast quarter, and the east-half of the southeast quarter of sec. 6, has remained vacant (United States ownership). The descriptions, the areas, and the above lot numbers are voided by this survey. New descriptions are of Tracts 37 and 47, lots 13 through 18 inclusive within section 6.

The above corner is to continue to function as Angle Point No. 3, lot 7 and Angle Point No. 5, lot 9 of secs. 6; whereas Angle Point No. 3, lot 8, and Angle Point No. 1, lot 10, are voided by this survey. The corner is designated to function for Angle Point No. 3, Tract 37.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W
 S|6
 L 9|L 7
 AP 5|AP 3
 ————
 AP 3
 TR 37

1975

Deposit the iron pipe corner marker alongside the iron post.

40.435

The east 1/16 sec. cor. of secs. 6 and 31 on the north boundary of the township, heretofore described.

From the north 1/16 sec. cor. of secs. 5 and 6, heretofore described.

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

39

CHAINS		
	S. 89° 54' W., on the east and west center line of the northeast quarter of sec. 6, and on blank line across lot 16 of sec. 6.	
7.84	Intersect the arc of a curve, line 1 - 2, Tract 37, hereinafter described. From this point of intersection Angle Point No. 1, Tract 37, bears along the arc of the above curve 10.655 chs. distant. Thence, on a blank line across Tract 37.	
19.95	Intersect the north and south center line of the northeast quarter, the northeast 1/16 sec. cor. of sec. 6, heretofore described.	
39.90	The center-north 1/16 sec. cor. of sec. 6, heretofore described. Discontinue the regular order of survey at this corner.	
	<hr/> N. 89° 58' W., on the east and west center line of the northwest quarter of sec. 6.	
10.235	Intersect the west boundary of the township; the point for the north 1/16 sec. cor. of sec. 6, determined latitudinally at proportionate distance and longitudinally on the west boundary of sec. 6. There is no evidence of the original monument. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 8 ins. below the surface of the road, mkd. N 1/16 S 6 1970	
	There are no suitable accessories nor locations available for reference monuments.	
	From this corner, the south 1/16 sec. cor. of sec. 1, Tp. 8 S., R. 21 W., bears S. 0° 05' E., 1.685 chs. distant, and is marked with an iron pipe, 1-inch in diam., with brass cap 8 ins. below the surface of the road, marked as described in the official field-note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this group.	
	From this same corner, Angle Point No. 1, Tract 40, Tp. 8 S., R. 21 W., bears N. 0° 05' W., 12.625 chs. distant, and is monumented with an iron post, 2 1/2 ins. in diam., set and marked as described in the official field-note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this group.	
	Discontinue the regular order of survey at this corner. <hr/>	

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

40

CHAINS

From Angle Point No. 5, lot 7, which is identical with the northeast corner of lot 16, sec. 6, and is located on the section line between secs. 5 and 6, heretofore described.

S. 80° 12' W., between lots 7 and 16 of sec. 6.

9.425

Angle Point No. 4, lot 7, which is identical with Angle Point No. 2, lot 8 of sec. 6, is marked with an iron pipe, with brass cap missing, 30 ins. long, 1-inch in diam., firmly set 27 ins. in the ground, and is accepted as the best available evidence of the position of the original corner.

The area of lots 8, 10, and 12, the south-half of the northeast quarter, and the east-half of the southeast quarter of sec. 6, has remained vacant (United States ownership). The descriptions, the areas, and the above lot numbers are voided by this survey. New descriptions are of Tracts 37 and 47, lots 13 through 18 inclusive within section 6.

The above corner is to continue to function as Angle Point No. 4, lot 7 of sec. 6; whereas Angle Point No. 2, lot 8 is voided by this survey. The corner is designated to function for a corner of lot 16, sec. 6.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W

S 6

L 7

AP 4

L 16

1975

Deposit the iron pipe corner marker alongside the iron post.

N. 76° 17' W., continue between lots 7 and 16 of sec. 6.

6.545

Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 2, Tract 37.

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W

S 6

AP 2

TR 37

1975

Continue along the south boundary of lot 7 of sec. 6, which is identical with line 2 - 3, Tract 37.

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

41

CHAINS		
10.975	<p>Angle Point No. 3, lot 7, which is identical with Angle Point No. 5, lot 9 and Angle Point No. 3, Tract 37, heretofore described.</p>	
8.745	<p>N. 76° 20' W., on line 5 - 4, lot 9 of sec. 6, which is identical with line 3 - 4, Tract 37.</p> <p>Angle Point No. 4, lot 9, which is identical with Angle Point No. 2, lot 10 of sec. 6, is determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of lots 8, 10, and 12, the south-half of the northeast quarter, and the east-half of the southeast quarter of sec. 6, has remained vacant (United States ownership). The descriptions, the areas, and the above lot numbers are voided by this survey. New descriptions are of Tracts 37 and 47, lots 13 through 18 inclusive within section 6.</p> <p>The above corner is to continue to function as Angle Point No. 4, lot 9 of sec. 6; whereas Angle Point No. 2, lot 10, is voided by this survey. The corner is designated to function for Angle Point No. 4, Tract 37.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R20W S 6 L 9 AP 4</p> <hr style="width: 10%; margin: auto;"/> <p style="text-align: center;">AP 4 TR 37</p> <p style="text-align: center;">1975</p>	
11.475	<p>N. 86° 02.5' W., on line 4 - 3, lot 9 of sec. 6, which is identical with line 4 - 5, Tract 37.</p> <p>Angle Point No. 3, lot 9, which is identical with Angle Point No. 4, lot 11 of sec. 6, and Angle Point No. 5, Tract 37, heretofore described.</p>	
10.34	<p>N. 82° 54' W., on line 4 - 3, lot 11 of sec. 6, which is identical with line 5 - 6, Tract 37.</p> <p>Intersect the west boundary of the township; the point for Angle Point No. 3, lot 11, which is identical with Angle Point No. 2, lot 12 of sec. 6, is determined in latitude at proportionate distance and in longitude on line between two accepted corners. There is no evidence of the original corner.</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
within Sections 6, 17, and 21
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

42

CHAINS

The area of lots 8, 10, and 12, the south-half of the northeast quarter, and the east-half of the southeast quarter of sec. 6, has remained vacant (United States ownership). The descriptions, the areas, and the above lot numbers are voided by this survey. New descriptions are of Tracts 37 and 47, lots 13 through 18 inclusive within section 6.

The above corner is to continue to function as Angle Point No. 3, lot 11 of sec. 6; whereas Angle Point No. 2, lot 12, is voided by this survey. The corner is designated to function for Angle Point No. 6, Tract 37.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 7 ins. below the surface of the road, mkd.

	T8S
	R21W R20W
	S 6
	L 11
TR 40	<u>AP 3</u>
	AP 6
	TR 37

1975

There are no suitable accessories nor locations available for reference monuments.

From this corner, Angle Point No. 1, Tract 40, Tp. 8 S., R. 21 W., bears N. 0° 05' W., 2.325 chs. distant, and is monumented with an iron post, 28 ins. long, 2 1/2 ins. in diam., set and marked as described in the field note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this group.

From this same corner, Angle Point No. 7, Tract 40, Tp. 8 S., R. 21 W., bears S. 0° 05' E., 12.85 chs. distant, and is monumented with an iron post, 2 1/2 ins. in diam., set and marked as described in the field-note record of the dependent resurvey of a portion of the east boundary of Tp. 8 S., R. 21 W., executed concurrently with this group.

Thence, in section 17

The 1/4 sec. cor. of secs. 17 and 20 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.

	BUREAU OF RECLAMATION
	1/4
	<u>S 17</u>
	S 20

1954

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

43

CHAINS														
	<p>N. 0° 03' W., on the north and south center line of sec. 17.</p>													
19.995	<p>The point for the center-south 1/16 sec. cor. of sec. 17 is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p>													
39.99	<p>The point for the center 1/4 sec. cor. of sec. 17 is determined in latitude on the center line of an east and west roadway and in longitude on line between two accepted corners. The above corner point is accepted as the best available evidence of the position of the original corner. This corner point is located within a lateral that bears north and south, where it is impracticable to establish a permanent monument; a witness corner is hereinafter described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 03' W., beginning new measurment.</p>													
10.00	<p>The point for Angle Point No. 6, lot 10, which is identical with Angle Point No. 5, lot 11 of sec. 17, is determined at proportionate distance; there is no evidence of the original corner.</p> <p>The area of lots 1, 2, 4, and 11, and the southeast quarter of sec. 17 is vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions are of Tracts 41 and 42; lots 14 through 17 inclusive within section 17.</p> <p>The above corner is to continue to function as Angle Point No. 6, lot 10 of sec. 17; whereas Angle Point No. 5, lot 11, is voided by this survey. The corner is designated to function for Angle Point No. 4, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin-top: 20px;"> <p>T8S R20W</p> <table style="border-collapse: collapse; margin: 0 auto;"> <tr><td style="padding-right: 5px;">TR 41</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">AP 4</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td colspan="2" style="text-align: center;">/</td></tr> <tr><td style="padding-right: 5px;">AP 6</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">L 10</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">S 17</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> </table> <p>1970</p> </div>	TR 41		AP 4		/		AP 6		L 10		S 17		
TR 41														
AP 4														
/														
AP 6														
L 10														
S 17														
19.98	<p>The point for the center-north 1/16 sec. cor. of sec. 17 is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p>													
25.59	<p>The point for Angle Point No. 4, lot 1, which is identical with Angle Point No. 6, lot 2 of sec. 17, is determined at proportionate distance; there is no evidence of the original corner.</p>													

44

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	<p>The area of lots 1, 2, 4, and 11, and the southeast quarter of sec. 17 is vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions are of Tracts 41 and 42; lots 14 through 17 inclusive within section 17.</p> <p>From the above corner point a diligent search was made for any evidence of Angle Point No. 3, lot 1, which is identical with Angle Point No. 7, lot 2 of sec. 17, and none was found.</p>
29.00	<p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 5, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 17 L 14 / AP 5 TR 41 </p> <p>1970</p> </div>
39.96	<p>The 1/4 sec. cor. of secs. 8 and 17, heretofore described.</p> <hr/> <p>Thence, in section 21</p> <p>The center 1/4 sec. cor. of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION C 1/4 S 21</p> <p>1952</p> </div> <p>The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr/> <p>NORTH, on the north and south center line of sec. 21, and on a blank line across Tract 43.</p>
14.20	<p>Angle Point No. 5, lot 7, which is identical with Angle Point No. 3, lot 8, Angle Point No. 1, lot 9, and Angle Point No. 3, lot 10 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 25 ins. in the ground, with brass cap mkd. for the above corner.</p>

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

45

	CHAINS		
		<p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21. I destroyed the above corner marker.</p> <p>From the above corner point a diligent search was made for any evidence of Angle Point No. 4, lot 9, which is identical with Angle Point No. 4, lot 10 of sec. 21, and one was found.</p> <p>Continue with course and measurment.</p>	
	20.02	<p>The point for the center-north 1/16 sec. cor. of sec. 21 is determined at proportionate distance; there is no evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C N 1/16 S 21 1970</p>	
	20.705	<p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49, lots 23 through 30 inclusive within section 21.</p> <p>From the above corner a diligent search was made for any evidence of Angle Point No. 4, lot 1, which is identical with Angle Point No. 6, lot 2, Angle Point No. 1, lot 7, and Angle Point No. 2, lot 8 of sec. 21, and none was found.</p> <p>Intersect line 11 - 12, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R20W S 21 L 24 L 23 TR 43 1970</p>	

46

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS

40.04

The 1/4 sec. cor. of secs. 16 and 21, heretofore described.

From the 1/4 sec. cor. of secs. 21 and 22.

N. 89° 57' W., on the east and west center line of sec. 21.


Thence, on a blank line across Tract 49.

18.535

The point for Angle Point No. 4, Tract 49

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W



19.985

The center-east 1/16 sec. cor. of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

E 1/16

C ——— C

S 21

1952

The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.


N. 89° 58' W., beginning new measurement.

10.21

Intersect line 11 - 12, Tract 43.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W



1970

Thence, on a blank line across Tract 43

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

47

CHAINS

14.89

The point for Angle Point No. 3, lot 9, which is identical Angle Point No. 5, lot 10, Angle Point 2, lot 11, and Angle Point No. 1, lot 12 of sec. 21, is determined at proportionate distance; there is no evidence of the original cor.

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

From the above corner point a diligent search was made for any evidence of Angle Point No. 3, lot 11, which is identical with Angle Point No. 7, lot 12; and Angle Point No. 4, lot 11, which is identical with Angle Point No. 6, lot 12 of sec. 21, and none was found.

19.995

The center 1/4 sec. cor. of sec. 21, heretofore described.

N. 89° 58' W., beginning new measurment.

6.25

Angle Point No. 3, lot 7, which is identical with Angle Point No. 2, lot 14, Angle Point No. 1, lot 15, and Angle Point No. 4, lot 22 of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION

T8S R20W

AP 4 AP 3

~~L 22 L 7~~

AP 1 AP 2

L 15 L 14

S 21

1954

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

The above corner is to continue to function as Angle Point No. 1, lot 15 and Angle Point No. 4, lot 22 of sec. 21; whereas Angle Point No. 3, lot 7 and Angle Point No. 2, lot 14 are voided by this survey. The corner is designated to function for Angle Point No. 5, Tract 43.

48

Dependent Resurvey of a Portion of the Subdivision Lines
 Within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W
 L 22
~~AP 4 TR 43~~
~~AP 1 AP 5~~
 L 15
 S 21

1970

Deposit the iron pipe corner marker alongside the iron post.

N. 89° 58' W., beginning new measurement.

13.74 The point for the center-west 1/16 sec. cor. of sec. 21 is determined at proportionate distance; there is no evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

C W 1/16
 S 21

1970

23.74 The point for the C-W-W 1/64 sec. cor. of sec. 21.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.

C W W
 1/64
 S 21

1970

from which

An iron post, 28 ins. long, 2 1/2 ins. in diam., set 23 ins. in the ground, for a reference monument, bears WEST, 68.5 ft. distant, with brass cap mkd. RM T8S R20W S21 68.5 FT., and an arrow pointing to the corner.

33.74 The 1/4 sec. cor. of secs. 20 and 21, heretofore described.

From the center-east 1/16 sec. cor. of sec. 21, heretofore described.

N. 0° 03' W., on the north and south center line of the northeast quarter of sec. 21.

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

49

CHAINS		
1.46	<p>The point for Angle Point No. 3, Tract 49.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W TR 49 E AP 3 S 21 E</p> <p>1981</p> </div> <p>Thence, on a blank line across Tract 49.</p>	
12.545	<p>Intersect line 1 - 2, Tract 49 and line 4 - 5, Tract 48, hereinafter described. From this point of intersection, Angle Point No. 1, Tract 49, which is identical with Angle Point No. 5, Tract 48, heretofore described, bears S. 89° 06' E., 20.015 chs. distant.</p> <p>Thence, on a blank line across Tract 48.</p>	
19.995	<p>The northeast 1/16 sec. cor. of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION NE 1/16 S 21</p> <p>1954</p> <hr/> </div> <p>N. 0° 04' E., beginning new measurement.</p>	
20.025	<p>The east 1/16 sec. cor. of secs. 16 and 21, heretofore described.</p> <hr/> <p>From the north 1/16 sec. cor. of secs. 21 and 22, heretofore described.</p> <p>N. 89° 58' W., on the east and west center line of the northeast quarter of sec. 21.</p> <p>On a blank line across Tract 48.</p>	
20.02	<p>The northeast 1/16 sec. cor. of sec. 21.</p> <hr/> <p>N. 89° 54' W., beginning new measurement.</p>	
14.195	<p>Intersect line 2 - 3, Tract 48, hereinafter described, from this point of intersection, Angle Point No. 3 (hereinafter described), bears S. 4° 38' E., 2.82 chs. distant.</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
within Sections 6, 17, and 21
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

50

CHAINS 19.66	Intersect line 11 - 12, Tract 43, hereinafter described. From this point of intersection, Angle Point No. 12, Tract 43, bears N. 25° 17' W., 22.155 chs. distant.
19.98	<p>Thence, on a blank line across Tract 43.</p> <p>Intersect the north and south center line, the center-north 1/16 sec. cor. of sec. 21, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the west 1/16 sec. cor. of secs. 21 and 28, heretofore described.</p> <p>N. 0° 02' W., on the north and south center line of the southwest quarter of sec. 21.</p>
10.00	<p>The C-S-SW 1/64 sec. cor. of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION 1966 S 21 C S SW 1/64</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p> <hr/> <p>N. 0° 02' W., beginning new measurement.</p>
10.00	<p>The southwest 1/16 sec. cor. of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION SW 1/16 S 21 1952</p> <p>The above corner marker was accepted and described in the official field-note record of the survey by Albin H. Wadin, Engineer, Bureau of Reclamation, in 1954. I did not remonument this corner.</p> <hr/> <p>N. 0° 02' W., beginning new measurement.</p>
10.00	<p>The point for the C-N-SW 1/64 sec. cor. of sec. 21.</p>

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

51

CHAINS		
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., with brass cap 11 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">C N SW 1/64 S 21 1970</p> <p>There are no suitable accessories nor locations available for reference monuments.</p>	
20.00	<p>Intersect the east and west center line, the center-west 1/16 sec. cor. of sec. 21, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p>	
	<hr/> <p>From the south 1/16 sec. cor. of secs. 21 and 22, heretofore described.</p> <p>WEST, on the east and west center line of the southeast quarter of sec. 21.</p>	
3.22	<p>The point for Angle Point No. 6, Tract 49.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T8S R20W TR 49 AP 6 S ————— S S 21 1981</p>	
20.035	<p>The southeast 1/16 sec. cor. of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION SE 1/16 S 21 1954</p> <hr/> <p>N. 89° 58.5' W., beginning new measurement.</p>	
0.765	<p>Intersect the arc of curve, line 10 - 11, Tract 43, hereinafter described. From this point of intersection, Angle Point No. 11, Tract 43, bears along the arc of the above curve 2.00 chs. distant.</p> <p>Thence, on a blank line across Tract 43.</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS
 5.79


The point for Angle Point No. 5, lot 11, which is identical Angle Point No. 5, lot 12, Angle Point 1, lot 17, and Angle Point No. 2, lot 18 of sec. 21, is determined at proportionate distance; there is no evidence of the original corner.

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

17.00

Angle Point No. 4, lot 12, which is identical with Angle Point No. 3, lot 13, Angle Point No. 1, lot 16, and Angle Point No. 2, lot 17 of sec. 21 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.

BUREAU OF RECLAMATION




1954

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

The above corner is to continue to function as Angle Point No. 3, lot 13 and Angle Point No. 1, lot 16 of sec. 21; whereas Angle Point No. 4, lot 12 and Angle Point No. 2, lot 17 are voided by this survey. The corner is designated to function for Angle Point No. 7, Tract 43.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



1970

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona


CHAINS		
	<p>Deposit the iron pipe corner marker alongside the iron post.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the southeast 1/16 sec. cor. of sec. 21, heretofore described.</p> <p>N. 0° 09' E., on the north and south center line of the southeast quarter of sec. 21.</p>	
19.975	<p>The center-east 1/16 sec. cor. of sec. 21, heretofore described.</p> <hr/> <p>From Angle Point No. 1, Tract 43, which is identical with Angle Point No. 1, lot 5 of sec. 21, heretofore described.</p>	
3.68	<p>S. 24° 23' E., on line 2 - 3, lot 4, which is identical with line 1 - 5, lot 5 of sec. 21.</p> <p>Angle Point No. 3, lot 2, which is identical with Angle Point No. 1, lot 3, Angle Point No. 3, lot 4, and Angle Point No. 5, lot 5 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 28 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">BUREAU OF RECLAMATION T8S R20W AP 3 L 4 AP 3 / L 2 AP 5 L 5 AP 1 L 3 S 21</p> <p style="text-align: center;">1954</p> <p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.</p> <p>The above corner is to continue to function as Angle Point No. 1, lot 3 and Angle Point No. 5, lot 5 of sec. 21; whereas Angle Point No. 3, lot 2 and Angle Point No. 3, lot 4 are voided by this survey. The corner is designated to function for Angle Point No. 2, Tract 43.</p> <p>At the corner point</p>	

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

54

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.




1970

Deposit the iron pipe corner marker alongside the iron post.

S. 17° 12' E., on line 3 - 4, lot 2, which is identical with line 1 - 4, lot 3 of sec. 21

8.74 Angle Point No. 4, lot 2, which is identical with Angle Point No. 4, lot 3 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 28 ins. in the ground, with brass cap mkd.

BUREAU OF RECLAMATION
 T8S R20W




1954

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

The above corner is to continue to function as Angle Point No. 4, lot 3 of sec. 21; whereas Angle Point No. 4, lot 2 is voided by this survey. The corner is designated to function for Angle Point No. 3, Tract 43.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



1970

Dependent Resurvey of a Portion of the Subdivision Lines
within Sections 6, 17, and 21
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

55

CHAINS

Deposit the iron pipe corner marker alongside the iron post.

8.56

S. 13° 12' E., on line 4 - 5, lot 2, which is identical with line 4 - 3, lot 3 of sec. 21.

Angle Point No. 5, lot 2, which is identical with Angle Point No. 3, lot 3, Angle Point No. 2, lot 7, and Angle Point No. 1, lot 21 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 26 ins. in the ground, with brass cap mkd.

BUREAU OF RECLAMATION

T8S R20W

AP 3	/	AP 5
L 3	/	L 2
AP 1	/	AP 2
L 21	/	L 7
S 21	/	

1954

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

The above corner is to continue to function as Angle Point No. 3, lot 3 and Angle Point No. 1, lot 21 of sec. 21; whereas Angle Point No. 5, lot 2 and Angle Point No. 2, lot 7 are voided by this survey. The corner is designated to function for Angle Point No. 4, Tract 43.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W

L 3	/	TR 43
AP 3	/	AP 4
AP 1	/	
L 21	/	
S 21	/	

1970

Deposit the iron pipe corner marker alongside the iron post.


S. 24° 41' E., on line 2 - 3, lot 7, which is identical with line 1 - 4, lot 21 of sec. 21.

Dependent Resurvey of a Portion of the Subdivision Lines
within Sections 6, 17, and 21
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS															
11.02	<p>The point for Angel Point No. 4, lot 21, which is identical with Angle Point No. 1, lot 22 of sec. 21, and is determined at proportionate distance; there is no evidence of the original corner. I did not monument this corner point.</p> <p>Continue with course and measurement of line 2 - 3, lot 7, which is now identical with line 1 - 4, lot 22 of sec. 21.</p>														
22.04	<p>Angle Point No. 1, lot 15, which is identical with Angle Point No. 4, lot 22 of sec. 21, and Angle Point No. 5, Tract 43, heretofore described.</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 26° 41' E., on line 2 - 3, lot 14, which is identical with line 1 - 5, lot 15 of sec. 21.</p>														
13.92	<p>Angle Point No. 3, lot 12, which is identical with Angle Point No. 1, lot 13, Angle Point No. 3, lot 14, and Angle Point No. 5, lot 15 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 26 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 20px 0;"> <p>BUREAU OF RECLAMATION</p> <p>T8S R20W</p> <table style="margin: auto; border-collapse: collapse;"> <tr><td style="padding-right: 5px;">AP 3</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">L 14</td><td style="border-left: 1px solid black; padding-left: 5px;"> AP 3</td></tr> <tr><td style="padding-right: 5px;"></td><td style="border-left: 1px solid black; padding-left: 5px;"> L 12</td></tr> <tr><td style="padding-right: 5px;">AP 5</td><td style="border-left: 1px solid black; padding-left: 5px;"> </td></tr> <tr><td style="padding-right: 5px;">L 15</td><td style="border-left: 1px solid black; padding-left: 5px;"> AP 1</td></tr> <tr><td style="padding-right: 5px;"></td><td style="border-left: 1px solid black; padding-left: 5px;"> L 13</td></tr> <tr><td style="padding-right: 5px;"></td><td style="border-left: 1px solid black; padding-left: 5px;"> S 21</td></tr> </table> <p>1954</p> </div> <p>The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.</p> <p>The above corner is to continue to function as Angle Point No. 1, lot 13 and Angle Point No. 5, lot 15 of sec. 21; whereas Angle Point No. 3, lot 12 and Angle Point No. 3, lot 14 are voided by this survey. The corner is designated to function for Angle Point No. 6, Tract 43.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	AP 3		L 14	AP 3		L 12	AP 5		L 15	AP 1		L 13		S 21
AP 3															
L 14	AP 3														
	L 12														
AP 5															
L 15	AP 1														
	L 13														
	S 21														

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS



1970

Deposit the iron pipe corner marker alongside the iron post.


S. 21° 39' E., on line 3 - 4, lot 12, which is identical with line 1 - 3, lot 13 of sec. 21.

8.12 Angle Point No. 3, lot 13, which is identical with Angle Point No. 1, lot 16 of sec. 21, and Angle Point No. 7, Tract 43, heretofore described.

S. 21° 43' E., on line 2 - 3, lot 17, which is identical with line 1 - 5, lot 16 of sec. 21.

12.56 Angle Point No. 3, lot 17, which is identical with Angle Point No. 5, lot 16 of sec. 21, is marked with an iron pipe, 36 ins. long, 1-inch in diam., firmly set 27 ins. in the ground, with brass cap mkd.

BUREAU OF RECLAMATION




1954

The area of lots 1, 2, 7, 8, 9, 10, 11, 12, 14, 17, 18, 19, and 20, and the west-half of the southwest quarter of sec. 21 is vacant (United States ownership) with the exception of the NE1/4 NW1/4 SW1/4 which is patented (private ownership). The description, lot numbers, and the corners controlling the position of these lots are voided (with the exception of the above area of exception) by this survey. New descriptions are of Tracts 39, 43, 48, and 49; lots 23 through 30 inclusive within section 21.

The above corner is to continue to function as Angle Point No. 5, lot 16 of sec. 21; whereas Angle Point No. 3, lot 17 is voided by this survey. The corner is designated to function for Angle Point No. 8, Tract 43.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



1970

Dependent Resurvey of a Portion of the Subdivision Lines
 within Sections 6, 17, and 21
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

58

CHAINS		
	<p>Deposit the iron pipe corner marker alongside the iron post.</p> <hr/> <p>S. 28° 25' E., on line 3 - 4, lot 17, which is identical with line 5 - 4, lot 16 of sec. 21.</p> <p>9.44 Angle Point No. 9, Tract 43, which is identical with Angle Point No. 4, lot 16 of sec. 21, heretofore described.</p>	
	<p style="text-align: center;">Survey of a Portion of the Subdivision Lines within a Number of Sections Township 8 South, Range 20 West Gila and Salt River Meridian, Arizona</p>	
	<p>Thence, in section 5</p> <p>From the west 1/16 sec. cor. of secs. 5 and 8, heretofore described.</p> <p>N. 0° 05' E., on the north and south center line of the southwest quarter of sec. 5.</p> <p>20.05 The southwest 1/16 sec. cor. of sec. 5 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 7 ins. above the surface of the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION SW 1/16 S 5 1952</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p>	
	<p>N. 0° 05' E., beginning new measurment.</p> <p>20.04 The center-west 1/16 sec. cor. of sec. 5 is marked with an iron pipe, 1-inch in diam., firmly set, projecting 8 ins. above the surface of the ground, with brass cap mkd.</p>	
	<p style="text-align: center;">BUREAU OF RECLAMATION W 1/16 C ————— C S 5 1952</p> <p>The above corner marker is accepted as the position of the corner. I did not remonument this corner.</p>	

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
11.175	<p>N. 89° 57' W., on the east and west center line of sec. 5.</p> <p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 1, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p>S 5</p> <hr style="width: 100px; margin: 0 auto;"/> <p>AP 1 /</p> <p>TR 38 /</p> <p>1970</p> </div>
20.065	<p>The 1/4 sec. cor. of secs. 5 and 6, heretofore described.</p> <hr/> <p>From the southwest 1/16 sec. cor. of sec. 5, heretofore described.</p> <p>N. 89° 57' W., on the east and west center line of the southwest quarter of sec. 5.</p>
5.04	<p>Intersect the arc of a curve, line 7 - 1, Tract 38, hereinafter described. From this point of intersection Angle Point No. 7, Tract 38, bears along the arc of the above curve 5.78 chs. distant.</p> <p>Thence on a blank line across Tract 38.</p>
20.02	<p>The south 1/16 sec. cor. of secs. 5 and 6, heretofore described.</p> <hr/> <p>Thence, in section 6</p> <p>From the east 1/16 sec. cor. of secs. 6 and 7, heretofore described.</p> <p>N. 0° 01.5' E., on the north and south center line of the southeast quarter of sec. 6.</p>
20.035	<p>Intersect the east and west center line of the southeast quarter, the point for the southeast 1/16 sec. cor. of sec. 6.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SE 1/16</p> <p>S 6</p> <p>1970</p> </div>
40.07	<p>Intersect the east and west center line, the center-east 1/16 sec. cor. of sec. 6, heretofore described.</p> <hr/> <p>From the south 1/16 sec. cor. of secs. 5 and 6, heretofore described.</p>

60

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	WEST, on the east and west center line of the southeast quarter of sec. 6.
0.315	Intersect the arc of a curve, line 9 - 10, Tract 37, hereinafter described. From this point of intersection Angle Point No. 10, Tract 37, bears along the arc of the above curve 2.43 chs. distant.
13.91	The point for Angle Point No. 6, Tract 47. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	Thence, on a blank line across Tract 47.
19.985	Intersect the north and south center line of the southeast quarter, the southeast 1/16 sec. cor. of sec. 6, heretofore described.
39.965	Intersect the north and south center line, the point for the center-south 1/16 sec. cor. of sec. 6, heretofore described.
	Thence, in section 8
	From the 1/4 sec. cor. of secs. 8 and 17, heretofore described.
	N. 0° 02' W., on the north and south center line of sec. 8.
19.99	The point for the center-south 1/16 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.
39.98	The center 1/4 sec. cor. of sec. 8 is marked with an iron pipe, of undetermined length, with the top 11 ins. below the surface of the roadway, and is accepted as the position of the corner. At the corner point Set an iron post, 28 ins. long, 2 1/2 ins. diam., over the corner marker, with brass cap 9 ins. below the surface of the roadway, mkd.


Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	T8S R20W C 1/4 S 8 1970 There are no suitable accessories nor locations available for reference monuments. Discontinue the regular order of survey at this corner. <hr style="width: 20%; margin: auto;"/> N. 89° 56' W., on the east and west center line of sec. 8.
20.00	The point for the center-west 1/16 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 9 ins. below the surface of the ground, mkd.
	C W 1/16 S 8 1970 There are no suitable accessories nor locations available for reference monuments.
22.50	The point for a 1/1024 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 9 ins. below the surface of the ground, mkd.
	1/ 1024 1970 There are no suitable accessories nor locations available for reference monuments.
23.51	Intersect the arc of a curve, line 11 - 12, Tract 40, hereinafter described. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	T8S R20W S 8 C ——— C TR 40 1970 From this intersection Angle Point No. 12, Tract 40 bears along the arc of the above curve 3.21 chs. distant. Thence, on a blank line across Tract 40.
38.685	Intersect the arc of a curve, line 3 - 4, Tract 40, hereinafter described.

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 8 C — C TR 40</p> </div> <p style="text-align: center;">1970</p>
40.00	<p>The 1/4 sec. cor. of secs. 7 and 8, heretofore described. Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the 1/1024 sec. cor. of sec. 8, which is located (at 22.50 chs. distant) on the east and west center line of sec. 8, heretofore described.</p> <p>N. 0° 02' W., on a north and south 1/1024 line of the northwest quarter of sec. 8.</p>
39.99	<p>The 1/1024 sec. cor. of secs. 5 and 8, heretofore described.</p> <hr/> <p>From the west 1/16 sec. cor. of secs. 8 and 17, heretofore described.</p> <p>N. 0° 01' W., on the north and south center line of the southwest quarter of sec. 8.</p>
17.49	<p>The point for a 1/1024 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">1/1024</p> <p style="text-align: center;">1970</p>
19.99	<p>Intersect the east and west center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SE 1/16 S 8</p> </div> <p style="text-align: center;">1970</p>
39.98	<p>Intersect the east and west center line, the center-west 1/16 sec. cor. of sec. 8, heretofore described.</p> <hr/> <p>From the center-south 1/16 sec. cor. of sec. 8, heretofore described.</p>

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89° 56.5' W., on the east and west center line of the southwest quarter of sec. 8.
20.00	Intersect the north and south center line of the southwest quarter, the southwest 1/16 sec. cor. of sec. 8, heretofore described.
22.50	The point for a 1/1024 sec. cor. of sec. 8. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd. 1/1024 1970
	Thence, on a blank line across Tract 40.
35.44	Intersect the arc of a curve, line 3 - 4, Tract 40, hereinafter described. From this point of intersection Angle Point No. 4, Tract 40, bears along the arc of the above curve 21.64 chs. distant.
40.00	The south 1/16 sec. cor. of secs. 7 and 8, heretofore described. Discontinue the regular order of survey at this corner.
	From the 1/1024 sec. cor. of sec. 8, which is located (at 22.50 chs. distant) on the east and west center line of the southwest quarter of sec. 8, heretofore described.
	N. 0° 01' W., on a north and south 1/1024 line of the NW1/4 of the SW1/4 of sec. 8.
11.44	Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 11, Tract 40. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd. <div style="text-align: center;">  <p>T8S R20W S 8 AP 11 TR 40 1970</p> </div>
19.99	Intersect the east and west center line, the 1/1024 sec. cor. of sec. 8, heretofore described.
	From the east-west 1/64 sec. cor. of secs. 8 and 17, heretofore described.
	N. 0° 01.5' W., on the north and south center line of the SE 1/4 of the SW 1/4 of sec. 8.
0.825	Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 6, Tract 40.

64

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 8 AP 6 TR 40</p> </div> <p style="text-align: center;">1970</p>
9.995	<p>The calculated position, the point for the SE-SW 1/64 sec. cor. of sec. 8.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>SE SW 1/64 S 8</p> <p>1970</p> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 89° 57' W., on the east and west center line of the SE 1/4 of the SW 1/4 of sec. 8.</p>
5.00	<p>The calculated position, the point for the C-W-SE-SW 1/256 sec. cor. of sec. 8. I did not monument this corner point.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 0° 01' W., on the north and south center line of the NW1/4 SE1/4 SW1/4 of sec. 8.</p>
5.00	<p>The calculated position, the point for the NW-SE-SW 1/256 sec. cor. of sec. 8. I did not monument this corner point.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 89° 56.5' W., on the east and west center line of the NW1/4 SE1/4 SW1/4 of sec. 8.</p>
2.50	<p>The calculated position, the point for a 1/1024 sec. cor. of sec. 8. I did not monument this corner point.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> </div> <p>N. 0° 01' W., on a north and south 1/1024 line of the NW1/4 SE1/4 SW1/4 of sec. 8.</p>
2.50	<p>The calculated position, the point for a 1/1024 sec. cor. of sec. 8. I did not monument this corner point.</p> <div style="text-align: center;"> <hr style="width: 20%; margin: 10px auto;"/> </div>

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona


CHAINS	
1.21	<p>N. 89° 56.5' W., on an east and west 1/1024 line of the NW1/4 SE1/4 SW1/4 of sec. 8.</p> <p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 7, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 8</p> <hr style="width: 100px; margin: 0 auto;"/> <p>AP 7 TR 40</p> <p>1970</p> </div>
2.50	<p>Intersect the north and south center line of the southwest quarter, the 1/1024 sec. cor. of sec. 8, heretofore described.</p> <hr style="border: 1px solid black;"/> <p>Thence, in section 17</p> <p>From the 1/4 sec. cor. of secs. 16 and 17, heretofore described.</p> <p>WEST, on the east and west center line of sec. 17.</p>
25.67	<p>The point for Angle Point No. 2, Tract 42.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 17</p> <hr style="width: 100px; margin: 0 auto;"/> <p>C L 16 AP 2 TR 42</p> <p>1970</p> </div>
39.93	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, for the witness center 1/4 sec. cor. of sec. 17, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W C 1/4 S 17</p> <p>WC ←</p> <p>1970</p> </div>
40.05	<p>Intersect the north and south center line, the true point for the center 1/4 sec. cor. of sec. 17, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr style="border: 1px solid black;"/> <p>From the south 1/16 sec. cor. of secs. 16 and 17, heretofore described.</p> <p>S. 89° 57' W., on the east and west center line of the southeast quarter of sec. 17.</p>

66

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
40.04	Intersect the north and south center line, the point for the center-south 1/16 sec. cor. of sec. 17, heretofore described.
	<hr/> <p>Thence, in section 21</p> <p>From the C-N-SW 1/64 sec. cor. of sec. 21, heretofore described.</p> <p>N. 89° 59' W., on the east and west center line of the NW1/4 of the SW1/4 of sec. 21.</p>
5.00	<p>The point for the C-E-NW-SW 1/256 sec. cor. of sec. 21.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 26 ins. below the surface of the ground, mkd.</p> <p style="text-align: center;">C E NW SW 1/256 S 21 1981</p>
7.98	<p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, for the witness NW-SW 1/64 sec. cor. of sec. 21, with brass cap mkd.</p> <p style="text-align: center;">NW SW 1/64 WC ← S 21 1970</p>
10.00	<p>The calculated position, the true point for the NW-SW 1/64 sec. cor. of sec. 21. This corner point is located within the bed of the Wellton-Mohawk Canal, where it is impracticable to establish a permanent monument.</p> <p>Discontinue the regular order of survey at this corner.</p> <p style="text-align: center;">_____</p> <p>N. 0° 02.5' W., on the north and south center line of the NW1/4 of the SW1/4 of sec. 21.</p>
10.00	<p>Intersect the east and west center line of the C-W-W 1/64 sec. cor. of sec. 21, heretofore described.</p> <hr/> <p>Thence, in section 27</p> <p>From the 1/4 sec. cor. of sec. 27 and 34, heretofore described.</p> <p>N. 0° 03' E., on the north and south center line of sec. 27, and on a blank line across Tract 44.</p>
11.49	<p>Intersect line 6 - 1, Tract 44, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
19.985	<div style="text-align: center;"> <p>T8S R20W S 27 TR 44 </p>  <p>1970</p> </div> <p>The point for the center-south 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>
39.97	<div style="text-align: center;"> <p>C S 1/16 S 27</p> <p>1970</p> </div> <p>Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 27. This corner point is located within a lateral; where it is impracticable to establish a permanent monument.</p>
40.13	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, for the witness center 1/4 sec. cor. of sec. 27, with brass cap mkd.</p>
79.94	<div style="text-align: center;"> <p>T8S R20W C 1/4 S 27 ↓ WC</p> <p>1970</p> </div> <p>The 1/4 sec. cor. of secs. 22 and 27, heretofore described.</p> <hr/> <p>The 1/4 sec. cor. of secs. 26 and 27 is marked with an iron pipe, 1-inch in diam., with brass cap 27 ins. below the surface of the road, mkd.</p> <div style="text-align: center;"> <p>BUREAU OF RECLAMATION 1/4 S 27 S 26</p> <p>1948</p> </div> <p>substantiated by:</p> <p style="padding-left: 40px;">A cross (+) chiseled on concrete headwall of a lateral, bears S. 37° 40' E., 48 ft. distant, mkd. + RP 48'.</p> <p>The above corner marker is accepted as the best available evidence of the position of the original corner.</p>

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	<p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., over the above corner marker, with brass cap 5 ins. below the surface of the road, mkd.</p> <p style="text-align: center;">T8S R20W 1/4 S 27 S 26 1970</p> <hr style="width: 20%; margin: 10px auto;"/> <p>S. 89° 56.5' W., on the east and west center line of sec. 27.</p>
19.99	<p>The point for the center-east 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C E 1/16 S 27 1970</p>
20.50	Enter and continue along lateral.
39.98	Intersect the north and south center line, the true point for the center 1/4 sec. cor. of sec. 27, heretofore described.
59.35	Leave lateral, lateral bears to the northwest.
60.035	<p>The point for the center-west 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">C W 1/16 S 27 1970</p>
80.09	<p>The 1/4 sec. cor. of secs. 27 and 28, heretofore described.</p> <p>Discontinue the regular order of survey at this corner.</p> <hr/> <p>From the west 1/16 sec. cor. of secs. 27 and 34, heretofore described.</p> <p>N. 0° 03' E., on the north and south center line of the southwest quarter of sec. 27.</p>
12.945	<p>Intersect line 3 - 4, Tract 44, hereinafter described. From this point of intersection Angle Point No. 3, bears N. 35° 35.5' W., 8.645 chs. distant.</p>

Survey of a Portion of the Subdivision Lines
 Within a Number of Sections
 Township 8 South, Range 20 West
 Gila and Salt River Meridian, Arizona

CHAINS	
	Thence, on a blank line across Tract 44.
19.98	<p>Intersect the east and west center line of the southwest quarter, the point for the southwest 1/16 sec. cor. of sec. 27.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>S W 1/16 S 27</p> <p>1970</p> </div>
39.47	<p>The point for Angle Point No. 1, Tract 44.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 27 AP 1 TR 44</p> <p>1970</p> </div>
39.96	<p>Intersect the east and west center line, the center-west 1/16 sec. cor. of sec. 27, heretofore described.</p> <hr/> <p>From the center-south 1/16 sec. cor. of sec. 27, heretofore described.</p> <p>S. 89° 57' W., on the east and west center line of the southwest quarter of sec. 27.</p>
6.085	<p>Intersect line 6 - 1, Tract 44, hereinafter described.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 27 TR 44</p> <p>1970</p> </div>
20.045	<p>Thence, on a blank line across Tract 44.</p> <p>Intersect the north and south center line of the southwest quarter, the southwest 1/16 sec. cor. of sec. 27, heretofore described.</p>
25.085	<p>The point for Angle Point No. 3, Tract 44.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>




70

Survey of a Portion of the Subdivision Lines
Within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	T8S R20W S 27 <hr style="width: 100px; margin: 0 auto;"/> AP 3 TR 44 1970
40.09	The south 1/16 sec. cor. of secs. 27 and 28, heretofore described.
	<hr/> From the east 1/16 sec. cor. of secs. 27 and 34, heretofore described. NORTH, on the north and south center line of the south-east quarter of sec. 27.
39.98	Intersect the east and west center line, the center-east 1/16 sec. cor. of sec. 27, heretofore described.
	<hr/> Thence, in section 34 The 1/4 sec. cor. of secs. 3 and 34 on the south boundary of the township is monumented with an iron post, 1-inch in diam., firmly set, projecting 11 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.
	$1/4 \frac{S \ 34}{S \ 3}$ 1915
39.99	N. 0° 01.5' W., on the north and south center line of sec. 34. Intersect the east and west center line, the point for the center 1/4 sec. cor. of sec. 34. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
	T8S R20W C 1/4 S 34 1970
43.15	The center line of the Southern Pacific Railroad (south track), bears N. 45° 55' W. and S. 45° 55' E.
43.45	The center line of the Southern Pacific Railroad (north track), parallels the above track.
59.09	Set an iron post, 28 ins. long, 2 1/2 ins. in diam., 20 ins. in the ground, for the witness center-north 1/16 sec. cor. of sec. 34, with brass cap mkd.

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

71

CHAINS	
	 <p style="text-align: center;">1970</p>
59.60	The south bank of the Wellton-Mohawk Canal, flows S. 49° 10' E.
59.99	The true point for the center-north 1/16 sec. cor. of sec. 34. This corner point is located within the bed of the Wellton-Mohawk Canal; where it is impracticable to establish a permanent monument.
60.60	The north bank of the Wellton-Mohawk Canal.
67.66	Intersect the arc of a curve, line 3 - 4, Tract 45, hereinafter described. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	 <p style="text-align: center;">1970</p>
79.99	Thence, on a blank line across Tract 45 The 1/4 sec. cor. of secs. 27 and 34, heretofore described.
	From the 1/4 sec. cor. of secs. 34 and 35, heretofore described. N. 89° 58.5' W., on the east and west center line of sec. 34.
20.02	The point for the center-east 1/16 sec. cor. of sec. 34. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	 <p style="text-align: center;">1970</p>
36.45	The center line of the Southern Pacific Railroad (north track), bears N. 45° 55' W., and S. 45° 55' E.
36.90	The center line of the Southern Pacific Railroad (south track), parallels the above track.
40.04	Intersect the north and south center line, the center 1/4 sec. cor. of sec. 34, heretofore described.
60.06	The point for the center-west 1/16 sec. cor. of sec. 34. I did not monument this corner point.

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

72

CHAINS	
80.08	<p>The 1/4 sec. cor. of secs. 33 and 34 is monumented with an iron post, 1-inch in diam., firmly set, projecting 12 ins. above the surface of the ground, with regulation General Land Office brass cap mkd.</p> <div style="text-align: center;"> <p>1/4 S 33 S 34 1915</p> </div> <hr/> <p>From the center-east 1/16 sec. cor. of sec. 34, heretofore described.</p> <p>N. 0° 01' E., on the north and south center line of the northeast quarter of sec. 34.</p>
15.10	<p>Intersect the arc of a curve, line 3 - 4, Tract 45, hereinafter described. From this point of intersection Angle Point No. 4, Tract 45, bears along the arc of the above curve 8.13 chs. distant.</p> <p>Thence, on a blank line across Tract 45.</p>
20.005	<p>Intersect the east and west center line of the northeast quarter, the point for the northeast 1/16 sec. cor. of sec. 34.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>NE 1/16 S 34 1970</p> </div>
32.215	<p>Intersect the arc of a curve, hereinafter described, the point for Angle Point No. 8, Tract 45.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. in diam., with brass cap 9 ins. below the surface of the ground, mkd.</p> <div style="text-align: center;"> <p>T8S R20W S 34 / AP 8 TR 45 1970</p> </div> <p>This corner is located within a cultivated field. There are no suitable accessories nor locations available for reference monuments.</p>
40.01	<p>The east 1/16 sec. cor. of secs. 27 and 34, heretofore described.</p> <hr/> <p>From the north 1/16 sec. cor. of secs. 34 and 35, heretofore described.</p>

Survey of a Portion of the Subdivision Lines
within a Number of Sections
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

73

CHAINS	
	WEST, on the east and west center line of the northeast quarter of sec. 34.
20.02	Intersect the north and south center line of the northeast quarter, the northeast 1/16 sec. cor. of sec. 34, heretofore described. Thence, on a blank line across Tract 45.
29.75	Intersect the arc of a curve, line 3 - 4, Tract 45, hereinafter described. From this point of intersection Angle Point No. 4, Tract 45, bears along the arc of the above curve 19.04 chs. distant.
40.04	Intersect the north and south center line, the true point for the center-north 1/16 sec. cor. of sec. 34, heretofore described.
	<hr/>
	From the point for the center-west 1/16 sec. cor. of sec. 34, heretofore described.
	N. 0° 03' W., on the north and south center line of the northwest quarter of sec. 34.
39.98	The west 1/16 sec. cor. of secs. 27 and 34, heretofore described.
	<hr/>
	The Metes and Bounds Survey of Tracts 37 through 49 inclusive Township 8 South, Range 20 West Gila and Salt River Meridian, Arizona
	<hr/>
	Thence, with the survey of Tract 37
	Beginning at Angle Point No. 1, Tract 37, heretofore described, and is located on the section line between secs. 5 and 6.
	Thence, on line 1 - 2, Tract 37, along the arc of a curve, curve data:
	Chord bears N. 51° 57.5' W. Chord length 19.87 chs. distant Radius 59.16 chs. distant Length of arc 19.965 chs. distant
	At 10.655 chs. distant on the arc of the curve. Intersect the east and west center line of the northeast quarter of sec. 6, heretofore described.
	At the end of the arc of the curve, Angle Point No. 2, Tract 37, heretofore described.
	<hr/>
	N. 76° 17' W., on line 2 - 3, Tract 37, which is identical with the south boundary of lot 7, sec. 6.

74

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS 4.43	<p>Angle Point No. 3, Tract 37, which is identical with Angle Point No. 3, lot 7 and Angle Point No. 5, lot 9 of sec. 6, heretofore described.</p> <hr/> <p>N. 76° 20' W., on line 3 - 4, Tract 37, which is identical with line 5 - 4, lot 9 of sec. 6.</p>
8.745	<p>Angle Point No. 4, Tract 37, which is identical with Angle Point No. 4, lot 9 of sec. 6, heretofore described.</p> <hr/> <p>N. 86° 02.5' W., on line 4 - 5, Tract 37, which is identical with line 4 - 3, lot 9 of sec. 6.</p>
11.475	<p>Angle Point No. 5, Tract 37, which is identical with Angle Point No. 3, lot 9 and Angle Point No. 4, lot 11 of sec. 6, heretofore described.</p> <hr/> <p>N. 82° 54' W., on line 5 - 6, Tract 37, which is identical with line 4 - 3, lot 11 of sec. 6.</p>
10.34	<p>Angle Point No. 6, Tract 37, which is identical with Angle Point No. 3, lot 11 of sec. 6, heretofore described, and on the west boundary of the township.</p> <hr/> <p>S. 0° 05' E., on line 6 - 7, Tract 37, which is identical with the west boundary of sec. 6.</p>
10.30	<p>The north 1/16 sec. cor. of sec. 6 (only) on the west boundary of sec. 6, heretofore described, which is designated to function for Angle Point No. 7, Tract 37.</p> <hr/> <p>S. 89° 58' E., on line 7 - 8, Tract 37, which is identical with the east and west center line of the north-west quarter of sec. 6.</p>
10.235	<p>The center-north 1/16 sec. cor. of sec. 6, heretofore described, which is designated to function for Angle Point No. 8, Tract 37.</p> <hr/> <p>S. 0° 04' W., on line 8 - 9, Tract 37, which is identical with the north and south center line of sec. 6.</p>
3.13	<p>Angle Point No. 9, Tract 37, heretofore described.</p> <hr/> <p>Thence, on line 9 - 10, Tract 37, along the arc of a curve, curve data:</p>

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Chord bears S. 45° 26' E. Chord length 56.03 chs. distant Radius 44.01 chs. distant Length of arc 60.74 chs. distant</p> <p>At 8.185 chs. distant on the arc of the curve. The point for Angle Point No. 13, Tract 47 (hereinafter described).</p> <p>At 16.395 chs. distant on the arc of the curve. The point for Angle Point No. 12, Tract 47 (hereinafter described).</p> <p>At 21.295 chs. distant on the arc of the curve. Intersect the north and south center line of the northeast quarter of sec. 6, heretofore described.</p> <p>At 36.23 chs. distant on the arc of the curve. Intersect the east and west center line of sec. 6, heretofore described.</p> <p>At 58.31 chs. distant on the arc of the curve. Intersect the east and west center line of the southeast quarter of sec. 6, heretofore described.</p> <p>At the end of the arc of the curve, Angle Point No. 10, Tract 37, which is identical with Angle Point No. 3, Tract 38, heretofore described.</p>	
		<hr/> <p>N. 0° 01' W., on line 10 - 1, Tract 37, which is identical with line 3 - 2, Tract 38, and is identical with the section line between secs. 5 and 6.</p>	
	2.41	The south 1/16 sec. cor. of secs. 5 and 6, heretofore described.	
	22.46	The 1/4 sec. cor. of secs. 5 and 6, heretofore described. This corner is designated to function for Angle Point No. 2, Tract 38.	
	35.29	Angle Point No. 1, Tract 37, and the place of beginning.	
		<hr/> <p>Thence, with the survey of Tract 38</p> <p>Beginning at Angle Point No. 1, Tract 38, heretofore described, and is located on the east and west center line of section 5.</p> <p>N. 89° 57' W., on line 1 - 2, Tract 38, which is identical with the east and west center line of sec. 5.</p>	
	8.89	The 1/4 sec. cor. of secs. 5 and 6, heretofore described, which is designated to function for Angle Point No. 2, Tract 38.	
		<hr/> <p>S. 0° 01' E., on line 2 - 3, Tract 38, which is identical with a portion of line 1 - 10, Tract 37, and is identical with the section line between secs. 5 and 6.</p>	

76

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
20.05	The south 1/16 sec. cor. of secs. 5 and 6, heretofore described.	
22.46	Angle Point No. 3, Tract 38, which is identical with Angle Point No. 10, Tract 37, heretofore described.	
	<hr/> <p>Thence, on line 3 - 4, Tract 38, along the arc of a curve, curve data:</p> <p>Chord bears S. 3° 31' E. Chord length 3.67 chs. distant Radius 44.01 chs. distant Length of arc 3.67 chs. distant</p> <p>At the end of the arc of the curve, the point for Angle Point No. 4, Tract 38</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	
13.98	<p style="text-align: center;">T8S R20W S 5 / TR 38 L 7 / AP 4</p> <p style="text-align: center;">1970</p> <hr/> <p>S. 1° 07' E., on line 4 - 5, Tract 38.</p>	
15.155	<p style="text-align: center;">T8S R20W TR 38 / S 5 AP 7 / L 6</p> <p style="text-align: center;">1970</p> <hr/> <p>S. 89° 57' E., on line 5 - 6, Tract 38, which is identical with line 2 - 1, Tract 40, and is identical with the section line between secs. 5 and 8.</p>	
14.29	<p style="text-align: center;">T8S R20W TR 38 / S 5 AP 7 / L 6</p> <p style="text-align: center;">1970</p> <hr/> <p>N. 1° 07' W., on line 6 - 7, Tract 38.</p> <p>The point for Angle Point No. 7, Tract 38.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

77

CHAINS		
	<p>Thence, on line 7 - 1, Tract 38, along the arc of a curve, curve data:</p> <p>Chord bears N. 14° 07.5' W. Chord length 26.62 chs. distant Radius 59.16 chs. distant Length of arc 26.85 chs. distant</p> <p>At 5.78 chs. distant on the arc of the curve. Intersect the east and west center line of the southwest quarter of sec. 5, heretofore described.</p> <p>At the end of the arc of the curve, Angle Point No. 1, Tract 38, and the place of beginning.</p> <hr/> <p>Thence, with the survey of Tract 39</p> <p>Beginning at the 1/4 sec. cor. of secs. 20 and 21, heretofore described, which is designated to function for Angle Point No. 1, Tract 39.</p> <p>S. 0° 03.5' E., on line 1 - 2, Tract 39, which is identical with the section line between secs. 20 and 21.</p>	
20.01	<p>The south 1/16 sec. cor. of secs. 20 and 21, heretofore described, which is designated to function for Angle Point No. 2, Tract 39.</p> <hr/> <p>S. 45° 00' E., on line 2 - 3, Tract 39.</p>	
28.275	<p>The west 1/16 sec. cor. of secs. 21 and 28, heretofore described, which is designated to function for Angle Point No. 3, Tract 39.</p> <hr/> <p>N. 0° 02' W., on line 3 - 4, Tract 39, which is identical with the north and south center line of the southwest quarter of sec. 21.</p>	
10.00	<p>The C-S-SW 1/64 sec. cor. sec. 21, heretofore described, which is designated to function for Angle Point No. 4, Tract 39.</p> <hr/> <p>N. 14° 04' W., on line 4 - 5, Tract 39.</p>	
20.62	<p>The C-E-NW-SW 1/256 sec. cor. of sec. 21, heretofore described, which is designated to function for Angle Point No. 5, Tract 39.</p> <hr/> <p>N. 89° 59' W., on line 5 - 6, Tract 39, which is identical with the east and west center line of the NW 1/4 of the SW 1/4 of sec. 21.</p>	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
2.98	The witness NW-SW 1/64 sec. cor. of sec. 21, heretofore described.	
5.00	The true point for the NW-SW 1/64 sec. cor. of sec. 21, heretofore described, which is designated to function for Angle Point No. 6, Tract 39.	
10.00	<hr/> <p>N. 0° 02.5' W., on line 6 - 7, Tract 39, which is identical with the north and south center line of the NW 1/4 of the SW 1/4 of sec. 21.</p>	
10.00	<hr/> <p>The C-W-W 1/64 sec. cor. of sec. 21, heretofore described, which is designated to function for Angle Point No. 7, Tract 39.</p>	
10.00	<hr/> <p>N. 89° 58' W., on line 7 - 1, Tract 39, which is identical with the east and west center line of sec. 21.</p>	
10.00	<hr/> <p>The 1/4 sec. cor. of secs. 20 and 21, which is designated to function for Angle Point No. 1, Tract 39, and the place of beginning.</p>	
15.155	<hr/> <p>Thence, with the survey of Tract 40 Beginning at Angle Point No. 1, Tract 40, which is identical with Angle Point No. 6, Tract 38, heretofore described. N. 89° 57' W., on line 1 - 2, Tract 40, which is identical with line 6 - 5, Tract 38, and is identical with the section line between secs. 5 and 8.</p>	
37.10	<hr/> <p>Angle Point No. 2, Tract 40, which is identical with Angle Point No. 5, Tract 38, heretofore described.</p>	
37.10	<hr/> <p>S. 1° 07.5' E., on line 2 - 3, Tract 40. The point for Angle Point No. 3, Tract 40.</p>	
	<hr/> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>	
	<hr/> <p style="text-align: center;">T8S R20W S 8 / TR 40 L 2 / AP 3 1970</p>	
	<hr/> <p>Thence, on line 3 - 4, Tract 40, along the arc of a curve, curve data:</p>	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

	CHAINS		
		<p>Chord bears S. 15° 00' E. Chord length 44.39 chs. distant Radius 92.425 chs. distant Length of arc 44.83 chs. distant</p> <p>At 2.90 chs. distant on the arc of the curve. Intersect the east and west center line of sec. 8, heretofore described.</p> <p>At 23.19 chs. distant on the arc of the curve. Intersect the east and west center line of the southwest quarter of sec. 8, heretofore described.</p> <p>At the end of the arc of the curve, Angle Point No. 4, Tract 40, which is identical with Angle Point No. 2, Tract 41, heretofore described.</p> <hr/> <p>S. 89° 57' E., on line 4 - 5, Tract 40, which is identical with line 2 - 1, Tract 41, and is identical with the section line between secs. 8 and 17.</p>	
	7.31	<p>The west 1/16 sec. cor. of secs. 8 and 17, heretofore described.</p> <p>Continue with course and measurement</p>	
	17.32	<p>The east-west 1/64 sec. cor. of secs. 8 and 17, heretofore described, which is designated to function for Angle Point No. 5, Tract 40.</p> <hr/> <p>N. 0° 01.5' W., on line 5 - 6, Tract 40, which is identical with the north and south center line of the SE 1/4 of the SW 1/4 of sec. 8.</p>	
	0.825	<p>Angle Point No. 6, Tract 40, heretofore described.</p> <hr/> <p>Thence, on line 6 - 7, Tract 40, along the arc of a curve, curve data:</p> <p>Chord bears N. 27° 37' W. Chord length 18.815 chs. distant Radius 77.275 chs. distant Length of arc 18.86 chs. distant</p> <p>At the end of the arc of the curve, Angle Point No. 7, Tract 40, heretofore described.</p> <hr/> <p>N. 89° 56.5' W., on line 7 - 8, Tract 40, which is identical with a east and west 1/1024 line of the NW1/4 SE1/4 SW1/4 of sec. 8.</p>	
	1.29	<p>A 1/1024 sec. cor. of sec. 8, heretofore described, which is designated to function for Angle Point No. 8, Tract 40.</p> <hr/>	

80

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
2.50	<p>N. 0° 01' W., on line 8 - 9, Tract 40, which is identical with the north and south center line of the southwest quarter of sec. 8.</p> <p>The southwest 1/16 sec. cor. of sec. 8, heretofore described, which is designated to function for Angle Point No. 9, Tract 40.</p> <hr/>
2.50	<p>N. 89° 56.5' W., on line 9 - 10, Tract 40, which is identical with the east and west center line of the southwest quarter of sec. 8.</p> <p>A 1/1024 sec. cor. of sec. 8, heretofore described, which is designated to function for Angle Point No. 10, Tract 40.</p> <hr/>
11.44	<p>N. 0° 01' W., on line 10 - 11, Tract 40, which is identical with the north and south 1/1024 line of the NW 1/4 of the SW 1/4 of sec. 8.</p> <p>Angle Point No. 11, Tract 40, heretofore described.</p> <hr/> <p>Thence, on line 11 - 12, Tract 40, along the arc of a curve, curve data:</p> <p>Chord bears N. 5° 31' W. Chord length 11.81 chs. distant Radius 77.275 chs. distant Length of arc 11.82 chs. distant</p> <p>At 8.61 chs. distant on the arc of the curve. Intersect the east and west center line of sec. 8, heretofore described.</p> <p>At the end of the arc of the curve, the point for Angle Point No. 12, Tract 40.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div data-bbox="755 1948 917 2136" style="text-align: center;"> <p>T8S R20W</p> <p>1970</p> </div> <hr/>
36.79	<p>N. 1° 07.5' W., on line 12 - 1, Tract 40.</p> <p>Angle Point No. 1, Tract 40, which is identical with Angle Point No. 6, Tract 38, and the place of beginning.</p> <hr/>

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona


81

	CHAINS		
		<p>Thence, with the survey of Tract 41</p> <p>Beginning at Angle Point No. 1, Tract 41, heretofore described.</p> <p>N. 89° 57' W., on line 1 - 2, Tract 41, which is identical with the section line between secs. 8 and 17.</p>	
	0.58	<p>The east-west 1/64 sec. cor. of secs. 8 and 17, which is designated to function for Angle Point No. 5, Tract 40, heretofore described.</p> <p>Continue with course and measurement of line 1 - 2, Tract 41, which is now identical with line 5 - 4, Tract 40.</p>	
	10.59	<p>The west 1/16 sec. cor. of secs. 8 and 17, heretofore described.</p>	
	17.90	<p>Angle Point No. 2, Tract 41, which is identical with Angle Point No. 4, Tract 40, heretofore described.</p> <hr/> <p>Thence, on line 2 - 3, Tract 41, along the arc of a curve, curve data:</p> <p>Chord bears S. 40° 57.5' E. Chord length 38.56 chs. distant Radius 92.425 chs. distant Length of arc 38.845 chs. distant</p> <p>At the end of the arc of the curve, intersect line 6 - 7, lot 10, which is identical with line 4 - 5, lot 11 of sec. 17.</p> <p>The area of lots 1, 2, 4, and 11, and the southeast quarter of sec. 17 is vacant (United States ownership). The description, lot numbers, and the corners controlling the position of these lots are voided by this survey. New descriptions are of Tracts 41 and 42; lots 14 through 17 inclusive within section 17.</p> <p>This point of intersection is the point for Angle Point No. 3, Tract 41.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div data-bbox="808 1975 1055 2231" style="text-align: center;"> <p>1970</p> </div> <p>From this corner Angle Point No. 7, lot 10, which is identical with Angle Point No. 4, lot 11, of sec. 17, bears N. 67° 20.5' W., 6.315 chs. distant, and is marked with an iron pipe, 1-inch in diam., firmly set, projecting 9 ins. above the surface of the ground, with brass cap mkd.</p>	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

BUREAU OF RECLAMATION




S 17

1954

The above corner is to continue to function as Angle Point No. 7, lot 10 of sec. 17; whereas Angle Point No. 4, lot 11 is voided by this survey. The corner is designated to function for a corner of lot 15 of sec. 17. I changed the markings on the above brass cap, as follows:

BUREAU OF RECLAMATION



S 17

70
1954

S. 67° 20.5' E., on line 3 - 4, Tract 41, which is identical with a portion of line 7 - 6, lot 10 of sec. 17.

2.245 Angle Point No. 4, Tract 41, which is identical with Angle Point No. 6, lot 10 of sec. 17, heretofore described.

N. 0° 03' W., on line 4 - 5, Tract 41, which is identical with the north and south center line of sec. 17.

9.98 The point for the center-north 1/16 sec. cor. of sec. 17, heretofore described.

19.00 Angle Point No. 5, Tract 41, heretofore described.

Thence, on line 5 - 1, Tract 41, along the arc of a curve, curve data:

Chord bears N. 40° 43.5' W.
Chord length 14.465 chs. distant
Radius 77.275 chs. distant
Length of arc 14.49 chs. distant

At the end of the arc of the curve, Angle Point No. 1, Tract 41, and the place of beginning.

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

83

	CHAINS	
		<p>Thence, with the survey of Tract 42</p> <p>Beginning at the 1/4 sec. cor. of secs. 16 and 17, heretofore described, which is designated to function for Angle Point No. 1, Tract 42.</p> <p>WEST, on line 1 - 2, Tract 42, which is identical with the east and west center line of sec. 17.</p>
	25.67	<p>Angle Point No. 2, Tract 42, heretofore described.</p> <hr/> <p>S. 57° 21.5' E., on line 2 - 3, Tract 42.</p>
	9.59	<p>The point for Angle Point No. 3, Tract 42.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div data-bbox="803 1048 1079 1249" style="text-align: center;"> </div> <hr/> <p>Thence, on line 3 - 4, Tract 42, along the arc of a curve, curve data:</p> <p>Chord bears S. 50° 06.5' E. Chord length 22.95 chs. distant Radius 90.91 chs. distant Length of arc 23.015 chs. distant</p> <p>At the end of the arc of the curve, Angle Point No. 4, Tract 42, heretofore described.</p> <hr/> <p>N. 0° 03' W., on line 4 - 1, Tract 42, which is identical with the section line between secs. 16 and 17.</p>
	19.895	<p>The 1/4 sec. cor. of secs. 16 and 17, which is designated to function for Angle Point No. 1, Tract 42, and the place of beginning.</p> <hr/> <p>Thence, with the survey of Tract 43</p> <p>Beginning at Angle Point No. 1, Tract 43, which is identical with Angle Point No. 1, lot 5 of sec. 21, heretofore described, and is located on the section line between secs. 16 and 21.</p> <p>S. 24° 23' E., on line 1 - 2, Tract 43, which is identical with line 1 - 5, lot 5 of sec. 21.</p>

84

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
3.68	<p>Angle Point No. 2, Tract 43, which is identical with Angle Point No. 1, lot 3 and Angle Point No. 5, lot 5 of sec. 21, heretofore described.</p> <hr/>	
	<p>S. 17° 12' E., on line 2 - 3, Tract 43, which is identical with line 1 - 4, lot 3 of sec. 21.</p>	
8.74	<p>Angle Point No. 3, Tract 43, which is identical with Angle Point No. 4, lot 3 of sec. 21, heretofore described.</p> <hr/>	
	<p>S. 13° 12' E., on line 3 - 4, Tract 43, which is identical with line 4 - 3, lot 3 of sec. 21.</p>	
8.56	<p>Angle Point No. 4, Tract 43, which is identical with Angle Point No. 3, lot 3, and Angle Point No. 1, lot 21 of sec. 21, heretofore described.</p> <hr/>	
	<p>S. 24° 41' E., on line 4 - 5, Tract 43, which is identical with line 1 - 4, lot 21 of sec. 21.</p>	
11.02	<p>The point for Angle Point No. 4, lot 21, which is identical with Angle Point No. 1, lot 22 of sec. 21, heretofore described.</p>	
	<p>Continue with course and measurement of line 4 - 5, Tract 43, which is now identical with line 1 - 4, lot 22 of sec. 21.</p>	
22.04	<p>Angle Point No. 5, Tract 43, which is identical with Angle Point No. 1, lot 15 and Angle Point No. 4, lot 22 of sec. 21, heretofore described.</p> <hr/>	
	<p>S. 26° 41' E., on line 5 - 6, Tract 43, which is identical with line 1 - 5, lot 15 of sec. 21.</p>	
13.92	<p>Angle Point No. 6, Tract 43, which is identical with Angle Point No. 1, lot 13 and Angle Point No. 5, lot 15 of sec. 21, heretofore described.</p> <hr/>	
	<p>S. 21° 39' E., on line 6 - 7, Tract 43, which is identical with line 1 - 3, lot 13 of sec. 21.</p>	
8.12	<p>Angle Point No. 7, Tract 43, which is identical with Angle Point No. 3, lot 13, and Angle Point No. 1, lot 16 of sec. 21, heretofore described.</p> <hr/>	
	<p>S. 21° 43' E., on line 7 - 8, Tract 43, which is identical with line 1 - 5, lot 16 of sec. 21.</p>	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

85

	CHAINS	
	12.56	Angle Point No. 8, Tract 43, which is identical with Angle Point No. 5, lot 16 of sec. 21, heretofore described.
		<hr/> <p>S. 28° 25' E., on line 8 - 9, Tract 43, which is identical with line 5 - 4, lot 16 of sec. 21.</p>
	9.44	Angle Point No. 9, Tract 43, which is identical with Angle Point No. 4, lot 16 of sec. 21, heretofore described.
		<hr/> <p>N. 89° 58' E., on line 9 - 10, Tract 43, which is identical with the section line between secs. 21 and 28.</p>
	7.86	The east 1/16 sec. cor. of secs. 21 and 28, heretofore described.
	19.015	Angle Point No. 10, Tract 43, heretofore described.
		<hr/> <p>Thence, on line 10 - 11, Tract 43, along the arc of a curve, curve data:</p> <p>Chord bears N. 30° 27' W. Chord length 25.24 chs. distant Radius 140.18 chs. distant Length of arc 25.275 chs. distant</p> <p>At 23.275 chs. distant on the arc of the curve. Intersect the east and west center line of the southeast quarter of sec. 21, heretofore described.</p> <p>At the end of the arc of the curve, the point for Angle Point No. 11, Tract 43.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div data-bbox="828 1827 1039 2002" style="text-align: center;"> <p>T8S R20W TR 43 AP 11 X S 21 1970</p> </div> <hr/>
	20.12	Intersect the east and west center line of sec. 21, heretofore described.
	42.26	Intersect the east and west center line of the northeast quarter of sec. 21, heretofore described.
	43.015	Intersect the north and south center line of sec. 21, heretofore described.


The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

86

<p>CHAINS 64.415</p>	<p>Angle Point No. 12, Tract 43, heretofore described.</p> <hr/> <p>N. 89° 55' W., on line 12 - 1, Tract 43, which is identical with the section line between secs. 16 and 21.</p>
<p>10.86</p>	<p>The west 1/16 sec. cor. of secs. 16 and 21, heretofore described.</p>
<p>12.38</p>	<p>Angle Point No. 1, Tract 43, which is identical with Angle Point No. 1, lot 5 of sec. 21, and the place of beginning.</p> <hr/> <p>Thence, with the survey of Tract 44</p> <p>Beginning at Angle Point No. 1, Tract 44, heretofore described, and is located on the north and south center line of the southwest quarter of sec. 27.</p> <p>S. 0° 03' W., on line 1 - 2, Tract 44, which is identical with the north and south center line of the southwest quarter of sec. 27.</p>
<p>19.49</p>	<p>The southwest 1/16 sec. cor. of sec. 27, heretofore described, which is designated to function for Angle Point No. 2, Tract 44.</p> <hr/> <p>S. 89° 57' W., on line 2 - 3, Tract 44, which is identical with the east and west center line of the southwest quarter of sec. 27.</p>
<p>5.04</p>	<p>Angle Point No. 3, Tract 44, heretofore described.</p> <hr/> <p>S. 35° 35.5' E., on line 3 - 4, Tract 44.</p>
<p>8.645</p>	<p>Intersect the north and south center line of the southwest quarter of sec. 27, heretofore described.</p>
<p>24.56</p>	<p>Angle Point No. 4, Tract 44, which is identical with Angle Point No. 2, Tract 45, heretofore described.</p> <hr/> <p>N. 89° 58.5' E., on line 4 - 5, Tract 44, which is identical with line 2 - 1, Tract 45, and is identical with the section line between secs. 27 and 34.</p>
<p>10.76</p>	<p>The 1/4 sec. cor. of secs. 27 and 34, heretofore described.</p>
<p>20.185</p>	<p>Angle Point No. 5, Tract 44, which is identical with Angle Point No. 1, Tract 45, heretofore described.</p> <hr/>

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

87

CHAINS	
	<p>Thence, on line 5 - 6, Tract 44, along the arc of a curve, curve data:</p> <p>Chord bears N. 41° 04.5' W. Chord length 10.135 chs. distant Radius 53.02 chs. distant Length of arc 10.15 chs. distant</p> <p>At the end of the arc of the curve, the point for Angle Point No. 6, Tract 44.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p>  <p>1970</p> <hr style="width: 20%; margin: 0 auto;"/> </div>
4.735	N. 35° 35.5' W., on line 6 - 1, Tract 44. Intersect the north and south center line of sec. 27, heretofore described.
15.175	Intersect the east and west center line of the southwest quarter of sec. 27, heretofore described.
39.13	Angle Point No. 1, Tract 44, and the place of beginning.
	<hr/> <p>Thence, with the survey of Tract 45</p> <p>Beginning at Angle Point No. 1, Tract 45, which is identical with Angle Point No. 5, Tract 44, heretofore described.</p> <p>S. 89° 58.5' W., on line 1 - 2, Tract 45, which is identical with line 5 - 4, Tract 44, and is identical with the section line between secs. 27 and 34.</p>
9.425	The 1/4 sec. cor. of secs. 27 and 34, heretofore described.
20.185	Angle Point No. 2, Tract 45, which is identical with Angle Point No. 4, Tract 44, heretofore described.
	<hr/> <p>S. 35° 35.5' E., on line 2 - 3, Tract 45.</p>
1.665	The point for Angle Point No. 3, Tract 45.
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p>

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

T8S R20W
TR 45
AP 3
S 34
1970

Thence, on line 3 - 4, Tract 45, along the arc of a curve, curve data:

Chord bears S. 55° 06.5' E.
Chord length 45.74 chs. distant
Radius 68.475 chs. distant
Length of arc 46.64 chs. distant

At 14.74 chs. distant on the arc of the curve. Intersect the north and south center line of sec. 34, heretofore described.

At 27.60 chs. distant on the arc of the curve. Intersect the east and west center line of the northeast quarter of sec. 34, heretofore described.

At 38.51 chs. distant on the arc of the curve. Intersect the north and south center line of the northeast quarter of sec. 34, heretofore described.

At the end of the arc of the curve. The point for Angle Point No. 4, Tract 45.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

T8S R20W
TR 45
AP 4
S 34
1970

S. 74° 37' E., on line 4 - 5, Tract 45.

12.765 Angle Point No. 5, Tract 45, heretofore described.

N. 0° 02.5' E., on line 5 - 6, Tract 45, which is identical with section line between secs. 34 and 35.

0.315 Angle Point No. 3, Tract 46, heretofore described.

Continue with course and measurement of line 5 - 6, Tract 45, which is now identical with line 3 - 2, Tract 46.

10.925 The north 1/16 sec. cor. of secs. 34 and 35, heretofore described, which is designated to function for Angle Point No. 6, Tract 45.

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

	CHAINS		
		WEST, on line 6 - 7, Tract 45, which is identical with the east and west center line of the northeast quarter of sec. 34.	
20.02		The northeast 1/16 sec. cor. of sec. 34, heretofore described, which is designated to function for Angle Point No. 7, Tract 45.	
		N. 0° 01' E., on line 7 - 8, Tract 45, which is identical with the north and south center line of the northeast quarter of sec. 34.	
12.21		Angle Point No. 8, Tract 45, heretofore described.	
		<p>Thence, on line 8 - 1, Tract 45, along the arc of a curve, curve data:</p> <p>Chord bears N. 53° 40.5' W. Chord length 13.15 chs. distant Radius 53.02 chs. distant Length of arc 13.185 chs. distant</p> <p>At the end of the arc of the curve, Angle Point No. 1, Tract 45, which is identical with Angle Point No. 5, Tract 44, and the place of beginning.</p>	
		<p>Thence, with the survey of Tract 46</p> <p>Beginning at Angle Point No. 1, Tract 46, heretofore described, and is located on the section line between secs. 35 and 36.</p> <p>N. 74° 37' W., on line 1 - 2, Tract 46.</p>	
82.845		Angle Point No. 2, Tract 46, heretofore described.	
		S. 0° 02.5' W., on line 2 - 3, Tract 46, which is identical with the section line between secs. 34 and 35.	
5.10		The north 1/16 sec. cor. of secs. 34 and 35, which is designated to function for Angle Point No. 6, Tract 45, heretofore described.	
		Continue with course and measurement of line 2 - 3, Tract 46, which is now identical with a portion of line 6 - 5, Tract 45.	
15.71		Angle Point No. 3, Tract 46, heretofore described.	
		S. 74° 37' E., on line 3 - 4, Tract 46.	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
82.865	Angle Point No. 4, Tract 46, heretofore described.
	<hr/> <p>N. 0° 01.5' W., on line 4 - 1, Tract 46, which is identical with the section line between secs. 35 and 36.</p>
12.52	The 1/4 sec. cor. of secs. 35 and 36, heretofore described.
15.72	Angle Point No. 1, Tract 46, and the place of beginning.
	<hr/> <p>Thence, with the survey of Tract 47</p> <p>Beginning at Angle Point No. 1, Tract 47, heretofore described, and is located on the north and south center line of sec. 6.</p> <p>S. 0° 04' W., on line 1 - 2, Tract 47, which is identical with the north and south center line of sec. 6.</p>
15.085	The center 1/4 sec. cor. of sec. 6, heretofore described which is designated to function for Angle Point No. 2, Tract 47
	<hr/> <p>N. 89° 58' E., on line 2 - 3, Tract 47, which is identical with the east and west center line of sec. 6.</p>
19.965	The center-east 1/16 sec. cor. of secs. 6, heretofore described, which is designated to function for Angle Point No. 3, Tract 47.
	<hr/> <p>S. 0° 01.5' W., on line 3 - 4, Tract 47, which is identical with the north and south center line of the southeast quarter of sec. 6.</p>
20.035	The southeast 1/16 sec. cor. of sec. 6, heretofore described.
40.07	The east 1/16 sec. cor. of secs. 6 and 7, heretofore described, which is designated to function for Angle Point No. 4, Tract 47.
	<hr/> <p>S. 89° 57' E., on line 4 - 5, Tract 47, which is identical with the section line between secs. 6 and 7.</p>
6.065	Angle Point No. 5, Tract 47, heretofore described.
	<hr/> <p>N. 0° 03' E., on line 5 - 6, Tract 47.</p>
20.04	Intersect the east and west center line of the southeast quarter of sec. 6, Angle Point No. 6, Tract 47, heretofore described.


The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS		
20.065	<p>N. 2° 44.5' W., on line 6 - 7, Tract 47.</p> <p>Intersect the east and west center line of sec. 6, Angle Point No. 7, Tract 47, heretofore described.</p> <hr/>	
6.905	<p>N. 47° 39' W., on line 7 - 8, Tract 47.</p> <p>Intersect the north and south center line of the north-east quarter of sec. 6, Angle Point No. 8, Tract 47, heretofore described.</p> <hr/>	
3.315	<p>N. 0° 01.5' E., on line 8 - 9, Tract 47, which is identical with the north and south center line of the north-east quarter of sec. 6.</p> <p>Angle Point No. 9, Tract 47, heretofore described.</p> <hr/>	
0.93	<p>N. 89° 56' W., on line 9 - 10, Tract 47.</p> <p>The point for Angle Point No. 10, Tract 47.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p> / S 6</p> <p>AP 10</p> <p>TR 47</p> <p>1980</p> </div> <hr/>	
4.455	<p>N. 49° 11' W., on line 10 - 11, Tract 47.</p> <p>The point for Angle Point No. 11, Tract 47.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <p>T8S R20W</p> <p> S 6</p> <p>AP 11</p> <p>TR 47</p> <p>1980</p> </div> <hr/>	
1.555	<p>N. 1° 04' E., on line 11 - 12, Tract 47.</p> <p>Intersect the arc of a curve, line 9 - 10, Tract 37, heretofore described. The point for Angle Point No. 12, Tract 47.</p>	

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.




1980

Thence, on line 12 - 13, Tract 47, which is identical with a portion of line 10 - 9, Tract 37, along the arc of a curve, curve data:

Chord bears N. 68° 59' W.
Chord length 8.195 chs. distant
Radius 44.01 chs. distant
Length of arc 8.21 chs. distant

At the end of the arc of the curve; the point for Angle Point No. 13, Tract 47.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



1980

S. 87° 43' W., on line 13 - 1, Tract 47.

8.035 Intersect the north and south center line of sec. 6, Angle Point No. 1, Tract 47, and the place of beginning.

Thence, with the survey of Tract 48

Beginning at the corner of secs. 15, 16, 21, and 22, which is designated to function for Angle Point No. 1, Tract 48.




N. 89° 53' W., on line 1 - 2, Tract 48, which is identical with the section line between secs. 16 and 21.

20.00 The east 1/16 sec. cor. of secs. 16 and 21, heretofore described.

35.85 Angle Point No. 2, Tract 48, heretofore described.

S. 4° 38' E., on line 2 - 3, Tract 48.

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
20.10	Intersect the east and west center line of the northeast quarter of sec. 21, heretofore described.
22.92	<p>The point for Angle Point No. 3, Tract 48.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 21 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T8S R20W TR 48 AP 3 S 21 1981</p> </div> <p>S. 41° 37' E., on line 3 - 4, Tract 48.</p>
6.03	<p>The point for Angle Point No. 4, Tract 48 and Angle Point No. 2, Tract 49</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;">  <p>T8S R20W TR 48 AP 4 S 21 AP 2 TR 49 1981</p> </div> <p>S. 89° 06' E., on line 4 - 5, Tract 48, which is identical with line 2 - 1, Tract 49.</p>
9.975	Intersect the north and south center line of the northeast quarter of sec. 21, heretofore described.
29.99	<p>Angle Point No. 5, Tract 48, which is identical with Angle Point No. 1, Tract 49, heretofore described.</p> <div style="text-align: center;">  </div> <p>NORTH, on line 5 - 1, Tract 48, which is identical with the section line between secs. 21 and 22</p>
7.76	The north 1/16 sec. cor. of secs. 21 and 22, heretofore described.
27.76	The corner of secs. 15, 16, 21, and 22, which is designated to function for Angle Point No. 1, Tract 48, and the place of beginning.
<p>Thence, with the survey of Tract 49</p> <p>Beginning at Angle Point No. 1, Tract 49, which is identical with Angle Point No. 5, Tract 48, heretofore described.</p>	

94

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

CHAINS	
	N. 89° 06' W., on line 1 - 2, Tract 49, which is identical with line 5 - 4, Tract 48.
20.015	Intersect the north and south center line of the north-east quarter of sec. 21, heretofore described.
29.99	Angle Point No. 2, Tract 49, which is identical with Angle Point No. 4, Tract 48, heretofore described.
	<hr/>
	S. 41° 37' E., on line 2 - 3, Tract 49.
15.035	Intersect the north and south center line of the north-east quarter of sec. 21, Angle Point No. 3, Tract 49, heretofore described.
	<hr/>
	S. 44° 53' E., on line 3 - 4, Tract 49.
2.06	Intersect the east and west center line of sec. 21, Angle Point No. 4, Tract 49, heretofore described.
	<hr/>
	S. 43° 21.5' E., on line 4 - 5, Tract 49.
12.865	The point for Angle Point No. 5, Tract 49. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.
	<div style="text-align: center;"> <p>T8S R20W TR 49 AP 5 S 21 1981</p> </div> <hr/>
	S. 31° 23.5' E., on line 5 - 6, Tract 49.
12.44	Intersect the east and west center line of the southeast quarter of sec. 21, Angle Point No. 6, Tract 49, heretofore described.
	<hr/>
	EAST, on line 6 - 7, Tract 49, which is identical with the east and west center line of the southeast quarter of sec. 21.
3.22	Angle Point No. 7, Tract 49, heretofore described.
	<hr/>
	NORTH, on line 7 - 1, Tract 49, which is identical with the section line between secs. 21 and 22.

The Metes and Bounds Survey
of Tracts 37 through 49 Inclusive
Township 8 South, Range 20 West
Gila and Salt River Meridian, Arizona

95

CHAINS		
19.96	The 1/4 sec. cor. of secs. 21 and 22, heretofore described.	
32.20	Angle Point No. 1, Tract 49, which is identical with Angle Point No. 5, Tract 48, and the place of beginning.	
<hr/>		
GENERAL DESCRIPTION		
<p>The land area within these surveys is nearly level to rolling. Drainage is to the northwest. The soil consists of sandy loam on the bottom land, sandy and rocky on the rolling land areas. The land area is mostly under cultivation, with the exception of the federally controlled lands, which are undeveloped; with French tamarisk, mesquite, paloverde, and tesota trees; undergrowth, young trees, creosote brush (shrub), cacti, and arrow-weed.</p>		
<p>Improvements located throughout the area, are: The Southern Pacific Railroad; the Wellton-Mohawk Canal, numerous canals and laterals for irrigations and/or drainage purposes; Yuma County and farm roads.</p>		
<hr/>		

CHAINS		
--------	--	--

Form 9600-11
(August 1979)




UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

NAMES	CAPACITY
James P. Scott	Cadastral Surveyor
Marvin T. Koppang	Cadastral Surveyor
Stephen Jaramillo	Surveying Aid
Norman Q. Hull	Surveying Aid
Neil K. Hull	Surveying Aid
Manual V. Almodova	Surveying Aid
Bryant H. Twist	Surveying Aid
Ernest E. Hurtado	Surveying Aid
Dale E. Phillips	Surveying Aid
Fordner Van Fleet, Jr.	Surveying Aid
Victor E. Templeton	Surveying Aid
John D. Robinson	Surveying Aid
Gene J. Davis	Surveying Aid
Eric A. Werner	Surveying Aid
Cruz D. Almanza	Surveying Aid
Jerold L. Peterson	Surveying Aid
Lewis J. Scheeler	Surveying Aid
Thomas E. Casinger	Cadastral Surveyor
Regina R. Lefort	Cadastral Surveyor
Kevin J. Curtis	Surveying Aid

CERTIFICATE OF SURVEY

~~XX~~(We), Ray Harpin, Douglas A. Cody and Paul J. Fisher, HEREBY CERTIFY upon honor that, in pursuance of special instructions bearing date of the 14th day of October, 1969, ~~XXXXXXXXXX~~ Supplemental Special Instructions dated November 20, 1969, Supplemental Special Instructions dated September 5, 1979, and Supplemental Special Instructions dated October 20, 1980, (We) have dependently resurveyed a portion of the north boundary, a portion of the subdivisional lines, and a portion of the subdivision lines within a number of sections; surveyed a portion of the subdivision lines within a number of sections, and surveyed the metes-and-bounds of Tracts 37 through 49 inclusive, Township 8 South, Range 20 West, of the Gila and Salt River Meridian, in the State of Arizona, which are represented in the foregoing field notes as having been executed by ~~XXXX~~ (us) and under ~~XXXX~~ (our) direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions for the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

May 13, 1981	
(Date)	(Cadastral Surveyor)
May 15, 1981	
(Date)	(Cadastral Surveyor)
May 21, 1981	
(Date)	(Cadastral Surveyor)

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Denver, Colorado

The foregoing field notes of the dependent resurvey of a portion of the north boundary, a portion of the subdivisional lines, and a portion of the subdivision lines within a number of sections; the survey of a portion of the subdivision lines within a number of sections, and the metes-and-bounds survey of Tracts 37 through 49 inclusive, Township 8 South, Range 20 West, of the Gila and Salt River Meridian, Arizona

executed by Ray Harpin, Douglas A. Cody and Paul J. Fisher, Cadastral Surveyors having been critically examined and found correct, are hereby approved.

NOV 23 1981

 (Date) 
 ACTING (Chief, Cadastral Survey Examination and Approval Staff)

CERTIFICATE OF TRANSCRIPT

I CERTIFY That the foregoing transcript of the field notes of the above-described surveys in _____, is a true copy of the original field notes.

 (Date) _____
 (Chief, Cadastral Survey Examination and Approval Staff)